



(12) **EUROPEAN PATENT APPLICATION**
published in accordance with Art. 153(4) EPC

(43) Date of publication:
18.04.2018 Bulletin 2018/16

(51) Int Cl.:
H01L 27/32^(2006.01) H01L 51/56^(2006.01)

(21) Application number: **15883642.9**

(86) International application number:
PCT/CN2015/093388

(22) Date of filing: **30.10.2015**

(87) International publication number:
WO 2016/197524 (15.12.2016 Gazette 2016/50)

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR
Designated Extension States:
BA ME
Designated Validation States:
MA

- **DONG, Xue**
Beijing 100176 (CN)
- **WANG, Haisheng**
Beijing 100176 (CN)
- **LIU, Peng**
Beijing 100176 (CN)
- **XUE, Hailin**
Beijing 100176 (CN)
- **ZHAO, Yiming**
Beijing 100176 (CN)
- **XUAN, Minghua**
Beijing 100176 (CN)

(30) Priority: **11.06.2015 CN 201510319389**

(71) Applicants:

- **BOE Technology Group Co., Ltd.**
Beijing 100015 (CN)
- **Beijing BOE Optoelectronics Technology Co., Ltd.**
Beijing 100176 (CN)

(74) Representative: **Brötz, Helmut et al**
Rieder & Partner mbB
Patentanwälte - Rechtsanwalt
Corneliusstrasse 45
42329 Wuppertal (DE)

(72) Inventors:

- **YANG, Shengji**
Beijing 100176 (CN)

(54) **ORGANIC ELECTROLUMINESCENT DISPLAY DEVICE, DISPLAY APPARATUS, AND MANUFACTURING METHOD THEREFOR**

(57) An organic light emitting diode (OLED) display, a display device and a manufacturing method thereof are provided. The OLED display includes a base substrate; and OLED pixel units arranged on the base substrate in a matrix. Each OLED pixel unit includes at least one OLED structure, and the OLED structure includes a cathode layer (001), an anode layer and an organic light emitting layer located therebetween, and the OLED pixel unit further includes a pixel circuit (101, 201, 301) that is connected correspondingly with the OLED structure and configured to drive it to illuminate light. The pixel circuit includes a switching unit and a capacitor (Cst1, Cst2, or Cst3) located above or below the layer in which the switching unit is located. The ratio of the foot area of the storage capacitor to the total foot area of the pixel circuit can be reduced in this OLED display.




FIG. 3

Description

TECHNICAL FIELD

[0001] Embodiments of the present disclosure relate to an organic light-emitting diode (OLED) display, a display device including the OLED display and a manufacturing method thereof.

BACKGROUND

[0002] As one of the hot research fields in the area of panel displays at present, organic light emitting diode (OLED) displays, compared with liquid crystal displays (LCDs), have advantages such as low energy consumption, low production costs, self-illumination, wide viewing angles, high response speeds and the like, so that at present they are taking the place of conventional LCDs in tablet display devices such as mobile phones, PDAs, digital cameras or the like.

[0003] Because the present OLED displays have a large number of thin film transistors in their pixel circuits, how to reduce the ratio of the foot area of the capacitor(s) in a pixel unit to the total foot area of the pixel circuit has drawn a great attention to manufacturers.

SUMMARY

[0004] Embodiments of the present disclosure provide an OLED display, a display device including the OLED display, and a manufacturing method thereof, which can reduce the ratio of the foot area of the capacitor in a pixel unit to the total foot area of the pixel unit.

[0005] An embodiment of the present disclosure provides an OLED display, including: a base substrate, and OLED pixel units arranged on the base substrate in a matrix. Each OLED pixel unit comprises at least one OLED structure and the OLED structure comprising: a cathode layer, an anode layer, and an organic light emitting layer located between the cathode layer and the anode layer, wherein the OLED pixel unit further comprises a pixel circuit that is connected correspondingly with the OLED structure and configured to drive the OLED structure, and the pixel circuit comprises a switching unit and a capacitor, and the capacitor is located above or below the layer in which the switching unit is located.

[0006] Further in some embodiments, the capacitor is located above the layer in which the switching unit is located, the OLED structure is located above the switching unit, and the capacitor is formed by the cathode layer of the OLED structure and a conducting layer located between the cathode layer and the layer in which the switching unit is located.

[0007] Further in some embodiments, the switching unit is a thin film transistor comprising a gate layer, an active layer and a source/drain metal layer above the active layer, and the conducting layer is the source/drain metal layer.

[0008] Further in some embodiments, the OLED pixel unit comprise three OLED structures disposed therein, which are stacked one on top of another and insulated from each other, and emit red, blue and green light respectively.

[0009] Further in some embodiments, the conducting layer has three conducting layer sub-areas corresponding to the three OLED structures and each of the conducting layer sub-areas separately forms a capacitor together with the cathode at the topmost layer of the stack of the three OLED structures.

[0010] Further in some embodiments, the capacitor is located above the layer in which the switching unit is located, and a part of each the pixel circuit that is below the capacitor only comprises two switching units, i.e., a driving thin film transistor (TFT) and a switching TFT.

[0011] Further in some embodiments, the three OLED structures are connected to three pixel circuits respectively or connected to a same and single pixel circuit.

[0012] An embodiment of the present disclosure provides a display device comprising the OLED display of any one embodiment.

[0013] An embodiment of the present disclosure provides a manufacturing method for any of the above OLED displays, comprising: providing a pixel circuit, including a switching unit and a capacitor, in an OLED pixel unit, wherein the pixel circuit is connected correspondingly with an OLED structure and configured to drive the OLED structure, and the capacitor is provided above or below a layer in which the switching unit is located.

[0014] Further in some embodiments, the capacitors is located above the layer in which the switching unit is located, the OLED structure is located above the switching unit, and the capacitor is formed by the cathode layer of the OLED structure and a conducting layer located between the cathode layer and the layer in which the switching unit is located.

[0015] Further in some embodiments, the switching unit is a thin film transistor including a gate layer, an active layer and a source/drain metal layer above the active layer, and the conducting layer is formed synchronously with the source/drain layer.

[0016] In embodiments of the present disclosure, an OLED display includes a base substrate and OLED pixel units arranged on the base substrate in a matrix. Each OLED pixel unit includes at least one OLED structure, each of which includes a cathode layer, an anode layer and an organic light emitting layer located therebetween, and the OLED pixel unit further includes a pixel circuit connected correspondingly with the OLED structure and used to drive the OLED structure to illuminate light. The pixel circuit includes a switching unit and a capacitor, and the capacitor is located above or below the layer in which the switching unit is located. With this configuration, the capacitor Cst in the pixel circuit is shifted upward, so that the ratio of the foot area of the capacitor Cst to the total foot area of the pixel circuit is reduced and accordingly a plurality of pixel circuits can be placed into one pixel.

BRIEF DESCRIPTION OF DRAWINGS

[0017] In order to clearly illustrate the technical solution of the embodiments of the disclosure, the drawings of the embodiments will be briefly described in the following; it is obvious that the described drawings are only related to some embodiments of the disclosure and thus are not limitative of the disclosure.

Fig. 1 is a structure diagram of an OLED pixel unit;
 Fig. 2 is a schematic diagram of the arrangement in a pixel circuit;
 Fig. 3 is a structure diagram of an OLED display provided in an embodiment of the present disclosure; and
 Fig. 4 illustrates an example of the stack configuration of RGB function layers provided in an embodiment of the present disclosure.

DETAILED DESCRIPTION

[0018] In order to make objects, technical details and advantages of the embodiments of the disclosure apparent, the technical solutions of the embodiments will be described in a clearly and fully understandable way in connection with the drawings related to the embodiments of the disclosure. Apparently, the described embodiments are just a part but not all of the embodiments of the disclosure. Based on the described embodiments herein, those skilled in the art can obtain other embodiment(s), without any inventive work, which should be within the scope of the disclosure.

[0019] Hereafter, in association with the accompanying drawings, specific implementations of the OLED displays and the display devices with the OLED displays provided in embodiments of the present disclosure will be described in detail.

[0020] Sizes and shapes of the film layers in the drawings do not reflect the real scale of an OLED display, and only a partial structure of an OLED display is illustrated only for the purpose of illustrating the present disclosure.

[0021] Fig. 1 illustrates a structure of an OLED display, which mainly includes a base substrate and OLED pixel units provided on the base substrate. Each OLED pixel unit includes an OLED structure 1 and a pixel circuit 2 that is connected electrically with the OLED structure 1 to drive it to emit light. Specifically, the OLED structure 1 generally includes an anode 01 and an opposite cathode 02 as well as a light emitting layer 03 disposed between the anode 01 and the cathode 02. The OLED display is enabled to illuminate in such an mechanism: a voltage is applied across the anode and the cathode through the pixel circuit, holes in the anode and electrons in the cathode are driven to recombine in the organic light emitting layer to produce excitons, the excitons are transferred by electric fields to pass energy to luminescent molecules in the light emitting layer and activate electrons in the luminescent molecules to transit from ground

state to excited state, and then photons are produced from the energy of the excited state through radiation transition.

[0022] Unlike LCDs which utilize stable voltages to control their brightness, OLEDs are driven by current and need stable currents to control their light illumination. Because of fabricating process, device aging or other reasons, threshold voltages V_{th} of driving transistors in 2T1C pixel circuits are not uniform and therefore the currents flowing through the OLEDs of respective pixels vary, resulting in uneven display brightness, which affects the display effect of a whole displayed image and in turn leads to uneven brightness in different areas in an OLED display.

[0023] In order to compensate for the non-uniformity of threshold voltages of driving transistors in pixel circuits, the numbers of thin film transistors and capacitors are increased in pixel circuits, so that the drift of the threshold voltages may be offset by means of the cooperation between the thin film transistors and the capacitors. However, downscaling in size of pixels is greatly restricted due to the increase of the numbers of thin film transistors and capacitors in pixel circuits. Fig. 2 illustrates a 6T1C pixel circuit, which includes six thin film transistors T1-T6 and a capacitor Cst, and the capacitor, as can be seen, has the biggest foot area in the pixel and thus affects the display effect the pixel.

[0024] As illustrated in Fig. 2, in the structure of the pixel circuit, it can be seen that the capacitor Cst, apart from the TFTs, occupies the biggest foot area in a pixel. Here, "pixel" in embodiments of the present disclosure corresponds to a "pixel unit" mentioned. That is to say, the term "pixel" has the same meaning as the term "pixel unit." An embodiment of the present disclosure provides an OLED display, which includes a base substrate and OLED pixel units arranged in a matrix on the base substrate. Each OLED pixel unit includes at least one OLED structure, each of which includes a cathode layer, an anode layer and an organic light emitting layer interposed between the anode layer and the cathode layer, and the OLED pixel unit further includes a pixel circuit connected correspondingly with the OLED structure and thus configured to drive the OLED structure to illuminate light. The pixel circuit includes a switching unit and a capacitor, and the capacitor is located above or below the switching unit. This type of OLED display can decrease the ratio of the foot area of the capacitor in the pixel circuit to the total foot area of the pixel circuit.

[0025] In some implementations, the pixel circuit includes a plurality of switching units. In some implementations, the capacitor is provided above or below the layer in which all of the switching units are located, or above the layer in which a certain switching unit is located.

[0026] By arranging the capacitor above or below the layer in which the switching units are located to shift the Cs upward in the pixel circuit, the ratio of the foot area of the capacitor to the total foot area of the pixel circuit is reduced and in turn a plurality of pixel circuits can be

arranged into one pixel.

[0027] In some implementations, the capacitor is provided above the layer in which the switching units are located, the OLED structure is located above the switching units, the capacitor is formed by the cathode layer of the OLED structure and a conducting layer, and the conducting layer is located between the cathode layer and the layer in which the switching units are located. In some implementations, when the capacitor is located below the layer in which the switching units are located, the capacitor may be formed by two separate electrode layers or share electrode layers with other existing structures, as long as the functionality of the existing structures is not affected.

[0028] In some implementations, the switching unit is a thin film transistor, and the thin film transistor includes a gate layer, an active layer, and a source/drain metal layer above the active layer. The source/drain metal layer acts as the conducting layer, i.e., the conducting layer and the source/drain metal layer share one layer.

[0029] In some implementations, the OLED pixel unit includes three OLED structures, which are stacked one on top of another and insulated from each other, and emit red, blue and green light respectively.

[0030] In some implementations, each of the three OLED structures is connected a respective pixel circuits, or they are all connected to a same and single pixel circuit.

[0031] An embodiment will be specifically illuminated hereafter, in which the capacitor is located above the layer in which the switching unit(s) is located, the OLED structure is located above the layer in which the switching unit(s) is located, and the capacitor is formed by the cathode layer of the OLED structure and a conducting layer located between the cathode layer of the OLED structure and the layer in which the switching unit(s) is located.

[0032] At present, a capacitor Cst is mainly formed with a Poly-Si layer and a gate layer, however it is obviously impossible to apply this kind of film layer structure in the OLED pixel unit including a plurality of OLED structures provided in the embodiment of the present disclosure. Therefore, it is proposed in an embodiment of the present disclosure that a conducting layer is added between the source/drain metal layer (SD layer) of the pixel circuit and the grounded electrode, and the conducting layer cooperate together with the cathode at the topmost layer of the layer stack to form a capacitor Cst. In this way, the capacitor Cst in the pixel circuit is shifted upward, so that the ratio of the foot area of the capacitor Cst to the total foot area of the pixel circuit is reduced and so is the foot area of each pixel circuit in a pixel. As a result, a plurality of pixel circuits can be placed into one pixel to control the anodes of each function layer and thus enable colorful display for each pixel.

[0033] Specifically, as illustrated in Fig. 3, in the case that a pixel unit includes three OLED structures that are disposed side by side and insulated from each other, which emit red, blue and green light respectively and are each connected to one individual pixel circuit, in an em-

bodiment of the present disclosure the capacitor in each pixel circuit is formed by the cathode 001 shared by all of the three OLED structures in the OLED pixel unit corresponding to the pixel circuit in connection with a conducting layer disposed between the cathode 001 and the TFTs in the pixel circuit (for example, the conducting layer may be the source/drain metal layer, not illustrated in the Figure). In the case that three OLED structures share the same one cathode, as illustrated in Fig. 3, the conducting layer 011 and the cathode 001 form a capacitor Cst1, the conducting layer 021 and the cathode 001 form a capacitor Cst2, and the conducting layer 031 and the cathode 001 form a capacitor Cst3; the capacitor Cst1 is connected to the pixel circuit 101 that is used to control the red function layer, the capacitor Cst2 is connected to the pixel circuit 201 that is used to control the green function layer, and the capacitor Cst3 is connected to the pixel circuit 301 that is used to control the blue function layer.

[0034] As can be seen in the aforesaid structure that the conducting layer in one pixel is divided into three conducting layer sub-areas, i.e., the conducting layer sub-areas 011, 021 and 031, which together with the cathode thereabove constitute three capacitors Cst, and these three storage capacitors are located above the pixel circuits, so that the pixel circuits below these capacitors only need to each include a driving TFT and a switching TFT, and thus the capacitors Cst are separated in space from the switching transistors for the pixel circuits, reducing the ratio of the foot area of the Cst to the foot area of the whole pixel circuit and rendering colorful display effect possible for the stack structure.

[0035] Fig. 4 illustrates an implementation of the stack configuration of RGB function layers. In this scheme, any RGB gray scale display effect can be achieved by a single RGB pixel and colorful display can be achieved through cathode sharing.

[0036] Additionally, in consideration of the particularity of the structure provided in the embodiment of the present disclosure, the cathode can be grounded all through the operating process of the whole pixel circuit as a grounded electrode.

[0037] In an embodiment of the present disclosure, the conducting layer may be composed of any conducting material, including various metal materials, such as copper, aluminum or the like. In embodiments of the present disclosure, the conducting layer is not limited in material and shape.

[0038] In some examples, in the above-mentioned OLED display provided in an embodiment of the present disclosure, there may be or may not be the same number of OLED structures in respective OLED pixel units, and there is no limitation in this respect herein.

[0039] In some examples, in the above-mentioned OLED display provided in an embodiment of the present disclosure, the OLED structures for light emission of different colors in individual OLED pixel units may be or may not be stacked in the same sequence and there is no limitation in this respect herein.

[0040] In some examples, in order to simplify the manufacturing process, in the above-mentioned OLED display provided in an embodiment of the present disclosure, the OLED structures for light emission of different colors in respective pixel units are stacked in the same sequence.

[0041] In some examples, in the above-mentioned OLED display provided in an embodiment of the present disclosure, the OLED structure includes an anode, a light emitting layer and a cathode stacked in this sequence. The material of the anode may be indium tin oxide (ITO), and the material of the cathode may be a transparent metal material

[0042] It is to be noted that although the above embodiments of the present disclosure take the OLED pixel unit including three pixel circuits for its OLED structures as an example, the structure design for capacitors in the present disclosure may also be applied in the case that only one pixel circuit for the OLED structures is included, i.e., the three OLED structures may be connected with a same and single pixel circuit, however there is no limitation about this herein.

[0043] An embodiment of the present disclosure provides a display device including the OLED display provided in any of the embodiments of the present disclosure. The display devices may be any products or components with display functions, such as mobile telephones, flat computers, TVs, displays, notebook computers, digital picture frames, navigators and the like. Other necessary components of the display device can be understood by those skilled in the art and will not be described any more here, nor will limit the scope of the present disclosure. Embodiments of the above mentioned OLED display may be referred to for implementations of the display device and redundant description will not be described any more here.

[0044] An embodiment of the present disclosure provides a manufacturing method for the above-mentioned OLED display, including: providing a pixel circuit in an OLED pixel unit. The pixel circuit is connected correspondingly with an OLED structure and configured to drive the OLED structure. The pixel circuit includes a switching unit and a capacitor, and the capacitor is located above or below the layer in which the switching unit is located.

[0045] In some implementations, the capacitor is located above the layer in which the switching unit is located, the OLED structure is located above the switching unit and the capacitor is formed by the cathode layer of the OLED structure along with a conducting layer located between the cathode layer and the layer in which the switching unit is located.

[0046] In some implementations, the switching unit is a thin film transistor, and the thin film transistor includes a gate layer, an active layer, and a source/drain metal layer above the active layer. The conducting layer is formed synchronously with the source/drain metal layer.

[0047] What has been described above is related to

the illustrative implementations of the present disclosure only and not limitative to the scope of the present disclosure; the scope of the present disclosure is defined by the accompanying claims.

[0048] The present application claims priority of Chinese patent application No. 201510319389.0 filed on June 11, 2015, the disclosure of which is incorporated herein in its entirety by reference as a part of the present application.

Claims

1. An organic light-emitting diode (OLED) display, including:

a base substrate, and
OLED pixel units arranged on the base substrate in a matrix, each OLED pixel unit comprising at least one OLED structure and the OLED structure comprising:

a cathode layer,
an anode layer, and
an organic light emitting layer located between the cathode layer and the anode layer, wherein

the OLED pixel unit further comprises a pixel circuit that is connected correspondingly with the OLED structure and configured to drive the OLED structure, and the pixel circuit comprises a switching unit and a capacitor, and the capacitor is located above or below the layer in which the switching unit is located.

2. The OLED display of claim 1, wherein the capacitor is located above the layer in which the switching unit is located, the OLED structure is located above the switching unit, the capacitor is formed by the cathode layer of the OLED structure and a conducting layer, and the conducting layer is located between the cathode layer and the layer in which the switching unit is located.

3. The OLED display of claim 2, wherein the switching unit is a thin film transistor comprising a gate layer, an active layer, and a source/drain metal layer above the active layer, and the conducting layer is the source/drain metal layer.

4. The OLED display of any one of claims 1 to 3, wherein the OLED pixel unit comprises three OLED structures disposed therein, which are stacked one on top of another and insulated from each other and emit red, blue and green light respectively.

5. The OLED display of claim 4, wherein the conducting

layer has three conducting layer sub-areas corresponding to the three OLED structures, and each of the conducting layer sub-areas separately forms a capacitor together with the cathode at the topmost layer of the stack of the three OLED structures.

5

6. The OLED display of any of claims 1-5, wherein the capacitor is located above the layer in which the switching unit is located, and a part of each the pixel circuit that is below the capacitor only comprises two switching units, i.e., a driving thin film transistor (TFT) and a switching TFT. 10
7. The OLED display of claim 4 or 5, wherein the three OLED structures are connected to three pixel circuits respectively or connected to a same and single pixel circuit. 15
8. A display device comprising the OLED display of any one of claims 1-7. 20
9. A manufacturing method for the OLED display of any of claims 1-7, comprising:

providing a pixel circuit, including a switching unit and a capacitor, in an OLED pixel unit, wherein the pixel circuit is connected correspondingly with an OLED structure and configured to drive the OLED structure, and the capacitor is provided above or below a layer in which the switching unit is located. 25 30
10. The method of claim 9, wherein the capacitors is located above the layer in which the switching unit is located, the OLED structure is located above the switching unit, the capacitor is formed by the cathode layer of the OLED structure and a conducting layer, and the conducting layer is located between the cathode layer and the layer in which the switching unit is located. 35 40
11. The method of claim 10, wherein the switching unit is a thin film transistor including a gate layer, an active layer, and a source/drain metal layer above the active layer, and the conducting layer is formed synchronously with the source/drain layer. 45

50

55




FIG. 1




FIG. 2




FIG. 3




FIG. 4

INTERNATIONAL SEARCH REPORT

International application No.

PCT/CN2015/093388

A. CLASSIFICATION OF SUBJECT MATTER

H01L 27/32 (2006.01) i; H01L 51/56 (2006.01) i

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

H01L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

DWPI, CNKI, CPRS, CNTXT: luminescent, top gate, bottom gate, amoled, organic, display, pixel, substrate, plate, board, anode, cathode, source, active, drive, switch, gate, drain, metal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	CN 103985736 A (BOE TECHNOLOGY GROUP CO., LTD.), 13 August 2014 (13.08.2014), description, paragraphs [0039]-[0060], and figures 3-5	1-11
X	CN 203850301 U (BOE TECHNOLOGY GROUP CO., LTD.), 24 September 2014 (24.09.2014), description, paragraphs [0029]-[0050], and figures 3-5	1-11
A	WO 2015007053 A1 (BOE TECHNOLOGY GROUP CO., LTD.), 22 January 2015 (22.01.2015), the whole document	1-11
A	CN 104393026 A (BOE TECHNOLOGY GROUP CO., LTD. et al.), 04 March 2015 (04.03.2015), the whole document	1-11

☐ Further documents are listed in the continuation of Box C.
 ☒ See patent family annex.

* Special categories of cited documents:	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"A" document defining the general state of the art which is not considered to be of particular relevance	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"E" earlier application or patent but published on or after the international filing date	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"&" document member of the same patent family
"O" document referring to an oral disclosure, use, exhibition or other means	
"P" document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search 06 March 2016 (06.03.2016)	Date of mailing of the international search report 18 March 2016 (18.03.2016)
Name and mailing address of the ISA/CN: State Intellectual Property Office of the P. R. China No. 6, Xitucheng Road, Jimenqiao Haidian District, Beijing 100088, China Facsimile No.: (86-10) 62019451	Authorized officer PENG, Lijuan Telephone No.: (86-10) 62411580

Form PCT/ISA/210 (second sheet) (July 2009)

INTERNATIONAL SEARCH REPORT
Information on patent family members

International application No.

PCT/CN2015/093388

Patent Documents referred in the Report	Publication Date	Patent Family	Publication Date
CN 103985736 A	13 August 2014	WO 2015165184 A1	05 November 2015
CN 203850301 U	24 September 2014	None	
WO 2015007053 A1	22 January 2015	US 2015340389 A1	26 November 2015
		CN 103390592 A	13 November 2013
CN 104393026 A	04 March 2015	None	

Form PCT/ISA/210 (patent family annex) (July 2009)

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- CN 201510319389 [0048]

专利名称(译)	有机电致发光显示装置，显示装置及其制造方法		
公开(公告)号	EP3309840A4	公开(公告)日	2018-12-19
申请号	EP2015883642	申请日	2015-10-30
[标]申请(专利权)人(译)	京东方科技集团股份有限公司 北京京东方光电科技有限公司		
申请(专利权)人(译)	京东方科技集团股份有限公司. 北京京东方光电科技有限公司.		
当前申请(专利权)人(译)	京东方科技集团有限公司 北京京东方光电科技有限公司		
[标]发明人	YANG SHENGJI DONG XUE WANG HAISHENG LIU PENG XUE HAILIN ZHAO YIMING XUAN MINGHUA		
发明人	YANG, SHENGJI DONG, XUE WANG, HAISHENG LIU, PENG XUE, HAILIN ZHAO, YIMING XUAN, MINGHUA		
IPC分类号	H01L27/32 H01L51/56		
CPC分类号	H01L27/3265 H01L27/3209 H01L27/3211 H01L2227/323		
优先权	201510319389.0 2015-06-11 CN		
其他公开文献	EP3309840A1		
外部链接	Espacenet		

摘要(译)

提供一种有机发光二极管 (OLED) 显示器，显示装置及其制造方法。OLED显示器包括基础基板;以及矩阵排列在基础基板上的OLED像素单元。每个OLED像素单元包括至少一个OLED结构，OLED结构包括阴极层 (001)，阳极层和位于其间的有机发光层，OLED像素单元还包括像素电路 (101,201， 301) 相应地与OLED结构连接并配置成驱动它照亮。像素电路包括开关单元和位于开关单元所在的层的上方或下方的电容器 (Cst1，Cst2或Cst3)。在该OLED显示器中，可以减小存储电容器的足部面积与像素电路的总足部面积的比率。