



(11)

**EP 3 125 294 B1**

(12)

**EUROPEAN PATENT SPECIFICATION**

(45) Date of publication and mention  
of the grant of the patent:  
**22.04.2020 Bulletin 2020/17**

(51) Int Cl.:  
**H01L 27/32** <sup>(2006.01)</sup> **H01L 51/52** <sup>(2006.01)</sup>

(21) Application number: **16181858.8**

(22) Date of filing: **29.07.2016**

**(54) ORGANIC LIGHT EMITTING DISPLAY DEVICE**

ORGANISCHE LICHEMITTIERENDE ANZEIGEVORRICHTUNG

DISPOSITIF ÉLECTROLUMINESCENT ORGANIQUE

(84) Designated Contracting States:  
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB  
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO  
PL PT RO RS SE SI SK SM TR**

(30) Priority: **29.07.2015 KR 20150107497**

(43) Date of publication of application:  
**01.02.2017 Bulletin 2017/05**

(73) Proprietor: **LG Display Co., Ltd.  
Yeongdeungpo-gu  
Seoul, 07336 (KR)**

(72) Inventors:  
• **SHIM, Sungbin  
626-840 Gyeongsangnam-do (KR)**

• **DO, Eui-Doo  
10895 Gyeonggi-do (KR)**  
• **KIM, Suhyeon  
10845 Gyeonggi-do (KR)**

(74) Representative: **Ter Meer Steinmeister & Partner  
Patentanwälte mbB  
Nymphenburger Straße 4  
80335 München (DE)**

(56) References cited:  
**EP-A1- 2 503 851 EP-A1- 2 827 371  
CN-A- 103 137 891 KR-A- 20160 079 523  
US-A1- 2015 097 171**

**EP 3 125 294 B1**

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

## Description

### CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application claims priority from Korean Patent Application No. 10-2015-0107497 filed on July 29, 2015.

### BACKGROUND OF THE INVENTION

#### Field of the Invention

[0002] The present embodiments relate to an organic light emitting display device, and more particularly, to an organic light emitting display device which can be manufactured to a large size using a bank pattern and a barrier rib disposed on an auxiliary electrode.

#### Description of the Related Art

[0003] With progress of the information-oriented society, various types of demands for display devices for displaying an image are increasing. Recently, various types of display devices such as a liquid crystal display (LCD) device, a plasma display panel (PDP) device, or an organic light emitting display (OLED) device have been used. Such display devices respectively include display panels suitable therefor.

[0004] In the display panel, thin film transistors are formed in each pixel area and a specific pixel area in the display panel is controlled by a current flow in the thin film transistors. The thin film transistor includes a gate and source/drain electrodes.

[0005] In the OLED device, an emission layer is formed between two different electrodes, and when electrons generated from one of the electrodes and holes generated from the other one electrode are injected into the emission layer, the injected electrons and holes are combined into excitons. When the generated excitons transfer from an excited state to a ground state, lights are emitted to display an image.

[0006] Such an OLED device does not have a problem when manufactured to a small size. However, when manufactured to a large size, the OLED device has the problem of non-uniformity in brightness and has a brightness difference between a peripheral area and a central area. More specifically, if a current flows from a cathode electrode of an organic light emitting element to a space between the peripheral area and the central area, the current can reach far from a current injection point. In this case, a voltage drop occurs due to a resistance of the cathode electrode of the organic light emitting element, which causes a brightness difference between the peripheral area and the central area.

[0007] That is, in a conventional OLED device having a large size, the uniformity in brightness is sharply decreased due to a brightness difference between a peripheral portion and a central portion caused by a resist-

ance of an upper electrode of an organic light emitting element. Thus, the conventional OLED device needs a means to compensate the brightness difference.

[0008] Therefore, an auxiliary electrode (or an auxiliary line) which can be in contact with a cathode electrode has been introduced in order to solve the problem of voltage drop. However, it is difficult for the cathode electrode and the auxiliary electrode to be in contact with each other since an organic material is formed on the auxiliary electrode. Further, the organic material is formed to a large thickness in part, and, thus, a leakage current may be generated.

[0009] Also, recently, there has been an attempt to solve this problem by providing a barrier rib on the auxiliary electrode. However, a process for forming the barrier rib is additionally needed. Therefore, there has been a demand for a method for suppressing a leakage current and bringing a cathode electrode into contact with an auxiliary electrode without an additional process.

[0010] EP 2 827 371 A1 discloses an organic light emitting display apparatus including a plurality of pixel areas, each pixel area comprising an emission area and a non-emission area; a first electrode formed in the emission area; a bus electrode formed in the non-emission area; an adherent pattern formed on a portion of the bus electrode; a separation pattern formed on at least a portion of the adherent pattern, the separation pattern having an inverted tapered shape; an organic layer formed on the first electrode, and the separation pattern, the organic layer comprising an emission layer, and a second electrode formed on the organic layer and on a portion of the bus electrode exposed by the separation pattern, and the second electrode electrically contacting the bus electrode.

[0011] CN 103 137 891 A discloses organic light-emitting diodes (LEDs) and an organic LED displayer composed of the same. Each organic LED comprises a substrate which comprises a pixel electrode area and an auxiliary electrode area, and an insulating layer formed between the pixel electrode area and the auxiliary electrode area, wherein the pixel electrode area comprises a first electrode formed on the substrate, an organic layer formed on the first electrode and a second electrode formed on the organic layer, and the auxiliary electrode layer comprises an auxiliary electrode formed on the substrate and a shielding structure formed on the auxiliary electrode or on the insulating layer. The shielding structure partially shields the auxiliary electrode, and the second electrode is in electric connection with the auxiliary electrode.

[0012] EP 2 503 851 A1 discloses an organic EL display formed by bonding an organic EL element substrate including a substrate, reflective electrode, organic EL layer, separation wall, barrier layer, transparent electrode, and color conversion layer; and a sealing substrate together, wherein the reflective electrode includes a plurality of partial electrodes; the organic EL layer is formed on the reflective electrode and includes a plurality of parts

separated by the separation wall; the transparent electrode is formed on the organic EL layer; the barrier layer covers the separation wall and the transparent electrode, and has a recessed part in a location corresponding to the reflective electrode; and the color conversion layer is formed in the recessed part.

**[0013]** US 2015/097171 A1 discloses an organic light-emitting display device including a substrate, a thin-film transistor formed on the substrate, a planarization layer formed on the thin-film transistor, an organic light-emitting element formed on the planarization layer, the emitting element including an organic light-emitting layer and a cathode, and a lower auxiliary wiring between the organic light-emitting element and the planarization layer, the wiring electrically connected with the cathode.

**[0014]** KR 2016 0079523 A discloses an organic light-emitting display device comprising a substrate which has a first sub pixel region and a second sub pixel region, which each include a thin film transistor, an anode, an organic emission layer, and a cathode; a first auxiliary electrode which is disposed on the substrate between the first sub pixel region and the second sub pixel region; a flattening layer which is disposed on the first auxiliary electrode and includes a contact hole through which a portion of the first auxiliary electrode is exposed; a second auxiliary electrode which is disposed on the flattening layer between the first sub pixel region and the second sub pixel region, and is electrically connected to the first auxiliary electrode through the contact hole; and a partition wall which is disposed on the second auxiliary electrode between the first sub pixel region and the second sub pixel region, and is inserted into the contact hole.

## SUMMARY OF THE INVENTION

**[0015]** An aspect of the present exemplary embodiments provides an organic light emitting display device which can suppress a voltage drop caused by a resistance of a cathode when manufactured to a large size, and can also suppress generation of a leakage current and simplify a process.

**[0016]** This object is solved by the subject-matter of the independent claims. Further advantageous embodiments and refinements are described in the respective dependent claims.

**[0017]** According to an aspect of the present disclosure, there is provided an organic light emitting display device as defined in claim 1 including a substrate, a first electrode and an auxiliary electrode disposed on the substrate; a bank pattern disposed on the first electrode and a part of an upper surface of the auxiliary electrode and divided into a first area and a second area disposed under the first area, a barrier rib disposed on a part of the upper surface of the auxiliary electrode and divided into a third area having a reverse-tapered shape and a fourth area disposed under the third area and having a tapered shape, an organic emission layer disposed on the substrate and a second electrode disposed on the organic

emission layer. The bank pattern is disposed on a part of an upper surface of the first electrode. Preferably, the bank pattern may be disposed between the first electrode and the auxiliary electrode and overlapping with an end of the first electrode and an end of the auxiliary electrode. Similarly, the barrier rib may be disposed on a central area of the auxiliary electrode. The organic emission layer may be disposed on the first electrode, the bank and the barrier rib. The organic emission layer may be disposed using a linear deposition process without step coverage property. The second electrode may be disposed using a non-linear deposition process with good step coverage property. The first electrode and the auxiliary electrode may be disposed on a same layer spaced apart from each other. That is, the first electrode and the auxiliary electrode may be electrically insulated from each other.

**[0018]** Preferably, a maximum width of the third area of the barrier rib may be greater than the maximum width of the fourth area of the barrier rib. The maximum width refers to an upper surface of the third area and the fourth area, respectively. Further, the first area of the bank pattern has a reverse-tapered shape. The second area of the bank pattern has a tapered shape. A height of the first area of the bank pattern is smaller than a height of the third area of the barrier rib. A height of the second area of the bank pattern is the same as a height of the fourth area of the barrier rib. The maximum width of the first area of the bank pattern may be smaller than the maximum width of the second area. The maximum width of the first area of the bank pattern is greater than the maximum width of the second area.

**[0019]** Furthermore, the organic emission layer may include one or more non-disposition areas. Herein, a first non-disposition area of the organic emission layer may correspond to partial areas of both lateral surfaces of the bank pattern. A second non-disposition area of the organic emission layer may correspond to both lateral surfaces of the third area of the barrier rib. A third non-disposition area of the organic emission layer may correspond to both lateral surfaces of the fourth area of the barrier rib and a part of the auxiliary electrode, e.g. a part of the upper surface of the auxiliary electrode which is exposed by the organic emission layer. The second electrode may be disposed to be in contact with the bank pattern in the first non-disposition area of the organic emission layer. The second electrode may be disposed to be in contact with an upper surface of the auxiliary electrode exposed by the bank pattern and barrier rib. The second electrode may be gradually decreased in thickness as approaching the fourth area of the barrier rib. The organic light emitting display device may further comprise an auxiliary line disposed under the auxiliary electrode. The substrate may include a plurality of sub-pixel areas, and the single auxiliary electrode may be disposed corresponding to each of the sub-pixel areas. The substrate may include pixel areas each including three to four sub-pixels, and the single auxiliary electrode

may be disposed corresponding to each of the pixel areas. The auxiliary electrode may be disposed corresponding to two or more pixel areas. The auxiliary electrode may be disposed in a mesh form on the substrate.

[0020] According to another aspect, a manufacturing method for an organic light emitting display device is provided as defined in claim 11, comprising the steps of: forming a first electrode of an organic light emitting element and an auxiliary electrode on a substrate; forming a first photoresist on the substrate; forming the first photoresist on an area overlapped with the end of the first electrode and end of the auxiliary electrode and a partial area of an upper surface of the auxiliary electrode into a reverse-tapered shape by irradiating a light through a mask on the first photoresist; forming an upper area of the first photoresist into a reverse-tapered shape and a lower area into a tapered shape by performing a heat treatment to the first photoresist formed into the reverse-tapered shape; removing the first photoresist formed in a region other than the first photoresist formed on any area overlapped with the end of the first electrode and end of the auxiliary electrode and the partial area of the upper surface of the auxiliary electrode; and forming an organic emission layer and a second electrode on the substrate. The organic emission layer may be disposed using a linear deposition process without step coverage property. The second electrode may be disposed using a non-linear deposition process with good step coverage property.

[0021] The removing of the first photoresist formed on any area except the area overlapped with the end of the first electrode and end of the auxiliary electrode and the partial area of the upper surface of the auxiliary electrode may include forming a second photoresist on the substrate; disposing a mask including a semi-transmissive portion facing the area overlapped with the end of the first electrode and end of the auxiliary electrode, a transmissive portion facing the partial area of the upper surface of the auxiliary electrode, and a shielding portion facing the area except the area overlapped with the end of the first electrode and end of the auxiliary electrode and the partial area of the upper surface of the auxiliary electrode; etching a part of the second photoresist corresponding to the area overlapped with the end of the first electrode and end of the auxiliary electrode and second photoresist corresponding to the area except the area overlapped with the end of the first electrode and end of the auxiliary electrode and the partial area of the upper surface of the auxiliary electrode, using the mask; and removing the first photoresist formed on the area except the area overlapped with the end of the first electrode and end of the auxiliary electrode and the partial area of the upper surface of the auxiliary electrode, using the remaining second photoresist as a mask. The manufacturing method may further comprise: after the removing of the first photoresist formed on any area except the area overlapped with the end of the first electrode and end of the auxiliary electrode and the partial area of the

upper surface of the auxiliary electrode, ashing the second photoresist formed on the area overlapped with the end of the first electrode and end of the auxiliary electrode and a part of the second photoresist formed on the partial area of the upper surface of the auxiliary electrode; and etching a part of the first photoresist formed on the area overlapped with the end of the first electrode and end of the auxiliary electrode, using the second photoresist formed on the partial area of the upper surface of the auxiliary electrode as a mask. The first photoresist may be a thermosetting photoresist.

[0022] According to the present exemplary embodiments, in the organic light emitting display device having a large size, the cathode electrode and the auxiliary electrode can be easily brought into contact with each other. Thus, a voltage drop caused by a resistance of the cathode electrode can be suppressed.

[0023] Further, according to the present exemplary embodiments, in the organic light emitting display device, the organic emission layer may include a first non-disposition area on a part of the lateral surfaces of the first area of the bank pattern. Thus, a leakage current caused by a change in thickness of the organic emission layer can be suppressed, and a process of forming the barrier rib can be simplified.

## BRIEF DESCRIPTION OF THE DRAWINGS

[0024] The above and other aspects, features and other advantages of the present disclosure will be more clearly understood from the following detailed description taken in conjunction with the accompanying drawings, in which:

FIG. 1 is a view simply illustrating an organic light emitting display device according to an exemplary embodiment;

FIG. 2 is a view simply illustrating an organic light emitting display device according to another exemplary embodiment;

FIG. 3 is a plane view of an organic light emitting display device according to an exemplary embodiment of the present disclosure;

FIG. 4 is a cross-sectional view taken along a line A-A' of an organic light emitting display device according to an exemplary embodiment of the present disclosure;

FIG. 5 is a view illustrating a bank pattern and a barrier rib of an organic light emitting display device according to an exemplary embodiment of the present disclosure;

FIG. 6A through FIG. 6C are views illustrating a manufacturing method for a bank pattern and a barrier rib of the present disclosure;

FIG. 7 is a view illustrating a bank pattern and a barrier rib of an organic light emitting display device according to another exemplary embodiment of the present disclosure;

FIG. 8 is a cross-sectional view of an organic light emitting display device according to yet another exemplary embodiment of the present disclosure; FIG. 9 is a plane view illustrating a disposition relationship between a sub-pixel and an auxiliary electrode according to an exemplary embodiment; FIG. 10 is a plane view illustrating a disposition relationship between a sub-pixel and an auxiliary electrode according to another exemplary embodiment; and FIG. 11 is a plane view illustrating a disposition relationship between a sub-pixel and an auxiliary electrode according to yet another exemplary embodiment.

## DETAILED DESCRIPTION OF THE EMBODIMENT

[0025] Hereinafter, exemplary embodiments of the present disclosure will be described in detail with reference to the accompanying drawings. The exemplary embodiments introduced hereinafter are provided as examples in order to convey their technical idea to a person having ordinary skill in the art. Therefore, the present disclosure is not limited to the following exemplary embodiments and can be embodied in a different shape. Also, the size and thickness of the device might be expressed to be exaggerated for the sake of convenience in the drawings. Like reference numerals generally denote like elements throughout the present specification.

[0026] Advantages and features of the present disclosure, and methods for accomplishing the same will be more clearly understood from exemplary embodiments described below with reference to the accompanying drawings. However, the present disclosure is not limited to the following exemplary embodiments but may be implemented in various different forms. The exemplary embodiments are provided only to complete disclosure of the present disclosure and to fully provide a person having ordinary skill in the art to which the present disclosure pertains with the category of the invention, and the present disclosure will be defined by the appended claims. Like reference numerals generally denote like elements throughout the present specification. In the drawings, the sizes and relative sizes of layers and regions may be exaggerated for clarity.

[0027] When an element or layer is referred to as being "on" another element or layer, it may be directly on the other element or layer, or intervening elements or layers may be present. Meanwhile, when an element is referred to as being "directly on" another element, any intervening elements may not be present.

[0028] The spatially-relative terms such as "below", "beneath", "lower", "above", and "upper" may be used herein for ease of description to describe the relationship of one element or components with another element(s) or component(s) as illustrated in the drawings. It will be understood that the spatially relative terms are intended to encompass different orientations of the element in use

or operation, in addition to the orientation depicted in the drawings. For example, if the element in the drawings is turned over, elements described as "below" or "beneath" other elements would then be oriented "above" the other elements. Thus, the exemplary term "below" can encompass both an orientation of above and below.

[0029] The terms used herein are provided only for illustration of the exemplary embodiments but not intended to limit the present disclosure. As used herein, the singular terms include the plural reference unless the context clearly indicates otherwise. The terms "comprises" and/or "comprising" specify the presence of stated components, steps, operations, and/or elements, but do not preclude the presence or addition of one or more other components, steps, operations, and/or elements.

[0030] FIG. 1 is a view simply illustrating an organic light emitting display device according to an exemplary embodiment. Referring to FIG. 1, an organic light emitting display device 10 according to an exemplary embodiment includes a substrate 100, a gate driver GD, a plurality of gate lines GL, a data driver DD, a plurality of data lines DL, an auxiliary electrode 130, and a plurality of sub-pixels SP.

[0031] The substrate 100 may be an insulation substrate formed of plastic, glass, ceramic, and the like. If the substrate 100 is formed of plastic, the substrate 100 may be flexible. However, a material of the substrate 100 is not limited thereto. The substrate 100 may be formed of metal.

[0032] Further, the gate driver GD sequentially supplies a scan signal to the plurality of gate lines GL. For example, the gate driver GD is a control circuit and supplies a scan signal to the plurality of gate lines GL in response to a control signal supplied from a timing controller (not illustrated). Then, the sub-pixels SP are selected according to the scan signal and sequentially supplied with a data signal.

[0033] The plurality of gate lines GL is disposed on the substrate 100 and extended in a first direction. The gate lines GL include a plurality of scan lines SL1 to SLn. The plurality of scan lines SL1 to SLn is connected to the gate driver GD and supplied with a scan signal from the gate driver GD.

[0034] Furthermore, the data driver DD supplies a data signal to data lines DL1 to DLm selected from the data lines DL in response to a control signal supplied from the outside, such as the timing controller (not illustrated). The data signal supplied to the data lines DL1 to DLm is supplied to the sub-pixel SP selected according to a scan signal whenever the scan signal is supplied to the scan lines SL1 to SLn. Thus, the sub-pixel SP is charged with a voltage corresponding to the data signal and emits a light at a brightness corresponding thereto.

[0035] Herein, the data lines DL are disposed in a second direction so as to intersect with the gate lines GL. Further, the data lines DL include a plurality of data lines DL1 to DLm and include a driving power supply line VD-DL. Further, the plurality of data lines DL1 to DLm is con-

nected to the data driver DD and supplied with a data signal from the data driver DD. Furthermore, the driving power supply line VDDL is connected to an external first power supply VDD and supplied with driving power from the first power supply VDD.

**[0036]** Meanwhile, organic light emitting display devices are classified into top-emission, bottom-emission, and dual-emission organic light emitting display devices. Herein, in any type of an organic light emitting display device, a voltage drop of a cathode electrode may occur while the cathode electrode is formed on the entire surface of a display panel having a large size. Thus, in order to solve this problem, an auxiliary electrode or an auxiliary line may be formed in a non-emission area. In the following, a top-emission display device will be described in the following exemplary embodiments. However, exemplary embodiments of the present disclosure are not limited to the top-emission display device, and can be applied to any display device capable of suppressing a voltage drop of a cathode electrode.

**[0037]** The auxiliary electrode 130 may be disposed on the substrate 100 so as to be in parallel with the plurality of data lines DL1 to DLm. That is, the auxiliary electrode 130 may be disposed in the second direction. Herein, although not illustrated in the drawing, more auxiliary lines in parallel with the data lines DL1 to DLm may be further disposed.

**[0038]** The auxiliary electrode 130 is not limited thereto, and may be disposed on the substrate 100 so as to be in parallel with the plurality of scan lines SL1 to SLn. That is, the auxiliary electrode 130 may be disposed in the first direction. Due to the auxiliary electrode 130, the organic light emitting display device 10 can suppress a voltage drop in response to a resistance of a cathode electrode (not illustrated) of an organic light emitting element (not illustrated) and a resultant brightness difference between a peripheral portion and a central portion.

**[0039]** Hereinafter, an organic light emitting display device according to another exemplary embodiment will be described with reference to FIG. 2. FIG. 2 is a view simply illustrating an organic light emitting display device according to another exemplary embodiment. The organic light emitting display device according to another exemplary embodiment of the present disclosure may include the same components as those of the above-described exemplary embodiment. The redundant description thereof may be omitted. Further, the same components will be assigned the same reference numerals.

**[0040]** Referring to FIG. 2, an organic light emitting display device 20 includes the plurality of scan lines SL1 to SLn disposed on the substrate 100 in the first direction and the data lines DL1 to DLm disposed in the second direction so as to intersect with the scan lines SL1 to SLn. Further, the organic light emitting display device 20 includes a plurality of auxiliary electrodes 230 disposed on the substrate.

**[0041]** Specifically, the organic light emitting display device 20 includes a plurality of first auxiliary electrodes

231 disposed in parallel with the plurality of scan lines SL1 to SLn and a plurality of second auxiliary electrodes 232 disposed in parallel with the plurality of data lines DL1 to DLm. That is, the auxiliary electrodes 230 may be disposed in a mesh form on the substrate 100. As such, the auxiliary electrodes 230 may be disposed in various forms. Further, although not illustrated in the drawing, auxiliary lines in parallel with the data lines DL1 to DLm may be further disposed. Due to the auxiliary electrodes 230, the organic light emitting display device 20 can suppress a voltage drop in response to a resistance of a cathode electrode (not illustrated) of an organic light emitting element (not illustrated) and a resultant brightness difference between a peripheral portion and a central portion.

**[0042]** Hereinafter, an organic light emitting display device including an auxiliary electrode and an auxiliary line will be described in detail with reference to FIG. 3 through FIG. 7.

**[0043]** FIG. 3 is a plane view of an organic light emitting display device according to an exemplary embodiment of the present disclosure. FIG. 4 is a cross-sectional view taken along a line A-A' of an organic light emitting display device according to an exemplary embodiment of the present disclosure. FIG. 5 is a view illustrating a bank pattern and a barrier rib of an organic light emitting display device according to an exemplary embodiment of the present disclosure. FIG. 6A through FIG. 6C are views illustrating a manufacturing method for a bank pattern and a barrier rib of the present disclosure. FIG. 7 is a view illustrating a bank pattern and a barrier rib of an organic light emitting display device according to another exemplary embodiment of the present disclosure.

**[0044]** Referring to FIG. 3, the organic light emitting display device according to an exemplary embodiment of the present disclosure includes an active layer 102 disposed on the substrate 100, a gate electrode 103, a data line DLm-1, DLm, a source electrode 106a branched from the data line DLm-1, DLm, a drain electrode 106b disposed to be separated from the source electrode 106a, and an auxiliary line 110 disposed on the same layer of connection electrode 109 which connects the source and drain electrodes 106a and 106b and formed of the same material as the source and drain electrodes 106a and 106b.

**[0045]** Further, a first electrode 120 of an organic light emitting element is in contact with the drain electrode 106b through a first contact hole 170 that exposes the drain electrode 106b. Herein, the first electrode 120 may be an anode electrode of the organic light emitting element.

**[0046]** Further, the auxiliary electrodes 130 are formed on the same layer and formed of the same material as the first electrode 120. The auxiliary electrodes 130 may be disposed in a horizontal direction and a vertical direction and thus disposed in a mesh form. However, a disposition form of the auxiliary electrodes 130 is not limited thereto, and the auxiliary electrodes 130 may be dis-

posed in any one direction of the horizontal and vertical directions.

**[0047]** Further, the auxiliary line is in contact with the auxiliary electrode 130 through a second contact hole 180. Also, a bank pattern 150 is disposed so as to expose a part of the auxiliary electrodes 130. An area of the auxiliary electrode 130 which is exposed by the bank pattern 150 is in contact with a second electrode (122 in Fig. 4) of the organic light emitting element and thus suppresses a voltage drop of the second electrode. Although not illustrated in the Fig. 3, a barrier rib (160 in Fig. 4) formed of the same material as the bank pattern 150 may be disposed on the part of the auxiliary electrode 130 which is exposed by the bank pattern 150, in order to bring the auxiliary electrode 130 into contact with the second electrode (not illustrated).

**[0048]** The auxiliary electrodes to be in contact with the second electrode of the organic light emitting element according to exemplary embodiments of the present disclosure are located between pixel areas and formed of the same material as the first electrode, the source/drain electrodes, or a connection electrode 109 that electrically connects them. Thus, a process of forming an auxiliary electrode can be performed without an additional mask.

**[0049]** Further, the auxiliary electrode and the auxiliary line according to exemplary embodiments of the present disclosure are used without distinction. Also, while the auxiliary line is connected to the second electrode of the organic light emitting element by increasing a distance between the auxiliary electrode/ auxiliary line and the organic emission layer, the auxiliary line and the second electrode can be connected due to a difference in step coverage between the organic emission layer and the second electrode material but the organic emission layer is not allowed to be introduced between the auxiliary line and the second electrode. Thus, a contact area between the auxiliary electrode and the second electrode can be increased.

**[0050]** Details thereof will be described below with reference to FIG. 4 as a cross-sectional view taken along the line A-A'. Referring to FIG. 4, the substrate 100 includes a pixel area and a contact area. Herein, a thin film transistor Tr and an organic light emitting element EL are disposed on the pixel area of the substrate 100. Further, the auxiliary electrode 130 and a second electrode 122 are connected at the contact area of the substrate 100.

**[0051]** Specifically, a buffer layer 101 is disposed on the substrate 100, and the active layer 102 is disposed on the buffer layer 101. A gate insulation film 105 is disposed on a channel layer (not illustrated) of the active layer 102. The gate electrode 103 is disposed on the gate insulation film 105.

**[0052]** The gate electrode 103 may be formed by laminating at least one of Cu, Mo, Al, Ag, Ti, or alloys formed of combinations thereof. However, a material of the gate electrode 103 is not limited thereto, and materials generally used for a gate electrode and a gate line may be used. Further, although the gate electrode 103 is illus-

trated as a single metal layer in the drawing, the gate electrode 103 may be formed by laminating at least two metal layers in some cases.

**[0053]** A first interlayer insulation film 104 is disposed on the gate electrode 103. Further, the source electrode 106a and the drain electrode 106b are disposed on the interlayer insulation film 104 so as to be separated from each other. The source electrode 106a and the drain electrode 106b are in contact with the active layer 102 through the first contact hole formed in the interlayer insulation film 104.

**[0054]** Herein, the source electrode 106a and the drain electrode 106b may be formed by laminating at least one of Cu, Mo, Al, Ag, Ti, and alloys formed of combinations thereof or ITO, IZO, and ITZO which are transparent conductive materials. However, materials of the source electrode 106a and the drain electrode 106b are not limited thereto, and the source electrode 106a and the drain electrode 106b may be formed of materials generally used for a data line. Further, although each of the source electrode 106a and the drain electrode 106b is illustrated as a single metal layer in the drawing, each of the source electrode 106a and the drain electrode 106b may be formed by laminating at least two metal layers in some cases. As such, the thin film transistor Tr may be disposed on the substrate 100.

**[0055]** In order to protect the source electrode 106a and the drain electrode 106b, a second interlayer insulation film 107 and a first flattening film 108 are disposed on the substrate 100 including the thin film transistor Tr. On the first flattening film 108, a connection electrode 109 connected to the drain electrode 106b of the thin film transistor Tr and the auxiliary line 110 on the same layer as the connection electrode 109 are disposed. Herein, the auxiliary line 110 may be formed on the same layer and/or of the same material as the connection electrode 109, but is not limited thereto. The auxiliary line 110 may be formed of the same material as the gate electrode 103 or the source/drain electrodes 106a and 106b.

**[0056]** The auxiliary line 110 is electrically connected to the second electrode 122 of the organic light emitting element EL and can suppress a voltage drop caused by a resistance of the second electrode 122. Herein, the auxiliary line 110 may be formed to a width and a thickness suitable for the organic light emitting display device in order to improve a voltage drop of the large-sized display device. Further, a resistance of the auxiliary line 110 can be calculated on the basis of a width, a length, a thickness, and a kind of a material of the auxiliary line 110.

**[0057]** The auxiliary line 110 is disposed on the first flattening film 108 as described above. Thus, the auxiliary line 110 is substantially flat, which means that the auxiliary line 110 is formed so as not to have a stepped portion. However, the auxiliary line 110 according to an exemplary embodiment of the present disclosure is not limited thereto. If the first flattening film 108 is not formed to a sufficiently large thickness, the first flattening film 108 may have a stepped portion due to the components dis-

posed thereunder. Therefore, the auxiliary line 110 may also have a stepped portion.

**[0058]** Herein, since the auxiliary line 110 is disposed on the first flattening film 108, an effect of a parasitic capacitance which may be generated with the components of the thin film transistor Tr can be minimized. Therefore, the first flattening film 108 may be formed to a sufficiently large thickness to suppress a parasitic capacitance between the auxiliary line 110 and the components of the thin film transistor Tr.

**[0059]** Further, the auxiliary line 110 is disposed under the first electrode 120 of the organic light emitting element EL. Thus, the auxiliary line 110 may be formed regardless of a size of an area where the first electrode 120 is disposed. Therefore, a size of the area where the first electrode 120 is disposed can be increased, and, thus, an emission area can be further increased.

**[0060]** A second flattening film 111 may be disposed on the substrate 100 including the connection electrode 109 and the auxiliary line 110. Herein, in order to connect the first electrode 120 of the organic light emitting element EL to the drain electrode 106b of the thin film transistor Tr, it is necessary to form a contact hole in the first flattening film 108 and the second flattening film 111. While the contact hole is formed, it is difficult to form the contact hole so as to expose the drain electrode 106b since a flattening film is formed as a double layer. Therefore, the connection electrode 109 is disposed between the first flattening film 108 and the second flattening film 111, and, thus, it becomes easy to electrically connect the drain electrode 106b and the first electrode 120.

**[0061]** Further, the first electrode 120 of the organic light emitting element EL in contact with the connection electrode 109 through the contact hole is disposed on the second flattening film 111. Furthermore, the auxiliary electrode 130 in contact with the auxiliary line 110 through the contact hole is disposed on the same layer as the first electrode 120. The auxiliary electrode 130 can solve the problem of voltage drop.

**[0062]** Herein, the first electrode 120 may be formed of a transparent conductive material having a high work function. For example, the first electrode 120 may be formed of any one selected from the group consisting of ITO (Indium Tin Oxide), IZO (Indium Zinc Oxide), and ZnO. Although the first electrode 120 is illustrated as a single layer in the drawing, the first electrode 120 may be formed as a multilayer including a reflective layer and a transparent conductive layer.

**[0063]** The auxiliary electrode 130 may be formed of the same material as the first electrode 120, but is not limited thereto. The auxiliary electrode 130 may be formed of the same material as the gate electrode 103, the source/drain electrodes 106a and 106b, the connection electrode 109, or the auxiliary line 110. The auxiliary electrode 130 may function to electrically connect the auxiliary line 110 and the second electrode of the organic light emitting element EL.

**[0064]** The bank pattern 150 may be disposed on both

lateral surfaces of the first electrode 120 and the auxiliary electrode 130. That is, the bank pattern 150 may be disposed to expose a part of upper surfaces of the first electrode 120 and of the auxiliary electrode 130. Further, a barrier rib 160 is disposed on the exposed part of the upper surface of the auxiliary electrode 130 which is exposed by the bank pattern 150. Herein, the barrier rib 160 may be disposed on the same layer as the bank pattern 150 and formed of the same material as the bank pattern 150. The barrier rib 160 can cut an organic emission layer 131 near the auxiliary electrode 130. Then, the auxiliary electrode 130 can facilitate contact a second electrode.

**[0065]** Hereinafter, the shapes of the bank pattern 150 and the barrier rib 160 will be described in detail with reference to FIG. 5. Referring to FIG. 5, the bank pattern 150 includes a first area 151 having a reverse-tapered shape gradually increased in width from the substrate 100 and a second area 152 having a tapered shape gradually decreased in width from the substrate 100 and disposed under the first area 151. Further, the barrier rib 160 may include a third area 161 having a reverse-tapered shape and a fourth area 162 having a tapered shape and disposed under the third area 161.

**[0066]** Herein, the bank pattern 150 may be formed of a thermosetting negative photoresist. While the bank pattern 150 is formed using a thermosetting negative photoresist 150a (refer to FIG. 6A through FIG. 6C), as a distance between a mask 500 and the thermosetting negative photoresist 150a is increased during an exposure process, a light 510 is scattered from an end of the mask 500. Due to scattering of the light 510, an exposure amount is different between an end and a central portion of the thermosetting negative photoresist 150a. Thus, the thermosetting negative photoresist 150a can be formed into a reverse-tapered shape.

**[0067]** After the exposure process of the thermosetting negative photoresist 150a, a lower portion of a cured thermosetting negative photoresist 150b, 150c may be formed into a tapered shape through a heat treatment process of applying heat 511 of 300°C or less. Specifically, the central portion of the thermosetting negative photoresist 150a is supplied with a sufficient exposure amount of light and thus completely initiated. However, the end of the thermosetting negative photoresist 150a is supplied with an insufficient exposure amount due to scattering of the light 510 and thus not sufficiently initiated as compared with the central portion thereof. Then, the central portion of the thermosetting negative photoresist 150a which has been sufficiently initiated is first cured during the heat treatment process for curing the thermosetting negative photoresist 150a. Then, the end of the thermosetting negative photoresist 150b, 150c is developed.

**[0068]** By curing the thermosetting negative photoresist 150a while adjusting duration of the heat treatment, a protrusion 150c may be formed at the lower portion of the thermosetting negative photoresist 150b. Thus, an

upper portion of the cured thermosetting negative photoresist may be formed into a reverse-tapered shape, and the lower portion of the thermosetting negative photoresist may be formed into a tapered shape.

**[0069]** Accordingly, the bank pattern 150b, 150c including both the reverse-tapered shape and the tapered shape may be formed. Further, a barrier rib pattern may be formed on the same layer as the bank pattern 150b, 150c through the same process of forming the bank pattern 150b, 150c.

**[0070]** The shapes of the bank pattern 150b, 150c and the barrier rib pattern formed as such may be finally determined through an exposure process using a half-tone mask 600. For example, a negative photoresist is formed on the bank pattern 150b, 150c and the barrier rib pattern, and the half-tone mask 600 including a shielding portion 600a, a transmissive portion 600d, and a semi-transmissive portion 600c is disposed on the substrate on which the negative photoresist is formed. Herein, the transmissive portion 600c transmits light, and the semi-transmissive portion 600d transmits less light than the transmissive portion 600c. The shielding portion 600a completely shields light.

**[0071]** The transmissive portion 600d of the half-tone mask 600 is disposed corresponding to the barrier rib pattern and the semi-transmissive portion 600c is disposed corresponding to the bank pattern 150b, 150c. Further, the shielding portion 600a is disposed corresponding to the other area where the bank pattern 150b, 150c and the barrier rib are not disposed. The thermosetting negative photoresist formed on the area where the bank pattern 150b, 150c and the barrier rib are not disposed is removed using the half-tone mask 600. Then, the negative photoresist formed on the bank pattern 150b, 150c is ashed. In this case, the negative photoresist disposed on the barrier rib is removed in part. Then, a part of the upper portion of the bank pattern 150b, 150c is etched using the negative photoresist remaining on the barrier rib as a mask. The photoresist may be a positive photoresist. In this case, the pattern of the half-tone mask 600 may be formed in reverse.

**[0072]** After the exposure process and the development process using the half-tone mask 600, each of the bank pattern 150 and the barrier rib 160 may be formed to have both a reverse-tapered shape and a tapered shape. As such, the bank pattern 150 and the barrier rib 160 may be formed through the same process. However, a process of forming the bank pattern 150 and the barrier rib 160 of the present disclosure is not limited thereto. Any process capable of forming the bank pattern 150 and the barrier rib 160 to have a reverse-tapered shape and a tapered shape, i.e. a shape of an hourglass, may be employed.

**[0073]** After the exposure process and the development process using the half-tone mask 600, the bank pattern 150 and the barrier rib 160 may be different in height. Herein, the heights of the bank pattern 150 and the barrier rib 160 having gone through the exposure

process and the development process using the half-tone mask 600 may be changed depending on an exposure amount or duration of exposure and development. Specifically, the height of the barrier rib 160 may be higher than the height of the bank pattern 150. More specifically, a height of the third area 160 of the barrier rib 160 may be higher than a height of the first area 151 of the bank pattern 150.

**[0074]** Herein, only a part of the first area 151 of the bank pattern 150 is etched during the exposure process and the development process using the half-tone mask 600, a height of the second area 152 of the bank pattern 150 may be the same as a height of the fourth area 162 of the barrier rib 160. In this case, the height of the second area 152 of the bank pattern 150 may be defined as a length from an upper surface of the first electrode 120 of the organic light emitting element EL to a contact point between the second area 152 and the first area 151 of the bank pattern 150. Further, the height of the fourth area 162 of the barrier rib 160 may be defined as a length from the upper surface of the first electrode 120 of the organic light emitting element EL to a contact point between the fourth area 162 and the third area 161 of the barrier rib 160.

**[0075]** That is, the second area 152 of the bank pattern 150 and the fourth area 162 of the barrier rib 160 have the same height and the height of the first area 151 of the bank pattern 150 is lower than the height of the third area 161 of the barrier rib 160. Thus, the overall height of the bank pattern 150 may be lower than the overall height of the barrier rib 160. Herein, since the height of the bank pattern 150 is lower than the height of the barrier rib 160, an open area between the bank pattern 150 and the barrier rib 160 may be formed to a large size. Thus, the second electrode 122 of the organic light emitting element EL may be disposed to a wide range on the exposed upper surface of the auxiliary electrode 130.

**[0076]** As illustrated in FIG. 4 and FIG. 5, an organic emission layer 131a, 131b, 131c, 141 of the organic light emitting element EL is disposed on the substrate 100 on which the bank pattern 150 and the barrier rib 160 are disposed. In this case, the organic emission layer 131a, 131b, 131c, 141 may be formed by a linear deposition or coating method. For example, the organic emission layer 131a, 131b, 131c, 141 may be formed by evaporation. The organic emission layer 131a, 131b, 131c, 141 formed by the above-described method may include first non-disposition areas 151a and 151b, second non-disposition areas 161a and 161b, and third non-disposition areas 162a and 162b on the substrate 100.

**[0077]** Herein, the first non-disposition areas 151a and 151b of the organic emission layer 131a, 131b, 131c, 141 correspond to partial areas of both lateral surfaces of the first area 151 of the bank pattern 150. The second non-disposition areas 161a and 161b of the organic emission layer 131a, 131b, 131c, 141 correspond to both lateral surfaces of the third area 161 of the barrier rib 160. The third non-disposition areas 162a and 162b of the

organic emission layer 131a, 131b, 131c, 141 correspond to both lateral surfaces of the fourth area 162 of the barrier rib 160 and a part of the upper surface of the auxiliary electrode 130 which is exposed by the organic emission layer 131a, 131b, 131c, 141.

**[0078]** Specifically, the organic emission layer 131a, 131b, 131c, 141 may be disposed on an upper surface of the bank pattern 150, parts of both lateral surfaces of the bank pattern 150, and an upper surface of the barrier rib 160. Herein, the organic emission layer 131b, 131c disposed on the parts of the both lateral surfaces of the bank pattern 150 may be disposed to expose an area of the first area 151 having a reverse-tapered shape where a taper angle is formed.

**[0079]** More specifically, since the organic emission layer 131a, 131b, 131c, 141 is formed by a linear deposition or coating method, the organic emission layer 131a, 131b, 131c, 141 is not formed on an area having a stepped portion or an area, such as the bank pattern 150, having a reverse-tapered structure. Therefore, the organic emission layer 131a, 131b, 131c, 141 is not deposited or coated on partial areas of the both lateral surfaces of the first area 151 of the bank pattern 150 where a taper angle is formed.

**[0080]** Further, the organic emission layer 131a, 131b, 131c, 141 is not deposited or coated around the barrier rib 160 having a reverse-tapered structure. Specifically, the organic emission layer 131a, 131b, 131c, 141 is formed only on an upper surface of the third area 161 of the barrier rib 160, but not formed on both lateral surfaces of the third area 161 of the barrier rib 160 and around the fourth area 162. More specifically, the organic emission layer 131a, 131b, 131c, 141 may be formed to expose the both lateral surfaces of the third area 161 and a part of the upper surface of the auxiliary electrode 130 around the fourth area 162.

**[0081]** The second electrode 122 of the organic light emitting element EL may be disposed on the substrate 100 on which the organic emission layer 131a, 131b, 131c, 141 is disposed. Herein, the second electrode 122 may be formed by a non-directional deposition or coating method. For example, the second electrode 122 may be formed by sputtering. Such a method has an excellent step coverage, and, thus, can easily form the second electrode 122 on a structure having a stepped portion or a reverse-tapered shape.

**[0082]** Therefore, the second electrode 122 can be easily disposed on the bank pattern 150 having a reverse-tapered shape and around the barrier rib 160. Specifically, the second electrode 122 may be disposed on any area of the bank pattern 150 and of the barrier rib 160 except for lateral surfaces of the third area 161. Herein, the second electrode 122 cannot be introduced on the lateral surfaces of the third area 161 of the barrier rib 160. Thus, the second electrode 122 is not formed on the lateral surfaces of the third area 161.

**[0083]** That is, the second electrode 122 may be disposed to be in contact with the bank pattern 150 on the

partial areas of the lateral surfaces of the first area 151 of the bank pattern 150 where the organic emission layer 131a, 131b, 131c, 141 is not disposed. Further, the second electrode 122 may be disposed on the auxiliary electrode 130 of which the upper surface is exposed in part since the organic emission layer 131a, 131b, 131c, 141 is not disposed. That is, the second electrode 122 may be disposed to be in contact with the part of the upper surface of the auxiliary electrode 130.

**[0084]** Herein, the second electrode 122 may be decreased in thickness around the both lateral surfaces of the first area 151 of the bank pattern 150, and may be decreased in thickness on the auxiliary electrode 130 around the fourth area 162 of the barrier rib 160. This is because while the second electrode 122 is formed, a pathway for a material of the second electrode 122 is blocked by the first area 151 of the bank pattern 150 having a reverse-tapered shape and the third area 161 of the barrier rib 160.

**[0085]** However, since the organic emission layer 131a, 131b, 131c, 141 is disposed to expose the part of the upper surface of the auxiliary electrode 130, the second electrode 122 and the auxiliary electrode 130 can be fully brought into contact with each other at the exposed area of the upper surface of the auxiliary electrode 130. Thus, a resistance of the second electrode 122 can be reduced.

**[0086]** In other words, since the first area 151 of the bank pattern 150 has a small height, the maximum width of the first area 151 of the bank pattern 150 may be smaller than the maximum width of the second area 152 of the bank pattern 150. Further, since the third area 161 of the barrier rib 160 has a great height, the maximum width of the third area 161 may be greater than the maximum width of the fourth area 162 of the barrier rib 160.

**[0087]** Meanwhile, since the organic emission layer 131a, 131b, 131c, 141 is formed by a linear deposition or coating method, as the maximum widths of the first area 151 and the third area 161 having a reverse-tapered shape are increased, an area for the organic emission layer 131a, 131b, 131c, 141 is decreased. That is, as the heights and the maximum widths of the first area 151 and the third area 161 are increased, an area covered by the widest portions of the first area 151 and the third area 161 is increased. Thus, the area for the organic emission layer 131a, 131b, 131c, 141 formed by a linear deposition or coating method is decreased.

**[0088]** That is, since the maximum width of the third area 161 of the barrier rib 160 having a reverse-tapered shape is greater than the maximum width of the fourth area 162, introduction of a material of the organic emission layer 131a, 131b, 131c, 141 into an area where the auxiliary electrode 130 is disposed can be suppressed. Specifically, when the maximum width of the third area 161 is greater than the maximum width of the fourth area 162, the third area 161 may be formed to be overlapped with the second area 152 of the bank pattern 150 and/or a part of the upper surface of the auxiliary electrode 130

which is exposed by the fourth area 162 of the barrier rib 160. Thus, the third area 161 covers the part of the upper surface of the auxiliary electrode 130. Therefore, deposition or coating of the organic emission layer 131a, 131b, 131c, 141 on the entire surface of the auxiliary electrode 130 can be suppressed.

**[0089]** That is, the organic emission layer 131a, 131b, 131c, 141 may be disposed to expose the part of the upper surface of the auxiliary electrode 130. Therefore, it is possible to adjust an area where the second electrode 122 and the auxiliary electrode 130 can be brought into contact with each other depending on a height of the third area 161 of the barrier rib 160. Accordingly, it is possible to effectively reduce a resistance of the second electrode 122.

**[0090]** Further, a conventional organic emission layer is formed to a large thickness at a boundary between a bank pattern and a first electrode of an organic light emitting element, and, thus, has the problem of a leakage current at the boundary between the bank pattern and the first electrode. However, the bank pattern 150 according to an exemplary embodiment of the present disclosure includes the first area 151 having a reverse-tapered shape. Therefore, the organic emission layer 131a, 131b, 131c, 141 includes the first non-disposition areas 151a and 151b on the partial areas of the both lateral surfaces of the first area 151. Thus, it is possible to suppress generation of a leakage current. That is, the bank pattern 150 and the second electrode 122 are disposed to be in contact with each other in the first non-disposition areas 151a and 151b of the organic emission layer 131a, 131b, 131c, 141, and the configuration of the organic emission layer 131a, 131b, 131c, 141 that causes a leakage current is eliminated. Therefore, it is possible to suppress generation of a leakage current.

**[0091]** Further, since the maximum width of the first area 151 of the bank pattern 150 is smaller than the maximum width of the second area 152, the organic emission layer 131a, 131b, 131c, 141 may include the first non-disposition areas 151a and 151b at a boundary between the bank pattern 150 and the first electrode 120 in order not to affect an emission area. In other words, according to an exemplary embodiment of the present disclosure, even if the organic emission layer 131a, 131b, 131c, 141 includes a non-disposition area, an emission area is not decreased but generation of a leakage current is suppressed. Thus, it is possible to suppress generation of a dark spot or a bright spot.

**[0092]** Hereinafter, the shape of the bank pattern according to another exemplary embodiment of the present disclosure will be described with reference to FIG. 7. The organic light emitting display device according to another exemplary embodiment of the present disclosure may include the same components as those of the above-described exemplary embodiment. The redundant description thereof may be omitted. Further, the same components will be assigned the same reference numerals.

**[0093]** Referring to FIG. 7, a bank pattern 250 accord-

ing to another exemplary embodiment of the present disclosure includes a first area 251 and a second area 252. The first area 251 of the bank pattern 250 is formed into a reverse-tapered shape, and the second area 252 of the bank pattern 250 is formed into a tapered shape.

**[0094]** In this case, the maximum width of the first area 251 of the bank pattern 250 may be greater than the maximum width of the second area 252 of the bank pattern 250. Thus, first non-disposition areas 251a and 251b of the organic emission layer 131a, 131b, 131c, 141 may be increased in size. Therefore, it is possible to further suppress generation of a leakage current caused by a large thickness of the organic emission layer 131a, 131b, 131c, 141.

**[0095]** Hereinafter, an organic light emitting display device according to yet another exemplary embodiment of the present disclosure will be described with reference to FIG. 8. FIG. 8 is a cross-sectional view of an organic light emitting display device according to yet another exemplary embodiment of the present disclosure. The organic light emitting display device according to yet another exemplary embodiment of the present disclosure may include the same components as those of the above-described exemplary embodiment. The redundant description thereof may be omitted. Further, the same components will be assigned the same reference numerals.

**[0096]** FIG. 8 is a plane view illustrating that the first flattening film 108, the connection electrode 109, and the auxiliary line 110 illustrated in the cross-sectional view of FIG. 4 are excluded from the organic light emitting display device according to yet another exemplary embodiment of the present disclosure and the first electrode 120 of the organic light emitting element EL is directly connected to the drain electrode 106b of the thin film transistor Tr. Herein, since the first flattening film 108, the connection electrode 109, and the auxiliary line 110 are excluded, the number of masks and the number of processes can be reduced.

**[0097]** Further, the auxiliary electrode and the barrier rib of the present disclosure may be disposed at various locations. Details thereof will be described with reference to FIG. 9 through FIG. 11. FIG. 9 is a plane view illustrating a disposition relationship between a sub-pixel and an auxiliary electrode according to an exemplary embodiment. Referring to FIG. 9, a plurality of pixel areas P is disposed on the substrate 100 of the organic light emitting display device. A plurality of sub-pixels is disposed on the pixel area P.

**[0098]** Specifically, the pixel area P may include a first sub-pixel SP1, a second sub-pixel SP2, a third sub-pixel SP3, and a fourth sub-pixel SP4. The pixel area P includes four sub-pixels in the drawing, but is not limited thereto. The pixel area P may include three sub-pixels.

**[0099]** Herein, the first sub-pixel SP1 may be a white (W) sub-pixel, the second sub-pixel SP2 may be a red (R) sub-pixel, the third sub-pixel SP3 may be a green (G) sub-pixel, and the fourth sub-pixel SP4 may be a blue (B) sub-pixel, but is not limited thereto.

**[0100]** Herein, the first to fourth sub-pixels SP1, SP2, SP3, and SP4 may be defined as an emission area EA and a non-emission area NEA by a bank pattern 350. That is, an area opened by the bank pattern 350 may be the emission area EA, and an area where the bank pattern 350 is disposed may be the non-emission area NEA. In this case, the non-emission area NEA may include an area where an auxiliary electrode 330 is disposed.

**[0101]** Further, the auxiliary electrode 330 may be disposed at one side of the first to fourth sub-pixels SP1, SP2, SP3, and SP4. That is, a single auxiliary electrode 330 may be included in each sub-pixel. Herein, the auxiliary electrode 330 may be disposed in parallel with a gate line (not illustrated), or may be disposed in parallel with a data line (not illustrated).

**[0102]** A barrier rib 360 may be disposed on a part of an upper surface of the auxiliary electrode 330. Herein, the bank pattern 350 and the barrier rib 360 may be disposed on the same layer and formed of the same material. Further, each of the bank pattern 350 and the barrier rib 360 may be formed to have both a reverse-tapered shape and a tapered shape.

**[0103]** Further, although the auxiliary electrode 330 is illustrated as being disposed at a lower side of the first to fourth sub-pixels SP1, SP2, SP3, and SP4 in Fig. 9, the present disclosure is not limited thereto. The auxiliary electrode 330 may be disposed at an upper side or a lateral side of each sub-pixel. That is, in an exemplary embodiment of the present disclosure, each sub-pixel is provided with an auxiliary electrode 330 respectively. As such, since the auxiliary electrode 330 is disposed in each sub-pixel, a voltage difference of the organic light emitting display device can be controlled by unit of a sub-pixel.

**[0104]** FIG. 10 is a plane view illustrating a disposition relationship between a sub-pixel and an auxiliary electrode according to another exemplary embodiment. The organic light emitting display device according to another exemplary embodiment of the present disclosure may include the same components as those of the above-described exemplary embodiment. The redundant description thereof may be omitted. Further, the same components will be assigned the same reference numerals. Referring to FIG. 10, pixel areas P each including a plurality of sub-pixels SP1, SP2, SP3, and SP4 are disposed on the substrate 100.

**[0105]** Further, an auxiliary electrode 430 may be disposed at one side of the pixel area P. That is, one auxiliary electrode 430 may be included in each pixel area P. Herein, the auxiliary electrode 430 may be disposed in parallel with a gate line (not illustrated), or may be disposed in parallel with a data line (not illustrated).

**[0106]** A barrier rib 460 disposed on the same layer and formed of the same material as a bank pattern 450 may be disposed on the auxiliary electrode 430. Each of the bank pattern 450 and the barrier rib 460 may be formed to have both a reverse-tapered shape and a tapered shape.

**[0107]** Although the auxiliary electrode 430 is illustrated as being disposed at a lower side of the pixel area P in the drawing, the present disclosure is not limited thereto. The auxiliary electrode 430 may be disposed at an upper side or a lateral side of the pixel area P. That is, in an exemplary embodiment of the present disclosure, a single auxiliary electrode 430 is sufficient for each pixel area P. As such, since the single auxiliary electrode 430 is disposed in each pixel, a voltage difference of the organic light emitting display device can be controlled by unit of a pixel area.

**[0108]** FIG. 11 is a plane view illustrating a disposition relationship between a sub-pixel and an auxiliary electrode according to yet another exemplary embodiment. The organic light emitting display device according to yet another exemplary embodiment of the present disclosure may include the same components as those of the above-described exemplary embodiments. The redundant description thereof may be omitted. Further, the same components will be assigned the same reference numerals.

**[0109]** Referring to FIG. 11, a first pixel area P1 and a second pixel area P2 each including a plurality of sub-pixels SP1, SP2, SP3, and SP4 are disposed on the substrate 100. Herein, the first pixel area P1 and the second pixel area P2 are disposed to be adjacent to each other. For example, the first pixel area P1 may be located on the second pixel area P2.

**[0110]** Herein, an auxiliary electrode 530 may be disposed between the first pixel area P1 and the second pixel area P2. Specifically, the auxiliary electrode 530 may be disposed between one sub-pixel disposed in the first pixel area P1 and the corresponding sub-pixel disposed in the second pixel area P2.

**[0111]** For example, the auxiliary electrode 530 may be disposed between the second sub-pixel SP2 disposed in the first pixel area P1 and the second sub-pixel SP2 disposed in the second pixel area P2. Herein, the second sub-pixels SP2 may be white (W) sub-pixels.

**[0112]** Although the auxiliary electrode 530 is illustrated as being disposed between the white (W) sub-pixel in the first pixel area P1 and the white (W) sub-pixel in the second pixel area P2 in the drawing, the present disclosure is not limited thereto. The auxiliary electrode 530 may be disposed between a red (R) sub-pixel in the first pixel area P1 and a red (R) sub-pixel in the second pixel area P2. Otherwise, the auxiliary electrode 530 may be disposed between a green (G) sub-pixel in the first pixel area P1 and a green (G) sub-pixel in the second pixel area P2. Alternatively, the auxiliary electrode 530 may be disposed between a blue (B) sub-pixel in the first pixel area P1 and a blue (B) sub-pixel in the second pixel area P2.

**[0113]** A barrier rib 560 disposed on the same layer and formed of the same material as a bank pattern 550 may be disposed on the auxiliary electrode 530. Each of the bank pattern 550 and the barrier rib 560 may be formed to have both a reverse-tapered shape and a tapered shape.

**[0114]** Further, although the single auxiliary electrode 530 is illustrated as being disposed between two pixel areas in an exemplary embodiment of the present disclosure, the present disclosure is not limited thereto. A plurality of pixel areas may share the single auxiliary electrode 530. As such, since a plurality of pixel areas includes the auxiliary electrode 530, a voltage difference of the organic light emitting display device can be controlled by unit of a plurality of pixel areas.

**[0115]** It should be understood that the exemplary embodiments described above should be considered in a descriptive sense only and not for purposes of limitation. It will be understood by those skilled in the art that various other modifications and applications may be made therein without departing from the scope of the exemplary embodiments. For example, respective components shown in detail in the exemplary embodiments may be executed while being modified. The invention is as specified in the set of appended claims.

## Claims

### 1. An organic light emitting display device comprising:

a substrate (100);  
 a first electrode (120) and an auxiliary electrode (130) disposed on the substrate (100);  
 a bank pattern (150) disposed on a part of the first electrode (120) and on a part of the auxiliary electrode (130) and divided into a first area (151) having a reverse-tapered shape gradually increased in width from the substrate (100) and a second area (152) below the first area (151) and having a tapered shape gradually decreased in width from the substrate (100);  
 a barrier rib (160) disposed on the auxiliary electrode (130) and divided into a third area (161) having a reverse-tapered shape and a fourth area (162) below the third area (161) and having a tapered shape;  
 an organic emission layer (131) disposed on the substrate (100) except of an area of the auxiliary electrode (130) adjacent to the barrier rib (160); and  
 a second electrode (122) disposed on the organic emission layer (131) and in contact with the auxiliary electrode (130),  
 wherein a height of the second area of the bank pattern (150) is the same as a height of the fourth area of the barrier rib (160), and a height of the first area of the bank pattern (150) is smaller than a height of the third area of the barrier rib (160).

2. The organic light emitting display device according to claim 1, wherein a height of the bank pattern (150) is smaller than a height of the barrier rib (160).

3. The organic light emitting display device according to any one of the preceding claims, wherein a maximum width of the third area (161) of the barrier rib (160) is greater than the maximum width of the fourth area (162).

4. The organic light emitting display device according to any one of the preceding claims, wherein the organic emission layer includes at least one of a first, a second and a third non-disposition area (151a, 151b, 161a, 161b, 162a, 162b), wherein:

the first non-disposition area (151a, 151b) of the organic emission layer (131) corresponds to a part of the lateral surfaces of the first area of the bank pattern (150),  
 the second non-disposition area (161a, 161b) of the organic emission layer (131) corresponds to lateral surfaces of the third area (161) of the barrier rib (160), and  
 the third non-disposition area (162a, 162b) of the organic emission layer (131) corresponds to lateral surfaces of the fourth area (162) of the barrier rib (160).

5. The organic light emitting display device according to claim 4, wherein the organic emission layer includes the first non-disposition area and wherein the second electrode (122) is in contact with the bank pattern (150) in the first non-disposition area (151a, 151b) of the organic emission layer (131).

6. The organic light emitting display device according to any one of the preceding claims, wherein the second electrode (122) is in contact with the auxiliary electrode (130) in the area of the auxiliary electrode (130) adjacent to the barrier rib (160) which is exposed by the bank pattern (150) and the barrier rib (160).

7. The organic light emitting display device according to any one of the preceding claims, wherein the first electrode (120) and the auxiliary electrode (130) are disposed on a same layer, and/or wherein the bank pattern (150) and the barrier rib (160) are disposed on a same layer.

8. The organic light emitting display device according to any one of the preceding claims, further comprising an auxiliary line (110) below the auxiliary electrode (130) and the first electrode (120) with a flattening film (111) inbetween, the auxiliary line (110) being in contact with the auxiliary electrode (130).

9. The organic light emitting display device according to claim 8, wherein the auxiliary line (110) overlaps with the first electrode (120).

10. The organic light emitting display device according to any one of the preceding claims, wherein the substrate (100) includes a plurality of pixel areas (P), each pixel area (P) including a plurality of sub-pixel areas (SP1, SP2, SP3, SP4), wherein the auxiliary electrode (130) is disposed corresponding to each of the sub-pixel areas (SP1, SP2, SP3, SP4), or corresponding to each of the pixel areas (P), or corresponding to two or more pixel areas (P).

11. A manufacturing method for an organic light emitting display device according to claim 1, comprising:

forming a first electrode (120) of an organic light emitting element (EL) and an auxiliary electrode (130) on a substrate (100);  
forming a first photoresist (150a) on an area overlapped with an end of the first electrode (120) and an end of the auxiliary electrode (130), corresponding to an area of a bank pattern (150), and on a central area of the auxiliary electrode (130), corresponding to an area of a barrier rib (160), into a reverse-tapered shape by irradiating a light through a mask (500) on the first photoresist (150a);  
forming a lower area of the first photoresist (150a) into a tapered shape by performing a heat treatment to the first photoresist (150a) formed into the reverse-tapered shape;  
removing the first photoresist (150a, 150b, 150c) formed in an area excluding the area corresponding to the bank pattern (150) and the area corresponding to the barrier rib (160); and  
forming an organic emission layer (131) and a second electrode (122) on the substrate (100).

12. The manufacturing method for an organic light emitting display device according to claim 11, wherein the removing of the first photoresist (150a) includes:

forming a second photoresist on the substrate (100);  
disposing a mask (600) including a semi-transmissive portion (600c) facing the area corresponding to the bank pattern (150), a transmissive portion (600d) facing the area corresponding to the barrier rib (160), and a shielding portion (600a) facing the area except the area corresponding to the bank pattern (150) and the area corresponding to the barrier rib (160);  
etching a part of the second photoresist in the area corresponding to the bank pattern (150) and the second photoresist in an area excluding the area corresponding to the bank pattern (150) and the area corresponding to the barrier rib (160), using the mask (600); and  
removing the first photoresist (150a, 150b, 150c) formed in an area excluding the area cor-

responding to the bank pattern (150) and the area corresponding to the barrier rib (160), using the remaining second photoresist as a mask.

13. The manufacturing method for an organic light emitting display device according to claim 12, further comprising:

after the removing of the first photoresist formed in an area excluding the area corresponding to the bank pattern (150) and the area corresponding to the barrier rib (160), ashing the second photoresist formed in the area corresponding to the bank pattern (150) and a part of the second photoresist formed in the area corresponding to the barrier rib (160); and  
etching a part of the first photoresist formed in the area corresponding to the bank pattern (150), using the second photoresist formed in the area corresponding to the barrier rib (160) as a mask.

14. The manufacturing method for an organic light emitting display device according to any one of claims 11 to 13, wherein the first photoresist (150a) is a thermosetting photoresist.

#### Patentansprüche

1. Organische lichtemittierende Vorrichtung, die Folgendes umfasst:

ein Substrat (100);  
eine erste Elektrode (120) und eine zusätzliche Elektrode (130), die auf dem Substrat (100) angeordnet sind;  
eine Bankstruktur (150), die auf einem Teil der ersten Elektrode (120) und auf einem Teil der zusätzlichen Elektrode (130) angeordnet ist und in einen ersten Bereich (151), der eine umgekehrt konisch zulaufende Form aufweist, deren Breite von dem Substrat (100) aus schrittweise zunimmt, und in einen zweiten Bereich (152) unter dem ersten Bereich (151), der eine konisch zulaufende Form aufweist, deren Breite von dem Substrat (100) aus schrittweise abnimmt, unterteilt ist;  
eine Barriererippe (160), die auf der zusätzlichen Elektrode (130) angeordnet ist und in einen dritten Bereich (161), der eine umgekehrt konisch zulaufende Form aufweist, und in einen vierten Bereich (162) unter dem dritten Bereich (161), der eine konisch zulaufende Form aufweist, unterteilt ist;  
eine organische Emissionslage (131), die auf dem Substrat (100) mit Ausnahme eines Bereichs der zusätzlichen Elektrode (130) angren-

- zend an die Barriererippe (160) angeordnet ist; und  
eine zweite Elektrode (122), die auf der organischen Emissionslage (131) und in Kontakt mit der zusätzlichen Elektrode (130) angeordnet ist, wobei eine Höhe des zweiten Bereichs der Bankstruktur (150) einer Höhe des vierten Bereichs der Barriererippe (160) entspricht und wobei eine Höhe des ersten Bereichs der Bankstruktur (150) kleiner als eine Höhe des dritten Bereichs der Barriererippe (160) ist.
2. Organische lichtemittierende Vorrichtung nach Anspruch 1, wobei eine Höhe der Bankstruktur (150) kleiner als eine Höhe der Barriererippe (160) ist.
3. Organische lichtemittierende Vorrichtung nach einem der vorhergehenden Ansprüche, wobei eine maximale Breite des dritten Bereichs (161) der Barriererippe (160) größer als die maximale Breite des vierten Bereichs (162) ist.
4. Organische lichtemittierende Vorrichtung nach einem der vorhergehenden Ansprüche, wobei die organische Emissionslage einen ersten und/oder einen zweiten und/oder einen dritten beschichtungsfreien Bereich (151a, 151b, 161a, 161b, 162a, 162b) umfasst, wobei:  
der erste beschichtungsfreie Bereich (151a, 151b) der organischen Emissionslage (131) einem Teil der seitlichen Oberflächen des ersten Bereichs der Bankstruktur (150) entspricht, der zweite beschichtungsfreie Bereich (161a, 161b) der organischen Emissionslage (131) seitlichen Oberflächen des dritten Bereichs (161) der Barriererippe (160) entspricht, und der dritte beschichtungsfreie Bereich (162a, 162b) der organischen Emissionslage (131) seitlichen Oberflächen des vierten Bereichs (162) der Barriererippe (160) entspricht.
5. Organische lichtemittierende Vorrichtung nach Anspruch 4, wobei die organische Emissionslage den ersten beschichtungsfreien Bereich umfasst und wobei die zweite Elektrode (122) mit der Bankstruktur (150) in dem ersten beschichtungsfreien Bereich (151a, 151b) der organischen Emissionslage (131) in Kontakt ist.
6. Organische lichtemittierende Vorrichtung nach einem der vorhergehenden Ansprüche, wobei die zweite Elektrode (122) mit der zusätzlichen Elektrode (130) in dem Bereich der zusätzlichen Elektrode (130) angrenzend an die Barriererippe (160), der durch die Bankstruktur (150) und die Barriererippe (160) freiliegt, in Kontakt ist.
7. Organische lichtemittierende Vorrichtung nach einem der vorhergehenden Ansprüche, wobei die erste Elektrode (120) und die zusätzliche Elektrode (130) auf der gleichen Lage angeordnet sind und/oder wobei die Bankstruktur (150) und die Barriererippe (160) auf der gleichen Lage angeordnet sind.
8. Organische lichtemittierende Vorrichtung nach einem der vorhergehenden Ansprüche, die ferner eine zusätzliche Leitung (110) unter der zusätzlichen Elektrode (130) und der ersten Elektrode (120) mit einer Glättungsschicht (111) dazwischen umfasst, wobei die zusätzliche Leitung (110) mit der zusätzlichen Elektrode (130) in Kontakt ist.
9. Organische lichtemittierende Vorrichtung nach Anspruch 8, wobei die zusätzliche Leitung (110) mit der ersten Elektrode (120) überlappt.
10. Organische lichtemittierende Vorrichtung nach einem der vorhergehenden Ansprüche, wobei das Substrat (100) mehrere Pixelbereiche (P) umfasst, wobei jeder Pixelbereich (P) mehrere Pixelunterbereiche (SP1, SP2, SP3, SP4) umfasst, wobei die zusätzliche Elektrode (130) in Übereinstimmung mit jedem der Pixelunterbereiche (SP1, SP2, SP3, SP4) oder in Übereinstimmung mit jedem der Pixelbereiche (P) oder in Übereinstimmung mit zwei oder mehreren Pixelbereichen (P) angeordnet ist.
11. Herstellungsverfahren für eine organische lichtemittierende Vorrichtung nach Anspruch 1, wobei das Verfahren die folgenden Schritte umfasst:  
Ausbilden einer ersten Elektrode (120) eines organischen Leuchtelements (EL) und einer zusätzlichen Elektrode (130) auf einem Substrat (100);  
Ausbilden eines ersten Fotolacks (150a) auf einem Bereich, der mit einem Ende der ersten Elektrode (120) und mit einem Ende der zusätzlichen Elektrode (130) überlappt, der einem Bereich einer Bankstruktur (150) entspricht, und auf einem zentralen Bereich der zusätzlichen Elektrode (130), der einem Bereich einer Barriererippe (160) entspricht, in einer umgekehrt konisch zulaufenden Form durch Bestrahlen des ersten Fotolacks (150a) mit Licht durch eine Maske (500);  
Ausbilden eines unteren Bereichs des ersten Fotolacks (150a) in eine konisch zulaufende Form durch Durchführen einer Wärmebehandlung bei dem ersten Fotolack (150a), der in der umgekehrt konisch zulaufenden Form ausgebildet ist;  
Entfernen des ersten Fotolacks (150a, 150b, 150c), der in einem Bereich mit Ausnahme des

Bereichs, der der Bankstruktur (150) entspricht, und des Bereichs, der der Barriererippe (160) entspricht, ausgebildet ist; und  
Ausbilden einer organischen Emissionslage (131) und einer zweiten Elektrode (122) auf dem Substrat (100).

12. Herstellungsverfahren für eine organische lichtemittierende Vorrichtung nach Anspruch 11, wobei das Entfernen des ersten Fotolacks (150a) die folgenden Schritte umfasst:

Ausbilden eines zweiten Fotolacks auf dem Substrat (100);  
Anordnen einer Maske (600), die einen teilweise lichtdurchlässigen Abschnitt (600c), der zu dem Bereich zeigt, der der Bankstruktur (150) entspricht, einen lichtdurchlässigen Abschnitt (600d), der zu dem Bereich zeigt, der der Barriererippe (160) entspricht, und einen abschirmenden Abschnitt (600a), der zu dem Bereich mit Ausnahme des Bereichs, der der Bankstruktur (150) entspricht, und des Bereichs, der der Barriererippe (160) entspricht, zeigt, umfasst;  
Ätzen eines Teils des zweiten Fotolacks in dem Bereich, der der Bankstruktur (150) entspricht, und des zweiten Fotolacks in einem Bereich mit Ausnahme des Bereichs, der der Bankstruktur (150) entspricht, und des Bereichs, der der Barriererippe (160) entspricht, unter Verwendung der Maske (600); und  
Entfernen des ersten Fotolacks (150a, 150b, 150c), der in einem Bereich mit Ausnahme des Bereichs, der der Bankstruktur (150) entspricht, und des Bereichs, der der Barriererippe (160) entspricht, ausgebildet ist, unter Verwendung des verbleibenden zweiten Fotolacks als eine Maske.

13. Herstellungsverfahren für eine organische lichtemittierende Vorrichtung nach Anspruch 12, das ferner die folgenden Schritte umfasst:

nach dem Entfernen des ersten Fotolacks, der in einem Bereich mit Ausnahme des Bereichs, der der Bankstruktur (150) entspricht, und des Bereichs, der der Barriererippe (160) entspricht, ausgebildet ist, Veraschen des zweiten Fotolacks, der in dem Bereich, der der Bankstruktur (150) entspricht, ausgebildet ist, und eines Teils des zweiten Fotolacks, der in dem Bereich, der der Barriererippe (160) entspricht, ausgebildet ist; und  
Ätzen eines Teils des ersten Fotolacks, der in dem Bereich ausgebildet ist, der der Bankstruktur (150) entspricht, unter Verwendung des zweiten Fotolacks, der in dem Bereich ausgebildet ist, der der Barriererippe (160) entspricht,

als eine Maske.

14. Herstellungsverfahren für eine organische lichtemittierende Vorrichtung nach einem der Ansprüche 11 bis 13, wobei der erste Fotolack (150a) ein wärmehärtender Fotolack ist.

## Revendications

1. Dispositif d'affichage électroluminescent organique comportant :

un substrat (100) ;  
une première électrode (120) et une électrode auxiliaire (130) disposées sur le substrat (100);  
un motif de banc (150) disposé sur une partie de la première électrode (120) et sur une partie de l'électrode auxiliaire (130) et divisé en une première zone (151) ayant une forme conique inversée augmentant graduellement en largeur à partir du substrat (100) et une deuxième zone (152) sous la première zone (151) et ayant une forme conique diminuant graduellement en largeur à partir du substrat (100) ;  
une nervure de barrière (160) disposée sur l'électrode auxiliaire (130) et divisée en une troisième zone (161) ayant une forme conique inversée et une quatrième zone (162) sous la troisième zone (161) et ayant une forme conique ;  
une couche d'émission organique (131) disposée sur le substrat (100) à l'exception d'une zone de l'électrode auxiliaire (130) adjacente à la nervure de barrière (160) ; et  
une seconde électrode (122) disposée sur la couche d'émission organique (131) et en contact avec l'électrode auxiliaire (130), dans lequel une hauteur de la deuxième zone du motif de banc (150) est la même qu'une hauteur de la quatrième zone de la nervure de barrière (160), et une hauteur de la première zone du motif de banc (150) est plus petite qu'une hauteur de la troisième zone de la nervure de barrière (160).

2. Dispositif d'affichage électroluminescent organique selon la revendication 1, dans lequel une hauteur du motif de banc (150) est plus petite qu'une hauteur de la nervure de barrière (160).  
3. Dispositif d'affichage électroluminescent organique selon l'une quelconque des revendications précédentes, dans lequel une largeur maximale de la troisième zone (161) de la nervure de barrière (160) est plus grande que la largeur maximale de la quatrième zone (162).  
4. Dispositif d'affichage électroluminescent organique

selon l'une quelconque des revendications précédentes, dans lequel la couche d'émission organique inclut au moins une zone parmi une première, une deuxième et une troisième zone de non-disposition (151a, 151b, 161a, 161b, 162a, 162b), dans lequel :

la première zone de non-disposition (151a, 151b) de la couche d'émission organique (131) correspond à une partie des surfaces latérales de la première zone du motif de banc (150),  
la deuxième zone de non-disposition (161a, 161b) de la couche d'émission organique (131) correspond à des surfaces latérales de la troisième zone (161) du motif de banc (160), et  
la troisième zone de non-disposition (162a, 162b) de la couche d'émission organique (131) correspond à des surfaces latérales de la quatrième zone (162) du motif de banc (160).

5. Dispositif d'affichage électroluminescent organique selon la revendication 4, dans lequel la couche d'émission organique inclut la première zone de non-disposition et dans lequel la seconde électrode (122) est en contact avec le motif de banc (150) dans la première zone de non-disposition (151a, 151b) de la couche d'émission organique (131).
6. Dispositif d'affichage électroluminescent organique selon l'une quelconque des revendications précédentes, dans lequel la seconde électrode (122) est en contact avec l'électrode auxiliaire (130) dans la zone de l'électrode auxiliaire (130) adjacente à la nervure de barrière (160) qui est exposée par le motif de banc (150) et la nervure de barrière (160).
7. Dispositif d'affichage électroluminescent organique selon l'une quelconque des revendications précédentes, dans lequel la première électrode (120) et l'électrode auxiliaire (130) sont disposées sur une même couche, et/ou dans lequel le motif de banc (150) et la nervure de barrière (160) sont disposés sur une même couche.
8. Dispositif d'affichage électroluminescent organique selon l'une quelconque des revendications précédentes, comportant en outre une ligne auxiliaire (110) sous l'électrode auxiliaire (130) et la première électrode (120) avec un film d'aplatissement (111) entre celles-ci, la ligne auxiliaire (110) étant en contact avec l'électrode auxiliaire (130).
9. Dispositif d'affichage électroluminescent organique selon la revendication 8, dans lequel la ligne auxiliaire (110) recouvre la première électrode (120).
10. Dispositif d'affichage électroluminescent organique selon l'une quelconque des revendications précédentes, dans lequel le substrat (100) inclut une plu-

ralité de surfaces de pixels (P), chaque surface de pixel (P) incluant une pluralité de surfaces de sous-pixels (SP1, SP2, SP3, SP4), dans lequel l'électrode auxiliaire (130) est disposée en correspondance avec chacune des surfaces de sous-pixels (SP1, SP2, SP3, SP4), ou en correspondance avec chacune des surfaces de pixels (P), ou en correspondance avec deux ou plus de deux surfaces de pixels (P).

11. Procédé de fabrication d'un dispositif d'affichage électroluminescent organique selon la revendication 1, comportant les étapes consistant à :

former une première électrode (120) d'un élément électroluminescent organique (EL) et une électrode auxiliaire (130) sur un substrat (100) ;  
donner à une première résine photosensible (150a) sur une zone recouverte par une extrémité de la première électrode (120) et une extrémité de l'électrode auxiliaire (130), correspondant à une zone d'un motif de banc (150), et sur une zone centrale de l'électrode auxiliaire (130), correspondant à une zone d'une nervure de barrière (160), une forme conique inversée en projetant une lumière à travers un masque (500) sur la première résine photosensible (150a) ;  
donner à une zone inférieure de la première résine photosensible (150a) une forme conique en réalisant un traitement thermique sur la première résine photosensible (150a) ayant la forme conique inversée ;  
retirer la première résine photosensible (150a, 150b, 150c) formée dans une zone excluant la zone correspondant au motif de banc (150) et la zone correspondant à la nervure de barrière (160) ; et  
former une couche d'émission organique (131) et une seconde électrode (122) sur le substrat (100).

12. Procédé de fabrication d'un dispositif d'affichage électroluminescent organique selon la revendication 11, dans lequel le retrait de la première résine photosensible (150a) inclut les étapes consistant à :

former une seconde résine photosensible sur le substrat (100) ;  
disposer un masque (600) incluant une portion semi-transmettrice (600c) dirigée vers la zone correspondant au motif de banc (150), une portion transmettrice (600d) dirigée vers la zone correspondant à la nervure de barrière (160), et une portion de protection (600a) dirigée vers la zone excluant la zone correspondant au motif de banc (150) et la zone correspondant à la nervure de barrière (160) ;

former par gravure une partie de la seconde résine photosensible dans la zone correspondant au motif de banc (150) et la seconde résine photosensible dans une zone excluant la zone correspondant au motif de banc (150) et la zone correspondant à la nervure de barrière (160), en utilisant le masque (600) ; et  
 retirer la première résine photosensible (150a, 150b, 150c) formée dans une zone excluant la zone correspondant au motif de banc (150) et la zone correspondant à la nervure de barrière (160), en utilisant la seconde résine photosensible restante comme un masque.

13. Procédé de fabrication d'un dispositif d'affichage électroluminescent organique selon la revendication 12, comportant en outre les étapes consistant à :

après le retrait de la première résine photosensible formée dans une zone excluant la zone correspondant au motif de banc (150) et la zone correspondant à la nervure de barrière (160), calciner la seconde résine photosensible formée dans la zone correspondant au motif de banc (150) et une partie de la seconde résine photosensible formée dans la zone correspondant à la nervure de barrière (160) ; et  
 former par gravure une partie de la première résine photosensible formée dans la zone correspondant au motif de banc (150), en utilisant la seconde résine photosensible formée dans la zone correspondant à la nervure de barrière (160) comme un masque.

14. Procédé de fabrication d'un dispositif d'affichage électroluminescent organique selon l'une quelconque des revendications 11 à 13, dans lequel la première résine photosensible (150a) est une résine photosensible thermodurcissable.

40

45

50

55




FIG.1




FIG. 2

*FIG. 3*







FIG. 4




*FIG.5*




*FIG. 6A*



*FIG. 6B*



*FIG. 6C*



*FIG. 7*







FIG. 8




*FIG. 9*



**FIG. 10**



**FIG. 11**



**REFERENCES CITED IN THE DESCRIPTION**

*This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.*

**Patent documents cited in the description**

- KR 1020150107497 [0001]
- EP 2827371 A1 [0010]
- CN 103137891 A [0011]
- EP 2503851 A1 [0012]
- US 2015097171 A1 [0013]
- KR 20160079523 A [0014]

|                |                                                                        |         |            |
|----------------|------------------------------------------------------------------------|---------|------------|
| 专利名称(译)        | 有机发光显示装置                                                               |         |            |
| 公开(公告)号        | <a href="#">EP3125294B1</a>                                            | 公开(公告)日 | 2020-04-22 |
| 申请号            | EP2016181858                                                           | 申请日     | 2016-07-29 |
| [标]申请(专利权)人(译) | 乐金显示有限公司                                                               |         |            |
| 申请(专利权)人(译)    | LG DISPLAY CO. , LTD.                                                  |         |            |
| 当前申请(专利权)人(译)  | LG DISPLAY CO. , LTD.                                                  |         |            |
| [标]发明人         | SHIM SUNGBIN<br>DO EUI DOO<br>KIM SUHYEON                              |         |            |
| 发明人            | SHIM, SUNGBIN<br>DO, EUI-DOO<br>KIM, SUHYEON                           |         |            |
| IPC分类号         | H01L27/32 H01L51/52                                                    |         |            |
| CPC分类号         | H01L27/3246 H01L27/3279 H01L51/5228 H01L51/56 H01L27/3213 H01L2227/323 |         |            |
| 优先权            | 1020150107497 2015-07-29 KR                                            |         |            |
| 其他公开文献         | EP3125294A1                                                            |         |            |
| 外部链接           | <a href="#">Espacenet</a>                                              |         |            |

## 摘要(译)

本示例性实施例涉及一种有机发光显示装置及其制造方法。有机发光显示装置包括有机发光元件的第一电极（120），与第一电极位于同一层上的辅助电极（130），位于第一电极上的堤坝图案（150）以及一部分辅助电极的上表面的分隔成第一区域（151）和第二区域（152）的阻挡肋（160）形成在同一层上并且与堤坝图案相同的材料形成并且分隔为第三区域（161）和第四区域（162），设置在基板上并包括第一至第三非沉积区域（151a, 151b, 161a, 161b, 162a, 162b）的有机发射层和第二电极（122）设置在基板上。根据本示例性实施例，可以抑制由阴极的电阻引起的电压降。




FIG. 1