

(19)



(11)

EP 3 300 068 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
18.09.2019 Bulletin 2019/38

(51) Int Cl.:
G09G 3/3233^(2016.01)

(21) Application number: **17192771.8**

(22) Date of filing: **22.09.2017**

(54) ORGANIC LIGHT EMITTING DIODE DISPLAY DEVICE

ANZEIGEVORRICHTUNG MIT ORGANISCHEN LEUCHTDIODEN

AFFICHEUR À DIODES ÉLECTROLUMINESCENTES ORGANIQUES

(84) Designated Contracting States:
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR**

(30) Priority: **22.09.2016 KR 20160121537**

(43) Date of publication of application:
28.03.2018 Bulletin 2018/13

(73) Proprietor: **Samsung Display Co., Ltd.
Gyeonggi-do 17113 (KR)**

(72) Inventors:
• **YANG, Sumin
Gyeonggi-do 16868 (KR)**

• **PARK, Jinwoo
Seoul 04594 (KR)**
• **BAE, Minseok
Gyeonggi-do 18480 (KR)**

(74) Representative: **Mouteney, Simon James
Marks & Clerk LLP
15 Fetter Lane
London EC4A 1BW (GB)**

(56) References cited:
**KR-A- 20170 021 678 US-A1- 2007 109 284
US-A1- 2011 043 551**

EP 3 300 068 B1

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

TECHNICAL FIELD

[0001] Embodiments of the present invention relate to a display device, and more particularly, to an organic light emitting diode ("OLED") display device and a method of driving the OLED display device.

DISCUSSION OF RELATED ART

[0002] Display devices generally include a plurality of pixels provided in an area defined by a black matrix and/or a pixel defining layer. Examples of display devices may include a liquid crystal display ("LCD") device, a plasma display panel ("PDP") device, and an organic light emitting diode ("OLED") display device.

[0003] In general, an OLED display device includes an insulating substrate, a thin film transistor ("TFT") disposed on the insulating substrate, a pixel electrode connected to the TFT, a partition wall dividing the pixel electrode, an organic layer disposed on the pixel electrode between the partition walls, and a common electrode disposed on the partition wall and the organic layer.

[0004] In such an example, the TFT controls light emission of the organic layer for each pixel area. A pixel electrode is disposed in each pixel area, and each pixel electrode is electrically isolated from an adjacent pixel electrode so that each pixel electrode may be independently driven. In addition, the partition walls that divide the pixel areas are formed to be higher than the pixel electrodes. The partition walls serve to divide pixel areas while substantially preventing a short circuit between the pixel electrodes. An organic layer including a hole injection layer and an organic light emitting layer is formed on the pixel electrode between the partition walls. An OLED having such a structure controls light emitted from the organic light emitting layer to display an image.

[0005] However, some of the light generated in the organic light emitting layer does not contribute to the display of the image. The lost light propagates inside the pixels and the peripheral pixels, thereby contributing to a deterioration of a TFT in the pixel.

[0006] US 2007/0109284 A1 discloses a display device which can reduce the difference in deterioration of a display element in each pixel and suppress variations in light emission of a display element in a pixel. For that purpose, a gray scale of a display pattern is changed to prevent the difference in deterioration of display element in pixels from increasing. Alternatively, a specific display pattern is prevented from being fixedly displayed in a specific region. Further alternatively, a pixel lagging behind in deterioration is deteriorated so that the accumulated lighting time of pixels is equal to each other.

[0007] US 2011/0043551 A1 discloses an image processing apparatus that performs display control of an image displayed on a display unit, and includes a first control circuit for controlling image data of a frame in

question or a display timing control signal corresponding to the image data so as to display each pixel forming the image with different brightness at given intervals, and a second control circuit for controlling the image data or the display timing control signal by different control from that by the first control circuit so as to display each pixel forming the image with different brightness at given intervals, wherein the first control circuit and the second control circuit control image data of an identical frame or a display timing control signal corresponding to the image data.

SUMMARY

[0008] An organic light emitting diode (OLED) display device according to the invention has the features of Claim 1. Optional features of this aspect of the invention are set-out in Claims 2 to 9.

[0009] A method of compensating for light-induced deterioration of an organic light emitting diode (OLED) display device according to the invention has the features of Claim 10. Optional features of this aspect of the invention are set-out in Claims 11 to 13.

BRIEF DESCRIPTION OF THE DRAWINGS

[0010] A more complete appreciation of the present invention and many of the attendant aspects thereof will be made more apparent by describing in detail embodiments thereof with reference to the accompanying drawings, wherein:

FIG. 1 is an equivalent circuit diagram illustrating one pixel of an active matrix type organic light emitting diode ("AMOLED") display device according to embodiments of the present invention;

FIG. 2 is a circuit diagram illustrating a comparative display device;

FIG. 3 is a light-induced deterioration experimental image of a comparative OLED display panel;

FIG. 4 is a result data image after displaying the experimental image of FIG. 3;

FIG. 5 is a graph illustrating a voltage V_{th} from the experimental result of FIG. 3;

FIG. 6 is an image illustrating light emission of a pixel according to the experiment of FIG. 4;

FIG. 7 is a configuration view illustrating an OLED display device according to an embodiment of the present invention;

FIG. 8 is an internal configuration view illustrating a light-induced deterioration compensation unit according to an embodiment of the present invention;

FIG. 9 is a flowchart illustrating an operation of a light-induced deterioration analysis unit according to an embodiment of the present invention;

FIG. 10A is a light-induced deterioration predictive image signal according to an embodiment of the present invention;

FIG. 10B is a light-induced deterioration gray level compensating value according to an embodiment of the present invention;

FIG. 10C is light-induced deterioration compensated image data according to an embodiment of the present invention;

FIG. 11A is a light-induced deterioration predictive image signal according to an embodiment of the present invention;

FIG. 11B is a light-induced deterioration gray level compensating value according to an embodiment of the present invention;

FIG. 11C is a light-induced deterioration compensated image data according to an embodiment of the present invention;

FIG. 12 is a flowchart illustrating a method of preventing light-induced deterioration according to an embodiment of the present invention;

FIG. 13A illustrates a first light-induced deterioration gray level compensating value according to an embodiment of the present invention;

FIG. 13B illustrates a second light-induced deterioration gray level compensating value according to an embodiment of the present invention;

FIG. 14 is a diagram illustrating a light-induced deterioration compensation area of an OLED display panel according to an embodiment of the present invention;

FIG. 15 is an enlarged view illustrating a light-induced deterioration predictive image signal of an area displaying a logo in FIG. 14;

FIG. 16 is a light-induced deterioration compensated image data employing a light-induced deterioration gray level compensating value according to an embodiment of the present invention;

FIG. 17 is a light-induced deterioration compensated image data employing a light-induced deterioration gray level compensating value according to an embodiment of the present invention;

FIG. 18 is a diagram illustrating a deterioration compensation unit according to an embodiment of the present invention; and

FIG. 19 is an image of an OLED display device according to an embodiment of the present invention.

DETAILED DESCRIPTION

[0011] In describing embodiments of the present invention, specific terminology is employed for sake of clarity. However, the present invention is not intended to be limited to the specific terminology so selected, and it is to be understood that each specific element includes all technical equivalents which operate in a similar manner.

[0012] In the drawings, the lengths and thicknesses of the illustrated elements may be exaggerated for clarity and ease of description thereof. When a layer, area, or other element is referred to as being "on" another layer, area, or other element, it may be directly on the other

layer, area, or other element, or intervening layers, areas, or other elements may be present therebetween.

[0013] Like reference numerals may refer to like elements throughout the specification.

5 [0014] FIG. 1 is an equivalent circuit diagram illustrating one pixel of an active matrix type organic light emitting diode ("AMOLED") display device in accordance with an embodiment of the present invention.

10 [0015] Referring to FIG. 1, a pixel of the OLED display device includes a gate line G and a data line D, and further includes a switching transistor N1, a capacitor C, a driving transistor N2, and an organic light emitting diode ("OLED") disposed between the gate line G and the data line D. In such an exemplary embodiment, each of the
15 switching transistor N1 and the driving transistor N2 may be a thin film transistor ("TFT") including amorphous silicon (a-Si: H) or a TFT including an oxide based on a metal such as indium (In), gallium (Ga), zinc (Zn), tin (Sn) and/or titanium (Ti).

20 [0016] A gate electrode of the switching transistor N1 is connected to the gate line G and a source electrode of the switching transistor N1 is connected to the data line D. One side of the capacitor C is connected to a drain electrode of the switching transistor N1 and another side
25 of the capacitor C is grounded (GND) like a source electrode of the driving transistor N2.

[0017] A drain electrode of the driving transistor N2 is connected to a cathode electrode of the OLED to which a driving voltage VDD is applied. A gate electrode of the driving transistor N2 is connected to the drain electrode
30 of the switching transistor N1. The source electrode of the driving transistor N2 is grounded (GND).

[0018] In addition, the switching transistor N1 is turned on in response to a gate signal applied from the gate line G to allow a current to flow between the source electrode and the drain electrode of the switching transistor N1. A data signal voltage, applied from the data line D during a turn-on period of the switching transistor N1, is applied
35 to the gate electrode of the driving transistor N2 and the capacitor C via the source electrode and the drain electrode of the switching transistor N1.

[0019] The driving transistor N2 controls a current flowing through the OLED according to the data signal voltage applied to the gate electrode of the driving transistor N2.
40 Further, the capacitor C stores the data signal voltage and then maintains the data signal voltage at a constant level for one frame period of the OLED display device.

[0020] FIG. 2 is a circuit diagram illustrating a comparative display device.

50 [0021] Referring to FIG. 2, the OLED display device 1 may include an OLED display panel 10, a gate driver 20, a data driver 30, and a timing controller 40.

[0022] A plurality of gate lines G1 to Gn and a plurality of data lines D1 to Dm are formed in the OLED display panel. The gate lines G1 to Gn and the data lines D1 to Dm intersect one another and define pixel areas.
55

[0023] In addition, as illustrated in FIG. 1, the switching transistor N1, the driving transistor N2, the capacitor C

and the OLED may be disposed in each pixel area P.

[0024] A red pixel R, a green pixel G and a blue pixel B may be disposed in the pixel area of the OLED display panel 10. The pixels may be arranged in the form of a checkerboard or a stripe pattern.

[0025] The gate driver 20 may generate a gate signal based on a gate control signal CNT1 applied from the timing controller 40 and may sequentially apply the gate signal to the plurality of gate lines G1 to Gn of the OLED display panel 10.

[0026] The data driver 30 may generate a data signal voltage based on a data control signal CNT2 and an image data R', G' and B' applied from the timing controller 40 and may apply the data signal voltage to the plurality of data lines D1 to Dm of the OLED display panel 10.

[0027] The timing controller 40 may generate the gate control signal CNT1 and the data control signal CNT2 for controlling the gate driver 20 and the data driver 30, respectively, based on a control signal CNT applied thereto, e.g., a vertical synchronization signal, a horizontal synchronization signal, a clock signal and a data enable signal. The gate control signal CNT1 and the data control signal CNT2 may be output to the gate driver 20 and the data driver 30, respectively.

[0028] FIG. 3 is a light-induced deterioration experimental image of a comparative OLED display panel.

[0029] A screen area of the OLED display panel 10 illustrated in FIG. 3 corresponds to a horizontal line 0 to a horizontal line 600 in direction H, and corresponds to a vertical line 600 to a vertical line 1600 in direction V. An experimental image includes two red box images in an upper portion of the screen and two green box images located adjacent to and below the two red box images, respectively. In the screen area, a peripheral area in which the red box image and the green box image are not displayed is located within a non-light emitting state.

[0030] In an area displaying the red box image, a red pixel (hereinafter, "a pixel R") emits light of a gray level 255, e.g. a maximum brightness. A green pixel (hereinafter, "a pixel G") and a blue pixel (hereinafter, "a pixel B") do not emit light, and have a gray level 0, e.g. a minimum brightness. In an area displaying the green box image, a pixel G emits light of a gray level 255, and a pixel R and a pixel B do not emit light, having a gray level 0.

[0031] According to the experiment, a turn-on threshold voltage (hereinafter, "a voltage Vth") of the driving transistor N2 in the pixel R is measured in an initial state (time = 0 hr) before the experimental image is displayed on the OLED display panel 10. Then, after the experimental image is displayed continuously for 5 hours (time = 5 hr), the voltage Vth of the pixel R is measured. In addition, after the experimental image is displayed continuously for 144 hours (time = 144 hr), the voltage Vth of the pixel R is measured. During the experiment, the experimental image is input to the OLED display panel 10 as a fixed image without variation (e.g. a still image).

[0032] FIG. 4 illustrates a resultant data image after

displaying the experimental image of FIG. 3.

[0033] FIG. 4 illustrates the result of measuring a voltage Vth of a pixel R after the experimental image of FIG. 3 is continuously displayed for 5 hours (time = 5 hr).

[0034] Referring to FIG. 4, an upper portion of the screen in which the red box image is displayed for 5 hours is represented in light gray, and a voltage Vth of a pixel R has a value of about -0.3 V. On the other hand, a lower portion of the screen in which the green box image is displayed is represented in dark gray, and a voltage Vth of a pixel R has a value of about -0.4 V or less. A peripheral area around the red box image and the green box image in which light has not been emitted for 5 hours is represented in gray, and a voltage Vth of a pixel R in the peripheral area has a value in a range of about -0.25 V to about -0.35 V. The voltage Vth of the pixel R in the peripheral area is relatively low in pixels located closer to the red box image and the green box image, and relatively high in pixels spaced farther from the red box image and the green box image.

[0035] FIG. 5 is a graph illustrating a voltage Vth from the experimental result of FIG. 3.

[0036] The graph in FIG. 5 illustrates a voltage Vth of a pixel R located at line A-A' illustrated in FIG. 3. The horizontal axis of the graph represents a position of the pixel R in the OLED display panel, and the vertical axis represents a voltage Vth of the pixel R.

[0037] The graph at time = 0 hr illustrates the voltage Vth of the pixel R measured before displaying the experimental image. The graph at time = 5 hr illustrates the voltage Vth of the pixel R after continuously displaying the experimental image for 5 hours (time = 5 hr), and the graph at time = 144 hr illustrates the voltage Vth of the pixel R after continuously displaying the experimental image for 144 hours (time = 144 hr).

[0038] Referring to FIG. 5, the graph at time = 0 hr illustrates that the voltage Vth is kept at a substantially constant level within a range of about -0.3 V to about -0.33 V in the pixel R from the horizontal line 0 to the horizontal line 600.

[0039] In the graph at time = 5 hr, the voltage Vth of the pixel R varies depending on the position. In an area from a horizontal line 61 to a horizontal line 280 in which the red box image is displayed, the pixel R maintains the voltage Vth in a range of about -0.3 V to about -0.32 V, while in an area from a horizontal line 291 to a horizontal line 510 in which the green box image is displayed, the voltage Vth of the pixel R drops to about -0.48 V. The voltage Vth of the pixel R varies by about 0.16 V depending on the difference in the experimental image. The difference in the voltage Vth of the pixel R may further increase as the continuous light emission time of the experimental image increases.

[0040] The graph at time = 144 hr illustrates the voltage Vth of the pixel R ranging from about -0.2678 V to -0.2968 V in an area from the horizontal line 61 to the horizontal line 280. In an area where the pixel R emits light to display the red box image, the voltage Vth of the pixel R does

not experience a great change with the lapse of the light emission time. In an area from the horizontal line 291 to the horizontal line 510 in which the green box image is displayed, the voltage V_{th} of the pixel R is in a range of about -0.8333 V to about -0.787 V.

[0041] In an area where a pixel R does not emit light while a pixel adjacent to the pixel R emits light, a voltage V_{th} of the pixel R changes largely in accordance with a light emission time. When measured after displaying the experimental image for 144 hours, a voltage V_{th} of a pixel R in a reference line 800 varies by about 0.5 V depending on whether the pixel R emits light.

[0042] The graph of FIG. 5 shows that the voltage V_{th} of the pixel R is affected by whether the pixel R is turned on and by whether the adjacent pixel (e.g., the pixel G or the pixel B) is turned on and a light emission time of the adjacent pixel. In particular, a voltage V_{th} of one pixel that does not emit light may be significantly lowered in the case where another pixel in a peripheral area emits light for a long period of time.

[0043] FIG. 6 is an image illustrating an OLED display panel according to the experiment of FIG. 4.

[0044] FIG. 6 is an image pictured when a pixel R of an OLED display panel emits light with a data signal voltage of a gray level 31 (31G) after the red pixel image and the green box image are continuously displayed for 5 hours as in FIG. 4.

[0045] Referring to FIGS. 5 and 6, a voltage V_{th} of a pixel R in an area where the red box image is displayed is about -0.32 V. A voltage V_{th} of a pixel R in an area where the green box image is displayed is about -0.48 V, which is lower than the voltage V_{th} of the pixel R in the area where the red box image is displayed. A driving voltage of the pixel R in the area where the green box image is displayed is higher than a driving voltage of the pixel R in the area where the red box image is displayed by about 0.16 V due to the effect of light-induced deterioration.

[0046] When a data signal voltage of a gray level 31 (31G) is applied to a pixel R, a driving voltage applied to a light emitting layer of the pixel R is determined based on a difference between the data signal voltage and a voltage V_{th} of a driving transistor in the pixel R.

[0047] As the voltage V_{th} of the pixel is lowered, the driving voltage of the pixel increases, and thus light may be emitted with a higher luminance than an applied gray value. Due to a deviation in the voltage V_{th} of the pixel arising from light-induced deterioration, the OLED display panel may exhibit uneven luminance.

[0048] Referring to FIG. 6, it is identified that there is a pixel emitting light with a relatively high luminance in a part of the periphery of an area in which the red box image is displayed. In this periphery of the area in which the red box image is displayed, the voltage V_{th} is lowered as a result of light emitted from the pixel R displaying the red box image.

[0049] Based on the experimental result of FIGS. 4, 5 and 6, when the green box image is displayed on the

OLED display panel, a light output from a pixel G deteriorates a TFT of a pixel R, and the light-induced deterioration phenomenon in which the voltage V_{th} of the deteriorated TFT has a tendency toward a more negative voltage occurs in the pixel R. The light-induced deterioration phenomenon occurs to a greater extent in the case where an oxide semiconductor layer is applied to a TFT of the pixel. The light-induced deterioration of the TFT may occur due to the material properties of the oxide semiconductor layer.

[0050] Examples of a material forming the oxide semiconductor layer may include an oxide based on a metal such as zinc (Zn), indium (In), gallium (Ga), tin (Sn) and titanium (Ti), or a compound of a metal, such as zinc (Zn), indium (In), gallium (Ga), tin (Sn) and titanium (Ti), and an oxide thereof. For example, the oxide semiconductor material may include at least one selected from the group consisting of: zinc oxide (ZnO), zinc-tin oxide (ZTO), zinc-indium oxide (ZIO), indium oxide (InO), titanium oxide (TiO), indium-gallium-zinc oxide (IGZO) and indium-zinc-tin oxide (IZTO).

[0051] FIG. 7 is a configuration view illustrating an OLED display device 1 according to an embodiment of the present invention.

[0052] Referring to FIG. 7, the timing controller 40 of the OLED display device 1, according to an embodiment of the present invention, may further include a light-induced deterioration compensation unit 50.

[0053] The configurations of the OLED display panel 10, the gate driver 20, and the data driver 30 may be the same as or similar to those corresponding elements illustrated in FIG. 2.

[0054] The timing controller 40 receives the control signal CNT and the image signal R, G and B provided thereto from an external source, determines an image signal that may undergo light-induced deterioration as a light-induced deterioration predictive image signal, and outputs a light-induced deterioration compensated image data R', G' and B' to the data driver 30.

[0055] The data driver 30 may generate a data signal voltage using the data control signal CNT2 and the light-induced deterioration compensated image data R', G' and B' provided thereto from the timing controller 40, and apply the data signal voltage to the plurality of data lines D1 to Dm of the OLED display panel 10.

[0056] FIG. 8 is an internal configuration view illustrating a light-induced deterioration compensation unit according to an embodiment of the present invention.

[0057] Referring to FIG. 8, the light-induced deterioration compensation unit 50 at the timing controller 40 receives the image signal R, G and B input to the timing controller 40, predicts possible light-induced deterioration that may occur in the OLED display panel 10, and outputs, to the data driver 30, the light-induced deterioration compensated image data R', G' and B' compensated not to cause light-induced deterioration.

[0058] The light-induced deterioration compensation unit 50 may include a light-induced deterioration analysis

unit 51, a gray level compensating value calculation unit 52, a gray level compensating value lookup table 53 and a light-induced deterioration compensated image data generation unit 54.

[0059] The light-induced deterioration analysis unit 51 may analyze the input image signal R, G and B to determine an image signal that is expected to undergo light-induced deterioration, and set a light-induced deterioration predictive image signal. To determine the light-induced deterioration, an image signal driving a same pixel with a gray level above a reference gray level value for a plurality of frames is detected, a black image signal driving a pixel located in the periphery of said same pixel is detected, and thereafter the corresponding image signals are set as a light-induced deterioration predictive image signal. The light-induced deterioration analysis unit 51 may determine that the light-induced deterioration may occur when the black image signal continues for 10 frames or more.

[0060] The light-induced deterioration predictive image signal may include both an image signal displaying a substantially same still image over a plurality of frames and an image signal displaying a black gray level (e.g. gray level 0) in the periphery of the still image. In such an exemplary embodiment, the black gray level may include a gray level having a gray level value of 0 and a gray level having a value lower than a light-induced deterioration compensating gray level value. For example, the black gray level may have a gray level value in a range of a gray level 0 to a gray level 4, and the light-induced deterioration compensating gray level value may be in a range of 2 to 8.

[0061] In general, when viewing a video signal, such as a television broadcast, on the OLED display device 1, a logo of a broadcasting company is displayed as a still image emitting light for a long period of time at a fixed position. Accordingly, light-induced deterioration might occur in non-light emitting pixels located in the periphery of the logo. The light-induced deterioration analysis unit 51 may analyze input image signals in adjacent pixels on the basis of a plurality of frames to set a light-induced deterioration predictive image signal.

[0062] FIG. 9 is a flowchart illustrating an operation of the light-induced deterioration analysis unit 51 according to an embodiment of the present invention.

[0063] First, the light-induced deterioration analysis unit 51 receives the image signal R, G and B from an external source (S110).

[0064] The light-induced deterioration analysis unit 51 analyzes the input image signal R, G and B of a plurality of successive frames to detect a still image that does not move in a plurality of frames (S120). In general, an image signal of a non-moving image is present at a substantially same position and has a substantially constant value over a plurality of frame signals (the number of which may be predetermined). Accordingly, the still image may be detected by subtracting image signals of successive frames. A pixel or an area of which a result of subtraction

operation between two frames is 0 may mean that the position of the image is fixed between at least two frames. In the case where the two frames are extended to frames spanning several seconds, a still image displayed on the screen may be detected. As described above, the still image may include an image such as a logo of a broadcasting company or a time display, and when the display device is used as a monitor, a partial area of a computer program may correspond to the still image (such as, for example, a menu bar or other stationary user interface elements).

[0065] The light-induced deterioration analysis unit 51 analyzes the image signal of the frame to extract a still image, and analyzes a black image signal applied to a pixel adjacent to the pixel in which the still image is displayed (S130). The pixel receiving the black image signal does not emit light or emits light with a significantly low gray level and thus may experience light-induced deterioration by an output light of the still image of an adjacent pixel. Although there is a pixel in which a still image is displayed, in the case where a pixel adjacent thereto does not receive a black image signal, it is determined that the possibility of light-induced deterioration is low, and the process returns to a step of analyzing an image signal again.

[0066] In the case where a black image signal is detected in a pixel adjacent to a pixel in which a still image is displayed, the light-induced deterioration analysis unit 51 counts a display time of the image signal that is likely to cause deterioration (S140). In this step, both a display time of the still image and duration of a non-light emitting state of an adjacent pixel are taken into account and accumulated.

[0067] The light-induced deterioration analysis unit 51 compares the display time of the light-induced deterioration predicted image with a preset deterioration reference time (S150). Since the condition to cause light-induced deterioration varies depending on the structure of the OLED display panel and the characteristics of a pixel TFT, the deterioration reference time is not particularly fixed and may be set in a range from several seconds to several tens of minutes, as determined by the structure of the OLED display panel and the characteristics of the pixel TFTs).

[0068] In the case where the display time of the light-induced deterioration predicted image exceeds the deterioration reference time, the light-induced deterioration analysis unit 51 sets the corresponding image signal as a light-induced deterioration predictive image signal (S160). The deterioration reference time may be determined based on the characteristics of the OLED display panel.

[0069] The light-induced deterioration analysis unit 51 transmits the determined light-induced deterioration predictive image signal to the gray level compensating value calculation unit 52. The gray level compensating value calculation unit 52 calculates a light-induced deterioration gray level compensating value to compensate for a

black image signal which is likely to cause light-induced deterioration with an image signal of a relatively low gray level.

[0070] FIG. 10A is a light-induced predictive image signal according to an embodiment of the present invention, FIG. 10B is a light-induced deterioration gray level compensating value according to an embodiment of the present invention, and FIG. 10C is light-induced deterioration compensated image data according to an embodiment of the present invention.

[0071] FIG. 10A illustrates a light-induced deterioration predictive image signal of a 9 X 9 pixel area including pixels R, pixels G and pixels B in the area of the green box image in the experimental image of FIG. 3. In the OLED display panel applied with a data signal voltage corresponding to the light-induced deterioration predictive image signal of FIG. 10A, in the area of the green box image, the pixel G displays a gray level of 255 (e.g. a substantially maximum luminance), and the pixel R and the pixel B do not emit light (e.g. a substantially minimum luminance). In TFTs of the pixel R and the pixel B, light-induced deterioration in which the voltage V_{th} of the pixel R and the pixel B is lowered due to a light output from the adjacent pixel G may occur.

[0072] The light-induced deterioration analysis unit 51 detects the light-induced deterioration predictive image signal illustrated in FIG. 10A from an input image signal and transmits the light-induced deterioration predictive image signal to the gray level compensating value calculation unit 52. The light-induced deterioration predictive image signal is an image signal having display gray level values corresponding to pixels in a predetermined area. Although described herein with reference to a gray level table, the light-induced deterioration predictive image signal may be configured differently from the examples of the present invention described above.

[0073] The gray level compensating value may be a gray level having a relatively low gray level value ranging from 2 to 8 that may turn on an adjacent pixel displaying an otherwise black gray level predicted to cause light-induced deterioration. In an exemplary embodiment of the present invention, an adjacent pixel of one pixel refers to a neighboring pixel sharing a boundary with the one pixel and a peripheral pixel of one pixel refers to a pixel in an area affected by a light output from said one pixel (e.g. a pixel that is close to but not necessarily adjacent to the one pixel).

[0074] FIG. 10B is a light-induced deterioration gray level compensating value according to an embodiment of the present invention. When a light-induced deterioration predictive image signal of FIG. 10A is displayed on the OLED display panel for a relatively long period of time, the voltage V_{th} of the driving TFTs of the pixel R and the pixel B may be lowered by the light-induced deterioration.

[0075] The gray level compensating value calculation unit 52 assigns a gray level 0 to an image signal of the pixel G of which an input image gray level corresponds

to a still image, and assigns a light-induced deterioration compensating value of a gray level 8 to image signals of the pixel R and the pixel B of which an input image gray level corresponds to a black image signal.

[0076] In an embodiment of the present invention, although a gray level 8 is selected as a light-induced deterioration compensating value by way of example, the light-induced deterioration gray level compensating value may have a different value that is determined according to a gray level value of a light emitting pixel and a distance with respect to the light emitting pixel.

[0077] The light-induced deterioration gray level compensating value selected based on the gray level value of the light emitting pixel and the distance with respect to the light emitting pixel, as variables, may be separately stored in a gray level compensating value lookup table 53. The stored light-induced deterioration gray level compensating value may be referred to by the gray level compensating value calculation unit 52. The gray level compensating value calculation unit 52 transmits the selected light-induced deterioration gray level compensating value to the light-induced deterioration compensated image data generation unit 54.

[0078] FIG. 10C illustrates a light-induced deterioration compensated image data compensated by the light-induced deterioration compensated image data generation unit 54. The light-induced deterioration compensated image data generation unit 54 compensates the input image signal R, G and B with the light-induced deterioration gray level compensating value transmitted from the gray level compensating value calculation unit 52 to generate the light-induced deterioration compensated image data R', G' and B'. Referring to the light-induced deterioration compensated image data of FIG. 10C, the gray level of pixel R maintains a gray level value of 255 of the input signal, and the gray levels of the pixel G and the pixel B are set as a light-induced deterioration gray level compensating value of 8 generated by the gray level compensating value calculation unit 52.

[0079] FIG. 11A is a light-induced deterioration predictive image signal according to an embodiment of the present invention, FIG. 11B is a light-induced deterioration gray level compensating value according to an embodiment of the present invention, and FIG. 11C is a light-induced deterioration compensated image data according to an embodiment of the present invention.

[0080] Referring to FIG. 11A, as for the light-induced deterioration predictive image signal, the gray level of the pixel G is a gray level 128, and the gray levels of the pixel R and the pixel B adjacent to the pixel G has a gray level 0. The pixel G has a gray level 128, which is an intermediate value among a set of gray levels ranging from 0 to 255, and compared to the case of displaying a gray level 255, a maximum gray level, the pixel G displaying a gray level 128 may induce less light-induced deterioration in a non-light emitting pixel.

[0081] Referring to the light-induced deterioration gray level compensating value in FIG. 11B, the gray level com-

compensating value calculation unit 52 assigns a gray level 0 to the gray level of the pixel G which is a light emitting pixel, and assigns a gray level 4 as the light-induced deterioration gray level compensating value to the gray levels of the pixel R and the pixel B which are non-light emitting pixels. The gray level compensating value calculation unit 52 may select a gray level 4, lower than a gray level 8, as the light-induced deterioration gray level compensating value, considering that the gray level value of the adjacent pixel G is a gray level 128.

[0082] FIG. 11C is a light-induced deterioration compensated image data generated by the light-induced deterioration compensated image data generation unit 54. The light-induced deterioration compensated image data generation unit 54 compensates the light-induced deterioration predictive image signal illustrated in FIG. 11A with the light-induced deterioration gray level compensating value applied from the gray level compensating value calculation unit 52 illustrated in FIG. 11B to generate the light-induced deterioration compensated image data.

[0083] Referring to FIG. 11C, as for the case of the light-induced deterioration compensated image data, the gray level of the pixel G maintains an input gray level value and the pixel R and the pixel B, which are vulnerable to light-induced deterioration, with the light-induced deterioration gray level compensating value of a gray level 4 generated from the gray level compensating value calculation unit 52. The pixel R and the pixel B applied with the light-induced deterioration compensated image data may emit light in a gray level 4, thereby rendering those pixels less influenced by the light-induced deterioration that may occur by the light output from the pixel G.

[0084] FIG. 12 is a flowchart illustrating a method of compensating for light-induced deterioration according to an embodiment of the present invention.

[0085] Referring to FIG. 12, a light-induced deterioration compensated image data generation unit 54 may selectively output a light-induced deterioration compensated image data and a light-induced deterioration uncompensated image data so that a contrast of the OLED display device is not degraded by the light-induced deterioration compensation.

[0086] In addition, the light-induced deterioration compensated image data generation unit 54 may alternately output the light-induced deterioration compensated image data and the light-induced deterioration uncompensated image data at periodic intervals.

[0087] The light-induced deterioration analysis unit 51 receives an image signal to be displayed on the OLED display panel (S210).

[0088] The input image signal is analyzed such that a light-induced deterioration predictive image signal is set (S220). The set light-induced deterioration predictive image signal is transmitted to the gray level compensating value calculation unit 52.

[0089] The gray level compensating value calculation unit 52 sets a light-induced deterioration gray level com-

pensating value of the image signal so that non-light emitting pixels that would otherwise be susceptible to light-induced deterioration may be compensated for and may thereby emit light (S230).

[0090] The light-induced deterioration compensated image data generation unit 54 compensates the input light-induced deterioration predictive image signal with the light-induced deterioration gray level compensating value and outputs the light-induced deterioration compensated image data (S240).

[0091] The light-induced deterioration compensated image data generation unit 54 counts light-induced deterioration compensating time during which the light-induced deterioration compensated image data is output (S250).

[0092] The light-induced deterioration compensated image data generation unit 54 compares the light-induced deterioration compensating time with a preset reference time (S260). The light-induced deterioration compensated image data generation unit 54 outputs the light-induced deterioration compensated image data until the light-induced deterioration compensating time exceeds the preset reference time.

[0093] When the light-induced deterioration compensating time exceeds the preset reference time, the light-induced deterioration compensated image data generation unit 54 stops outputting the light-induced deterioration compensated image data, and outputs the light-induced deterioration uncompensated image data, generated from the input image signal, of which light-induced deterioration is not compensated (S270).

[0094] The light-induced deterioration compensated image data generation unit 54 counts light-induced deterioration time while outputting the light-induced deterioration uncompensated image data (S280).

[0095] The light-induced deterioration compensated image data generation unit 54 compares the light-induced deterioration time with a preset reference deterioration time (S290). When the light-induced deterioration time does not exceed the preset reference deterioration time, the light-induced deterioration compensated image data generation unit 54 outputs the light-induced deterioration uncompensated image data.

[0096] When the light-induced deterioration time exceeds the reference deterioration time, the light-induced deterioration compensated image data generation unit 54 moves to a step of outputting a light-induced deterioration compensated image data reflecting the light-induced deterioration gray level compensating value.

[0097] As such, as the light-induced deterioration compensated image data generation unit 54 alternately displays the light-induced deterioration compensated image data and the light-induced deterioration uncompensated image data periodically, the light-induced deterioration may be substantially prevented while maintaining a desired level of contrast within the screen in an OLED display device according to an embodiment of the present invention.

[0098] FIG. 13A illustrates a first light-induced deterioration gray level compensating value according to an embodiment of the present invention, and FIG. 13B illustrates a second light-induced deterioration gray level compensating value according to an embodiment of the present invention.

[0099] FIGS. 13A and 13B respectively illustrate first and second light-induced deterioration gray level compensating values each configured so that light-induced deterioration gray level compensating values alternate on the basis of horizontal line.

[0100] The first light-induced deterioration gray level compensating value illustrated in FIG. 13A is configured so that the pixels R and the pixels B in odd-numbered horizontal lines are represented with a gray level 0, and the pixels R and the pixels B in even-numbered horizontal lines are represented with a gray level 8.

[0101] The second light-induced deterioration gray level compensating value illustrated in FIG. 13B is configured so that the pixels R and the pixels B in odd-numbered horizontal lines are represented with a gray level 8, and the pixels R and the pixels B in even-numbered horizontal lines are represented with a gray level 0.

[0102] The gray level compensating value calculation unit 52 alternately outputs the first light-induced deterioration gray level compensating value and the second light-induced deterioration gray level compensating value to be used for deterioration compensation in the light-induced deterioration compensated image data generation unit 54. In an embodiment of the present invention, as pixels in upper and lower portions on the display screen alternately emit light with the light-induced deterioration gray level compensating value, light-induced deterioration may be compensated without causing contrast degradation.

[0103] The first and second light-induced deterioration gray level compensating values in FIGS. 13A and 13B may be alternately output on the basis of an image frame.

[0104] In an embodiment of the present invention, the light-induced deterioration gray level compensating value may be converted in synchronization with a time point at which an image configuration displayed on the screen changes through the image signal analysis. The image signal analysis may be determined by, for example, analyzing a histogram of an image information. When an amount of change of the histogram information for each color is at or above a predetermined level, it may be determined that conversion of a channel or an image cut occurs. In the case where a light-induced deterioration gray level compensation pattern is switched in synchronization with the time point at which the screen changes, a screen of the light-induced deterioration gray level compensating value being changed might not be easily recognized by a user.

[0105] In addition, a method of converting the light-induced deterioration image pattern and the light-induced deterioration gray level compensation pattern may vary based on the degree of light-induced deterioration of the

particular OLED display device and various other considerations.

[0106] FIG. 14 is an explanatory view illustrating a light-induced deterioration compensation area of an OLED display panel 10 according to an embodiment of the present invention.

[0107] Referring to FIG. 14, the OLED display panel 10 displays a moving image of a car, and displays a logo of a broadcasting company at a fixed position on an upper right side. Since an image having a motion, like a car, has a mix of a light emitting state and a non-light emitting state of the pixel, a voltage V_{th} of a certain pixel may be rarely changed due to light-induced deterioration. However, a still image, such as a logo of a broadcasting company, which emits light with a high luminance at a substantially same position may cause light-induced deterioration in a non-emitting pixel in an area adjacent to a light emitting pixel area, such that luminance unevenness may occur in the OLED display panel 10.

[0108] FIG. 15 illustrates an example of a light-induced deterioration predictive image signal of a display screen of FIG. 14.

[0109] Referring to FIG. 15, a logo LOGO is displayed as a white character with a relatively high luminance whereby each of a pixel R, a pixel G, and a pixel B has a gray level of 255. An image signal of each of a pixel R, a pixel G, and a pixel B in the periphery of a light emitting pixel area in which the logo LOGO is displayed has a black gray level (e.g. a gray level 0).

[0110] The logo LOGO is displayed on the OLED display panel 10 for a relatively long period of time and may be set as a light-induced deterioration predictive image signal.

[0111] FIG. 16 is a light-induced deterioration compensated image data according to an embodiment of the present invention.

[0112] Referring to FIG. 16, with respect to the light-induced deterioration predictive image signal of FIG. 15, the light-induced deterioration compensation unit 50 assigns a light-induced deterioration gray level compensating value of 8 to a non-light emitting pixel in the periphery of a light emitting pixel in which light-induced deterioration may occur according to the light-induced deterioration predictive image signal to generate a light-induced deterioration compensated image data.

[0113] Referring to FIG. 16, a light-induced gray level compensating value of 8 may be assigned to a non-light emitting pixel spaced apart from a light emitting pixel by 6 pixels.

[0114] In an embodiment of the present invention, a range of the non-light emitting pixels in the peripheral area corresponds to a distance affected by a light output from the light emitting pixel, and may be experimentally determined based on light emission of the light emitting pixel, the size of the pixel, the distance between pixels, and characteristics of the pixel TFT.

[0115] FIG. 17 illustrates a light-induced deterioration compensated image data according to an embodiment

of the present invention.

[0116] Referring to FIG. 17, with respect to the light-induced deterioration predictive image signal of FIG. 15, the light-induced deterioration compensation unit 50 assigns a light-induced gray level compensating value of 8 or 4 to a black image signal applied to a pixel spaced apart from a light emitting pixel according to the light-induced deterioration predictive image signal to generate a light-induced deterioration compensated image data.

[0117] Because a degree of light-induced deterioration is proportional to an output light incident to pixels in the peripheral area, as a distance from the light emitting pixel increases, a lower light-induced deterioration gray level compensating value may be applied. When compensated with a less light-induced deterioration gray level compensating value in accordance with an increase in distance, the display screen of the light-induced deterioration compensated image data might not become rough. In an embodiment of the present invention, the light-induced deterioration gray level compensating value of two stages is taken as an example, but more steps may be set.

[0118] In the case where the light-induced deterioration compensated image data is applied, a substantially same light-induced deterioration gray level compensating value may be assigned to a pixel R, a pixel G, and a pixel B so that color artifacts might not be visually recognized in a low gray level environment.

[0119] FIG. 18 is a configuration view illustrating a deterioration compensation unit 60 according to an embodiment of the present invention.

[0120] Referring to FIG. 18, the deterioration compensation unit 60 may include an image deterioration compensation unit 61, an image deterioration stress analysis unit 62, a light-induced deterioration compensation unit 63, and a deterioration stress analysis unit 64.

[0121] The image deterioration compensation unit 61 may substantially prevent deterioration of an organic light emitting layer of a pixel caused by a same pixel emitting light for a relatively long period of time. The image deterioration compensation unit 61 detects a still image and moves the display screen including the still image to an upper or lower and/or left or right direction by one to two unit pixels on the OLED display panel. The image deterioration compensation unit 61 may move the entire screen on the pixel basis or may move only a part of the entire screen where image sticking occurs.

[0122] The image deterioration stress analysis unit 62 may analyze image deterioration occurring in the image screen moved by the image deterioration compensation unit 61. The image deterioration corresponds to a deterioration occurring in a light emitting pixel, and image sticking that may occur afterwards may be predicted through the image deterioration stress analysis. The image deterioration stress analysis unit 62 is configured to separately measure the influence of the image deterioration.

[0123] The light-induced deterioration compensation

unit 63 compensates for the light-induced deterioration occurring in a non-light emitting pixel in the periphery of a pixel that emits light for a relatively long period of time. The light-induced deterioration compensation unit 63 detects a still image and, when the still image is detected, compensates for an image signal so that the non-light emitting pixel in the peripheral area may emit light with a relatively low gray level.

[0124] The deterioration stress analysis unit 64 analyzes deterioration stress of the image signal compensated by the image deterioration compensation unit 61 and the light-induced deterioration compensation unit 63. The image signals compensated for deterioration are accumulated and the accumulated image signals are modeled. The image signal modeling may include accumulating output image signals and converting them to a maximum gray level for an accumulation time. With respect to the converted maximum gray level for the accumulation time, a deterioration stress may be analyzed for each panel based on the characteristics of the panel. The deterioration stress analysis unit 64 transmits the deterioration stress for each panel to the image deterioration compensation unit 61 and/or the light-induced deterioration compensation unit 63. The image deterioration compensation unit 61 and the light-induced deterioration compensation unit 63 may determine whether to compensate for the deterioration and adjust the deterioration compensating value based on the deterioration stress applied thereto.

[0125] FIG. 19 is a display image of an OLED display device according to an embodiment of the present invention.

[0126] FIG. 19 illustrates a pictured image of a light emitting state of a pixel R when a data signal voltage of a gray level 31 (31G) is applied to the pixel R of the OLED display panel 10 after a red box image and a green box image are continuously displayed for 210 hours (time = 210 hr) on the screen of the OLED display panel 10.

[0127] The display image includes two red box images in the upper portion of the screen and two green box images below the two red box images, respectively. In the red box image, a pixel R represents a gray level 255 (e.g. a maximum brightness), and a pixel G and a pixel B represent a gray level 8 (which is a relatively low gray level within the scale of 0 to 255). As for the green box image, a pixel G represents 255 gray level and a pixel R and a pixel B represent a gray level 8.

[0128] Referring to FIG. 19, it is verified that the luminance unevenness caused by the light-induced deterioration of the pixel R that occurs in the green area is corrected, as compared with the results of lighting experiment for 5 hours shown in FIG. 6.

[0129] As such, according to an embodiment of the present invention, a change in the voltage V_{th} due to light-induced deterioration may be suppressed and the luminance unevenness in the panel may be avoided by compensating for an image signal applied to a non-light emitting pixel in the periphery of a light emitting pixel area

with the light-induced deterioration gray level compensating value of a relatively low gray level.

[0130] As set forth hereinabove, in one or more embodiments of the present invention, an OLED display may analyze an image signal input to the OLED display device, detect a light-induced deterioration predictive image signal predicting possible light-induced deterioration, and compensate for a black image signal of the light-induced deterioration predictive image signal with a relatively low gray level, such that light-induced deterioration may be avoided.

[0131] Embodiments of the invention described herein are illustrative, and many variations can be introduced without departing from the scope of the appended claims. For example, elements and/or features of different embodiments may be combined with each other and/or substituted for each other within the scope of the appended claims.

Claims

1. An r active matrix type organic light emitting diode (OLED) display device comprising:

an organic light emitting diode display panel comprising a plurality of gate lines, a plurality of data lines intersecting the plurality of gate lines, and a plurality of pixels connected to the plurality of gate lines and the plurality of data lines;
 a timing controller configured to receive an image signal of a plurality of frames and output image data based on the plurality of frames; and
 a data driver configured to generate a data signal voltage corresponding to the image data output from the timing controller,
 wherein a light-induced deterioration compensation unit is included in the timing controller and is configured to detect whether the image signal includes a black image signal to one pixel of the plurality of pixels having a minimum gray level value that continues for at least a predetermined plurality of frames;
 the light-induced deterioration compensation unit is further configured to detect whether the image signal includes a gray level value above a reference gray level value for a pixel adjacent to said one pixel that continues for the predetermined plurality of frames; and
 the light-induced deterioration compensation unit is further configured, in response to detecting that both said conditions are met, to convert the black image signal by outputting a first image data to the one pixel, wherein the first image data has a first gray level value that is greater than the minimum gray level value of the black image signal.

2. An organic light emitting diode display device as claimed in claim 1, wherein the predetermined plurality of frames comprises at least ten successive frames.

3. An organic light emitting diode display device as claimed in claim 1 or 2, wherein when the minimum gray level value of the image signal is defined as a gray level value of 0 and a maximum gray level value of the image signal is defined as a gray level value of 255, the black image signal has the gray level value of 0.

4. An organic light emitting diode display device as claimed in claim 3, wherein the first image data has a gray level value ranging from 2 to 8.

5. An organic light emitting diode display device as claimed in any preceding claim, wherein the timing controller is configured to alternately output the first image data and a second image data having a second gray level value different from the first gray level value during the plurality of frames.

6. An organic light emitting diode display device as claimed in claim 5, wherein the second gray level value is equal to the minimum gray level value of the black image signal.

7. An organic light emitting diode display device as claimed in claim 1, wherein the light-induced deterioration compensation unit of the timing controller comprises:

a light-induced deterioration analysis unit configured to set a light-induced deterioration predictive image signal in response to detecting that both said conditions are met;
 a gray level compensating value calculation unit configured to receive the light-induced deterioration predictive image signal from the light-induced deterioration analysis unit and to calculate a light-induced deterioration gray level compensating value therefrom; and
 a light-induced deterioration compensated image data generation unit configured to compensate for the light-induced deterioration predictive image signal with the light-induced deterioration gray level compensating value to generate and output a light-induced deterioration compensated image data which coincides with said first image data.

8. An organic light emitting diode display device as claimed in any preceding claim, wherein the pixel comprises a thin film transistor comprising an oxide semiconductor layer.

9. An organic light emitting diode display device as

claimed in claim 8, wherein the oxide semiconductor layer comprises at least one material selected from the group consisting of: zinc oxide (ZnO), zinc-tin oxide (ZTO), zinc-indium oxide (ZIO), indium oxide (InO), titanium oxide (TiO), indium-gallium-zinc oxide (IGZO), and indium-zinc-tin oxide (IZTO).

10. A method of compensating for light-induced deterioration of the organic light emitting diode (OLED) display device of claim 1, the method comprising:

receiving an image signal comprising image information;
 detecting whether the image signal includes a black image signal to one pixel of the plurality of pixels having a minimum gray level value that continues for at least a predetermined plurality of frames;
 detecting whether the image signal includes a gray level value above a reference gray level value for a pixel adjacent to said one pixel that continues for the predetermined plurality of frames; and,
 in response to detecting that both said conditions are met, converting the black image signal by outputting a first image data to the one pixel, wherein the first image data has a first gray level value that is greater than the minimum gray level value of the black image signal.

Patentansprüche

1. Anzeigevorrichtung vom Aktivmatrixtyp mit organischen Leuchtdioden (OLED), umfassend:

eine Anzeigetafel mit organischen Leuchtdioden, die eine Vielzahl von Gate-Leitungen, eine Vielzahl von Datenleitungen, welche die Vielzahl von Gate-Leitungen kreuzen, und eine Vielzahl von Pixeln, die mit der Vielzahl von Gate-Leitungen und der Vielzahl von Datenleitungen verbunden sind, umfasst;
 eine Zeitsteuerungseinrichtung, die dafür konfiguriert ist, ein Bildsignal aus einer Vielzahl von Einzelbildern zu empfangen und Bilddaten auszugeben, die auf der Vielzahl von Einzelbildern beruhen; und
 einen Datentreiber, der dafür konfiguriert ist, eine Datensignalspannung zu erzeugen, die den von der Zeitsteuerungseinrichtung ausgegebenen Bilddaten entspricht,
 worin eine Ausgleichseinheit für lichtinduzierte Verschlechterung in der Zeitsteuerungseinrichtung enthalten und dafür konfiguriert ist, zu ermitteln, ob das Bildsignal ein Schwarzbildsignal für ein Pixel aus der Vielzahl von Pixeln einschließt, das einen minimalen Graustufenwert

aufweist, der für mindestens eine vorbestimmte Vielzahl von Einzelbildern fortbesteht;
 wobei die Ausgleichseinheit für lichtinduzierte Verschlechterung ferner dafür konfiguriert ist, zu ermitteln, ob das Bildsignal für ein an das eine Pixel angrenzendes Pixel einen Graustufenwert oberhalb eines Referenzgraustufenwertes einschließt, der für die vorbestimmte Vielzahl von Einzelbildern fortbesteht; und
 wobei die Ausgleichseinheit für lichtinduzierte Verschlechterung ferner dafür konfiguriert ist, als Reaktion auf das Ermitteln, dass beide genannten Bedingungen erfüllt sind, das Schwarzbildsignal durch Ausgeben von ersten Bilddaten an das eine Pixel zu konvertieren, worin die ersten Bilddaten einen ersten Graustufenwert aufweisen, der größer als der minimale Graustufenwert des Schwarzbildsignals ist.

2. Anzeigevorrichtung mit organischen Leuchtdioden nach Anspruch 1, worin die vorbestimmte Vielzahl von Einzelbildern mindestens zehn aufeinanderfolgende Einzelbilder umfasst.
3. Anzeigevorrichtung mit organischen Leuchtdioden nach Anspruch 1 oder 2, worin, wenn der minimale Graustufenwert des Bildsignals als ein Graustufenwert 0 ist und der maximale Graustufenwert des Bildsignals als ein Graustufenwert 255 definiert ist, das Schwarzbildsignal den Graustufenwert 0 aufweist.
4. Anzeigevorrichtung mit organischen Leuchtdioden nach Anspruch 3, worin die ersten Bilddaten einen Graustufenwert im Bereich von 2 bis 8 aufweisen.
5. Anzeigevorrichtung mit organischen Leuchtdioden nach einem der vorhergehenden Ansprüche, worin die Zeitsteuerungseinrichtung dafür konfiguriert ist, während der Vielzahl von Einzelbildern abwechselnd die ersten Bilddaten und zweite Bilddaten mit einem zweiten Graustufenwert, der sich vom ersten Graustufenwert unterscheidet, auszugeben.
6. Anzeigevorrichtung mit organischen Leuchtdioden nach Anspruch 5, worin der zweite Graustufenwert gleich dem minimalen Graustufenwert des Schwarzbildsignals ist.
7. Anzeigevorrichtung mit organischen Leuchtdioden nach Anspruch 1, worin die Ausgleichseinheit für lichtinduzierte Verschlechterung der Zeitsteuerungseinrichtung umfasst:

eine Einheit zur Analyse der lichtinduzierten Verschlechterung, die dafür konfiguriert ist, als Reaktion auf das Ermitteln, dass beide Bedingungen erfüllt sind, ein Bildsignal mit Vorhersage der lichtinduzierten Verschlechterung einzu-

- stellen;
eine Graustufenausgleichswert-Berechnungseinheit, die dafür konfiguriert ist, von der Einheit zur Analyse der lichtinduzierten Verschlechterung das Bildsignal mit Vorhersage der lichtinduzierten Verschlechterung zu empfangen und daraus einen Graustufenwertausgleichswert für die lichtinduzierte Verschlechterung zu berechnen; und
eine Erzeugungseinheit für Bilddaten mit Ausgleich der lichtinduzierten Verschlechterung, die dafür konfiguriert ist, das Bildsignal mit Vorhersage der lichtinduzierten Verschlechterung mit dem Graustufenwertausgleichswert für die lichtinduzierte Verschlechterung auszugleichen, um Bilddaten mit Ausgleich der lichtinduzierten Verschlechterung zu erzeugen und auszugeben, die mit den ersten Bilddaten zusammenfallen.
8. Anzeigevorrichtung mit organischen Leuchtdioden nach einem der vorhergehenden Ansprüche, worin das Pixel einen Dünnschichttransistor umfasst, der eine Oxidhalbleiterschicht umfasst.
9. Anzeigevorrichtung mit organischen Leuchtdioden nach Anspruch 8, worin die Oxidhalbleiterschicht mindestens ein Material umfasst, das aus der Gruppe ausgewählt wird, die aus Folgendem besteht: Zinkoxid (ZnO), Zink-Zinn-Oxid (ZTO), Zink-Indium-Oxid (ZIO), Indiumoxid (InO), Titanoxid (TiO), Indium-Gallium-Zink-Oxid (IGZO) und Indium-Zinn-Oxid (IZTO).
10. Verfahren zum Ausgleichen der lichtinduzierten Verschlechterung der Anzeigevorrichtung mit organischen Leuchtdioden (OLED) nach Anspruch 1, wobei das Verfahren umfasst:
- Empfangen eines Bildsignals, das Bildinformation umfasst;
Ermitteln, ob das Bildsignal ein Schwarzbildsignal für ein Pixel aus der Vielzahl von Pixeln einschließt, das einen minimalen Graustufenwert aufweist, der für mindestens eine vorbestimmte Vielzahl von Einzelbildern fortbesteht;
Ermitteln, ob das Bildsignal für ein an das eine Pixel angrenzendes Pixel einen Graustufenwert oberhalb eines Referenzgraustufenwertes einschließt, der für die vorbestimmte Vielzahl von Einzelbildern fortbesteht; und
als Reaktion auf das Ermitteln, dass beide Bedingungen erfüllt sind, erfolgreiches Konvertieren des Schwarzbildsignals durch Ausgeben von ersten Bilddaten an das eine Pixel, worin die ersten Bilddaten einen ersten Graustufenwert aufweisen, der größer als der minimale Graustufenwert des Schwarzbildsignals ist.

Revendications

1. Dispositif d'affichage à diodes électroluminescentes organiques (OLED) du type à matrice active comprenant :

un panneau d'affichage à diodes électroluminescentes organiques qui comprend une pluralité de lignes de grille, une pluralité de lignes de données qui intersectent les lignes de grille de la pluralité de lignes de grille et une pluralité de pixels qui sont connectés à la pluralité de lignes de grille et à la pluralité de lignes de données ; un contrôleur de cadencement qui est configuré de manière à ce qu'il reçoive un signal d'image d'une pluralité de trames et de manière à ce qu'il émette en sortie des données d'image sur la base de la pluralité de trames ; et un dispositif de pilotage de données qui est configuré de manière à ce qu'il génère une tension de signal de données qui correspond aux données d'image qui sont émises en sortie depuis le contrôleur de cadencement ; dans lequel :

une unité de compensation de détérioration induite par la lumière est incluse dans le contrôleur de cadencement et elle est configurée de manière à ce qu'elle détecte si oui ou non le signal d'image inclut un signal d'image de noir pour un pixel de la pluralité de pixels qui présente une valeur de niveau de gris minimum qui se poursuit pendant au moins une pluralité prédéterminée de trames ;

l'unité de compensation de détérioration induite par la lumière est en outre configurée de manière à ce qu'elle détecte si oui ou non le signal d'image inclut une valeur de niveau de gris au-delà d'une valeur de niveau de gris de référence pour un pixel qui est adjacent audit un pixel considéré qui se poursuit pendant la pluralité prédéterminée de trames ; et

l'unité de compensation de détérioration induite par la lumière est en outre configurée de manière à ce que, en réponse à la détection du fait que lesdites conditions sont toutes deux satisfaites, elle convertisse le signal d'image de noir en émettant en sortie des premières données d'image pour le pixel considéré, dans lequel les premières données d'image présentent une première valeur de niveau de gris qui est supérieure à la valeur de niveau de gris minimum du signal d'image de noir.

2. Dispositif d'affichage à diodes électroluminescentes organiques tel que revendiqué selon la revendica-

tion 1, dans lequel la pluralité prédéterminée de trames comprend au moins dix trames successives.

3. Dispositif d'affichage à diodes électroluminescentes organiques tel que revendiqué selon la revendication 1 ou 2, dans lequel, lorsque la valeur de niveau de gris minimum du signal d'image est définie en tant que valeur de niveau de gris de 0 et qu'une valeur de niveau de gris maximum du signal d'image est définie en tant que niveau de gris de 255, le signal d'image de noir présente la valeur de niveau de gris de 0. 5
4. Dispositif d'affichage à diodes électroluminescentes organiques tel que revendiqué selon la revendication 3, dans lequel les premières données d'image présentent une valeur de niveau de gris qui s'inscrit à l'intérieur d'une plage qui va de 2 à 8. 10
5. Dispositif d'affichage à diodes électroluminescentes organiques tel que revendiqué selon l'une quelconque des revendications qui précèdent, dans lequel le contrôleur de cadencement est configuré de manière à ce qu'il émette en sortie en alternance les premières données d'image et des secondes données d'image qui présentent une seconde valeur de niveau de gris qui est différente de la première valeur de niveau de gris pendant la pluralité de trames. 20
6. Dispositif d'affichage à diodes électroluminescentes organiques tel que revendiqué selon la revendication 5, dans lequel la seconde valeur de niveau de gris est égale à la valeur de niveau de gris minimum du signal d'image de noir. 25
7. Dispositif d'affichage à diodes électroluminescentes organiques tel que revendiqué selon la revendication 1, dans lequel l'unité de compensation de détérioration induite par la lumière du contrôleur de cadencement comprend : 30
 - une unité d'analyse de détérioration induite par la lumière qui est configurée de manière à ce qu'elle définisse un signal d'image de prédiction de détérioration induite par la lumière en réponse à la détection du fait que lesdites conditions sont toutes deux satisfaites ;
 - une unité de calcul de valeur de compensation de niveau de gris qui est configurée de manière à ce qu'elle reçoive le signal d'image de prédiction de détérioration induite par la lumière en provenance de l'unité d'analyse de détérioration induite par la lumière et de manière à ce qu'elle calcule une valeur de compensation de niveau de gris de détérioration induite par la lumière à partir de ce signal ; et
 - une unité de génération de données d'image à compensation de détérioration induite par la lu-

mière qui est configurée de manière à ce qu'elle compense le signal d'image de prédiction de détérioration induite par la lumière à l'aide de la valeur de compensation de niveau de gris de détérioration induite par la lumière de manière à ce qu'elle génère et émette en sortie des données d'image à compensation de détérioration induite par la lumière qui coïncide avec lesdites premières données d'image.

8. Dispositif d'affichage à diodes électroluminescentes organiques tel que revendiqué selon l'une quelconque des revendications qui précèdent, dans lequel le pixel comprend un transistor à film mince qui comprend une couche semiconductrice à base d'oxyde(s). 35
9. Dispositif d'affichage à diodes électroluminescentes organiques tel que revendiqué selon la revendication 8, dans lequel la couche semiconductrice à base d'oxyde(s) comprend au moins un matériau qui est sélectionné parmi le groupe qui est constitué par : l'oxyde de zinc (ZnO), l'oxyde de zinc et d'étain (ZTO), l'oxyde de zinc et d'indium (ZIO), l'oxyde d'indium (InO), l'oxyde de titane (TiO), l'oxyde d'indium, de gallium et de zinc (IGZO) et l'oxyde d'indium, de zinc et d'étain (IZTO). 40
10. Procédé de compensation de la détérioration induite par la lumière du dispositif d'affichage à diodes électroluminescentes organiques (OLED) selon la revendication 1, le procédé comprenant : 45

- la réception d'un signal d'image qui comprend une information d'image ;
- la détection de si oui ou non le signal d'image inclut un signal d'image de noir pour un pixel de la pluralité de pixels qui présente une valeur de niveau de gris minimum qui se poursuit pendant au moins une pluralité prédéterminée de trames ;
- la détection de si oui ou non le signal d'image inclut une valeur de niveau de gris au-delà d'une valeur de niveau de gris de référence pour un pixel qui est adjacent audit un pixel considéré qui se poursuit pendant la pluralité prédéterminée de trames ; et
- en réponse à la détection du fait que lesdites conditions sont toutes deux satisfaites, la conversion du signal d'image de noir en émettant en sortie une première donnée d'image pour le pixel considéré, dans lequel les premières données d'image présentent une première valeur de niveau de gris qui est supérieure à la valeur de niveau de gris minimum du signal d'image de noir. 50

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10A

R	G	B	R	G	B	R	G	B
0	255	0	0	255	0	0	255	0
0	255	0	0	255	0	0	255	0
0	255	0	0	255	0	0	255	0
0	255	0	0	255	0	0	255	0
0	255	0	0	255	0	0	255	0
0	255	0	0	255	0	0	255	0
0	255	0	0	255	0	0	255	0
0	255	0	0	255	0	0	255	0
0	255	0	0	255	0	0	255	0

FIG. 10B

R	G	B	R	G	B	R	G	B
8	0	8	8	0	8	8	0	8
8	0	8	8	0	8	8	0	8
8	0	8	8	0	8	8	0	8
8	0	8	8	0	8	8	0	8
8	0	8	8	0	8	8	0	8
8	0	8	8	0	8	8	0	8
8	0	8	8	0	8	8	0	8
8	0	8	8	0	8	8	0	8
8	0	8	8	0	8	8	0	8

FIG. 10C

R	G	B	R	G	B	R	G	B
8	255	8	8	255	8	8	255	8
8	255	8	8	255	8	8	255	8
8	255	8	8	255	8	8	255	8
8	255	8	8	255	8	8	255	8
8	255	8	8	255	8	8	255	8
8	255	8	8	255	8	8	255	8
8	255	8	8	255	8	8	255	8
8	255	8	8	255	8	8	255	8
8	255	8	8	255	8	8	255	8

FIG. 11A

R	G	B	R	G	B	R	G	B
0	128	0	0	128	0	0	128	0
0	128	0	0	128	0	0	128	0
0	128	0	0	128	0	0	128	0
0	128	0	0	128	0	0	128	0
0	128	0	0	128	0	0	128	0
0	128	0	0	128	0	0	128	0
0	128	0	0	128	0	0	128	0
0	128	0	0	128	0	0	128	0
0	128	0	0	128	0	0	128	0

FIG. 11B

R	G	B	R	G	B	R	G	B
4	0	4	4	0	4	4	0	4
4	0	4	4	0	4	4	0	4
4	0	4	4	0	4	4	0	4
4	0	4	4	0	4	4	0	4
4	0	4	4	0	4	4	0	4
4	0	4	4	0	4	4	0	4
4	0	4	4	0	4	4	0	4
4	0	4	4	0	4	4	0	4
4	0	4	4	0	4	4	0	4

FIG. 11C

R	G	B	R	G	B	R	G	B	R
4	128	4	4	128	4	4	128	4	4
4	128	4	4	128	4	4	128	4	4
4	128	4	4	128	4	4	128	4	4
4	128	4	4	128	4	4	128	4	4
4	128	4	4	128	4	4	128	4	4
4	128	4	4	128	4	4	128	4	4
4	128	4	4	128	4	4	128	4	4
4	128	4	4	128	4	4	128	4	4
4	128	4	4	128	4	4	128	4	4

FIG. 12




FIG. 13A

R	G	B	R	G	B	R	G	B
0	0	0	0	0	0	0	0	0
8	0	8	8	0	8	8	0	8
0	0	0	0	0	0	0	0	0
8	0	8	8	0	8	8	0	8
0	0	0	0	0	0	0	0	0
8	0	8	8	0	8	8	0	8
0	0	0	0	0	0	0	0	0
8	0	8	8	0	8	8	0	8
0	0	0	0	0	0	0	0	0

FIG. 13B

R	G	B	R	G	B	R	G	B
8	0	8	8	0	8	8	0	8
0	0	0	0	0	0	0	0	0
8	0	8	8	0	8	8	0	8
0	0	0	0	0	0	0	0	0
8	0	8	8	0	8	8	0	8
0	0	0	0	0	0	0	0	0
8	0	8	8	0	8	8	0	8
0	0	0	0	0	0	0	0	0
8	0	8	8	0	8	8	0	8

FIG. 14




FIG. 15

R	G	B	R	G	B	R	G	B	R	G	B	R	G	B
0	0	0	0	0	0	255	255	255	0	0	0	0	0	0
0	0	0	0	0	0	255	255	255	0	0	0	0	0	0
0	0	0	0	0	0	255	255	255	0	0	0	0	0	0
0	0	0	0	0	0	255	255	255	0	0	0	0	0	0
0	0	0	0	0	0	255	255	255	0	0	0	0	0	0
0	0	0	0	0	0	255	255	255	255	255	255	255	255	255
0	0	0	0	0	0	255	255	255	255	255	255	255	255	255
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0

FIG. 16

R	G	B	R	G	B	R	G	B	R	G	B	R	G	B
8	8	8	8	8	8	255	255	255	8	8	8	8	8	8
8	8	8	8	8	8	255	255	255	8	8	8	8	8	8
8	8	8	8	8	8	255	255	255	8	8	8	8	8	8
8	8	8	8	8	8	255	255	255	8	8	8	8	8	8
8	8	8	8	8	8	255	255	255	8	8	8	8	8	8
8	8	8	8	8	8	255	255	255	255	255	255	255	255	255
8	8	8	8	8	8	255	255	255	255	255	255	255	255	255
8	8	8	8	8	8	8	8	8	8	8	8	8	8	8
8	8	8	8	8	8	8	8	8	8	8	8	8	8	8

FIG. 17

R	G	B	R	G	B	R	G	B	R	G	B	R	G	B
4	4	4	8	8	8	255	255	255	8	8	8	4	4	4
4	4	4	8	8	8	255	255	255	8	8	8	4	4	4
4	4	4	8	8	8	255	255	255	8	8	8	4	4	4
4	4	4	8	8	8	255	255	255	8	8	8	4	4	4
4	4	4	8	8	8	255	255	255	8	8	8	8	8	8
4	4	4	8	8	8	255	255	255	255	255	255	255	255	255
4	4	4	8	8	8	255	255	255	255	255	255	255	255	255
4	4	4	8	8	8	8	8	8	8	8	8	8	8	8
4	4	4	4	4	4	4	4	4	4	4	4	4	4	4

FIG. 18





FIG. 19



REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US 20070109284 A1 [0006]
- US 20110043551 A1 [0007]

专利名称(译)	有机发光二极管显示装置		
公开(公告)号	EP3300068B1	公开(公告)日	2019-09-18
申请号	EP2017192771	申请日	2017-09-22
[标]申请(专利权)人(译)	三星显示有限公司		
申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	YANG SUMIN PARK JINWOO BAE MINSEOK		
发明人	YANG, SUMIN PARK, JINWOO BAE, MINSEOK		
IPC分类号	G09G3/3233		
优先权	1020160121537 2016-09-22 KR		
其他公开文献	EP3300068A1		
外部链接	Espacenet		

摘要(译)

有机发光二极管 (OLED) 显示装置包括：OLED显示面板，该OLED显示面板具有栅极线，与该栅极线相交的数据线以及连接至该栅极线和该数据线的多个像素。时序控制器接收包括多个帧的图像信号，并基于多个帧输出图像数据。数据驱动器产生与从定时控制器输出的图像数据相对应的数据信号电压。当图像信号包括到至少连续多个预定帧的多个像素中的一个像素的黑色图像信号时，定时控制器输出第一图像数据，其中黑色图像信号已被转换为第一灰度级该值大于黑色图像信号的灰度值。

FIG. 1

