



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
16.02.2011 Bulletin 2011/07

(51) Int Cl.:
G09G 3/32^(2006.01)

(21) Application number: **10251386.8**

(22) Date of filing: **03.08.2010**

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR
Designated Extension States:
BA ME RS

(72) Inventors:
• **Park, Sung-Un**
Chungcheongnam-do (KR)
• **Park, Sung-Cheon**
Chungcheongnam-do (KR)
• **Lee, Wook**
Chungcheongnam-do (KR)

(30) Priority: **03.08.2009 KR 20090071274**

(71) Applicant: **Samsung Mobile Display Co., Ltd.**
Yongin-city, Gyunggi-do 446-711 (KR)


(74) Representative: **Mouteney, Simon James**
Marks & Clerk LLP
90 Long Acre
London
WC2E 9RA (GB)

(54) **Organic light emitting display and method of driving the same**

(57) An organic light emitting display capable of reducing power consumption in a standby mode to increase the use time of a battery and a method of driving the same. The organic light emitting display includes a pixel unit (101) for displaying an image by utilizing a plurality of frames and in accordance with data signals and scan

signals; a data driver (200) for outputting the data signals; a scan driver (300) for outputting the scan signals; and a controller (500) for controlling the data driver and the scan driver so that, in at least one frame of the plurality of frames, the scan signals are not transmitted to the pixel unit.

FIG. 2



Description

BACKGROUND

1. Field

[0001] The present invention relates to an organic light emitting display and a method of driving the same.

2. Description of the Related Art

[0002] Various flat panel displays (FPD) that are lighter in weight and smaller in volume than comparable cathode ray tube (CRT) displays are being developed. Nonlimiting examples of these FPDs include a liquid crystal display (LCD), a field emission display (FED), a plasma display panel (PDP), and an organic light emitting display.

[0003] Among the FPDs, the organic light emitting display displays an image using organic light emitting diodes (OLED) that generate light by re-combination of electrons and holes generated to correspond to the flow of current.

[0004] The organic light emitting display is widely utilized in a personal digital assistant (PDA), an MP3 player, and/or a mobile telephone due to its excellent color reproducibility and small thickness.

[0005] FIG. 1 is a block diagram illustrating the structure of an organic light emitting display according to an embodiment of the present invention. Referring to FIG. 1, the organic light emitting display includes a pixel unit (a display region) 10, a data driver 20, a scan driver 30, and a controller 40.

[0006] A plurality of pixels 11 are arranged in the pixel unit 10 and each of the pixels 11 includes an organic light emitting diode (OLED) that emits light to correspond to the flow of current therein. The pixel unit 10 includes n scan lines S1, S2, ..., Sn-1, and Sn formed to extend in a first direction (a row direction) and to transmit scan signals, and m data lines D1, D2, ..., Dm-1, and Dm formed to extend in a second direction (a column direction) crossing the first direction and to transmit data signals.

[0007] In addition, the pixel unit 10 receives a first power of a first power source and a second power of a second power source having a lower voltage level than that of the first power source to be driven. Therefore, in the pixel unit 10, current flows to the OLED by utilizing the scan signals, the data signals, the first power source, and the second power source to emit light and to display an image.

[0008] The data driver 20 receives data driver control signals DCS and image signals R,G,B data from the controller 40 to generate the data signals. The data driver 20 is coupled to the data lines D1, D2, ..., Dm-1, and Dm of the pixel unit 10 to apply the generated data signals to the pixel unit 10.

[0009] The scan driver 30 receives scan driver control signals SCS from the controller 40 to generate the scan signals. The scan driver 30 is coupled to the scan lines

S1, S2, ..., Sn-1, and Sn to transmit the scan signals to specific rows of the pixel unit 10. The data signal output from the data driver 20 is transmitted to the pixel 11 where the scan signal is transmitted so that the voltage corresponding to the data signal is transmitted to the pixel 11.

[0010] The controller 40 controls the data driver 20 and the scan driver 30 so that the pixel unit 10 can display an image.

[0011] When the above structured organic light emitting display is used for a mobile telephone, in a standby mode, an image representing date and hour is displayed only on a partial region of the pixel unit and the image is not displayed on the remaining region.

[0012] The image is displayed only on the partial region (a partial screen) in order to reduce power consumption and to increase the use time of a battery of the organic light emitting display.

[0013] However, in the standby mode, the data driver 20 and the scan driver 30 are driven in the same way. That is, the power consumptions of the data driver 20 and the scan driver 30 do not change in the standby mode. Therefore, in order to reduce power consumption, an improved method of reducing power consumption in the data driver 20 and the scan driver 30 in the standby mode is needed.

SUMMARY OF THE INVENTION

[0014] The present invention is directed toward an organic light emitting display with a relatively small power consumption and a method of using the same.

[0015] The present invention sets out to provide an organic light emitting display capable of reducing power consumption in a standby mode to increase the use time of a battery of the display and a method of using the same.

[0016] An embodiment of the present invention provides an organic light emitting display, including a pixel unit (display region) for displaying an image by utilizing a plurality of frames and in accordance with data signals and scan signals; a data driver for outputting the data signals; a scan driver for outputting the scan signals; and a controller for controlling the data driver and the scan driver so that, in at least one frame of the plurality of frames, the scan signals are not transmitted to the pixel unit.

[0017] In one embodiment, the scan driver is stopped from being driven by the controller during a frame period of the at least one frame when the scan signals are not transmitted.

[0018] In one embodiment, the organic light emitting display further includes a demultiplexer between the data driver and the pixel unit to distribute a plurality of data signals output from one output end of the data driver during a frame period of at least an other frame of the plurality of frames. Here, an operation of the demultiplexer may stop in the at least one frame when the scan signals are not transmitted to the pixel unit.

[0019] In one embodiment, the image is displayed only

in a partial region of the pixel unit.

[0020] In one embodiment, the image is a standby image.

[0021] Another embodiment of the present invention provides a method of driving an organic light emitting display for displaying an image by utilizing a plurality of frames and in accordance with data signals and scan signals. The method includes: transmitting the data signals to pixels of a pixel unit of the organic light emitting display by the scan signals to display a first image of a first frame of the plurality of frames; and maintaining the data signals transmitted in the first frame in the pixels to display a second image of a second frame of the plurality of frames.

[0022] In one embodiment, the scan signals are not transmitted in the second frame.

[0023] In one embodiment, the first and second images are displayed only on a part of the pixel unit. The first and second images may be a standby image.

[0024] In one embodiment, the second frame is an adjacent frame following the first frame.

[0025] In the organic light emitting display and the method of driving the same according to embodiments of the present invention, the scan driver is driven to output the scan signals only in a part of the time where the image is displayed so that power consumption in accordance with the driving of the scan signals can be reduced.

[0026] The above and other features of the invention are set out in the appended claims.

BRIEF DESCRIPTION OF THE DRAWINGS

[0027] The accompanying drawings, together with the specification, illustrate embodiments of the present invention, and, together with the description, serve to explain the principles of the present invention.

[0028] FIG. 1 is a block diagram illustrating the structure of an organic light emitting display;

[0029] FIG. 2 is a block diagram illustrating the structure of an organic light emitting display according to an embodiment of the present invention;

[0030] FIG. 3 is a view illustrating an image displayed on the pixel unit of the organic light emitting display of FIG. 2 in a standby mode;

[0031] FIG. 4 is a circuit diagram illustrating a pixel adopted by the organic light emitting display of FIG. 2; and

[0032] FIG. 5 is a waveform diagram illustrating scan signals and demultiplexer control signals input to the organic light emitting display of FIG. 2.

DETAILED DESCRIPTION

[0033] Hereinafter, certain embodiments according to the present invention will be described with reference to the accompanying drawings. Here, when a first element is described as being coupled to a second element, the first element may be not only directly coupled to the sec-

ond element but may also be indirectly coupled to the second element via one or more third elements. Further, some of the elements that are not essential to the complete understanding of the invention are omitted for clarity. Also, like reference numerals refer to like elements throughout.

[0034] Hereinafter, an embodiment of the present invention will be described in detail with reference to the accompanying drawings.

[0035] FIG. 2 is a block diagram illustrating the structure of an organic light emitting display according to the present invention. Referring to FIG. 2, the organic light emitting display includes a pixel unit (display region) 100, a data driver 200, a scan driver 300, a demultiplexer 400, and a controller 500.

[0036] A plurality of pixels 101 are arranged in the pixel unit 100, and each of the pixels 101 includes an organic light emitting diode (OLED) that emits light to correspond to the flow of current. The pixel unit 100 includes n scan lines S1, S2, ..., Sn-1, and Sn formed to extend in a first direction (a row direction) and to transmit scan signals, and m data lines D1, D2, ..., Dm-1, and Dm formed to extend in a second direction (a column direction) crossing the first direction and to transmit data signals.

[0037] In addition, the pixel unit 100 receives a first power of a first power source ELVDD and a second power of a second power source ELVSS having a lower voltage level than the first power source ELVDD to be driven. Therefore, in the pixel unit 100, current flows to the OLED by utilizing the scan signals, the data signals, the first power source ELVDD, and the second power source ELVSS to emit light and to display an image.

[0038] The data driver 200 receives data driver control signals DCS and image signals R,G,B data from the controller 500 to generate the data signals. The data driver 200 is coupled to the data lines D1, D2, ..., Dm-1, and Dm of the pixel unit 100 through the demultiplexer 400 to apply the generated data signals to the pixel unit 100.

[0039] The scan driver 300 receives scan driver control signals SCS from the controller 500 to generate the scan signals. The scan driver 300 is coupled to the scan lines S1, S2, ..., Sn-1, and Sn to transmit the scan signals to specific rows of the pixel unit 100. The data signal output from the data driver 200 is transmitted to the pixel 101 where the scan signal is transmitted so that the voltage corresponding to the data signal is transmitted to the pixel 101.

[0040] The demultiplexer 400 transmits the data signals transmitted through the output terminals O1...Ok of the data driver 200 to the data lines D1, D2, ..., Dm-1, and Dm. In particular, one output terminal of the data driver 200 is coupled to three data lines through the demultiplexer. One output terminal of the data driver 200 sequentially outputs red, green, and blue data signals. The demultiplexer 400 has the red, green, and blue data signals transmitted to the three data lines by demultiplexer control signals CLA, CLB, and CLC. Therefore, the number of output terminals O1...Ok of the data driver 200

can be reduced by the demultiplexer 400.

[0041] The controller 500 transmits the image signals R,G,B data and the data driver control signals DCS to the data driver 200, transmits the scan driver control signals SCS to the scan driver 300, transmits demultiplexer control signals CLA, CLB, and CLC to the demultiplexer 400, and has the data driver 200 select transmitted data signals so that the pixel unit 100 can display an image.

[0042] FIG. 3 is a view illustrating an image displayed on the pixel unit of the organic light emitting display of FIG. 2 in a standby mode. Referring to FIG. 3, the organic light emitting display is driven in a display mode where images such as a moving picture and a photograph are displayed and in a standby mode where only date and hour are displayed.

[0043] In order to reduce power consumption in the standby mode, the pixel unit is divided into a non-display region 110 and a display region 120. In the display region 120, icons such as date and hour are displayed. The non-display region 110 does not emit light so that the non-display region 110 is displayed black (displays no emitting light).

[0044] Since the organic light emitting display displays an image corresponding to the current that flows to each pixel, current flows to the pixels positioned in the display region 120 in the standby mode and current does not flow to the pixels positioned in the non-display region 110. That is, the amount of the current that flows to the pixel unit 100 in the standby mode is smaller than the amount of the current that flows to the pixel unit in the display mode. Therefore, power consumption is reduced.

[0045] However, in the case where the image is displayed only in the display region 120 that is not the entire region of the pixel unit 100 but is a part of the pixel unit 100, the scan driver 300 performs the same operation as when the scan driver 300 operates in the display mode. Therefore, in order to effectively reduce power consumption, the scan signals input to the pixel unit 100 are to be differently transmitted in the display mode and in the standby mode.

[0046] FIG. 4 is a circuit diagram illustrating a pixel adopted by the organic light emitting display of FIG. 2. Referring to FIG. 4, the pixel 101 includes a first transistor M1, a second transistor M2, a capacitor Cst, and an organic light emitting diode (OLED) and receives a data signal and a scan signal through the data line Dm and the scan line Sn.

[0047] The source of the first transistor M1 is coupled to the first power source ELVDD. The drain of the first transistor M1 is coupled to the anode electrode of the OLED. The gate of the first transistor M1 is coupled to a first node N1. Therefore, the amount of the current that flows from the source to the drain is determined to correspond to the voltage of the first node N1.

[0048] The source of the second transistor M2 is coupled to the data line Dm. The drain of the second transistor M2 is coupled to the first node N1. The gate of the second transistor M2 is coupled to the scan line Sn.

Therefore, the data signal transmitted through the data line Dm to correspond to the scan signal transmitted through the scan line Sn can be transmitted to the first node N1.

[0049] The first electrode of the capacitor Cst is coupled to the first power source ELVDD and the second electrode of the capacitor Cst is coupled to the first node N1. Therefore, the voltage of the first node N1 can be maintained.

[0050] The anode electrode of the OLED is coupled to the drain of the first transistor M1. The cathode electrode of the OLED is coupled to the second power source ELVSS. A light emitting layer is formed between the anode electrode and the cathode electrode. Light is emitted to correspond to the current that flows from the anode electrode to the cathode electrode. Therefore, light is emitted to correspond to the amount of current that flows from the source of the first transistor M1 to the drain of the first transistor M1.

[0051] FIG. 5 is a waveform diagram illustrating scan signals and demultiplexer control signals input to the organic light emitting display of FIG. 2. Referring to FIG. 5, the image displayed by the pixel unit 100 of the organic light emitting display is displayed by utilizing a plurality of frames.

[0052] First, in a first frame period, the scan signal Sn and demultiplexer control signals are transmitted. Therefore, the data signals output from the data driver 200 by the demultiplexer control signals CLA, CLB, and CLC are sequentially distributed to the data lines. Then, the data signal is transmitted to a specific pixel 101 by the scan signal Sn and the pixel 101 emits light to correspond to the data signal. Therefore, an image (a standby image) is displayed on the display region 120 of the pixel unit 100.

[0053] The scan signal Sn and the demultiplexer control signals CLA, CLB, and CLC are not transmitted in a second frame period (e.g., an adjacent frame following the first frame). Therefore, the data signals corresponding to the second frame are not transmitted to the pixel 101. However, since the data signals transmitted in the first frame period are previously stored in the capacitor Cst in the pixel 101, the same image as the image of the first frame is displayed in the second frame.

[0054] Then, in a third frame period (e.g., an adjacent frame following the second frame), the scan signal Sn and the demultiplexer control signals CLA, CLB, and CLC are transmitted. At this time, light is emitted from the pixel 101 in accordance with (to correspond to) the transmitted data signals.

[0055] Therefore, the scan signal Sn is not transmitted in the second frame period since the scan driver 300 is not driven. Therefore, power consumption utilized by the scan driver 300 can be reduced by the stopping of driving of the scan driver 300. In addition, since the icons displayed in the standby mode are images that do not frequently change, although the data signals are not received during all of the frames, it is still possible to reduce or prevent the images from being distorted or wrongly

transmitted.

[0056] While the present invention has been described in connection with certain exemplary embodiments, it is to be understood that the invention is not limited to the disclosed embodiments, but, on the contrary, is intended to cover various modifications and equivalent arrangements included within the scope of the appended claims, and equivalents thereof.

Claims

1. An organic light emitting display, comprising:

a pixel unit for displaying an image by utilizing a plurality of frames and in accordance with data signals and scan signals;
a data driver for outputting the data signals;
a scan driver for outputting the scan signals; and
a controller for controlling the data driver and the scan driver so that, in at least one frame of the plurality of frames, the scan signals are not transmitted to the pixel unit.

2. An organic light emitting display as claimed in claim 1, wherein the controller is adapted to stop the scan driver from being driven to output the scan signals during a frame period of the at least one frame when the scan signals are not transmitted.

3. An organic light emitting display as claimed in claim 1 or 2, further comprising a demultiplexer between the data driver and the pixel unit to distribute a plurality of data signals output from one output end of the data driver during a frame period of at least another frame of the plurality of frames.

4. An organic light emitting display as claimed in claim 3, wherein the controller is adapted to stop an operation of the demultiplexer in the at least one frame when the scan signals are not transmitted to the pixel unit.

5. An organic light emitting display as claimed in any preceding claim, wherein the image is displayed only in a partial region of the pixel unit.

6. An organic light emitting display as claimed in any preceding claim, wherein the image is a standby image.

7. An organic light emitting display as claimed in any preceding claim, wherein the pixel unit is adapted to maintain the data signals transmitted in a previous frame during a frame period of the at least one frame when the scan signals are not transmitted.

8. An organic light emitting display as claimed in claim

7, wherein the data driver is configured to not transmit the data signals during the frame period of the at least one frame when the scan signals are not transmitted.

9. A method of driving an organic light emitting display for displaying an image by utilizing a plurality of frames and in accordance with data signals and scan signals, comprising:

transmitting the data signals to pixels of a pixel unit of the organic light emitting display by the scan signals to display a first image of a first frame of the plurality of frames; and
maintaining the data signals transmitted in the first frame in the pixels to display a second image of a second frame of the plurality of frames.

10. A method as claimed in claim 9, wherein the scan signals are not transmitted in the second frame.

11. A method as claimed in claim 9 or 10, wherein the first and second images are displayed only on a part of the pixel unit.

12. A method as claimed in one of claims 9 to 11, wherein the first and second images are a standby image.

13. A method as claimed in any one of claims 9 to 12, wherein the second frame is an adjacent frame following the first frame.

FIG. 1




FIG. 2




FIG. 3




FIG. 4





FIG. 5





EUROPEAN SEARCH REPORT

Application Number
EP 10 25 1386

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
X	EP 1 391 871 A1 (SHARP KK [JP]) 25 February 2004 (2004-02-25)	1,2, 6-10,12, 13	INV. G09G3/32
Y	* paragraph [0011] * * paragraph [0047] - paragraph [0070] * * paragraph [0107]; figures 1-3 * -----	3-5,11	
X	US 2002/180673 A1 (TSUDA KAZUHIHO [JP] ET AL TSUDA KAZUHIKO [JP] ET AL) 5 December 2002 (2002-12-05)	1,2, 7-10,13	
Y	* paragraph [0184] - paragraph [0374]; figures 23-25,28-45 * -----	3-6,11, 12	
Y	US 2006/097974 A1 (HASHIMOTO YOSHIHARU [JP] ET AL) 11 May 2006 (2006-05-11) * paragraph [0002] - paragraph [0006] * * paragraph [0029] - paragraph [0033] * * paragraph [0041] - paragraph [0056]; figures 1,2,5a,5b,6 * -----	3-6,11, 12	
Y	US 2009/167648 A1 (JEON CHANG HOON [KR] ET AL) 2 July 2009 (2009-07-02) * paragraphs [0005] - [0008], [0025] - [0028], [0041] - [0045]; figures 2,4 * -----	3,4	TECHNICAL FIELDS SEARCHED (IPC) G09G
Y	US 2007/063959 A1 (IWABUCHI TOMOYUKI [JP] ET AL) 22 March 2007 (2007-03-22) * paragraphs [0002] - [0004], [0080] - [0092]; figures 1-3 * -----	5,11	
The present search report has been drawn up for all claims			
Place of search Munich		Date of completion of the search 17 September 2010	Examiner Harke, Michael
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

1
EPO FORM 1503 03.82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 10 25 1386

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

17-09-2010

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 1391871	A1	25-02-2004	CN 1485806 A	31-03-2004
			JP 2004078124 A	11-03-2004
			KR 20040018191 A	02-03-2004
			TW 225630 B	21-12-2004
			US 2004036669 A1	26-02-2004

US 2002180673	A1	05-12-2002	CN 1440514 A	03-09-2003
			EP 1296174 A1	26-03-2003
			WO 0184226 A1	08-11-2001
			TW 573167 B	21-01-2004

US 2006097974	A1	11-05-2006	CN 1783173 A	07-06-2006
			JP 2006133551 A	25-05-2006

US 2009167648	A1	02-07-2009	CN 101471032 A	01-07-2009
			KR 20090070371 A	01-07-2009

US 2007063959	A1	22-03-2007	EP 1917656 A1	07-05-2008
			WO 2007013646 A1	01-02-2007

专利名称(译)	有机发光显示器及其驱动方法		
公开(公告)号	EP2284826A1	公开(公告)日	2011-02-16
申请号	EP2010251386	申请日	2010-08-03
[标]申请(专利权)人(译)	三星显示有限公司		
申请(专利权)人(译)	三星移动显示器有限公司.		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	PARK SUNG UN PARK SUNG CHEON LEE WOOK		
发明人	PARK, SUNG-UN PARK, SUNG-CHEON LEE, WOOK		
IPC分类号	G09G3/32		
CPC分类号	G09G3/3233 G09G2310/0297 G09G2330/022		
优先权	1020090071274 2009-08-03 KR		
外部链接	Espacenet		

摘要(译)

一种有机发光显示器及其驱动方法，能够降低待机模式下的功耗以增加电池的使用时间。有机发光显示器包括像素单元（101），用于通过利用多个帧并根据数据信号和扫描信号显示图像；数据驱动器（200），用于输出数据信号；扫描驱动器（300），用于输出扫描信号；控制器（500），用于控制数据驱动器和扫描驱动器，使得在多个帧的至少一帧中，扫描信号不被发送到像素单元。

FIG. 2

