



(12) **EUROPEAN PATENT APPLICATION**
published in accordance with Art. 153(4) EPC

(43) Date of publication:
05.04.2017 Bulletin 2017/14

(51) Int Cl.:
G09G 3/32 (2016.01)

(21) Application number: **14868726.2**

(86) International application number:
PCT/CN2014/087632

(22) Date of filing: **28.09.2014**

(87) International publication number:
WO 2015/180341 (03.12.2015 Gazette 2015/48)

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR
Designated Extension States:
BA ME

(72) Inventors:
• **XIE, Hongjun**
Beijing 100176 (CN)
• **ZHANG, Weiqiang**
Beijing 100176 (CN)

(30) Priority: **30.05.2014 CN 201410240219**

(74) Representative: **Klunker . Schmitt-Nilson . Hirsch**
Patentanwälte
Destouchesstraße 68
80796 München (DE)

(71) Applicant: **BOE Technology Group Co., Ltd.**
Beijing 100015 (CN)

(54) **DRIVE CIRCUIT AND ORGANIC ELECTROLUMINESCENT DISPLAY DEVICE**

(57) There are disclosed a driving circuit of an organic light emitting display panel and an organic light emitting display apparatus. The driving circuit comprises: a power supply detection circuit configured to detect an operating state of an external input power supply, send a normal signal of power supply detection when it is determined that the external input power supply is in a normal state, and send a abnormal signal of power supply detection when it is determined that the external input power supply is in an abnormal state; a clock control circuit configured to convert a received video data into image data recognizable by the organic light emitting display panel and

then output it to the organic light emitting display panel when the normal signal of power supply detection sent by the power supply detection circuit is received, and output image data of black picture to the organic light emitting display panel when the abnormal signal power supply detection sent by the power supply detection circuit is received. In this way, pixel charges accumulated on respective display pixels can be released, which avoids transistors inside the display pixels from producing stress, and finally avoids occurrence of shutdown image sticking due to power-down.




Fig.1

Description

TECHNICAL FIELD

[0001] The present disclosure relates to a driving circuit of an organic light emitting display panel and an organic light emitting display apparatus.

BACKGROUND

[0002] An organic light emitting diode (OLED) is a hot topic in the flat panel display research field. Compared with a liquid crystal display, OLED has advantages of low power consumption, low production cost, self-luminescent, wide view angle and fast response speed and so on. At present, in the display field of mobile phone, PDA, and digital camera and the like, OLED has taken place of the traditional LCD display screen.

[0003] A user's voluntary shutdown or an abnormal shutdown caused by a sudden power-down may occur to the existing OLED in the process of using. In the case of the sudden power-down, there exist in the OLED display panel the phenomenon that pixel charges remained inside respective display pixels to make transistors inside the display pixels produce stress, which causes that images stagnate and fade away gradually within a short period of time after the display screen is powered down. This abnormal phenomenon becomes shutdown image sticking, and the shutdown image sticking would leave a mark inside the display screen. Residual images may be viewed when the display screen is power on next time, which influences the user's visual perception.

[0004] Therefore, how to eliminate the shutdown image sticking phenomenon when OLED is shut down abnormally is a problem urgently to be solved in the OLED display field.

SUMMARY

[0005] Given that, there provide in embodiments of the present disclosure a driving circuit of an organic light emitting display panel and an organic light emitting display apparatus, which are used to solve the problem of shutdown image sticking that occurs when the existing OLED is shut down abnormally.

[0006] According to one aspect of the present disclosure, there is provided a driving circuit of an organic light emitting display panel, comprising:

- a power supply detection circuit configured to detect an operating state of an external input power supply, send a normal signal of power supply detection when it is determined that the external input power supply is in a normal state, and send a abnormal signal of power supply detection when it is determined that the external input power supply is in an abnormal state;
- a clock control circuit configured to convert a re-

ceived video data into image data recognizable by the organic light emitting display panel and then output it to the organic light emitting display panel when the normal signal of power supply detection sent by the power supply detection circuit is received, and output image data of black picture to the organic light emitting display panel when the abnormal signal of power supply detection sent by the power supply detection circuit is received.

[0007] In the driving circuit of the above organic light emitting display panel of the embodiment of the present disclosure, it is indicated that voltage of the external input power supply starts to be powered down when the power supply detection circuit detects that the operating state of the external input power supply is the abnormal state. Due to hysteresis of power supply of the driving circuit, the driving circuit will be maintained operating normally for a short period of time, and at this time the power supply detection circuit outputs the abnormal signal of power supply detection to the clock control circuit. The clock control circuit changes from sending normal image data to the organic light emitting display panel into sending black picture image data to the organic light emitting display panel after receiving the abnormal signal. The organic light emitting display panel can release pixel charges accumulated on respective display pixels when displaying the black picture image, which avoids transistors inside the display pixels from producing stress, and finally avoids occurrence of shutdown image sticking due to power-down.

[0008] In an alternative implementation, in the above driving circuit provided in the embodiment of the present disclosure, the power supply detection circuit can comprise:

- an input unit configured to obtain an alternating current voltage of the external input power supply and perform rectifying process on the external input power supply;
- a detection unit configured to detect an operating state of the alternating current voltage of the external input power supply processed by the input unit;
- an output unit configured to send the normal signal of power supply detection to the clock control circuit when the detection unit determines that the external input power supply is in the normal state, and send the abnormal signal of power supply detection to the clock control circuit when the detection unit determines that the external input power supply is in the abnormal state.

[0009] In an alternative implementation, in the above driving circuit of the embodiment of the present disclosure, the detection unit can be configured to determine that the external input power supply is in the normal state when it is determined that a ratio of a voltage value of the external input power supply to a reference voltage

value is greater than a predetermined threshold value, and determine that the external input power supply is in the abnormal state when it is determined that a ratio of a voltage value of the external input power supply to a reference voltage value is not greater than the predetermined threshold value.

[0010] In an alternative implementation, in the above driving circuit of the embodiment of the present disclosure, the predetermined threshold value set in the detection unit is 0.6-0.85.

[0011] In an alternative implementation, in the above driving circuit of the embodiment of the present disclosure, the normal signal of power supply detection and the abnormal signal of power supply detection output by the output unit are LVTTTL signals.

[0012] In an alternative implementation, in the above driving circuit of the embodiment of the present disclosure, it further comprises: a power supply circuit configured to provide power supply for respective circuits in the driving circuit after converting the received alternating current voltage of the external input power supply into a direct current voltage required by the respective circuits.

[0013] In an alternative implementation, in the above driving circuit of the embodiment of the present disclosure, the power supply detection circuit is integrated in the power supply circuit.

[0014] In an alternative implementation, in the above driving circuit of the embodiment of the present disclosure, it further comprises: a system circuit configured to receive an external video signal, convert the external video signal into video data and then output it to the clock control circuit.

[0015] According to another aspect, there is provided an organic light emitting display apparatus comprising the organic light emitting display panel and the driving circuit of the organic light emitting display panel of the embodiments of the present disclosure.

BRIEF DESCRIPTION OF THE DRAWINGS

[0016]

Fig.1 is a schematic diagram of a structure of a driving circuit in an embodiment of the present disclosure;

Fig.2 is a schematic diagram of a structure of a power supply detection circuit in the driving circuit in an embodiment of the present disclosure;

Fig.3 is a schematic diagram of a specific circuit of a power supply detection circuit in a driving circuit in an embodiment of the present disclosure;

Fig.4 is a schematic diagram of operations in respective phases of a driving circuit in an embodiment of the present disclosure.

DETAILED DESCRIPTION

[0017] Specific implementations of a driving circuit of

an organic light emitting display panel and an organic light emitting display apparatus in embodiments of the present disclosure will be described in detail below by combining with the accompanying figures.

[0018] Fig.1 shows schematically a driving circuit 100 of an organic light emitting display panel in an embodiment of the present disclosure. As shown in Fig.1, the driving circuit 100 comprises: a power supply detection circuit 110 and a clock control circuit 120.

[0019] The power supply detection circuit 110 is configured to detect an operating state of an external input power supply 200, sends a normal signal of power supply detection to the clock control circuit 120 when it is determined that the external input power supply 200 is in a normal state, and sends an abnormal signal of power supply detection to the clock control circuit 120 when it is determined that the external input power supply 200 is in an abnormal state.

[0020] The clock control circuit 120 is configured to convert a received video data into image data that can be recognized by an organic light emitting display panel 300 and then output it to the organic light emitting display panel 300 when the normal signal of power supply detection is received, and output black picture image data to the organic light emitting display panel 300 when the abnormal signal of power supply detection is received.

[0021] In the driving circuit of the organic light emitting display panel in the embodiment of the present disclosure as shown in Fig.1, it is indicated that voltage of the external input power supply 200 starts to be powered down when the power supply detection circuit 110 detects that the operating state of the external input power supply 200 is the abnormal state. Due to the hysteresis of power supply of the power supply circuit in the driving circuit 100, the driving circuit 100 can still be maintained operating normally for a short period of time. Now, the power supply detection circuit 100 outputs the abnormal signal of power supply detection to the clock control circuit 120. The clock control circuit 120 changes from sending normal image data to the organic light emitting display panel 300 into sending black picture image data to the organic light emitting display panel 300 after having received the abnormal signal. The organic light emitting display panel 300 can release pixel charges accumulated on respective display pixels when displaying the black picture image, which avoids transistors inside the display pixels from producing stress, and finally avoids occurrence of shutdown image sticking due to the power-down.

[0022] Fig.2 schematically shows the structure of the power supply detection circuit 110 in the driving circuit 100 in the embodiment of the present disclosure. As shown in Fig.2, the power supply detection circuit 110 can comprise:

an input unit 111 configured to obtain an alternating current voltage of the external input power supply, and perform rectifying process on the alternating current voltage of the external input power supply;

an detection unit 112 configured to detect an operating state of the alternating current voltage of the external input power supply 200 processed by the input unit 111;

an output unit 113 configured to send the normal signal of power supply detection to the clock control circuit 120 when the detection unit 112 determines that the external input power supply 200 is in the normal state, and send the abnormal signal of power supply detection to the clock control circuit 120 when the detection unit 112 determines that the external input power supply 200 is in the abnormal state.

[0023] Alternatively, the normal signal of power supply detection and the abnormal signal of power supply detection outputted by the output unit 113 in the power supply detection circuit 110 can adopt LVTTTL signals, and generally adopt LVTTTL (Low Voltage TTL) signals of 3.3V in a level standard. For example, a high level LVTTTL signal can be used as the normal signal of power supply detection and a low level LVTTTL signal can be used as the abnormal signal of power supply detection. The high level LVTTTL signal herein refers to LVTTTL signals of 2.2V-3.3V, and the low level LVTTTL signal herein refers to LVTTTL signals of 0-0.9V.

[0024] Exemplarily, when the detection unit 112 in the power supply detection circuit 110 detects the operating state of the alternating current voltage of the external input power supply 200 processed by the input unit 111, it can determine whether the external input power supply 200 operates normally in a manner of comparing a voltage value of the external input power supply 200 with a reference value. For example, it can be determined that the external input power supply 200 is in the normal state when it is determined that a ratio of the voltage value of the external input power supply 200 to the reference voltage value is greater than a predetermined threshold value; and it can be determined that the external input power supply 200 is in the abnormal state when it is determined that a ratio of the voltage value of the external input power supply 200 to the reference voltage value is not greater than the predetermined threshold value.

[0025] Exemplarily, the predetermined threshold value set in the detection unit 112 can be generally set between 0.6 and 0.85. For example, the alternating current voltage of the external input power supply is in general 220V, and 220V can be taken as the reference voltage. When a drop of the voltage of the external input power supply 200 received by the power supply detection circuit 110 exceeds 20% of 200V, it can be regarded that the external input power supply 200 starts to be powered down, that is, it is regarded that the external input power supply 200 is in the abnormal state. When the drop of the voltage of the external input power supply 200 received by the power supply detection circuit 110 does not exceed 20% of 200V, it can be regarded that the external input power supply 200 is in the normal state.

[0026] Fig.3 schematically shows the circuit structure

of the input unit 111, the detection unit 112 and the output unit 113 in the power supply detection circuit 110. The circuit structure is just illustrated for description. In the actual application, a circuit structure can be taken as the power supply detection circuit only if it can realize functions of the above units.

[0027] As shown in Fig.1, the driving circuit 100 in the embodiment of the present disclosure can generally comprise: a power supply circuit 130 configured to convert the received alternating current voltage of the external input power supply 200 into a direct current voltage required by respective circuits in the driving circuit 100 and then provide power supply for the circuits. At present, the external input power supply 200 is input generally the alternating current voltage of 220V, and the power supply circuit 130 can convert the alternating current voltage into the direct current voltage of several channels and output it to a corresponding circuit in the driving circuit to provide power supply for the circuit. In addition, there are relatively large capacitors and inductive coils in the power supply circuit 130 generally. When the alternating current voltage of the external input power supply 200 starts to be powered down, these components can make the output voltage VDD of the power supply circuit 130 maintained normal for a period of time, so that the driving circuit 100 can operate temporally.

[0028] For example, in order to raise integration level of the driving circuit, in the actual operation, as shown in Fig.1, the power supply detection circuit 110 can be integrated in the power supply circuit 130, that is, the power supply detection circuit 110 is manufactured in the same circuit board as a newly added module of the power supply circuit 130. In this way, the utilization rate of the circuit board can be raised, which is advantageous for reducing the number of components in the display device.

[0029] As shown in Fig.1, the driving circuit 100 in the embodiment of the present disclosure can generally comprise: a system circuit 140 configured to receive an external video signal, convert the external video signal into video data and then output it to the clock control circuit 120. After receiving the video data send by the system circuit, the clock control circuit 120 forms image data through a series of algorithms and processes. When the clock control circuit 120 receives the normal signal of power supply detection, the image data is directly sent to the organic light emitting display panel to be displayed.

[0030] Fig.4 schematically shows a complete operating process of the driving circuit 100 in the embodiment of the present disclosure from normal operation to power-down. For example, this operating process can be divided into following three phases:

[0031] A first phase T1: the external input power supply 200 operates normally, and the power supply circuit 130 provides a normal direct current voltage VDD to the system circuit 140 and the clock control circuit 120. At this time, the power supply detection circuit 110 detects that the operating state of the external input power supply 200 is normal, and sends the high level LVTTTL signal to

the clock control circuit 120. When receiving the high level LVTTTL signal, the clock control circuit 120 converts the video data sent by the system circuit 140 into image data and then sends it to the organic light emitting display panel 300 to be displayed normally.

[0032] A second phase T2: abnormality occurs to the external input power supply 200, and the drop of the input voltage exceeds 20% of 200V. The power supply circuit 130 has a relatively large capacitor and inductive coil, so that the power supply circuit 130 can provide the normal direct current voltage VDD to the system circuit 140 and the clock control circuit 120. At this time, the power supply detection circuit 110 detects that the operating state of the external input power supply 200 is abnormal, and send the low level LVTTTL signal to the clock control circuit 120. When receiving the low level LVTTTL signal, the clock control circuit 120 outputs image data of the black picture so that the organic light emitting display panel 300 displays the black picture. When displaying the black picture image, the organic light emitting display panel 300 can release the pixel charges accumulated on the respective display pixels, so as to avoid the transistors inside the display pixels from producing stress.

[0033] A third phase T3: due to power-down, the final input voltage of the external input power supply 200 is 0V, it is not enough for the power supply circuit 130 to maintain providing the normal direct current voltage VDD to the system circuit 140 and the clock control circuit 120. That is, VDD starts to drop to 0V, the system circuit 140 and the clock control circuit 120 stop operating, and the organic light emitting display panel 300 suffers a black screen.

[0034] It can be seen from the operating process of the above driving circuit that when the power supply circuit 130 can output the normal direct current voltage VDD in the second phase, the organic light emitting display panel 300 has started to display the black picture. In this way, it can ensure that the organic light emitting display panel 300 display the black picture when the clock control circuit 120 cannot operate, which avoids the problem of image sticking.

[0035] Based on the same inventive concept, the embodiments of the present disclosure further provide an organic light emitting display apparatus comprising the organic light emitting display panel and the driving apparatus of the organic light emitting display panel in the embodiments of the present disclosure. The display apparatus can be any product or components having the display function, such as a mobile phone, a tablet computer, a television, a display, a notebook computer, a digital photo frame, a navigator and so on. The implementation of the display apparatus can refer to the embodiments of the driving circuit, and thus no further description is given repetitively herein.

[0036] In the driving circuit of the organic light emitting display panel and the organic light emitting display apparatus of the embodiments of the present disclosure, it is indicated that voltage of the external input power supply

starts to be powered down when the power supply detection circuit detects that the operating state of the external input power supply is the abnormal state. Due to hysteresis of power supply of the driving circuit, the driving circuit will be maintained operating normally for a short period of time, and at this time the power supply detection circuit outputs the abnormal signal of power supply detection to the clock control circuit. The clock control circuit changes from sending normal image data to the organic light emitting display panel into sending black picture image data to the organic light emitting display panel after receiving the abnormal signal. The organic light emitting display panel can release pixel charges accumulated on respective display pixels when displaying the black picture image, which avoids transistors inside the display pixels from producing stress, and finally avoids occurrence of shutdown image sticking due to power-down.

[0037] Obviously, those skilled in the art can make various amendments and modifications to the embodiments of the present disclosure without departing from the spirit and scope of the present disclosure. As such, if these amendments and modifications of the present disclosure fall into the scope of the claims of the specification as well as equivalents thereof, the present disclosure intends to include these amendments and modifications.

[0038] The present application claims the priority of a Chinese patent application No. 201410240219.9 filed on May 30, 2014. Herein, the content disclosed by the Chinese patent application is incorporated in full by reference as a part of the present disclosure.

Claims

1. A driving circuit of an organic light emitting display panel, comprising:

a power supply detection circuit configured to detect an operating state of an external input power supply, send a normal signal of power supply detection when it is determined that the external input power supply is in a normal state, and send an abnormal signal of power supply detection when it is determined that the external input power supply is in an abnormal state;

a clock control circuit configured to convert a received video data into image data recognizable by the organic light emitting display panel and then output it to the organic light emitting display panel when the normal signal of power supply detection sent by the power supply detection circuit is received, and output image data of black picture to the organic light emitting display panel when the abnormal signal of power supply detection sent by the power supply detection circuit is received.

2. The driving circuit according to claim 1, wherein the power supply detection circuit comprises:

an input unit configured to obtain an alternating current voltage of the external input power supply and perform rectifying process on the alternating current voltage of the external input power supply;
 a detection unit configured to detect an operating state of the alternating current voltage of the external input power supply processed by the input unit;
 an output unit configured to send the normal signal of power supply detection to the clock control circuit when the detection unit determines that the external input power supply is in the normal state, and send the abnormal signal of power supply detection to the clock control circuit when the detection unit determines that the external input power supply is in the abnormal state.

to the clock control circuit.

9. An organic light emitting display apparatus comprising the organic light emitting display panel and the driving circuit of the organic light emitting display panel according to any one of claims 1-8,

3. The driving circuit according to claim 2, wherein the detection unit is configured to determine that the external input power supply is in the normal state when a ratio of a voltage value of the external input power supply to a reference voltage value is greater than a predetermined threshold value, and determine that the external input power supply is in the abnormal state when the ratio of the voltage value of the external input power supply to the reference voltage value is not greater than the predetermined threshold value.
4. The driving circuit according to claim 3, wherein the predetermined threshold value set in the detection unit is 0.6-0.85.
5. The driving circuit according to claim 2, wherein the normal signal of power supply detection and the abnormal signal of power supply detection output by the output unit are LVTTTL signals.
6. The driving circuit according to any one of claims 1 to 5, further comprising: a power supply circuit configured to provide power supply for respective circuits in the driving circuit after converting the received alternating current voltage of the external input power supply into a direct current voltage required by the respective circuits.
7. The driving circuit according to claim 6, wherein the power supply detection circuit is integrated in the power supply circuit.
8. The driving circuit according to any one of claims 1 to 5, further comprising: a system circuit configured to receive an external video signal, convert the external video signal into video data and then output it




Fig.1




Fig.2




Fig.3




Fig.4

INTERNATIONAL SEARCH REPORT

International application No.
PCT/CN2014/087632

A. CLASSIFICATION OF SUBJECT MATTER

G09G 3/32 (2006.01) i

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

G09G

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

CPRSABS; CNABS; VEN: driv+, G09G3/32, power, detect+, timing, panel?, clock

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	TW 554322 B (AU OPTRONICS CORP.) 21 September 2003 (21.09.2003) description, page 5-8, the claims, and figures 1-4	1-9
X	CN 1920925 A (QUNKANG SCI & TECHNOLOGY SHENZHEN CO., LTD. et al.) 28 February 2007 (28.02.2007) description, pages 1 and 2, and figures 1 and 2	1-9
X	US 2008165099 A1 (SAMSUNG ELECTRONICS CO., LTD. et al.) 10 July 2008 (10.07.2008) description, paragraphs [0019]-[0046], and figures 1-7	1-9
A	CN 102103835 A (CHUNGHWA PICTURE TUBES CO., LTD. et al.) 22 June 2011 (22.06.2011) the whole document	1-9

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"A" document defining the general state of the art which is not considered to be of particular relevance	
"E" earlier application or patent but published on or after the international filing date	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"O" document referring to an oral disclosure, use, exhibition or other means	
"P" document published prior to the international filing date but later than the priority date claimed	"&" document member of the same patent family

Date of the actual completion of the international search
12 February 2015

Date of mailing of the international search report
02 March 2015

Name and mailing address of the ISA
State Intellectual Property Office of the P. R. China
No. 6, Xitucheng Road, Jimenqiao
Haidian District, Beijing 100088, China
Facsimile No. (86-10) 62019451

Authorized officer
XI, Wanhua
Telephone No. (86-10) 62085833

INTERNATIONAL SEARCH REPORT

International application No.
PCT/CN2014/087632

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	CN 1588528 A (AU OPTRONICS CORP.) 02 March 2005 (02.03.2005) the whole document	1-9
A	US 2008129903 A1 (LG DISPLAY CO., LTD. et al.) 05 June 2008 (05.06.2008) the whole document	1-9
A	US 2008129903 A1 (LG DISPLAY CO., LTD. et al.) 05 June 2008 (05.06.2008) the whole document	1-9

Form PCT/ISA /210 (continuation of second sheet) (July 2009)

INTERNATIONAL SEARCH REPORT
Information on patent family members

International application No.
PCT/CN2014/087632

Patent Documents referred in the Report	Publication Date	Patent Family	Publication Date
TW 554322 B	21 September 2003	US 2002041279 A1	11 April 2002
		US 6476590 B2	05 November 2002
		JP 2002175063 A	21 June 2002
CN 1920925 A	28 February 2007	CN 100403392 C	16 July 2008
US 2008165099 A1	10 July 2008	KR 20080064280 A	09 July 2008
CN 102103835 A	22 June 2011	None	
CN 1588528 A	02 March 2005	CN 100373218 C	05 March 2008
US 2008129903 A1	05 June 2008	US 8125424 B2	28 February 2012
		KR 20080049592 A	04 June 2008
		KR 1362155 B	13 February 2014

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- CN 201410240219 [0038]

专利名称(译)	驱动电路和有机电致发光显示装置		
公开(公告)号	EP3151231A1	公开(公告)日	2017-04-05
申请号	EP2014868726	申请日	2014-09-28
[标]申请(专利权)人(译)	京东方科技集团股份有限公司		
申请(专利权)人(译)	京东方科技集团股份有限公司.		
当前申请(专利权)人(译)	京东方科技集团股份有限公司.		
[标]发明人	XIE HONGJUN ZHANG WEIQIANG		
发明人	XIE, HONGJUN ZHANG, WEIQIANG		
IPC分类号	G09G3/32 G09G3/3208		
CPC分类号	G09G3/3233 G09G3/3225 G09G3/3258 G09G2310/0245 G09G2310/08 G09G2320/0257 G09G2320/046 G09G2330/027 G09G2330/04 G09G2330/12		
优先权	201410240219.9 2014-05-30 CN		
其他公开文献	EP3151231A4		
外部链接	Espacenet		

摘要(译)

公开了一种有机发光显示面板的驱动电路和有机发光显示装置。驱动电路包括：电源检测电路，用于检测外部输入电源的工作状态，当确定外部输入电源处于正常状态时，发送电源检测的正常信号，并发送当确定外部输入电源处于异常状态时，电源检测的异常信号；时钟控制电路，用于将接收到的视频数据转换为有机发光显示面板可识别的图像数据，并在接收到电源检测电路发送的电源检测正常信号时，将其输出到有机发光显示面板当接收到由电源检测电路发送的异常信号电源检测时，将黑色图像的图像数据输出到有机发光显示面板。以这种方式，可以释放在各个显示像素上累积的像素电荷，这避免了显示像素内的晶体管产生应力，并且最终避免由于掉电而发生关闭图像残留。




Fig.1