



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
03.10.2012 Bulletin 2012/40

(51) Int Cl.:
G09G 3/20 (2006.01) **G09G 3/32** (2006.01)
H01L 27/32 (2006.01)

(21) Application number: **11005894.8**

(22) Date of filing: **19.07.2011**

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR
Designated Extension States:
BA ME

(72) Inventors:
• **Liu, Chih-Chi**
Hsin-Chu
(TW)
• **Tsai, Tze-Chien**
Hsin-Chu
(TW)

(30) Priority: **28.03.2011 US 73387**

(71) Applicant: **AU Optonics Corporation**
Hsin-Chu (TW)

(74) Representative: **Günther, Constantin et al**
Gramm, Lins & Partner GbR
Freundallee 13a
30173 Hannover (DE)

(54) **Electroluminescent display and method of driving same**

(57) In one aspect of the present invention, an electroluminescent (EL) display device has a plurality of pixels spatially arranged in a form of a matrix, each pixel having a first EL element, a second EL element, a third EL element, and a fourth EL element, a plurality of gate lines, each gate line coupled to a respective row of pixels, a plurality of first data lines, each first data line coupled to the first EL elements of a respective column of pixels, a plurality of second data lines, each second data line coupled to the second EL elements of a respective column of pixels, a plurality of first switches, each first switch coupled to a respective third EL element, a plurality of second switches, each second switch coupled to a respective fourth EL element, a switch control line coupled

to the plurality of first switches and the plurality of second switches for providing a switching control signal to set the first switches and the second switches to be in an ON state or an OFF state, such that when the first switches are cooperatively in the ON state, the second switches are cooperatively in the OFF state, and vice versa, and a plurality of third data lines, each third data line coupled to the first switches and the second switches corresponding to a respective column of pixels for transmitting a data signal, such that when the first switches are cooperatively in the ON state, the data signal is provided to the third EL elements of the respective column of pixels, and when the second switches are cooperatively in the ON state, the data signal is provided to the fourth EL elements of the respective column of pixels.




FIG. 1

Description**FIELD OF THE INVENTION**

[0001] The present invention relates generally to an electroluminescent (EL) display, and more particularly to an EL display device with each pixel having four light emitting elements and methods of driving same.

BACKGROUND OF THE INVENTION

[0002] Display devices employing electroluminescent display elements, such as organic light emitting diodes (OLEDs), have become a popular choice among flat panel displays. EL displays are used as television screens, computer monitors, portable electronic systems such as mobile phones and personal digital assistants (PDAs). An OLED is a light emitting diode (LED) in which the emissive electroluminescent (EL) layer is a film of an organic material which emit light in response to an electric current. This layer of organic material is situated between two electrodes. Generally, at least one of these electrodes is transparent. An EL display functions without a backlight. Thus, it can display deep black levels and can also be thinner and lighter than other flat panel displays such liquid crystal displays (LCDs).

[0003] An EL display panel may comprise a plurality of pixels spatially arranged in a form of a matrix with a plurality of rows and a plurality of columns in a display area. For a color EL display panel, each pixel may comprise several OLEDs each emitting light of a different color in the visible spectrum from which various colors may be composed. FIG. 8(a) shows schematically a typical pixel 810 for a color EL display panel that has three light emitting elements 812, each emitting red (R), green (G), and blue (B) light, respectively. The traditional organic material used for blue OLEDs has a relatively low luminous efficiency. Consequently, a relatively large electrical current is required in order for a blue OLED to emit light with a certain intensity. Operating an OLED at the large electrical currents would have the adverse effect of shortening the lifetime of the OLED.

[0004] Recently, a new material of emitting yellow-green light with a higher luminous efficiency has been reported. Table 1 summarizes the luminous efficiencies for four EL materials used in color EL displays. In this table, R stands for an EL material for red OLEDs, G stands for an EL material for green OLEDs, B2 stands for a traditional EL material for blue OLEDs, and B1 stands for a new EL material for yellow-green OLEDs. The 1931 CIE color space (x, y) parameters associated with the light emitted by these materials are also listed. As can be seen in Table 1, the new EL material B1 for yellow-green OLEDs has a luminous efficiency that is more than four times that of the traditional EL material B2 for blue OLEDs. The new material B1 may be used in addition to the traditional material B2 for producing blue light in a color EL display panel.

Table 1: the luminous efficiencies for four EL materials used in color EL displays

Material	1931 CIE (x, y)	Luminous Efficiency (cd/A)
R	(0.67, 0.33)	35
G	(0.21, 0.70)	90
B2	(0.14, 0.06)	5
B1	(0.114, 0.148)	22.5

[0005] FIG. 8(b) shows a pixel 820 for a color EL display panel that includes four light emitting elements 822, one emitting red light (R), one emitting green light (G), one emitting yellow-green light (B1), and one emitting blue light (B2). The four light emitting elements 822 are spatially arranged as a 2x2 sub-array.

[0006] FIG. 9 shows schematically an EL display device 900 that has such a pixel arrangement as FIG. 8(b). The EL display device 900 includes a plurality of pixels 910 spatially arranged in a form of a matrix with a plurality of rows and a plurality of columns. Each pixel 910 includes four light emitting elements 912 labeled as R, G, B1, and B2, respectively, according to the color of the light emitted by the elements. The EL display device 900 includes a plurality of gate lines GAn and GBn (n=1,2,...) and a plurality of data lines SAn and SBn (n=1,2,...). Each gate line GAn is coupled to the R and B1 elements of a respective row of pixels, and each gate line GBn is coupled to the G and B2 elements of a respective row of pixels. A gate driver outputs scanning signals to the plurality of gate lines GAn and GBn sequentially so that the elements in the pixels are sequentially driven in a row-by-row fashion. Each data line SAn is coupled to the R and G elements of a respective column of pixels, and each data line SBn is coupled to the B1 and B2 elements of a respective column of pixels. Therefore, in this configuration, two gate lines GAn and GBn are required for each row of pixels and two data lines SAn and SBn are required for each column of pixels. For example, for a display panel with a 240x320 resolution, there would be 480 total data lines and 640 total gate lines. In comparison, for a display with the same

resolution but comprising RGB pixels as shown in FIG. 8(a), the required data lines and gate lines would be 720 and 320, respectively. Therefore, the display device 900 requires twice the number of gate lines as that required in a display panel with the same resolution comprising RGB pixels. Consequently, the scan driver is more complicated which in turn results in higher cost.

[0007] Therefore, a heretofore unaddressed need exists in the art to address the aforementioned deficiencies and inadequacies.

SUMMARY OF THE INVENTION

[0008] The present invention, in one aspect, relates to an electroluminescent (EL) display device. In one embodiment, the EL display device includes a plurality of pixels spatially arranged in a form of a matrix with a plurality of rows and a plurality of columns, each pixel has a first EL element operably emitting light of a first color, a second EL element operably emitting light of a second color, a third EL element operably emitting light of a third color, and a fourth EL element operably emitting light of a fourth color. In one embodiment, the first color is a red color, the second color is a green color, the third color is a yellow-green color and the fourth color is a blue color. In one embodiment, the first EL element, the second EL element, the third EL element and the fourth EL element of each pixel are spatially arranged as a 2x2 sub-array.

[0009] The EL display device also includes a plurality of gate lines. Each gate line is coupled to a respective row of pixels.

[0010] The EL display device further includes a plurality of first data lines, a plurality of second data lines, and a plurality of third data lines. Each first data line is coupled to the first EL elements of a respective column of pixels. Each second data line is coupled to the second EL elements of a respective column of pixels.

[0011] Additionally, the EL display device includes a plurality of first switches, a plurality of second switches, and a plurality of switch control lines. Each first switch coupled to a respective third EL element. Each second switch coupled to a respective fourth EL element. The first switches coupled to the third EL elements of a respective column of pixels are configured to be cooperatively in an ON state or an OFF state. The second switches coupled to the fourth EL elements of a respective column of pixels are configured to be cooperatively in an ON state or an OFF state. Each switch control line is coupled to the first switches and the second switches corresponding to a respective column of pixels for transmitting a switching control signal to set the first switches and the second switches to be in the ON state or the OFF state, such that when the first switches are cooperatively in the ON state, the second switches are cooperatively in the OFF state, and vice versa.

[0012] Further, each third data line coupled to the first switches and the second switches corresponding to a respective column of pixels for transmitting a data signal, such that when the first switches are cooperatively in the ON state, the data signal is provided to the third EL elements of the respective column of pixels, and when the second switches are cooperatively in the ON state, the data signal is provided to the fourth EL elements of the respective column of pixels.

[0013] In one embodiment, the EL display device may also have an image processor for processing an image to be displayed according to the pixel matrix of the EL display device such that the processed image has a plurality of pixel data signals, each pixel data signal being associated with a respective pixel and having a first sub-pixel data signal, a second sub-pixel data signal, a third sub-pixel data signal and a fourth sub-pixel data signal indicating intensities for the first EL element, the second EL element, the third EL element and the fourth EL element, respectively, of the respective pixel, and a selector configured to compare the third sub-pixel data signal and the fourth sub-pixel data signal of each pixel, to assign a logic value of 1 to the corresponding pixel if the third sub-pixel data signal is greater than or equal to the fourth sub-pixel data signal, or a logic value of 0 to the corresponding pixel if the third sub-pixel data signal is less than the fourth sub-pixel data signal, and to count the number of the logic value of 1, NB1, and the number of the logic value of 0, NB2, of each column of pixels.

[0014] In one embodiment, the switching control signal for a respective column of pixels is configured to set the first switches and the second switches corresponding to the respective column of pixels in the ON state and the OFF state, respectively, if $NB1 \geq NB2$ for the respective column of pixels, and the first switches and the second switches in the OFF state and the ON state, respectively, if $NB1 < NB2$ for the respective column of pixels.

[0015] In one embodiment, the switching control signal for a respective column of pixels is characterized with a waveform having a low voltage and a high voltage. When the switching control signal for the respective column of pixels has one of the low voltage and the high voltage, the first switches and the second switches corresponding to the respective column of pixels are set in the ON state and the OFF state, respectively. When the switching control signal for the respective column of pixels has the other of the low voltage and the high voltage, the first switches and the second switches corresponding to the respective column of pixels are set in the OFF state and the ON state, respectively.

[0016] In one embodiment, each of the plurality of first switches comprises one of an N-type thin film transistor (TFT) and a P-type TFT, and each of the plurality of second switches comprises the other of the N-type TFT and the P-type TFT, wherein each of the N-type TFT and the P-type TFT has a gate, a source and a drain. The gate, source and drain of each N-type TFT are respectively coupled to a corresponding switching control line, a corresponding third data line

and one of the third EL element and the fourth EL element of a corresponding pixel. The gate, source and drain of each P-type TFT are respectively coupled to the corresponding switching control line, the corresponding third data line and the other of the third EL element and the fourth EL element of the corresponding pixel.

[0017] In another aspect, the present invention relates to a method of driving the EL display device disclosed above.

In one embodiment, the method includes the steps of processing an image to be displayed according to the pixel matrix of the EL display device such that the processed image has a plurality of pixel data signals, each pixel data signal being associated with a respective pixel and having a first sub-pixel data signal, a second sub-pixel data signal, a third sub-pixel data signal and a fourth sub-pixel data signal indicating intensities for the first EL element, the second EL element, the third EL element and the fourth EL element, respectively, of the respective pixel, and comparing the third sub-pixel data signal and the fourth sub-pixel data signal of each pixel, assigning a logic value of 1 to the corresponding pixel if the third sub-pixel data signal is greater than or equal to the fourth sub-pixel data signal, or a logic value of 0 to the corresponding pixel if the third sub-pixel data signal is less than the fourth sub-pixel data signal, counting the number of the logic value of 1, NB 1, and the number of the logic value of 0, NB2, of each column of pixels, and configuring the switching control signal for a respective column of pixels so as to set the first switches and the second switches corresponding to the respective column of pixels in the ON state and the OFF state, respectively, if $NB1 \geq NB2$ for the respective column of pixels, and the first switches and the second switches in the OFF state and the ON state, respectively, if $NB1 < NB2$ for the respective column of pixels.

[0018] In yet another aspect, the present invention relates to an EL display device. In one embodiment, the EL display device has a plurality of pixels spatially arranged in a form of a matrix with a plurality of rows and a plurality of columns, each pixel comprising a first EL element operably emitting light of a first color, a second EL element operably emitting light of a second color, a third EL element operably emitting light of a third color, and a fourth EL element operably emitting light of a fourth color, a plurality of gate lines, each gate line coupled to a respective row of pixels, a plurality of first data lines, each first data line coupled to the first EL elements of a respective column of pixels, a plurality of second data lines, each second data line coupled to the second EL elements of a respective column of pixels, a plurality of first switches, each first switch coupled to a respective third EL element, wherein the plurality of first switches are configured to be cooperatively in an ON state or an OFF state, a plurality of second switches, each second switch coupled to a respective fourth EL element, wherein the plurality of second switches are configured to be cooperatively in an ON state or an OFF state, a switch control line coupled to the plurality of first switches and the plurality of second switches for providing a switching control signal to set the first switches and the second switches to be in the ON state or the OFF state, such that when the plurality of first switches are cooperatively in the ON state, the plurality of second switches are cooperatively in the OFF state, and vice versus, and a plurality of third data lines, each third data line coupled to the first switches and the second switches corresponding to a respective column of pixels for transmitting a data signal, such that when the first switches are cooperatively in the ON state, the data signal is provided to the third EL elements of the respective column of pixels, and when the second switches are cooperatively in the ON state, the data signal is provided to the fourth EL elements of the respective column of pixels.

[0019] In one embodiment, the EL display device further has an image processor for processing an image to be displayed according to the pixel matrix of the EL display device such that the processed image has a plurality of pixel data signals, each pixel data signal being associated with a respective pixel and having a first sub-pixel data signal, a second sub-pixel data signal, a third sub-pixel data signal and a fourth sub-pixel data signal indicating intensities for the first EL element, the second EL element, the third EL element and the fourth EL element, respectively, of the respective pixel, and a selector configured to compare the third sub-pixel data signal and the fourth sub-pixel data signal of each pixel, to assign a logic value of 1 to the corresponding pixel if the third sub-pixel data signal is greater than or equal to the fourth sub-pixel data signal, or a logic value of 0 to the corresponding pixel if the third sub-pixel data signal is less than the fourth sub-pixel data signal, and to count the number of the logic value of 1, NB 1, and the number of the logic value of 0, NB2, of the plurality of pixels.

[0020] In one embodiment, the switching control signal is configured to set the plurality of first switches in the ON state and the plurality of second switches in the OFF state, respectively, if $NB1 \geq NB2$, and the plurality of first switches in the OFF state and the plurality of second switches in the ON state, respectively, if $NB1 < NB2$.

[0021] In one embodiment, the switching control signal is characterized with a waveform having a low voltage and a high voltage. When the switching control signal has one of the low voltage and the high voltage, the plurality of first switches and the plurality of second switches are set in the ON state and the OFF state, respectively. When the switching control signal has the other of the low voltage and the high voltage, the plurality of first switches and the plurality of second switches are set in the OFF state and the ON state, respectively.

[0022] In one embodiment, each of the plurality of first switches comprises one of an N-type TFT and a P-type TFT, and each of the plurality of second switches comprises the other of the N-type TFT and the P-type TFT, wherein each of the N-type TFT and the P-type TFT has a gate, a source and a drain. The gate, source and drain of each N-type TFT are respectively coupled to the switching control line, a corresponding third data line and one of the third EL element and the fourth EL element of a corresponding pixel. The gate, source and drain of each P-type TFT are respectively

coupled to the switching control line, the corresponding third data line and the other of the third EL element and the fourth EL element of the corresponding pixel.

[0023] In one embodiment, the first color is a red color, the second color is a green color, the third color is a yellow-green color and the fourth color is a blue color. In one embodiment, the first EL element, the second EL element, the third EL element and the fourth EL element of each pixel are spatially arranged as a 2×2 sub-array.

[0024] In a further aspect, the present invention relates to a method of driving the EL display device. In one embodiment, the method has the steps of processing an image to be displayed according to the pixel matrix of the EL display device such that the processed image has a plurality of pixel data signals, each pixel data signal being associated with a respective pixel and having a first sub-pixel data signal, a second sub-pixel data signal, a third sub-pixel data signal and a fourth sub-pixel data signal indicating intensities for the first EL element, the second EL element, the third EL element and the fourth EL element, respectively, of the respective pixel, comparing the third sub-pixel data signal and the fourth sub-pixel data signal of each pixel, assigning a logic value of 1 to the corresponding pixel if the third sub-pixel data signal is greater than or equal to the fourth sub-pixel data signal, or a logic value of 0 to the corresponding pixel if the third sub-pixel data signal is less than the fourth sub-pixel data signal, counting the number of the logic value of 1, NB1, and the number of the logic value of 0, NB2, of the plurality of pixels, and configuring the switching control signal so as to set the plurality of first switches in the ON state and the plurality of second switches in the OFF state, respectively, if $NB1 \geq NB2$, and the plurality of first switches in the OFF state and the plurality of second switches in the ON state, respectively, if $NB1 < NB2$.

[0025] These and other aspects of the present invention will become apparent from the following description of the preferred embodiment taken in conjunction with the following drawings, although variations and modifications therein may be affected without departing from the spirit and scope of the novel concepts of the disclosure.

BRIEF DESCRIPTION OF THE DRAWINGS

[0026] The accompanying drawings illustrate one or more embodiments of the invention and, together with the written description, serve to explain the principles of the invention. Wherever possible, the same reference numbers are used throughout the drawings to refer to the same or like elements of an embodiment, and wherein:

FIG. 1 shows schematically an electroluminescent (EL) display device according to one embodiment of the present invention;

FIG. 2 shows a block diagram of a driver for an EL display device according to one embodiment of the present invention;

FIG. 3 shows schematically a time chart of a scanning signal G and a plurality of switching control signals Q1, Q2, ... Qn for driving an EL display device according one embodiment of the present invention;

FIG. 4 shows schematically an EL display device according to one embodiment of the present invention;

FIG. 5 shows schematically an EL display device according to another embodiment of the present invention;

FIG. 6 shows schematically a time chart of a scanning signal G and a single switching control signal Q for driving an EL display device according to one embodiment of the present invention;

FIG. 7 shows schematically an EL display device according to one embodiment of the present invention;

FIG. 8 shows schematically two pixel arrangements (a) and (b) for a conventional EL display device; and

FIG. 9 shows schematically a conventional EL display device.

DETAILED DESCRIPTION OF THE INVENTION

[0027] The present invention is more particularly described in the following examples that are intended as illustrative only since numerous modifications and variations therein will be apparent to those skilled in the art. Various embodiments of the invention are now described in detail. Referring to the drawings, like numbers indicate like components throughout the views. As used in the description herein and throughout the claims that follow, the meaning of "a", "an", and "the" includes plural reference unless the context clearly dictates otherwise. Also, as used in the description herein and throughout the claims that follow, the meaning of "in" includes "in" and "on" unless the context clearly dictates otherwise.

[0028] The terms used in this specification generally have their ordinary meanings in the art, within the context of the invention, and in the specific context where each term is used. Certain terms that are used to describe the invention are discussed below, or elsewhere in the specification, to provide additional guidance to the practitioner regarding the description of the invention. The use of examples anywhere in this specification, including examples of any terms discussed herein, is illustrative only, and in no way limits the scope and meaning of the invention or of any exemplified term. Likewise, the invention is not limited to various embodiments given in this specification.

[0029] As used herein, "around", "about" or "approximately" shall generally mean within 20 percent, preferably within 10 percent, and more preferably within 5 percent of a given value or range. Numerical quantities given herein are

approximate, meaning that the term "around", "about" or "approximately" can be inferred if not expressly stated.

[0030] As used herein, the terms "comprising," "including," "having," "containing," "involving," and the like are to be understood to be open-ended, i.e., to mean including but not limited to.

[0031] The description will be made as to the embodiments of the present invention in conjunction with the accompanying drawings in FIGS. 1-7. In accordance with the purposes of this invention, as embodied and broadly described herein, this invention, in one aspect, relates to an EL display device with each pixel having four light emitting elements and a method of driving the same.

[0032] Referring to FIG. 1, an EL display device 100 is schematically shown according to one embodiment of the present invention. The EL display device 100 includes a plurality of pixels 110 spatially arranged in a form of a matrix with a plurality of rows and a plurality of columns. Each pixel 110 has four light emitting elements 111-114 spatially arranged as a 2x2 sub-pixel array. The four light emitting elements 111-114 in one embodiment correspond to a first EL element 111 operably emitting light of a first color, a second EL element 112 operably emitting light of a second color, a third EL element 113 operably emitting light of a third color, and a fourth EL element 114, operably emitting light of a fourth color. The first, second and third colors are corresponding to red (R), green (G) and yellow-green (B1) colors, respectively, while the fourth color in one embodiment is corresponding to a blue (B2) color. Each of four light emitting elements 111-114 is formed of a different EL material. In one embodiment, the EL material forming the light emitting element (B1) 113 has a higher luminous efficiency than that of the EL material in the light emitting element (B2) 114.

[0033] The EL display device 100 also includes a plurality of gate lines, {Gj}, j = 1, 2, 3, ..., M, M being a positive integer and the row number of the pixel matrix. Each gate line Gj is coupled to the four light emitting elements 111-114 of a respective row of pixels 110. In this arrangement, only one gate line is required for each row of pixels, which substantially reduces the number of the gate lines required for each row of pixels in a conventional EL display device 900 shown in FIG. 9. In operation, a plurality of scanning signals generated from a gate driver (not shown) is respectively applied the plurality of gate lines {Gj} for sequentially driving the pixels in a row-by-row fashion.

[0034] The EL display device 100 further includes a plurality of first data lines {SRk}, k = 1, 2, 3, ..., N, N being a positive integer and the column number of the pixel matrix, a plurality of second data lines {SGk}, and a plurality of third data lines {SBk}. Each first data line SRk is coupled to the first EL elements (R) 111 of a respective column of pixels. Each second data line SGk is coupled to the second EL elements 112 of a respective column of pixels. Each third data line SBk is coupled to the third EL elements (B1) 113 and the fourth EL elements (B2) 114 of a respective column of pixels.

[0035] The EL display device 100 also includes a plurality of first switches 121, a plurality of second switches 122, and a plurality of switch control lines {Qk}.

[0036] As shown in FIG. 1, each first switch 121 is coupled to a respective third EL element (B1) 113, while each second switch 122 is coupled to a respective fourth EL element (B2) 114. In this exemplary embodiment, the first switches 121 coupled to the third EL elements (B1) 113 of a respective column of pixels are configured to be cooperatively in an ON state or an OFF state. The second switches 122 coupled to the fourth EL elements (B2) 114 of a respective column of pixels are configured to be cooperatively in an ON state or an OFF state. Each switch control line Qk is coupled to the first switches 121 and the second switches 122 corresponding to a respective column of pixels for transmitting a switching control signal to set the first switches 121 and the second switches 122 to be in the ON state or the OFF state, such that when the first switches 121 are cooperatively in the ON state, the second switches 122 are cooperatively in the OFF state, and vice versus.

[0037] Further, each third data line SBk is coupled to the first switches 121 and the second switches 122 corresponding to a respective column of pixels for transmitting a data signal, such that when the first switches 121 are cooperatively in the ON state, the data signal is provided to the third EL elements 113 of the respective column of pixels, and when the second switches 122 are cooperatively in the ON state, the data signal is provided to the fourth EL elements 114 of the respective column of pixels.

[0038] According to this embodiment shown in FIG. 1, only three data lines SRk, SGk and SBk are required for each column of pixels, same as in a conventional color EL display device with each pixel having three light emitting elements. Only one of the two light emitting elements B1 and B2 will emit light at a given time.

[0039] The plurality of first data lines {SRk}, the plurality of second data lines {SGk}, and the plurality of third data lines {SBk} are coupled to a source driver (not shown) that outputs pixel data signals of an image to be displayed on the display device 100.

[0040] FIG. 2 schematically shows a block diagram of a system 200 of for driving an EL display device according to one embodiment of the present invention. The system 200 includes an image process (not shown) for processing an image to be displayed on the EL display device 100 according to the pixel matrix of the EL display device 100, which is input to an input line buffer 210. The processed image has a plurality of pixel data signals. Each pixel data signal is associated with a respective pixel in the EL display device 100 and includes a first sub-pixel data signal indicating an intensity level for the red light emitting element R of the respective pixel, a second sub-pixel data signal indicating an intensity level for the green light emitting element G of the respective pixel, a third sub-pixel data signal indicating an intensity level for the yellow-green light emitting element B1 of the respective pixel, and a fourth sub-pixel data signal

indicating an intensity level for the blue light emitting element B2 of the respective pixel.

[0041] The processed image is then input to a data processor 230. The data processor 230 includes a selector 232 and a driver integrated circuit (IC) 234. The selector 232 then compares the third sub-pixel data signal and the fourth sub-pixel data signal of each pixel. If the third sub-pixel data signal is greater than or equal to the fourth sub-pixel data signal, the selector 232 assigns a logic value of 1 to the corresponding pixel. Otherwise, the selector 232 assigns a logic value of 0 to the corresponding pixel. Then, the selector 232 counts the number of the logic value of 1, NB1, and the number of the logic value of 0, NB2, of each column of pixels.

[0042] If $NB1 \geq NB2$ for a respective column of pixels, the switching control signal for the respective column of pixels is configured to set the first switches 121 and the second switches 122 corresponding to the respective column of pixels in the ON state and the OFF state, respectively. If $NB1 < NB2$ for the respective column of pixels, the first switches 121 and the second switches 122 corresponding to the respective column of pixels in the OFF state and the ON state, respectively.

[0043] The driver IC 234 converts, for each pixel, the first sub-pixel data signal to a first voltage to be applied to a corresponding first data line SRk, the second sub-pixel data signal to a second voltage to be applied to a corresponding second data line SGk, the third sub-pixel data signal if the corresponding pixel has a logic value of 1 or the fourth sub-pixel data signal if the corresponding pixel has a logic value of 0 to a third voltage to be applied to a corresponding third data line SBk. In addition, the system 200 includes a driving system 220 that outputs a clock signal CLK, a vertical synchronizing signal VS, a horizontal synchronizing signal HS to the data processor 230, so that the plurality of pixel data signals of the image is driven to the EL display device 100 sequentially in a row-by-row fashion controlled by the plurality of scanning signals.

[0044] FIG. 3 shows schematically a time chart for a scanning signal and a plurality of switching control signals, for driving an EL display device according to one embodiment of the present invention. Each switching control signal for a respective column of pixels is characterized with a waveform having a low voltage, L, and a high voltage, H, for controlling the first switches 121 and the second switches 122 corresponding to the respective column of pixels. The scanning signal (a high voltage pulse) activates a corresponding row of pixels in the EL display device 100 so that data signals are applied to the plurality of pixels in the corresponding rows.

[0045] Each switching control signal determines whether the yellow-green light emitting elements B1 or the blue light emitting elements B2 of a corresponding pixel in the corresponding row of pixel receives a third sub-pixel data signal. For example, in one embodiment, the first switches 121 and second switches 122 are configured such that when the switching control signal for the respective column of pixels has the high voltage H, the first switches 121 and the second switches 122 corresponding to the respective column of pixels are set in the ON state and the OFF state, respectively. Therefore, the third sub-pixel data signal is applied to the yellow-green light emitting elements B1. When the switching control signal for the respective column of pixels has the low voltage L, the first switches 121 and the second switches 122 corresponding to the respective column of pixels are set in the OFF state and the ON state, respectively. Accordingly, the third sub-pixel data signal is applied to the blue light emitting elements B2.

[0046] Other configuration of the first switches 121 and the second switches 122 can also be utilized to practice the invention. For example, when the switching control signal for the respective column of pixels has the low voltage L, the first switches 121 and the second switches 122 corresponding to the respective column of pixels are set in the ON state and the OFF state, respectively, whereby the third sub-pixel data signal is applied to the yellow-green light emitting elements B1. When the switching control signal for the respective column of pixels has the high voltage H, the first switches 121 and the second switches 122 corresponding to the respective column of pixels are set in the OFF state and the ON state, respectively, whereby the third sub-pixel data signal is applied to the blue light emitting elements B2.

[0047] The first switches 121 and the second switches 122 can be any types of two state switches, such as thin film transistors (TFTs), as shown in FIG. 4.

[0048] FIG. 4 shows schematically an EL display device 400 according to one embodiment of the present invention, where each of the plurality of first switches 421 is an N-type TFT, while each of the plurality of second switches 422 is a P-type TFT. The gate, source and drain of each first switches 421 (e.g. N-type TFTs) are respectively coupled to a corresponding switching control line Qk, a corresponding third data line SBk and the third EL element (B1) 413 of a corresponding pixel. The gate, source and drain of each second switches 422 (e.g. P-type TFTs) are respectively coupled to the corresponding switching control line Qk, the corresponding third data line SBk and the fourth EL element (B2) 414 of the corresponding pixel. For such an arrangement, when a switching control signal for a respective column of pixels has the high voltage H, the first switches 421 of the respective column of pixels are turned on (in the ON state), while the second switches 422 of the respective column of pixels are turned off (in the OFF state). Accordingly, the third sub-pixel data signal provided from the respective third data line SBk is applied to the third EL elements (B1) 413 of the respective column of pixels. Otherwise, when the switching control signal for the respective column of pixels has the low voltage L, the first switches 421 of the respective column of pixels are turned off (in the OFF state), while the second switches 422 of the respective column of pixels are turned on (in the ON state). Accordingly, the third sub-pixel data signal provided from the respective third data line SBk is applied to the fourth EL elements (B2) 414 of the respective

column of pixels.

[0049] In an alternative embodiment, each of the plurality of first switches 421 is a P-type TFT, while each of the plurality of second switches 422 is an N-type TFT. In this example, when a switching control signal for a respective column of pixels has the low voltage L, the second switches 422 (e.g. N-type TFTs) of the respective column of pixels are turned off (in the OFF state), while the first switches (e.g. P-type TFTs) of the respective column of pixels are turned on (in the ON state). Accordingly, the third sub-pixel data signal provided from the respective third data line SBk is applied to the third EL elements (B1) of the respective column of pixels. When the switching control signal for the respective column of pixels has the high voltage H, the second switches 422 (e.g. N-type TFTs) of the respective column of pixels are turned on (in the ON state), while the first switches (e.g. P-type TFTs) of the respective column of pixels are turned off (in the OFF state). Accordingly, the third sub-pixel data signal provided from the respective third data line SBk is applied to the fourth EL elements (B2) of the respective column of pixels.

[0050] Accordingly, one aspect of the present invention provides a method of driving such an EL display device. The method includes the following steps. At first, an image to be displayed is processed according to the pixel matrix of the EL display device such that the processed image has a plurality of pixel data signals, each pixel data signal being associated with a respective pixel and having a first sub-pixel data signal, a second sub-pixel data signal, a third sub-pixel data signal and a fourth sub-pixel data signal indicating intensities for the first EL element, the second EL element, the third EL element and the fourth EL element, respectively, of the respective pixel. Then, the third sub-pixel data signal and the fourth sub-pixel data signal of each pixel are compared. A logic value of 1 is assigned to the corresponding pixel if the third sub-pixel data signal is greater than or equal to the fourth sub-pixel data signal, or a logic value of 0 assigned to the corresponding pixel if the third sub-pixel data signal is less than the fourth sub-pixel data signal. The number of the logic value of 1, NB1, and the number of the logic value of 0, NB2, of each column of pixels are counted subsequently. Next, the switching control signal for a respective column of pixels is configured to set the first switches and the second switches corresponding to the respective column of pixels in the ON state and the OFF state, respectively, if $NB1 \geq NB2$ for the respective column of pixels, and the first switches and the second switches in the OFF state and the ON state, respectively, if $NB1 < NB2$ for the respective column of pixels.

[0051] While each of the EL display devices 100 and 400 shown in FIGS. 1 and 4, respectively, has fewer gate lines and data lines than a conventional EL display device, it still has $2 \times M \times N$ switches that require N switching control signals/lines Qk ($k = 1, 2, 3, \dots, N$), where M and N are equal to the numbers of row and columns, respectively, of pixels. Therefore the electrical layout of the display devices is still relatively complicated and consequently results in higher cost.

[0052] FIG. 5 schematically shows an EL display device 500 according to another embodiment of the present invention in which the number of switching control signals/lines is reduced to one. Similar to the EL display device 100 shown in FIG. 1, the EL display device 500 has a plurality of pixels 510 spatially arranged in a form of a matrix with a plurality of rows and a plurality of columns. Each pixel 510 has a first EL element (R) 511 operably emitting light of a red color, a second EL element (G) 512 operably emitting light of a green color, a third EL element (B1) 513 operably emitting light of a yellow-green color, and a fourth EL element (B2) 514 operably emitting light of a blue color. The EL display device 500 is adapted for displaying an image. Operably, the image is processed by an image processor, according to the pixel matrix of the EL display device 500 such that the processed image has a plurality of pixel data signals, each pixel data signal being associated with a respective pixel and having a first sub-pixel data signal, a second sub-pixel data signal, a third sub-pixel data signal and a fourth sub-pixel data signal indicating intensities for the first EL element (R) 511, the second EL element (G) 511, the third EL element (B1) 513 and the fourth EL element (B2) 514, respectively, of the respective pixel.

[0053] The EL display device 500 also has a plurality of gate lines {Gj}, $j = 1, 2, 3, \dots, M$, M being the row number of the pixel matrix, a plurality of first data lines, {SRk}, $k = 1, 2, 3, \dots, N$, N being the column number of the pixel matrix, a plurality of second data lines, {SGk}, a plurality of third data lines, {SBk}, a plurality of first switches 521, a plurality of second switches 522, and a signal switch control line, Q.

[0054] Each gate line Gj is coupled to a respective row of pixels. Each first data line SRk is coupled to the first EL elements (R) 511 of a respective column of pixels. Each second data line SGk is coupled to the second EL elements (G) 512 of a respective column of pixels. Each third data line SBk is coupled, via the first switches 521 and the second switches 522, to the third EL elements (B1) 513 and the fourth EL elements (B2) 514 of a respective column of pixels.

[0055] Each first switch 521 is coupled to a respective third EL element (B1) 513, while each second switch 522 is coupled to a respective fourth EL element (B2) 514. The single switch control line Q is coupled to all of the first switches 521 and the second switches 522 for providing a switching control signal to set the first switches 521 and the second switches 522 to be in the ON state or the OFF state. In this exemplary embodiment, all of the first switches 521 are configured to be cooperatively in an ON state or an OFF state, while all of the second switches 522 are configured to be cooperatively in the OFF state or the ON state.

[0056] Accordingly, when the first switches 521 are cooperatively in the ON state, the third sub-pixel data signal from a respective third data line SBk is provided to the third EL elements (B1) 513 of the respective column of pixels, and when the second switches 522 are cooperatively in the ON state, the third sub-pixel data signal from the respective third

data line SB_k is provided to the fourth EL elements (B2) 514 of the respective column of pixels.

[0057] To determine which switches are turned on or off, a selector is adapted and configured to compare the third sub-pixel data signal and the fourth sub-pixel data signal of each pixel, to assign a logic value of 1 to the corresponding pixel if the third sub-pixel data signal is greater than or equal to the fourth sub-pixel data signal, or a logic value of 0 to the corresponding pixel if the third sub-pixel data signal is less than the fourth sub-pixel data signal, and to count the number of the logic value of 1, NB₁, and the number of the logic value of 0, NB₂, of the plurality of pixels. If $NB_1 \geq NB_2$, the switching control signal is configured to set the first switches 521 in the ON state and the second switches 522 in the OFF state, respectively. Otherwise, if $NB_1 < NB_2$, the switching control signal is configured to the first switches 521 in the OFF state and the second switches 522 in the ON state, respectively, if $NB_1 < NB_2$.

[0058] In one embodiment, the switching control signal is characterized with a waveform having a low voltage, L, and a high voltage, H, for controlling the first switches 521 and the second switches 522, as shown in FIG. 6. For example, when the switching control signal has the low voltage L, the first switches 521 and the second switches 522 are set in the ON state and the OFF state, respectively, and when the switching control signal has the high voltage H, the first switches 521 and the second switches 522 are set in the OFF state and the ON state, respectively. Now, instead of N switching control signals, the single switching control signal controls whether each third data line SB_k is coupled to the third light emitting element (B1) 513 or to the fourth light emitting element (B2) 514 of a respective pixel.

[0059] FIG. 7 shows schematically an EL display device 700 according to one embodiment of the present invention. The display device 700 has a similar layout as that of the display device 500. However, each first switch 721 includes an N-type TFT, while each second switch 722 includes a P-type TFT. The gate, source and drain of each N-type TFT are respectively coupled to the switching control line Q, a corresponding third data line SB_k and the third EL element (B1) 713 of a corresponding pixel. The gate, source and drain of each P-type TFT are respectively coupled to the switching control line Q, the corresponding third data line SB_k and the fourth EL element (B2) 714 of the corresponding pixel. For such an arrangement, when the switching control signal has the low voltage L, all of the first switches 721 are turned off and all of the second switches 722 are turned on. Accordingly, a third sub-pixel data signal is input to the fourth light emitting element (B2) 714 of a respective column of pixels. When the switching control signal has the high voltage H, all of the first switches 721 are turned on and all of the second switches 722 are turned off. Accordingly, a third sub-pixel data signal is input to the third light emitting element (B1) 713 of the respective column of pixels.

[0060] In an alternative embodiment, each first switch 721 is a P-type TFT and each second switch 722 is an N-type TFT,

[0061] Furthermore, another aspect of the present invention provides a method of driving such an EL display device 500 (or 700). The method includes the following steps. At first, an image to be displayed is processed according to the pixel matrix of the EL display device. The processed image has a plurality of pixel data signals, each pixel data signal being associated with a respective pixel and having a first sub-pixel data signal, a second sub-pixel data signal, a third sub-pixel data signal and a fourth sub-pixel data signal indicating intensities for the first EL element, the second EL element, the third EL element and the fourth EL element, respectively, of the respective pixel.

[0062] Next, the third sub-pixel data signal and the fourth sub-pixel data signal of each pixel are compared. A logic value of 1 is assigned to the corresponding pixel if the third sub-pixel data signal is greater than or equal to the fourth sub-pixel data signal, or a logic value of 0 is assigned to the corresponding pixel if the third sub-pixel data signal is less than the fourth sub-pixel data signal. The number of the logic value of 1, NB₁, and the number of the logic value of 0, NB₂, of the plurality of pixels are counted.

[0063] Then, the switching control signal is configured to set the plurality of first switches 721 in the ON state and the plurality of second switches 722 in the OFF state, respectively, if $NB_1 \geq NB_2$, and the plurality of first switches 721 in the OFF state and the plurality of second switches 722 in the ON state, respectively, if $NB_1 < NB_2$.

[0064] The foregoing description of the exemplary embodiments of the invention has been presented only for the purposes of illustration and description and is not intended to be exhaustive or to limit the invention to the precise forms disclosed. Many modifications and variations are possible in light of the above teaching.

[0065] The embodiments were chosen and described in order to explain the principles of the invention and their practical application so as to activate others skilled in the art to utilize the invention and various embodiments and with various modifications as are suited to the particular use contemplated. Alternative embodiments will become apparent to those skilled in the art to which the present invention pertains without departing from its spirit and scope. Accordingly, the scope of the present invention is defined by the appended claims rather than the foregoing description and the exemplary embodiments described therein.

Claims

1. An electroluminescent (EL) display device, comprising:

a. a plurality of pixels spatially arranged in a form of a matrix with a plurality of rows and a plurality of columns,

each pixel comprising a first EL element operably emitting light of a first color, a second EL element operably emitting light of a second color, a third EL element operably emitting light of a third color, and a fourth EL element operably emitting light of a fourth color;

b. a plurality of gate lines, each gate line coupled to the respective matrix of pixels;

c. a plurality of first data lines, each first data line coupled to the first EL elements of a respective column of pixels;

d. a plurality of second data lines, each second data line coupled to the second EL elements of a respective column of pixels;

e. a plurality of first switches, each first switch coupled to a respective third EL element, wherein the first switches coupled to the third EL elements of a respective column of pixels are configured to be cooperatively in an ON state or an OFF state;

f. a plurality of second switches, each second switch coupled to a respective fourth EL element, wherein the second switches coupled to the fourth EL elements of a respective column of pixels are configured to be cooperatively in an ON state or an OFF state;

g. a plurality of switch control lines, each switch control line coupled to the first switches and the second switches corresponding to a respective column of pixels for transmitting a switching control signal to set the first switches and the second switches to be in the ON state or the OFF state, such that when the first switches are cooperatively in the ON state, the second switches are cooperatively in the OFF state, and vice versus; and

h. a plurality of third data lines, each third data line coupled to the first switches and the second switches corresponding to a respective column of pixels for transmitting a data signal, such that when the first switches are cooperatively in the ON state, the data signal is provided to the third EL elements of the respective column of pixels, and when the second switches are cooperatively in the ON state, the data signal is provided to the fourth EL elements of the respective column of pixels.

2. The EL display device of claim 1, further comprising:

i. an image processor for processing an image to be displayed according to a pixel matrix of the EL display device such that the processed image has a plurality of pixel data signals, each pixel data signal being associated with a respective pixel and having a first sub-pixel data signal, a second sub-pixel data signal, a third sub-pixel data signal and a fourth sub-pixel data signal indicating intensities for the first EL element, the second EL element, the third EL element and the fourth EL element, respectively, of the respective pixel; and

ii. a selector configured to compare the third sub-pixel data signal and the fourth sub-pixel data signal of each pixel, to assign a logic value of 1 to the corresponding pixel if the third sub-pixel data signal is greater than or equal to the fourth sub-pixel data signal, or a logic value of 0 to the corresponding pixel if the third sub-pixel data signal is less than the fourth sub-pixel data signal, and to count the number of the logic value of 1, NB1, and the number of the logic value of 0, NB2, of each column of pixels.

3. The EL display device of claim 2, wherein the switching control signal for a respective column of pixels is configured to set the first switches and the second switches corresponding to the respective column of pixels in the ON state and the OFF state, respectively, if $NB1 \geq NB2$ for the respective column of pixels, and the first switches and the second switches corresponding to the respective column of pixels in the OFF state and the ON state, respectively, if $NB1 < NB2$ for the respective column of pixels.

4. The EL display device of claim 3, wherein the switching control signal for a respective column of pixels is characterized with a waveform having a low voltage and a high voltage, when the switching control signal for the respective column of pixels has one of the low voltage and the high voltage, the first switches and the second switches corresponding to the respective column of pixels are set in the ON state and the OFF state, respectively, and when the switching control signal for the respective column of pixels has the other of the low voltage and the high voltage, the first switches and the second switches corresponding to the respective column of pixels are set in the OFF state and the ON state, respectively.

5. The EL display device of claim 1, wherein each of the plurality of first switches comprises one of an N-type thin film transistor (TFT) and a P-type TFT, and each of the plurality of second switches comprises the other of the N-type TFT and the P-type TFT, wherein each of the N-type TFT and the P-type TFT has a gate, a source and a drain, the gate, source and drain of each N-type TFT are respectively coupled to a corresponding switching control line, a corresponding third data line and one of the third EL element and the fourth EL element of a corresponding pixel, and the gate, source and drain of each P-type TFT are respectively coupled to the corresponding switching control line, the corresponding third data line and the other of the third EL element and the fourth EL element of the corresponding pixel.

6. The EL display device of claim 1, wherein the first color is a red color, the second color is a green color, the third color is a yellow-green color and the fourth color is a blue color.

7. The EL display device of claim 1, wherein the first EL element, the second EL element, the third EL element and the fourth EL element of each pixel are spatially arranged as a 2×2 sub-array.

8. A method of driving the EL display device of claim 1, comprising the steps of:

i. processing an image to be displayed according to a pixel matrix of the EL display device such that the processed image has a plurality of pixel data signals, each pixel data signal being associated with a respective pixel and having a first sub-pixel data signal, a second sub-pixel data signal, a third sub-pixel data signal and a fourth sub-pixel data signal indicating intensities for the first EL element, the second EL element, the third EL element and the fourth EL element, respectively, of the respective pixel;

ii. comparing the third sub-pixel data signal and the fourth sub-pixel data signal of each pixel;

iii. assigning a logic value of 1 to the corresponding pixel if the third sub-pixel data signal is greater than or equal to the fourth sub-pixel data signal, or a logic value of 0 to the corresponding pixel if the third sub-pixel data signal is less than the fourth sub-pixel data signal;

iv. counting the number of the logic value of 1, NB1, and the number of the logic value of 0, NB2, of each column of pixels; and

v. configuring the switching control signal for a respective column of pixels so as to set the first switches and the second switches corresponding to the respective column of pixels in the ON state and the OFF state, respectively, if $NB1 \geq NB2$ for the respective column of pixels, and the first switches and the second switches in the OFF state and the ON state, respectively, if $NB1 < NB2$ for the respective column of pixels.

9. An electroluminescent (EL) display device, comprising:

a. a plurality of pixels spatially arranged in a form of a matrix with a plurality of rows and a plurality of columns, each pixel comprising a first EL element operably emitting light of a first color, a second EL element operably emitting light of a second color, a third EL element operably emitting light of a third color, and a fourth EL element operably emitting light of a fourth color;

b. a plurality of gate lines, each gate line coupled to a respective row of pixels;

c. a plurality of first data lines, each first data line coupled to the first EL elements of a respective column of pixels;

d. a plurality of second data lines, each second data line coupled to the second EL elements of a respective column of pixels;

e. a plurality of first switches, each first switch coupled to a respective third EL element, wherein the plurality of first switches are configured to be cooperatively in an ON state or an OFF state;

f. a plurality of second switches, each second switch coupled to a respective fourth EL element, wherein the plurality of second switches are configured to be cooperatively in an ON state or an OFF state;

g. a switch control line coupled to the plurality of first switches and the plurality of second switches for providing a switching control signal to set the first switches and the second switches to be in the ON state or the OFF state, such that when the plurality of first switches are cooperatively in the ON state, the plurality of second switches are cooperatively in the OFF state, and vice versa; and

h. a plurality of third data lines, each third data line coupled to the first switches and the second switches corresponding to a respective column of pixels for transmitting a data signal, such that when the first switches are cooperatively in the ON state, the data signal is provided to the third EL elements of the respective column of pixels, and when the second switches are cooperatively in the ON state, the data signal is provided to the fourth EL elements of the respective column of pixels.

10. The EL display device of claim 9, further comprising:

i. an image processor for processing an image to be displayed according to a pixel matrix of the EL display device such that the processed image has a plurality of pixel data signals, each pixel data signal being associated with a respective pixel and having a first sub-pixel data signal, a second sub-pixel data signal, a third sub-pixel data signal and a fourth sub-pixel data signal indicating intensities for the first EL element, the second EL element, the third EL element and the fourth EL element, respectively, of the respective pixel; and

ii. a selector configured to compare the third sub-pixel data signal and the fourth sub-pixel data signal of each pixel, to assign a logic value of 1 to the corresponding pixel if the third sub-pixel data signal is greater than or equal to the fourth sub-pixel data signal, or a logic value of 0 to the corresponding pixel if the third sub-pixel

data signal is less than the fourth sub-pixel data signal, and to count the number of the logic value of 1, NB1, and the number of the logic value of 0, NB2, of the plurality of pixels.

11. The EL display device of claim 9, wherein the switching control signal is configured to set the plurality of first switches in the ON state and the plurality of second switches in the OFF state, respectively, if $NB1 \geq NB2$, and the plurality of first switches in the OFF state and the plurality of second switches in the ON state, respectively, if $NB1 < NB2$, the switching control signal is characterized with a waveform having a low voltage and a high voltage, when the switching control signal has one of the low voltage and the high voltage, the plurality of first switches and the plurality of second switches are set in the ON state and the OFF state, respectively, and when the switching control signal has the other of the low voltage and the high voltage, the plurality of first switches and the plurality of second switches are set in the OFF state and the ON state, respectively.

12. The EL display device of claim 9, wherein each of the plurality of first switches comprises one of an N-type thin film transistor (TFT) and a P-type TFT, and each of the plurality of second switches comprises the other of the N-type TFT and the P-type TFT, wherein each of the N-type TFT and the P-type TFT has a gate, a source and a drain, the gate, source and drain of each N-type TFT are respectively coupled to the switching control line, a corresponding third data line and one of the third EL element and the fourth EL element of a corresponding pixel, and the gate, source and drain of each P-type TFT are respectively coupled to the switching control line, the corresponding third data line and the other of the third EL element and the fourth EL element of the corresponding pixel.

13. The EL display device of claim 9, wherein the first color is a red color, the second color is a green color, the third color is a yellow-green color and the fourth color is a blue color.

14. The EL display device of claim 9, wherein the first EL element, the second EL element, the third EL element and the fourth EL element of each pixel are spatially arranged as a 2×2 sub-array.

15. A method of driving the EL display device of claim 9, comprising the steps of:


i. processing an image to be displayed according to a pixel matrix of the EL display device such that the processed image has a plurality of pixel data signals, each pixel data signal being associated with a respective pixel and having a first sub-pixel data signal, a second sub-pixel data signal, a third sub-pixel data signal and a fourth sub-pixel data signal indicating intensities for the first EL element, the second EL element, the third EL element and the fourth EL element, respectively, of the respective pixel;

ii. comparing the third sub-pixel data signal and the fourth sub-pixel data signal of each pixel;

iii. assigning a logic value of 1 to the corresponding pixel if the third sub-pixel data signal is greater than or equal to the fourth sub-pixel data signal, or a logic value of 0 to the corresponding pixel if the third sub-pixel data signal is less than the fourth sub-pixel data signal;

iv. counting the number of the logic value of 1, NB1, and the number of the logic value of 0, NB2, of the plurality of pixels; and

v. configuring the switching control signal so as to set the plurality of first switches in the ON state and the plurality of second switches in the OFF state, respectively, if $NB1 \geq NB2$, and the plurality of first switches in the OFF state and the plurality of second switches in the ON state, respectively, if $NB1 < NB2$.






FIG. 2




FIG. 3




FIG. 4




FIG. 5





FIG. 6






FIG. 8
(Related Art)

900




FIG. 9
(Related Art)

**PARTIAL EUROPEAN SEARCH REPORT**

under Rule 62a and/or 63 of the European Patent Convention.
This report shall be considered, for the purposes of
subsequent proceedings, as the European search report

Application Number

EP 11 00 5894

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
X	US 2007/139437 A1 (BOROSON MICHAEL L [US] ET AL) 21 June 2007 (2007-06-21) * paragraph [0002] - paragraph [0096]; figures 1-10 * * figure 1 *	1, 14	INV. G09G3/20 G09G3/32 H01L27/32
A	US 2008/165171 A1 (CHIOU YU-WEN [TW]) 10 July 2008 (2008-07-10) * paragraph [0001] - paragraph [0047]; figures 1-9 * -----	1	
			TECHNICAL FIELDS SEARCHED (IPC)
			G09G H01L
INCOMPLETE SEARCH			
The Search Division considers that the present application, or one or more of its claims, does/do not comply with the EPC so that only a partial search (R.62a, 63) has been carried out.			
Claims searched completely :			
Claims searched incompletely :			
Claims not searched :			
Reason for the limitation of the search: see sheet C			
1	Place of search Munich	Date of completion of the search 21 October 2011	Examiner Gartlan, Michael
CATEGORY OF CITED DOCUMENTS		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons ----- & : member of the same patent family, corresponding document	
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document			

EPO FORM 1503 03.82 (P04E07)



**INCOMPLETE SEARCH
SHEET C**

Application Number
EP 11 00 5894

Claim(s) completely searchable:
9-15

Claim(s) not searched:
1-8

Reason for the limitation of the search:

Rule 62a



Application Number

EP 11 00 5894

CLAIMS INCURRING FEES

The present European patent application comprised at the time of filing claims for which payment was due.

☐ Only part of the claims have been paid within the prescribed time limit. The present European search report has been drawn up for those claims for which no payment was due and for those claims for which claims fees have been paid, namely claim(s):

☐ No claims fees have been paid within the prescribed time limit. The present European search report has been drawn up for those claims for which no payment was due.

LACK OF UNITY OF INVENTION

The Search Division considers that the present European patent application does not comply with the requirements of unity of invention and relates to several inventions or groups of inventions, namely:

see sheet B

☐ All further search fees have been paid within the fixed time limit. The present European search report has been drawn up for all claims.

☐ As all searchable claims could be searched without effort justifying an additional fee, the Search Division did not invite payment of any additional fee.

☐ Only part of the further search fees have been paid within the fixed time limit. The present European search report has been drawn up for those parts of the European patent application which relate to the inventions in respect of which search fees have been paid, namely claims:

☒ None of the further search fees have been paid within the fixed time limit. The present European search report has been drawn up for those parts of the European patent application which relate to the invention first mentioned in the claims, namely claims:

9-11, 14, 15

☐ The present supplementary European search report has been drawn up for those parts of the European patent application which relate to the invention first mentioned in the claims (Rule 164 (1) EPC).



**LACK OF UNITY OF INVENTION
SHEET B**

Application Number
EP 11 00 5894

The Search Division considers that the present European patent application does not comply with the requirements of unity of invention and relates to several inventions or groups of inventions, namely:

1. claims: 9-11, 14, 15

an image processor for processing an image to be displayed according to a pixel matrix of the EL display device such that the processed image has a plurality of pixel data signals, each pixel data signal being associated with a respective pixel and having a first sub-pixel data signal, a second sub-pixel data signal, a third sub-pixel data signal and a fourth sub-pixel data signal indicating intensities for the first EL element, the second EL element, the third EL element and the fourth EL element, respectively, of the respective pixel to adapt incoming signals to be suitable for display on the display device.

2. claim: 12

each of the plurality of first switches comprises one of an N-type thin film transistor (TFT) and a P-type TFT, and each of the plurality of second switches comprises the other of the N-type TFT and the P-type TFT to simplify control of the switches.

3. claim: 13

the third color is a yellow-green color to improve the efficiency and/or color gamut of the display

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 11 00 5894

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

21-10-2011

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2007139437 A1	21-06-2007	EP 1964091 A1	03-09-2008
		JP 2009520241 A	21-05-2009
		US 2007139437 A1	21-06-2007
		WO 2007075276 A1	05-07-2007

US 2008165171 A1	10-07-2008	CN 101236719 A	06-08-2008
		TW 200832337 A	01-08-2008
		US 2008165171 A1	10-07-2008
		US 2011175896 A1	21-07-2011

专利名称(译)	电致发光显示器及其驱动方法		
公开(公告)号	EP2506238A1	公开(公告)日	2012-10-03
申请号	EP2011005894	申请日	2011-07-19
[标]申请(专利权)人(译)	友达光电股份有限公司		
申请(专利权)人(译)	友达光电股份有限公司		
当前申请(专利权)人(译)	友达光电股份有限公司		
[标]发明人	LIU CHIH CHI TSAI TZE CHIEN		
发明人	LIU, CHIH-CHI TSAI, TZE-CHIEN		
IPC分类号	G09G3/20 G09G3/32 H01L27/32		
CPC分类号	G09G3/2003 G09G3/3233 G09G3/3283 G09G2300/0452 G09G2300/0804 G09G2300/0809 G09G2300/0814 G09G2320/043 G09G2320/0666 G09G2330/021 G09G2340/06 G09G2360/16 H01L27/3213		
审查员(译)	GARTLAN, MICHAEL		
优先权	13/073387 2011-03-28 US		
其他公开文献	EP2506238B1		
外部链接	Espacenet		

摘要(译)

在本发明的一个方面中，电致发光（EL）显示装置具有以矩阵形式在空间上排列的多个像素，每个像素具有第一EL元件，第二EL元件，第三EL元件和第四EL元件。EL元件，多条栅极线，每条栅极线耦合到相应的一行像素，多条第一数据线，每条第一数据线耦合到相应列的像素的第一EL元件，多条第二数据线每个第二数据线耦合到相应像素列的第二EL元件，多个第一开关，每个第一开关耦合到相应的第三EL元件，多个第二开关，每个第二开关耦合到相应的第四EL元件，开关控制线耦合到多个第一开关和多个第二开关，用于提供开关控制信号，以将第一开关和第二开关设置为ON状态或OFF状态，使得当第一开关协同处于ON状态时，第二开关共同处于OFF状态，并且相对于多个第三数据线，每个第三数据线耦合到第一开关，第二开关对应于用于传输数据信号的相应像素列，使得当第一数据线时开关协同处于ON状态，数据信号提供给各列像素的第三EL元件，当第二开关协同处于ON状态时，数据信号提供给各自的第四EL元件。专栏像素。




FIG. 1