



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
15.10.2014 Bulletin 2014/42

(51) Int Cl.:
H01L 51/50 (2006.01) **H01L 27/32** (2006.01)
G09G 3/32 (2006.01)

(21) Application number: **14169766.4**

(22) Date of filing: **29.11.2004**

(84) Designated Contracting States:
DE FR GB

(30) Priority: **29.11.2003 KR 20030087797**

(62) Document number(s) of the earlier application(s) in accordance with Art. 76 EPC:
04090475.7 / 1 536 495

(71) Applicant: **Samsung Display Co., Ltd.**
Yongin-City, Gyeonggi-Do, 446-711 (KR)

(72) Inventors:
• **KIM, lee-Gon**
Suwon-si (KR)

• **Kim, Tae-Hyung**
Suwon-si (KR)

(74) Representative: **Gulde & Partner**
Patent- und Rechtsanwaltskanzlei mbB
Wallstraße 58/59
10179 Berlin (DE)


Remarks:

This application was filed on 26-05-2014 as a divisional application to the application mentioned under INID code 62.

(54) **Organic electro luminescence display**

(57) An active matrix organic electro luminescence display (400) in which a first pixel and a second pixel (410, 540) are formed in one pixel portion to achieve a high aperture ratio and to facilitate a fabrication process. The organic electro luminescence display is constructed with gate lines (420, 510), data lines (430, 520), and power lines (440, 530) which are formed on an insulating substrate, and pixel regions which are defined by the gate lines (420, 510), the data lines (430, 520) and the power lines (440, 530), wherein each of the pixel regions includes a first pixel and a second pixel (410, 540), and the pixel regions are arranged in a matrix form and wherein two gate lines (420, 510) defining each of said plurality of pixel portions are adjacent to each other, and the first pixel (410, 540) and the second pixel (410, 540) are formed symmetrically about said two gate lines (420, 510).

FIG. 4



Description

CLAIM OF PRIORITY

[0001] This application claims priority to and the benefit of Korean Patent Application No. 2003-87797, filed November 29, 2003, the disclosure of which is incorporated herein by reference in its entirety.

Background of the Invention

Field of the Invention

[0002] The present invention relates to an organic electroluminescence display and, more particularly, to an active matrix organic electroluminescence display in which two opposite pixels are formed in one pixel portion to achieve a high aperture ratio and to facilitate a fabrication process.

Description of the Related Art

[0003] A cathode ray tube (CRT) as one of normally used display devices is primarily used for televisions (TVs) as well as monitors of measurement instruments, information terminals, and the like. However, the cathode ray tube cannot satisfy a need for compact and lightweight electronic products because of its weight and size.

[0004] Flat panel display devices having compact and lightweight features have been attracted attention as substitutes for the CRT. The flat panel display devices include a liquid crystal display (LCD), an organic electroluminescence display (OLED), and the like.

[0005] Of these flat panel display devices, the organic electroluminescence display is an electro luminescence display that emits light when excitons are transitioned from an excited state to a ground state. The excitons are created when respective electrons and holes from an electron injection electrode (i.e., a cathode) and a hole injection electrode (i.e., an anode) are injected into an emission layer and the injected electrons and holes are combined.

[0006] This principle eliminates a need for a separate light source, which is needed for a conventional thin film liquid crystal display device. It is, therefore, possible to reduce the volume and weight of the device.

[0007] The organic electroluminescence display may be classified into a passive matrix manner and an active matrix manner according to a driving manner.

[0008] The passive matrix organic electroluminescence display may be easily fabricated because of its simple configuration. However, there are disadvantages of high power consumption and a difficulty in making a large-sized display device. Also, in making the passive matrix organic electroluminescence display, the aperture ratio is reduced as the number of lines are increased.

[0009] For these reasons, the passive matrix organic electroluminescence display is used for a small-sized display device while the active matrix organic electroluminescence display is used for a large-sized display device.

play device while the active matrix organic electroluminescence display is used for a large-sized display device.

[0010] The conventional organic electroluminescence display has a problem in that the thickness of the organic emission layer is not uniform in a stepped portion of the opening corresponding to each pixel, which makes it impossible to achieve uniform luminescence properties.

[0011] A method of forming an opening in a stripe manner to solve the aforementioned problem was introduced, as disclosed in Korean Laid-open Patent No. 2002-0077241. A method of forming an opening in a delta manner was also introduced.

[0012] There is, however, a problem that when the stripe or delta type is used to increase an aperture ratio, visibility of the organic electroluminescence display is degraded due to optical interference between adjacent pixels.

[0013] Further, in the case of forming the opening in the dot manner, the stripe type and the delta type in the organic electroluminescence display, R, G, B pixels are arranged to have the same form in uniform positions. That is, the pixels are arranged uniformly. Since the minuteness of a pattern is inversely proportional to a high aperture ratio, there is a problem associated with the manner of increasing the aperture ratio of the pixel in a stripe or delta type for a high quality data processing that requires a minute pattern as well as a high aperture ratio.

[0014] Furthermore, European patent application no. 0 935 229 discloses a display apparatus having pairs of pixels arranged on both sides of a common power feed line in order to reduce the number of power feed lines. U.S. patent application no. 6,011,531 discloses a display device in which two adjacent pixels share one single gate line. Furthermore, European patent application no. 0 293 048 and U.S. patent application no. US 5,977,562 disclose a display device in which two adjacent pixels share at least one common line. Furthermore, U.S. patent application 2002/0021268 A1 discloses an organic electroluminescence display comprising pixel regions defined by the gate lines, the data lines and the power lines, wherein the emission layer is shared by all the pixels in the same row.

SUMMARY OF THE INVENTION

[0015] It is therefore an object of the present invention to provide an improved organic electroluminescence display.

[0016] It is also an object of the present invention to solve aforementioned problems associated with conventional devices by providing an active matrix organic electroluminescence display.

[0017] It is further an object of the present invention to provide an organic electroluminescence display in which two opposite pixels are formed in one pixel portion to achieve a high aperture ratio and facilitate a fabrication process.

[0018] In order to achieve the above and other objec-

tives, an exemplary embodiment of the present invention includes: gate lines, data lines, and power lines formed on an insulating substrate; and pixel regions defined by the gate lines, the data lines, and the power lines, wherein each of the pixel regions includes a first pixel and a second pixel, the pixel regions being arranged in a matrix form, wherein the two gate lines are adjacent to each other, and the first pixel and the second pixel are formed symmetrically about said two gate lines. It is preferable that the two opposite pixels emit light of the same color. It is preferable that the two opposite pixels use emission layers as common layers. It is preferable that each of the pixel regions is integrally arranged between two adjacent gate lines and between a data line and a power line crossing the gate lines.

[0019] In another exemplary embodiment according to the present invention, an organic electroluminescence display includes: gate lines and data lines formed on an insulating substrate; and a plurality of pixel regions defined by the gate lines and the data lines, each of the plurality of pixel regions comprising a pair of emission regions, wherein the emission regions in different pixel regions from each other that emit light of the same color are arranged to be equally biased.

[0020] It is preferable that the pair of emission regions in the pixel regions use emission layers as common layers, and the pair of emission regions emit light of the same color.

[0021] In yet another exemplary embodiment according to the present invention, an organic electroluminescence display includes: gate lines and data lines formed on an insulating substrate; pixel portions partitioned by the gate lines and the data lines, each of the pixel portions having a first pixel and a second pixel, each of the first pixel and the second pixel comprising: a driving transistor for adjusting the amount of emitted light by adjusting the amount of current supplied to an organic emission portion; a switching transistor turned on by a signal applied from the gate line to apply a signal on the data line to the driving transistor; and the organic emission portion, wherein the directions of the currents applied from the switching transistors of the first pixel and the second pixel to the organic emission portions are opposite to each other.

[0022] It is preferable that each of the organic emission portions includes a pixel electrode, an organic emission layer and an upper electrode, and the first and second pixels use the organic emission layers as common layers.

[0023] In still another exemplary embodiment, two pixels in each of the pixel regions are integrally arranged between two gate lines and the two pixels are formed adjacent and opposite to each other.

[0024] In further another exemplary embodiment, two gate lines defining each of the pixel portions are adjacent to each other, and the two pixels are formed symmetrically about the two gate lines.

[0025] In still further another exemplary embodiment, two pixels share one gate line and face each other about

the power line.

[0026] In yet another exemplary embodiment, two data lines defining each of the plurality of pixel portions are adjacent to each other, two pixels are formed symmetrically about the two data lines, and the two pixels share one gate line.

BRIEF DESCRIPTION OF THE DRAWINGS

[0027] A more complete appreciation of the present invention, and many of the above and other features and advantages of the present invention, will be readily apparent as the same becomes better understood by reference to the following detailed description when considered in conjunction with the accompanying drawings in which like reference symbols indicate the same or similar components, wherein:

FIG. 1 is a top view of a conventional organic electroluminescence display;

FIG. 2 is a cross-sectional view of a conventional organic electroluminescence display;

FIG. 3 is a top view illustrating the arrangement of R, G and B pixels of a conventional organic electroluminescence display;

FIGS. 4 and 5 are top views illustrating the arrangement of R, G, B pixels of an organic electroluminescence display according to an exemplary embodiment of the present invention; and

FIG. 6 is a top view illustrating a unit pixel structure of an organic electroluminescence display according to the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0028] A conventional organic electroluminescence display will be hereinafter described with reference to the accompanying drawings.

[0029] FIG. 1 is a top view of a conventional organic electroluminescence display, and FIG. 2 is a cross-sectional view of a conventional organic electroluminescence display. In FIG. 1, the display is shown only with a capacitor, a driving transistor, and an organic electroluminescence element connected to the driving transistor.

[0030] Referring to FIG. 1, the conventional organic electroluminescence display includes a plurality of gate lines 110 insulated from one another and arranged in one direction; a plurality of data lines 120 insulated from one another and arranged in a direction intersecting with the gate lines 110; common power lines 130 insulated from one another and arranged to intersect with the gate lines 110 and to be in parallel with the data lines 120; a plurality of pixel regions 140 formed by the gate lines 110, the data lines 120 and the common power lines 130; and a plurality of pixel electrodes 150 each arranged per pixel region 140.

[0031] R, G, B unit pixels are arranged in each of the pixel regions 140. Each of the unit pixels includes an organic electroluminescence element having two thin film transistors 160 and 180, one capacitor 170, and the pixel electrode 150. Here, a reference numeral 189 denotes a via-hole for connecting a drain electrode 187 of the driving transistor 180 to the pixel electrode 150.

[0032] The switching transistor 160 of the two thin film transistors 160 and 180 includes an active layer 161 having source and drain regions, a gate electrode 163 connected to the gate line 110, and source and drain electrodes 165 and 167 connected to the source and drain regions in the active layer 161 through a contact hole. Further, the driving transistor 180 includes an active layer 181 having source and drain regions, a gate electrode 183, and source and drain electrodes 185 and 187 connected to the source and drain regions in the active layer 181 through a contact hole.

[0033] Meanwhile, the capacitor 170 includes a lower electrode 171 connected to a gate electrode 183 of the driving transistor 180 and to the drain electrode 187 of the driving transistor 180 through a contact hole, and an upper electrode 173 connected to the common power line 130 to which the source electrode 185 of the driving transistor 180 is connected through a contact hole. The pixel electrode 150 is connected to the drain electrode 187 of the driving transistor 180 through the via-hole 189.

[0034] Referring to FIG. 2, a buffer layer 210 is formed on an insulating substrate 200. An active layer 220 having source and drain regions 221 and 225 is formed on the buffer layer 210. A gate electrode 241, a lower electrode 245 of a capacitor C, and a gate line 247 are formed on a gate insulating layer 230. Source and drain electrodes 263 and 265 connected to the source and drain regions 221 and 225 through contact holes 251 and 255, an upper electrode 285 of the capacitor C connected to one of the source and drain electrodes 263 and 265, for example, the source electrode 263, and a data line 267 are formed on an interlayer insulating layer 250.

[0035] A passivation layer 270 is formed on the entire surface of the insulating substrate 200. A lower electrode 281 which is formed on the passivation layer 270 is a pixel electrode of an organic electroluminescence element E connected to one of the source and drain electrodes 263 and 265, for example the drain electrode 265 through a via-hole 275. A pixel defining layer (PDL) 290 is formed which has an opening 295 formed to expose a portion of the lower electrode 281. An organic emission layer 283 is formed on the lower electrode 281 in the opening 295, and an upper electrode 285 is formed on the entire surface of the insulating substrate 200, resulting in the organic electroluminescence element E.

[0036] Meanwhile, FIG. 3 is a top view illustrating the arrangement of R, G, B pixels of a conventional organic electroluminescence display. There is shown a structure in which each pixel is a dot matrix type.

[0037] Referring to FIG. 3, an organic electroluminescence display 300 is composed of a plurality of pixels

310 that are arranged in a matrix form. Each of the pixels 310 includes a switching transistor and a driving transistor, such as thin film transistors. The organic electroluminescence element emits light as the switching transistor of each pixel 310 is driven by voltages applied to a gate line corresponding to a row and a data line corresponding to a column. An R pixel, a G pixel and a B pixel may be arranged variously. As shown in FIG. 3, for example, the R pixel, the G pixel, and the B pixel may be arranged in the form of a straight line or a stripe (on the column).

[0038] There is, however, a problem associated with the organic electroluminescence display as described above that the thickness of the organic emission layer is not uniform in a step of the opening corresponding to each pixel shown in FIG. 3, which makes it impossible to achieve uniform luminescence properties.

[0039] Hereinafter, exemplary embodiments of the present invention will be described with reference to the accompanying drawings.

[0040] FIG. 4 is a top view illustrating the arrangement of R, G, B pixels of an organic electroluminescence display according to an exemplary embodiment of the present invention. There is shown a structure in which two adjacent pixels are arranged in a non-uniform manner.

[0041] Referring to FIG. 4, in an organic electroluminescence display 400 of the present invention, two pixels 410 for each of the R, G, B pixels are formed adjacent and opposite to each other. Each of the pixels 410 is composed of a switching thin film transistor, a capacitor, a driving thin film transistor, and an organic electroluminescence element connected to the driving thin film transistor. The organic electroluminescence element emits light as the switching thin film transistor and the driving thin film transistor are driven with a gate line 420 corresponding to a row of each pixel 410, a data line 430 corresponding to a column thereof, and a power line 440. The R, G, B pixels may be arranged variously. The pixels may be arranged, for example, in the form of a straight line (i.e., a column), as shown in FIG. 4.

[0042] The respective R, G, B pixels 410 are arranged in a non-uniform manner, unlike the pixels of the conventional organic electroluminescence display that are arranged in a uniform manner. In other words, the respective pixels are not formed in the same position and form, but two adjacent pixels are formed opposite to each other (i.e., a mirror image). The device has a structure in which the two opposite pixels are repeated.

[0043] FIG. 5 is a top view illustrating an organic electroluminescence display according to a first exemplary embodiment of the present invention, in which each of the two adjacent pixels opposite to each other in FIG. 4 is shown only with a switching transistor, a capacitor, a driving transistor, and an organic electroluminescence element connected to the driving transistor.

[0044] Referring to FIG. 5, the organic electroluminescence display of the present invention has a structure in

which two pixels are formed opposite to each other within a pixel region defined by a data line 520, a power line 530, and two gate lines 510, namely, a non-uniform arrangement structure in which the pixels are formed in different positions from each other. In other words, when an organic emission layer is formed on a pixel electrode 550, the organic emission layer is integrally formed on one pixel electrode as well as on the opposite pixel electrode, namely, in the pixel region defined by the data line 520, the power line 530, and two gate lines 510.

[0045] One pixel includes a switching thin film transistor 560, a driving thin film transistor 580, a capacitor 570, and an emission region emitting light, wherein an organic electroluminescence element connected to the driving thin film transistor 580 is formed in the emission region.

[0046] A drain electrode 567 of the switching thin film transistor 560 is connected to the data line 520, a source electrode 565 is connected to a lower electrode 571 of the capacitor 570, and the gate electrode 563 is connected to the gate line 510.

[0047] A source electrode 585 of the driving thin film transistor 580 is connected to the power line 530, a drain electrode 587 is connected to the pixel electrode 550 through a via hole 589, and a gate electrode 583 is connected to an upper electrode 573 of the capacitor 570.

[0048] In each of the pixels of the organic electroluminescence display formed as described above, the data line 520 delivers an image signal, the gate line 510 delivers a selection signal, the switching thin film transistor 560 delivers data to the capacitor 570 in response to the selection signal of the gate line 510, and the capacitor 570 stores and holds the applied data. The driving thin film transistor 580 supplies current to the pixel electrode 550 to drive the organic electroluminescence element.

[0049] The two adjacent pixels also have the respective opposite current directions. In other words, a signal begins to be delivered through the gate lines 510 formed at both sides of the pixel portion and arrives at the organic electroluminescence element, which is similar to a direction when viewed in front of a mirror.

[0050] Further, the emission regions are equally biased, wherein in the emission regions, light emitted from each pixel in different pixel portions from each other, i.e., the pixel composed of the switching and driving thin film transistors, the capacitor, and the organic emission layer is taken out.

[0051] One pixel of the organic electroluminescence display of the present invention includes a driving thin film transistor having an active layer which is formed on an insulating substrate having a buffer layer and which has source and drain regions, a gate electrode formed on a gate insulating layer, and source and drain electrodes electrically connected to the source and drain regions through a contact hole. The pixel also includes an organic electroluminescence element composed of a lower electrode electrically connected to the thin film transistor, an organic emission layer, and an upper electrode.

[0052] The first pixel and the second pixel which are

adjacent to each other are opened with the organic emission layer being shared therewith, and are formed opposite to each other. In other words, the two pixels face each other and have a structure in which respective components are arranged opposite to each other.

[0053] FIG. 6 is a top view illustrating an organic electroluminescence display according to a second exemplary embodiment of the present invention.

[0054] Referring to FIG. 6, a pixel structure of the organic electroluminescence display in the second exemplary embodiment has the same components as those in the first exemplary embodiment except that there is a difference in the arrangement of the components. In the first exemplary embodiment, two pixels 540 are integrally arranged between two gate lines 510 and are formed adjacent and opposite to each other while in the second exemplary embodiment, two gate lines 510 are formed adjacent to each other and the pixels 540 are formed symmetrically about the gate line 510.

[0055] In the above-described exemplary embodiments of the present invention, because two opposite adjacent pixels of the same color share the organic emission layers and the organic emission layers are opened simultaneously, it is possible to obtain a higher aperture ratio compared to the method of forming the opening of the pixel in the conventional dot manner.

[0056] Further, it is possible to achieve the visibility of the organic electroluminescence display, because a more precise pattern is obtained as compared to the method of forming the opening of the pixel in the conventional stripe or delta manner.

[0057] As described above, according to the present invention, it is possible to provide an active matrix organic electroluminescence display in which two opposite pixels are formed in one pixel portion to achieve a high aperture ratio and to facilitate a fabrication process.

[0058] Although the preferred embodiments of the present invention have been described, it will be appreciated by those skilled in the art that various modifications and variations may be made to the present invention without departing from the scope of the present invention as set forth in the appending claims.

Claims

1. An organic electroluminescence display (400), comprising:

gate lines (420, 510), data lines (430, 520), and power lines (440, 530) formed on an insulating substrate; and
pixel regions defined by the gate lines (420, 510), the data lines (430, 520) and the power lines (440, 530), each of the pixel regions comprising a first pixel (410, 540) and a second pixel (410, 540) adjacent to each other, the pixel regions being arranged in a matrix form,

wherein two gate lines (420, 510) defining each of said plurality of pixel portions are adjacent to each other, and the first pixel (410, 540) and the second pixel (410, 540) are formed symmetrically about said two gate lines (420, 510).

5

2. The device according to claim 1, wherein the first pixel (410, 540) and the second pixel (410, 540) emit light of the same color.

10

3. The device according to claim 1, wherein the first pixel (410, 540) and the second pixel (410, 540) share an emission layer.

4. The device according to one of the preceding claims, each of said first pixel (410, 540) and said second pixel (410, 540) comprising:

15

a driving transistor (580) for adjusting the amount of emitted light by adjusting the amount of current supplied to an organic emission portion;

20

a switching transistor (560) adapted to be turned on by a signal applied from the gate line (420, 510) to apply a signal on the data line (430, 520) to the driving transistor (580); and an organic emission portion;

25

wherein the switching transistors (560) of the first pixel (410, 540) and the second pixel (410, 540) are adapted to apply currents of opposite directions to the organic emission portion.

30

5. The device according to claim 4, wherein each of the organic emission portions includes a pixel electrode (550), an organic emission layer, and an upper electrode, and wherein the first pixel and the second pixel share the organic emission layer.

35

40

45

50

55

FIG. 1
(PRIOR ART)




FIG. 2
(PRIOR ART)




FIG. 3
(PRIOR ART)




FIG. 4




FIG. 5





FIG. 6





EUROPEAN SEARCH REPORT

Application Number
EP 14 16 9766

5

10

15

20

25

30

35

40

45

50

55

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
X	EP 0 935 229 A (SEIKO EPSON CORPORATION) 11 August 1999 (1999-08-11)	1	INV. H01L51/50 H01L27/32 G09G3/32
Y	* paragraph [0024] - paragraph [0029];	2,3	
A	figures 2-3 *	4,5	
Y	US 6 011 531 A (MEI ET AL) 4 January 2000 (2000-01-04)	2	
A	* the whole document *	1	
	* figures 2,10,12-23 *		
A	EP 0 293 048 A (PHILIPS ELECTRONIC AND ASSOCIATED INDUSTRIES LIMITED; N.V. PHILIPS' GL) 30 November 1988 (1988-11-30) * the whole document *	1-3	
	* figures 4,5 *		
A	US 5 977 562 A (HIRAKATA ET AL) 2 November 1999 (1999-11-02) * the whole document *	1-3	TECHNICAL FIELDS SEARCHED (IPC) H01L G09G
	* figures 14,15,18,20 *		
A	US 2003/085340 A1 (STREET ROBERT A) 8 May 2003 (2003-05-08) * figures 4,5 *	1-3	
Y	JP 2003 229616 A (CANON KK) 15 August 2003 (2003-08-15) * abstract *	3	
Y	EP 1 331 666 A2 (SEMICONDUCTOR ENERGY LAB [JP]) 30 July 2003 (2003-07-30) * paragraph [0064]; figure 1B *	3	
The present search report has been drawn up for all claims			
Place of search Munich		Date of completion of the search 9 September 2014	Examiner Bernabé Prieto, A
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 03.82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 14 16 9766

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

09-09-2014

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0935229 A	11-08-1999	CN 1231046 A	06-10-1999
		CN 1485807 A	31-03-2004
		CN 1485808 A	31-03-2004
		DE 69829356 D1	21-04-2005
		DE 69829356 T2	28-07-2005
		EP 0935229 A1	11-08-1999
		EP 1505650 A2	09-02-2005
		EP 1505651 A2	09-02-2005
		EP 1505652 A2	09-02-2005
		EP 2112693 A2	28-10-2009
		JP 3520396 B2	19-04-2004
		JP H1124606 A	29-01-1999
		KR 20050084306 A	26-08-2005
		KR 20050085670 A	29-08-2005
		TW 388854 B	01-05-2000
		US 6618029 B1	09-09-2003
		US 2003151568 A1	14-08-2003
		US 2003193493 A1	16-10-2003
		US 2005052371 A1	10-03-2005
		US 2008158209 A1	03-07-2008
		US 2008165174 A1	10-07-2008
		US 2008198152 A1	21-08-2008
		WO 9901856 A1	14-01-1999
US 6011531 A	04-01-2000	JP 4138053 B2	20-08-2008
		JP H10222097 A	21-08-1998
		US 6011531 A	04-01-2000
EP 0293048 A	30-11-1988	EP 0293048 A2	30-11-1988
		GB 2205191 A	30-11-1988
		JP S63311388 A	20-12-1988
		US 4931787 A	05-06-1990
US 5977562 A	02-11-1999	US 5977562 A	02-11-1999
		US 6268617 B1	31-07-2001
		US 2001045556 A1	29-11-2001
US 2003085340 A1	08-05-2003	US 6593557 B1	15-07-2003
		US 2003085340 A1	08-05-2003
JP 2003229616 A	15-08-2003	JP 4366039 B2	18-11-2009
		JP 2003229616 A	15-08-2003
EP 1331666 A2	30-07-2003	CN 1434668 A	06-08-2003
		CN 101369634 A	18-02-2009
		CN 102214796 A	12-10-2011

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.

EP 14 16 9766

5

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

09-09-2014

10

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
		EP 1331666 A2	30-07-2003
		EP 2509109 A2	10-10-2012
		JP 2010153397 A	08-07-2010
		JP 2012094538 A	17-05-2012
		JP 2013175470 A	05-09-2013
		KR 20030064303 A	31-07-2003
		SG 126714 A1	29-11-2006
		SG 143063 A1	27-06-2008
		TW 1277359 B	21-03-2007
		TW 1278255 B	01-04-2007
		US 2003137325 A1	24-07-2003
		US 2005012105 A1	20-01-2005
		US 2007114921 A1	24-05-2007
		US 2010230664 A1	16-09-2010
		US 2012097994 A1	26-04-2012

15

20

25

30

35

40

45

50

55

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- KR 200387797 [0001]
- KR 20020077241 [0011]
- EP 0935229 A [0014]
- US 6011531 A [0014]
- EP 0293048 A [0014]
- US 5977562 A [0014]
- US 20020021268 A1 [0014]

专利名称(译)	有机电致发光显示器		
公开(公告)号	EP2790241A1	公开(公告)日	2014-10-15
申请号	EP2014169766	申请日	2004-11-29
[标]申请(专利权)人(译)	三星显示有限公司		
申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	KIM IEE GON KIM TAE HYUNG		
发明人	KIM, IEE-GON KIM, TAE-HYUNG		
IPC分类号	H01L51/50 H01L27/32 G09G3/32 H05B33/12 G09F9/30 G09G3/20 G09G3/30		
优先权	1020030087797 2003-11-29 KR		
外部链接	Espacenet		

摘要(译)

一种有源矩阵有机电致发光显示器 (400) , 其中第一像素和第二像素 (410,540) 形成在一个像素部分中, 以实现高孔径比并便于制造工艺。有机电致发光显示器由在绝缘基板上形成的栅极线 (420,510) , 数据线 (430,520) 和电源线 (440,530) 以及由栅极线限定的像素区域构成。 (420,510) , 数据线 (430,520) 和电源线 (440,530) , 其中每个像素区域包括第一像素和第二像素 (410,540) , 并且排列像素区域以矩阵形式并且其中限定所述多个像素部分中的每一个的两条栅极线 (420,510) 彼此相邻, 并且第一像素 (410,540) 和第二像素 (410,540) 关于对称地形成所述两条栅极线 (420,510) 。

FIG. 4

