



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 657 763 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
17.05.2006 Bulletin 2006/20

(51) Int Cl.:
H01L 51/52 (2006.01)

(21) Application number: **05022910.3**

(22) Date of filing: **20.10.2005**

(84) Designated Contracting States:
**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HU IE IS IT LI LT LU LV MC NL PL PT RO SE SI
SK TR**
Designated Extension States:
AL BA HR MK YU

(72) Inventor: **Son, Woo Hyun**
Gum-si
Gyeongsangbuk-do (KR)

(74) Representative: **Zech, Stefan Markus et al**
Meissner, Bolte & Partner GbR
(Depotstrasse 5 1/2, 86199 Augsburg)
Postfach 10 26 05
86016 Augsburg (DE)

(30) Priority: **11.11.2004 KR 2004092140**


(71) Applicant: **LG ELECTRONICS INC.**
Seoul (KR)

(54) Organic electro-luminescence display device and fabricating method thereof

(57) There are disclosed an organic electro luminescence display device that is adaptive for improving its contrast ratio, and a fabricating method thereof.
An organic electro luminescence display device ac-

cording to an embodiment of the present invention includes an anode electrode formed on a substrate; and a concavo-convex area formed on the substrate in an area except for an area where the anode electrode is formed.

FIG. 4



EP 1 657 763 A1

Description

[0001] This application claims the benefit of the Korean Patent Application No. P2004-92140 filed on November 11, 2004, which is hereby incorporated by reference.

BACKGROUND OF THE INVENTION

Field of the Invention

[0002] The present invention relates to an organic electro luminescence display device, and more particularly to an organic electro luminescence display device that is adaptive for improving its contrast ratio, and a fabricating method thereof.

Description of the Related Art

[0003] Recently, there have been developed a variety of flat panel display devices that can reduce their weight and size, which are a disadvantage of a cathode ray tube CRT. The flat panel display device includes a liquid crystal display LCD, a field emission display FED, a plasma display panel PDP and an electro luminescence EL display device.

[0004] Especially, the EL display device basically has a shape of sticking an electrode to both side surfaces of an organic light emitting layer which is made up of a hole transport layer, a light emitting layer and an electron transport layer, and the EL display device attracts attention as a next generation flat panel display because of its wide viewing angle, high aperture ratio, high color sense and so on.

[0005] The EL display device is largely divided into an inorganic EL display device and an organic EL display device in accordance with a material used. The organic EL display device among these has an advantage of being driven with lower voltage than an inorganic EL display device because electrons and holes form pairs and then they become extinct to emit light when electric charges are injected into an organic EL layer which is formed between a hole injection electrode and an electron injection electrode. Further, the organic EL display device can form elements even on a transparent substrate which is flexible like plastics, and the organic EL display device can be driven at a low voltage of below 10V, has relatively low power consumption and has excellent color sense in comparison with the PDP or the inorganic EL display device.

[0006] FIG. 1 is a perspective view representing a related art organic EL display device, and FIG. 2 is a diagram representing the organic EL display device shown in FIG. 1, taken along the line I-I'

[0007] The organic EL display device shown in FIG. 1 has a first electrode (or an anode electrode) 4 and a second electrode (or a cathode electrode) 12 formed on a substrate 2 in a direction of crossing each other.

[0008] A plurality of anode electrodes 4 are formed on

the substrate 2 to be separated from each other with a designated gap. An insulating film 6 having an aperture part for each EL cell area is formed on the substrate 2 where the anode electrode 4 is formed. Barrier ribs 8 are located on the insulating film 6 for separating an organic light emitting layer 10 and the cathode electrode 12 which are to be formed thereon. The barrier ribs 8 are formed in a direction of crossing the anode electrode 4 and have a reverse taper structure where an upper end part has a wider width than a lower end part. The organic light emitting layer 10 and the cathode electrode 12 formed of an organic compound are sequentially deposited over the entire surface of the insulating film 6 where the barrier ribs 8 are formed. The organic light emitting layer 10 has a hole transport layer, a light emitting layer and an electron transport layer deposited and formed on the insulating film. The organic EL display device has electrons and holes emitted if a driving signal is applied to the anode electrode 4 and the cathode electrode 12, and the electrons and holes emitted from the anode electrode 4 and the cathode electrode 12 are recombined within the organic light emitting layer 10 to generate a visible ray. At this moment, the generated visible ray exits to the outside through the anode electrode 4 to display a designated picture or image.

[0009] On the other hand, in the related art organic EL display device, the light incident from the outside almost completely transmits the anode electrode 4, the barrier rib 8 and the organic light emitting layer 10. As a result, when the light is not emitted from the organic light emitting layer 10, as shown in FIG. 3, an external light 40 being incident from the surface of the substrate 2 transmits the organic light emitting layer 10 and the anode electrode 4 of a transparent conductive material, and is reflected by the cathode electrode 12 of metal electrode to exit to the outside of the device. Accordingly, there is a problem in that its contrast ratio is deteriorated.

SUMMARY OF THE INVENTION

[0010] Accordingly, it is an object of the present invention to provide an organic electro luminescence display device that is adaptive for improving its contrast ratio by intercepting an external light, and a fabricating method thereof.

[0011] In order to achieve these and other objects of the invention, an organic electro luminescence display device according to an aspect of the present invention includes an anode electrode formed on a substrate; and a concavo-convex area formed on the substrate in an area except for an area where the anode electrode is formed.

[0012] In the organic electro luminescence display device further includes an insulating film which partially exposes the anode electrode to define a light emitting area; an organic light emitting layer formed on the light emitting area; and a cathode electrode which crosses the anode electrode with the organic light emitting layer therebe-

tween, and wherein the concavo-convex area intercepts a progress path of an external light which is incident to the anode electrode and reflected in the cathode electrode.

[0013] A fabricating method of an organic electro luminescence display device according to another aspect of the present invention includes the steps of forming a concavo-convex area in an area except for an area where an anode electrode is formed on a substrate; forming the anode electrode in an area except for the concavo-convex area; forming an insulating film which partially exposes the anode electrode to define a light emitting area; forming an organic light emitting layer on the light emitting area; and forming a cathode electrode which crosses the anode electrode with the organic light emitting layer therebetween.

[0014] In the fabricating method, the concavo-convex area which is formed on the substrate is formed by use of at least any one of a laser, a photolithography process and a sand blast process.

[0015] In the fabricating method, the concavo-convex area intercepts an external light.

BRIEF DESCRIPTION OF THE DRAWINGS

[0016] These and other objects of the invention will be apparent from the following detailed description of the embodiments of the present invention with reference to the accompanying drawings, in which:

[0017] FIG. 1 a perspective view briefly illustrating a related art organic electro luminescence display device;

[0018] FIG. 2 is a sectional diagram representing the organic electro luminescence display device shown in FIG. 1, taken along the line I-I' ;

[0019] FIG. 3 is a diagram representing that an incident external light is reflected in a cathode electrode of an organic electro luminescence display device;

[0020] FIG. 4 is a perspective view representing an organic electro luminescence display device according to an embodiment of the present invention;

[0021] FIG. 5 is a sectional diagram representing the organic electro luminescence display device shown in FIG. 4, taken along the line II-II' ;

[0022] FIG. 6 is a diagram representing a light shielding role of a concavo-convex area shown in FIG. 5; and

[0023] FIGs. 7A to 7F are diagrams representing a fabricating method of a related art organic electro luminescence display device.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

[0024] Reference will now be made in detail to the preferred embodiments of the present invention, examples of which are illustrated in the accompanying drawings.

[0025] With reference to FIGs. 4 to 7 F, embodiments of the present invention will be explained as follows.

[0026] FIG. 4 is a perspective view representing an

organic EL display device according to an embodiment of the present invention, and FIG. 5 is a sectional diagram illustrating the organic EL display device, taken along the line II-II' shown in FIG. 4.

[0027] An organic EL display device shown in FIGs. 4 and 5 has a first electrode (or an anode electrode) 104 and a second electrode (or a cathode electrode) 112 formed on a display area P1 of a substrate 102 in a direction of crossing each other, and includes a concavo-convex area (A) formed in an area except for an area where the first electrode 104 is located in the display area P1 of the substrate 102.

[0028] A plurality of anode electrodes 104 are formed on the substrate 102 to be separated from each other with a designated gap. An insulating film 106 having an aperture part for each EL cell area is formed on the substrate 102 where the anode electrode 104 is formed. Barrier ribs 108 are located on the insulating film 106 for separating an organic light emitting layer 110 and the cathode electrode 112 which are to be formed thereon. The barrier ribs 108 are formed in a direction of crossing the anode electrode 104 and have a reverse taper structure where an upper end part has a wider width than a lower end part. The organic light emitting layer 110 and the cathode electrode 112 formed of an organic compound are sequentially deposited over the entire surface of the insulating film 106 where the barrier ribs 108 are formed. The organic light emitting layer 110 has a hole transport layer, a light emitting layer and an electron transport layer deposited and formed on the insulating film 106.

[0029] The concavo-convex area (A) plays the role of shielding or absorbing an external light. That is, the concavo-convex area (A) is a uneven area which is damaged by irradiating a laser to the substrate 102 or formed by use of a photo resist process and an etching process, so that the concavo-convex area (A) plays the role of shielding the external light.

[0030] In other words, the external light 140 being incident to the substrate 102, as shown in FIG. 6, becomes extinct by a plurality of reflection within the concavo-convex area (A), and the external light 140 being incident through an area except for the concavo-convex area (A) is reflected by the cathode electrode 112, and then the external light 140 almost cannot exit to the outside and becomes extinct by the concavo-convex area (A). In this way, the concavo-convex area (A) intercepts a progress path of the external light, thereby enabling to improve its contrast ratio.

[0031] In this way, in the organic EL display device according to the present invention, the concavo-convex area (A) is formed in an area except for the anode electrode 104 on the display area P1. The concavo-convex area (A) intercepts a considerable amount of the external light which is incident to the inside of the device from the outside, and plays the role of also intercepting the external light which is partially transmitted and reflected in the cathode electrode 112. Accordingly, the contrast ratio is

improved.

[0032] Hereinafter, in reference to FIGs. 7A to 7F, a fabricating method of the related art organic EL display device is described as follows.

[0033] Firstly, after providing a substrate 102 which is formed by use of soda lime or hard glass, a laser is irradiated to an area except for an area where the anode electrode 104 is to be formed in the display area P1 of the substrate 102 so as to give damage to the surface of the substrate 102, or a photolithography process and an etching process are performed, thereby forming the concavo-convex area (A) on the substrate 102, as shown in FIG. 7A. On the other hand, the concavo-convex area (A) can be formed by use of a sand blast method using a dry film resist DFR instead of the photolithography process and the dry etching process.

[0034] After depositing a transparent conductive metal material on the substrate 102 where the concavo-convex area (A) is formed, the transparent conductive metal material is patterned by the photolithography process and the etching process, thereby forming the anode electrode 104, as shown in FIG. 7B. Herein, the metal material is indium tin oxide or SnO₂.

[0035] After forming a photo sensitive insulating material on the substrate 102 where the anode electrode 104 is formed, the photo sensitive insulating material is patterned by the photolithography process, thereby partially exposing the anode electrode 104 to form the insulating film 106 which defines a light emitting area, as shown in FIG. 7C.

[0036] After a photo sensitive organic material is deposited on the substrate 102 where the insulating film 106 is formed, the photo sensitive organic material is patterned by the photolithography process, thereby forming the barrier rib 108, as shown in FIG. 7D. The barrier rib 108 is formed in a non light emitting area to cross a plurality of anode electrodes 104 for dividing pixels.

[0037] An organic material is deposited on the substrate 102 where the barrier rib 108 is formed by use of a thermal deposition method and a vacuum deposition method, thereby forming the organic light emitting layer 110, as shown in FIG. 7E.

[0038] A metal material is deposited on the substrate 102 where the organic light emitting layer 110 is formed, thereby forming the cathode electrode 112, as shown in FIG. 7F.

[0039] As described above, the organic EL display device and the fabricating method thereof according to the present invention has the concavo-convex area formed in the area except for the anode electrode on the display area. The concavo-convex area intercepts a considerable amount of the external light which is incident to the inside of the device from the outside, and plays the role of also intercepting the external light which is partially transmitted and reflected in the cathode electrode. Accordingly, the contrast ratio is improved.

[0040] Although the present invention has been explained by the embodiments shown in the drawings de-

scribed above, it should be understood to the ordinary skilled person in the art that the invention is not limited to the embodiments, but rather that various changes or modifications thereof are possible without departing from the spirit of the invention. Accordingly, the scope of the invention shall be determined only by the appended claims and their equivalents.

10 Claims

1. An organic electro luminescence display device, comprising:

an anode electrode formed on a substrate; and
a concavo-convex area formed on the substrate in an area except for an area where the anode electrode is formed.

2. The organic electro luminescence display device according to claim 1, further comprising:

an insulating film which partially exposes the anode electrode to define a light emitting area;
an organic light emitting layer formed on the light emitting area; and
a cathode electrode which crosses the anode electrode with the organic light emitting layer therebetween,

and
wherein the concavo-convex area intercepts a progress path of an external light which is incident to the anode electrode and reflected in the cathode electrode.

3. A fabricating method of an organic electro luminescence display device, comprising the steps of:

forming a concavo-convex area in an area except for an area where an anode electrode is formed on a substrate;
forming the anode electrode in an area except for the concavo-convex area;
forming an insulating film which partially exposes the anode electrode to define a light emitting area;
forming an organic light emitting layer on the light emitting area; and
forming a cathode electrode which crosses the anode electrode with the organic light emitting layer therebetween.

4. The fabricating method according to claim 3, wherein the concavo-convex area which is formed on the substrate is formed by use of at least any one of a laser, a photolithography process and a sand blast process.

5. The fabricating method according to claim 3, wherein the concavo-convex area intercepts an external light.

5

10

15

20

25

30

35

40

45

50

55

FIG. 1
RELATED ART




FIG.2
RELATED ART




FIG. 3
RELATED ART




FIG. 4




FIG.5




FIG.6




FIG. 7A




FIG.7B




FIG. 7C




FIG. 7D




FIG. 7E





FIG. 7F





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 05 02 2910

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
X	US 2003/062520 A1 (TOGUCHI SATORU ET AL) 3 April 2003 (2003-04-03) * the whole document *	1-5	H01L51/52
X	US 2004/211971 A1 (TAKEI MANABU ET AL) 28 October 2004 (2004-10-28) * the whole document *	1-5	
A	US 2001/033135 A1 (DUGGAL ANIL RAJ ET AL) 25 October 2001 (2001-10-25) * the whole document *	1-5	
A	US 2003/107314 A1 (URABE TETSUO ET AL) 12 June 2003 (2003-06-12) * the whole document *	1-5	
			TECHNICAL FIELDS SEARCHED (IPC)
			H01L
The present search report has been drawn up for all claims			
Place of search Munich		Date of completion of the search 10 February 2006	Examiner Saldamli, S
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

2
EPO FORM 1503 03.82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 05 02 2910

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

10-02-2006

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2003062520 A1	03-04-2003	CN 1411325 A	16-04-2003
		JP 2003115377 A	18-04-2003

US 2004211971 A1	28-10-2004	CN 1545824 A	10-11-2004
		EP 1504631 A1	09-02-2005
		WO 03096755 A1	20-11-2003
		JP 2003332067 A	21-11-2003
		TW 595255 B	21-06-2004

US 2001033135 A1	25-10-2001	NONE	

US 2003107314 A1	12-06-2003	CN 1426269 A	25-06-2003
		JP 2003234186 A	22-08-2003
		SG 107123 A1	29-11-2004
		TW 223969 B	11-11-2004

专利名称(译)	有机电致发光显示装置及其制造方法		
公开(公告)号	EP1657763A1	公开(公告)日	2006-05-17
申请号	EP2005022910	申请日	2005-10-20
申请(专利权)人(译)	LG电子株式会社.		
当前申请(专利权)人(译)	LG电子株式会社.		
[标]发明人	SON WOO HYUN		
发明人	SON, WOO HYUN		
IPC分类号	H01L51/52 H01L51/50 H05B33/02		
CPC分类号	H01L51/5281 H01L27/3281 H01L51/52		
优先权	1020040092140 2004-11-11 KR		
外部链接	Espacenet		

摘要(译)

公开了一种适于改善其对比度的有机电致发光显示装置及其制造方法。根据本发明实施方案的有机电致发光显示装置包括形成在基板上的阳极;在除了形成阳极的区域之外的区域中,在基板上形成凹凸区域。

FIG.4

