



US008304981B2

(12) **United States Patent**
Kim et al.

(10) **Patent No.:** **US 8,304,981 B2**
(45) **Date of Patent:** **Nov. 6, 2012**

(54) **ORGANIC LIGHT EMITTING DIODE
DISPLAY AND MANUFACTURING METHOD
THEREOF**

2005/0017244 A1* 1/2005 Hoffman et al. 257/72
2005/0250260 A1* 11/2005 Hayase et al. 438/149
2007/0099333 A1* 5/2007 Moriya 438/96
2007/0188089 A1* 8/2007 Choi et al. 313/506
2008/0035920 A1* 2/2008 Takechi et al. 257/43

(75) Inventors: **Mu-Gyeom Kim**, Hwaseong-si (KR);
Byoung-Seong Jeong, Yongin-si (KR);
Seong-Kweon Heo, Suwon-si (KR);
Min-Chul Shin, Seoul (KR); **Jong-Moo**
Huh, Hwaseong-si (KR); **Chang-Mo**
Park, Hwaseong-si (KR)

FOREIGN PATENT DOCUMENTS

JP	08-330600	12/1996
JP	2006-203073	8/2006
KR	100567272	3/2006
KR	100684835	2/2007
KR	100696522	3/2007
KR	100708722	4/2007
KR	100712210	4/2007
KR	1020070102969	10/2007
KR	100787439	12/2007

(73) Assignee: **Samsung Display Co., Ltd.**, Yongin,
Gyeonggi-Do (KR)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 104 days.

(Continued)

OTHER PUBLICATIONS

(21) Appl. No.: **12/433,093**

English Abstract for Publication No. 08-330600.

(22) Filed: **Apr. 30, 2009**

(Continued)

(65) **Prior Publication Data**

US 2010/0133991 A1 Jun. 3, 2010

Primary Examiner — Karabi Guharay

(74) *Attorney, Agent, or Firm* — F. Chau & Associates, LLC

(30) **Foreign Application Priority Data**

Dec. 1, 2008 (KR) 10-2008-0120713

(57) **ABSTRACT**

(51) **Int. Cl.**
H01L 51/00 (2006.01)
(52) **U.S. Cl.** **313/504; 257/59**
(58) **Field of Classification Search** 313/504,
313/506; 257/72, 40, 59
See application file for complete search history.


An organic light emitting diode display includes a substrate. A control electrode is on the substrate. A gate insulating film covers the control electrode. An input electrode and an output electrode are on the gate insulating film and face each other. An oxide semiconductor is between the input electrode and the output electrode and on the control electrode. A pixel electrode is on portions of the edges of the output electrode and is electrically connected. An organic light emitting member is on the pixel electrode. A common electrode is on the organic light emitting member. The oxide semiconductor and the pixel electrode may be of the same layer.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,943,372 B2 9/2005 Lin
7,208,756 B2 4/2007 Shih et al.
2002/0056838 A1* 5/2002 Ogawa 257/59

10 Claims, 12 Drawing Sheets



FOREIGN PATENT DOCUMENTS

KR	100810645	2/2008
KR	1020080011829	2/2008
KR	1020080077829	2/2008
KR	1020080052107	6/2008
KR	100845557	7/2008


OTHER PUBLICATIONS

English Abstract for Publication No. 100567272.
English Abstract for Publication No. 2006-203073.
English Abstract for Publication No. 100684835.

English Abstract for Publication No. 100696522.
English Abstract for Publication No. 100708722.
English Abstract for Publication No. 100712210.
English Abstract for Publication No. 1020070102969.
English Abstract for Publication No. 100787439.
English Abstract for Publication No. 1020080011829.
English Abstract for Publication No. 100810645.
English Abstract for Publication No. 1020080052107.
English Abstract for Publication No. 100845557.

* cited by examiner

FIG. 1






FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11





FIG. 12



ORGANIC LIGHT EMITTING DIODE DISPLAY AND MANUFACTURING METHOD THEREOF

CROSS-REFERENCE TO RELATED APPLICATION

This application claims priority to and the benefit of Korean Patent Application No. 10-2008-0120713 filed in the Korean Intellectual Property Office on Dec. 1, 2008, the entire contents of which are incorporated herein by reference.

BACKGROUND OF THE INVENTION

(a) Field of the Invention

The present disclosure relates to display devices, and, more particularly, to an organic light emitting diode (OLED) display and a manufacturing method thereof.

(b) Discussion of the Related Art

With the demand for lightweight and thin monitors or televisions liquid crystal displays ("LCDs") are being substituted for conventional cathode ray tubes ("CRTs").

However, since the LCD is a light receiving/emitting device, the LCD requires a backlight, and may have a slow response speed and limited viewing angle as compared with the conventional CRT.

In recent years, an OLED display has attracted attention as a display device due to its faster response speed and wider viewing angle.

The OLED display includes two electrodes and a light emitting layer positioned therebetween. Electrons injected from one electrode and holes injected from the other electrode are combined in the light emitting layer so as to form excitons, and the excitons emit light through energy emission.

Since the OLED display is a self-emitting type, it does not need an additional light source. Therefore, the OLED display has low power consumption, as well as excellent response speed, viewing angle, and contrast ratio.

An OLED display can be classified as a passive matrix OLED display and an active matrix OLED display according to its driving mode.

Among these, an active matrix OLED display has a structure in which electrodes and a light emitting layer are on a thin film transistor display panel, and the thin film transistor display panel includes signal lines, a switching thin film transistor connected to the signal lines that controls a data voltage, and a driving thin film transistor that flows a current into a organic light emitting device by supplying the data voltage received from the switching thin film transistor as a gate voltage.

A semiconductor constituting the channel layer of the thin film transistor of the OLED display may have its characteristics changed during a photolithography process for forming another thin film, and such a change of characteristics of the semiconductor may deteriorate the performance of the thin film transistor.

An oxide semiconductor can be used for the semiconductor constituting the channel layer of the thin film transistor of the OLED display. When an oxide semiconductor is used, the characteristics of the semiconductor layer may deteriorate due to light. Thus, it is important to block external light.

Further, when forming a thin film transistor, an organic light emitting element, and thin film layers such as an anode and a cathode of an OLED display, a photolithography process is used involving a mask. As the number of masks used in each photolithography process increases, the manufacturing process becomes complicated and the manufacturing cost

increases. Therefore, in order to improve the productivity of OLED displays, it becomes desirable to form a thin film layer using a smaller number of masks.

SUMMARY OF THE INVENTION

In accordance with exemplary embodiments of the present invention an OLED display is provided which minimizes the influence on a semiconductor layer during the formation of another thin film layer, raises the productivity of the OLED display by simplifying the manufacturing process, and prevents deterioration of the performance of an oxide semiconductor caused by external light.

An OLED display according to an exemplary embodiment of the present invention includes: a substrate; a control electrode on the substrate; a gate insulating film that covers the control electrode; an input electrode and an output electrode on the gate insulating film and facing each other; an oxide semiconductor between the input electrode and the output electrode and on the control electrode; a pixel electrode on and electrically connected to portions of the edges of the output electrode; an organic light emitting member on the pixel electrode; and a common electrode on the organic light emitting member.

The oxide semiconductor and the pixel electrode may be a same layer, and may include hydrogen injected into the upper part thereof.

The OLED display may further include an insulation film covering the oxide semiconductor and having a first opening exposing the pixel electrode, and the organic light emitting member may be in the first opening.

The insulating film may include a black pigment.

The gate insulating film may have a second opening, and the OLED display may further include a blocking portion that covers the second opening may be further provided.

The lower edges of the oxide semiconductor may be surrounded by the control electrode, the input electrode and the output electrode, and the blocking portion.

A surface of the pixel electrode may be plasma treated.

The gate insulating layer may have a third opening, and the OLED display may further include a blocking portion that covers the third opening is further provided.

The blocking portion may include a black pigment.

The blocking portion may be made of a same material as the input electrode and the output electrode.

Edges of the oxide semiconductor proximal to the substrate may be surrounded by the control electrode, the input electrode, the output electrode, and the blocking member.

A width of the oxide semiconductor may be smaller than a width of the input electrode and a width of the output electrode.

The pixel electrode may be formed directly on the portions of edges of the output electrode.

A manufacturing method of an OLED display according to one exemplary embodiment of the present invention includes: forming a control electrode on a substrate; forming a gate insulating film on the control electrode; forming an input electrode and an output electrode that face each other on the gate insulating film; forming a semiconductor on the control electrode above the input electrode and the output electrode and forming a pixel electrode on portions of the edges of the output electrode; forming an organic light emitting member on the pixel electrode; and forming a common electrode on the organic light emitting member.

The forming of a semiconductor and a pixel electrode may include depositing an oxide semiconductor on the substrate and photo-etching the oxide semiconductor, and heat-treating the pixel electrode.

The heat treating may be performed under an atmosphere of oxygen (O₂) and nitrogen (N₂), or under an atmosphere of oxygen (O₂), nitrogen (N₂), and hydrogen (H₂).

At least 50 sccm of the atmosphere gas may be injected.

The heat treating may be performed at a temperature of about 100° C. or more.

The manufacturing method of an OLED display may further include forming an insulation film that covers the semiconductor and has a first opening that exposes the pixel electrode, and the organic light emitting member may be in the first opening.

The insulation film may be made of silicon oxide or silicon nitride containing a black pigment.

The forming of the gate insulating film may further comprise: forming a second opening in the gate insulating film; and the manufacturing method of an OLED display may further include forming a blocking portion that covers the second opening.

According to exemplary embodiments of the present invention, by forming a semiconductor layer on the input electrode and the output electrode, damage to the semiconductor layer can be reduced.

Furthermore, a semiconductor and a pixel electrode are simultaneously by the use of an oxide semiconductor, thus simplifying the manufacturing process and raising the productivity, and a layer containing a black pigment is above and below the semiconductor, thereby blocking light that can enter the semiconductor layer and preventing degradation of the characteristics of the semiconductor layer caused by light.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an equivalent circuit diagram of an OLED display according to an exemplary embodiment of the present invention.

FIG. 2 is a layout view of an OLED display according to an exemplary embodiment of the present invention.

FIG. 3 is a sectional view of the OLED display shown in FIG. 2 taken along lines III-III' and lines III''-III'''.

FIGS. 4, 5, 6, 7 and 8 are sectional views of intermediate steps of a manufacturing method of the OLED display shown in FIGS. 2 and 3.

FIG. 9 is a graph showing the conductivity of pixel electrodes.

FIGS. 10 and 11 are sectional views of an intermediate step of a manufacturing method of the OLED display shown in FIGS. 2 and 3.

FIG. 12 is a sectional view of an OLED display according to an exemplary embodiment of the present invention.

DETAILED DESCRIPTION OF THE EMBODIMENTS

Referring now to FIG. 1, an OLED display according to this exemplary embodiment includes a plurality of signal lines 121, 171, 172, and a plurality of pixels PX connected thereto and arranged substantially in a matrix.

The signal lines include a plurality of gate lines 121 that transmit gate signals (or scanning signals), a plurality of data lines 171 that transmit data signals, and a plurality of driving voltage lines 172 that transmit a driving voltage. The gate lines 121 extend in a row direction and are substantially parallel to each other. The data lines 171 and the driving

voltage lines 172 extend in a column direction and are substantially parallel to each other.

Each pixel PX includes a switching transistor Qs, a driving transistor Qd, a storage capacitor Cst, and an organic light emitting element LD.

The switching transistor Qs includes a control terminal, an input terminal, and an output terminal. The control terminal is connected to the gate lines 121, the input terminal is connected to the data lines 171, and the output terminal is connected to the driving transistor Qd, respectively. The switching transistor Qs transmits data signals received from the data lines 171 to the driving transistor Qd in response to a scanning signal from the gate lines 121.

The driving transistor Qd also has a control terminal, an input terminal, and an output terminal. The control terminal is connected to the switching transistor Qs, the input terminal is connected to the driving voltage lines 172, and the output terminal is connected to the organic light emitting element LD. The driving transistor Qd generates an output current ILD having a magnitude depending on a voltage difference between the control terminal and the output terminal.

The capacitor Cst is connected between the control terminal and the input terminal of the driving transistor Qd. The capacitor Cst stores the data signals applied to the control terminal of the driving transistor Qd and maintains the signals after the switching transistor Qs turns off.

The organic light emitting element LD is, for example, an OLED, which has an anode connected to the output terminal of the driving transistor Qd and a cathode connected to a common voltage (not shown) via voltage line 332. The organic light emitting element LD displays images by emitting light with varied intensity according to the output current ILD of the driving transistor Qd.

As appreciated by those skilled in the art, the connections among the transistors Qs, Qd, the capacitor Cst, and the organic light emitting element LD may be modified. In some cases, there may be other transistors that compensate for the threshold voltage of the organic light emitting element LD and the driving transistor Qd as well as a switching transistor Qs and a driving transistor Qd.

Hereinafter, the detailed structure of the OLED display shown in FIG. 1 will be described with reference to FIGS. 2 and 3 along with FIG. 1.

FIG. 2 is a layout view of an OLED display according to an exemplary embodiment of the present invention, and FIG. 3 is a sectional view of the OLED display shown in FIG. 2 taken along lines III-III' and lines III''-III'''.

Referring to FIGS. 2 and 3, gate lines 121 including first control electrodes 124a and second control electrodes 124b are formed on an insulating substrate 110 made of transparent glass or plastic.

The gate lines 121 extend in a row direction and the first control electrode 124a protrudes upward in FIG. 2. The gate lines 121 may include a wide end part (not shown) for connecting to another layer or an external driving circuit.

The second control electrodes 124b are separated from the gate lines 121, and include storage electrodes 127 that extend longitudinally in a column direction.

A gate insulating film 140 made of silicon oxide or silicon nitride is formed on the gate lines 121 and the second control electrodes 124b. Openings 84 surrounding portions of the periphery of the first control electrodes 124a and the second control electrodes 124b are formed at positions spaced a predetermined distance from the first control electrodes 124a on the gate insulating film 140, and contact holes 85 exposing portions of the storage electrodes 127 are formed thereon.

Data lines **171**, driving voltage lines **172**, first output electrodes **175a** and second output electrodes **175b**, and blocking members **176** are formed on the gate insulating film **140**.

The data lines **171** and the driving voltage lines **172** extend in a column direction and cross the gate lines **121**. The data lines **171** include first input electrodes **173a** extending toward the first control electrodes **124a**, and the driving voltage lines **172** include second input electrodes **173b** extending toward the second control electrodes **124b**.

The first and second output electrodes **175a**, **175b** are separated from each other, and are also separated from the data lines **171** and the driving voltage lines **172**. The first input electrodes **173a** and the first output electrodes **175a** face each other with the first control electrodes **124a** interposed therebetween. The second input electrodes **173b** and the second output electrodes **175b** face each other with the second control electrodes **124b** interposed therebetween.

The blocking member **176** is formed so as to surround portions of the peripheries of the first control electrodes **124a** and the second control electrodes **124b** at positions spaced a predetermined distance from the first control electrodes **124a** and the second control electrodes **124b**, and covers the openings **84** of the gate insulating film **140**.

The data lines **171**, the driving voltage lines **172**, the first and second output electrodes **175a**, **175b**, and the blocking member **176** may be formed of the same layer, may be made of a transparent metal, and may function as a light blocking member since they contain a black pigment.

The storage electrodes **127** are connected to the first output electrodes **175a** through the contact holes **85**.

Pixel electrodes **191** and first and second semiconductor islands **154a**, **154b** are formed on the gate insulating film **140**, the first and second input electrodes **173a**, **173b**, and the first and second output electrodes **175a**, **175b**.

The first semiconductor islands **154a** are positioned on the first control electrodes **124a**, and the second semiconductor islands **154b** are positioned on the second control electrodes **124b**.

The pixel electrodes **191** and the first and second semiconductor islands **154a**, **154b** may be made of a transparent oxide including zinc (Zn), magnesium (Mg), cadmium (Cd), tin (Sn), indium (In), gallium (Ga), hafnium (Hf), and the like, particularly, IGZO (indium gallium zinc oxide).

The pixel electrodes **191** and the first and second semiconductor islands **154a**, **154b** may be simultaneously formed.

Portions of the edges of the pixel electrodes **191** are formed directly on the second output electrodes **175b** and are electrically connected thereto.

A plasma treatment may be performed on the surfaces of the pixel electrodes **191**, and hydrogen atoms may be injected therein.

The first control electrode **124a**, the first input electrode **173a**, and the first output electrode **175a** together with the first semiconductor **154a** form the switching thin film transistor (switching TFT) Qs, and the second control electrode **124b**, the second input electrode **173b**, and the second output electrode **175b** together with the second semiconductor **154b** form the driving thin film transistor Qd.

The structures of the switching thin film transistor Qs, driving thin film transistor Qd, gate lines **121**, data lines **171**, and driving voltage lines **172** are only one example. Those skilled in the art will appreciate that various other examples are possible.

An insulation film **361** is formed on the data lines **171**, driving voltage lines **172**, output electrodes **175a**, **175b**, semiconductor islands **154a**, **154b**, and pixel electrodes **191**. The insulation film **361** has banked openings **365** surrounding the

edges of the pixel electrodes **191**. The insulation film **361** may be made of an organic insulating material having thermal resistance and solvent resistance such as acrylic resin and polyimide resin, or an inorganic insulating material such as silicon dioxide (SiO₂) or titanium dioxide (TiO₂), and may have multiple layers. Also, the insulation film **361** may be made of an inorganic material such as silicon oxide or silicon nitride, or an organic material such as a polyacryl.

In the present exemplary embodiment, the insulation film **361** includes a black pigment, and thus defines a pixel area and serves as a light blocking member. Therefore, the insulation film **361** blocks the light entering the upper portions of the first and second semiconductors **154a**, **154b**, thereby preventing the first and second semiconductors **154a**, **154b** from being damaged.

As described above, the data lines **171**, driving voltage lines **172**, first and second output electrodes **175a**, **175b**, and blocking member **176** also include a black pigment and serve as a light blocking member such that the light entering the lower portions or lateral sides of the first and second semiconductors **154a**, **154b** is blocked, thereby preventing the first and second semiconductors **154a**, **154b** from being damaged. Particularly, in the OLED display according to the present exemplary embodiment, the width of the first and second semiconductor islands **154a**, **154b** is smaller than the width of the first and second input electrodes **173a**, **173b** and the first and second output electrodes **175a**, **175b**, and a blocking member **176** is formed under the other edges excluding the edges surrounded by the first and second input electrodes **173a**, **173b**, first and second output electrodes **175a**, **175b**, and first and second control electrodes **124a**, **124b**. Due to this, the lower portions of the edges of the first and second semiconductor islands **154a**, **154b** are surrounded by the first and second control electrodes **124a**, **124b**, first and second input electrodes **173a**, **173b**, first and second output electrodes **175a**, **175b**, and blocking member **176**. Therefore, the light entering from the lower portions and lateral sides of the first and second semiconductor islands **154a**, **154b** is sufficiently blocked by the first and second input electrodes **173a**, **173b**, first and second output electrodes **175a**, **175b**, and blocking member **176**.

Organic light emitting members **370** are formed in the banked openings **365**. The organic light emitting members **370** may have a multilayered structure including an emitting layer (not shown) for emitting light and an auxiliary layer (not shown) for improving the light emitting efficiency of the emitting layer.

The emitting layer may be made of a high molecular material or a low molecular material that inherently emits any one of three primary colors (e.g., red, green, and blue), or a compound thereof.

The auxiliary layer may include one or more layers selected from the group consisting of an electron transport layer (not shown) and a hole transport layer (not shown) for adjusting the balance of electrons and holes, and an electron injecting layer (not shown) and a hole injecting layer (not shown) for enhancing the injection of electrons and holes.

The organic light emitting members **370** may implement a desired color for each pixel by arranging emitting layers emitting light of colors, such as red, green, and blue, in each pixel, or may implement a desired color by arranging emitting layers of three colors, such as red, green, and blue in one pixel with vertical or horizontal deposition to form a white emitting layer and forming color filters for implementing colors, such as red, green, and blue under or above the white emitting layer.

Furthermore, the luminance can be improved by further including the white pixel (W) as well as the red, green, and blue pixels (R, G, B) with stripe or checkered arrangements.

A common electrode **270** is formed on the organic light emitting members **370**. The common electrode **270** is formed on the whole surface of the substrate, and may be made of an opaque conductor, such as gold (Au), platinum (Pt), nickel (Ni), copper (Cu), tungsten (W), or their alloys.

The common electrode **270** forms a pair with the pixel electrodes **191** to flow the current to the organic light emitting members **370**.

As described above, the first control electrode **124a** electrically connected to the gate lines **121** and the first input electrode **173a** and first output electrode **175a** electrically connected to the data lines **171** together with the first semiconductor island **154a** constitute the switching thin film transistor (switching TFT) Qs, and a channel of the driving thin film transistor Qd is formed in the first semiconductor island **154a** between the first input electrode **173a** and the first output electrode **175a**.

The second control electrode **124b** electrically connected to the first output electrode **175a**, together with the second input electrode **173b** electrically connected to the driving voltage lines **172** and the second output electrode **175b** and second semiconductor island **154b** connected to the pixel electrodes **191**, constitute the driving thin film transistor Qd, and a channel of the driving thin film transistor Qd is formed in the second semiconductor island **154b** between the second input electrode **173b** and the second output electrode **175b**.

The pixel electrode **191**, the organic light emitting member **370**, and the common electrode **270** form an OLED LD. The pixel electrode **191** becomes an anode, and the common electrode **270** becomes a cathode. Alternatively, the pixel electrode **191** becomes a cathode and the common electrode **270** becomes an anode. Also, the storage electrode **127** and the driving voltage line **172**, which are overlapped with one another, form a storage capacitor Cst.

The OLED display according to the present exemplary embodiment displays images by emitting light downward (in FIG. 3) of the substrate **110**, and the light emitted upward of the substrate **110** from the organic light emitting members **370** is reflected by the common electrode **270** and directed downward again.

In an exemplary embodiment, the OLED display may alternatively display images by emitting light upward of the substrate.

While the OLED display according to the present exemplary embodiment has been described as having only one switching TFT and one driving TFT, the OLED display may further include at least one TFT and a plurality of lines for driving the TFT for compensating and preventing the OLED LD and the driving TFT Qd from being degraded even if the OLED display is driven for a long time, so as to prevent the lifetime of the OLED display from being shortened.

Now, a manufacturing method of the OLED display shown in FIGS. 2 and 3 according to an exemplary embodiment of the present invention will be described with reference to FIGS. 4 to 8 which are sectional views of intermediate steps of the manufacturing method.

Referring first to FIG. 4, gate lines **121** including first control electrodes **124a**, second control electrodes **124b**, and storage electrodes **127** are formed on a substrate **110**, and a gate insulating film **140** having openings **84** exposing portions of the edges of the first and second control electrodes **124a**, **124b** and contact holes **85** exposing portions of the storage electrodes **127** are formed thereon.

Referring to FIG. 5, data lines **171** including first input electrodes **173a**, driving voltage lines **172** including second input electrodes **173b** first and second output electrodes **175a**, **175b**, and a blocking member **176** are formed on the gate insulating film **140** and the exposed storage electrodes **127**. At this time, an opaque metal layer is deposited by sputtering or the like, and is photo-etched. In the deposition of an opaque metal layer, a black pigment may be mixed and deposited together.

Referring to FIG. 6, a transparent oxide, for example IGZO (indium gallium zinc oxide), containing zinc (Zn), magnesium (Mg), cadmium (Cd), tin (Sn), indium (In), gallium (Ga), hafnium (Ha), and so forth, is deposited on the gate insulating film **140** and the first and second output electrodes **175a**, **175b** and then photo-etched to thus simultaneously form pixel electrodes **191** and first and second semiconductor islands **154a**, **154b**.

Referring to FIG. 7, portions A where the pixel electrodes **191** are formed are heat-treated under an atmosphere of oxygen (O₂) and nitrogen (N₂) or under an atmosphere of oxygen (O₂), nitrogen (N₂), and hydrogen (H₂). The other regions excluding the portions A where the pixel electrodes **191** are formed are covered with a mask, or a photosensitive film is formed on those regions, and then a heat treatment is performed. At least 50 sccm of an atmosphere gas of oxygen (O₂), nitrogen (N₂), and hydrogen (H₂) is injected, and the heat treatment temperature is about 100° C. or more, and particularly about 300° C. When the heat treatment is performed under these conditions, the conductivity of the pixel electrodes **191** increases.

Through the heat treatment, the conductivity of the pixel electrodes **191** made of an oxide semiconductor is increased, and thus can be used as an anode or cathode of the OLED.

Next, referring to FIG. 8, a material layer such as an acrylic resin, a polyimide resin, silicon oxide, titanium oxide, etc., containing a black pigment is deposited on the data lines **171**, driving voltage lines **172**, output electrodes **175a**, **175b**, semiconductor islands **154a**, **154b**, and pixel electrodes **191**, and then photo-etched to form an insulation film **361** having banked openings **365**.

Although the insulation film **361** having banked openings **365** is formed after the heat treatment of the pixel electrodes **191** in the present exemplary embodiment, the insulation film **361** having banked openings **365** exposing the pixel electrodes **191** may be formed and then the heat treatment may be performed by using the insulation film **361** as a mask.

Finally, as shown in FIG. 3, organic light emitting members **370** are formed in the banked openings **365**, and a common electrode **270** is formed thereon.

Next, the conductivity of the pixel electrodes **191** of the OLED display fabricated by the manufacturing method of an OLED display according to the present exemplary embodiment will be described with reference to FIG. 9 which is a graph showing the conductivity of the pixel electrodes **191** made of an oxide semiconductor. In the graph, the conductivity of the pixel electrodes **191** when heat treatment is not performed is denoted by Ref, and when heat treatment temperatures are about 100° C., 200° C., and 300° C., the conductivities of the pixel electrodes **191** are denoted by 100 deg, 200 deg, and 300 deg, respectively. About 50 sccm of oxygen (O₂) and nitrogen (N₂) is supplied as the atmosphere gas.

Referring to FIG. 9, in the case that the pixel electrodes **191** made of an oxide semiconductor are heat-treated under an atmosphere of oxygen (O₂) and nitrogen (N₂), it can be seen that the conductivities (100 deg, 200 deg, and 300 deg) of the pixel electrodes **191** when a heat treatment is performed are greater than that obtained when the heat treatment is not

performed (Ref). Because the higher the heat treatment temperature the greater the conductivity, the conductivities are greatly increased when a heat treatment is performed at a temperature of about 300° C., and, as such, the pixel electrodes **191** can be sufficiently used as the anode or cathode of the OLED.

Next, another manufacturing method of the OLED display shown in FIGS. **2** and **3** according to an exemplary embodiment of the present invention will be described with reference to FIGS. **10** and **11** which are sectional views of intermediate steps of the manufacturing method.

The manufacturing method of an OLED display according to the present exemplary embodiment is substantially the same as the manufacturing method of an OLED display according to the previous exemplary embodiment.

First, as shown in FIGS. **4** to **6**, gate lines **121** including first control electrodes **124a**, second control electrodes **124b**, and storage electrodes **127** are formed on a substrate **110**, and a gate insulating film **140** is formed thereon. Thereafter, data lines **171** including first input electrodes **173a**, driving voltage lines **172** including second input electrodes **173b** and first and second output electrodes **175a**, **175b**, and a blocking member **176** are formed thereon, and a transparent oxide, for example IGZO (indium gallium zinc oxide), containing zinc (Zn), magnesium (Mg), cadmium (Cd), tin (Sn), indium (In), gallium (Ga), hafnium (Ha), and so forth, is deposited on the gate insulating film **140** and the first and second output electrodes **175a**, **175b** and then photo-etched to thus form pixel electrodes **191** and first and second semiconductor islands **154a**, **154b**.

Next, as shown in FIG. **10**, the portions A' where the pixel electrodes **191** are formed are plasma-treated. The other regions excluding the portions A where the pixel electrodes **191** are formed are covered with a mask, and then a plasma treatment is performed. Through the plasma treatment, hydrogen atoms may be introduced into the pixel electrodes **191**.

Next, referring to FIG. **11**, a silicon oxide (SiOx) or silicon nitride (SiNx) layer containing a black pigment is deposited on the data lines **171**, driving voltage lines **172**, output electrodes **175a**, **175b**, semiconductor islands **154a**, **154b**, and pixel electrodes **191**, and then photo-etched to thus form an insulation film **361** having banked openings **365**. The silicon oxide (SiOx) or silicon nitride (SiNx) layer is dry-etched. During this dry-etching process, hydrogen atoms produced when depositing the silicon oxide (SiOx) or silicon nitride (SiNx) layer are injected into upper portions of the pixel electrodes **191**. As shown in FIG. **10**, hydrogen atoms can be easily introduced into upper portions of the pixel electrodes **191** by performing plasma treatment on the top surfaces of the pixel electrodes **191**.

In this manner, by injecting hydrogen atoms into the upper portions of the pixel electrodes **191** made of an oxide semiconductor, the conductivity of the pixel electrodes **191** is increased, so that the pixel electrodes **191** can be used as the anode or cathode of the OLED.

Finally, as shown in FIG. **3**, organic light emitting members **370** are formed in the banked openings **365**, and a common electrode **270** is formed thereon.

As described above, in the OLED display and manufacturing method thereof according to the exemplary embodiments of the present invention, semiconductors **154a**, **154b** and pixel electrodes **191** are simultaneously formed by the use of an oxide semiconductor, thus simplifying the manufacturing process and raising the productivity, and the conductivity of the pixel electrodes **191** is increased by heat treatment,

plasma treatment, and the like, thus enabling the pixel electrodes **191** to be used as the anode or cathode of the OLED.

Furthermore, by forming semiconductors **154a**, **154b** on the control electrodes, the input electrodes, and the output electrodes, damage to the semiconductor layer, which may occur in a thin film process, can be reduced.

Furthermore, by forming data lines **171**, driving voltage lines **172**, output electrodes **175a**, **175b**, and a blocking member **176** containing a black pigment below the semiconductors **154a**, **154b**, and forming an insulation film **361** containing a black pigment above the semiconductors **154a**, **154b**, light entering the oxide semiconductor can be blocked, thus preventing degradation in the characteristics of the oxide semiconductor caused by the light.

Next, referring to FIG. **12**, an OLED display according to an exemplary embodiment of the present invention will be described. The layer structure of the OLED display according to the present exemplary embodiment is substantially the same as that of the OLED display shown in FIGS. **2** and **3**. However, unlike the OLED display shown in FIGS. **2** and **3**, a reflection member **177** is formed below the pixel electrodes **191**. The reflection member **177** may be formed as the same layer as the data lines **171**, driving voltage lines **172**, and output electrodes **175a**, **175b**. Further, the common electrode **270** of the OLED display according to the present exemplary embodiment may be formed of a transparent conductor, such as ITO or IZO.

Such an OLED display emits light upward of the substrate **110** to display images, and the light emitted from the organic light emitting members **370** toward the substrate **110** is reflected by the reflection member **177** and directed upward again.

All of the characteristics of the OLED display described with reference to FIGS. **2** and **3** may be applied to the OLED display shown in FIG. **12**.

Those skilled in the art will appreciate that the exemplary embodiments of the present invention may be applicable to an OLED display having different structures.

While this invention has been described in connection with what is presently considered to be practical exemplary embodiments, it is to be understood that the present invention is not limited to the disclosed embodiments, but, on the contrary, is intended to cover various modifications and equivalent arrangements included within the spirit and scope of the appended claims.

What is claimed is:

1. An organic light emitting diode display, comprising:

- a substrate;
- a control electrode disposed on the substrate;
- a gate insulating film covering the control electrode the gate insulating film having an opening that exposes the substrate;
- an input electrode and an output electrode disposed on the gate insulating film and facing each other;
- an oxide semiconductor disposed on the input electrode and the output electrode and disposed over the control electrode;
- a pixel electrode disposed on and electrically connected to portions of edges of the output electrode;
- an organic light emitting member disposed on the pixel electrode;
- a common electrode disposed on the organic light emitting member, and
- a blocking member covering the opening that exposes the substrate and configured such that light entering lower portions or lateral sides of the oxide semiconductor is blocked,

11

wherein the pixel electrode comprises the same material as the oxide semiconductor.

2. The organic light emitting diode display of claim 1, wherein the pixel electrode comprises hydrogen injected into a portion of the pixel electrode.

3. The organic light emitting diode display of claim 2, further comprising an insulation film covering the oxide semiconductor and having an opening that exposes the pixel electrode, and

wherein the organic light emitting member is disposed in the opening that exposes the pixel electrode.

4. The organic light emitting diode display of claim 3, wherein the insulation film comprises a black pigment.

5. The organic light emitting diode display of claim 3, wherein a surface of the pixel electrode is plasma treated.

6. The organic light emitting diode display of claim 1, wherein the blocking member comprises a black pigment.

7. The organic light emitting diode display of claim 1, wherein the blocking member is made of a same material as the input electrode and the output electrode.

12

8. The organic light emitting diode display of claim 1, wherein a width of the oxide semiconductor is smaller than a width of the input electrode and a width of the output electrode.

9. The organic light emitting diode display of claim 1, wherein the pixel electrode is formed directly on the portions of edges of the output electrode.

10. The organic light emitting diode display of claim 1, wherein:

10 the pixel electrode has a length that extends in a first direction and a length that extends in a second direction, the length that extends in the first direction being greater than the length that extends in the second direction; and
15 a driving voltage line is connected to the input electrode, the driving voltage line being substantially parallel to the pixel electrode length that extends in the first direction.

* * * * *

专利名称(译)	有机发光二极管显示器及其制造方法		
公开(公告)号	US8304981	公开(公告)日	2012-11-06
申请号	US12/433093	申请日	2009-04-30
[标]申请(专利权)人(译)	KIM MU GYEOM JEONG BYOUNG SEONG HEO SEONG KWEON SHIN MIN CHUL HUH JONG MOO 长园MO		
申请(专利权)人(译)	KIM MU-GYEOM JEONG BYOUNG-SEONG HEO晟KWEON SHIN MIN CHUL HUH钟武 朴昌MO		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	KIM MU GYEOM JEONG BYOUNG SEONG HEO SEONG KWEON SHIN MIN CHUL HUH JONG MOO PARK CHANG MO		
发明人	KIM, MU-GYEOM JEONG, BYOUNG-SEONG HEO, SEONG-KWEON SHIN, MIN-CHUL HUH, JONG-MOO PARK, CHANG-MO		
IPC分类号	H01L51/00		
CPC分类号	H01L27/3262 H01L27/3246 H01L2251/305 H01L27/3272		
优先权	1020080120713 2008-12-01 KR		
其他公开文献	US20100133991A1		
外部链接	Espacenet USPTO		

摘要(译)

有机发光二极管显示器包括基板。控制电极位于基板上。栅极绝缘膜覆盖控制电极。输入电极和输出电极位于栅极绝缘膜上并且彼此面对。氧化物半导体位于输入电极和输出电极之间以及控制电极上。像素电极位于输出电极边缘的一部分上并且电连接。有机发光构件位于像素电极上。公共电极位于有机发光构件上。氧化物半导体和像素电极可以是同一层。

