

(12) United States Patent Cho et al.

US 7,842,404 B2 (10) Patent No.: (45) **Date of Patent:** *Nov. 30, 2010

(54) COMPOUND AND ORGANIC LIGHT EMITTING DEVICE USING THE SAME

(75) Inventors: Wook Dong Cho, Daejeon Metropolitan (KR); Ji Eun Kim, Daejeon

Metropolitan (KR); Byung Sun Jeon, Seoul (KR); Dong Seob Jeong, Seoul (KR); Seok Hee Yoon, Daejeon Metropolitan (KR); Jae Min Moon,

Daejeon Metropolitan (KR)

(73) Assignee: LG Chem, Ltd., Seoul (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35

U.S.C. 154(b) by 688 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: 11/658,770

(22) PCT Filed: Sep. 23, 2005

(86) PCT No.: PCT/KR2005/003176

§ 371 (c)(1),

(2), (4) Date: Jan. 30, 2007

(87) PCT Pub. No.: WO2006/080643

PCT Pub. Date: Aug. 3, 2006

(65)**Prior Publication Data**

US 2009/0200542 A1 Aug. 13, 2009

(30)Foreign Application Priority Data

Sep. 24, 2004 (KR) 10-2004-0077245

(51) Int. Cl. H01L 51/54

(2006.01)(52) **U.S. Cl.** **428/690**; 428/917; 313/504;

313/506; 252/301.16; 257/40; 257/E51.032; 546/15; 546/16; 546/18

(58) Field of Classification Search 556/408 See application file for complete search history.

(56)**References Cited**

U.S. PATENT DOCUMENTS

6,605,373 B2	8/2003	Woo et al.
6,613,454 B2	9/2003	Ara et al.
6,630,254 B2	10/2003	Leclerc et al.
.004/0219386 A1	11/2004	Thoms

FOREIGN PATENT DOCUMENTS

EP	1 310 539 B1	3/2005
JP	2008-510800	4/2008
JP	2008-511157	4/2008
JP	2008-511158	4/2008
JP	2008-511160	4/2008
WO	WO 93/09074	5/1993
WO	WO 2006/080640	8/2006
WO	WO 2006/080641	8/2006
WO	WO 2006/080642	8/2006
WO	WO 2006/080643	8/2006
WO	WO 2006/080644	8/2006

OTHER PUBLICATIONS

W. Tritschler, Synthese un Konformation von Spiroacridanen, Chem. Ber. 117, pp. 2703-2713; 1984.


Patrick Keller, "Photo-Cross-Linkable Liquid-Crystalline Side-Chain Polysiloxanes", Chemistry of Materials, vol. 2, pp. 3-4, 1990. Geselowitz et al., "Quantitation of Triple-Helix Formation Using a Photo-Cross-Linkable Aryl Azide/Biotin/Oligonucleotide Conjugate", Bioconjugate Chem., vol. 6, pp. 502-506, 1995.

Primary Examiner—D. L Tarazano Assistant Examiner—Michael Wilson (74) Attorney, Agent, or Firm—McKenna Long & Aldridge

(57)ABSTRACT

Disclosed is an organic light emitting device. The organic light emitting device comprises a first electrode, organic material layer(s) comprising a light emitting layer, and a second electrode. The first electrode, the organic material layer(s), and the second electrode form layered structure and at least one layer of the organic material layer(s) include the compound of Formula 1 or the compound of Formula 1 into which a thermosetting or photo-crosslinkable functional group is introduced.

7 Claims, 1 Drawing Sheet



COMPOUND AND ORGANIC LIGHT EMITTING DEVICE USING THE SAME

This application claims priority to International Application No. PCT/KR2005/003176, filed on Sep. 23, 2005, and 5 Korean Patent Application No. 10-2004-0077245, filed on Sep. 24, 2004, which are hereby incorporated by reference in their entirety.

TECHNICAL FIELD

The present invention relates to an organic light emitting device in which a novel compound capable of significantly improving a lifespan, efficiency, and electrochemical and thermal stabilities of the organic light emitting device is contained in an organic compound layer.

BACKGROUND ART

An organic light emission phenomenon is an example of a 20 conversion of current into visible rays through an internal process of a specific organic molecule. The organic light emission phenomenon is based on the following mechanism. When an organic material layer is interposed between an anode and a cathode, if voltage is applied between the two electrodes, electrons and holes are injected from the cathode 25 and the anode into the organic material layer. The electrons and the holes which are injected into the organic material layer are recombined to form an exciton, and the exciton is reduced to a bottom state to emit light. An organic light emitting device which is based on the above mechanism 30 typically comprises a cathode, an anode, and an organic material layer, for example, an organic material layer including a hole injection layer, a hole transport layer, a light emitting layer, and an electron transport layer, interposed therebetween.

The materials used in the organic light emitting device are mostly pure organic materials or complexes of organic material and metal. The material used in the organic light emitting device may be classified as a hole injection material, a hole transport material, a light emitting material, an electron transport material, or an electron injection material, according to 40 its use. In connection with this, an organic material having a p-type property, which is easily oxidized and is electrochemically stable when it is oxidized, is mostly used as the hole injection material or the hole transport material. Meanwhile, an organic material having an n-type property, which is easily reduced and is electrochemically stable when it is reduced, is used as the electron injection material or the electron transport material. As the light emitting layer material, an organic material having both p-type and n-type properties is preferable, which is stable when it is oxidized and when it is reduced. Also a material having high light emission efficiency 50 for conversion of the exciton into light when the exciton is formed is preferable.

In addition, it is preferable that the material used in the organic light emitting device further have the following properties.

First, it is preferable that the material used in the organic light emitting device have excellent thermal stability. The reason is that joule heat is generated by movement of electric charges in the organic light emitting device. NPB, which has recently been used as the hole transport layer material, has a glass transition temperature of 100° C. or lower, thus it is difficult to apply to an organic light emitting device requiring a high current.

Second, in order to produce an organic light emitting device that is capable of being actuated at low voltage and has 65 high efficiency, holes and electrons which are injected into the organic light emitting device must be smoothly transported to

2

a light emitting layer, and must not be released out of the light emitting layer. To achieve this, a material used in the organic light emitting device must have a proper band gap and a proper HOMO or LUMO energy levels. A LUMO energy level of PEDOT:PSS, which is currently used as a hole transport material of an organic light emitting device produced using a solution coating method, is lower than that of an organic material used as a light emitting layer material, thus it is difficult to produce an organic light emitting device having high efficiency and a long lifespan.

Moreover, the material used in the organic light emitting device must have excellent chemical stability, electric charge mobility, and interfacial characteristic with an electrode or an adjacent layer. That is to say, the material used in the organic light emitting device must be little deformed by moisture or oxygen. Furthermore, proper hole or electron mobility must be assured so as to balance densities of the holes and of the electrons in the light emitting layer of the organic light emitting device to maximize the formation of excitons. Additionally, it has to be able to have a good interface with an electrode including metal or metal oxides so as to assure stability of the device.

Accordingly, there is a need to develop an organic light emitting device including an organic material having the above-mentioned requirements in the art.

DISCLOSURE OF INVENTION

Technical Problem

Therefore, the object of the present inventions is to provide an organic light emitting device which is capable of satisfying conditions required of a material usable for an organic light emitting device, for example, a proper energy level, electrochemical stability, and thermal stability, and which includes a fluorene derivative having a chemical structure capable of playing various roles required in the organic light emitting device, depending on a substituent group.

Technical Solution

The present invention provides an organic light emitting device which comprises a first electrode, organic material layer(s) comprising a light emitting layer, and a second electrode, wherein the first electrode, the organic material layer(s), and the second electrode form a layered structure and at least one layer of the organic material layer(s) includes a compound of the following Formula 1 or a compound of Formula 1 into which a thermosetting or photo-crosslinkable functional group is introduced:

[Formula 1]

In Formula 1, X is C or Si, A is

and B is

a and b are zero or positive integer.

Y is a bond; bivalent aromatic hydrocarbons; bivalent aromatic hydrocarbons which are substituted with at least one substituent group selected from the group consisting of nitro, nitrile, halogen, alkyl, alkoxy, and amino groups; a bivalent heterocyclic group; or a bivalent heterocyclic group which is substituted with at least one substituent group selected from the group consisting of nitro, nitrile, halogen, alkyl, alkoxy, and amino groups.

Y1 to Y4 are each independently bivalent aromatic hydrocarbons; bivalent aromatic hydrocarbons which are substituted with at least one substituent group selected from the group consisting of nitro, nitrile, halogen, alkyl, alkoxy, and amino groups; a bivalent heterocyclic group; or a bivalent heterocyclic group which is substituted with at least one substituent group selected from the group consisting of nitro, nitrile, halogen, alkyl, alkoxy, and amino groups.

Z1 to Z8 are each independently hydrogen; aliphatic 35 hydrocarbons having a carbon number of 1-20; aromatic hydrocarbons; aromatic hydrocarbons which are substituted with at least one substituent group selected from the group consisting of the nitro, nitrile, halogen, alkyl, alkoxy, amino, aromatic hydrocarbon, and heterocyclic groups; a silicon group substituted with aromatic hydrocarbons; a heterocyclic group; a heterocyclic group which is substituted with at least one substituent group selected from the group consisting of the nitro, nitrile, halogen, alkyl, alkoxy, amino, aromatic hydrocarbon, and heterocyclic groups; a thiophenyl group which is substituted with hydrocarbons having a carbon number of 1-20 or aromatic hydrocarbons having a carbon number of 6-20; or a boron group which is substituted with aromatic hydrocarbons.

R1 to R11 are each independently hydrogen, a substituted or unsubstituted alkyl group, a substituted or unsubstituted alkoxy group, a substituted or unsubstituted alkenyl group, a substituted or unsubstituted or unsubstituted or unsubstituted or unsubstituted or unsubstituted heterocyclic group, an amino group, a nitrile group, a nitro group, a halogen group, an amide group, or an ester group. R1 to R11 may form aliphatic or hetero condensation rings along with adjacent groups.

R7 and R8 may be directly connected to each other, or may form a condensation ring along with a group selected from the 60 group consisting of O, S, NR, PR, C=O, CRR', and SiRR'. R and R' are each independently or collectively hydrogen, a substituted or unsubstituted alkyl group, a substituted or unsubstituted alkoxy group, a substituted aryl group, a 65 substituted or unsubstituted arylamine group, a substituted or unsubstituted or unsubstituted arylamine group, a namide

4

group, or an ester group. R and R' may form a condensation ring to form a spiro compound.

A detailed description will be given of the substituent groups of Formula 1.

In Z1 to Z8 as the substituent groups of Formula 1, the aromatic hydrocarbons are exemplified by monocyclic aromatic rings, such as phenyl, biphenyl, and terphenyl, and multicyclic aromatic rings, such as naphthyl, anthracenyl, pyrenyl, and perylenyl. The heterocyclic group is exemplified by thiophene, furan, pyrrole, imidazole, thiazole, oxazole, oxadiazole, thiadiazole, triazole, pyridyl, pyridazyl, pyrazine, quinoline, and isoquinoline.

Examples of aliphatic hydrocarbons having a carbon number of 1-20 include straight chain aliphatic hydrocarbons, branched chain aliphatic hydrocarbons, saturated aliphatic hydrocarbons, and unsaturated aliphatic hydrocarbons. They are exemplified by an alkyl group, such as a methyl group, an ethyl group, an n-propyl group, an isopropyl group, an n-butyl group, a sec-butyl group, an iso-butyl group, a ter-butyl group, a pentyl group, and a hexyl group; an alkenyl group having a double bond, such as styryl; and an alkynyl group having a triple bond, such as an acetylene group.

The carbon number of the alkyl, alkoxy, and alkenyl groups of R1 to R11 of Formula 1 is not limited, but is preferably 1-20.

The length of the alkyl group contained in the compound does not affect the conjugate length of the compound, but may affect the method of applying the compound to the organic light emitting device, for example, a vacuum deposition method or a solution coating method.

Illustrative, but non-limiting, examples of the aryl group of R1 to R11 of Formula 1 include monocyclic aromatic rings, such as a phenyl group, a biphenyl group, a terphenyl group, and a stilbene group, and multicyclic aromatic rings, such as a naphthyl group, an anthracenyl group, a phenanthrene group, a pyrenyl group, and a perylenyl group.

Illustrative, but non-limiting, examples of the arylamine group of R1 to R11 of Formula 1 include a diphenylamine group, a dinaphthylamine group, a dibiphenylamine group, a phenylnaphthylamine group, a phenyldiphetylamine group, a ditolylamine group, a phenyltolylamine group, a carbazolyl group, and a triphenylamine group.

Illustrative, but non-limiting, examples of the heterocyclic group of R1 to R11 of Formula 1 include a thiophenyl group, a furan group, a pyrrolyl group, an imidazolyl group, a thiazolyl group, an oxazolyl group, an oxadiazolyl group, a triazolyl group, a pyridyl group, a pyradazine group, a quinolinyl group, an isoquinoline group, and an acridyl group.

In addition, illustrative, but non-limiting, examples of the alkenyl, aryl, arylamine, and heterocyclic groups of R1 to R11 of Formula 1 include compounds shown in the following Formulae.

In the above Formulae, Z is a group selected from the group consisting of hydrogen, aliphatic hydrocarbons having a carbon number of 1-20, an alkoxy group, an arylamine group, an aryl group, a heterocyclic group, a nitrile group, and an acetylene group. Examples of the arylamine, aryl, and heterocyclic groups of Z are as shown in the above-mentioned substituent groups of R1 to R11.

According to a preferred embodiment of the present invention, X of Formula 1 is C, and R7 and R8 are directly connected to each other, or form a condensation ring along with a group selected from the group consisting of O, S, NR, PR, C—O, CRR', and SiRR' (R and R' are as defined in Formula 1).

According to another preferred embodiment of the present invention, X of Formula 1 is Si, and R7 and R8 are directly connected to each other, or form a condensation ring along with a group selected from the group consisting of O, S, NR, PR, C=O, CRR', and SiRR' (R and R' are as defined in Formula 1).

According to still another preferred embodiment of the present invention, the compound of Formula 1 are any one of compounds of the following Formulae 2 to 5.

[Formulae 2 to 5]

[Formula 3]

derivatives. For example, if the compound of Formula 2 is combined with the group 1, the resulting product will be designated by the compound of Formula 2-1.

[A and B]

In the above Formulae, \boldsymbol{A} and \boldsymbol{B} are as defined in Formula 1.

lllustrative, but non-limiting, examples of A and B groups $_{65}$ of Formula 1 are as follows. Combination of the compounds of Formulae 2 to 5 and the following groups can form various

-continued

N

$$NO_2$$

-continued

-continued

. .


-continued

OMe

N

N

NO2



-continued

-continued

-continued

-continued

$$NO_2$$

-continued

OMe

5

N

10

-continued

-continued OMe

-continued

OMe 5

N 10

-continued 216
OMe

-continued

-continued

-continued NO₂

-continued

282

35

60

NO₂

CN 288

N 10

-continued

60

55

_

-continued

317 —N

-continued

-continued

-continued

-continued
NO₂

338

339

`

30

337

NO₂
35

NO₂
40

45


60

346 ₃₀

-continued

-continued

-continued



-continued

 -continued
375

-continued

389

30


-N

-continued

NO₂

-continued

408



-continued

-continued

-continued

-continued

-continued

-continued

424

65

-continued

-continued

435

10

N

20

-continued

N OMe N -continued

-continued

-continued

-continued

455

5

N

10

15

-continued

30

25

CN 458

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates an organic light emitting device comprising a substrate 1, an anode 2, a light emitting layer 3, and a 30 cathode 4; and


FIG. 2 illustrates an organic light emitting device comprising a substrate 1, an anode 2, a hole injection layer 5, a hole transport layer 6, a light emitting layer 7, an electron transport layer 8, and a cathode 4.

BEST MODE FOR CARRYING OUT THE INVENTION

Hereinafter, a detailed description will be given of the $_{\rm 40}$ present invention.

Various substituent groups are introduced into a core structure shown in Formula 1, in detail, the core structure in which a fluorene group is bonded to a combination of an acridine group and a carbazolyl group to form a spiro structure, thereby the compound of Formula 1 has characteristics suitable for application to an organic material layer used in an organic light emitting device. This will be described in detail, below.

The steric core structure of the compound of Formula 1, for convenience of explanation, can be divided into two portions, 50 A and B, as shown in the following Formula.



The compound of Formula 1 has the steric core structure in which a plane A meets with a plane B at right angles around X, and conjugation does not occur between the A and B portions around X. Furthermore, since one nitrogen atom is positioned among three aryl groups in the plane B, conjugation is limited in the plane B.

The conjugation length of the compound has a close relationship with an energy band gap. In detail, the energy band gap is reduced as the conjugation length of the compound increases. As described above, since a conjugation structure is limited in the core structure of the compound of Formula 1, the core structure has a large energy band gap.

As described above, in the present invention, various substituent groups are introduced to R1 to R11 positions and Z1 to Z8 positions of the core structure having the large energy band gap so as to produce compounds having various energy band gaps. Generally, it is easy to control the energy band gap by introducing substituent groups into a core structure having a large energy band gap, but it is difficult to significantly control the energy band gap by introducing substituent groups into a core structure having a small energy band gap. Furthermore, in the present invention, it is possible to control HOMO and LUMO energy levels of the compound by introducing various substituent groups into the R1 to R11 positions and the Z1 to Z8 positions of the core structure.

Additionally, by introducing various substituent groups into the core structure, compounds having intrinsic characteristics of the substituent groups can be synthesized. For example, substituent groups, which are frequently applied to hole injection layer materials, hole transport layer materials, light emitting layer materials, and electron transport layer materials which are used during the production of the organic light emitting device, are introduced into the core structure so as to produce substances capable of satisfying requirements 35 of each organic material layer. For example, since the core structure of the compound of Formula 1 includes the arylamine structure, it has an energy level suitable for the hole injection and/or hole transport materials in the organic light emitting device. In the present invention, the compound having the proper energy level is selected depending on the substituent group among the compounds represented by Formula 1 to be used in the organic light emitting device, thereby it is possible to realize a device having a low actuating voltage and a high light efficiency.

Furthermore, various substituent groups are symmetrically introduced into the core structure (the A and B portions are located at both sides of the core structure) so as to precisely control the energy band gap, improve interfacial characteristics with organic materials, and apply the compound to various fields.

As well, if the number of amine contained in the substituent groups A and B are each set to 4 or more (the numbers of amine contained in the A and B structures are each 2 or more), it is possible to precisely control the HOMO and LUMO energy levels and the energy band gap, and on the other hand interfacial characteristics with the organic materials is improved and thereby make it possible to apply the compound to various fields.

Additionally, various substituent groups are introduced into the steric structure of the compound of Formula 1 using spiro bonding to control the three-dimensional structure of the organic material so as to minimize π-π interaction in the organic material, thereby formation of excimers is prevented.

With respect to the energy band gap and the energy level, for example, since the compound of Formula 2-1, in which arylamine is introduced into the hole transport material or the hole injection material of the structure of Formula 1, has

HOMO of 5.22 eV, it has an energy level suitable for the hole injection layer or the hole transport layer. Meanwhile, the compound of Formula 2-1 has the band gap of 2.89 eV, which is still larger than that of NPB, typically used as the hole transport layer material, thus it has a LUMO value of about 5 2.33 eV, which is considered to be very high. If a compound having a high LUMO value is used as the hole transport layer, it increases the energy wall of LUMO of the material constituting the light emitting layer to prevent the movement of electrons from the light emitting layer to the hole transport 10 layer. Accordingly, the above-mentioned compound improves the light emission efficiency of the organic light emitting device so that efficiency is higher than that of conventionally used NPB (HOMO 5.4 eV, LUMO 2.3 eV, and energy band gap 3.1 eV). In the present invention, the energy 15 band gap is calculated by a typical method using a UV-VIS

As well, the compound of Formula 1 has stable redox characteristics. Redox stability is estimated using a CY (cyclovoltammetry) method. For example, if oxidation voltage is 20 repeatedly applied to the compound of Formula 2-1, oxidation repeatedly occurs at the same voltage and the current amount is the same. This means that the compound has excellent stability to oxidation.

Meanwhile, since the compound of Formula 1 has a high 25 glass transition temperature (Tg), it has excellent thermal stability. For example, the glass transition temperature of the compound of Formula 2-1 is 172° C., which is still higher than that of conventionally used NPB (Tg: 96° C.). Such increase in thermal stability is an important factor providing 30 actuating stability to the device.

Furthermore, the compound of Formula 1 may be used to form the organic material layer using a vacuum deposition process or a solution coating process during the production of the organic light emitting device. In connection with this, 35 illustrative, but non-limiting, examples of the solution coating process include a spin coating process, a dip coating process, an inkjet printing process, a screen printing process, a spray process, and a roll coating process.

Tertiary alcohol, which is produced by a reaction of a 40 lithiated aryl and keto group, is heated in the presence of an acid catalyst to form a hexagonal cyclic structure while water is removed, thereby producing the compound having a spiro structure according to the present invention. The above-mentioned procedure for producing the compound is well known 45 in the art, and those skilled in the art can change the production conditions during the production of the compound of Formula 1. The production will be described in detail in the preparation examples later.

The organic light emitting device of the present invention 50 can be produced using known materials through a known process, modified only in that at least one layer of organic material layer(s) includes the compound of the present invention, that is, the compound of Formula 1.

The organic material layer(s) of the organic light emitting 55 device according to the present invention may have a single layer structure, or alternatively, a multilayered structure in which two or more organic material layers are layered. For example, the organic light emitting device of the present invention may comprise a hole injection layer, a hole transport layer, a light emitting layer, an electron transport layer, and an electron injection layer as the organic material layer(s). However, the structure of the organic light emitting device is not limited to this, but may comprise a smaller number of organic material layers.

Furthermore, the organic light emitting device of the present invention may be produced, for example, by sequentially layering a first electrode, organic material layer(s), and a second electrode on a substrate. In connection with this, a physical vapor deposition (PVD) method, such as a sputtering method or an e-beam evaporation method, may be used, but the method is not limited to these.

A method of producing the compound of Formula 1 and the production of the organic light emitting device using the same will be described in detail in the following preparation examples and examples. However, the following preparation examples and examples are set forth to illustrate, but are not to be construed to limit the present invention.

MODE FOR THE INVENTION

A better understanding of a method of producing an organic compound represented by Formula 1 and the production of an organic light emitting device using the same may be obtained in light of the following preparation examples and examples which are set forth to illustrate, but are not to be construed to limit the present invention.

In order to produce the compound represented by Formula 1, any one of the compounds of the following Formulae, a to c, may be used as a starting material.

PREPARATION EXAMPLE 1

Production of a Starting Material Represented by Formula a

Carbazole (1.672 g, 10 mmol), 1-bromo-2-iodobenzene (1.5 ml, 12 mmol), potassium carbonate (K_2CO_3 , 2.7646 g, 20 mmol), copper iodide (Cul, 95 mg, 0.5 mmol), and 25 ml of xylene were refluxed in a nitrogen atmosphere. After cooling to normal temperature, a product was extracted with ethyl acetate, water was removed with anhydrous magnesium sulfate (MgSO₄), and the solvent was removed at a reduced pressure. The resulting product was passed through a silica gel column using a hexane solvent to produce a compound, the solvent was removed at a reduced pressure, and vacuum drying was conducted to produce the resulting white solid compound (800 mg, 25% yield). MS: [M+H]⁺=323.

PREPARATION EXAMPLE 2

Production of a Starting Material Represented by Formula b

The starting material represented by Formula a (6.96 g, 21.6 mmol) was dissolved in 300 ml of purified THF and cooled to -78° C., and n-BuLi (2.5 M in hexane, 8.64 ml, 21.6 mmol) was slowly dropped thereon. Stirring was conducted 30 at the same temperature for 30 min, and 2,7-dibromo-9-fluorenone (6.08 g, 18.0 mmol) was added thereto. After stirring at the same temperature for 40 min, the temperature was raised to normal temperature and stirring was carried out for an additional 3 hours. The reaction was completed in an 35 ammonium chloride (NH₄Cl) aqueous solution, and extraction was conducted with ethyl ether. Water was removed from an organic material layer using anhydrous magnesium sulfate (MgSO₄), and an organic solvent was then removed therefrom. The produced solid was dispersed in ethanol, stirred for one day, filtered, and vacuum dried to produce 10.12 g of intermediate material (96.7% yield). The intermediate solid was dispersed in 10 ml of acetic acid, ten drops of concentrated sulfuric acid were added thereto, and reflux was conducted for 4 hours. The resulting solid was filtered, washed with ethanol, and vacuum dried to produce 9.49 g of compound of Formula b (96.8% yield). MS: [M+H]⁺=563.

PREPARATION EXAMPLE 3

Production of a Starting Material Represented by Formula c

The starting material represented by Formula b (10.0 g, 17.8 mmol) was completely dissolved in 200 ml of THF, 4-chloro-phenylboronic acid (8.30 g, 53.3 mmol), 2M potassium carbonate solution, tetrakis(triphenylphosphine)palladium(0) (0.62 g, 0.53 mmol), and 10 ml of ethanol were added thereto, and reflux was conducted for 24 hours. After the reaction was completed, cooling to normal temperature was conducted, and filtration was conducted. Washing was conducted with water and ethanol several times. Recrystallization was conducted with ethanol, and vacuum drying was conducted to produce a compound (9.5 g, 85% yield). MS: [M+H]⁺=625.

200

EXAMPLE 1

Production of the Compound Represented by Formula 2-1

1) Synthesis of arylamine (4-(N-phenyl-N-phenylamino) phenyl-1-phenylamine) to produce the compound represented by Formula 2-1: 13.5 g of 4-bromophenyl-N-phenyl-N-phenylamine (41.6 mmol) and 3.98 ml of aniline (43.7 mmol) were dissolved in 120 ml of toluene, 10.00 g of sodium-tert-butoxide (104.1 mmol), 0.48 g of bis(dibenzylidene acetone)palladium(0) (0.83 mmol), and 0.58 ml of 50 wt % tri-tert-butylphosphine toluene solution (1.25 mmol) were added thereto, and reflux was conducted in a nitrogen atmosphere for 2 hours. Distilled water was added to the reaction solution to complete the reaction, and the organic layer was extracted. A column separation process was conducted using a solvent of n-hexane and tetrahydrofuran at a ²⁰ ratio of 10:1, stirring was conducted using petroleum ether, and vacuum drying was conducted to produce an arylamine connection group (9.6 g, yield 69%). MS: [M+H]⁺=336.

2) 3.0 g of compound of Formula b (5.3 mmol) and 4.12 g
of 4-(N-phenyl-N-phenylamino)phenyl-1-phenylamine
(12.3 mmol) were dissolved in 80 ml of toluene, 1.54 g of
sodium-tert-butoxide (16.0 mmol), 0.06 g of bis(dibenzylidene acetone)paladium (0) (0.11 mmol), and 0.06 ml of
50 wt % tri-tert-butylphosphine toluene solution (0.16 mmol)
were added thereto, and reflux was conducted in a nitrogen
atmosphere for 2 hours. Distilled water was added to the
reaction solution to complete the reaction, and the organic
layer was extracted. A column separation process was conducted using a solvent of n-hexane and tetrahydrofuran at a
stratio of 4:1, stirring was conducted using petroleum ether, and
vacuum drying was conducted to produce the compound of
Formula 2-1 (2.7 g, yield 47%). MS: [M+H]*=1074.

EXAMPLE 2

Production of the Compound Represented by Formula 2-2

1) Synthesis of arylamine (4-(N-phenyl-N-phenylamino) phenyl-1-naphthylamine) to produce the compound represented by Formula 2-2: 15.0 g of 4-bromophenyl-N-phenyl-N-phenylamine (46.3 mmol) and 7.29 g of 1-naphthylamine (50.9 mmol) were dissolved in 200 ml of toluene, 13.34 g of 50 sodium-tert-butoxide (138.8 mmol), 0.53 g of bis(dibenzylidene acetone)palladium(0) (0.93 mmol), and 0.56 ml of 50 wt % tri-tert-butylphosphine toluene solution (1.39 mmol) were added thereto, and reflux was conducted in a nitrogen atmosphere for 2 hours. Distilled water was added to the reaction solution to complete the reaction, and the organic layer was extracted. A column separation process was conducted using a solvent of n-hexane and tetrahydrofuran at a ratio of 10:1, stirring was conducted using petroleum ether, and vacuum drying was conducted to produce an arylamine connection group (13 g, yield 73%). MS: [M+H]⁺=386.

2) 5.00 g of compound of Formula b (8.88 mmol) and 7.90 g of 4-(N-phenyl-N-phenylamino)phenyl-1-naphthylamine (20.4 mmol) were dissolved in 120 ml of toluene, 5.89 g of sodium-tert-butoxide (61.3 mmol), 0.24 g of tris(dibenzylidene acetone)dipalladium(0) (0.41 mmol), and 0.25 ml of 50 wt % tri-tert-butylphosphine toluene solution (0.61 mmol)

:

were added thereto, and reflux was conducted in a nitrogen atmosphere for 2 hours. Distilled water was added to the reaction solution to complete the reaction, and the organic layer was extracted. A column separation process was conducted using a solvent of n-hexane and tetrahydrofuran at a ratio of 4:1, stirring was conducted using petroleum ether, and vacuum drying was conducted to produce the compound of Formula 2-2 (5.2 g, yield 50%). MS: [M+H]⁺=1174.

EXAMPLE 3

Production of the Compound Represented by Formula 2-4

1) Synthesis of arylamine (4-(N-phenyl-N-phenylamino) phenyl-1-biphenylamine) to produce the compound represented by Formula 2-4: 17.4 g of 4-bromophenyl-N-phenyl-N-phenylamine (53.7 mmol) and 9.99 g of 4-aminobiphenyl (59.0 mmol) were dissolved in 250 ml of toluene, 17.02 g of sodium-tert-butoxide (177.1 mmol), 0.68 g of bis(dibenzylidene acetone)palladium(0) (1.2 mmol), and 0.72 ml of 50 wt % tri-tert-butylphosphine toluene solution (1.8 mmol) were added thereto, and reflux was conducted in a nitrogen atmosphere for 2 hours. Distilled water was added to the reaction solution to complete the reaction, and the organic layer was extracted. A column separation process was conducted using a solvent of n-hexane and tetrahydrofuran at a ratio of 10:1, stirring was conducted using petroleum ether, and vacuum drying was conducted to produce an arylamine connection group (16 g, yield 73%). MS: [M+H]⁺=412.

2) 4.7 g of compound of Formula b (8.3 mmol) and 7.9 g of 4-(N-phenyl-N-phenylamino)phenyl-1-biphenylamine (19.2 mmol) were dissolved in 150 ml of toluene, 5.53 g of sodium-tert-butoxide (57.5 mmol), 0.22 g of bis(dibenzylidene acetone)palladium(0) (0.38 mmol), and 0.23 ml of 50 wt % tri-tert-butylphosphine toluene solution (0.58 mmol) were added thereto, and reflux was conducted in a nitrogen atmosphere for 2 hours. Distilled water was added to the reaction solution to complete the reaction, and the organic layer was extracted. A column separation process was conducted using a solvent of n-hexane and tetrahydrofuran at a ratio of 4:1, stirring was conducted using petroleum ether, and vacuum drying was conducted to produce the compound of Formula 2-4 (4.9 g, yield 48%). MS: [M+H]⁺=1225.

EXAMPLE 4

Production of the Compound Represented by Formula 2-18

1) Synthesis of arylamine (4-(N-phenyl-N-naphthy- 50 MS: [M+H]⁺=1227. lamino)phenyl-1-phenylamine) to produce the compound represented by Formula 2-18: 7.00 g of 4-bromophenyl-Nphenyl-N-naphthylamine (18.7 mmol) and 2.56 ml of aniline (28.1 mmol) were dissolved in 100 ml of toluene, 5.40 g of sodium-tert-butoxide (56.1 mmol), 0.22 g of bis(diben- 55 zvlidene acetone)palladium(0) (0.37 mmol), and 0.28 ml of 50 wt % tri-tert-butylphosphine toluene solution (0.37 mmol) were added thereto, and reflux was conducted in a nitrogen atmosphere for 2 hours. Distilled water was added to the reaction solution to complete the reaction, and the organic 60 layer was extracted. A column separation process was conducted using a solvent of n-hexane and tetrahydrofuran at a ratio of 10:1, stirring was conducted using petroleum ether, and vacuum drying was conducted to produce an arylamine connection group (5.1 g, yield 70%). MS: [M+H]⁺=386.

2) 2.5 g of compound of Formula b (4.4 mmol) and 3.86 g of 4-(N-phenyl-N-naphthylamino)phenyl-1-phenylamine

202

(10.0 mmol) were dissolved in 50 ml of toluene, 1.26 g of sodium-tert-butoxide (13.2 mmol), 0.08 g of tris(dibenzylidene acetone)dipalladium(0) (0.08 mmol), and 0.04 ml of 50 wt % tri-tert-butylphosphine toluene solution (0.13 mmol) were added thereto, and reflux was conducted in a nitrogen atmosphere for 2 hours. Distilled water was added to the reaction solution to complete the reaction, and the organic layer was extracted. A column separation process was conducted using a solvent of n-hexane and tetrahydrofuran at a ratio of 4:1, stirring was conducted using petroleum ether, and vacuum drying was conducted to produce the compound of Formula 2-18 (2.5 g, yield 49%). MS: [M+H]⁺=1173.

EXAMPLE 5

Production of the Compound Represented by Formula 2-19

1) Synthesis of arylamine (4-(N-phenyl-N-naphthy-20 lamino)phenyl-1-naphthylamine) to produce the compound represented by Formula 2-19: 14.0 g of 4-bromophenyl-Nphenyl-N-naphthylamine (37.4 mmol) and 6.43 g of 1-naphthylamine (44.9 mmol) were dissolved in 200 ml of toluene, and 0.645 g of bis(dibenzylidene acetone)palladium(0) (1.12 mmol), 0.74 ml of 50 wt % tri-tert-butylphosphine toluene solution (1.5 mmol), and 8.99 g of sodium-tert-butoxide (93.5 mmol) were added thereto. After reflux was conducted in a nitrogen atmosphere for 2 hours, distilled water was added to the reaction solution to complete the reaction. The organic layer was extracted, a column separation process was conducted using a developing solvent of n-hexane and tetrahydrofuran at a ratio of 10:1, stirring was conducted using petroleum ether, and vacuum drying was conducted to produce an arylamine connection group (8.53 g, yield 52.2%). $MS: [M+H]^+=437.$

2) 5.00 g of compound of Formula b (8.88 mmol) and 8.53 g of 4-(N-phenyl-N-naphthylamino)phenyl-1-naphthylamine (19.5 mmol) were dissolved in 50 ml of toluene, and 0.204 g of bis(dibenzylidene acetone)palladium(0) (0.360 mmol), 0.31 ml of 50 wt % tri-tert-butylphosphine toluene solution (0.62 mmol), and 4.69 g of sodium-tert-butoxide (48.8 mmol) were added thereto. After reflux was conducted in a nitrogen atmosphere for 2 hours, distilled water was added to the reaction solution to complete the reaction. The
45 organic layer was extracted, a column separation process was conducted using a developing solvent of n-hexane and tetrahydrofuran at a ratio of 8:1, stirring was conducted using petroleum ether, and vacuum drying was conducted to produce the compound of Formula 2-19 (5.60 g, yield 49.5%).
50 MS: [M+H]*=1227.

EXAMPLE 6

Production of the Compound Represented by Formula 2-21

1) Synthesis of arylamine (4-(N-phenyl-N-naphthy-lamino)phenyl-1-biphenylamine) to produce the compound represented by Formula 2-21: 14.0 g of 4-bromophenyl-N-phenyl-N-naphthylamine (37.4 mmol) and 6.96 g of 4-aminobiphenyl (41.2 mmol) were dissolved in 200 ml of toluene, and 0.47 g of bis(dibenzylidene acetone)palladium(0) (0.82 mmol), 0.50 ml of 50 wt % tri-tert-butylphosphine toluene solution (1.2 mmol), and 11.86 g of sodium-tert-butoxide (123.4 mmol) were added thereto. After reflux was conducted in a nitrogen atmosphere for 2 hours, distilled water was added to the reaction solution to complete the reaction. The

organic layer was extracted, a column separation process was conducted using a developing solvent of n-hexane and tetrahydrofuran at a ratio of 10:1, stirring was conducted using petroleum ether, and vacuum drying was conducted to produce an arylamine connection group (7.5 g, yield 43%). MS: 5 [M+H]⁺=462.

2) 3.3 g of compound of Formula b (5.8 mmol) and 5.90 g of 4-(N-phenyl-N-naphthylamino)phenyl-1-biphenylamine (12.8 mmol) were dissolved in 70 ml of toluene, and 0.15 g of bis(dibenzylidene acetone)palladium(0) (0.26 mmol), 0.16 10 ml of 50 wt % tri-tert-butylphosphine toluene solution (0.38 mmol), and 3.68 g of sodium-tert-butoxide (38.3 mmol) were added thereto. After reflux was conducted in a nitrogen atmosphere for 2 hours, distilled water was added to the reaction solution to complete the reaction. The organic layer was extracted, a column separation process was conducted using a developing solvent of n-hexane and tetrahydrofuran at a ratio of 8:1, stirring was conducted using petroleum ether, and vacuum drying was conducted to produce the compound of Formula 2-21 (3.9 g, yield 51%). MS: [M+H]⁺=1227.

EXAMPLE 7

Production of the Compound Represented by Formula 2-256

1) Synthesis of arylamine (4-(N,N-diphenylamino)-biphenyl-aniline) to produce the compound represented by Formula 2-256: 4.00 g of 4-chlorobiphenyl-N,N-diphenylamine (11.2 mmol) and 1.13 ml of aniline (12.4 mmol) were dissolved in 100 ml of toluene, and 0.129 g of bis(dibenzylidene acetone)palladium(0) (0.225 mmol), 0.17 ml of 50 wt % tri-tert-butylphosphine toluene solution (0.34 mmol), and 2.70 g of sodium-tert-butoxide (28.1 mmol) were added thereto. After reflux was conducted in a nitrogen atmosphere for 5 hours, distilled water was added to the reaction solution to complete the reaction. The organic layer was extracted, a column separation process was conducted using a developing solvent of n-hexane and tetrahydrofuran at a ratio of 10:1, stirring was conducted using petroleum ether, and vacuum drying was conducted to produce an arylamine connection group as an amine derivative (3.77 g, yield 81.3%). MS: $[M+H]^{+}=413.$

2) 2.30 g of compound of Formula b (4.08 mmol) and 3.70 g of 4-(N,N-diphenylamino)-biphenyl-aniline (8.97 mmol) were dissolved in 30 ml of toluene, and 0.094 g of bis(dibenzylidene acetone)palladium(0) (0.16 mmol), 0.14 ml of 50 wt % tri-tert-butylphosphine toluene solution (0.29 mmol), and 2.16 g of sodium-tert-butoxide (22.4 mmol) were added thereto. After reflux was conducted in a nitrogen atmosphere for 2 hours, distilled water was added to the reaction solution to complete the reaction. The organic layer was extracted, a column separation process was conducted using a developing solvent of n-hexane and tetrahydrofuran at a ratio of 8:1, stirring was conducted using petroleum ether, and vacuum drying was conducted to produce the compound of Formula 2-256 (2.7 g, yield 54%). MS: [M+H]⁺=1227.

EXAMPLE 8

Production of the Compound Represented by Formula 3-2

60

1) Synthesis of arylamine (4-(N-phenyl-N-phenylamino) phenyl-1-naphthylamine) to produce the compound represented by Formula 3-2: Synthesis was conducted through the 65 same procedure as in synthesis of the arylamine connection group of Formula 2-2.

2) 5.00 g of compound of Formula c (7.98 mmol) and 7.09 g of 4-(N-phenyl-N-phenylamino)phenyl-1-naphthylamine (18.4 mmol) were dissolved in 120 ml of toluene, 5.29 g of sodium-tert-butoxide (55.0 mmol), 0.21 g of bis(dibenzylidene acetone)palladium(0) (0.37 mmol), and 0.22 ml of 50 wt % tri-tert-butylphosphine toluene solution (0.55 mmol) were added thereto, and reflux was conducted in a nitrogen atmosphere for 2 hours. Distilled water was added to the reaction solution to complete the reaction, and the organic layer was extracted. A column separation process was conducted using a solvent of n-hexane and tetrahydrofuran at a ratio of 4:1, stirring was conducted using petroleum ether, and vacuum drying was conducted to produce the compound of Formula 2-2 (5.6 g, yield 53%). MS: [M+H]⁺=1174.

EXAMPLE 9

Production of an Organic Light Emitting Device

A glass substrate (corning 7059 glass), on which ITO (indium tin oxide) was applied to a thickness of 1000 Å to form a thin film, was put in distilled water, in which a detergent was dissolved, and washed using ultrasonic waves. In connection with this, a product manufactured by Fischer Inc. was used as the detergent, and distilled water was produced by filtering twice using a filter manufactured by Millipore Inc. After ITO was washed for 30 min, ultrasonic washing was conducted twice using distilled water for 10 min. After the washing using distilled water was completed, ultrasonic washing was conducted using isopropyl alcohol, acetone, and methanol solvents, and drying was then conducted. Next, it was transported to a plasma washing machine. Furthermore, the substrate was dry washed using oxygen plasma for 5 min, and then transported to a vacuum evaporator.

Hexanitrile hexaazatriphenylene (hereinafter, referred to as "HAT") of the following Formula was vacuum deposited to a thickness of 80 Å by heating on a transparent 1TO electrode, which was prepared through the above procedure, so as to form a thin film. The thin film can improve the characteristics of an interface of the substrate and a hole injection layer. Subsequently, the compound of Formula 2-1 was deposited on the thin film to a thickness of 800 Å to form an anode including an 1TO conductive layer and an N-type organic material.

NPB was deposited thereon to a thickness of 300 Å so as to form a hole transport layer, and Alq3 was then deposited thereon to a thickness of 300 Å to form a light emitting layer. An electron transport layer material of the following Formula was deposited to a thickness of 200 Å on the light emitting layer to form an electron transport layer.

25

35

Production of an Organic Light Emitting Device

The procedure of example 9 was repeated to produce a device except that the compound of Formula 2-1 used as the hole injection layer was substituted with the compound of Formula 2-4.

The resulting device had an electric field of 7.36 V at a forward current density of 100 mA/cm², and a spectrum having at a light efficiency of 2.12 lm/W.

EXAMPLE 12

Production of an Organic Light Emitting Device

The procedure of example 9 was repeated to produce a device except that the compound of Formula 2-1 used as the hole injection layer was substituted with the compound of Formula 2-18.

The resulting device had an electric field of 8.58 V at a forward current density of 100 mA/cm², and a spectrum having at a light efficiency of 1.97 lm/W.

EXAMPLE 13

Production of an Organic Light Emitting Device

The procedure of example 9 was repeated to produce a device except that the compound of Formula 2-1 used as the hole injection layer was substituted with the compound of Formula 2-19.

The resulting device had an electric field of 9.20~V at a forward current density of $100~mA/cm^2$, and a spectrum having at a light efficiency of 2.36~lm/W.

EXAMPLE 14

Production of an Organic Light Emitting Device

The procedure of example 9 was repeated to produce a device except that the compound of Formula 2-1 used as the hole injection layer was substituted with the compound of Formula 2-21.

The resulting device had an electric field of 8.18 V at a forward current density of $100~\text{mA/cm}^2$, and a spectrum having at a light efficiency of 2.67~lm/W.

EXAMPLE 15

Production of an Organic Light Emitting Device

The procedure of example 9 was repeated to produce a device except that the compound of Formula 2-1 used as the hole injection layer was substituted with the compound of Formula 2-256.


The resulting device had an electric field of 6.79 V at a 55 forward current density of 100 mA/cm², and a spectrum having at a light efficiency of 1.83 lm/W.


EXAMPLE 16

Production of an Organic Light Emitting Device

The procedure of example 9 was repeated to produce a device except that the compound of Formula 2-1 used as the hole injection layer was substituted with the compound of Formula 3-2.

The resulting device had an electric field of 8.91 V at a forward current density of 100 mA/cm², and a spectrum having at a light efficiency of 2.08 lm/W.





Electron transport layer material

Lithium fluoride (LiF) having a thickness of 12 Å and aluminum having a thickness of 2000 Å were sequentially deposited on the electron transport layer to form a cathode.

In the above procedure, the deposition speed of an organic material was maintained at 0.3-0.8 Å/sec. Furthermore, lithium fluoride and aluminum were deposited at speeds of 0.3 Å/sec and 1.5-2.5 Å/sec, respectively, on the cathode. During the deposition, a vacuum was maintained at $1-3\times10^{-7}$.

The resulting device had an electric field of 8.78 V at a forward current density of 100 mA/cm², and a spectrum having a light efficiency of 2.01 lm/W. The operation and light emission of the device at the above-mentioned actuating voltage mean that the compound of Formula 2-1, which formed the layer between the thin film on the substrate and the hole transport layer, functions to inject holes.

EXAMPLE 10

Production of an Organic Light Emitting Device

The procedure of example 9 was repeated to produce a 60 device except that the compound of Formula 2-1 used as the hole injection layer was substituted with the compound of Formula 2-2.

The resulting device had an electric field of 8.75~V at a $_{65}$ forward current density of $100~mA/cm^2$, and a spectrum having at a light efficiency of 2.01~lm/W.

20

40

INDUSTRIAL APPLICABILITY

The compound of the present invention can be used as an organic material layer material, particularly, hole injection and/or transport materials in an organic light emitting device, 5 and when applied to an organic light emitting device it is possible to reduce the actuating voltage of the device, to improve the light efficiency thereof, and to improve the lifespan of the device through the thermal stability of the compound.

What is claimed is:

1. An organic light emitting device, comprising: a first electrode;

organic material layer(s) comprising a light emitting layer, wherein at least one layer of the organic material layer(s) 15 includes the compound of Formula 1; and a second electrode;

wherein the first electrode, the organic material layer(s), and the second electrode form layered structure,

> [Formula 1] 6R 25 7R R3 30 10R Ŕ11 Ŕ1 35

wherein X is C or Si; A is

B is

a and b are zero or positive integer;

Y is a bond; bivalent aromatic hydrocarbons; bivalent aromatic hydrocarbons which are substituted with at least 55 one substituent group selected from the group consisting of nitro, nitrile, halogen, alkyl, alkoxy, and amino groups; a bivalent heterocyclic group; or a bivalent heterocyclic group which is substituted with at least one substituent group selected from the group consisting of 60 nitro, nitrile, halogen, alkyl, alkoxy, and amino groups;

Y1 to Y4 are each bivalent aromatic hydrocarbons; bivalent aromatic hydrocarbons which are substituted with at least one substituent group selected from the group consisting of nitro, nitrile, halogen, alkyl, alkoxy, and amino 65 groups; a bivalent heterocyclic group; or a bivalent heterocyclic group which is substituted with at least one

208

substituent group selected from the group consisting of nitro, nitrile, halogen, alkyl, alkoxy, and amino groups;

Z1 to Z8 are each independently hydrogen; aliphatic hydrocarbons having a carbon number of 1-20; aromatic hydrocarbons; aromatic hydrocarbons which are substituted with at least one substituent group selected from the group consisting of the nitro, nitrile, halogen, alkyl, alkoxy, amino, aromatic hydrocarbon, and heterocyclic groups; a silicon group substituted with aromatic hydrocarbons; a heterocyclic group; a heterocyclic group which is substituted with at least one substituent group selected from the group consisting of the nitro, nitrile, halogen, alkyl, alkoxy, amino, aromatic hydrocarbon, and heterocyclic groups; a thiophenyl group which is substituted with hydrocarbons having a carbon number of 1-20 or aromatic hydrocarbons having a carbon number of 6-20; or a boron group which is substituted with aromatic hydrocarbons;

R1 to R11 are each independently hydrogen, a substituted or unsubstituted alkyl group, a substituted or unsubstituted alkoxy group, a substituted or unsubstituted alkenyl group, a substituted or unsubstituted aryl group, a substituted or un-substituted arylamine group, a substituted or unsubstituted heterocyclic group, an amino group, a nitrile group, a nitro group, a halogen group, an amide group, or an ester group, and

R1 to R11 may form aliphatic or hetero condensation rings along with adjacent groups; and R7 and R8 may be directly connected to each other, or may form a condensation ring along with a group selected from the group consisting of O, S, NR, PR, C=O, CRR', and SiRR', wherein R and R' are each independently or collectively are hydrogen, a substituted or unsubstituted alkyl group, a substituted or un-substituted alkoxy group, a substituted or unsubstituted alkenyl group, a substituted or unsubstituted aryl group, a substituted or unsubstituted arylamine group, a substituted or unsubstituted heterocyclic group, a nitrile group, an amide group, or an ester group, and may form a condensation ring to form a spiro compound.

2. The organic light emitting device as set forth in claim 1, wherein R7 and R8 of Formula 1 form a condensation ring along with a group selected from the group consisting of O, S, NR, PR, C=O, CRR', and SiRR'.

3. The organic light emitting device as set forth in claim 1, wherein the compound of Formula 1 is any one of compounds of Formulae 2 to 5:

-continued

. The organic light emitting device as set forth in claim **1**, wherein A or B of Formula 1 is any one of following groups:

-continued

-continued

-continued

-continued

$$NO_2$$

-continued

50 25

-continued

-continued

-continued -ОМе NO_2

-continued

-continued

-continued

-continued

-continued

-continued

114 25

$$NO_2$$

-continued

-continued

ОМе

15

20

-continued

OMe

5

N

10

20

OMe 30

-continued

OMe

5

N

10

20

65

-continued

5 -N

-continued

45

-continued

258 5 N

-continued 268 -OMe 10

-continued

-continued

323

30

321 35

25

NO₂
40
45

-N-CN

60

-continued

-continued

368

5

N

10

-continued

-continued

-continued

NO₂

405

-continued

55

60

$$\frac{1}{\sqrt{N}}$$

-continued

418
40
N
45

420

65

60

60

65

-continued

-continued 425 -CN 5

-continued

472 35 -OMe

NO₂

15

20

25

-continued

CN N -continued
476

5. The organic light emitting device as set forth in claim 1, wherein the organic material layer(s) comprise a hole transport layer, and the hole transport layer includes the compound $_{30}$ of Formula 1.

6. The organic light emitting device as set forth in claim **1**, wherein the organic material layer(s) comprise a hole injection layer, and the hole injection layer includes the compound of Formula 1.

7. The organic light emitting device as set forth in claim 1, wherein the organic material layer(s) comprise a layer which both injects and transports holes and which includes the compound of Formula 1.

* * * * *



专利名称(译)	使用其的化合物和有机发光装置		
公开(公告)号	<u>US7842404</u>	公开(公告)日	2010-11-30
申请号	US11/658770	申请日	2005-09-23
[标]申请(专利权)人(译)	CHO董旭 金姬EUN JEON BYUNG SUN JEONG DONG SEOB 尹锡HEE MOON JAE MIN		
申请(专利权)人(译)	CHO董旭 金姬EUN JEON BYUNG SUN JEONG DONG SEOB 尹锡HEE MOON JAE MIN		
当前申请(专利权)人(译)	LG化学有限公司.		
[标]发明人	CHO WOOK DONG KIM JI EUN JEON BYUNG SUN JEONG DONG SEOB YOON SEOK HEE MOON JAE MIN		
发明人	CHO, WOOK DONG KIM, JI EUN JEON, BYUNG SUN JEONG, DONG SEOB YOON, SEOK HEE MOON, JAE MIN		
IPC分类号	H01L51/54		
CPC分类号	C07D221/20 C09K11/06 H01L51/006 H01L51/0061 H01L51/0072 H05B33/14 C09K2211/1022 C09K2211/1029 C09K2211/1458 C09K2211/1466 H01L51/0058 H01L51/5012 H01L51/5048 H01L51 /5088 Y10S428/917		
助理审查员(译)	WILSON , MICHAEL		
优先权	1020040077245 2004-09-24 KR		
其他公开文献	US20090200542A1		
外部链接	Espacenet USPTO		

摘要(译)

公开了一种有机发光器件。有机发光装置包括第一电极,包括发光层的有机材料层和第二电极。第一电极,有机材料层和第二电极 形成层状结构,并且至少一层有机材料层包括式1的化合物或式1的化合物,其中热固性或光固化-引入了可交联的官能团。

[Formula 1]