



US006333603B1

(12) **United States Patent**
Juang et al.

(10) **Patent No.:** **US 6,333,603 B1**
(45) **Date of Patent:** **Dec. 25, 2001**

(54) **ORGANIC LIGHT EMISSION DEVICE DISPLAY MODULE**

5,962,970 * 10/1999 Yokoi et al. 313/506

* cited by examiner

(75) Inventors: **Dar-Chang Juang; Kun-Wei Lin**, both of Hsinchu (TW)

Primary Examiner—Don Wong

Assistant Examiner—Jimmy T. Vu

(73) Assignee: **Sunplus Technology Co., Ltd.** (TW)

(74) *Attorney, Agent, or Firm*—Lowe Hauptman Gilman & Berner, LLP

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(57) **ABSTRACT**

An organic light emission display module is formed by an organic light emission device panel and a driving circuit board. In manufacturing the organic light emission device panel, electrodes are extended to the edges of the panel. The bonding pads are produced by forming aluminum films. The driving circuit board is made of thin printed circuit board, and bonding pads are manufactured at the edges of the printed circuit board, which are corresponding to the bonding pads of the organic light emission device panel, respectively. The driving circuit board is adhered to the organic light emission device panel, and the each bonding pad of the organic light emission device panel is connected to a respective bonding pad of the driving circuit board. Epoxy resin is filled into the bonding area and gaps between the printed circuit board and the organic light emission device panel.

(21) Appl. No.: **09/597,258**

(22) Filed: **Jun. 19, 2000**

(51) **Int. Cl.⁷** **G09G 3/10**

(52) **U.S. Cl.** **315/169.3; 315/169.1; 315/169.2; 315/169.4; 313/496; 313/505**


(58) **Field of Search** **315/169.3, 169.1, 315/169.4, 169.2; 313/505, 496**

(56) **References Cited**

U.S. PATENT DOCUMENTS

- 4,459,514 * 7/1984 Morimoto et al. 315/169.1
- 5,142,388 * 8/1992 Watanabe et al. 313/496
- 5,793,163 * 8/1998 Okuda 315/169.3

17 Claims, 6 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 7




FIG. 6




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG.14 PRIOR ART




FIG.15 PRIOR ART

ORGANIC LIGHT EMISSION DEVICE DISPLAY MODULE

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to the field of organic light emission devices, and especially to an organic light emission device display module having an organic light emission device panel and a driving circuit board connected to the organic light emission device panel by bonding wires.

2. Description of Related Art

An organic light emission device (hereinafter abbreviated as OLED) is an electronic element capable of converting electrical energy into light energy for output. The operating principle of the OLED is very similar to that of a light emitting diode (LED). FIG. 14 shows a circuit diagram of an OLED panel formed by a plurality of OLEDs 901. Each OLED 901 has two ends connected to an InTiO₃ (hereinafter abbreviated as ITO) electrode 902 and an aluminum electrode 903, respectively. As such, by applying current to the electrodes 902 and 903, the OLEDs 901 are controlled to emit light. Since illuminated light generated by the OLED 901 is approximately proportional to the working current thereof, the driving current applied to the OLED panel is generally very large. Therefore, the resistance of a connection between the OLED panel and a driving circuit must be relatively low to avoid the current loss and sustaining the uniform of illumination.

With reference to FIG. 15, in conventional skill, the connection between the OLED panel 900 and driving circuit is achieved by a tape carrier (TC) manner. That is, a soft aluminum foil board 905 is provided as a conductor tape for connecting the OLED panel 900 with a printed circuit board (hereinafter abbreviated as PCB) (not shown) having the driving circuit. By adhering the joint points at one end of the soft aluminum board 905 to the electrodes 902 and 903 of the OLED panel 900, the OLED panel 900 is electrically connected to the driving circuit. Alternatively, a chip that includes the driving circuit may be adhered to the soft aluminum board 905 by welding in using the tap automatic bonding (TAB) technique. However, in the above conventional skill, the soft aluminum foil board 905 is too expensive and the cost for TAB package is relatively high. Furthermore, the package dimension can not be decreased due to the large aluminum foil board, which results in a difficulty in the miniaturization of OLED products. In addition, since the relatively long conductor tape is carried with a large driving current necessary by the OLEDs. It is likely to result in a current loss due to a large resistance of the conductor tape, and also cause an electromagnetic interference (hereinafter abbreviated as EMI) problem. Therefore, it is desired to have a novel OLED display module that can mitigate and/or obviate the aforementioned problems.

SUMMARY OF THE INVENTION

Accordingly, the primary object of the present invention is to provide a low-cost and miniaturized OLED display module that does not cause the current loss and EMI problems.

To achieve the above object, the OLED display module in accordance with the present invention includes an OLED panel and a driving circuit board. The OLED panel has a plurality of electrodes extended to edges of the OLED panel for forming a plurality of first bonding pads, respectively.

The driving circuit board has a driving circuit for driving the OLED panel, and a plurality of second bonding pads connected to the driving circuit. The plurality of second bonding pads of the driving circuit board are arranged with respect to the plurality of first bonding pads of the OLED panel, and each of the second bonding pads is connected to a respective first bonding pad by a bonding wire.

The various objects and advantages of the present invention will be more readily understood from the following detailed description when read in conjunction with the appended drawing.

BRIEF DESCRIPTION OF DRAWINGS

FIG. 1 is a schematic view showing that the transparent electrodes are formed on a glass substrate for producing an OLED panel used in the present invention;

FIG. 2 is a schematic view showing that an organic light emission film is formed on the glass substrate for producing the OLED panel used in the present invention;

FIG. 3 is a schematic view showing that a chromium layer is formed on the glass substrate for producing the OLED panel used in the present invention;

FIG. 4 is a schematic view showing that the metal electrodes are formed on the glass substrate for producing the OLED panel used in the present invention;

FIG. 5 is a schematic view showing that an insulation coating and light shield film are formed on the glass substrate for producing the OLED panel used in the present invention;

FIG. 6 is a cross sectional view showing the OLED panel of FIG. 5 by taking along the sectional line A—A;

FIG. 7 is a cross sectional view showing the OLED panel of FIG. 5 by taking along the sectional line B—B;

FIG. 8 is a plane view showing the driving circuit board used in the first embodiment of the present invention;

FIG. 9 is a plane view showing the OLED display module in accordance with the first embodiment of the present invention;

FIG. 10 is a perspective view of the OLED module in accordance with the first embodiment of the present invention;

FIG. 11 is a plane view of the driving circuit board used in the second embodiment of the present invention;

FIG. 12 is a plane view of the OLED display module in accordance with the second embodiment of the present invention;

FIG. 13 is a cross sectional view of the OLED display module in accordance with the second embodiment of the present invention shown in FIG. 12 by taking along the sectional line C—C;

FIG. 14 is a circuit diagram of a conventional OLED panel; and

FIG. 15 is a schematic view showing the connection between an OLED panel and a driving circuit board in prior art.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

One preferred embodiment of the OLED display module in accordance with the present invention may refer to FIGS. 1 to 5, wherein the manufacturing process of an OLED panel is illustrated. As shown in FIG. 1, at first, a plurality of lateral transparent electrodes 102 are formed on a glass

substrate **101**. It is preferred that the transparent electrode **102** is an ITO electrode. Each transparent electrode **102** has an end **104** extended to an edge of the glass substrate **102**. Next, as shown in FIG. 2, by using a technique such as vapor deposition, an organic light emission film **105** is formed on the surface of the glass substrate **101** that is formed with the transparent electrodes **102**, such that the transparent electrodes **102** are substantially covered, except that the extended ends **104** are exposed.

FIG. 3 shows that each extended end **104** of the transparent electrode **102** is formed with a chromium (Cr) layer **103**. Then, as shown shown in FIG. 4, a plurality of longitudinal metal electrode **107** are further formed on the organic light emission film **105** by, for example, vapor deposition technique. It is preferred that the metal electrodes **107** are aluminum electrodes. Each metal electrode **107** has an end **108** protruded out of the organic light emission film **105**, and extended to another edge of the glass substrate **101**, so that the extended end **108** of the metal electrodes **107** are provided as a bonding pad **109**. In this manufacturing process of forming the aluminum metal electrodes **107**, a metal film **106** made of the same material as that of the metal electrodes **107** are formed on the chromium layer **103** at the extended end **104** of the transparent electrode **102** for being provided as a bonding pad **109**. In this preferred embodiment, the metal film **106** is an aluminum film. Because the chromium can be securely bonded to the InTiO₃, the aluminum metal film **106** is thus securely combined with the transparent electrode **102**, so as to form a bonding pad **109** capable of bonding wires.

Then, with reference to the FIGS. 5, 6, and 7, an insulation coating **111** and a light shield film **112** are sequentially formed on the part of the glass substrate **101** that is formed with the organic light emission film **105**, so as to provide a protection and light-shield capability. Furthermore, the bonding pads **109** are exposed out of the insulation coating **111** and light shield film **112** for being connected to a driving circuit. As a result, an OLED panel **100** having the electrodes **102** and **107** extended to the edges of the panel for forming bonding pads **109** is provided.

This OLED panel **100** can be electrically connected to a driving circuit board, which has a driving circuit to drive the OLED panel **100**, by bonding wires. With reference to FIG. 8, the driving circuit board **801** is made of thin PCB **802**, which is installed with a driving circuit formed by driver chips **803**. On two edges of the PCB **802**, a plurality of bonding pads **804** are formed and connected to the driving circuit. These bonding pads **804** are arranged with respect to the bonding pads **109** of the OLED panel **100**. As shown in FIG. 9, the driving circuit board **801** can be overlapped and adhered to the OLED panel **100**, and the bonding pads **109** of the OLED panel **100** are connected to the bonding pads **804** of the driving circuit board **801**, respectively, by bonding wires **805**. Then, as shown in FIG. 10, encapsulation material **806**, such as epoxy resin, is filled into the bonding area where the bonding wires **805** are arranged, and the gaps between the driving circuit board **801** and the OLED panel **100**, so as to protect the bonding wires **805** and secure the OLED panel **100** to the driving circuit board **801**. As such, an OLED display module in accordance with the present invention is completed. Because the OLED panel **100** is electrically connected to the driving circuit board **801** by very short bonding wires **805**, there is no need to have the large and expensive soft aluminum foil board, as generally employed in the conventional skill. Accordingly, a low-cost and miniaturized OLED display module can be manufactured without the current loss and EMI problems, so as to enhance the performance of the OLED display module significantly.

FIG. 11 shows a driving circuit board **811** used in another preferred embodiment of the present invention. The driving circuit board **811** is also made of a thin PCB **812**, which is installed with a driving circuit formed by driver chips **813**. The PCB **812** defines an aperture **819**, which has a dimension slightly smaller than that of the OLED panel **100**. On two internal edges of the PCB **812** near the aperture **819**, a plurality of bonding pads **814** are formed and connected to the driving circuit. These bonding pads **814** are arranged with respect to the bonding pads **109** of the OLED panel **100**. As shown in FIG. 12, the driving circuit board **801** can be substantially installed in the aperture **819** and adhered to the driving circuit board **811**, and the bonding pads **109** of the OLED panel **100** are connected to the bonding pads **814** of the driving circuit board **811**, respectively, by bonding wires **815**. Then, as shown in FIG. 13, encapsulation material **816**, such as epoxy resin, is filled into the bonding area where the bonding wires **815** are arranged, and the gaps between the driving circuit board **811** and the OLED panel **100**, so as to protect the bonding wires **815** and secure the OLED panel **100** to the driving circuit board **811**. As a result, an OLED display module having the same function as the previous embodiment but with a small thickness is completed.

Although the present invention has been described with reference to the preferred embodiments, it will be understood that the invention is not limited to the details described thereof. Various substitutions and modifications have been suggested in the foregoing description, and others will occur to those of ordinary skill in the art. Therefore, all such substitutions and modifications are intended to be embraced within the scope of the invention as defined in the appended claims.

What is claimed is:

1. An organic light emission device display module comprising:

an organic light emission device panel having a plurality of electrodes extended to edges of the organic light emission device panel for forming a plurality of first bonding pads, respectively; and

a driving circuit board having a driving circuit for driving the organic light emission device panel, and a plurality of second bonding pads connected to the driving circuit,

wherein the plurality of second bonding pads of the driving circuit board are arranged with respect to the plurality of first bonding pads of the organic light emission device panel, and each of the second bonding pads is connected to a respective first bonding pad by a bonding wire.

2. The organic light emission device display module as claimed in claim 1, wherein the plurality of second bonding pads are formed at an edge of the driving circuit board.

3. The organic light emission device display module as claimed in claim 2, wherein the organic light emission device panel is overlapped on the driving circuit board.

4. The organic light emission device display module as claimed in claim 3, wherein the electrodes of the organic light emission device panel includes a plurality of transparent electrodes and a plurality of metal electrodes, each transparent electrode having an extended end formed thereon a metal film, so as to be provided as the first bonding pad.

5. The organic light emission device display module as claimed in claim 4, wherein the metal electrode is an aluminum electrode and the metal film is an aluminum film.

6. The organic light emission device display module as claimed in claim 5, wherein the extended end of each

5

transparent electrode is first formed with a chromium layer, and then formed with the aluminum film.

7. The organic light emission device display module as claimed in claim 6, wherein the aluminum film and the aluminum electrode are formed in the same manufacturing process.

8. The organic light emission device display module as claimed in claim 3, wherein encapsulation material is filled to a bonding area where the bonding wires are arranged, and gaps between the organic light emission device panel and the driving circuit board.

9. The organic light emission device display module as claimed in claim 8, wherein the encapsulation material is epoxy resin.

10. The organic light emission device display module as claimed in claim 1, wherein the driving circuit board defines an aperture, and the plurality of second bonding pads are formed at an internal edge of the driving circuit board near the aperture.

11. The organic light emission device display module as claimed in claim 10, wherein the organic light emission device panel is installed in the aperture of the driving circuit board.

12. The organic light emission device display module as claimed in claim 11, wherein the electrodes of the organic light emission device panel includes a plurality of transpar-

6

ent electrodes and a plurality of metal electrodes, each transparent electrode having an extended end formed thereon a metal film, so as to be provided as the first bonding pad.

13. The organic light emission device display module as claimed in claim 12, wherein the metal electrode is an aluminum electrode and the metal film is an aluminum film.

14. The organic light emission device display module as claimed in claim 13, wherein the extended end of each transparent electrode is first formed with a chromium layer, and then formed with the aluminum film.

15. The organic light emission device display module as claimed in claim 14, wherein the aluminum film and the aluminum electrode are formed in the same manufacturing process.

16. The organic light emission device display module as claimed in claim 11, wherein encapsulation material is filled to a bonding area where the bonding wires are arranged, and gaps between the organic light emission device panel and the driving circuit board.

17. The organic light emission device display module as claimed in claim 16, wherein the encapsulation material is epoxy resin.

* * * * *

专利名称(译)	有机发光器件显示模块		
公开(公告)号	US6333603	公开(公告)日	2001-12-25
申请号	US09/597258	申请日	2000-06-19
[标]申请(专利权)人(译)	凌阳科技股份有限公司		
申请(专利权)人(译)	天普科技有限公司		
[标]发明人	JUANG DAR CHANG LIN KUN WEI		
发明人	JUANG, DAR-CHANG LIN, KUN-WEI		
IPC分类号	H01L27/28 H01L27/32 G09G3/32 H05K3/32 H05K1/11 G09G3/10		
CPC分类号	H01L27/3288 G09G3/3216 H05K1/117 H05K3/328		
审查员(译)	黄, DON		
外部链接	Espacenet USPTO		

摘要(译)

有机发光显示模块由有机发光装置面板和驱动电路板形成。在制造有机发光器件面板时，电极延伸到面板的边缘。通过形成铝膜来制造键合焊盘。驱动电路板由薄印刷电路板制成，并且在印刷电路板的边缘处制造键合焊盘，其分别对应于有机发光器件面板的键合焊盘。驱动电路板粘附到有机发光装置面板，并且有机发光装置面板的每个焊盘连接到驱动电路板的相应焊盘。将环氧树脂填充到印刷电路板和有机发光器件面板之间的粘合区域和间隙中。

