



US008148894B2

(12) **United States Patent**
Park et al.

(10) **Patent No.:** **US 8,148,894 B2**
(45) **Date of Patent:** **Apr. 3, 2012**

(54) **ORGANIC LIGHT EMITTING DIODE DISPLAY**

(75) Inventors: **Soon-Ryong Park**, Yongin (KR);
Woo-Suk Jung, Yongin (KR);
Hee-Seong Jeong, Yongin (KR);
Hee-Chul Jeon, Yongin (KR);
Chul-Woo Jeong, Yongin (KR);
Jaе-Yong Kim, Yongin (KR); **Eun-Ah Kim**, Yongin (KR); **Noh-Min Kwak**, Yongin (KR); **Joo-Hwa Lee**, Yongin (KR)

6,297,864	B1	10/2001	Kaneko et al.	
6,417,892	B1 *	7/2002	Sharp et al.	348/742
6,552,767	B1 *	4/2003	Kaneko	349/119
6,624,936	B2	9/2003	Kotchick et al.	
6,667,784	B2 *	12/2003	Sharp et al.	349/78
6,774,962	B2	8/2004	Yoon	
6,787,976	B2	9/2004	Minoura et al.	
6,841,803	B2	1/2005	Aizawa et al.	
6,898,018	B2	5/2005	Minoura et al.	
2002/0043931	A1	4/2002	Minoura et al.	
2002/0122235	A1	9/2002	Kurtz et al.	

(Continued)

FOREIGN PATENT DOCUMENTS

EP 0588504 A1 3/1994

(Continued)

(73) Assignee: **Samsung Mobile Display Co., Ltd.**, Yongin (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 260 days.

OTHER PUBLICATIONS

European search report for European patent application No. 09166447.4-2203 dated Nov. 24, 2009 by European Patent Office.

(Continued)

(21) Appl. No.: **12/536,315**

(22) Filed: **Aug. 5, 2009**

Prior Publication Data

US 2010/0156282 A1 Jun. 24, 2010

Primary Examiner — Nimeshkumar Patel

Assistant Examiner — Christopher Raabe

(74) *Attorney, Agent, or Firm* — Knobbe, Martens, Olson & Bear LLP

Foreign Application Priority Data

Aug. 27, 2008 (KR) 10-2008-0083913

(57) **ABSTRACT**

The present invention relates to an OLED display. In some embodiments, the OLED display may employ combinations of linear polarization, circular or elliptical polarization, and phase delay in order to suppress reflection from external light while minimizing the loss of emitted light from the OLED display. For example, the OLED in the display includes a stack having a first electrode, an organic emission layer, and a second electrode, a DBEF formed on the OLED, a first polarizing plate formed on the DBEF, a second polarizing plate formed on the first polarizing plate, and a plurality of phase delay plates formed between the first polarizing plate and the second polarizing plate.

(51) **Int. Cl.**

H05B 33/12 (2006.01)

(52) **U.S. Cl.** **313/504**; 313/507

(58) **Field of Classification Search** 313/498-512; 315/169.3; 345/36, 45, 76


See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,118,504	A	9/2000	Iijima et al.
6,169,708	B1	1/2001	Kaneko et al.

17 Claims, 11 Drawing Sheets



U.S. PATENT DOCUMENTS

2002/0145689	A1 *	10/2002	Kaneko	349/114
2003/0127656	A1	7/2003	Aizawa et al.	
2004/0051445	A1	3/2004	Adachi	
2004/0189167	A1	9/2004	Adachi et al.	
2004/0227698	A1 *	11/2004	Yamazaki et al.	345/32
2005/0035353	A1 *	2/2005	Adachi et al.	257/72
2005/0127820	A1 *	6/2005	Yamazaki et al.	313/501
2005/0151896	A1 *	7/2005	Hara et al.	349/96
2006/0145600	A1	7/2006	Yu et al.	
2006/0187384	A1	8/2006	Hisatake	
2006/0291238	A1 *	12/2006	Epstein et al.	362/600
2007/0024777	A1	2/2007	Sawayama et al.	
2007/0085476	A1	4/2007	Hirakata et al.	
2007/0145889	A1	6/2007	Tamura et al.	
2007/0230211	A1	10/2007	Osato et al.	
2008/0123321	A1	5/2008	Hsu et al.	
2008/0144177	A1	6/2008	Miller	
2009/0290079	A1	11/2009	Evans et al.	

FOREIGN PATENT DOCUMENTS

EP	0969296	A2	1/2000
GB	2437553	A	10/2007
JP	06-109925	A	4/1994
JP	06-235914		8/1994
JP	07-205322	(A)	8/1995
JP	2001-357979		12/2001
JP	2002-198184		7/2002
JP	2003-121835		4/2003
JP	2003-186413		7/2003
JP	2003-186413	A	7/2003
JP	2003-279988	(A)	10/2003
JP	2003-315548	A	11/2003
JP	2004-030955	A	1/2004
JP	2004-070094	A	3/2004
JP	2004-086145		3/2004
JP	2004-219825	A	8/2004
JP	2004-296162		10/2004
JP	2004-296162	A	10/2004
JP	2004-361774	A	12/2004

JP	2005-108540		4/2005
JP	2006-343553		12/2006
JP	2006-343553	A	12/2006
JP	2007-041536	(A)	2/2007
JP	2007-141824	(A)	6/2007
KR	10-2002-0003428	A	1/2002
KR	2003-0038037		5/2003
KR	10-2003-0077402	A	10/2003
KR	10-0454748		10/2004
KR	10-2005-0018401	A	2/2005
KR	10-2005-0020332	A	3/2005
KR	10-2005-0026863	A	3/2005
KR	10-2005-0071387	A	7/2005
KR	10-2005-0106004	A	11/2005
KR	10-2006-0065729	A	6/2006
KR	10-0606778		8/2006
KR	10-0706730		4/2007
KR	10-0714015		4/2007
KR	10-2007-0095826	A	10/2007
KR	10-2008-0061791	A	7/2008
KR	10-2008-0076384	A	8/2008

OTHER PUBLICATIONS

European search report for European patent application No. 09166444.1-1235 dated Nov. 23, 2009 by European Patent Office.
The Extended European Search Report for European patent application No. 09168087.6-2203 dated Dec. 2, 2009 by European Patent Office.
Office Action dated Mar. 22, 2011 in related U.S. Appl. No. 12/508,426, filed Jul. 23, 2009.
Office Action dated Apr. 4, 2011 in related U.S. Appl. No. 12/508,409, filed Jul. 23, 2009.
Japanese Notice of Allowance dated Jan. 24, 2012 for Japanese Patent Application No. JP 2009-097936 which shares priority of Korean Patent Application No. KR 10-2009-0009364 with U.S. Appl. No. 12/508,438, filed Jul. 23, 2009, which is related to captioned U.S. Appl. No. 12/536,315.

* cited by examiner

FIG. 1




FIG. 2




FIG. 4




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10





FIG. 11



ORGANIC LIGHT EMITTING DIODE DISPLAY

CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims priority to and the benefit of Korean Patent Application No. 10-2008-0083913 filed in the Korean Intellectual Property Office on Aug. 27, 2008, the entire contents of which are incorporated herein by reference.

BACKGROUND

1. Field of the Invention

The present invention relates to an organic light emitting diode (OLED) display. More particularly, it relates to an OLED display having improved display characteristics.

2. Description of the Related Art

An OLED display includes a plurality of organic light emitting diodes (OLEDs). OLEDs typically include hole injection electrodes, an organic light emission layer, and electron injection electrodes. Light is emitted when excitons are generated in the organic light emission layer. Excitons are generated as electrons and holes are combined drop from an excited state to a ground state. The OLED display displays an image by using the light resulting from these excitons.

Accordingly, the OLED display has self-luminance characteristics, and unlike a liquid crystal display (LCD), the thickness and weight thereof can be reduced since a separate light source is not required. Thus, OLED displays are used in various applications, such as displays in mobile electronic devices, because an OLED display has low power consumption, high luminance, and high reaction speed.

Unfortunately, one of the electrodes and other metal wires in the OLED display can reflect external light, such as ambient light. This reflected light can deteriorate the performance of the OLED display, especially when the OLED display is used in a bright setting. For example, the OLED display's expression of black color and contrast can be deteriorated due to reflections of external light, thereby reducing visibility of the OLED display.

One known technique for solving this problem is the use of a polarizing plate and a phase delay plate. These plates are arranged on an OLED for suppressing reflection of external light. However, because light from the organic emission layer must pass through them, the polarizing plate and phase delay plate also reduce the light generated from the OLED and may decrease the performance and visibility of the OLED display device.

The above information disclosed in this Background section is only for enhancement of understanding. Therefore, it may contain information that does not form the prior art that is already known in this country to a person of ordinary skill in the art.

SUMMARY

Embodiments of the present invention provide an organic light emitting diode (OLED) display having advantages of improving visibility by suppressing reflection of external light and minimizing loss of light emitted from an organic emission layer of the OLED display. In addition, embodiments of the OLED display can reduce power consumption and may have increased life-span.

An exemplary OLED display according to an embodiment of the present invention includes an OLED formed by sequentially stacking a first electrode, an organic emission layer, and

a second electrode, a dual brightness enhancement film (DBEF) formed on the OLED, a first polarizing plate formed on the DBEF, a second polarizing plate formed on the first polarizing plate, and a plurality of phase delay plates formed between the first polarizing plate and the second polarizing plate. The first polarizing plate and the DBEF may have the same polarizing axis. An angle of intersection between the polarizing axis of the first polarizing plate and a polarizing axis of the second polarizing plate may be about 45 degrees.

In an embodiment, the plurality of phase delay plates may include a first phase delay plate, a second phase delay plate, and a third phase delay plate. The first phase delay plate can be a $\frac{1}{2}$ wavelength plate interposed between the first polarizing plate and the second polarizing plate. The second phase delay plate may be a $\frac{1}{4}$ wavelength plate interposed between the first polarizing plate and the first phase delay plate. And, the third phase delay plate may be a $\frac{1}{4}$ wavelength plate interposed between the first polarizing plate and the second phase delay plate.

An angle of intersection between the polarizing axis of the second polarizing plate and a light axis of the first phase delay plate may range from about 17.5 degrees to about 27.5 degrees.

An angle of intersection between the polarizing axis of the first polarizing plate and the light axis of the first phase delay plate may range from about 17.5 degrees to about 27.5 degrees.

An angle of intersection between the polarizing axis of the second polarizing plate and the light axis of the second phase delay plate may range from about 40 degrees to about 50 degrees.

An angle of intersection between the polarizing axis of the first polarizing plate and the light axis of the second phase delay plate may range from about 0 degrees to about 5 degrees.

An angle of intersection between the polarizing axis of the second polarizing plate and a light axis of the third phase delay plate may range from about 85 degrees to about 90 degrees.

An angle of intersection between the polarizing axis of the first polarizing plate and the light axis of the third phase delay plate may range from about 40 degrees to about 50 degrees.

An angle of intersection between the light axis of the second phase delay plate and the light axis of the third phase delay plate may be about 45 degrees.

In another embodiment, the plurality of phase delay plates may include a first phase delay and a second phase delay plate. The first phase delay plate can be a $\frac{1}{2}$ wavelength plate interposed between the first polarizing plate and the second polarizing plate. The second phase delay plate can be a $\frac{1}{4}$ wavelength plate interposed between the first polarizing plate and the first phase delay plate.

An angle of intersection between the polarizing axis of the second polarizing plate and the light axis of the first phase delay plate may range from about 10 degrees to about 20 degrees.

An angle of intersection between the polarizing axis of the first polarizing plate and the light axis of the first phase delay plate may range from about 25 degrees to about 35 degrees.

An angle of intersection between the polarizing axis of the second polarizing plate and the light axis of the second phase delay plate may range from about 70 degrees to about 80 degrees.

An angle of intersection between the polarizing axis of the first polarizing plate and the light axis of the second phase delay plate may range from about 25 degrees to about 35 degrees.

In an embodiment, the OLED display may further include an additional phase delay plate interposed between the OLED and the DBEF. An angle of intersection between a light axis of the additional phase delay plate and the polarizing axis of the DBEF may range from about 40 degrees to about 50 degrees.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a cross-sectional view of an organic light emitting diode (OLED) display according to a first exemplary embodiment of the present invention.

FIG. 2 is a layout view of a circuit layout of a driving circuit and an OLED of the OLED display of FIG. 1.

FIG. 3 and FIG. 4 are a cross-sectional view and a configuration diagram of a path for transmission of light from outside into the OLED display of FIG. 1.

FIG. 5 and FIG. 6 are a cross-sectional view and a configuration diagram of a path for emission of light generated from an OLED of the OLED display of FIG. 1 to the outside.

FIG. 7 is a cross-sectional view of an OLED display according to a second exemplary embodiment of the present invention.

FIG. 8 and FIG. 9 are a cross-sectional view and a configuration diagram of a path for transmission of light from outside into the OLED display of FIG. 7.

FIG. 10 and FIG. 11 are a cross-sectional view and a configuration diagram of a path for emission of light generated from an OLED of the OLED display of FIG. 7 to the outside.

DETAILED DESCRIPTION OF SOME EMBODIMENTS

The present invention will be described with reference to the accompanying drawings, in which exemplary embodiments of the invention are shown. As those skilled in the art will realize, the described embodiments may be modified in various different ways, all without departing from the spirit or scope of the present invention. Constituent elements having the same configuration are representatively described with reference to one or more embodiments. Other exemplary embodiments may then be described by referring to various differences between the embodiments.

The drawings and description are to be regarded as illustrative in nature and not restrictive. Like reference numerals designate like elements throughout the specification.

In the drawings, the thickness of layers, films, panels, regions, etc., are exaggerated for clarity. For example, it should be understood that when an element such as a layer, film, region, or substrate is referred to as being "on" another element, it can be directly on the other element or intervening elements may also be present. When an element is referred to as being "directly on" another element, there are no intervening elements present. In addition, the size and thickness of each element in the drawing are provided for better understanding and ease of description of various embodiments and are not intended to limit the present invention.

Exemplary embodiments of the present invention will now be described with reference to FIG. 1 and FIG. 2. Exemplary embodiments of an OLED display 100 may have improved visibility by efficiently suppressing the reflection of external light and minimizing the loss of light emitted out from its organic emission layer. In addition, the OLED display 100 can efficiently emit light generated from its organic emission layer to thereby reduce power consumption and increase its life-span. In some embodiments, the OLED display may employ combinations of linear polarization, circular or ellip-

tical polarization, and phase delay in order to suppress reflection from external light while minimizing the loss of emitted light from the OLED display.

As shown in FIG. 1, an organic light emitting diode (OLED) display 100 includes a first substrate 51, a second substrate 52, and an optical member 58. The first and second substrates 51 and 52 are bonded to each other.

The first substrate 51 includes a substrate member 511, a driving circuit unit DC formed on the substrate member 511, and an OLED L1 formed on the driving circuit unit DC. The driving circuit unit DC is shown and described further with reference to FIG. 2.

In the driving circuit unit DC, the driving transistor T2 includes a gate electrode 531, a drain electrode 532, and a source electrode 533. The driving transistor T2 supplies an output current I_{OLED} that is proportional to the square of a voltage difference between the voltage stored in the storage capacitor C1 (shown in FIG. 2) and a threshold voltage to the OLED L1. The OLED L1 then emits light based on the output current I_{OLED} .

The OLED L1 includes a first electrode 544, an organic emission layer 545 formed on the first electrode 544, and a second electrode 546 formed on the organic emission layer 545. The OLED L1 emits light toward the second electrode 546 from the organic emission layer 545, and the OLED display 100 displays an image based on this light. For purposes of illustration, the OLED display 100 is shown as a top light emitting type. However, other embodiments of the OLED display 100 may employ other emitting types.

In general, the first electrode 544 may serve as an anode and the second electrode 546 may serve as a cathode. However, other embodiments may use different configurations. For example, the first electrode 544 may serve as the cathode and the second electrode 546 may serve as the anode. The first electrode 544 of the OLED L1 is connected to the drain electrode 532 of the driving transistor T2. At least one of the first and second electrodes 544 and 546 is made to be trans-reflective or reflective, and thus, reflects light.

The second substrate 52 covers the first substrate 51 on which the OLED L1 and the driving circuit unit DC are formed. For example, the second substrate 52 can be disposed facing the first substrate 51 and cover or protect the components of driving circuit unit DC (e.g., thin film transistors T1 and T2, and the capacitor C1), and the OLED L1 from the external environment.

The second substrate 52 can be bonded to the first substrate 110 by a sealing material (not shown). This sealing material may be formed along an edge of the second substrate 52 to seal a space between the substrates 51 and 52. The second substrate 52 may also cover the optical member 58 formed on the OLED L1.

However, the present invention is not limited to these configurations. For example, the optical member 58 can be formed on the second substrate 52. Thus, the optical member 58 can be disposed outside the sealed space between the first and second substrates 51 and 52. One skilled in the art will recognize that the location of the optical member 58 can be any location on the OLED L1.

The optical member 58 improves visibility of the OLED display 100 by suppressing reflection of external light and minimizes loss of light emitted out from the OLED L1. The optical member 58 includes a DBEF 586, a first polarizing plate 585, a second polarizing plate 581, and a plurality of phase delay plates 582, 583, and 584.

The DBEF **586** is disposed on the OLED **L1**. The first polarizing plate **585** is disposed on the DBEF **586**, and the second polarizing plate **581** is disposed on the first polarizing plate **585**.

The plurality of delay plates **582**, **583**, and **584** are interposed between the first polarizing plate **585** and the second polarizing plate **581**. In some embodiments, phase delay plates **582**, **583**, and **584** are sequentially stacked on the first polarizing plate **585**. For example, the first phase delay plate **582** can be interposed between the first polarizing plate **585** and the second polarizing plate **581**. The second phase delay plate **583** can be interposed between the first polarizing plate **585** and the first phase delay plate **582**. The third phase delay plate **584** can be interposed between the first polarizing plate **585** and the second phase delay plate **583**.

The optical member **58** can further include an additional phase delay plate **587** disposed between the DBEF **586** and the OLED **L1**. Hereinafter, the additional phase delay plate **587** may be referred to as a fourth phase delay plate **587**. However, the embodiments can employ any number of phase delay plates. Thus, the fourth phase delay plate **587** can be omitted if desired.

The first polarizing plate **585** and the second polarizing plate **581** respectively have a polarizing axis and linearly polarize light toward their polarization axis. The first polarizing plate **585** and the second polarizing plate **581** transmit light that matches the polarizing axis of each of the first and second polarizing plates **585** and **581**, and absorbs light that does not match the polarizing axes. Thus, light passed through the first polarizing plate **585** and the second polarizing plate **581** are linearly-polarized along their polarizing axis directions.

The DBEF **586** also transmits light matching the polarizing axes and reflects light that significantly mismatches the polarizing axes. Therefore, the first polarizing plate **585** and the second polarizing plate **581** are different from the DBEF **586**, because the first polarizing plate **585** and the second polarizing plate **581** absorb light that mismatches their polarizing axes.

In some embodiments, the DBEF **586** and the first polarizing plate **585** have polarization axes in the same direction. For example, the angle of intersection between the polarization axis of the first polarizing plate **585** and the polarization axis of the second polarizing plate **581** may be about 45 degrees.

The first phase delay plate **582** is a $\frac{1}{2}$ wavelength plate, and the first phase delay plate **582** has a light axis that is turned by an angle ranging from about 17.5 degrees to about 27.5 degrees from the polarizing axis of the second polarizing plate **581**. That is, an angle of intersection between the light axis of the first phase delay plate **582** and the polarizing axis of the second polarizing plate **581** may range from about 17.5 degrees to about 27.5 degrees. In addition, the angle of intersection between the light axis of the first phase delay plate **582** and the polarizing axis of the first polarizing plate **585** may range from about 17.5 degrees to about 27.5 degrees.

The second phase delay plate **583** is a $\frac{1}{4}$ wavelength plate, and has a light axis that is turned by an angle ranging from about 40 degrees to about 50 degrees from the polarizing axis of the second polarizing plate **581**. That is, the angle of intersection between the light axis of the second phase delay plate **583** and the polarizing axis of the second polarizing plate **581** may range from about 40 degrees to about 50 degrees. In addition, an angle of intersection between the light axis of the second phase delay plate **583** and the polarizing axis of the first polarizing plate **585** may range from about 0 degrees to about 5 degrees.

The third phase delay plate **584** is a $\frac{1}{4}$ wavelength plate, and has a light axis that is turned by an angle ranging from about 85 degrees to about 95 degrees from the polarizing axis of the second polarizing plate **581**. That is, an angle of intersection between the light axis of the third phase delay plate **584** and the polarizing axis of the second polarizing plate **581** may range from about 85 degrees to about 95 degrees. In addition, an angle of intersection between the light axis of the third phase delay plate **584** and the polarizing axis of the first polarizing plate **585** may range from about 40 degrees to about 50 degrees.

The fourth phase delay plate **587** is a $\frac{1}{4}$ wavelength plate, and has a light axis that is turned by an angle ranging from about 40 degrees to about 50 degrees from the polarizing axis of the DBEF **586**.

Referring now to FIG. 2, a driving circuit unit DC may include two or more thin film transistors **T1** and **T2** and at least one storage capacitor **C1**. Configurations of the driving circuit unit DC and the OLED **L1** are not limited to the described embodiments. One skilled in the art will recognize that the embodiments can be variously modified.

As shown, the driving circuit unit DC may include a switching transistor **T1** and a driving transistor **T2**. The switching transistor **T1** is connected to a scan line **SL1** and a data line **DLL**. The switching transistor **T1** transmits a data voltage input from the data line **DL1** according to a switching voltage input to the scan line **SL1** to the driving transistor **T2**.

The storage capacitor **C1** is connected to the switching transistor **T1** and a power source line **VDD**. The capacitor **C1** stores a voltage corresponding to a voltage difference of a voltage transmitted from the switching transistor **T1** and a voltage supplied to the power source line **VDD**.

Referring now to FIG. 3 to FIG. 6, the manner in which the optical member **58** efficiently suppresses reflection of external light and minimizes loss of light emitted to the outside will be further described. The manner in which visible light passes through the optical member **58** will now be described.

As is well known, visible light can be classified according to wavelength bands or colors. For example, blue light has a wavelength range of approximately 420 nm to 480 nm. Green light has a wavelength range of about 550 nm, and red light has a wavelength of about 650 nm.

Since each color has a different wavelength, variations occur when the visible light passes through the optical member **58**. Accordingly, the various light axes of the optical member **58** are set to have appropriate angles to compensate for colors included in the external light. This allows the optical member **58** to efficiently suppress reflection based on the conditions of light emitted from the OLED **L1**.

For illustrative purposes, an exemplary optical member **58** that is arranged to emit light generated from the OLED **L1** with a minimum loss of blue light will now be discussed. Such an embodiment of the optical member **58** can be appropriate when luminance of blue light emitted from the OLED **L1** is relatively low.

In general, the various colors or wavelengths of visible light will not behave substantially differently when passing through the optical member **58**. Thus, the discussion of the behavior of blue light as an example can be generally illustrative of the embodiments. However, slight variations for the different wavelengths of light may be exhibited. For example, transmittance of the different wavelengths may vary when passing through the optical member **58**.

Reference will now be made to FIG. 3 and FIG. 4 to describe the inbound path of light transmitted into the optical member **58** from outside. External light initially includes a mixture of phases. However, most of the inbound light pass-

ing through the optical member 58 is absorbed or extinguished. Therefore, the OLED display 100 can efficiently suppress reflection of the external light and thereby improving visibility of the display.

As shown in FIG. 3, external inbound light passes through the second polarizing plate 581. As it passes through the second polarizing plate 581, the light is linearly polarized along the polarizing axis direction of the polarizing plate 581.

This linearly-polarized light then passes through the first phase delay plate 582. The first phase delay plate is the $\frac{1}{2}$ wavelength plate. Relative to the second polarizing plate 581, the light axis of the first phase delay plate 582 is rotated by about 45 degrees. The first phase delay plate 582 also maintains the linearly-polarized state of the light passing through. The axis of light passing through the first phase delay plate 582 is turned by about 22.5 degrees from the polarizing axis of the second polarizing plate 581. That is, the angle of intersection between the light axis of the first phase delay plate 582 and the polarizing axis of the second polarizing plate 581 is about 22.5 degrees.

The inbound light next passes through the second phase delay plate 583. The second phase delay plate 583 is the $\frac{1}{4}$ wavelength plate. Relative to the second polarizing plate 581, the light axis of the second phase delay plate 583 is turned by about 45 degrees. Thus, the angle of intersection of the second phase delay plate 583 and the polarizing axis of the second polarizing plate 581 is about 45 degrees.

Since the light was rotated by about 45 degrees and was linearly-polarized after passing through the first phase delay plate 582, the inbound light is substantially equivalent to the light axis direction of the second phase delay plate 583. Accordingly, this light can pass through the second phase delay plate 583 without substantial loss. Here, the substantial equivalence implies that the visible light has several wavelengths for respective colors, and therefore, light axis directions of the entire light passed through the first phase delay plate 582 are not completely equivalent to each other.

The light that has passed through the second phase delay plate 583 is now rotated 45 degrees and is linearly polarized. Some of this light next passes through the third phase delay plate 584. Relative to the polarizing axis of the second polarizing plate 581, the light axis of the third phase delay plate 584 is turned by about 90 degrees. That is, the angle of intersection between the light axis of the third phase delay plate 584 and the polarizing axis of the second polarizing plate 581 is now about 90 degrees.

Since the angle of intersection between the axis direction of the 45-degree rotated and linearly-polarized light and the light axis direction of the third phase delay plate 584 is about 45 degrees, the light passing through the third phase delay plate 584 is circularly polarized. However, this light is also linearly-polarized along the polarizing axis direction of the first polarizing plate 585.

Light that passes through the first polarizing plate 585 is light that matches the polarizing axis of the first polarizing plate 585. But, light that does not match the polarizing axis of the first polarizing plate 585 is absorbed. Thus, some of the circularly-polarized light may pass through the first polarizing plate 585, but most of the circularly-polarized light is absorbed in the first polarizing plate 585 and extinguished. This feature suppresses much of the reflection of external light.

The light that is linearly-polarized and passing through the first polarizing plate 585 may next pass through the DBEF 586 without substantial loss. This light is reflected to electrodes 544 and 546 of the OLED L1 after passing through the fourth phase delay plate 587. In addition, the light can be

reflected to other metal wires. This light path will be further described later with reference to FIG. 5 and FIG. 6 since it is essentially the same light path as outbound light from the OLED L1 to the outside.

The path for outbound light emitted from the organic emission layer 545 to the outside will now be described with reference to FIG. 5 and FIG. 6. Initially, light emitted from the organic emission layer 545 sequentially passes through the second electrode 546 and the fourth phase delay plate 587. At this time, the light includes a mixture of various phases.

The light that is passed through the fourth phase delay plate 587 is transmitted to the DBEF 586. The light matching the polarizing axis of the DBEF 586 passes through and is also linearly polarized. Meanwhile, light mismatching the polarizing axis of the DBEF 586 is reflected back to the fourth phase delay plate 587.

The light reflected from the DBEF 586 passes through the fourth phase delay plate 587 and may be reflected again by the electrodes 544 and 546 of the OLED L1. Accordingly, some of the light reflected from the DBEF 586 is linearly-polarized and the rest of the light is continuously re-reflected. This process may recycle several times between the DBEF 586 and the electrodes 544 and 546 of the OLED L1. Eventually, most of the light emitted from the OLED L1 is linearly polarized and passes through the DBEF 586.

The outbound light next reaches the first polarizing plate 585. As noted above, the fourth phase delay plate 587 changes the phase of the light when the light recycles between the DBEF 586 and the electrodes 544 and 546 of the OLED L1 in order to help the light more efficiently pass through the DBEF 586. Thus, the light that is passed through the DBEF 586 is linearly-polarized and can pass through the first polarizing plate 585 without substantial loss. This is because the polarizing plate of the DBEF 586 is the same configuration as that of the first polarizing plate 585.

The light next passes through the third phase delay plate 584, which is the $\frac{1}{4}$ wavelength plate. Relative to the first polarizing plate 585, the light axis of the third phase delay plate 584 is turned by about 45 degrees. Thus, the angle of intersection between the light axis of the third phase delay plate 584 and the polarizing axis of the first polarizing plate 585 is about 45 degrees. Accordingly, since the angle of intersection between the light axis direction of the light that is passed through the first polarizing plate 585 and linearly polarized and the light axis direction of the third phase delay plate 584 is 45 degrees, the linearly-polarized light is circularly polarized while passing through the third phase delay plate 584.

The light next reaches the second phase delay plate 583, which is the $\frac{1}{4}$ wavelength plate. The light axis of the second phase delay plate 583 is equivalent to the polarizing axis of the first polarizing plate 585. Therefore, the light that is circularly-polarized while passing through the third phase delay plate 584 is linearly polarized while passing through the second phase delay plate 583 as in the linearly-polarized state before passing through the third phase delay plate 584. That is, the light that is linearly polarized while passing through the first polarizing plate 585 and the light linearly polarized while passing through the second phase delay plate 583 are substantially equivalent to each other.

The light that is linearly polarized while passing through the second phase delay plate 583 passes through the first phase delay plate 582 which is the $\frac{1}{2}$ wavelength plate and rotates by 45 degrees while maintaining the linearly-polarized state. In this case, the light axis of the first phase delay plate 582 is turned by 22.5 degrees from the polarizing axis of the first polarizing plate 585. That is, the angle of intersection

between the light axis of the first phase delay plate **582** and the polarizing axis of the first polarizing plate **585** is 22.5 degrees.

In addition, the axis direction of the linearly-polarized light that is rotated by 45 degrees while passing through the first phase delay plate **582** is substantially equivalent to the polarizing axis direction of the second polarizing plate **581**. Therefore, the 45-degree rotated linearly-polarized light is passed through the second polarizing plate without any substantial loss and emitted to the outside.

By the above-described configuration, the light emitted from the OLED L1 is mostly passed through the optical member **58** without significant loss and emitted to the outside. In the case of a conventional structure in which one polarizing plate and one phase delay plate are arranged, 40% of light emitted from an OLED L1 is emitted to the outside. On the other hand, in the case of the OLED display **100** according to the first exemplary embodiment of the present invention, it is experimentally proven that 80% of the light generated from the OLED L1 is passed through the optical member **58** and efficiently emitted to the outside. Accordingly, loss of out-bound light emitted from the organic emission layer **545** to the outside can be minimized. In addition, the OLED display **100** can efficiently emit light generated from the organic emission layer **545** to the outside so that power consumption can be reduced and life-span can be increased.

A second exemplary embodiment of the present invention will now be described with reference to FIG. 7. As shown in FIG. 7, an OLED display **200** includes a first substrate **51**, a second substrate **52**, and an optical member **59**. The first and second substrates **51** and **52** are bonded to each other. The optical member **59** includes a second polarizing plate **591**, a plurality of phase delay plates **592** and **593**, a first polarizing plate **595**, and a DBEF **596**.

The DBEF **596** is disposed on an OLED L1. The first polarizing plate **595** is disposed on the DBEF **596**, and the second polarizing plate **591** is disposed on the first polarizing plate **595**.

The plurality of phase delay plates **592** and **593** are interposed between the first polarizing plate **595** and the second polarizing plate **591**. The first phase delay plate **592** is interposed between the first and second polarizing plates **595** and **591**. The second phase delay plate **593** is interposed between the first polarizing plate **595** and the first phase delay plate **592**. That is, the second phase delay plate **593** and the first phase delay plate **592** are sequentially stacked on the first polarizing plate **595**.

In an embodiment, the optical member **59** can further include an additional phase delay plate **597** disposed interposed between the DBEF **596** and the OLED L1. Hereinafter, the additional phase delay plate will be referred to as a third phase delay plate **597**. However, embodiments of the present invention are not limited to a specific number or configuration of phase delay plates. For example, the third phase delay plate **597** can be omitted as desired, for example, to reduce manufacturing costs.

The DBEF **596** and the first polarizing plate **595** have polarizing axes with the same direction. In addition, an angle of intersection between the polarizing axis of the first polarizing plate **595** and the polarizing axis of the second polarizing plate **591** is about 45°.

The first phase delay plate **592** is a ½ wavelength plate, and has a light axis turned by an angle ranging from about 10 degrees to about 20 degrees from the polarizing axis of the second polarizing plate **591**. That is, the angle of intersection between the light axis of the first phase delay plate **592** and the polarizing axis of the second polarizing plate **591** may range from about 10 degrees to 20 degrees. In addition, the angle of

intersection between the light axis of the first phase delay plate **592** and the polarizing axis of the first polarizing plate **595** may range from about 25 degrees to 35 degrees.

The second phase delay plate **593** is a ¼ wavelength plate and has a light axis that is turned by an angle ranging from about 70 degrees to 80 degrees from the polarizing axis of the second polarizing plate **591**. That is, the angle of intersection between the light axis of the second phase delay plate **593** and the polarizing axis of the second polarizing plate **591** may range from about 70 degrees to about 80 degrees. In addition, the angle of intersection between the light axis of the second phase delay plate **593** and the polarizing axis of the first polarizing plate **595** may range from about 25 degrees to 35 degrees.

The third phase delay plate **597** is a ¼ wavelength plate and has a light axis that is turned by an angle range ranging from about 40 degrees to 50 about degrees from the polarizing axis of the DBEF **596**.

With the above-described configuration, the OLED display **200** can improve visibility by effectively suppressing reflection of external light while minimizing loss of light emitted out from the organic emission layer **545**. In addition, the OLED display **200** can reduce power consumption and extend life-span by efficiently emitting light generated from the organic emission layer **545**. Thus, the display characteristics of the OLED display **200** can be improved.

The manner in which the optical member **59** of the OLED display **100** can minimize loss of light emitted out from the organic emission layer **545** while efficiently suppressing reflection of external light will now be described with reference to FIG. 8 to FIG. 11. For purposes of illustration, the optical member **59** described herein is arranged to minimize the loss of blue light in emission of light from an OLED L1. However, one skilled in the art will recognize that this is merely an exemplary description and that optical member **59** can be arranged differently.

The following example regarding blue light can be illustrative because other colors of visible light will not behave significantly differently from blue light. In other words, behavior of other colors of visible light will be substantially the same as that of the blue light when passing the optical member **59**. However, the behavior of other colors of visible light can be slightly different due to differences in wavelength. Thus, transmittance of the other colors of visible light may be decreased when passing through an exemplary optical member **59**.

An inbound light path from outside to inside through the optical member **59** will now be described with reference to FIG. 8 and FIG. 9. External light from the outside may include a mixture of phases. As light passes through the second polarizing plate **591**, the external light is linearly polarized.

Next, this linearly polarized light passes through the first phase delay plate **592** which is the ½ wavelength plate. The light is rotated by about 30 degrees while maintaining its linearly polarized state. The light axis of the first phase delay plate **592** is turned by about 15 degrees from the polarizing axis of the second polarizing plate **591**. That is, the angle of intersection between the light axis of the first phase delay plate **592** and the polarizing axis of the second polarizing plate **591** is about 15 degrees.

Next, the light passes through the second phase delay plate **593**, which is the ¼ wavelength plate. The light axis of the second phase delay plate **593** is turned by about 75 degrees from the polarizing axis of the second polarizing plate **591**. That is, the angle of intersection between the light axis of the second phase delay plate **593** and the polarizing axis of the

second polarizing plate 591 is about 75 degrees. The angle of intersection between the axis direction of the 30-degree rotated and linearly-polarized light and a light axis direction of the second phase delay plate 593 is about 45 degrees. While passing through the second phase delay plate 593, the linearly-polarized light is circularly-polarized.

Next, the light is linearly polarized along a polarizing axis direction of the first polarizing plate 595 while passing through the polarizing plate 595. The light that passes through the first polarizing plate 595 matches the polarizing axis of the first polarizing plate 595. Light that does not match the polarizing axis of the first polarizing plate 595 is absorbed or extinguished. Thus, some of the circularly-polarized light passes through the first polarizing plate 595. However, much of the circularly-polarized light is absorbed in the first polarizing plate 595 and extinguished. Since most of the circularly-polarized light is extinguished while passing through the first polarizing plate 595, the OLED display 100 effectively suppresses reflection of external light.

The light that is linearly-polarized while passing through the first polarizing plate 595 is passed through the DBEF 596 without substantial loss and may be reflected to electrodes 544 and 546 of the OLED L1 after passing through the third phase delay plate 597. In addition, the light can be reflected to other metal wires. This light path will be further described later with reference to FIG. 10 and FIG. 11 since it is essentially the same light path as outbound light from the OLED L1 to the outside.

With the above-described configuration, inbound light transmitted from outside is mostly suppressed or extinguished by the optical member 59 in the first polarizing plate 595. Therefore, the OLED display 200 can improve visibility by efficiently suppressing reflection of the external light.

An outbound light path from the organic emission layer 545 of FIG. 7 will now be described with reference to FIG. 10 and FIG. 11. Light emitted from the organic emission layer 545 sequentially passes through the second electrode 546 and the third phase delay plate 597. The light initially includes a mixture of various phases.

The light that is passed through the third phase delay plate 597 is transmitted toward the DBEF 596. The light matching the polarizing axis of the DBEF 596 passes through the third phase delay plate 597 and is also linearly polarized. Meanwhile, light that does not match the polarizing axis of the DBEF 596 is reflected back to the third phase delay plate 597.

The light reflected from the DBEF 596 passes through the third phase delay plate 597 and may be reflected again by the electrodes 544 and 546. Accordingly, some of the light reflected from the DBEF 596 is linearly polarized and the rest of the light is continuously re-reflected. This process may recycle several times between the DBEF 596 and the electrodes 544 and 546. Eventually, most of the light emitted from the OLED L1 is linearly polarized and passes through the third phase delay plate. Therefore, the fourth phase delay plate 597 effectively changes the phase of the light when the light recycles between the DBEF 596 and the electrodes 544 and 546 and can help the light more efficiently pass through the DBEF 596.

The light that is passed through the DBEF 596 and linearly-polarized is next passes through the first polarizing plate 595 without any substantial loss. This is because the polarizing plate of the DBEF 596 matches the polarization of the first polarizing plate 595.

The linearly-polarized light then passes through the second phase delay plate 593 and is elliptically polarized. The second phase delay plate 593 is the $\frac{1}{4}$ wavelength plate. The light axis of the second phase delay plate 593 is turned by about 30

degrees from the polarizing axis of the first polarizing plate 595. That is, the angle of intersection between the light axis of the second phase delay plate 593 and the polarizing axis of the first polarizing plate 595 is about 30 degrees.

Since the angle of intersection between an axis direction of the linearly-polarized light passed through the first polarizing plate 595 and a light axis direction of the second phase delay plate 593 becomes 30 degrees, the linearly-polarized light is elliptically polarized while passing through the second phase delay plate 593. The linearly-polarized light can be circularly polarized when the angle of intersection between the axis direction of the linearly-polarized light and the light axis of the second phase delay plate 593 is about 45 degrees. Therefore, the linearly-polarized light is elliptically polarized since the angle of intersection therebetween is about 30 degrees.

The light next passes through the first phase delay plate 592, which is the $\frac{1}{2}$ wavelength plate and rotates by about 15 degrees while maintaining the elliptically-polarized state of the light. The light axis of the first phase delay plate 592 is turned by about 30 degrees from the polarizing axis of the first polarizing plate 595. That is, the angle of intersection between the light axis of the first phase delay plate 592 and the polarizing axis of the first polarizing plate 595 is about 30 degrees.

In addition, the longer axis direction of the elliptically-polarized light that is rotated by 15 degrees while passing through the first phase delay plate 592 is substantially equivalent to the polarizing axis direction of the second polarizing plate 591. Therefore, most of the light is passed through the second polarizing plate 591 and emitted to the outside even though it is in the elliptically-polarized state rather than a linearly-polarized state.

With the above-described configuration, the light generated from the OLED L1 can pass through the optical member 59 and can be efficiently emitted to the outside. Therefore, the loss of light emitted to the outside from the organic emission layer 545 can be minimized. In addition, the OLED display 200 can efficiently emit light generated from the organic emission layer 545 to the outside so that power consumption can be reduced and life-span can be increased.

While this invention has been described in connection with what is presently considered to be practical exemplary embodiments, it is to be understood that the invention is not limited to the disclosed embodiments, but, on the contrary, is intended to cover various modifications and equivalent arrangements included within the spirit and scope of the appended claims.

What is claimed is:

1. An organic light emitting diode (OLED) display comprising:

an OLED formed by sequentially stacking a first electrode, an organic emission layer, and a second electrode; a dual brightness enhancement film (DBEF) formed on the OLED;

a first polarizing plate formed on the DBEF;

a second polarizing plate formed on the first polarizing plate; and

a plurality of phase delay plates formed between the first polarizing plate and the second polarizing plate.

2. The OLED display of claim 1, wherein the first polarizing plate and the DBEF have the same polarizing axis.

3. The OLED display of claim 2, wherein an angle of intersection between the polarizing axis of the first polarizing plate and a polarizing axis of the second polarizing plate is about 45 degrees.

4. The OLED display of claim 3, wherein the plurality of phase delay plates comprise a first phase delay plate which is

13

a $\frac{1}{2}$ wavelength plate interposed between the first polarizing plate and the second polarizing plate, a second phase delay plate which is a $\frac{1}{4}$ wavelength plate interposed between the first polarizing plate and the first phase delay plate, and a third phase delay plate which is a $\frac{1}{4}$ wavelength plate interposed between the first polarizing plate and the second phase delay plate.

5. The OLED display of claim 4, wherein an angle of intersection between the polarizing axis of the second polarizing plate and a light axis of the first phase delay plate may range from about 17.5 degrees to 27.5 degrees, and an angle of intersection between the polarizing axis of the first polarizing plate and the light axis of the first phase delay plate is within the range of 17.5 degrees to 27.5 degrees.

6. The OLED display of claim 5, wherein an angle of intersection between the polarizing axis of the second polarizing plate and the light axis of the second phase delay plate may range from about 40 degrees to 50 degrees, and an angle of intersection between the polarizing axis of the first polarizing plate and the light axis of the second phase delay plate may range from about 0 degrees to 5 degrees.

7. The OLED display of claim 6, wherein an angle of intersection between the polarizing axis of the second polarizing plate and a light axis of the third phase delay plate may range from about 85 degrees to 90 degrees, and an angle of intersection between the polarizing axis of the first polarizing plate and the light axis of the third phase delay plate may range from about 40 degrees to 50 degrees.

8. The OLED display of claim 7, wherein an angle of intersection between the light axis of the second phase delay plate and the light axis of the third phase delay plate is 45 degrees.

9. The OLED display of claim 3, wherein the plurality of phase delay plates comprise a first phase delay plate which is a $\frac{1}{2}$ wavelength plate interposed between the first polarizing plate, and the second polarizing plate and a second phase delay plate which is a $\frac{1}{4}$ wavelength plate interposed between the first polarizing plate and the first phase delay plate.

14

10. The OLED display of claim 9, wherein an angle of intersection between the polarizing axis of the second polarizing plate and the light axis of the first phase delay plate may range from about 10 degrees to 20 degrees, and an angle of intersection between the polarizing axis of the first polarizing plate and the light axis of the first phase delay plate may range from about 25 degrees to 35 degrees.

11. The OLED display of claim 10, wherein an angle of intersection between the polarizing axis of the second polarizing plate and the light axis of the second phase delay plate may range from about 70 degrees to 80 degrees, and an angle of intersection between the polarizing axis of the first polarizing plate and the light axis of the second phase delay plate may range from about 25 degrees to 35 degrees.

12. The OLED display of claim 1, further comprising an additional phase delay plate interposed between the OLED and the DBEF.

13. The OLED display of claim 12, wherein an angle of intersection between a light axis of the additional phase delay plate and the polarizing axis of the DBEF may range from about 40 degrees to 50 degrees.

14. The OLED display of claim 4, further comprising an additional phase delay plate interposed between the OLED and the DBEF.

15. The OLED display of claim 14, wherein an angle of intersection between a light axis of the additional phase delay plate and the polarizing axis of the DBEF may range from about 40 degrees to 50 degrees.

16. The OLED display of claim 9, further comprising an additional phase delay plate interposed between the OLED and the DBEF.

17. The OLED display of claim 16, wherein an angle of intersection between a light axis of the additional phase delay plate and the polarizing axis of the DBEF may range from about 40 degrees to 50 degrees.

* * * * *

专利名称(译)	有机发光二极管显示器		
公开(公告)号	US8148894	公开(公告)日	2012-04-03
申请号	US12/536315	申请日	2009-08-05
[标]申请(专利权)人(译)	三星显示有限公司		
申请(专利权)人(译)	三星移动显示器有限公司.		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	PARK SOON RYONG JUNG WOO SUK JEONG HEE SEONG JEON HEE CHUL JEONG CHUL WOO KIM JAE YONG KIM EUN AH KWAK NOH MIN LEE JOO HWA		
发明人	PARK, SOON-RYONG JUNG, WOO-SUK JEONG, HEE-SEONG JEON, HEE-CHUL JEONG, CHUL-WOO KIM, JAE-YONG KIM, EUN-AH KWAK, NOH-MIN LEE, JOO-HWA		
IPC分类号	H05B33/12		
CPC分类号	H01L51/5281 G02B27/281		
审查员(译)	帕特尔NIMESHKUMAR		
优先权	1020080083913 2008-08-27 KR		
其他公开文献	US20100156282A1		
外部链接	Espacenet USPTO		

摘要(译)

OLED显示器技术领域本发明涉及OLED显示器。在一些实施例中，OLED显示器可以采用线性偏振，圆形或椭圆偏振和相位延迟的组合，以便抑制来自外部光的反射，同时最小化来自OLED显示器的发射光的损失。例如，显示器中的OLED包括具有第一电极，有机发光层和第二电极的堆叠，形成在OLED上的DBEF，形成在DBEF上的第一偏振板，形成在第一偏振板上的第二偏振板偏振片和在第一偏振片和第二偏振片之间形成的多个相位延迟板。

