




US 20060022915A1

(19) **United States**(12) **Patent Application Publication** (10) **Pub. No.: US 2006/0022915 A1**
(43) **Pub. Date: Feb. 2, 2006**(54) **METHOD AND APPARATUS FOR POWER
LEVEL CONTROL AND/OR CONTRAST
CONTROL IN A DISPLAY DEVICE****Publication Classification**(51) **Int. Cl.**
G09G 3/30 (2006.01)
(52) **U.S. Cl.** **345/77**(76) **Inventors: Sebastien Weitbruch, Niedereschach
(DE); Dennis Cota, Villingen (DE);
Philippe Le Roy, Betton (FR)**Correspondence Address:
THOMSON LICENSING INC.
PATENT OPERATIONS
PO BOX 5312
PRINCETON, NJ 08543-5312 (US)(57) **ABSTRACT**

The present invention relates to a method and an apparatus for controlling the power level and/or the contrast in a display device having a plurality of luminous elements corresponding to the colour components of the pixels of a picture, wherein the luminance generated by each of said luminous element is based on the intensity of the signal supplied to the luminous element and the power level and/or contrast for each picture is controlled by adjusting the intensity of the signal to be supplied to each luminous element. The invention is applicable to organic light emitting displays (OLED). According to the invention, the intensity of the signal to be supplied to each luminous element is based on reference signals and the adjustment of the signal intensity is made by adjusting the level of the reference signals.

(21) **Appl. No.: 11/184,214**(22) **Filed: Jul. 19, 2005**(30) **Foreign Application Priority Data**

Jul. 29, 2004 (EP) 04291945.6






FIGURE 1




FIGURE 2




FIGURE 3




FIGURE 4




FIGURE 5

METHOD AND APPARATUS FOR POWER LEVEL CONTROL AND/OR CONTRAST CONTROL IN A DISPLAY DEVICE

[0001] The present invention relates to a method and an apparatus for controlling the power level and/or the contrast in a display device having a plurality of luminous elements corresponding to the colour components of the pixels of a picture, wherein the luminance generated by each of said luminous element is based on the intensity of the signal supplied to the luminous element.

[0002] More specifically, the invention is closely related to organic light emitting displays (OLED).

BACKGROUND

[0003] A high peak-white luminance is always required to achieve a good contrast ratio in every display technologies even with ambient light conditions and, for every kind of active displays, more peak white luminance corresponds to a higher power that flows in the electronic of the display. Therefore, if no specific management is done, the enhancement of the peak luminance for a given electronic efficacy will introduce an increase of the power consumption.

[0004] The main idea behind every kind of power management concept associated with peak white enhancement is based on the variation of the peak-luminance depending on the picture content in order to stabilize the power consumption to a specified value. This concept is shown in **FIG. 1**. When the picture load is low, the peak luminance is high and when the picture load is high, the peak luminance is low. The concept described on this figure enables to avoid any overloading of the power supply of the display panel as well as a maximum contrast for a given picture.

[0005] Such a concept suits very well to the human visual system. When the picture load is low, the contrast ratio is high and when the picture is high, the human eye is dazzled and is less sensitive to contrast ratio. So, for a full-white picture, the contrast ratio can be lower than for a peak-white picture.

[0006] In the case of cathode Ray Tubes (CRTs), the power management is based on a so called ABL function (Average Beam-current Limiter), which is implemented by analog means and which decreases video gain as a function of the average luminance of the pictures.

[0007] In the case of an organic light-emitting diode display, also called. OLED display, the luminance as well as the power consumption is directly linked to the current that flows through each cell. Currently, there is no power level control means for stabilizing the power consumption to a target value.

[0008] In the other hand, in such a display device, the contrast is adjusted by a video scaler acting on the video signal. If the video signal is coded on 8 bits and if the contrast should be reduced by 50%, the video signal is rescaled leading to a video signal with only a 7 bit resolution. So, there is a loss of video resolution.

INVENTION

[0009] The present invention proposes a new method and apparatus for controlling the power level and/or the contrast in display devices having a plurality of luminous elements,

wherein the luminance generated by each of said luminous element is based on the intensity of the signal supplied to the luminous element and the power level and/or contrast for each picture is controlled by adjusting the intensity of the signal to be supplied to each luminous element.

[0010] The basic idea of this invention is to supply the luminous elements of the display device with a signal whose intensity is based on reference signals and to modify the level of these reference signals for adjusting the intensity of the signals supplied to the luminous elements.

[0011] So, the invention relates to a method for controlling the power level and/or the contrast in a display device having a plurality of luminous elements corresponding to the colour components of the pixels of a picture, wherein the luminance generated by each of said luminous elements is based on the intensity of the signal supplied to the luminous element and the power level and/or contrast for each picture is controlled by adjusting the intensity of the signal to be supplied to each luminous element, characterized in that the intensity of the signal to be supplied to each luminous element is based on reference signals and in that the adjustment of the signal intensity is made by adjusting the level of the reference signals.

[0012] By this method, the resolution of the video signal supplied to the luminous elements is not modified.

[0013] For controlling the power level, the method further comprises the two following steps:

[0014] calculating, for each picture received by the display device, a parameter representative of the power needed by the display device for displaying said picture; this parameter is for example the average power level; and

[0015] adjusting the intensity of the signal to be supplied to each luminous element in order that the power needed by the display device for displaying said picture is lower than a target value.

[0016] For controlling the contrast of the pictures displayed by the display device, the method further comprises the following steps:

[0017] calculating an adjustment factor to be applied to the intensity of the picture signal supplied to the luminous elements in order that the resulting contrast is equal to a required contrast, and

[0018] applying said adjustment factor to said reference signals.

[0019] In a preferred embodiment, a non linear transformation is applied to reference signals, before adjustment of the signal intensity, in order to increase the amplitude of the low-amplitude reference signals. To compensate this transformation, the inverse transformation is applied to the picture signal.

[0020] The invention concerns also an apparatus for controlling the power level and/or the contrast in a display device having a plurality of luminous elements corresponding to the colour components of the pixels of a picture, wherein the luminance generated by each of said luminous elements is based on the intensity of the signal supplied to the luminous element and the power level and/or contrast for each picture is controlled by adjusting the intensity of the signal to be supplied to each luminous element, character-

ized in that the intensity of the signal to be supplied to each luminous element is based on reference signals and in that it comprises adjustment means for modifying the signal intensity by adjusting the level of the reference signals.

[0021] For controlling the power level, the apparatus further comprises calculation means for calculating, for each picture received by the display device, a parameter representative of the power needed by the display device for displaying said picture, and in that the adjustment means adjusts the level of the reference signals in order that the power needed by the display device for displaying each picture is lower than a target value. The calculation means calculates for example, for each picture received by the display device, the average power level of said picture.

[0022] For controlling the contrast of the pictures displayed by the display device, the apparatus further comprises calculation means for calculating an adjustment factor to be applied to the intensity of the signal supplied to the luminous elements in order that the resulting contrast is equal to a required contrast, and in that the adjustment means applies said adjustment factor to said reference signals.

[0023] For these two applications, the apparatus comprises a frame memory for storing a picture before transmitting it to the display device.

[0024] In a preferred embodiment, the adjustment means of the apparatus comprises means for applying a non linear transformation to reference signals in order to increase the amplitude of the low-amplitude reference signals and the apparatus comprises means for applying the inverse transformation to the picture signal.

[0025] Lastly, the invention concerns also a display device comprising

[0026] a plurality of organic light emitting diodes,

[0027] signal processing means for processing the picture signal received by the display device,

[0028] driving means for driving said plurality of organic light emitting diodes according to the signal processed by the signal processing means,

[0029] reference signalling means for outputting reference signals to the driving means, and

[0030] an apparatus as defined above which is integrated to the signal processing means.

BRIEF DESCRIPTION OF THE DRAWINGS

[0031] Exemplary embodiments of the invention are illustrated in the drawings and in more detail in the following description.

[0032] In the figures:

[0033] FIG. 1 shows the variation of the peak luminance versus the picture load in a display device;

[0034] FIG. 2 shows the structure of the control electronic in a OLED display;

[0035] FIG. 3 shows the variations of reference voltages according to picture load in a basic embodiment of the invention;

[0036] FIG. 4 shows the variations of reference voltages according to picture load in an improved embodiment of the invention; and

[0037] FIG. 5 shows the structure of the control electronic in a OLED display used for implementing the method of the invention;

DESCRIPTION OF PREFERRED EMBODIMENTS

[0038] The invention is described in relation to a OLED display with an active matrix where each luminous element of the display is controlled via an association of several thin-film transistors (TFTs). The general structure of the electronic for controlling the OLED elements is illustrated by FIG. 2. It comprises:

[0039] an active matrix 1 containing, for each OLED element, an association of several thin-film transistors with a capacitor connected to the OLED material of the luminous element; the capacitor acts as a memory component that stores the value of the luminous element during a certain part of the frame; the thin-film transistors act as switches enabling the selection of the luminous element, the storage of the capacitor and the lighting of the luminous element; in the present structure, the value stored in the capacitor determines the luminance produced by the luminous element;

[0040] at least one row driver 2 that selects line by line the luminous elements of the display in order to refresh their content,

[0041] at least one column driver 3 that delivers the value or content to be stored in each luminous element of the current selected line; this component receives the video information for each luminous element;

[0042] a digital processing and driving unit 4 that applies required video and signal processing steps to the video input signal and that delivers the required signals to the row and column drivers.

[0043] Actually, there are two ways for driving the OLED elements:

[0044] in a current driven concept, the digital video information sent by the digital processing and driving unit 4 is converted by the column driver 3 in a current amplitude that is supplied to the luminous element via the active matrix 1;

[0045] in a voltage driven concept, the digital video information sent by the digital processing and driving unit 4 is converted by the column driver 3 in a voltage amplitude that is supplied to the luminous element via the active matrix 1; but, even so, it should be noticed that an OLED element is a current driven so that each voltage based driving unit is based on a voltage to current converter to achieve appropriate lighting.

[0046] The column driver 3 represents, with the digital processing and driving unit 4, the real active part of the electronic and can be considered as a high-level digital to analog converter. The row driver 2 has a quite simple function since it only has to apply a selection line by line. It is more or less a shift register.

[0047] The functioning of said electronic is the following: the input video signal is forwarded to the digital processing

and driving unit 4 that delivers, after internal processing, a timing signal for row selection to the row driver 2 synchronized with the data sent to the column driver 3. Depending on the used column driver 3, the data are sent either in a parallel way or in a serial way. Additionally, the column driver 3 is equipped with a reference signaling device 5 for delivering reference signals. More precisely, this device delivers a set of reference voltages in case of voltage driven circuitry or a set of reference currents in case of current driven circuitry, the highest reference being used for the highest gray level (white) and the lowest for the smallest gray level. These reference signals are used by the column driver 3 for generating the signal to be supplied to the OLED element.

[0048] An example of reference signals is given below for a voltage driven circuitry. Eight reference voltages named V_0 to V_7 are used

[0049] $V_0=3V$

[0050] $V_1=2,6V$

[0051] $V_2=2,2V$

[0052] $V_3=1,4V$

[0053] $V_4=0,6V$

[0054] $V_5=0,3V$

[0055] $V_6=0,16V$

[0056] $V_7=0V$ The different gray levels can be defined as given by the following table. The whole table is given by the annex 1.

gray level	gray level voltage	Gray level voltage
0	V_7	0.00 V
1	$V_7 + (V_6 - V_7) \times 9/1175$	0.001 V
2	$V_7 + (V_6 - V_7) \times 32/1175$	0.005 V
3	$V_7 + (V_6 - V_7) \times 76/1175$	0.011 V
4	$V_7 + (V_6 - V_7) \times 141/1175$	0.02 V
5	$V_7 + (V_6 - V_7) \times 224/1175$	0.032 V
6	$V_7 + (V_6 - V_7) \times 321/1175$	0.045 V
7	$V_7 + (V_6 - V_7) \times 425/1175$	0.06 V
8	$V_7 + (V_6 - V_7) \times 529/1175$	0.074 V
9	$V_7 + (V_6 - V_7) \times 630/1175$	0.089 V
10	$V_7 + (V_6 - V_7) \times 727/1175$	0.102 V
11	$V_7 + (V_6 - V_7) \times 820/1175$	0.115 V
12	$V_7 + (V_6 - V_7) \times 910/1175$	0.128 V
13	$V_7 + (V_6 - V_7) \times 998/1175$	0.14 V
14	$V_7 + (V_6 - V_7) \times 1086/1175$	0.153 V
15	V_6	0.165 V
16	$V_6 + (V_5 - V_6) \times 89/1097$	0.176 V
.	.	.
.	.	.
.	.	.
252	$V_1 + (V_0 - V_1) \times 2549/3029$	2.937 V
253	$V_1 + (V_0 - V_1) \times 2694/3029$	2.956 V
254	$V_1 + (V_0 - V_1) \times 2851/3029$	2.977 V
255	V_0	3.00 V

[0057] Of course, these voltage levels are converted into current before being supplied to the OLED elements. For deducing a luminance value from these voltages, it will be assumed in the rest of the present specification that a 3V voltage applied to an OLED element corresponds to a 400 cd/m luminance and that it represents the maximal lumi-

nance that can be displayed by the screen of the display device. This value is given as an example.

[0058] For a $\frac{4}{3}$ screen with a 6.5" (=16.25 cm) diagonal (size=13 cm×9.75 cm) and an efficacy for the OLED material around 14 Cd/A, the surface of the screen is 13×9.75=126.75 cm² and the current density is 40000/14000=2.86 mA/cm². So, the total current needed by the panel is 126.75×2.86=362.1 mA.

[0059] This current value can be considered as too high. For example, it is sought a maximum current value of 80 mA.

[0060] According to the invention, the luminance of the display panel is adjusted in order that the current value necessary for displaying the picture is lower than a maximum current value.

[0061] The power of the incoming picture is first evaluated and the luminance of the panel is then adjusted in order to limit the power consumption of the panel to the maximum current value.

[0062] A first step of the inventive method consists in evaluating the power of the incoming picture to decide which luminance should be used for a white level. The computation of the picture power is done by computing the Average Power Level (APL) of the picture through the following function:

$$APL(I(x, y)) = \frac{1}{C \times L} \cdot \sum_{x,y} I(x, y)$$

[0063] where $I(x,y)$ represents the video level of the pixel with coordinates x, y in the picture, C is the number of elements columns of the screen and L is the number of elements lines of the screen.

[0064] In the present specification, the APL value of a picture will be expressed as a percentage of white surface in the picture for clarity and simplicity reasons.

[0065] In a second step, the maximal luminance of the screen is determined for different percentages of white surface as shown in the following table. In the case of a maximum current value of 80 mA, the luminance of a full white image (100% white surface) for the above-mentioned $\frac{4}{3}$ screen is:

$$80 \cdot \frac{40 \cdot 10^{-3}}{126.75 \cdot 10^{-4}} = 88.363 \text{ cd/m}^2.$$

Surface (white)	Luminance (Cd/m2)	Power (mA)
100.00%	88.363 Cd/m2	80.00 mA
97.50%	90.629 Cd/m2	80.00 mA
95.00%	93.014 Cd/m2	80.00 mA
92.50%	95.527 Cd/m2	80.00 mA
90.00%	98.181 Cd/m2	80.00 mA
87.50%	100.986 Cd/m2	80.00 mA
85.00%	103.956 Cd/m2	80.00 mA

-continued

Surface (white)	Luminance (Cd/m2)	Power (mA)	Surface (white)	V0	Luminance (Cd/m2)
82.50%	107.107 Cd/m2	80.00 mA	100.00%	1.41 V	88.363 Cd/m2
80.00%	110.454 Cd/m2	80.00 mA	97.50%	1.43 V	90.629 Cd/m2
77.50%	114.017 Cd/m2	80.00 mA	95.00%	1.45 V	93.014 Cd/m2
75.00%	117.817 Cd/m2	80.00 mA	92.50%	1.47 V	95.527 Cd/m2
72.50%	121.88 Cd/m2	80.00 mA	90.00%	1.49 V	98.181 Cd/m2
70.00%	126.233 Cd/m2	80.00 mA	87.50%	1.51 V	100.986 Cd/m2
67.50%	130.908 Cd/m2	80.00 mA	85.00%	1.53 V	103.956 Cd/m2
65.00%	135.943 Cd/m2	80.00 mA	82.50%	1.55 V	107.107 Cd/m2
62.50%	141.381 Cd/m2	80.00 mA	80.00%	1.58 V	110.454 Cd/m2
60.00%	147.272 Cd/m2	80.00 mA	77.50%	1.6 V	114.017 Cd/m2
57.50%	153.675 Cd/m2	80.00 mA	75.00%	1.63 V	117.817 Cd/m2
55.00%	160.66 Cd/m2	80.00 mA	72.50%	1.66 V	121.88 Cd/m2
52.50%	168.31 Cd/m2	80.00 mA	70.00%	1.69 V	126.233 Cd/m2
50.00%	176.726 Cd/m2	80.00 mA	67.50%	1.72 V	130.908 Cd/m2
47.50%	186.027 Cd/m2	80.00 mA	65.00%	1.75 V	135.943 Cd/m2
45.00%	196.362 Cd/m2	80.00 mA	62.50%	1.78 V	141.381 Cd/m2
42.50%	207.913 Cd/m2	80.00 mA	60.00%	1.82 V	147.272 Cd/m2
40.00%	220.907 Cd/m2	80.00 mA	57.50%	1.86 V	153.675 Cd/m2
37.50%	235.634 Cd/m2	80.00 mA	55.00%	1.9 V	160.66 Cd/m2
35.00%	252.465 Cd/m2	80.00 mA	52.50%	1.95 V	168.31 Cd/m2
32.50%	271.886 Cd/m2	80.00 mA	50.00%	2.0 V	176.726 Cd/m2
30.00%	294.543 Cd/m2	80.00 mA	47.50%	2.05 V	186.027 Cd/m2
27.50%	321.32 Cd/m2	80.00 mA	45.00%	2.1 V	196.362 Cd/m2
25.00%	353.452 Cd/m2	80.00 mA	42.50%	2.16 V	207.913 Cd/m2
22.50%	392.724 Cd/m2	80.00 mA	40.00%	2.23 V	220.907 Cd/m2
20.00%	400.00 Cd/m2	72.429 mA	37.50%	2.3 V	235.634 Cd/m2
17.50%	400.00 Cd/m2	63.375 mA	35.00%	2.38 V	252.465 Cd/m2
15.00%	400.00 Cd/m2	54.321 mA	32.50%	2.47 V	271.886 Cd/m2
12.50%	400.00 Cd/m2	45.268 mA	30.00%	2.58 V	294.543 Cd/m2
10.00%	400.00 Cd/m2	36.214 mA	27.50%	2.69 V	321.32 Cd/m2
7.50%	400.00 Cd/m2	27.161 mA	25.00%	2.82 V	353.452 Cd/m2
5.00%	400.00 Cd/m2	18.107 mA	22.50%	2.97 V	392.724 Cd/m2
2.50%	400.00 Cd/m2	9.054 mA	20.00%	3.0 V	400.00 Cd/m2
			17.50%	3.0 V	400.00 Cd/m2
			15.00%	3.0 V	400.00 Cd/m2
			12.50%	3.0 V	400.00 Cd/m2
			10.00%	3.0 V	400.00 Cd/m2
			7.50%	3.0 V	400.00 Cd/m2
			5.00%	3.0 V	400.00 Cd/m2
			2.50%	3.0 V	400.00 Cd/m2

[0066] As the luminance is in this example limited to 400 cd/m², the power consumption for the picture with a white surface percentage inferior to 22% is inferior to 80 mA. The maximal contrast ratio is obtained for a 22% white surface percentage and is equal to 4.5.

[0067] According to an important characteristics of the invention, the luminance of the screen is adjusted by modifying the value of the reference levels V_n , $n \in [0, \dots, 7]$ defined above. The luminance LUM of the screen can be approximated by a quadratic function of the applied voltage V:

$$LUM(x; y) = 44 \times (V(x; y))^2,$$

[0068] This formula is given as an example. The following table gives the different voltage values for the reference voltage V0:

[0069] The other reference levels, V1 to V7, can be adjusted in a linear way from the reference level V0. For example, the reference level V_n for a given average power level APL can then be computed as follows:

$$V_n(APL) = \frac{V0(APL) \times V_n(0\%)}{V0(0\%)}$$

[0070] The following table gives the voltage values of all the reference levels V0 to V7 for different APL:

Surface (white)	V0	V1	V2	V3	V4	V5	V6	V7
100.00%	1.41 V	1.22 V	1.03 V	0.66 V	0.28 V	0.14 V	0.08 V	0.0 V
97.50%	1.43 V	1.24 V	1.05 V	0.67 V	0.29 V	0.14 V	0.08 V	0.0 V
95.00%	1.45 V	1.25 V	1.06 V	0.68 V	0.29 V	0.14 V	0.08 V	0.0 V
92.50%	1.47 V	1.27 V	1.08 V	0.68 V	0.29 V	0.15 V	0.08 V	0.0 V
90.00%	1.49 V	1.29 V	1.09 V	0.69 V	0.3 V	0.15 V	0.08 V	0.0 V
87.50%	1.51 V	1.31 V	1.11 V	0.7 V	0.3 V	0.15 V	0.08 V	0.0 V

-continued

Surface (white)	V0	V1	V2	V3	V4	V5	V6	V7
85.00%	1.53 V	1.33 V	1.12 V	0.71 V	0.31 V	0.15 V	0.08 V	0.0 V
82.50%	1.55 V	1.35 V	1.14 V	0.72 V	0.31 V	0.16 V	0.08 V	0.0 V
80.00%	1.58 V	1.37 V	1.16 V	0.74 V	0.32 V	0.16 V	0.08 V	0.0 V
77.50%	1.6 V	1.39 V	1.18 V	0.75 V	0.32 V	0.16 V	0.09 V	0.0 V
75.00%	1.63 V	1.41 V	1.19 V	0.76 V	0.33 V	0.16 V	0.09 V	0.0 V
72.50%	1.66 V	1.44 V	1.21 V	0.77 V	0.33 V	0.17 V	0.09 V	0.0 V
70.00%	1.69 V	1.46 V	1.24 V	0.79 V	0.34 V	0.17 V	0.09 V	0.0 V
67.50%	1.72 V	1.49 V	1.26 V	0.8 V	0.34 V	0.17 V	0.09 V	0.0 V
65.00%	1.75 V	1.52 V	1.28 V	0.82 V	0.35 V	0.17 V	0.09 V	0.0 V
62.50%	1.78 V	1.55 V	1.31 V	0.83 V	0.36 V	0.18 V	0.1 V	0.0 V
60.00%	1.82 V	1.58 V	1.34 V	0.85 V	0.36 V	0.18 V	0.1 V	0.0 V
57.50%	1.86 V	1.61 V	1.36 V	0.87 V	0.37 V	0.19 V	0.1 V	0.0 V
55.00%	1.9 V	1.65 V	1.39 V	0.89 V	0.38 V	0.19 V	0.1 V	0.0 V
52.50%	1.95 V	1.69 V	1.43 V	0.91 V	0.39 V	0.19 V	0.1 V	0.0 V
50.00%	2.0 V	1.73 V	1.46 V	0.93 V	0.4 V	0.2 V	0.11 V	0.0 V
47.50%	2.05 V	1.77 V	1.5 V	0.96 V	0.41 V	0.2 V	0.11 V	0.0 V
45.00%	2.1 V	1.82 V	1.54 V	0.98 V	0.42 V	0.21 V	0.11 V	0.0 V
42.50%	2.16 V	1.88 V	1.59 V	1.01 V	0.43 V	0.22 V	0.12 V	0.0 V
40.00%	2.23 V	1.93 V	1.64 V	1.04 V	0.45 V	0.22 V	0.12 V	0.0 V
37.50%	2.3 V	2.0 V	1.69 V	1.08 V	0.46 V	0.23 V	0.12 V	0.0 V
35.00%	2.38 V	2.07 V	1.75 V	1.11 V	0.48 V	0.24 V	0.13 V	0.0 V
32.50%	2.47 V	2.14 V	1.81 V	1.15 V	0.49 V	0.25 V	0.13 V	0.0 V
30.00%	2.58 V	2.23 V	1.89 V	1.2 V	0.52 V	0.26 V	0.14 V	0.0 V
27.50%	2.69 V	2.33 V	1.97 V	1.26 V	0.54 V	0.27 V	0.14 V	0.0 V
25.00%	2.82 V	2.45 V	2.07 V	1.32 V	0.56 V	0.28 V	0.15 V	0.0 V
22.50%	2.97 V	2.58 V	2.18 V	1.39 V	0.59 V	0.3 V	0.16 V	0.0 V
20.00%	3.0 V	2.6 V	2.2 V	1.4 V	0.6 V	0.3 V	0.16 V	0.0 V
17.50%	3.0 V	2.6 V	2.2 V	1.4 V	0.6 V	0.3 V	0.16 V	0.0 V
15.00%	3.0 V	2.6 V	2.2 V	1.4 V	0.6 V	0.3 V	0.16 V	0.0 V
12.50%	3.0 V	2.6 V	2.2 V	1.4 V	0.6 V	0.3 V	0.16 V	0.0 V
10.00%	3.0 V	2.6 V	2.2 V	1.4 V	0.6 V	0.3 V	0.16 V	0.0 V
7.50%	3.0 V	2.6 V	2.2 V	1.4 V	0.6 V	0.3 V	0.16 V	0.0 V
5.00%	3.0 V	2.6 V	2.2 V	1.4 V	0.6 V	0.3 V	0.16 V	0.0 V
2.50%	3.0 V	2.6 V	2.2 V	1.4 V	0.6 V	0.3 V	0.16 V	0.0 V

[0071] FIG. 3 shows curves illustrating this table and showing the variations of the reference voltages for the percentages of white surface 5%, 10%, 30%, 40%, 50%, 60%, 70%, 80%, 90% and 100%.

[0072] A problem can appear when the voltage references related to the lowest gray levels are very low, which is the case in the above table for the reference voltages V5 and V6 when the picture load is high. Actually, in a voltage driven system, if the voltage is too low, the error (coming from the mismatch between neighbouring luminous elements) becomes higher than the required precision and the information is lost. In a current driven system, the problem is different. In such a system, the lower the current is, the longer it takes to load the capacitance of the luminous

element. So, if the required current is too low, the writing time of the luminous element will be too long for a video application.

[0073] In the present example, the voltage values below 0.16V (bold values in the above table) can create a precision error. So, as an improvement, it is proposed to modify the reference voltages V1 to V7 in a non-linear way according to the reference level V0. The voltage values for the reference voltage V0 is kept constant while the other ones are modified by a non-linear mathematical transformation $f(x, y, z)$ as followed:

$$Vn(APL)=f(V0(APL); Vn(0\%); V0(0\%)).$$

[0074] An example of the result of such a transformation is given in the next table:

Surface (white)	V0	V1	V2	V3	V4	V5	V6	V7
100.00%	1.41 V	1.35 V	1.26 V	0.97 V	0.5 V	0.27 V	0.16 V	0.0 V
97.50%	1.44 V	1.38 V	1.28 V	0.97 V	0.5 V	0.27 V	0.16 V	0.0 V
95.00%	1.47 V	1.4 V	1.3 V	0.98 V	0.5 V	0.27 V	0.16 V	0.0 V
92.50%	1.51 V	1.43 V	1.32 V	0.99 V	0.5 V	0.27 V	0.16 V	0.0 V
90.00%	1.54 V	1.45 V	1.34 V	1.0 V	0.51 V	0.27 V	0.16 V	0.0 V
87.50%	1.57 V	1.48 V	1.36 V	1.01 V	0.51 V	0.27 V	0.16 V	0.0 V
85.00%	1.61 V	1.51 V	1.38 V	1.02 V	0.51 V	0.27 V	0.16 V	0.0 V
82.50%	1.65 V	1.54 V	1.4 V	1.03 V	0.51 V	0.27 V	0.16 V	0.0 V
80.00%	1.68 V	1.57 V	1.42 V	1.04 V	0.51 V	0.27 V	0.16 V	0.0 V
77.50%	1.72 V	1.6 V	1.45 V	1.05 V	0.52 V	0.27 V	0.16 V	0.0 V
75.00%	1.76 V	1.63 V	1.47 V	1.06 V	0.52 V	0.28 V	0.16 V	0.0 V
72.50%	1.81 V	1.66 V	1.5 V	1.07 V	0.52 V	0.28 V	0.16 V	0.0 V

-continued

Surface (white)	V0	V1	V2	V3	V4	V5	V6	V7
70.00%	1.85 V	1.7 V	1.52 V	1.09 V	0.53 V	0.28 V	0.16 V	0.0 V
67.50%	1.9 V	1.73 V	1.55 V	1.1 V	0.53 V	0.28 V	0.16 V	0.0 V
65.00%	1.94 V	1.77 V	1.58 V	1.11 V	0.53 V	0.28 V	0.16 V	0.0 V
62.50%	1.99 V	1.81 V	1.61 V	1.12 V	0.53 V	0.28 V	0.16 V	0.0 V
60.00%	2.04 V	1.85 V	1.64 V	1.14 V	0.54 V	0.28 V	0.16 V	0.0 V
57.50%	2.1 V	1.89 V	1.67 V	1.15 V	0.54 V	0.28 V	0.16 V	0.0 V
55.00%	2.15 V	1.94 V	1.7 V	1.17 V	0.55 V	0.28 V	0.16 V	0.0 V
52.50%	2.21 V	1.98 V	1.73 V	1.18 V	0.55 V	0.28 V	0.16 V	0.0 V
50.00%	2.27 V	2.03 V	1.77 V	1.2 V	0.55 V	0.29 V	0.16 V	0.0 V
47.50%	2.33 V	2.08 V	1.81 V	1.22 V	0.56 V	0.29 V	0.16 V	0.0 V
45.00%	2.4 V	2.13 V	1.85 V	1.24 V	0.56 V	0.29 V	0.16 V	0.0 V
42.50%	2.47 V	2.18 V	1.89 V	1.25 V	0.57 V	0.29 V	0.16 V	0.0 V
40.00%	2.54 V	2.24 V	1.93 V	1.27 V	0.57 V	0.29 V	0.16 V	0.0 V
37.50%	2.61 V	2.29 V	1.97 V	1.29 V	0.57 V	0.29 V	0.16 V	0.0 V
35.00%	2.68 V	2.35 V	2.01 V	1.31 V	0.58 V	0.29 V	0.16 V	0.0 V
32.50%	2.76 V	2.41 V	2.06 V	1.33 V	0.58 V	0.3 V	0.16 V	0.0 V
30.00%	2.83 V	2.47 V	2.1 V	1.35 V	0.59 V	0.3 V	0.16 V	0.0 V
27.50%	2.9 V	2.52 V	2.14 V	1.37 V	0.59 V	0.3 V	0.16 V	0.0 V
25.00%	2.96 V	2.57 V	2.18 V	1.39 V	0.6 V	0.3 V	0.16 V	0.0 V
22.50%	3.0 V	2.6 V	2.2 V	1.4 V	0.6 V	0.3 V	0.16 V	0.0 V
20.00%	3.0 V	2.6 V	2.2 V	1.4 V	0.6 V	0.3 V	0.16 V	0.0 V
17.50%	3.0 V	2.6 V	2.2 V	1.4 V	0.6 V	0.3 V	0.16 V	0.0 V
15.00%	3.0 V	2.6 V	2.2 V	1.4 V	0.6 V	0.3 V	0.16 V	0.0 V
12.50%	3.0 V	2.6 V	2.2 V	1.4 V	0.6 V	0.3 V	0.16 V	0.0 V
10.00%	3.0 V	2.6 V	2.2 V	1.4 V	0.6 V	0.3 V	0.16 V	0.0 V
7.50%	3.0 V	2.6 V	2.2 V	1.4 V	0.6 V	0.3 V	0.16 V	0.0 V
5.00%	3.0 V	2.6 V	2.2 V	1.4 V	0.6 V	0.3 V	0.16 V	0.0 V
2.50%	3.0 V	2.6 V	2.2 V	1.4 V	0.6 V	0.3 V	0.16 V	0.0 V

[0075] FIG. 4, to be compared with FIG. 3, illustrates these new variations of voltage references V0 to V7 by curves. After this transformation, there are almost no more differences for the reference voltages V6 and V7 between the different APL values.

[0076] This non linear transformation f applied to the reference voltages V1 to V7 should be compensated by an inverse transformation f^{-1} in the video signal processing chain of the device. With such transformations (f and f^{-1}), it is possible to obtain an optimized power management without introducing too much difficulties in the low level gradations (low voltages/low currents).

[0077] A circuit implementation of the digital processing and driving unit 4 to be used the power level control method of the invention is given at FIG. 5.

[0078] An input picture is forwarded to a power evaluation block 41 that performs the computation of the APL level of the input picture. The APL value is transmitted to a power management block 42. Since the result of this computation can be only made after a complete frame, the input picture should be then stored in a frame memory 43, for example a DDRAM, in order to dispose of one frame delay. This memory can be inside or outside the unit 4.

[0079] Based on this APL value, an appropriate set of reference signals Refn is chosen for instance from a Look Up Table and sent to the Reference Signaling Unit 5 via a programming bus. Advantageously, a non-linear transformation f is integrated in these signals. As indicated previously, these reference signals can be reference voltages or reference currents. This programming should occur during the vertical blanking in order not to disturb the displayed picture.

[0080] In parallel to that, a non-linear transfer function f^{-1} (it can be a mathematical function or a Look Up Table)

which is the inverse of the transformation integrated in the chosen set of reference signals Refn is chosen and is applied to the delayed picture by a block 44. The picture after processing is sent to a standard OLED processing block 45 and then to a standard OLED driving block 46 for finally driving the display with the current picture information.

[0081] The method of the invention can be used for controlling the contrast of the pictures displayed by the display device. In that case, the method consists in calculating an adjustment factor that is to be applied to the intensity of the signal supplied to the luminous elements in order to make the contrast go from a present value to a required value. This adjustment factor is then applied to the reference signals.

[0082] For example, for reducing the contrast by 50%, the reference signals are decreased from 50%.

Annexel 1

[0083]

0	V7	0.00 V
1	$V7 + (V6 - V7) \times 9/1175$	0.001 V
2	$V7 + (V6 - V7) \times 32/1175$	0.004 V
3	$V7 + (V6 - V7) \times 76/1175$	0.01 V
4	$V7 + (V6 - V7) \times 141/1175$	0.019 V
5	$V7 + (V6 - V7) \times 224/1175$	0.03 V
6	$V7 + (V6 - V7) \times 321/1175$	0.043 V
7	$V7 + (V6 - V7) \times 425/1175$	0.057 V
8	$V7 + (V6 - V7) \times 529/1175$	0.071 V
9	$V7 + (V6 - V7) \times 630/1175$	0.084 V
10	$V7 + (V6 - V7) \times 727/1175$	0.097 V
11	$V7 + (V6 - V7) \times 820/1175$	0.11 V
12	$V7 + (V6 - V7) \times 910/1175$	0.122 V
13	$V7 + (V6 - V7) \times 998/1175$	0.133 V

-continued

14	V7 + (V6 - V7) × 1086/1175	0.145 V
15	V6	0.157 V
16	V6 + (V5 - V6) × 89/1097	0.167 V
17	V6 + (V5 - V6) × 173/1097	0.177 V
18	V6 + (V5 - V6) × 250/1097	0.186 V
19	V6 + (V5 - V6) × 320/1097	0.194 V
20	V6 + (V5 - V6) × 386/1097	0.202 V
21	V6 + (V5 - V6) × 451/1097	0.21 V
22	V6 + (V5 - V6) × 517/1097	0.217 V
23	V6 + (V5 - V6) × 585/1097	0.225 V
24	V6 + (V5 - V6) × 654/1097	0.233 V
25	V6 + (V5 - V6) × 723/1097	0.241 V
26	V6 + (V5 - V6) × 790/1097	0.249 V
27	V6 + (V5 - V6) × 855/1097	0.257 V
28	V6 + (V5 - V6) × 917/1097	0.264 V
29	V6 + (V5 - V6) × 977/1097	0.271 V
30	V6 + (V5 - V6) × 1037/1097	0.278 V
31	V5	0.285 V
32	V5 + (V4 - V5) × 60/1501	0.298 V
33	V5 + (V4 - V5) × 119/1501	0.31 V
34	V5 + (V4 - V5) × 176/1501	0.322 V
35	V5 + (V4 - V5) × 231/1501	0.334 V
36	V5 + (V4 - V5) × 284/1501	0.345 V
37	V5 + (V4 - V5) × 335/1501	0.356 V
38	V5 + (V4 - V5) × 385/1501	0.366 V
39	V5 + (V4 - V5) × 434/1501	0.376 V
40	V5 + (V4 - V5) × 483/1501	0.387 V
41	V5 + (V4 - V5) × 532/1501	0.397 V
42	V5 + (V4 - V5) × 580/1501	0.407 V
43	V5 + (V4 - V5) × 628/1501	0.417 V
44	V5 + (V4 - V5) × 676/1501	0.427 V
45	V5 + (V4 - V5) × 724/1501	0.438 V
46	V5 + (V4 - V5) × 772/1501	0.448 V
47	V5 + (V4 - V5) × 819/1501	0.458 V
48	V5 + (V4 - V5) × 866/1501	0.468 V
49	V5 + (V4 - V5) × 912/1501	0.477 V
50	V5 + (V4 - V5) × 957/1501	0.487 V
51	V5 + (V4 - V5) × 1001/1501	0.496 V
52	V5 + (V4 - V5) × 1045/1501	0.505 V
53	V5 + (V4 - V5) × 1088/1501	0.514 V
54	V5 + (V4 - V5) × 1131/1501	0.523 V
55	V5 + (V4 - V5) × 1173/1501	0.532 V
56	V5 + (V4 - V5) × 1215/1501	0.541 V
57	V5 + (V4 - V5) × 1257/1501	0.55 V
58	V5 + (V4 - V5) × 1298/1501	0.559 V
59	V5 + (V4 - V5) × 1339/1501	0.567 V
60	V5 + (V4 - V5) × 1380/1501	0.576 V
61	V5 + (V4 - V5) × 1421/1501	0.584 V
62	V5 + (V4 - V5) × 1461/1501	0.593 V
63	V4	0.601 V
64	V4 + (V3 - V4) × 40/2215	0.615 V
65	V4 + (V3 - V4) × 80/2215	0.628 V
66	V4 + (V3 - V4) × 120/2215	0.641 V
67	V4 + (V3 - V4) × 160/2215	0.654 V
68	V4 + (V3 - V4) × 200/2215	0.667 V
69	V4 + (V3 - V4) × 240/2215	0.681 V
70	V4 + (V3 - V4) × 280/2215	0.694 V
71	V4 + (V3 - V4) × 320/2215	0.707 V
72	V4 + (V3 - V4) × 360/2215	0.72 V
73	V4 + (V3 - V4) × 400/2215	0.734 V
74	V4 + (V3 - V4) × 440/2215	0.747 V
75	V4 + (V3 - V4) × 480/2215	0.76 V
76	V4 + (V3 - V4) × 520/2215	0.773 V
77	V4 + (V3 - V4) × 560/2215	0.787 V
78	V4 + (V3 - V4) × 600/2215	0.80 V
79	V4 + (V3 - V4) × 640/2215	0.813 V
80	V4 + (V3 - V4) × 680/2215	0.826 V
81	V4 + (V3 - V4) × 719/2215	0.839 V
82	V4 + (V3 - V4) × 758/2215	0.852 V
83	V4 + (V3 - V4) × 796/2215	0.865 V
84	V4 + (V3 - V4) × 834/2215	0.877 V
85	V4 + (V3 - V4) × 871/2215	0.889 V
86	V4 + (V3 - V4) × 908/2215	0.902 V
87	V4 + (V3 - V4) × 944/2215	0.914 V
88	V4 + (V3 - V4) × 980/2215	0.925 V
89	V4 + (V3 - V4) × 1016/2215	0.937 V

-continued

90	V4 + (V3 - V4) × 1052/2215	0.949 V
91	V4 + (V3 - V4) × 1087/2215	0.961 V
92	V4 + (V3 - V4) × 1122/2215	0.972 V
93	V4 + (V3 - V4) × 1157/2215	0.984 V
94	V4 + (V3 - V4) × 1192/2215	0.996 V
95	V4 + (V3 - V4) × 1226/2215	1.007 V
96	V4 + (V3 - V4) × 1260/2215	1.018 V
97	V4 + (V3 - V4) × 1294/2215	1.029 V
98	V4 + (V3 - V4) × 1328/2215	1.04 V
99	V4 + (V3 - V4) × 1362/2215	1.052 V
100	V4 + (V3 - V4) × 1396/2215	1.063 V
101	V4 + (V3 - V4) × 1429/2215	1.074 V
102	V4 + (V3 - V4) × 1462/2215	1.085 V
103	V4 + (V3 - V4) × 1495/2215	1.096 V
104	V4 + (V3 - V4) × 1528/2215	1.107 V
105	V4 + (V3 - V4) × 1561/2215	1.118 V
106	V4 + (V3 - V4) × 1593/2215	1.128 V
107	V4 + (V3 - V4) × 1625/2215	1.139 V
108	V4 + (V3 - V4) × 1657/2215	1.149 V
109	V4 + (V3 - V4) × 1688/2215	1.16 V
110	V4 + (V3 - V4) × 1719/2215	1.17 V
111	V4 + (V3 - V4) × 1750/2215	1.18 V
112	V4 + (V3 - V4) × 1781/2215	1.19 V
113	V4 + (V3 - V4) × 1811/2215	1.20 V
114	V4 + (V3 - V4) × 1841/2215	1.21 V
115	V4 + (V3 - V4) × 1871/2215	1.22 V
116	V4 + (V3 - V4) × 1901/2215	1.23 V
117	V4 + (V3 - V4) × 1930/2215	1.24 V
118	V4 + (V3 - V4) × 1959/2215	1.249 V
119	V4 + (V3 - V4) × 1988/2215	1.259 V
120	V4 + (V3 - V4) × 2016/2215	1.268 V
121	V4 + (V3 - V4) × 2044/2215	1.277 V
122	V4 + (V3 - V4) × 2072/2215	1.287 V
123	V4 + (V3 - V4) × 2100/2215	1.296 V
124	V4 + (V3 - V4) × 2128/2215	1.305 V
125	V4 + (V3 - V4) × 2156/2215	1.314 V
126	V4 + (V3 - V4) × 2185/2215	1.324 V
127	V3	1.334 V
128	V3 + (V2 - V3) × 31/2343	1.344 V
129	V3 + (V2 - V3) × 64/2343	1.354 V
130	V3 + (V2 - V3) × 97/2343	1.365 V
131	V3 + (V2 - V3) × 130/2343	1.375 V
132	V3 + (V2 - V3) × 163/2343	1.386 V
133	V3 + (V2 - V3) × 196/2343	1.396 V
134	V3 + (V2 - V3) × 229/2343	1.407 V
135	V3 + (V2 - V3) × 262/2343	1.417 V
136	V3 + (V2 - V3) × 295/2343	1.428 V
137	V3 + (V2 - V3) × 328/2343	1.438 V
138	V3 + (V2 - V3) × 361/2343	1.449 V
139	V3 + (V2 - V3) × 395/2343	1.46 V
140	V3 + (V2 - V3) × 429/2343	1.471 V
141	V3 + (V2 - V3) × 463/2343	1.481 V
142	V3 + (V2 - V3) × 497/2343	1.492 V
143	V3 + (V2 - V3) × 531/2343	1.503 V
144	V3 + (V2 - V3) × 566/2343	1.514 V
145	V3 + (V2 - V3) × 601/2343	1.525 V
146	V3 + (V2 - V3) × 636/2343	1.536 V
147	V3 + (V2 - V3) × 671/2343	1.548 V
148	V3 + (V2 - V3) × 706/2343	1.559 V
149	V3 + (V2 - V3) × 741/2343	1.57 V
150	V3 + (V2 - V3) × 777/2343	1.581 V
151	V3 + (V2 - V3) × 813/2343	1.593 V
152	V3 + (V2 - V3) × 849/2343	1.604 V
153	V3 + (V2 - V3) × 885/2343	1.616 V
154	V3 + (V2 - V3) × 921/2343	1.627 V
155	V3 + (V2 - V3) × 958/2343	1.639 V
156	V3 + (V2 - V3) × 995/2343	1.651 V
157	V3 + (V2 - V3) × 1032/2343	1.663 V
158	V3 + (V2 - V3) × 1069/2343	1.674 V
159	V3 + (V2 - V3) × 1106/2343	1.686 V
160	V3 + (V2 - V3) × 1143/2343	1.698 V
161	V3 + (V2 - V3) × 1180/2343	1.71 V
162	V3 + (V2 - V3) × 1217/2343	1.722 V
163	V3 + (V2 - V3) × 1255/2343	1.734 V
164	V3 + (V2 - V3) × 1293/2343	1.746 V
165	V3 + (V2 - V3) × 1331/2343	1.758 V

-continued

166	$V3 + (V2 - V3) \times 1369/2343$	1.77 V
167	$V3 + (V2 - V3) \times 1407/2343$	1.782 V
168	$V3 + (V2 - V3) \times 1445/2343$	1.794 V
169	$V3 + (V2 - V3) \times 1483/2343$	1.806 V
170	$V3 + (V2 - V3) \times 1521/2343$	1.819 V
171	$V3 + (V2 - V3) \times 1559/2343$	1.831 V
172	$V3 + (V2 - V3) \times 1597/2343$	1.843 V
173	$V3 + (V2 - V3) \times 1635/2343$	1.855 V
174	$V3 + (V2 - V3) \times 1673/2343$	1.867 V
175	$V3 + (V2 - V3) \times 1712/2343$	1.879 V
176	$V3 + (V2 - V3) \times 1751/2343$	1.892 V
177	$V3 + (V2 - V3) \times 1790/2343$	1.904 V
178	$V3 + (V2 - V3) \times 1829/2343$	1.917 V
179	$V3 + (V2 - V3) \times 1868/2343$	1.929 V
180	$V3 + (V2 - V3) \times 1907/2343$	1.942 V
181	$V3 + (V2 - V3) \times 1946/2343$	1.954 V
182	$V3 + (V2 - V3) \times 1985/2343$	1.966 V
183	$V3 + (V2 - V3) \times 2024/2343$	1.979 V
184	$V3 + (V2 - V3) \times 2064/2343$	1.992 V
185	$V3 + (V2 - V3) \times 2103/2343$	2.004 V
186	$V3 + (V2 - V3) \times 2143/2343$	2.017 V
187	$V3 + (V2 - V3) \times 2183/2343$	2.03 V
188	$V3 + (V2 - V3) \times 2223/2343$	2.042 V
189	$V3 + (V2 - V3) \times 2263/2343$	2.055 V
190	$V3 + (V2 - V3) \times 2303/2343$	2.068 V
191	$V2$	2.081 V
192	$V2 + (V1 - V2) \times 40/1638$	2.09 V
193	$V2 + (V1 - V2) \times 81/1638$	2.10 V
194	$V2 + (V1 - V2) \times 124/1638$	2.11 V
195	$V2 + (V1 - V2) \times 168/1638$	2.121 V
196	$V2 + (V1 - V2) \times 213/1638$	2.131 V
197	$V2 + (V1 - V2) \times 259/1638$	2.142 V
198	$V2 + (V1 - V2) \times 306/1638$	2.153 V
199	$V2 + (V1 - V2) \times 353/1638$	2.165 V
200	$V2 + (V1 - V2) \times 401/1638$	2.176 V
201	$V2 + (V1 - V2) \times 450/1638$	2.188 V
202	$V2 + (V1 - V2) \times 499/1638$	2.199 V
203	$V2 + (V1 - V2) \times 548/1638$	2.211 V
204	$V2 + (V1 - V2) \times 597/1638$	2.223 V
205	$V2 + (V1 - V2) \times 646/1638$	2.234 V
206	$V2 + (V1 - V2) \times 695/1638$	2.246 V
207	$V2 + (V1 - V2) \times 745/1638$	2.258 V
208	$V2 + (V1 - V2) \times 795/1638$	2.27 V
209	$V2 + (V1 - V2) \times 846/1638$	2.282 V
210	$V2 + (V1 - V2) \times 897/1638$	2.294 V
211	$V2 + (V1 - V2) \times 949/1638$	2.307 V
212	$V2 + (V1 - V2) \times 1002/1638$	2.319 V
213	$V2 + (V1 - V2) \times 1056/1638$	2.332 V
214	$V2 + (V1 - V2) \times 1111/1638$	2.345 V
215	$V2 + (V1 - V2) \times 1167/1638$	2.359 V
216	$V2 + (V1 - V2) \times 1224/1638$	2.372 V
217	$V2 + (V1 - V2) \times 1281/1638$	2.386 V
218	$V2 + (V1 - V2) \times 1339/1638$	2.40 V
219	$V2 + (V1 - V2) \times 1398/1638$	2.414 V
220	$V2 + (V1 - V2) \times 1458/1638$	2.428 V
221	$V2 + (V1 - V2) \times 1518/1638$	2.442 V
222	$V2 + (V1 - V2) \times 1578/1638$	2.457 V
223	$V1$	2.471 V
224	$V1 + (V0 - V1) \times 60/3029$	2.478 V
225	$V1 + (V0 - V1) \times 120/3029$	2.486 V
226	$V1 + (V0 - V1) \times 180/3029$	2.493 V
227	$V1 + (V0 - V1) \times 241/3029$	2.501 V
228	$V1 + (V0 - V1) \times 304/3029$	2.509 V
229	$V1 + (V0 - V1) \times 369/3029$	2.517 V
230	$V1 + (V0 - V1) \times 437/3029$	2.526 V
231	$V1 + (V0 - V1) \times 507/3029$	2.534 V
232	$V1 + (V0 - V1) \times 580/3029$	2.544 V
233	$V1 + (V0 - V1) \times 655/3029$	2.553 V
234	$V1 + (V0 - V1) \times 732/3029$	2.563 V
235	$V1 + (V0 - V1) \times 810/3029$	2.572 V
236	$V1 + (V0 - V1) \times 889/3029$	2.582 V
237	$V1 + (V0 - V1) \times 969/3029$	2.592 V
238	$V1 + (V0 - V1) \times 1050/3029$	2.602 V
239	$V1 + (V0 - V1) \times 1133/3029$	2.613 V
240	$V1 + (V0 - V1) \times 1218/3029$	2.623 V
241	$V1 + (V0 - V1) \times 1304/3029$	2.634 V

-continued

242	$V1 + (V0 - V1) \times 1393/3029$	2.645 V
243	$V1 + (V0 - V1) \times 1486/3029$	2.657 V
244	$V1 + (V0 - V1) \times 1583/3029$	2.669 V
245	$V1 + (V0 - V1) \times 1686/3029$	2.682 V
246	$V1 + (V0 - V1) \times 1794/3029$	2.695 V
247	$V1 + (V0 - V1) \times 1907/3029$	2.71 V
248	$V1 + (V0 - V1) \times 2026/3029$	2.724 V
249	$V1 + (V0 - V1) \times 2150/3029$	2.74 V
250	$V1 + (V0 - V1) \times 2278/3029$	2.756 V
251	$V1 + (V0 - V1) \times 2411/3029$	2.773 V
252	$V1 + (V0 - V1) \times 2549/3029$	2.79 V
253	$V1 + (V0 - V1) \times 2694/3029$	2.808 V
254	$V1 + (V0 - V1) \times 2851/3029$	2.828 V
255	$V0$	2.85 V

1) Method for controlling the power level and/or the contrast in a display device having a plurality of luminous elements corresponding to the colour components of the pixels of a picture, wherein the luminance generated by each of said luminous elements is based on the intensity of the signal supplied to the luminous element and the power level and/or contrast for each picture is controlled by adjusting the intensity of the signal to be supplied to each luminous element, wherein the intensity of the signal to be supplied to each luminous element is based on reference signals and in that the adjustment of the signal intensity is made by adjusting the level of the reference signals.

2) Method according to claim 1, wherein, for controlling the power level, it further comprises the following steps:

calculating, for each picture received by the display device, a parameter representative of the power needed by the display device for displaying said picture, and

adjusting the intensity of the signal to be supplied to each luminous element in order that the power needed by the display device for displaying said picture is lower than a target value.

3) Method according to claim 2, wherein the parameter representative of the power needed by the display device for displaying a picture is the average power level of said picture.

4) Method according to claim 1, wherein, for the controlling the contrast of the pictures displayed by the display device, it further comprises the following steps:

calculating an adjustment factor to be applied to the intensity of the picture signal supplied to the luminous elements in order that the resulting contrast is equal to a required contrast, and

applying said adjustment factor to said reference signals.

5) Method according to claim 1, wherein, before adjustment of the signal intensity, a non linear transformation is applied to reference signals in order to increase the amplitude of the low-amplitude reference signals and in that the inverse transformation is applied to the picture signal.

6) Method according to claim 1, wherein the luminous elements are organic light emitting display diodes.

7) Method according to claim 1, wherein the reference signals are reference voltages or reference currents.

8) Apparatus for controlling the power level and/or the contrast in a display device having a plurality of luminous elements corresponding to the colour components of the pixels of a picture, wherein the luminance generated by each

of said luminous elements is based on the intensity of the signal supplied to the luminous element and the power level and/or contrast for each picture is controlled by adjusting the intensity of the signal to be supplied to each luminous element, wherein the intensity of the signal to be supplied to each luminous element is based on reference signals and in that it comprises adjustment means for modifying the signal intensity by adjusting the level of the reference signals.

9) Apparatus according to claim 8, wherein, for controlling the power level, it further comprises calculation means for calculating, for each picture received by the display device, a parameter representative of the power needed by the display device for displaying said picture, and in that the adjustment means adjusts the level of the reference signals in order that the power needed by the display device for displaying each picture is lower than a target value.

10) Apparatus according to claim 9, wherein the calculation means calculates, for each picture received by the display device, the average power level of said picture.

11) Apparatus according to claim 8, wherein, for controlling the contrast of the pictures displayed by the display device, it further comprises calculation means for calculating an adjustment factor to be applied to the intensity of the signal supplied to the luminous elements in order that the resulting contrast is equal to a required contrast, and in that the adjustment means applies said adjustment factor to said reference signals.

12) Apparatus according to claim 8, wherein it comprises a frame memory for storing a picture before transmitting it to the display device.

13) Apparatus according to claim 8, wherein the adjustment means comprises means for applying a non linear transformation to reference signals and in that it comprises means for applying the inverse transformation to the picture signal.

14) Display device comprising

a plurality of organic light emitting diodes,

signal processing means for processing the picture signal received by the display device,

driving means for driving said plurality of organic light emitting diodes according to the signal processed by the signal processing means,

reference signalling means for outputting reference signals to the driving means,

wherein said signal processing means comprises an apparatus according to claim 8.

* * * * *

专利名称(译)	用于显示设备中的功率电平控制和/或对比度控制的方法和设备		
公开(公告)号	US20060022915A1	公开(公告)日	2006-02-02
申请号	US11/184214	申请日	2005-07-19
[标]申请(专利权)人(译)	韦特布吕克SEBASTIEN COTA DENNIS ROY PHILIPPE 大号		
申请(专利权)人(译)	韦特布吕克SEBASTIEN COTA DENNIS ROY PHILIPPE 大号		
[标]发明人	WEITBRUCH SEBASTIEN COTA DENNIS ROY PHILIPPE LE		
发明人	WEITBRUCH, SEBASTIEN COTA, DENNIS ROY, PHILIPPE LE		
IPC分类号	G09G3/30 G09G3/32		
CPC分类号	G09G3/3225 G09G2320/0233 G09G2320/0626 G09G2360/16 G09G2330/021 G09G2330/028 G09G2320/066		
优先权	2004291945 2004-07-29 EP		
其他公开文献	US7800559		
外部链接	Espacenet USPTO		

摘要(译)

本发明涉及一种用于控制显示装置中的功率电平和/或对比度的方法和装置，该显示装置具有与图像的像素的颜色分量对应的多个发光元件，其中由每个所述亮度产生的亮度发光元件基于提供给发光元件的信号强度，并且通过调节要提供给每个发光元件的信号强度来控制每个图像的功率电平和/或对比度。本发明适用于有机发光显示器（OLED）。根据本发明，要提供给每个发光元件的信号强度基于参考信号，并且通过调节参考信号的电平来调节信号强度。

