

US008698381B2

(12) **United States Patent**  
**Lee et al.**

(10) **Patent No.:** **US 8,698,381 B2**  
(45) **Date of Patent:** **Apr. 15, 2014**

(54) **ORGANIC ELECTROLUMINESCENT DISPLAY DEVICE INCLUDING HEAT-RADIATING MEANS**

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,990,618	A *	11/1999	Morita et al.	313/582
2003/0001488	A1 *	1/2003	Sundahl	313/483
2004/0016568	A1 *	1/2004	Palanisamy	174/260
2004/0027057	A1 *	2/2004	Sundahl	313/504
2005/0068738	A1 *	3/2005	Kim et al.	361/704
2005/0077615	A1 *	4/2005	Yu et al.	257/706
2005/0140260	A1 *	6/2005	Park et al.	313/292
2005/0270436	A1 *	12/2005	Miyamura et al.	349/58
2006/0132031	A1 *	6/2006	Chang et al.	313/512
2006/0226773	A1 *	10/2006	Kim et al.	313/512
2008/0054795	A1 *	3/2008	Ohmi et al.	313/504

(75) Inventors: **Hyun Lee**, Gyeongsangbuk-do (KR);  
**Kwon-Min Park**, Busan (KR); **Yong-II Kwon**, Gyeongsangbuk-do (KR);  
**Hye-Min Park**, Changwon-si (KR)

(73) Assignee: **LG Display Co., Ltd.**, Seoul (KR)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 1067 days.

FOREIGN PATENT DOCUMENTS

CN	1161621	A	10/1997
CN	1602151	A	3/2005

(21) Appl. No.: **12/591,359**

\* cited by examiner

(22) Filed: **Nov. 17, 2009**

*Primary Examiner* — Britt D Hanley

(65) **Prior Publication Data**

(74) *Attorney, Agent, or Firm* — McKenna Long & Aldridge, LLP

US 2010/0156763 A1 Jun. 24, 2010

(30) **Foreign Application Priority Data**

(57) **ABSTRACT**

Dec. 22, 2008 (KR) ..... 10-2008-0131126

An organic electroluminescent display device includes an organic electroluminescent display (OLED) panel having a first surface for displaying images and a second surface opposite to the first surface, a thermal pad attached to the second surface, a heat sink attached to the thermal pad such that the thermal pad is disposed between the OLED panel and the heat sink, a bottom case spaced apart from the heat sink and protecting the second surface of the OLED panel, the bottom case formed of a metallic material, and a top case covering edges of the first surface of the OLED panel and combined with the bottom case, wherein a plurality of heat-radiating pins are formed on a surface of the heat sink facing the bottom case.

(51) **Int. Cl.**

**H01L 51/50** (2006.01)  
**H01L 51/52** (2006.01)


(52) **U.S. Cl.**


CPC ..... **H01L 51/529** (2013.01)  
USPC ..... **313/46**; 313/504

**10 Claims, 7 Drawing Sheets**

(58) **Field of Classification Search**

CPC ..... H01L 51/529  
See application file for complete search history.





**FIG. 1**  
*Related Art*




FIG. 2




FIG. 3





FIG. 4A



**FIG. 4B**




FIG. 5




FIG. 6




FIG. 7




FIG. 8

# ORGANIC ELECTROLUMINESCENT DISPLAY DEVICE INCLUDING HEAT-RADIATING MEANS

The present application claims the benefit of Korean Patent Application No. 10-2008-0131126 filed in Korea on Dec. 22, 2008, which is hereby incorporated by reference for all purposes as if fully set forth herein.

## BACKGROUND OF THE INVENTION

### 1. Field of the Invention

The present invention relates to an organic electroluminescent display (OLED) device, and more particularly, to an OLED device including a heat-radiating means.

### 2. Discussion of the Related Art

Until a recent date, cathode ray tube (CRT) devices have been mainly used as display devices. However, recently, flat panel display devices, such as plasma display panel (PDP) devices, liquid crystal display (LCD) devices and organic electroluminescent display (OLED) devices, have been widely researched and used.

Among the flat panel display devices, organic electroluminescent display (OLED) devices have the advantages of slimness and lightweight because OLED devices are self-luminescent and do not require an additional light source differently from liquid crystal display (LCD) devices.

In addition, as compared to LCD devices, the OLED devices have excellent contrast ratios, wide viewing angles and a short response time. The OLED devices are advantageous in power consumption and are driven by low direct current (DC) voltages. Since the OLED devices solid state devices, the OLEDs sufficiently withstand external impact and have greater operational temperature ranges. Furthermore, due to their simple fabricating process, the fabrication costs of the OLED devices are low when compared with those of LCD devices.

The OLED devices are classified into a passive matrix type and an active matrix type. In the passive matrix type, scan lines and signal lines cross each other to form diodes in a matrix shape. On the other hand, in the active matrix type, a switching thin film transistor for turning on/off a pixel, a driving thin film transistor for flowing currents, and a capacitor for maintaining voltages applied to the driving thin film transistor during a frame are formed at each pixel. The passive matrix type devices have limitations on the display resolution, power consumption, lifetime, and so on, and the active matrix type devices has been researched and developed because of their low power consumption, high definition and large-sized possibility.

The OLED devices are commonly categorized as top emission-type and bottom emission-type according to a direction of the emitted light. The bottom emission-type devices have advantages in the stability and fabrication method. However, it is difficult to adopt the bottom emission-type devices into high definition products because of their restricted aperture ratio. Accordingly, the top emission-type devices have been widely used for high definition and high aperture ratio products.

FIG. 1 is a cross-sectional view illustrating an active matrix type OLED panel according to the related art. The related art OLED panel is a top emission-type.

In FIG. 1, the OLED panel 10 includes a first substrate 1 and a second substrate 2 facing the first substrate 1. The first and second substrates 1 and 2 are spaced apart from each other and are attached such that a seal pattern 20 seals edges thereof

More particularly, a driving thin film transistor DTr is formed at each pixel region P on the first substrate 1, and a connection electrode 3 is connected to the driving thin film transistor DTr.

A first electrode 5, an organic luminescent layer 7 on the first electrode 5, and a second electrode 9 on the organic luminescent layer 7 are formed on an inner surface of the second substrate 2 facing the first substrate 1. The organic luminescent layer 7 emits a predetermined color light at each pixel region P. A partition wall (not shown) may be formed between adjacent pixel regions P on the first electrode 5. When the partition wall is formed, the organic luminescent layer 7 and the second electrode 9 may be patterned and separated at each pixel region P without a patterning process.

In general, to show red, green or blue color, the organic luminescent layer 7 may include organic materials emitting red, green and blue and patterned at the pixel regions.

The first and second electrodes 5 and 9 and the organic luminescent layer 7 constitute an organic light-emitting diode E. In the OLED panel having the above mentioned structure, the first electrode 5 functions as a cathode electrode, and the second electrode 9 serves as an anode electrode.

The driving thin film transistor DTr on the first substrate 1 is electrically connected to the organic light-emitting diode E on the second substrate 2 through a connection pattern 11.

The connection pattern 11 connects the organic light-emitting diode E and the driving thin film transistor DTr across a gap between the first and second substrates 1 and 2.

Here, the second substrate 2 may be omitted to provide a flexible OLED device.

However, in the OLED panel 10, the lifespan may be rapidly decreased due to degradation of the driving thin film transistor DTr and heats generated when the OLED panel 10 is driven.

To solve the problem, various heat-radiating means have been suggested, and for example, a fan or heat pipe is added to a modularizing tool of the OLED panel. This heat-radiating means have some disadvantages. That is, the heat-radiating means has relatively weak effects for costs, and the structure and setting-up are complicated. In addition, the heat-radiating means increases the weight and thickness of the display device.

## SUMMARY OF THE INVENTION

Accordingly, the present invention is directed to an organic electroluminescent display (OLED) device that substantially obviates one or more of the problems due to limitations and disadvantages of the related art.

An advantage of the present invention is to provide an OLED device that effectively radiates heats.

Another advantage is to provide an OLED device that has a relatively thin thickness and light weight.

Another advantage is to provide an OLED device that reduces manufacturing costs.

Additional features and advantages of the invention will be set forth in the description which follows, and in part will be apparent from the description, or may be learned by practice of the invention. These and other advantages of the invention will be realized and attained by the structure particularly pointed out in the written description and claims hereof as well as the appended drawings.

To achieve these and other advantages and in accordance with the purpose of the present invention, as embodied and broadly described herein, an organic electroluminescent display device includes an organic electroluminescent display (OLED) panel having a first surface for displaying images

and a second surface opposite to the first surface, a thermal pad attached to the second surface, a heat sink attached to the thermal pad such that the thermal pad is disposed between the OLED panel and the heat sink, a bottom case spaced apart from the heat sink and protecting the second surface of the OLED panel, the bottom case formed of a metallic material, and a top case covering edges of the first surface of the OLED panel and combined with the bottom case, wherein a plurality of heat-radiating pins are formed on a surface of the heat sink facing the bottom case.

It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this specification, illustrate embodiments of the invention and together with the description serve to explain the principles of the invention.

In the drawings:

FIG. 1 is a cross-sectional view illustrating an active matrix type OLED panel according to the related art;

FIG. 2 is a cross-sectional view of a top emission-type OLED panel according to a first embodiment of the present invention;

FIG. 3 is a view of schematically illustrating a thermal pad according to the present invention;

FIG. 4A is a top-viewed perspective view of schematically illustrating a heat sink according to the present invention, and FIG. 4B is a bottom-viewed perspective view of schematically illustrating a heat sink according to the present invention;

FIG. 5 is a view of schematically illustrating an OLED panel modularized by a top case and a bottom case according to the present invention;

FIG. 6 is a view of schematically illustrating a path of transmitting heats from an OLED panel to a bottom case according to the present invention;

FIG. 7 is a cross-sectional view of a top emission-type OLED panel according to a second embodiment of the present invention; and

FIG. 8 is a cross-sectional view of a bottom emission-type OLED panel according to a third embodiment of the present invention.

#### DETAILED DESCRIPTION OF THE ILLUSTRATED EMBODIMENTS

Reference will now be made in detail to embodiments of the present invention, examples of which are illustrated in the accompanying drawings. The same reference numbers may be used throughout the drawings to refer to the same or like parts.

FIG. 2 is a cross-sectional view of a top emission-type OLED panel according to a first embodiment of the present invention.

For convenience of explanation, a driving region DA, a non-emission region NA, an emission region PA are defined. A driving thin film transistor is formed in the driving region DA, a connection pattern is formed in the non-emission region NA, and an organic light-emitting diode E is formed in the emission region PA. Although not shown in the figure, a switching region, where a switching thin film transistor is formed, is further defined.

In FIG. 2, the OLED panel 100 includes a first substrate 101 and a second substrate 102 facing and spaced apart from each other. A driving thin film transistor DTr and a switching thin film transistor are formed on the first substrate 101, and an organic light-emitting diode E is formed on the second substrate 102. The first and second substrates 101 and 102 are attached by a seal pattern 160 of a thermohardening resin or an UV curable resin at peripheries thereof.

Gate lines (not shown) and data lines 115 are formed on the first substrate 101 and cross each other to define pixel regions P. A switching thin film transistor (not shown) is formed at each crossing portion of the gate lines and the data lines 115 as a switching element, and a driving thin film transistor DTr is electrically connected to the switching thin film transistor. The driving thin film transistor DTr includes a gate electrode 103 connected to the switching thin film transistor, an gate insulating layer 106 on the gate electrode 103, a semiconductor layer 110 on the gate insulating layer 106, and source and drain electrodes 117 and 119 on the semiconductor layer 110. The semiconductor layer 110 includes an active layer 110a of intrinsic amorphous silicon and ohmic contact layers 110b of impurity-doped amorphous silicon.

A passivation layer 120 is formed over the switching thin film transistor and the driving thin film transistor DTr. The passivation layer 120 has a drain contact hole 125 exposing the drain electrode 119 of the driving thin film transistor DTr.

The passivation layer 120 is formed of one selected from an inorganic insulating material group including silicon oxide (SiO<sub>2</sub>) and silicon nitride (SiN<sub>x</sub>). As occasion demands, the passivation layer 120 may be formed of one selected from an organic insulating material group including benzocyclobutene (BCB) and photo acryl.

A connection electrode 130 is formed in each pixel region P on the passivation layer 120. The connection electrode 130 is connected to the drain electrode 119 through the drain contact hole 125.

An auxiliary electrode 151 is formed in each non-emission region NA on the second substrate 102 facing the first substrate 101. A first electrode 141 is formed on a substantially entire surface of the second substrate 102 including the auxiliary electrode 151 as an element of the organic light-emitting diode E. The first electrode 141 may function as an anode electrode. The first electrode 141 may be formed of a material having relatively high work function such as indium-tin-oxide (ITO).

A buffer layer 153 is formed on the first electrode 141 in the non-emission region NA.

A connection pattern 155 is formed on the buffer layer 153 in the non-emission region NA. The connection pattern 155 electrically connects the driving thin film transistor DTr and the organic light-emitting diode E to provide currents to the organic light-emitting diode E.

A partition wall 157 is formed on the buffer layer 153 in the non-emission region NA and surrounds a boundary of each pixel region P. The partition wall 157 has a predetermine thickness.

An organic luminescent layer 143 and a second electrode 154 are sequentially formed on the first electrode 141 in each pixel region P.

The first and second electrodes 141 and 145 and the organic luminescent layer 143 interposed therebetween constitute the organic light-emitting diode E.

The organic luminescent layer 143 and the second electrode 154 may be automatically separated by the partition wall 157 without a mask process. There exist an organic luminescent material layer 143a and a metallic material layer 145a on the partition wall 157.

Since the first electrode **141** of the organic light-emitting diode E is formed of a transparent conductive material such as ITO, lights emitted from the organic luminescent layer **143** are emanated through the first electrode **141**, and the OLED panel is a top-emission type.

Here, the organic luminescent layer **143** may have a single-layered structure of a luminous material. To increase emission efficiency, the organic luminescent layer **143** may have a multiple-layered structure including a hole injection layer, a hole transportation layer, an emission layer, an electron transportation layer, and an electron injection layer.

The second electrode **145** may function as a cathode electrode and may be formed of a metallic material having relatively low work function such as aluminum (Al) or aluminum alloy of aluminum neodymium (AlNd).

The second electrode **145** right over the connection pattern **155** contacts the connection electrode **130** over the first substrate **101**.

The connection pattern **155** has a columnar shape and a predetermined thickness. The connection pattern **155** maintains a gap between the first and second substrates **101** and **102** and electrically connects the first and second substrates **101** and **102**.

More particularly, the connection electrode **130**, which is connected to the drain electrode **119** of the driving thin film transistor DTr, contacts the second electrode **145**, which covers the connection pattern **155**. Accordingly, the organic light-emitting diode E on the second substrate **102** is electrically connected to the driving thin film transistor DTr on the first substrate **101**.

The first substrate **101**, which has the switching thin film transistor and the driving thin film transistor DTr, and the second substrate **102**, which has the organic light-emitting diode E, are manufactured separately and then attached to each other, thereby completing the OLED panel **100**.

In the OLED panel **100**, voltages are respectively applied to the first and second electrodes **141** and **145** according to a signal for a selected color, and holes injected from the first electrode **141** and electrons injected from the second electrode **145** are transported to the organic luminescent layer **143** to generate excitons. When the excitons transition from an excited state to a ground state, lights are generated and emitted as visible rays.

The emitted lights are emanated through the transparent first electrode **141** to the outside, and images are displayed through an outer surface of the second substrate **102**.

A heat-radiating means **200** is attached to an outer surface of the first substrate **101** and releases heats generated in the OLED panel **100**.

A temperature of the OLED panel **100** increases up to about 80 to 90 degrees of Celsius due to the degradation of the driving thin film transistor DTr and heats generated when the OLED panel **100** is driven. This shortens the lifespan of the OLED panel **100**.

Accordingly, in the present invention, the heat-radiating means **200** is disposed at a surface of the OLED panel **100** through which the images are not displayed. The heats generated in the OLED panel **100** are radiated, and the lifespan of the OLED panel **100** is prevented from being shortened.

The heat-radiating means **200** includes a thermal pad **210** and a heat sink **220**. The thermal pad **210** is attached to a rear surface of the OLED panel **100**, that is, the outer surface of the first substrate **101**, and the heat sink contacts the thermal pad **210**. Accordingly, the heats generated in the OLED panel **100** are effectively released to the outside through the thermal pad **210** and the heat sink **220**.

This will be explained in more detail hereinafter with reference to FIGS. **3** and **4**.

FIG. **3** is a view of schematically illustrating a thermal pad according to the present invention.

In FIG. **3**, the thermal pad **210** is attached to a rear surface of the OLED panel **100** of FIG. **2**. The thermal pad **210** may be formed of a ductile material, for example, a thermal interface material (TIM). TIM has relatively good interface properties and high thermal conductivity and includes a silicon-based material.

By using TIM as the thermal pad **210**, the thermal pad **210** may make a plane contact with the OLED panel **100** of FIG. **2** along an entire contact surface.

More particularly, the rear surface of the OLED panel **100** of FIG. **2** has roughness. If the thermal pad **210** is rigid, a surface of the thermal pad **210** may also have roughness. In this case, the thermal pad **210** may make a point contact with the OLED panel **100** of FIG. **2**, and there may be an air pocket between the thermal pad **210** and the rear surface of the OLED panel **100** of FIG. **2**.

On the other hand, if the thermal pad **210** is formed of TIM, the thermal pad **210** may be soft. The thermal pad **210** may make substantially uniformly and continuously contact the OLED panel **100** of FIG. **2** without the air pocket between the thermal pad **210** and the OLED panel **100** of FIG. **2**. Accordingly, the contact surface is maximized.

Moreover, a path for carrying the heats is expanded by the entire contact surface of the thermal pad **210** and the OLED panel **100** of FIG. **2**, and thermal contact resistance is considerably decreased. Therefore, the heats generated in the OLED panel **100** of FIG. **2** are effectively conducted to the thermal pad **210**.

The thermal pad **210** may have the same size as the rear surface of the OLED panel **100** of FIG. **2** to completely cover the rear surface of the OLED panel **100** of FIG. **2**. By the way, the thermal pad **210** may be attached to the rear surface of the OLED panel **100** of FIG. **2** by hands of a worker because it is not easy to perform an automatic process. There may be poor attachments during the process.

Thus, the thermal pad **210** may be divided into several pieces, for example, two or three pieces, which are spaced apart from each other, and may be attached to the rear surface of the OLED panel **100** of FIG. **2**. The process may be efficiently performed.

A surface of the heat sink **220** of FIG. **2** contacting the thermal pad **210** also has roughness. Since the thermal pad **210** has the ductility, the thermal pad **210** may have a plane contact with the heat sink **220** of FIG. **2** along a contact surface.

Therefore, the heats generated in the OLED panel **100** of FIG. **2** are effectively conducted to the heat sink **220** of FIG. **2**.

FIG. **4A** is a top-viewed perspective view of schematically illustrating a heat sink according to the present invention, and FIG. **4B** is a bottom-viewed perspective view of schematically illustrating a heat sink according to the present invention.

In FIG. **4A**, the heat sink **220** has a rectangular plate shape corresponding to the rear surface of the OLED panel **100** of FIG. **2**. The heat sink **220** may be formed of a metallic material having relatively high thermal conductivity, for example, aluminum (Al). The aluminum may have purity of about 99.5%.

The heat sink **220**, beneficially, may be anodized, and a black oxidation film may be formed at a surface of the heat

sink **220**. Since the heat sink **220** is black, a heat-absorbing efficiency is increased, and the heat sink **220** has relatively high thermal conductivity.

The heats transferred to the heat sink **220** are spread effectively all over the heat sink **220**.

In FIG. 4B, a plurality of heat-radiating pins **221** are formed on a rear surface of the heat sink **220** opposite to a front surface of the heat sink **220** contacting the thermal pad **210** of FIG. 3. The heat-radiating pins **221** are spaced apart from each other and projected from the rear surface of the heat sink **220** with a predetermined height.

The heat-radiating pins **221** may have various shapes. It is desirable that the heat-radiating pins **221** are protruded to face a direction for conducting heats and to have a maximized surface area.

As the number of the heat-radiating pins **221** increases, the surface area for radiating the heats conducted to the heat-radiating pins **221** increases, and a high heat-radiating effect can be obtained. The number of the heat-radiating pins **221** is within such a range that natural convection passes between adjacent heat-radiating pins **221**.

For example, in the present invention, the heat-radiating pins **221** may be protruded from the rear surface of the heat sink **220** with the height H of at least 1 to 2 mm. A width W of the heat-radiating pins **221** may be within a range of 1 to 2 mm, and a distance S between adjacent heat-radiating pins **221** may be within a range of 2 to 3 mm.

Accordingly, natural convection passes between adjacent heat-radiating pins **221**, and some of the heats conducted to the heat sink **220** can be released.

To further increase the heat-radiating effect of the heat sink **220**, it is beneficial to release the heats conducted to the heat sink **220** to the outside through a modularizing tool of the OLED panel **100** of FIG. 2. To do this, heat-radiating contact terminals **223** may be formed at four corner areas of the rear surface of the heat sink **220**.

The heat-radiating contact terminals **223** may be projected from the rear surface of the heat sink **220** with a higher height than the heat-radiating pins **221**. When the heat-radiating contact terminals **223** contacts the modularizing tool of the OLED panel **100** of FIG. 2, the heat-radiating pins **221** do not contact the modularizing tool of the OLED panel **100** of FIG. 2, and there is a gap between the heat-radiating pins **221** and the modularizing tool.

Here, the modularizing tool of the OLED panel **100** of FIG. 2 may be a top case and a bottom case.

FIG. 5 is a view of schematically illustrating an OLED panel modularized by a top case and a bottom case according to the present invention.

In FIG. 5, a heat-radiating means **220** is disposed at a rear surface of an OLED panel **100**. The heat-radiating means **220** includes a thermal pad **210** attached to the rear surface of the LED panel **100** and a heat sink **220** attached to a rear surface of the thermal pad **210**.

A plurality of heat-radiating pins **221** and heat-radiating contact terminals **223** are formed on the rear surface of the heat sink **220**.

The OLED panel **100** and the heat-radiating means **220** are modularized by a top case **320** and a bottom case **310**. The top case **320** has a rectangular frame shape with an L-shaped cross-section to cover edges of a front surface and side surfaces of the OLED panel **100**. A front surface of the top case **320** has an opening, wherein images of the OLED panel **100** are displayed through the opening. The top case **320** may be formed of a metallic material.

The bottom case **310**, which the OLED panel **100** and the heat-radiating means **220** are disposed over and which is a

base of an OLED module, has a rectangular plate shape, and edges of the bottom case **310** are bent toward the OLED panel **100**. Thus, the bottom case **310** may include a bottom wall and side walls. The bottom case **310** protects a rear side of the OLED panel **100**. The bottom case **310** may be formed of a metallic material.

The heat-radiating contact terminals **223** formed on the rear surface of the heat sink **220** contacts the bottom case **310** of a metallic material. Accordingly, a path of transmitting heats can be obtained from the OLED panel **100** to the bottom case **310**. Namely, heats generated in the OLED panel **100** are effectively conducted to the bottom case **310** through the heat-radiating means **220** and released to the outside.

Here, the top case **320** may be referred to as a case top or a top cover, and the bottom case **310** may be referred to as a cover bottom, a bottom cover or a lower cover.

FIG. 6 is a view of schematically illustrating a path of transmitting heats from an OLED panel to a bottom case according to the present invention.

In FIG. 6, the heats generated in the OLED panel **100** are conducted to the heat sink **220** through the thermal pad **210**. Some of the heats conducted to the heat sink **220** are radiated by natural convection passes between adjacent heat-radiating pins **221**, and other of the heats are released to the outside through the bottom case **310** of a metallic material contacting the heat-radiating contact terminals **223** of the heat sink **220**.

Therefore, while the temperature of the related art OLED panel goes up to more than 80 to 90 degrees of Celsius, the temperate of the OLED panel **100** may go up to 55 to 60 degrees of Celsius due to the heat-radiating means **220**.

Meanwhile, in the first embodiment of the present invention, even though the heat-radiating means **220** contacts the bottom case **310**, the heat-radiating means **220** may be formed to contact the top case **320**.

In addition, in the first embodiment of the present invention, the driving thin film transistor DTr of FIG. 2 and the organic light-emitting diode E of FIG. 2 are formed on different substrates. In another embodiment, the driving thin film transistor and the organic light-emitting diode may be formed on the same substrate.

FIG. 7 is a cross-sectional view of a top emission-type OLED panel according to a second embodiment of the present invention. For convenience of explanation, the same parts as the first embodiment will be summarily explained.

In FIG. 7, the OLED panel **400** includes a driving thin film transistor DTr and an organic light-emitting diode E formed on the same substrate **401**.

A second electrode **415**, an organic luminescent layer **413** and a first electrode **411** are sequentially formed on an inner surface of the substrate **401** and constitute the organic light-emitting diode E. The second electrode **415** is electrically connected to the driving thin film transistor DTr.

Here, the second electrode **415** may be formed of an opaque conductive material, and the first electrode **411** may be formed of a transparent conductive material. Accordingly, lights emitted from the organic luminescent layer **413** are emanated through the first electrode **411**.

A transparent passivation film **420** may be formed to cover a display area of the substrate **401** having the organic light-emitting diode E.

As stated above, the lights are emanated toward a direction from the substrate **401** to the passivation film **420** to thereby display images. Therefore, an outer surface of the passivation film **420** is a display surface.

A heat-radiating means **220** is attached to an outer surface of the substrate **401** and releases the heats generated in the OLED panel **400**.

In the meantime, a counter substrate facing the substrate **401** may be disposed instead of the passivation film **420**. At this time, the counter substrate may be attached with the substrate **401** by a seal pattern (not shown).

In the second embodiment, the heat-radiating means **200** is positioned on the rear surface of the substrate **401** including the driving thin film transistor DTr. The heat-radiating means **200** may be disposed on an outer surface of a substrate facing the substrate **401** that includes the driving thin film transistor DTr. This will be explained hereafter with reference to FIG. **8**.

FIG. **8** is a cross-sectional view of a bottom emission-type OLED panel according to a third embodiment of the present invention. For convenience of explanation, the same parts as the first and second embodiments will be summarily explained.

In FIG. **8**, an organic light-emitting diode E and a driving thin film transistor DTr are formed on the same substrate, that is, on a first substrate **501**.

A second electrode **515**, an organic luminescent layer **513** and a first electrode **511** are sequentially formed on an inner surface of the first substrate **501** and constitute the organic light-emitting diode E. The second electrode **515** is electrically connected to the driving thin film transistor DTr.

Here, the second electrode **515** may be formed of a transparent conductive material, and the first electrode **511** may be formed of an opaque conductive material. Accordingly, lights emitted from the organic luminescent layer **513** are emanated through the second electrode **511**.

A second substrate **502** is spaced apart from the first substrate **501**. A moisture-absorbing means **530** may be attached to an inner surface of the second substrate **502**. The moisture-absorbing means **530** removes moisture and oxygen in the OLED panel **500**.

In the OLED panel **500**, the lights are emanated toward a direction from the second substrate **502** to the first substrate **501** to thereby display images. Therefore, an outer surface of the first substrate **501** is a display surface.

A heat-radiating means **200** is attached to an outer surface of the second substrate **502** and releases the heats generated in the OLED panel **500**.

As mentioned above, in the present invention, the heat-radiating means **200** including the thermal pad **210** and the heat sink **220** is disposed at the outer surface of a side of the OLED panel that does not display images, and thus the path of transmitting heats can be obtained from the OLED panel to the bottom case. Accordingly, the heats generated in the OLED panel are effectively released to the outside, and the heat-radiating effect can be maximized.

Moreover, the heat-radiating means **200** has a simple structure and is easily set up. As compared with the fan or heat pipe of the related art, the heat-radiating effect may be relatively high, and a display device having light weight and thin thickness can be obtained.

It will be apparent to those skilled in the art that various modifications and variation can be made in the present invention without departing from the spirit or scope of the invention. Thus, it is intended that the present invention cover the modifications and variations of this invention provided they come within the scope of the appended claims and their equivalents.

What is claimed is:

1. An organic electroluminescent display device, comprising:

an organic electroluminescent display (OLED) panel having a first surface for displaying images and a second surface opposite to the first surface;

a thermal pad attached to the second surface;

a heat sink attached to the thermal pad such that the thermal pad is disposed between the OLED panel and the heat sink;

a bottom case spaced apart from the heat sink and protecting the second surface of the OLED panel, the bottom case formed of a metallic material; and

a top case covering edges of the first surface of the OLED panel and combined with the bottom case,

wherein a plurality of heat-radiating pins are formed on a surface of the heat sink facing the bottom case, and

wherein the thermal pad is formed of a ductile thermal interface material including a silicon-based material, the thermal pad directly contacts the OLED panel, and there is no air pocket between the thermal pad and the OLED panel.

2. The device according to claim 1, wherein the thermal pad has a size corresponding to the second surface of the OLED panel.

3. The device according to claim 1, wherein thermal pad is divided into several pieces that are spaced apart from each other.

4. The device according to claim 1, wherein the heat sink has a plate shape and a size corresponding to the second surface of the OLED panel.

5. The device according to claim 1, wherein the plurality of heat-radiating pins are protruded from the heat sink and spaced apart from each other.

6. The device according to claim 5, wherein heat-radiating contact terminals are formed on the surface of the heat sink facing the bottom case and contact the bottom case.

7. The device according to claim 6, wherein the heat-radiating contact terminals have a higher height than the plurality of heat-radiating pins such that the plurality of heat-radiating pins are spaced apart from the bottom case.

8. The device according to claim 6, wherein the heat-radiating contact terminals are disposed at four corner areas of the surface of the heat sink facing the bottom case.

9. The device according to claim 1, wherein the OLED panel includes:

first and second substrates facing each other;

a switching thin film transistor and a driving thin film transistor on an inner surface of the first substrate; and an organic light-emitting diode on an inner surface of the second substrate,

wherein lights emitted from the light-emitting diode are emanated through the second substrate.

10. The device according to claim 1, wherein the OLED panel includes:

first and second substrates facing each other; and

a switching thin film transistor, a driving thin film transistor and an organic light-emitting diode on an inner surface of the first substrate,

wherein lights emitted from the light-emitting diode are emanated through the second substrate.

\* \* \* \* \*

专利名称(译)	有机电致发光显示装置包括散热装置		
公开(公告)号	<a href="#">US8698381</a>	公开(公告)日	2014-04-15
申请号	US12/591359	申请日	2009-11-17
[标]申请(专利权)人(译)	李炫 PARK权敏 权容IL PARK HYE MIN		
申请(专利权)人(译)	李炫 PARK KWON-MIN KWON金永 PARK HYE-MIN		
当前申请(专利权)人(译)	LG DISPLAY CO. , LTD.		
[标]发明人	LEE HYUN PARK KWON MIN KWON YONG IL PARK HYE MIN		
发明人	LEE, HYUN PARK, KWON-MIN KWON, YONG-IL PARK, HYE-MIN		
IPC分类号	H01L51/50 H01L51/52		
CPC分类号	H01L51/529		
优先权	1020080131126 2008-12-22 KR		
其他公开文献	US20100156763A1		
外部链接	<a href="#">Espacenet</a> <a href="#">USPTO</a>		

摘要(译)

一种有机电致发光显示装置，包括：有机电致发光显示器（OLED）面板，具有用于显示图像的第一表面和与第一表面相对的第二表面，附接到第二表面的导热垫，附接到导热垫的散热器，使得导热垫设置在OLED面板和散热器之间，底壳与散热器间隔开并保护OLED面板的第二表面，底壳由金属材料形成，顶壳覆盖OLED的边缘OLED面板的第一表面并与底壳结合，其中多个散热销形成在散热器的面向底壳的表面上。

