



US008597798B2

(12) United States Patent
Parham et al.**(10) Patent No.: US 8,597,798 B2**
(45) Date of Patent: Dec. 3, 2013**(54) MATERIALS FOR ORGANIC
ELECTROLUMINESCENT DEVICES****(75) Inventors:** Amir Hossain Parham, Frankfurt (DE);
Arne Buesing, Frankfurt (DE); Anja
Gerhard, Veitschöchheim (DE);
Joachim Kaiser, Darmstadt (DE);
Rocco Fortte, Frankfurt (DE)**(73) Assignee:** Merck Patent GmbH (DE)**(*) Notice:** Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 369 days.**(21) Appl. No.: 13/001,234****(22) PCT Filed: Oct. 15, 2009****(86) PCT No.: PCT/EP2009/007407**§ 371 (c)(1),
(2), (4) Date: **Dec. 23, 2010****(87) PCT Pub. No.: WO2010/054731**PCT Pub. Date: **May 20, 2010****(65) Prior Publication Data**

US 2011/0095281 A1 Apr. 28, 2011

(30) Foreign Application Priority Data

Nov. 13, 2008 (DE) 10 2008 057 050

(51) Int. Cl.
H01L 51/54 (2006.01)
C09K 11/06 (2006.01)**(52) U.S. Cl.**
USPC **428/690**; 428/917; 313/504; 313/506;
252/301.16; 257/40; 257/E51.044; 546/4;
546/10; 548/103**(58) Field of Classification Search**
None
See application file for complete search history.**(56) References Cited**

U.S. PATENT DOCUMENTS

4,539,507 A 9/1985 VanSlyke et al.
5,151,629 A 9/1992 VanSlyke
5,621,131 A 4/1997 Kreuder et al.
6,653,438 B1 11/2003 Spreitzer et al.
7,345,301 B2 3/2008 Gerhard et al.
7,442,797 B2 10/2008 Itoh et al.
7,659,540 B2 2/2010 Heun et al.
7,701,131 B2 4/2010 Gerhard et al.
7,723,455 B2 5/2010 Becker et al.
7,795,801 B2 9/2010 Ueda et al.
7,834,136 B2 11/2010 Parham et al.
2005/0069729 A1 3/2005 Ueda et al.
2006/0134461 A1 6/2006 Huo et al.
2006/0243966 A1 11/2006 Sotoyama et al.
2006/0255332 A1 11/2006 Becker et al.
2006/0284140 A1 12/2006 Breuning et al.
2007/0075311 A1 4/2007 Okada
2007/0082284 A1 4/2007 Stoessel et al.2007/0176147 A1 8/2007 Buesing et al.
2007/0205714 A1 9/2007 Busing et al.
2008/0038586 A1 2/2008 Nishizeki et al.
2009/0134384 A1 5/2009 Stoessel et al.
2009/0167166 A1 7/2009 Bach et al.
2009/0226759 A1 9/2009 Heun et al.
2009/0302742 A1 12/2009 Komori et al.
2009/0302752 A1 12/2009 Parham et al.
2010/0102305 A1 4/2010 Heun et al.
2010/0187977 A1 7/2010 Kai et al.
2010/0244009 A1 9/2010 Parham et al.
2010/0288974 A1 11/2010 Buesing et al.
2011/0068304 A1 3/2011 Parham et al.

FOREIGN PATENT DOCUMENTS

DE 102008033943 A1 1/2010
DE 102008036982 A1 2/2010
DE 102008056688 A1 5/2010
EP 652273 A1 5/1995
EP 707020 A2 4/1996
EP 842208 A1 5/1998
EP 894107 A1 2/1999
EP 1028136 8/2000
EP 1205527 A1 5/2002
EP 1617710 A1 1/2006
EP 1617711 A1 1/2006
EP 1731584 A1 12/2006
JP 2004-288381 A 10/2004
JP 2005-347160 A 12/2005
WO WO-92/18552 A1 10/1992
WO WO-00/22026 A1 4/2000
WO WO-2004/013080 A1 2/2004
WO WO-2004/041901 A1 5/2004
WO WO-2004/070772 A2 8/2004
WO WO-2004/093207 A2 10/2004
WO WO-2004/108857 A1 12/2004
WO WO-2004/113412 A2 12/2004
WO WO-2004/113468 A1 12/2004
WO WO-2005/003253 A2 1/2005
WO WO-2005/011013 A1 2/2005
WO WO-2005/014689 A2 2/2005
WO WO-2005/039246 A1 4/2005
WO WO-2005/040302 A1 5/2005
WO WO-2005/042444 A2 5/2005
WO WO-2005/042550 A1 5/2005
WO WO-2005/104264 A1 11/2005
WO WO-2005/111172 A2 11/2005

(Continued)

Primary Examiner — Michael H Wilson

(74) Attorney, Agent, or Firm — Novak Druce Connolly
Bove + Quigg LLP**(57) ABSTRACT**The present invention relates to transition-metal complexes
of the general formula I or II, in particular as emitter mol-
ecules in organic electronic devices, to a layer and an elec-
tronic device which comprise the compounds according to the
invention, and to a process for the preparation of the com-
pounds according to the invention.**15 Claims, No Drawings**

(56) **References Cited**

FOREIGN PATENT DOCUMENTS

WO	WO-2006/005627	A1	1/2006
WO	WO-2006/061181	A1	6/2006
WO	WO-2006/098120	A1	9/2006
WO	WO-2006/117052	A1	11/2006
WO	WO-2007/017066	A1	2/2007

WO	WO-2007/063754	A1	6/2007
WO	WO-2007/137725	A1	12/2007
WO	WO-2008/056746	A1	5/2008
WO	WO-2008/066192	A1	6/2008
WO	WO-2008/086851	A1	7/2008
WO	WO-2009/062578	A1	5/2009
WO	WO-2010/006680		1/2010
WO	WO-2010/015306		2/2010
WO	WO-2010/054729		5/2010

MATERIALS FOR ORGANIC ELECTROLUMINESCENT DEVICES

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a national stage application (under 35 U.S.C. §371) of PCT/EP2009/007407, filed Oct. 15, 2009, which claims benefit of German application 10 2008 057 050.8, filed Nov. 13, 2008.

BACKGROUND OF THE INVENTION

The present invention relates to transition-metal complexes of the general formula I or II, in particular as emitter molecules in organic electronic devices, to a layer and an electronic device which comprise the compounds according to the invention, and to a process for the preparation of the compounds according to the invention.

Chelate complexes and organometallic compounds are used as functional materials in a number of applications of different types which can be ascribed to the electronics industry in the broadest sense. In the case of organic electroluminescent devices based on organic components (general description of the structure cf. U.S. Pat. Nos. 4,539,507 and 5,151,629) and individual components thereof, the organic light-emitting diodes (OLEDs), the market introduction has already taken place. In spite of the successes that have already been achieved, further improvements are still desirable here.

In recent years, organometallic complexes which exhibit phosphorescence instead of fluorescence have increasingly been under discussion (M. A. Baldo, S. Lamansky, P. E. Burrows, M. E. Thompson, S. R. Forrest, Appl. Phys. Lett., 1999, 75, 4-6). For theoretical spin-statistical reasons, an up to fourfold increase in energy and power efficiency is possible using organometallic compounds as phosphorescence emitters. The main conditions that should be mentioned here for practical use are, in particular, a long operating lifetime, high stability to temperature stresses and a low use and operating voltage in order to facilitate mobile applications.

Besides the individual specific weak points for each material, the class of known metal complexes has a general need for improvement, which is described briefly below:

Many of the known metal complexes have low thermal stability (cf.: R. G. Charles, J. Inorg. Nucl. Chem., 1963, 25, 45). On vacuum deposition, this inevitably always results in the liberation of organic pyrolysis products, which, in some cases even in small amounts, considerably shorten the operating lifetime of OLEDs.

The strong interaction of the complex units in the solid, in particular in the case of planar complexes of d⁸ metals, such as platinum(II), likewise causes aggregation of the complex units in the emitter layer if the degree of doping exceeds about 0.1%, which is the case in accordance with the current prior art. This aggregation results in the formation of so-called excimers or exciplexes on excitation (optical or electrical). These aggregates frequently have an unstructured, broad emission band, which makes the generation of pure primary colours (RGB) considerably more difficult or completely impossible. In general, the efficiency for this transition also drops.

In addition, it is evident from the above-said that the emission colour is highly dependent on the degree of doping,

a parameter which can be controlled precisely only with considerable technical effort, in particular in large production plants.

Known in OLED technology are metal complexes of the group 10 transition metals (Ni, Pd, Pt) in which the central metal is bonded via two aromatic N atoms and two C atoms (WO 2004/108857, WO 2005/042550, WO 2005/042444, US 2006/0134461 A1) or two imine-like N atoms in combination with two phenolic O atoms (WO 2004/108857) or via two aromatic N atoms and two basic N atoms (WO 2004/108857). The known compounds have, inter alia, electroluminescence in the blue, red and green region of the electromagnetic spectrum.

Nevertheless, there is still a demand for further compounds which do not have the above-mentioned disadvantages and preferably exhibit electroluminescence in the blue, red and green region of the electromagnetic spectrum and in particular can also be employed in the solid state as light-emitting layer.


BRIEF SUMMARY OF THE INVENTION

The object of the invention was thus to provide compounds of this type.

Surprisingly, it has been found that a long operating lifetime is achieved by metal complexes having imine-like N atoms in combination with aromatic C atoms or olefinic C atoms in combination with aromatic N atoms as phosphorescence emitters in OLEDs and high stability to temperature stresses and a low use and operating voltage are achieved by bridging these ligands.

The present invention provides in this respect a compound of the general formula I

formula I



where

M is a metal ion in oxidation state +2,


Ar is, identically or differently on each occurrence, an aromatic or heteroaromatic ring system, which may be substituted by one or more radicals R of any desired type, and the ring systems Ar may optionally be linked to one another by single bonds or any desired radicals R,

Y is, identically or differently on each occurrence, C, N or P, with the proviso that either two C atoms and two N atoms or two C atoms and two P atoms are always bonded to the metal,

R¹ is any desired radical.

DETAILED DESCRIPTION OF THE INVENTION

The present invention furthermore provides a compound of the general formula II



formula II

where

M is a metal ion in oxidation state +2,

Ar is, identically or differently on each occurrence, an aromatic or heteroaromatic ring system, which may be substituted by one or more radicals R of any desired type, and the ring systems Ar may optionally be linked to one another by single bonds or any desired radicals R,

Y is, identically or differently on each occurrence, C, N or P, with the proviso that either two C atoms and two N atoms or two C atoms and two P atoms are always bonded to the metal,

R¹ is any desired radical.

In a preferred embodiment of the invention, in the compounds of the general formula I or II,

Ar is, identically or differently on each occurrence, an aromatic or heteroaromatic ring system, which may be substituted by one or more radicals R of any desired type, and the ring systems Ar may optionally be linked to one another by single bonds or any desired radicals R,

R is, identically or differently on each occurrence, H, D, F, Cl, Br, I, N(Ar¹)₂, N(R²)₂, CN, NO₂, Si(R²)₃, B(OR²)₂, C(=O)Ar¹, C(=O)R², P(=O)(Ar¹)₂, P(=O)(R²)₂, S(=O)R¹, S(=O)R², S(=O)₂Ar¹, S(=O)₂R², CR²=CR²Ar¹, OSO₂R², a straight-chain alkyl, alkoxy or thioalkoxy group having 1 to 40 C atoms or a branched or cyclic alkyl, alkoxy or thioalkoxy group having 3 to 40 C atoms, each of which may be substituted by one or more radicals R², where one or more non-adjacent CH₂ groups may be replaced by R²C=CR², C≡C, Si(R²)₂, Ge(R²)₂, Sn(R²)₂, C=O, C=S, C=Se, C=NR², P(=O)(R²), SO, SO₂, NR², O, S or CONR² and where one or more H atoms may be replaced by D, F, Cl, Br, I, CN or NO₂, or an aromatic or heteroaromatic ring system having 5 to 60 aromatic ring atoms, which may in each case be substituted by one or more radicals R², or an aryloxy or heteroaryloxy group having 5 to 60 aromatic ring atoms, which may be substituted by one or more radicals R², or a combination of these systems, where two or more substituents R may also form a mono- or polycyclic, aliphatic or aromatic ring system with one another,

Ar¹ is, identically or differently on each occurrence, an aromatic or heteroaromatic ring system having 5 to 40 aromatic ring atoms, which may be substituted by one or more non-aromatic radicals,

R¹ is, identically or differently on each occurrence, H, D, F, CF₃, CN, an alkyl, alkoxy or thioalkoxy group having 1 to 40 C atoms or a branched or cyclic alkyl, alkoxy or thioalkoxy group having 3 to 40 C atoms, each of which may be

substituted by one or more radicals R², where one or more non-adjacent CH₂ groups may be replaced by R²C=CR², C≡C, Si(R²)₂, Ge(R²)₂, Sn(R²)₂, and where one or more H atoms may be replaced by D, F, Cl, Br, I, CN or NO₂, or an aromatic or heteroaromatic ring system having 5 to 60 aromatic ring atoms, which may in each case be substituted by one or more radicals R², or an aryloxy or heteroaryloxy group having 5 to 60 aromatic ring atoms, which may be substituted by one or more radicals R², or a combination of these systems, where R¹ may also form a mono- or polycyclic, aliphatic or aromatic ring system with R,

R² is, identically or differently on each occurrence, H, D, F, CN or an aliphatic, aromatic and/or heteroaromatic hydrocarbon radical having 1 to 20 C atoms, in which, in addition, one or more H atoms may be replaced by F, where two or more substituents R² also form a mono- or polycyclic, aliphatic or aromatic ring system with one another.

In a further preferred embodiment of the invention, M is equal to Pd or equal to Pt. M is particularly preferably equal to Pt.

In still a further preferred embodiment of the invention, in the compounds of the general formula I or II,

M is Pt,

Ar is, identically or differently on each occurrence, an aromatic or heteroaromatic ring system having 5 to 10 aromatic ring atoms, which may be substituted by a plurality of radicals R,

Y is, identically or differently on each occurrence, C or N, with the proviso that two C atoms and two N atoms are always bonded to the metal,

R is, identically or differently on each occurrence, H, N(Ar¹)₂, CN, a straight-chain alkyl group having 1 to 10 C atoms or an aromatic or heteroaromatic ring system having 5 to 15 aromatic ring atoms, each of which may be substituted by one or more radicals R²,

R¹ is, identically or differently on each occurrence, H, D, CN, an alkyl group having 1 to 3 C atoms or an aromatic or heteroaromatic ring system having 5 to 10 aromatic ring atoms, each of which may be substituted by one or more radicals R²,

R² is, identically or differently on each occurrence, H, F, CN or an aliphatic, aromatic and/or heteroaromatic hydrocarbon radical having 1 to 20 C atoms, where two or more substituents R² may also form a mono- or polycyclic, aliphatic or aromatic ring system with one another, and Ar¹ is as defined above.

If the radicals defined above occur a number of times within one compound, the radicals may, independently of one another on each occurrence, be identical or different, corresponding to the respective definition.

The following general definitions are furthermore used within this invention:

For the purposes of this invention, an aryl group contains 6 to 60 C atoms; for the purposes of this invention, a heteroaryl group contains 2 to 60 C atoms and at least one heteroatom, with the proviso that the sum of C atoms and heteroatoms is at least 5. The heteroatoms are preferably selected from N, O and/or S. An aryl group or heteroaryl group here is taken to mean either a simple aromatic ring, i.e. benzene, or a simple heteroaromatic ring, for example pyridine, pyrimidine, thiophene, etc., or a condensed (fused) aryl or heteroaryl group, for example naphthalene, anthracene, phenanthrene, quinoline, isoquinoline, carbazole, etc.

For the purposes of this invention, the group Ar in the general formulae I and II is particularly preferably benzene, naphthalene, pyridine, pyrimidine, pyrazine, pyridazine, quinoline, isoquinoline, furan, thiophene, pyrrole, benzofu-

ran, benzothiophene and indole, where benzene, naphthalene, pyridine, quinoline and isoquinoline are most preferred.

For the purposes of this invention, an aromatic ring system contains 6 to 60 C atoms in the ring system. For the purposes of this invention, a heteroaromatic ring system contains 2 to 60 C atoms and at least one heteroatom in the ring system, with the proviso that the sum of C atoms and heteroatoms is at least 5. The heteroatoms are preferably selected from N, O and/or S. For the purposes of this invention, an aromatic or heteroaromatic ring system is intended to be taken to mean a system which does not necessarily contain only aryl or heteroaryl groups, but instead in which a plurality of aryl or heteroaryl groups may also be interrupted by a non-aromatic unit (preferably less than 10% of the atoms other than H), such as, for example, an sp^3 -hybridised C, N or O atom. Thus, for example, systems such as 9,9'-spirobifluorene, 9,9'-diarylfuorene, triarylamine, diaryl ether, stilbene, etc. are also intended to be taken to be aromatic ring systems for the purposes of this invention, as are systems in which two or more aryl groups are interrupted, for example, by a linear or cyclic alkyl group or by a silyl group.


An aromatic or heteroaromatic ring system having 5-60 aromatic ring atoms, which may also in each case be substituted by the above-mentioned radicals R^1 and which may be linked to the aromatic or heteroaromatic ring system via any desired positions, is taken to mean, in particular, groups derived from benzene, naphthalene, anthracene, benzanthracene, phenanthrene, pyrene, chrysene, perylene, fluoranthene, naphthacene, pentacene, benzopyrene, biphenyl, biphenylene, terphenyl, terphenylene, fluorene, spirobifluorene, dihydrophenanthrene, dihydropyrene, tetrahydropyrene, cis- or trans-indenofluorene, truxene, isotruxene, spirotruxene, spiroisotruxene, furan, benzofuran, isobenzofuran, dibenzofuran, thiophene, benzothiophene, isobenzothiophene, dibenzothiophene, pyrrole, indole, isoindole, carbazole, pyridine, quinoline, isoquinoline, acridine, phenanthridine, benzo-5,6-quinoline, benzo-6,7-quinoline, benzo-7,8-quinoline, phenothiazine, phenoxazine, pyrazole, indazole, imidazole, benzimidazole, naphthimidazole, phenanthrimidazole, pyridimidazole, pyrazinimidazole, quinoxalinimidazole, oxazole, benzoxazole, naphthoxazole, anthroxazole, phenanthroxazole, isoxazole, 1,2-thiazole, 1,3-thiazole, benzothiazole, pyridazine, benzopyridazine, pyrimidine, benzopyrimidine, quinoxaline, 1,5-diazaanthracene, 2,7-diazapyrene, 2,3-diazapyrene, 1,6-diazapyrene, 1,8-diazapyrene, 4,5-diazapyrene, 4,5,9,10-tetraazaperylene, pyrazine, phenazine, phenoxazine, phenothiazine, fluorubin, naphthyridine, azacarbazole, benzocarboline, phenanthroline, 1,2,3-triazole, 1,2,4-triazole, benzotriazole, 1,2,3-oxadiazole, 1,2,4-oxadiazole, 1,2,5-oxadiazole, 1,3,4-oxadiazole, 1,2,3-thiadiazole, 1,2,4-thiadiazole, 1,2,5-thiadiazole, 1,3,4-thiadiazole, 1,3,5-triazine, 1,2,4-triazine, 1,2,3-triazine, tetrazole, 1,2,4,5-tetrazine, 1,2,3,4-tetrazine, 1,2,3,5-tetrazine, purine, pteridine, indolizine and benzothiadiazole.

For the purposes of the present invention, an aliphatic hydrocarbon radical or an alkyl group, which may typically contain 1 to 40 or also 1 to 20 C atoms, and in which, in addition, individual H atoms or CH_2 groups may be substituted by the above-mentioned groups, is preferably taken to mean the radicals methyl, ethyl, n-propyl, i-propyl, n-butyl, i-butyl, s-butyl, t-butyl, 2-methylbutyl, n-pentyl, s-pentyl, cyclopentyl, n-hexyl, cyclohexyl, n-heptyl, cycloheptyl, n-octyl, cyclooctyl, 2-ethylhexyl, trifluoromethyl, pentafluoroethyl, 2,2,2-trifluoroethyl, ethenyl, propenyl, butenyl, pentenyl, cyclopentenyl, hexenyl, cyclohexenyl, heptenyl, cycloheptenyl, octenyl, cyclooctenyl, ethynyl, propynyl, butynyl, pentynyl, hexynyl, heptynyl or octynyl. An alkoxy group


having 1 to 40 C atoms is preferably taken to mean methoxy, trifluoromethoxy, ethoxy, n-propoxy, i-propoxy, n-butoxy, i-butoxy, s-butoxy, t-butoxy, n-pentoxo, s-pentoxo, 2-methylbutoxy, n-hexoxy, cyclohexyloxy, n-heptoxy, cycloheptyloxy, n-octyloxy, cyclooctyloxy, 2-ethylhexyloxy, pentafluoroethoxy or 2,2,2-trifluoroethoxy. A thioalkyl group having 1 to 40 C atoms is taken to mean, in particular, methylthio, ethylthio, n-propylthio, i-propylthio, n-butylthio, i-butylthio, s-butylthio, t-butylthio, n-pentylthio, s-pentylthio, n-hexylthio, cyclohexylthio, n-heptylthio, cycloheptylthio, n-octylthio, cyclooctylthio, 2-ethylhexylthio, trifluoromethylthio, pentafluoroethylthio, 2,2,2-trifluoroethylthio, ethenylthio, propenylthio, butenylthio, pentenylthio, cyclopentenylthio, hexenylthio, cyclohexenylthio, heptenylthio, cycloheptenylthio, octenylthio, cyclooctenylthio, ethynylthio, propynylthio, butynylthio, pentynylthio, hexynylthio, heptynylthio or octynylthio. In general, alkyl, alkoxy or thioalkyl groups in accordance with the present invention may be straight-chain, branched or cyclic, where one or more non-adjacent CH_2 groups may be replaced by $R^1C=CR^1$, $C\equiv C$, $Si(R^1)_2$, $Ge(R^1)_2$, $Sn(R^1)_2$, $C=O$, $C=S$, $C=Se$, $C=NR^1$, $P(=O)(R^1)$, SO , SO_2 , NR^1 , O, S or $CONR^1$; furthermore, one or more H atoms may also be replaced by F, Cl, Br, I, CN or NO_2 , preferably F, Cl or CN, furthermore preferably F or Cl, particularly preferably F.

A preferred embodiment of the compounds of the formulae I and II are the compounds of the following formulae III and IV:

formula III








formula IV



where M, Y, R and R^1 have the meaning mentioned above, and X stands for CR or N. It is preferred here for a maximum of two symbols X, particularly preferably a maximum of one symbol X, per ring to stand for N and for the other symbols X in this ring to stand for CR. Very particularly preferably, all groups X in a ring stand for CR.

Particularly preferred embodiments of the compounds mentioned above are the compounds of the following formulae V to XVI:

7



8

-continued

formula V

5

10

formula VI

15

20

25

formula VII

30

35

40

formula VIII

45






50

formula IX

55

60

65



formula X

formula XI


formula XII

formula XIII

formula XIV

9

-continued



10

-continued


formula XVI

formula XV

5

10

15



where the symbols used have the meanings mentioned above.

Besides the preferred compounds mentioned above, particular preference is furthermore given to the compounds shown in Table 1 below:

TABLE 1


Examples of compounds of the formulae I to XVI according to the invention

1


2

3


Examples of compounds of the formulae I to XVI according to the
invention




4



5




6




7


Examples of compounds of the formulae I to XVI according to the invention




8



9




10




11


Examples of compounds of the formulae I to XVI according to the
invention




12



13




14




15


Examples of compounds of the formulae I to XVI according to the invention




16



17




18




19


Examples of compounds of the formulae I to XVI according to the invention




20



21




22




23


Examples of compounds of the formulae I to XVI according to the invention




24



25




26




27


Examples of compounds of the formulae I to XVI according to the invention




28



29




30




31


Examples of compounds of the formulae I to XVI according to the invention




32



33




34




35


Examples of compounds of the formulae I to XVI according to the invention




36



37




38




39


Examples of compounds of the formulae I to XVI according to the
invention




40



41




42




43


Examples of compounds of the formulae I to XVI according to the invention




44



45




46




47


Examples of compounds of the formulae I to XVI according to the invention




48



49




50




51


Examples of compounds of the formulae I to XVI according to the invention




52



53




54




55


Examples of compounds of the formulae I to XVI according to the invention




56



57




58




59

TABLE 1-continued


Examples of compounds of the formulae I to XVI according to the
invention




60



61




62




63


Examples of compounds of the formulae I to XVI according to the
invention




64



65




66




67


Examples of compounds of the formulae I to XVI according to the invention




68



69




70




71


Examples of compounds of the formulae I to XVI according to the invention




72



73




74




75

TABLE 1-continued


Examples of compounds of the formulae I to XVI according to the invention




76



77




78




79

TABLE 1-continued


Examples of compounds of the formulae I to XVI according to the invention




80



81




82




83


Examples of compounds of the formulae I to XVI according to the
invention




84



85




86




87

TABLE 1-continued


Examples of compounds of the formulae I to XVI according to the invention




88



89




90




91


Examples of compounds of the formulae I to XVI according to the invention



92




93




94

TABLE 1-continued

Examples of compounds of the formulae I to XVI according to the invention



95




96

The compounds according to the invention are preferably 40
square-planar complexes or approximately square-planar
complexes which contain a tetracoordinated metal ion, in
oxidation state +2. The metal is preferably selected from
metals from group 10 of the Periodic Table of the Elements, in 45
particular Pd and Pt. The compounds according to the inven-
tion have triplet emission and have a very good lifetime, high
efficiency, high stability to temperature stresses and a high
glass transition temperature T_g.


The invention also relates to a process for the preparation of 50
a compound of the general formula I or II

-continued

formula II



formula I 55



where M, Y, Ar, R, R¹ and R² have the meaning defined above.

The compounds of the formula I or II according to the invention can be prepared by synthetic steps generally known to the person skilled in the art.

The starting point for the ligand synthesis can be, for 60
example, 6-phenylpyridine-2-carboxaldehyde (J. Am. Chem. Soc. 2003, 125(8), 2113-2128), 2-biphenylamine (Tetrahedron Lett. 2008, 49(9), 1555-1558), 3-pyridin-2-yl-benzaldehyde (Org. Lett. 2004, 6(19), 3337-3340) or 2-chloro-8-nitroquinoline (Australian J. Chem. 2003, 56(1), 39-44).


65 A first step involves the synthesis of the corresponding part-ligands, which are combined in a further step to give the desired ligand system. A reaction is subsequently carried out

59

with the corresponding metal (for example Pt or Pd), which is usually employed as a solution of a suitable metal salt, for example K_2PtCl_4 or K_2PdCl_4 .

A general synthetic procedure for the preparation of the metal complexes of the formula I or II is depicted in schemes 1 to 4. The central metal Pt here can be replaced by Pd in analogous reactions.


Scheme 1



X = C and X' = N and X'' = C or
X = N and X' = C and X'' = C or
X = C and X' = C and X'' = N


60

Scheme 2




X = C and X' = N and X'' = N or
X = N and X' = N and X'' = C or
X = N and X' = C and X'' = N

Scheme 3



61


-continued



$\text{X} = \text{C}$ and $\text{X}' = \text{N}$ and $\text{X}'' = \text{C}$ or
 $\text{X} = \text{N}$ and $\text{X}' = \text{C}$ and $\text{X}'' = \text{C}$ or
 $\text{X} = \text{C}$ and $\text{X}' = \text{C}$ and $\text{X}'' = \text{N}$


62

-continued



$\text{X} = \text{C}$ and $\text{X}' = \text{N}$ and $\text{X}'' = \text{C}$ or
 $\text{X} = \text{N}$ and $\text{X}' = \text{C}$ and $\text{X}'' = \text{C}$ or
 $\text{X} = \text{N}$ and $\text{X}' = \text{C}$ and $\text{X}'' = \text{N}$

Scheme 4



The invention also relates to the use of the compounds according to the invention in an organic electronic device. The organic electronic device used in accordance with the invention can be organic electroluminescent devices (OLEDs) or polymeric electroluminescent devices (PLEDs), organic integrated circuits (O-ICs), organic field-effect transistors (O-FETs), organic thin-film transistors (O-TFTs), organic light-emitting transistors (O-LETs), organic solar cells (O-SCs), organic optical detectors, organic photoreceptors, organic field-quench devices (O-FQDs), light-emitting electrochemical cells (LECs) or organic laser diodes (O-lasers), but in particular organic electroluminescent devices (=Organic light-emitting diodes, OLEDs, PLEDs).

In particular, the invention relates to the use of the compounds according to the invention as emitter compound and/or as charge-transport material and/or charge-injection material, preferably in a corresponding layer. This can be either a hole-transport layer, hole-injection layer, electron-transport layer or electron-injection layer. The use as charge-blocking material is also possible, depending on the structure.

The invention likewise relates to organic electronic devices, such as, for example, organic electroluminescent devices or polymeric electroluminescent devices (OLEDs, PLEDs), organic integrated circuits (O-ICs), organic field-effect transistors (O-FETs), organic thin-film transistors (O-TFTs), organic light-emitting transistors (O-LETs), organic solar cells (O-SCs), organic optical detectors, organic photoreceptors, organic field-quench devices (O-FQDs), light-emitting electrochemical cells (LECs) or organic laser diodes (O-lasers), but in particular organic electroluminescent devices (=Organic light-emitting diodes, OLEDs, PLEDs), comprising one or more compounds of the formula I or II, as defined above. For the purposes of this invention, an organic electronic device is taken to mean an electronic device comprising an anode, cathode and at least one layer which comprises at least one organic material. The device here may also comprise inorganic materials in addition to the organic material.

The compound of the formula I or II is preferably present within one layer in the electronic device.

The invention thus also relates to a layer comprising a compound of the formula I or II, as defined above.

The organic electroluminescent device comprises a cathode, anode and at least one emitting layer. Apart from these layers, it may also comprise further layers, for example in each case one or more hole-injection layers, hole-transport layers, hole-blocking layers, electron-transport layers, electron-injection layers, exciton-blocking layers and/or charge-generation layers (IDMC 2003, Taiwan; Session 21 OLED (5), T. Matsumoto, T. Nakada, J. Endo, K. Mori, N. Kawamura, A. Yokoi, J. Kido, *Multiphoton Organic EL Device Having Charge Generation Layer*). It is likewise possible for interlayers, which have, for example, an exciton-blocking function, to be introduced between two emitting layers. However, it should be pointed out that each of these layers does not necessarily have to be present. These layers may comprise compounds of the general formula I or II, as defined above.

In a preferred embodiment of the invention, the compound of the formula I or II is employed as emitting compound in an emitting layer or as charge-transport compound. The organic electroluminescent device here may comprise one emitting layer or a plurality of emitting layers, where at least one emitting layer comprises at least one compound of the formula I or II, as defined above. If a plurality of emission layers are present, these preferably have a plurality of emission maxima between 380 nm and 750 nm, resulting overall in white emission, i.e. various emitting compounds which are able to fluoresce or phosphoresce are used in the emitting layers. Particular preference is given to three-layer systems, where the three layers exhibit blue, green and orange or red emission (for the basic structure, see, for example, WO 05/011013).

If the compound of the formula I or II is employed as emitting compound in an emitting layer, it is preferably employed in combination with one or more compounds functioning as matrix. In these cases, the mixture comprising the compound of the formula I or II and the matrix material comprises between 1 and 99% by weight, preferably between 2 and 90% by weight, particularly preferably between 3 and 40% by weight, in particular between 5 and 15% by weight, of

the compound of the formula I or II, based on the entire mixture comprising emitter and matrix material. Correspondingly, the mixture comprises between 99 and 1% by weight, preferably between 98 and 10% by weight, particularly preferably between 97 and 60% by weight, in particular between 95 and 85% by weight, of the matrix material, based on the entire mixture comprising emitter and matrix material.

Preferred matrix materials are aromatic ketones, aromatic phosphine oxides or aromatic sulfoxides or sulfones, for example in accordance with WO 04/013080, WO 04/093207, WO 06/005627 or the unpublished application DE 102008033943.1, triarylamines, carbazole derivatives, for example CBP (N,N-biscarbazolylbiphenyl) or the carbazole derivatives disclosed in WO 05/039246, US 2005/0069729, JP 2004/288381, EP 1205527 or WO 08/086,851, indolocarbazole derivatives, for example in accordance with WO 07/063,754 or WO 08/056,746, azacarbazole derivatives, for example in accordance with EP 1617710, EP 1617711, EP 1731584, JP 2005/347160, bipolar matrix materials, for example in accordance with WO 07/137,725, silanes, for example in accordance with WO 05/111172, azaboroles or boronic esters, for example in accordance with WO 06/117052, triazine derivatives, for example in accordance with the unpublished application DE 102008036982.9, WO 07/063,754 or WO 08/056,746, zinc complexes, for example in accordance with EP 652273 or WO 09/062,578, or diazasilole or tetraazasilole derivatives, for example in accordance with the unpublished application DE 102008056688.8.

A further preferred embodiment of the invention is the use of the compound of the formula I or II as emitter material in combination with two or more different matrix materials. Suitable matrix materials in these cases are the preferred compounds mentioned above.

Preference is furthermore given to an organic electroluminescent device in which one or more layers are applied by means of a sublimation process, in which the materials are vapour-deposited in vacuum sublimation units at a pressure below 10^{-5} mbar, preferably below 10^{-6} mbar, particularly preferably below 10^{-7} mbar.

Preference is likewise given to an organic electroluminescent device, characterised in that one or more layers are applied by means of the OVPD (organic vapour phase deposition) process or with the aid of carrier-gas sublimation, in which the materials are applied at a pressure of between 10^{-5} mbar and 1 bar. A special case of this process is the OVJP (organic vapour jet printing) process, in which the materials are applied directly through a nozzle and thus structured (for example M. S. Arnold et al., *Appl. Phys. Lett.* 2008, 92, 053301).

Preference is furthermore given to an organic electroluminescent device, characterised in that one or more layers are produced from solution, such as, for example, by spin coating, or by means of any desired printing process, such as, for example, screen printing, flexographic printing or offset printing, but particularly preferably LITI (light induced thermal imaging, thermal transfer printing) or ink-jet printing. Soluble compounds, which are obtained, if necessary, by suitable substitution, are necessary for this purpose.

These processes are generally known to the person skilled in the art and can be applied by him without problems to organic electroluminescent devices comprising compounds of the formula I or II, as defined above.

The compounds according to the invention described above, in particular compounds which are substituted or functionalised by reactive groups, can be used as monomers for the preparation of corresponding oligomers, dendrimers or polymers.

65

The invention therefore furthermore relates to oligomers, polymers or dendrimers comprising one or more compounds of the formula I or II, as defined above, where one or more bonds are present from the compounds of the formula I or II to the polymer, oligomer or dendrimer. Depending on the linking of the compound of the formula I or II, the complex therefore forms a side chain of the oligomer or polymer or is linked in the main chain. The polymers, oligomers or dendrimers may be conjugated, partially conjugated or non-conjugated. The oligomers or polymers may be linear, branched or dendritic.

For the preparation of the oligomers or polymers, the functionalised compounds of the formula I or II are homopolymerised or copolymerised with further monomers. Preference is given to copolymers, where the compounds of the formula I or II are present to the extent of 0.01 to 50 mol %, particularly preferably in the range from 0.1 to 20 mol %. Suitable and preferred comonomers which form the polymer backbone are selected from fluorenes (for example in accordance with EP 842208 or WO 00/22026), spirobifluorenes (for example in accordance with EP 707020, EP 894107 or WO 06/061181), para-phenylenes (for example in accordance with WO 92/18552), carbazoles (for example in accordance with WO 04/070772 or WO 04/113468), thiophenes (for example in accordance with EP 1028136), dihydrophenanthrenes (for example in accordance with WO 05/014689), cis- and trans-indenofluorenes (for example in accordance with WO 04/041901 or WO 04/113412), ketones (for example in accordance with WO 05/040302), phenanthrenes (for example in accordance with WO 05/104264 or WO 07/017,066) or also a plurality of these units. The proportion of these units in total is preferably in the region of at least 50 mol %. The polymers, oligomers and dendrimers may also contain further units, for example hole-transport units, in particular those based on triaryl amines, and/or electron-transport units.

Polymers comprising compounds of the general formula I or II can be used for the production of PLEDs, in particular as emitter layer in PLEDs. A polymeric emitter layer can be produced, for example, by coating from solution (spin coating or printing processes).

The compounds according to the invention and the organic electroluminescent devices produced therewith are distinguished by the following surprising advantages over the prior art:

In contrast to many metal complexes in accordance with the prior art, which undergo partial or complete pyrolytic decomposition on sublimation, the compounds according to the invention have high thermal stability.

The use of bulky substituents on the aromatic or heteroaromatic ring systems prevents aggregation of the complexes and thus the formation of excimers or exciplexes to be substantially suppressed.

Organic electroluminescent devices comprising compounds of the formula I or II as emitting materials have an excellent lifetime.

Blue-, red- and green-phosphorescent complexes which have an efficient dark-blue, red or even green emission colour and have a long lifetime on use in organic electroluminescent devices are accessible. This is a significant advance over the prior art, since blue-, red- and green-phosphorescent devices were hitherto frequently accessible with poor colour coordinates and in particular a poor lifetime.

66

The compounds according to the invention, employed in organic electroluminescent devices, result in high efficiencies and steep current-voltage curves at the same time as low use voltages.

These above-mentioned advantages are not accompanied by an impairment of the other electronic properties.


The invention is explained in greater detail by the following examples, without wishing to restrict it thereby. The person skilled in the art will be able to synthesise further compounds according to the invention without inventive step and employ them in organic electroluminescent devices.

EXAMPLES

The following syntheses are carried out under a protective-gas atmosphere in dried solvents, unless indicated otherwise. The starting materials used are, for example, 6-phenylpyridine-2-carboxaldehyde (J. Am. Chem. Soc. 2003, 125(8), 2113-2128), 2-biphenylamine (Tetrahedron Lett. 2008, 49(9), 1555-1558), 3-pyridin-2-ylbenzaldehyde (Org. Lett. 2004, 6(19), 3337-3340), 2-chloro-8-nitroquinoline (Austrian J. Chem. 2003, 56(1), 39-44).


Example 1

Synthetic Procedure for Metal Complex (1)




67

-continued



68

-continued



1st Step: Ligand Synthesis


The ligand synthesis is carried out utilising azeotropic distillation for removal of the water formed. Firstly, 300 ml of dried toluene are heated to the boil in a distillation apparatus in a 500 ml three-necked flask with stirrer, internal thermometer and dropping funnel. A solution of 20 g (120 mmol) of 2-biphenylamine in 50 ml of dried toluene and a solution of 21.9 g (120 mmol) of 6-phenylpyridine-2-carboxaldehyde in 50 ml of toluene are subsequently slowly added dropwise. Catalytic amounts of p-toluenesulfonic acid are added to the mixture. The distillation is carried out until the clear condensed toluene appears. The residues of the solvent are removed in an oil-pump vacuum (130 Pa). The ligand is recrystallised from toluene and washed with MeOH, giving 31.5 g (94 mmol) of crystalline solid. The overall yield is 80%.

2nd Step: Complex Synthesis

A solution of 13.8 g (41.5 mmol) of imine ligand in 1300 ml of acetic acid is added to a solution of 17.2 g of K_2PtCl_4 (41.5 mmol) in 1300 ml of acetic acid under N_2 , and the mixture is stirred at 90° C. for 3 days. After 72 h, the precipitated solid is washed with cold methanol, dried in vacuo and subsequently recrystallised from absolute EtOH under a protective gas, giving 15.9 g (30 mmol) of crystalline solid. The overall yield is 73%.

Example 2

Synthetic Procedure for Metal Complex (8)



1st Step: Ligand Synthesis


The ligand synthesis is carried out utilising azeotropic distillation for removal of the water formed. Firstly, 300 ml of dried toluene are heated to the boil in a distillation apparatus in a 500 ml three-necked flask with stirrer, internal thermometer and dropping funnel. A solution of 20 g (120 mmol) of 2-biphenylamine in 50 ml of dried toluene and a solution of 21.9 g (120 mmol) of 3-pyridin-2-ylbenzaldehyde in 50 ml of toluene are subsequently slowly added dropwise. Catalytic amounts of p-toluenesulfonic acid are added to the mixture. The distillation is carried out until the clear condensed toluene appears. The residues of the solvent are removed in an oil-pump vacuum (130 Pa). The ligand is recrystallised from toluene and washed with MeOH, giving 30.1 g (90 mmol) of crystalline solid. The overall yield is 76%.

2nd Step: Complex Synthesis

A solution of 13.8 g (41.5 mmol) of imine ligand in 1300 ml of acetic acid is added to a solution of 17.2 g of K_2PtCl_4 (41.5 mmol) in 1300 ml of acetic acid under N_2 , and the mixture is stirred at 90° C. for 3 days. After 72 h, the precipitated solid is washed with cold methanol, dried in vacuo and subsequently recrystallised from absolute EtOH under a protective gas, giving 14.3 g (27 mmol) of crystalline solid. The overall yield is 66%.


Example 3

Synthetic Procedure for Metal Complex (30)



69

-continued



1st Step: 8-Nitro-2-naphthylquinoline

18.9 g (110.0 mmol) of 1-naphthylboronic acid, 22.9 g (110.0 mmol) of 2-chloro-8-nitroquinoline and 44.6 g (210.0 mmol) of tripotassium phosphate are suspended in 500 ml of toluene, 500 ml of dioxane and 500 ml of water. 913 mg (3.0 mmol) of tri-*o*-tolylphosphine and then 112 mg (0.5 mmol) of palladium(II) acetate are added to this suspension, and the reaction mixture is heated under reflux for 16 h. After cooling, the organic phase is separated off, filtered through silica gel, washed three times with 200 ml of water and subsequently evaporated to dryness. The yield is 26.4 g (87 mmol), corresponding to 80% of theory.

2nd Step: 8-Amino-2-naphthylquinoline

12.6 g (42 mmol) of 8-nitro-2-naphthylquinoline and 1.99 g of Pd/C (10%) are suspended in 200 ml of methanol. 8.4 g (222 mmol) of sodium borohydride are added in portions with stirring at 0° C. After stirring for 2 h, the clear solution is neutralised using dilute HCl. The solvent is then removed, and the resultant residue is washed vigorously with water and recrystallised from dioxane. The precipitate is filtered and dried in vacuo, giving 9.9 g (56.9 mmol) of crystalline solid. The overall yield is 88%.

3rd Step: 1-[(E)-8-Quinolinylimino)methyl]naphthalene

The ligand synthesis is carried out utilising azeotropic distillation for removal of the water formed. Firstly, 300 ml of

70

dried toluene are heated to the boil in a distillation apparatus in a 500 ml three-necked flask with stirrer, internal thermometer and dropping funnel. A solution of 32.4 g (120 mmol) of 8-amino-2-naphthylquinoline in 50 ml of dried toluene and a solution of 12.7 g (120 mmol) of benzaldehyde in 50 ml of toluene are subsequently slowly added dropwise. Catalytic amounts of *p*-toluenesulfonic acid are added to the mixture. The distillation is carried out until the clear condensed toluene appears. The residues of the solvent are removed in an oil-pump vacuum (130 Pa). The ligand is recrystallised from toluene and washed with MeOH, giving 32.1 g (89 mmol) of crystalline solid. The overall yield is 75%.

4th Step: Complex Synthesis

A solution of 14.8 g (41.5 mmol) of imine ligand in 1300 ml of acetic acid is added to a solution of 17.2 g of K₂PtCl₄ (41.5 mmol) in 1300 ml of acetic acid under N₂, and the mixture is stirred at 90° C. for 3 days. After 72 h, the precipitated solid is washed with cold methanol, dried in vacuo and subsequently recrystallised from absolute EtOH under protective gas, giving 13.4 g (24 mmol) of crystalline solid. The overall yield is 59%.

Example 4


Production and Characterisation of Organic Electroluminescent Devices

Electroluminescent devices according to the invention can be produced as described, for example, in WO 05/003253. The results for various OLEDs are compared here. The basic structure, the materials used, the degree of doping and their layer thicknesses are identical for better comparability. The first device example describes a comparative standard in accordance with the prior art, in which the emission layer consists of the host material spiro-ketone and the guest material (dopant) Ir(piq)₃ or a compound according to the invention. Furthermore, OLEDs having various structures are described, with the host material in each case being spiro-ketone. OLEDs having the following structure are produced analogously to the general process mentioned above:


Hole-injection layer (HIL)	20 nm of 2,2',7,7'-tetrakis(di- <i>para</i> -tolyl-amino)spiro-9,9'-bifluorene
Hole-transport layer (HTL)	20 nm of NPB (N-naphthyl-N-phenyl-4,4'-diaminobiphenyl)
Emission layer (EML)	40 nm of host: spiro-ketone (SK) (bis(9,9'-spirobifluorene-2-yl) ketone) Dopant: Ir(piq) ₃ (10% doping, vapour-deposited; synthesised in accordance with WO 03/0068526) or compounds according to the invention
Electron conductor (ETL)	20 nm of AlQ ₃ (tris(quinolinato)aluminium-(III))
Cathode	1 nm of LiF, 150 nm of Al on top.

71

The structures of Ir(piq)₃ and spiro-ketone are depicted below for clarity:



The compounds according to the invention are depicted below:



These as yet unoptimised OLEDs are characterised by standard methods. For this purpose, the electroluminescence spectra, the efficiency (measured in cd/A) as a function of the luminance, calculated from current-voltage-luminance characteristic lines (IUL characteristic lines), and the lifetime are determined.

Table 2 shows the results of the device measurement. The electroluminescent devices comprising the compounds according to the invention exhibit a longer lifetime with improved efficiency.


72

TABLE 2


Device results with spiro-ketone as host material and with Ir(piq) ₃ or compounds according to the invention as dopant						
Ex.	EML	Max. efficiency [cd/A]	Voltage at 1000 cd/m ²	CIE (x, y)	Lifetime, initial luminance 1000 cd/m ²	
5						
4a	SK: 10%	8	5.0	0.68/0.32	30000	
(comp.)						
10	4b	SK: 10%	8.5	5.2	0.68/0.32	36000
	Ex. 1					
	4c	SK: 10%	22	5.3	0.62/0.38	25000
	Ex. 3					

The invention claimed is:

1. A compound of the general formula I



or of the general formula II



wherein

M is a metal ion in oxidation state +2,

Ar, is, identically or differently on each occurrence, an aromatic or heteroaromatic ring system having 5 to 10 aromatic ring atoms, which is optionally substituted by a plurality of radicals R,

R is, identically or differently on each occurrence, H, D, F, Cl, Br, I, N(Ar¹)₂, N(R²)₂, CN, NO₂, Si(R²)₃, B(OR²)₂, C(=O)Ar¹, C(=O)R², P(=O)(Ar¹)₂, P(=O)(R²)₂, S(=O)Ar¹, S(=O)R², S(=O)₂Ar¹, S(=O)₂R², CR²=CR²Ar¹OSO₂R², a straight-chain alkyl, alkoxy or thioalkoxy group having 1 to 40 C atoms or a branched or cyclic alkyl, alkoxy or thioalkoxy group having 3 to 40 C atoms, each of which is optionally substituted by one or more radicals R², where one or more non-adjacent CH₂ groups is optionally replaced by R²C=CR², C=O, O, or S and where one or more H atoms is optionally replaced by D, F, Cl, Br, I, CN or NO₂, or an aromatic or heteroaromatic ring system having 5 to 60 aromatic ring atoms, which may in each case

73

be substituted by one or more radicals R^2 , or an aryloxy or heteroaryloxy group having 5 to 15 aromatic ring atoms, which is optionally substituted by one or more radicals R^2 , or a combination of these systems, where two or more substituents R optionally forms a mono- or polycyclic, aliphatic or aromatic ring system with one another,

Ar^1 is, identically or differently on each occurrence, an aromatic or heteroaromatic ring system having 5 to 40 aromatic ring atoms, which is optionally substituted by one or more non-aromatic radicals R,

Y is, identically or differently on each occurrence, C, N or P, with the proviso that either two C atoms and two N atoms or two C atoms and two P atoms are always bonded to the metal, and

R^1 is, identically or differently on each occurrence, H, D, F, CF_3 , CN, an alkyl, alkoxy or thioalkoxy group having 1 to 40 C atoms or a branched or cyclic alkyl, alkoxy or thioalkoxy group having 3 to 40 C atoms, each of which is optionally substituted by one or more radicals R^2 , where one or more non-adjacent CH_2 groups is optionally replaced by $R^2C=CR^2$, $C\equiv C$, $Si(R^2)_2$, $Ge(R^2)_2$, $Sn(R^2)_2$ and where one or more H atoms is optionally replaced by D, F, Cl, Br, I, CN or NO_2 , or an aromatic or heteroaromatic ring system having 5 to 60 aromatic ring atoms, which may in each case be substituted by one or more radicals R^2 , or an aryloxy or heteroaryloxy group having 5 to 60 aromatic ring atoms, which is optionally substituted by one or more radicals R^2 , or a combination of these systems, where R^1 may also form a mono- or polycyclic, aliphatic or aromatic ring system with R, and

R^2 is, identically or differently on each occurrence, H, D, F, CN or an aliphatic, aromatic and/or heteroaromatic hydrocarbon radical having 1 to 20 C atoms, in which, in addition, one or more H atoms is optionally replaced by F, where two or more substituents R^2 also form a mono- or polycyclic, aliphatic or aromatic ring system with one another.

2. The compound according to claim 1, wherein M is Pt or Pd.

3. The compound according to claim 1, wherein M is Pt.

4. The compound according to claim 1, wherein

M is Pt,

Y is, identically or differently on each occurrence, C or N, with the proviso that two C atoms and two N atoms are always bonded to the metal,

R is, identically or differently on each occurrence, H, $N(Ar^1)_2$, CN, a straight-chain alkyl group having 1 to 10 C atoms or an aromatic or heteroaromatic ring system having 5 to 15 aromatic ring atoms, each of which is optionally substituted by one or more radicals R^2 ,

R^1 is, identically or differently on each occurrence, H, D, CN, an alkyl group having 1 to 3 C atoms or an aromatic or heteroaromatic ring system having 5 to 10 aromatic ring atoms, each of which is optionally substituted by one or more radicals R^2 ,

R^2 is, identically or differently on each occurrence, H, F, CN or an aliphatic, aromatic and/or heteroaromatic hydrocarbon radical having 1 to 20 C atoms, where two or more substituents R^2 may also form a mono- or polycyclic, aliphatic or aromatic ring system with one another, and

74


Ar^1 is, identically or differently on each occurrence, an aromatic or heteroaromatic ring system having 5 to 40 aromatic ring atoms, which is optionally substituted by one or more non-aromatic radicals R.

5. The compound according to claim 1, wherein Ar is benzene, naphthalene, pyridine, pyrimidine, pyrazine, pyridazine, quinoline, isoquinoline, furan, thiophene, pyrrole, benzofuran, benzothiophene or indole.


6. The compound according to claim 1, wherein Ar is benzene, naphthalene, pyridine, quinoline or isoquinoline.

7. The compound according to claim 1, wherein the compound is of the formulae V to XVI:


formula V




formula VI



formula VII








formula VIII



75


-continued

**76**

-continued

formula IX


5



10

formula X

15




20

25

formula XI

30



35

40

formula XII

8. A oligomer, polymer or dendrimer comprising one or more compounds according to claim 1, where one or more bonds are present from the compounds of the formula I or II to the polymer, oligomer or dendrimer.

45

9. A process for the preparation of the compound according to claim 1, which comprises reacting a free ligand with a corresponding metal salt to give the complex.

50

10. A layer comprising one or more of the compounds according to claim 1.


11. The compound according to claim 1, wherein the compound is of the formula III or IV:

formula XIII

55

formula III


60



65

77

-continued



wherein

X is CR or N.

12. The compound according to claim **11**, wherein a maximum of two symbols X per ring stand for N and the other symbols X in this ring stand for CR.

78

formula IV

13. An electronic device comprising one or more compounds according to claim **1**.

14. The electronic device as claimed in claim **13**, wherein the electronic device is an organic electroluminescent device or polymeric electroluminescent device (OLED, PLED), an organic integrated circuit (O-IC), an organic field-effect transistor (O-FET), an organic thin-film transistor (O-TFT), an organic light-emitting transistor (O-LET), an organic solar cell (O-SC), an organic optical detector, an organic photoreceptor, an organic field-quench device (O-FQD), a light-emitting electrochemical cell (LEC) or an organic laser diodes (O-laser).


15. An organic electroluminescent device according to claim **14**, wherein the compound is employed as emitting compound in an emitting layer or as charge-transport compound in a charge-transport or charge-injection layer.

* * * * *

专利名称(译)	用于有机电致发光器件的材料		
公开(公告)号	US8597798	公开(公告)日	2013-12-03
申请号	US13/001234	申请日	2009-10-15
申请(专利权)人(译)	MERCK PATENT GMBH		
当前申请(专利权)人(译)	MERCK PATENT GMBH		
[标]发明人	PARHAM AMIR HOSSAIN BUESING ARNE GERHARD ANJA KAISER JOACHIM FORTTE ROCCO		
发明人	PARHAM, AMIR HOSSAIN BUESING, ARNE GERHARD, ANJA KAISER, JOACHIM FORTTE, ROCCO		
IPC分类号	H01L51/54 C09K11/06		
CPC分类号	C07F15/006 C07F15/0086 C09K11/06 H01L51/0087 H05B33/14 C09B23/14 C09B23/145 C09B55/003 C09B57/00 C09B57/10 C09K2211/1022 C09K2211/1029 C09K2211/185 H01L51/0081 Y02E10/549		
优先权	102008057050 2008-11-13 DE		
其他公开文献	US20110095281A1		
外部链接	Espacenet USPTO		

摘要(译)

本发明涉及通式I或II的过渡金属配合物，特别是作为有机电子器件中的发光体分子，涉及包含本发明化合物的层和电子器件，以及制备方法根据本发明的化合物。



formula I