



US 20120280215A1

(19) **United States**(12) **Patent Application Publication**
CHOI et al.(10) **Pub. No.: US 2012/0280215 A1**(43) **Pub. Date: Nov. 8, 2012**(54) **ORGANIC LIGHT-EMITTING DISPLAY
APPARATUS**(76) Inventors: **Jun-Ho CHOI**, Yongin-City (KR);
Jin-Koo Chung, Yongin-City (KR);
Gun-Shik Kim, Yongin-city (KR)(21) Appl. No.: **13/268,273**(22) Filed: **Oct. 7, 2011**(30) **Foreign Application Priority Data**

May 3, 2011 (KR) 10-2011-0041991

Publication Classification(51) **Int. Cl.**
H01L 27/32 (2006.01)(52) **U.S. Cl.** **257/40; 257/E27.119**(57) **ABSTRACT**

An organic light-emitting display apparatus including: a substrate; a plurality of pixels on a first surface of the substrate, each pixel of the pixels having a first region in which visible rays are emitted and a second region through which external light penetrates, such that the plurality of pixels provide a plurality of first and second regions; a plurality of pixel circuit units in the first region of each pixel, each pixel circuit unit of the pixel circuit units including at least one thin film transistor (TFT); a plurality of first electrodes independently disposed in the first region of each pixel, each first electrode of the first electrodes being electrically connected to each pixel circuit unit; a second electrode facing the first electrodes, the second electrode being electrically connected throughout the pixels; and an intermediate layer including an organic emitting layer between the first electrodes and the second electrode.




FIG. 1




FIG. 2




FIG. 3




FIG. 4





FIG. 5






FIG. 7





FIG. 10



ORGANIC LIGHT-EMITTING DISPLAY APPARATUS

CROSS-REFERENCE TO RELATED PATENT APPLICATION

[0001] This application claims the benefit of Korean Patent Application No. 10-2011-0041991, filed on May 3, 2011, in the Korean Intellectual Property Office, the disclosure of which is incorporated herein in its entirety by reference.

BACKGROUND

[0002] 1. Field

[0003] Embodiments relate to an organic light-emitting display apparatus.

[0004] 2. Description of the Related Art

[0005] Display apparatuses are being replaced with portable, slim flat panel display apparatuses. Among various flat panel display apparatuses, an organic light-emitting display apparatus is a self-luminescent display apparatus having wide viewing angles, excellent contrast, and short response times. Therefore, an organic light-emitting display apparatus may be applied to various fields.

SUMMARY

[0006] According to an embodiment, there may be an organic light-emitting display apparatus including a substrate; a plurality of pixels on a first surface of the substrate, each pixel of the plurality of pixels having a first region in which visible rays are emitted and a second region through which external light penetrates, such that the plurality of pixels provide a plurality of first and second regions; a plurality of pixel circuit units in the first region of each pixel, each pixel circuit unit of the plurality of pixel circuit units including at least one thin film transistor (TFT); a plurality of first electrodes independently disposed in the first region of each pixel, each first electrode of the plurality of first electrodes being electrically connected to each pixel circuit unit; a second electrode facing the first electrodes, the second electrode being electrically connected throughout the pixels; and an intermediate layer including an organic emitting layer between the first electrodes and the second electrode, wherein second regions included in at least two adjacent pixels of the pixels in a first direction are integrally connected to form a plurality of second region groups obliquely disposed relative to each other in the first direction.

[0007] Every second one of the plurality of second region groups is mutually aligned in the first direction.

[0008] Second region groups adjacent to each other in a second direction perpendicular to the first direction may be parallel to each other.

[0009] The second region groups may be formed by integrally connecting second regions included in three adjacent pixels in the first direction.

[0010] At least two second region groups adjacent to each other in a second direction perpendicular to the first direction may be integrally connected to form a plurality of second region group sets.

[0011] The second region group sets may be obliquely disposed relative to each other in the first direction.

[0012] Every second one of the plurality of second region group sets may be mutually aligned in the first direction.

[0013] The second region group sets adjacent to each other in the second direction perpendicular to the first direction may be parallel to each other.

[0014] The first electrodes may include light penetration electrodes.

[0015] The first electrodes may include light reflection electrodes.

[0016] The second electrode may include a plurality of first penetration windows in positions corresponding to the second regions.

[0017] The first penetration windows may be formed corresponding to the second region groups.

[0018] The organic light-emitting display apparatus may further include: at least one insulation film between the substrate and the second electrode, wherein the insulation film includes a plurality of second penetration windows corresponding to the plurality of second region groups.

[0019] The first region of each pixel may include a light-emitting region and a circuit region, the at least one TFT is disposed in the circuit region, the plurality of first electrodes are disposed in the light-emitting region, and the light-emitting region and the circuit region of each pixel are adjacent to each other.

[0020] The first region of each pixel may include a light-emitting region and a circuit region, the plurality of pixel circuit units are disposed in the circuit region, the plurality of first electrodes are disposed in the light-emitting region, and the light-emitting region overlaps the circuit region to cover the circuit-region.

[0021] A first area of each first electrode of each pixel may be a same area as a second area of the first region.

BRIEF DESCRIPTION OF THE DRAWINGS

[0022] The above and other features will become more apparent by describing in detail exemplary embodiments thereof with reference to the attached drawings in which:

[0023] FIG. 1 is a schematic cross-sectional view of an organic light-emitting display apparatus according to an embodiment;

[0024] FIG. 2 is a schematic cross-sectional view of an organic light-emitting display apparatus according to another embodiment;

[0025] FIG. 3 is a cross-sectional view illustrating in detail the organic light-emitting display apparatus of FIG. 1 or 2, according to an embodiment;

[0026] FIG. 4 is a cross-sectional view illustrating in detail the organic light-emitting display apparatus of FIG. 1 or 2, according to another embodiment;

[0027] FIG. 5 is a schematic plan view of an organic light-emitter of FIG. 3 or 4, according to an embodiment;

[0028] FIG. 6 is a cross-sectional view of a pixel of the organic light-emitter of FIG. 5, according to an embodiment;

[0029] FIG. 7 is a schematic plan view of the organic light-emitter of FIG. 3 or 4, according to another embodiment;

[0030] FIG. 8 is a cross-sectional view of a pixel of the organic light-emitter of FIG. 7, according to another embodiment;

[0031] FIG. 9 is a cross-sectional view of a pixel of the organic light-emitter of FIG. 7, according to another embodiment; and

[0032] FIG. 10 is a schematic plan view of the organic light-emitter of FIG. 3 or 4, according to another embodiment.

DETAILED DESCRIPTION

[0033] Example embodiments will now be described more fully hereinafter with reference to the accompanying drawings; however, they may be embodied in different forms and should not be construed as limited to the embodiments set forth herein.

[0034] FIG. 1 is a schematic cross-sectional view of an organic light-emitting display apparatus according to an embodiment.

[0035] Referring to FIG. 1, the organic light-emitting display apparatus includes a display unit 2 disposed on a substrate 1.

[0036] In the organic light-emitting display apparatus, an external light penetrates through the substrate 1 and the display unit 2. Also, the display unit 2 is configured such that the external light penetrates therethrough. As shown in FIG. 1, a user located at a side where an image is realized may be able to view an image of an upper external side of the substrate 1.

[0037] The organic light-emitting display apparatus of FIG. 1 is a bottom-emission type, wherein the image of the display unit 2 is realized toward the substrate 1. Alternatively, as shown in FIG. 2, the organic light-emitting display apparatus may be a top-emission type, wherein the image of the display unit 2 is realized in an opposite direction of the substrate 1. Here, the user may view the image of the display unit 2 above the substrate 1, and an external image under the substrate 1. However, the type of the organic light-emitting display apparatus is not limited thereto. The type of the organic light-emitting display apparatus may be a two-sided emission type, wherein the image of the display unit 2 is realized toward and in an opposite direction of the substrate 1.

[0038] FIGS. 1 and 2 show a first pixel P1 and a second pixel P2, which are two adjacent pixels of the organic light-emitting display apparatus.

[0039] Each of the first and second pixels P1 and P2 includes a first region 31 and a second region 32. The image is formed on the display unit 2 through the first region 31, and the external light penetrates through the second region 32.

[0040] In other words, both the first and second pixels P1 and P2 include the first region 31 that realizes the image and the second region 32 through which the external light penetrates. Thus, the user may view an external image when not viewing the image formed on the display unit 2.

[0041] Here, devices, such as a thin film transistor (TFT), a capacitor, and an organic light-emitting device, are not formed in the second region 32 so as to maximize external light transmittance in the second region 32, thereby increasing external light transmittance of the display unit 2. Also, distortion of an external penetrated image due to the devices, i.e., the TFT, the capacitor, and the organic light-emitting device, may be reduced.

[0042] FIG. 3 is a cross-sectional view illustrating in detail the organic light-emitting display apparatus of FIG. 1 or 2, according to an embodiment. Referring to FIG. 3, the display unit 2 includes an organic light-emitter 21 formed on a first surface 11 of the substrate 1 and a sealing substrate 23 sealing the organic light-emitter 21.

[0043] The sealing substrate 23 is formed of a transparent material so that the image is realized from the organic light-

emitter, and prevents any external air or moisture from penetrating into the organic light-emitter.

[0044] Boundaries of the substrate 1 and the display unit 2 are combined with the sealing material 24. Thus, a space 25 between the substrate 1 and the sealing substrate 23 are sealed. A moisture absorbent or a filling material may be disposed in the space 25.

[0045] As shown in FIG. 4, a sealing film 26, instead of the sealing substrate 23, may be formed on the organic light-emitter 21 so as to protect the organic light-emitter 21 from external air. The sealing film 26 may have a structure in which a film formed of an inorganic material, and a film formed of an organic material, are alternately stacked on each other. However, the structure of the sealing film 26 is not limited thereto, and may have any sealing structure formed of a transparent thin film.

[0046] Although not shown, the sealing substrate 23 of FIG. 3 may be formed on the sealing film 26 of FIG. 4 as a sealing structure with respect to the organic light-emitter 21.

[0047] Reflection prevention films for preventing external light from being reflected may be respectively formed in a bottom surface of the substrate 1 and a top external surface of the display unit 2.

[0048] Next, the organic light-emitter 21 according to embodiments will be described.

[0049] FIG. 5 is a schematic plan view of the organic light-emitter 21 of FIG. 3 or 4, according to an embodiment. More specifically, FIG. 5 is a schematic plan view of a first pixel P1, a second pixel P2, a third pixel P3, a fourth pixel P4, a fifth pixel P5, a sixth pixel P6, a seventh pixel P7, an eighth pixel P8, a ninth pixel P9, a tenth pixel P10, an eleventh pixel P11, a twelfth pixel P12, a thirteenth pixel P13, a fourteenth pixel P14, a fifteenth pixel P15, a sixteenth pixel P16, a seventeenth pixel P17, and an eighteenth pixel P18 of the organic light-emitter 21 that are adjacent to each other.

[0050] Each of the first through eighteenth pixels P1 through P18 includes a circuit region 311 and a light-emitting region 312 in the first region 31. The circuit region 311 and the light-emitting region 312 are disposed to be adjacent to each other.

[0051] Also, the second regions 32 allowing the external light to penetrate therethrough are disposed to be adjacent to the first regions 31. Second region groups 32A, 32B, 32C, 32D, 32E, and 32F are formed by integrally connecting the second regions 32 that are adjacent to each other.

[0052] For descriptive convenience, in FIG. 5, no reference numeral denotes the second regions 32 for a pixel as shown in FIGS. 1 and 2, and the second regions 32 are shown as the second region groups 32A, 32B, 32C, 32D, 32E, and 32F formed by integrally connecting the second regions 32 that are adjacent to each other.

[0053] The second region groups 32A, 32B, 32C, 32D, 32E, and 32F will now be described in detail below.

[0054] The first pixel P1, the second pixel P2, and the third pixel P3 are adjacent to each other in a first direction (in an X axial direction of FIG. 5). The second regions included in the first pixel P1, the second pixel P2, and the third pixel P3 are integrally connected to form the second region group A 32A.

[0055] The pixel P4, the fifth pixel P5, and the sixth pixel P6 are adjacent to each other in the first direction. The second regions included in the pixel P4, the fifth pixel P5, and the sixth pixel P6 are integrally connected to form the second region group B 32B.

[0056] The seventh pixel P7, the eighth pixel P8, and the ninth pixel P9 are adjacent to each other in the first direction. The second regions included in the seventh pixel P7, the eighth pixel P8, and the ninth pixel P9 are integrally connected to form the second region group C 32C.

[0057] The tenth pixel P10, the eleventh pixel P11, and the twelfth pixel P12 that are adjacent to the first pixel P1, the second pixel P2, and the third pixel P3 in a second direction (in a Y axial direction of FIG. 5) are adjacent to each other in the first direction (in the X axial direction of FIG. 5). The second regions included in the tenth pixel P10, the eleventh pixel P11, and the twelfth pixel P12 are integrally connected to form the second region group D 32D.

[0058] The thirteenth pixel P13, the fourteenth pixel P14, and the fifteenth pixel P15 that are adjacent to the fourth pixel P4, the fifth pixel P5, and the sixth pixel P6 in the second direction are adjacent to each other in the first direction. The second regions included in the thirteenth pixel P13, the fourteenth pixel P14, and the fifteenth pixel P15 are integrally connected to form the second region group E 32E.

[0059] The sixteenth pixel P16, the seventeenth pixel P17, and the eighteenth pixel P18 that are adjacent to the seventh pixel P7, the eighth pixel P8, and the ninth pixel P9 in the second direction are adjacent to each other in the first direction. The second regions included in the sixteenth pixel P16, the seventeenth pixel P17, and the eighteenth pixel P18 are integrally connected to form the second region group F 32F.

[0060] The second regions are connected to each other throughout three adjacent pixels, so that an area of the second regions through which the external light penetrates may be increased. Thus, transmittance of the display unit 2 may be increased.

[0061] Although the second regions are connected to each other throughout three adjacent pixels in FIG. 5, present embodiments are not limited thereto. The second regions may be integrally connected to each other throughout at least two adjacent pixels to form second region groups.

[0062] The second region groups 32A, 32B, 32C, 32D, 32E, and 32F are obliquely disposed relative to each other in the first direction. Every second one of the second region groups 32A, 32B, 32C, 32D, 32E, and 32F are disposed in line with each other in the first direction.

[0063] More specifically, the second region group A 32A, the second region group B 32B, and the second region group C 32C are not disposed in line with each other but are disposed obliquely relative to each other. However, the second region group A 32A and the second region group C 32C of every other line are disposed in line with each other. Although not shown, the arrangement of the second region group A 32A, the second region group B 32B, and the second region group C 32C may be continuously repeated.

[0064] The second region group D 32D, the second region group E 32E, and the second region group F 32F are not disposed in line with each other but are disposed obliquely relative to each other. However, the second region group D 32D and the second region group F 32F of every other line are disposed in line with each other. Although not shown, the arrangement of the second region group D 32D, the second region group E 32E, and the second region group F 32F may be continuously repeated.

[0065] The second region groups 32A, 32B, 32C, 32D, 32E, and 32F that are adjacent to each other in the second direction are disposed in parallel with each other.

[0066] That is, the second region group A 32A and the second region group D 32D are disposed in parallel with each other, the second region group B 32B and the second region group E 32E are disposed in parallel with each other, and the second region group C 32C and the second region group F 32F are disposed in parallel with each other.

[0067] If the second region groups 32A, 32B, 32C, 32D, 32E, and 32F are disposed in line with each other in the first direction, spaces between the second region groups 32A, 32B, 32C, 32D, 32E, and 32F disposed in line with each other in the first direction are much greater than those therebetween disposed in parallel with each other in the second direction. Thus, this may cause image distortion when a user views an image through the second region groups 32A, 32B, 32C, 32D, 32E, and 32F.

[0068] However, in present embodiments, the second region groups 32A, 32B, 32C, 32D, 32E, and 32F are disposed obliquely relative to each other in the first direction, in particular, every second one thereof are disposed in line with each other in the first direction. Thus, differences in the spaces therebetween in the first direction and in the second direction are reduced, thereby reducing the image distortion.

[0069] FIG. 6 is a cross-sectional view of the first pixel P1 of the first through eighteenth pixels P1 through P18 of FIG. 5, according to an embodiment. Referring to FIG. 6, a pixel circuit unit PC including a TFT TR is disposed in the circuit region 311. Although one TFT TR is shown in FIG. 6, present embodiments are not limited thereto. The pixel circuit unit PC may further include a plurality of other TFTs, aside from the TFT TR, a storage capacitor, and wires, i.e., a scan line, a data line, and a Vdd line, which are connected to the TFTs and the storage capacitor.

[0070] The organic light-emitting device EL constituting a light-emitting device is disposed in the light-emitting region 312. The organic light-emitting device EL is electrically connected to the TFT TR of the pixel circuit unit PC.

[0071] A buffer film 211 is formed on the substrate 1, and the pixel circuit unit PC including the TFT TR is formed on the buffer film 211.

[0072] First, a semiconductor active layer 212 is formed on the buffer film 211. The buffer film 211 is formed of any transparent insulating material, which prevents penetration of an impure element and smoothes a surface of the buffer film 211. For example, the buffer film 211 may be formed of an inorganic material, i.e., a silicon oxide, a silicon nitride, a silicon oxynitride, an aluminum oxide, an aluminum nitride, a titanium oxide, or a titanium nitride, an organic material, such as polyimide, polyester, acryl, or a stacked structure of the inorganic material and the organic material. The buffer film 211 is not an essential element, and may not be included.

[0073] The semiconductor active layer 212 may be formed of polycrystalline silicon, but is not limited thereto. The semiconductor active layer 212 may be formed of an oxide semiconductor. For example, the semiconductor active layer 212 may be a G—I—Z—O layer [(In₂O₃)_a(Ga₂O₃)_b(ZnO)_c layer], wherein a, b, and c are each a real number satisfying a ≥ 0, b ≥ 0, c > 0. When the semiconductor active layer 212 is formed of an oxide semiconductor, transmittance of external light of the circuit region 311 of the first region 31 may be increased. Thus, external light transmittance of the display unit 2 may be increased.

[0074] A gate insulation film 213, which is formed of a transparent insulating material, is formed on the buffer film

211 to cover the semiconductor active layer **212**. A gate electrode **214** is formed on the gate insulation film **213**.

[0075] An interlayer insulation film **215**, which is formed of a transparent insulating material, is formed on the gate insulation film **213** to cover the gate electrode **214**, and a source electrode **216** and a drain electrode **217** are formed on the interlayer insulation film **215**, each contacting the semiconductor active layer **212** via a hole.

[0076] The structure of the TFT TR is not limited thereto, and may vary.

[0077] A passivation film **218** is formed to cover the pixel circuit unit PC including the TFT TR. The passivation film **218** may be a single or plurality of insulation films, wherein a top surface is smooth. The passivation film **218** may be formed of a transparent inorganic insulating material and/or organic insulating material. The passivation film **218** may be formed throughout all pixels.

[0078] As shown in FIG. 6, a first electrode **221** of the organic light-emitting device EL electrically connected to the TFT TR is formed on the passivation film **218**. The first electrode **221** is formed in an individual and independent island form with respect to all pixels.

[0079] A pixel definition film **219** formed of an organic and/or inorganic insulating material is formed on the passivation film **218**. The pixel definition film **219** covers a boundary and exposes a predetermined region of the first electrode **221**. The pixel definition film **219** may cover the first region **31**, and may cover only a part of the first electrode **221**. The part of the first electrode **221** may specifically be the boundary of the first electrode **221**, and not the entire first region **31**.

[0080] An intermediate layer **223** and a second electrode **222** are sequentially stacked on the first electrode **221**. The second electrode **222** is formed on the intermediate layer **223** and the pixel definition film **219**, and is electrically connected throughout all pixels.

[0081] The organic light emitting layer included in the intermediate layer **223** may be a low molecular or high molecular organic film. The low molecular organic film may have a single or complex structure, in which a hole injection layer (HIL), a hole transport layer (HTL), an emission layer (EML), an electron transport layer (ETL), and an electron injection layer (EIL) are stacked on each other, and may be formed of an organic material, i.e., copper phthalocyanine (CuPc), N,N'-Di(naphthalene-1-yl)-N,N'-diphenyl-benzidine (NPB), or tris-8-hydroxyquinoline aluminum (Alq3). In this case, the intermediate layer **23** may be formed in various ways. Here, the HIL, the HTL, the ETL, and the EIL are common layers and may be formed in all pixels irrespective of their colors.

[0082] The first electrode **221** operates as an anode and the second electrode **222** operates as a cathode. Alternatively, polarities of the first and second electrodes **221** and **222** may be changed.

[0083] The first electrode **221** may be a transparent electrode and the second electrode **222** may be a reflective electrode. The first electrode **221** may be formed of indium tin oxide (ITO), an indium zinc oxide (IZO), zinc oxide (ZnO), or indium oxide (In₂O₃), which have a high work function. Also, the second electrode **222** may be formed of a metal having a low work function, i.e., silver (Ag), magnesium (Mg), aluminum (Al), platinum (Pt), palladium (Pd), gold (Au), nickel (Ni), neodymium (Nd), iridium (Ir), chromium (Cr), lithium (Li), or calcium (Ca). Accordingly, the organic

light-emitting device EL is a bottom emission type realizing an image in a direction of the first electrode **221**.

[0084] However, alternatively, the second electrode **222** may also be a transparent electrode.

[0085] As described above, the passivation film **218**, the gate insulation film **213**, the interlayer insulation film **215**, and the pixel definition film **219** may each be a transparent insulation film so as to increase external light transmittance. The sealing substrate **23** may be disposed above the second electrode **222**. As shown in FIG. 3, the sealing substrate **23** is combined to the substrate **1** by using the separate sealing material **24** in the boundary of the display unit **2**, so as to seal the organic light-emitter **21** from external air. A separate filling material (not shown) or a moisture absorbent may be disposed in a space between the sealing substrate **23** and the second electrode **222**. However, a sealing structure of the display unit **2** is not limited to using the sealing substrate **23** of FIG. 6. The sealing film of FIG. 3 may be alternatively used.

[0086] Meanwhile, the second electrode **222** and the pixel definition film **219** may respectively include a first penetrating window **224** and a second penetrating window **225**. The first penetrating window **224** may be formed by removing a portion of the second electrode **222**, which corresponds to the second region **32**. The second penetrating window **225** may be formed by removing a portion of the pixel definition film **219**, which corresponds to the second region **32**. The first and second penetrating windows **224** and **225** may be connected to each other.

[0087] The first penetrating window **224** and the second penetrating window **225** may be formed in island patterns. As shown in FIG. 5, the first penetrating window **224** and the second penetrating window **225** may be formed throughout adjacent pixels and, in particular, corresponding to the second region groups **32A**, **32B**, **32C**, **32D**, **32E**, and **32F**. In this regard, the first penetrating window **224** is only shown in FIG. 5 for descriptive convenience, the second penetrating window **225** may be formed in a pattern corresponding to the second region groups **32A**, **32B**, **32C**, **32D**, **32E**, and **32F**.

[0088] The second penetrating window **225** may be further formed in at least one of the passivation film **218**, the interlayer insulation film **215**, the gate insulation film **213**, and the buffer film **211**. However, the first and second penetrating windows **224** and **225** do not have to exist together, and any one of the first and second penetrating windows **224** and **225** may be formed. Here, only the first penetrating window **224** may be formed so as to increase transmittance of external light.

[0089] Present embodiments are not limited thereto, and the first penetrating window **224** and the second penetrating window **225** may be formed by removing predetermined thicknesses of portions of the second electrode **222** and the pixel definition film **219** corresponding to the second region **32** rather than completely removing the portions.

[0090] FIG. 7 is a schematic plan view of the organic light-emitter **21** of FIG. 3 or 4, according to an embodiment. More specifically, FIG. 7 is a schematic plan view of the first pixel P1, the second pixel P2, the third pixel P3, the fourth pixel P4, the fifth pixel P5, the sixth pixel P6, the seventh pixel P7, the eighth pixel P8, the ninth pixel P9, the tenth pixel P10, the eleventh pixel P11, the twelfth pixel P12, the thirteenth pixel P13, the fourteenth pixel P14, the fifteenth pixel P15, the

sixteenth pixel P16, the seventeenth pixel P17, and the eighteenth pixel P18 of the organic light-emitter 21 that are adjacent to each other.

[0091] Each of the first through eighteenth pixels P1 through P18 includes a circuit region 311 and a light-emitting region 312 in the first region 31. The circuit region 311 and the light-emitting region 312 are disposed to overlap with each other.

[0092] Also, the second regions, through which the external light penetrates, are disposed to be adjacent to the first regions 31. The second region groups 32A, 32B, 32C, 32D, 32E, and 32F are formed by integrally connecting the second regions 32 that are adjacent to each other.

[0093] The first through eighteenth pixels P1 through P18 each include the first electrode 221 that corresponds to the first region 31.

[0094] A scan line S extends in a first direction (in an X axial direction of FIG. 7) and is connected to each of the first through eighteenth pixels P1 through P18. First through third data lines D1 through D3 are electrically connected to the first electrodes 221 of the first through third pixels P1 through P3. A first Vdd line V1 is electrically connected to the first electrode 221 of the first pixel P1 and the first electrode 221 of the second pixel P2. A second Vdd line V2 is electrically connected to the first electrode 221 of the third pixel P3. Although not shown for descriptive convenience, data lines of the fourth through eighteenth pixels P4 through P18 and the first and second Vdd lines V1 and V2 are connected in a similar manner to the first through third pixels P1 through P3.

[0095] The second region groups 32A, 32B, 32C, 32D, 32E, and 32F will now be described in detail below.

[0096] The first pixel P1, the second pixel P2, and the third pixel P3 are adjacent to each other in the first direction (in the X axial direction of FIG. 7). The second regions included in the first pixel P1, the second pixel P2, and the third pixel P3 are integrally connected to form the second region group A 32A.

[0097] The pixel P4, the fifth pixel P5, and the sixth pixel P6 are adjacent to each other in the first direction. The second regions included in the pixel P4, the fifth pixel P5, and the sixth pixel P6 are integrally connected to form the second region group B 32B.

[0098] The seventh pixel P7, the eighth pixel P8, and the ninth pixel P9 are adjacent to each other in the first direction. The second regions included in the seventh pixel P7, the eighth pixel P8, and the ninth pixel P9 are integrally connected to form the second region group C 32C.

[0099] The tenth pixel P10, the eleventh pixel P11, and the twelfth pixel P12 that are adjacent to the first pixel P1, the second pixel P2, and the third pixel P3 in a second direction (in a Y axial direction of FIG. 7) are adjacent to each other in the first direction (in the X axial direction of FIG. 7). The second regions included in the tenth pixel P10, the eleventh pixel P11, and the twelfth pixel P12 are integrally connected to form the second region group D 32D.

[0100] The thirteenth pixel P13, the fourteenth pixel P14, and the fifteenth pixel P15 that are adjacent to the fourth pixel P4, the fifth pixel P5, and the sixth pixel P6 in the second direction are adjacent to each other in the first direction. The second regions included in the thirteenth pixel P13, the fourteenth pixel P14, and the fifteenth pixel P15 are integrally connected to form the second region group E 32E.

[0101] The sixteenth pixel P16, the seventeenth pixel P17, and the eighteenth pixel P18 that are adjacent to the seventh

pixel P7, the eighth pixel P8, and the ninth pixel P9 in the second direction are adjacent to each other in the first direction. The second regions included in the sixteenth pixel P16, the seventeenth pixel P17, and the eighteenth pixel P18 are integrally connected to form the second region group F 32F.

[0102] The second regions are connected to each other throughout three adjacent pixels, so that an area of the second regions through which the external light penetrates, and thus transmittance of the display unit 2 may be increased.

[0103] Although the second regions are connected to each other throughout three adjacent pixels in FIG. 7, present embodiments are not limited thereto. The second regions may be integrally connected to each other throughout at least two adjacent pixels to form second region groups.

[0104] The second region groups 32A, 32B, 32C, 32D, 32E, and 32F are obliquely disposed relative to each other in the first direction. Every second one of the second region groups 32A, 32B, 32C, 32D, 32E, and 32F are disposed in line with each other in the first direction.

[0105] More specifically, the second region group A 32A, the second region group B 32B, and the second region group C 32C are not disposed in line with each other but are disposed obliquely relative to each other. However, the second region group A 32A and the second region group C 32C of every other line are disposed in line with each other. Although not shown in FIG. 7, the arrangement of the second region group A 32A, the second region group B 32B, and the second region group C 32C may be continuously repeated.

[0106] The second region group D 32D, the second region group E 32E, and the second region group F 32F are not disposed in line with each other but are disposed obliquely relative to each other. However, the second region group D 32D and the second region group F 32F of every other line are disposed in line with each other. Although not shown in FIG. 7, the arrangement of the second region group D 32D, the second region group E 32E, and the second region group F 32F may be continuously repeated.

[0107] The second region groups 32A, 32B, 32C, 32D, 32E, and 32F that are adjacent to each other in the second direction are disposed in parallel with each other.

[0108] That is, the second region group A 32A and the second region group D 32D are disposed in parallel with each other, the second region group B 32B and the second region group E 32E are disposed in parallel with each other, and the second region group C 32C and the second region group F 32F are disposed in parallel with each other.

[0109] However, in the present embodiment, the second region groups 32A, 32B, 32C, 32D, 32E, and 32F are disposed obliquely relative to each other in the first direction, in particular, every second one thereof are disposed in line with each other in the first direction, and thus differences in the spaces therebetween in the first direction and in the second direction are reduced, thereby reducing image distortion.

[0110] FIG. 8 is a cross-sectional view of the first pixel P1 of the first through eighteenth pixels P1 through P18 of FIG. 7, according to an embodiment. Referring to FIG. 8, the pixel circuit unit PC including first and second TFTs TR1 and TR2 is disposed in the circuit region 311. Although now shown in FIG. 8, the pixel circuit unit PC may further include wires, such as a scan line, a data line, and a Vdd line.

[0111] Referring to FIG. 8, the buffer film 211 is formed on the first surface 11 of the substrate 1, and the first TFT TR1, a capacitor Cst, and the second TFT TR2 are formed on the buffer film 211.

[0112] First, a first semiconductor active layer **212a** and a second semiconductor active layer **212b** are formed on the buffer film **211**.

[0113] The first semiconductor active layer **212a** and the second semiconductor active layer **212b** may be formed of polycrystalline silicon, but is not limited thereto, and may be formed of an oxide semiconductor. For example, the semiconductor active layer **212** may be a G—I—Z—O layer [(In₂O₃)^a(Ga₂O₃)^b(ZnO)^c layer], wherein a, b, and c are each a real number satisfying $a \geq 0$, $b \geq 0$, $c > 0$.

[0114] The gate insulation film **213** is formed on the buffer film **211** to cover the first semiconductor active layer **212a** and the second semiconductor active layer **212b**, and a first gate electrode **214a** and a second gate electrode **214b** are formed on the gate insulation film **213**.

[0115] The interlayer insulation film **215** is formed on the gate insulation film **213** to cover the first gate electrode **214a** and the second gate electrode **214b**, and a first source electrode **216a**, a second source electrode **216b**, a first drain electrode **217a**, and a second source electrode **217b** are formed on the interlayer insulation film **215**, each contacting the first semiconductor active layer **212a** and the second semiconductor active layer **212b** via a hole.

[0116] The scan line S may be formed simultaneously with the formation of the first gate electrode **214a** and the second gate electrode **214b**. The first data line D1 may be formed to be simultaneously connected to the first source electrode **216a**. The first Vdd line V may be formed to be simultaneously connected to the second source electrode **216b**.

[0117] A bottom electrode **220a** of the capacitor Cst may be formed simultaneously with the formation of the first gate electrode **214a** and the second gate electrode **214b**. The top electrode **220b** of the capacitor Cst may be formed simultaneously with the formation of the first drain electrode **217a**.

[0118] The structures of the first TFT TR1, the capacitor Cst, and the second TFT TR2 are not limited thereto, and may vary. For example, the first TFT TR1 and the second TFT TR2 may have a top gate structure, whereas the first TFT TR1 and the second TFT TR2 may have a bottom gate structure in which the first gate electrode **214a** and the second gate electrode **214b** are disposed in bottom portions of the first semiconductor active layer **212a** and the second semiconductor active layer **212b**. All applicable structures of a TFT may be applied.

[0119] The passivation film **218** is formed to cover the first TFT TR1, the capacitor Cst, and the second TFT TR2. The passivation film **218** may be a single or plurality of insulation films, wherein a top surface is even. The passivation film **218** may be formed of an inorganic material and/or organic material.

[0120] The first electrode **221** is formed on the passivation film **218** to cover the first TFT TR1, the capacitor Cst, and the second TFT TR2. The first electrode **221** is connected to the second drain electrode **217b** of the second TFT TR2. The first electrode **221** is formed in an individual and independent island form according to all pixels as shown in FIG. 7.

[0121] The pixel definition film **219** is formed on the passivation film **218** to cover the boundary of the first electrode **221**. The intermediate layer **223** including the organic light emitting layer and the second electrode **222** are sequentially stacked on the first electrode **221**. The second electrode **222** may be formed throughout the first and second regions **31** and **32**.

[0122] The first electrode **221** operates as an anode and the second electrode **222** operates as a cathode, or alternatively, polarities of the first and second electrodes **221** and **222** may be changed.

[0123] The first electrode **221** has a size corresponding to the first region **31** according to pixels. The second electrode **222** may be a common electrode to cover all pixels.

[0124] According to an embodiment, the first electrode **221** may be a reflective electrode and the second electrode **222** may be a transparent electrode. Accordingly, the organic light-emitter **21** is a top emission type realizing an image in a direction of the second electrode **222**.

[0125] Accordingly, the first electrode **221** may include a reflective film formed of Ag, Mg, Al, Pt, Pd, Au, Ni, Nd, Ir, Cr, Li, Ca, or a compound thereof, and ITO, IZO, ZnO, or In₂O₃, which has a high work function. Meanwhile, the second electrode **222** may be formed of a metal having a low work function, such as Ag, Mg, Al, Pt, Pd, Au, Ni, Nd, Ir, Cr, Li, Ca, or an alloy thereof. The second electrode **222** may be formed as a thin film for high transmittance.

[0126] As such, when the first electrode **221** is a reflective electrode, the pixel circuit unit PC disposed below the first electrode **221** is covered by the first electrode **221**, and thus, a user at an upper outer side of the second electrode **222** is unable to view patterns of the first TFT TR1, the capacitor Cst, and the second TFT TR2, the scan line S, the first data line D, and the first Vdd line V1, which are below the first electrode **221**.

[0127] Since the first electrode **221** is the reflective electrode, an emitted light is only transmitted to the user, i.e., upward. Thus, the amount of light lost in an opposite direction of the user may be reduced. Also, as described above, since the first electrode **221** covers various patterns of a pixel circuit therebelow, the user is able to view a clear external image.

[0128] As described above, the passivation film **218**, the gate insulation film **213**, the interlayer insulation film **215**, and the pixel definition film **219** may be transparent insulation films to increase transmittance of external light.

[0129] Meanwhile, the first penetrating window **224** may be formed in a portion of the second electrode **222** of the second region group A **32A**. FIG. 9 is a cross-sectional view of a pixel of the organic light-emitter of FIG. 7, according to another embodiment. The second penetrating window **225** is further formed in the pixel definition film **219**. The second penetrating window **225** may be formed by removing a portion of the pixel definition film **219** corresponding to the second region group A **32A**. The first and second penetrating windows **224** and **225** may be connected to each other.

[0130] Although the first penetrating window **224** is only shown in FIG. 7, the second penetrating window **225** may be formed in the same pattern as the first penetrating window **224**.

[0131] The second penetrating window **225** may be further formed in at least one of the passivation film **218**, the interlayer insulation film **215**, the gate insulation film **213**, and the buffer film **211**. However, the first and second penetrating windows **224** and **225** do not have to exist together, and any one of the first and second penetrating windows **224** and **225** may be formed. Here, only the first penetrating window **224** may be formed so as to increase transmittance of external light.

[0132] Present embodiments are not limited thereto, and the first penetrating window **224** and the second penetrating window **225** may be formed by removing predetermined

thicknesses of portions of the second electrode **222** and the pixel definition film **219** corresponding to the second region **32** rather than completely removing the portions.

[0133] FIG. **10** is a schematic plan view of the organic light-emitter **21** of FIG. **3** or **4**, according to an embodiment. More specifically, FIG. **10** is a schematic plan view of the first pixel **P1**, the second pixel **P2**, the third pixel **P3**, the fourth pixel **P4**, the fifth pixel **P5**, the sixth pixel **P6**, the seventh pixel **P7**, the eighth pixel **P8**, the ninth pixel **P9**, the tenth pixel **P10**, the eleventh pixel **P11**, the twelfth pixel **P12**, the thirteenth pixel **P13**, the fourteenth pixel **P14**, the fifteenth pixel **P15**, the sixteenth pixel **P16**, the seventeenth pixel **P17**, and the eighteenth pixel **P18** of the organic light-emitter **21** that are adjacent to each other.

[0134] Each of the first through eighteenth pixels **P1** through **P18** includes a circuit region **311** and a light-emitting region **312** in the first region **31**. The circuit region **311** and the light-emitting region **312** are disposed to be adjacent to each other.

[0135] Also, the second regions allowing the external light to penetrate therethrough are disposed to be adjacent to the first regions **31**. A plurality of second region groups are formed by integrally connecting the second regions that are adjacent to each other. The second region groups are integrally connected to form second region group sets **32AA**, **32BB**, and **32CC**.

[0136] The second region group sets **32AA**, **32BB**, and **32CC** will now be described in detail below.

[0137] The first pixel **P1**, the second pixel **P2**, and the third pixel **P3** are adjacent to each other in a first direction (in an X axial direction of FIG. **10**). The second regions included in the first pixel **P1**, the second pixel **P2**, and the third pixel **P3** are integrally connected to form a second region group. The fourth pixel **P4**, the fifth pixel **P5**, and the sixth pixel **P6** that are adjacent to the first pixel **P1**, the second pixel **P2**, and the third pixel **P3** in a second direction (in a Y axial direction of FIG. **10**) are adjacent to each other in the first direction. The second regions included in the fourth pixel **P4**, the fifth pixel **P5**, and the sixth pixel **P6** are integrally connected to form another second region group. The second regions of the first through sixth pixels **P1** through **P6** are integrally connected to form the second region group set **AA 32AA**.

[0138] A center line **L1** of the second region group set **AA 32AA** may be a boundary of the first pixel **P1** and the fourth pixel **P4**, a boundary of the second pixel **P2** and the fifth pixel **P5**, and a boundary of the third pixel **P3** and the sixth pixel **P6**.

[0139] The seventh pixel **P7**, the eighth pixel **P8**, and the ninth pixel **P9** are adjacent to each other in the first direction (in the X axial direction of FIG. **10**). The second regions included in the seventh pixel **P7**, the eighth pixel **P8**, and the ninth pixel **P9** are integrally connected to form a second region group. The tenth pixel **P10**, the eleventh pixel **P11**, and the twelfth pixel **P12** that are adjacent to the seventh pixel **P7**, the eighth pixel **P8**, and the ninth pixel **P9** in the second direction (in the Y axial direction of FIG. **10**) are adjacent to each other in the first direction. The second regions included in the tenth pixel **P10**, the eleventh pixel **P11**, and the twelfth pixel **P12** are integrally connected to form another second region group. The second regions of the seventh through twelfth pixels **P7** through **P12** are integrally connected to form the second region group set **BB 32BB**.

[0140] The center line **L1** of the second region group set **BB 32BB** may be a boundary of the seventh pixel **P7** and the tenth

pixel **P10**, a boundary of the eighth pixel **P8** and the eleventh pixel **P11**, and a boundary of the ninth pixel **P11** and the twelfth pixel **P12**.

[0141] The thirteenth pixel **P13**, the fourteenth pixel **P14**, and the fifteenth pixel **P15** are adjacent to each other in the first direction (in the X axial direction of FIG. **10**). The second regions included in the thirteenth pixel **P13**, the fourteenth pixel **P14**, and the fifteenth pixel **P15** are integrally connected to form a second region group. The sixteenth pixel **P16**, the seventeenth pixel **P17**, and the eighteenth pixel **P18** that are adjacent to the thirteenth pixel **P13**, the fourteenth pixel **P14**, and the fifteenth pixel **P15** in the second direction (in the Y axial direction of FIG. **10**) are adjacent to each other in the first direction. The second regions included in the sixteenth pixel **P16**, the seventeenth pixel **P17**, and the eighteenth pixel **P18** are integrally connected to form another second region group. The second regions of the thirteenth through eighteenth pixels **P13** through **P18** are integrally connected to form the second region group set **CC 32CC**.

[0142] The center line **L1** of the second region group set **CC 32CC** may be a boundary of the thirteenth pixel **P13** and the sixteenth pixel **P16**, a boundary of the fourteenth pixel **P14** and the seventeenth pixel **P17**, and a boundary of the fifteenth pixel **P15** and the eighteenth pixel **P18**.

[0143] The second regions are connected to each other throughout six adjacent pixels to form the second region group sets **32AA**, **32BB**, and **32CC**, so that an area of the second regions through which the external light penetrates increases. Thus, transmittance of the display unit **2** may be increased.

[0144] The second region group sets **32AA**, **32BB**, and **32CC** are obliquely disposed relative to each other in the first direction. Every second one of the second region group sets **32AA**, **32BB**, and **32CC** are disposed in line with each other in the first direction.

[0145] More specifically, the second region group set **AA 32AA**, the second region group set **BB 32BB**, and the second region group set **CC 32CC** are not disposed in line with each other but are disposed obliquely relative to each other. However, the second region group set **AA 32AA** and the second region group set **CC 32CC** of every other line are disposed in line with each other. Although not shown in FIG. **10**, the arrangement of the second region group set **AA 32AA**, the second region group set **BB 32BB**, and the second region group set **CC 32CC** may be continuously repeated.

[0146] The second region group set **AA 32AA**, the second region group set **BB 32BB**, and the second region group set **CC 32CC** that are adjacent to each other in the second direction are disposed in parallel with each other.

[0147] In the present embodiment, the second region group set **AA 32AA**, the second region group set **BB 32BB**, and the second region group set **CC 32CC** are disposed obliquely relative to each other in the first direction. In particular, every second one thereof are disposed in line with each other in the first direction. Thus, differences in the spaces therebetween in the first direction and in the second direction are reduced, thereby reducing the image distortion.

[0148] By way of summation and review, an organic light-emitting apparatus may include a transparent display apparatus. However, when the organic light-emitting apparatus is used as the transparent display apparatus, a user sees light from the object or the image penetrating through an organic light-emitting device, a transparent thin film transistor (TFT), a pattern of several wires, and a space between the wires.

Hence, transmittances of the organic light-emitting diode of the organic light-emitting apparatus, the TFT, and the wires may not be high. In this regard, the space between the wires is very small, contributing to the transmittance of the organic light-emitting apparatus not being high.

[0149] In contrast, embodiments are directed to an organic light-emitting display apparatus with improved external light transmittance and image quality.

[0150] Exemplary embodiments have been disclosed herein, and although specific terms are employed, they are used and are to be interpreted in a generic and descriptive sense only and not for purpose of limitation.

What is claimed is:

1. An organic light-emitting display apparatus, comprising:

a substrate;

a plurality of pixels on a first surface of the substrate, each pixel of the plurality of pixels having a first region in which visible rays are emitted and a second region through which external light penetrates, such that the plurality of pixels provide a plurality of first and second regions;

a plurality of pixel circuit units in the first region of each pixel, each pixel circuit unit of the plurality of pixel circuit units including at least one thin film transistor (TFT);

a plurality of first electrodes independently disposed in the first region of each pixel, each first electrode of the plurality of first electrodes being electrically connected to each pixel circuit unit;

a second electrode facing the first electrodes, the second electrode being electrically connected throughout the pixels; and

an intermediate layer including an organic emitting layer between the first electrodes and the second electrode, wherein the second regions included in at least two adjacent pixels of the plurality of pixels in a first direction are integrally connected to form a plurality of second region groups obliquely disposed relative to each other in the first direction.

2. The organic light-emitting display apparatus as claimed in claim 1, wherein every second one of the plurality of second region groups is mutually aligned in the first direction.

3. The organic light-emitting display apparatus as claimed in claim 1, wherein second region groups adjacent to each other in a second direction perpendicular to the first direction are parallel to each other.

4. The organic light-emitting display apparatus as claimed in claim 1, wherein the second region groups are formed by integrally connecting second regions included in three adjacent pixels in the first direction.

5. The organic light-emitting display apparatus as claimed in claim 1, wherein at least two second region groups adjacent

to each other in a second direction perpendicular to the first direction are integrally connected to form a plurality of second region group sets.

6. The organic light-emitting display apparatus as claimed in claim 5, wherein the second region group sets are obliquely disposed relative to each other in the first direction.

7. The organic light-emitting display apparatus as claimed in claim 6, wherein every second one of the plurality of second region group sets is mutually aligned in the first direction.

8. The organic light-emitting display apparatus as claimed in claim 6, wherein the second region group sets adjacent to each other in the second direction perpendicular to the first direction are parallel to each other.

9. The organic light-emitting display apparatus as claimed in claim 1, wherein the first electrodes include light penetration electrodes.

10. The organic light-emitting display apparatus as claimed in claim 1, wherein the first electrodes include light reflection electrodes.

11. The organic light-emitting display apparatus as claimed in claim 1, wherein the second electrode includes a plurality of first penetration windows in positions corresponding to the second regions.

12. The organic light-emitting display apparatus as claimed in claim 11, wherein the first penetration windows are formed corresponding to the second region groups.

13. The organic light-emitting display apparatus as claimed in claim 12, further comprising at least one insulation film between the substrate and the second electrode,

wherein the insulation film includes a plurality of second penetration windows corresponding to the plurality of second region groups.

14. The organic light-emitting display apparatus as claimed in claim 1, wherein the first region of each pixel includes a light-emitting region and a circuit region, the at least one TFT is disposed in the circuit region, the plurality of first electrodes are disposed in the light-emitting region, and the light-emitting region and the circuit region of each pixel are adjacent to each other.

15. The organic light-emitting display apparatus as claimed in claim 1, wherein the first region of each pixel includes a light-emitting region and a circuit region, the plurality of pixel circuit units are disposed in the circuit region, the plurality of first electrodes are disposed in the light-emitting region, and the light-emitting region overlaps the circuit region to cover the circuit region.

16. The organic light-emitting display apparatus as claimed in claim 15, wherein a first area of each first electrode of each pixel is a same area as a second area of the first region.

* * * * *

专利名称(译)	有机发光显示装置		
公开(公告)号	US20120280215A1	公开(公告)日	2012-11-08
申请号	US13/268273	申请日	2011-10-07
[标]申请(专利权)人(译)	才俊HO 钟金KOO KIM GUN植		
申请(专利权)人(译)	CHOI JUN-HO 钟金辜 KIM GUN植		
当前申请(专利权)人(译)	CHOI JUN-HO 钟金辜 KIM GUN植		
[标]发明人	CHOI JUN HO CHUNG JIN KOO KIM GUN SHIK		
发明人	CHOI, JUN-HO CHUNG, JIN-KOO KIM, GUN-SHIK		
IPC分类号	H01L27/32		
CPC分类号	H01L27/326		
优先权	1020110041991 2011-05-03 KR		
其他公开文献	US8816331		
外部链接	Espacenet USPTO		

摘要(译)

一种有机发光显示装置，包括：基板；基板的第一表面上的多个像素，像素的每个像素具有发射可见光的第一区域和外部光穿过的第二区域，使得多个像素提供多个第一和第二区域；每个像素的第一区域中的多个像素电路单元，像素电路单元的每个像素电路单元包括至少一个薄膜晶体管（TFT）；多个第一电极独立地设置在每个像素的第一区域中，第一电极的每个第一电极电连接到每个像素电路单元；面向第一电极的第二电极，第二电极在整个像素中电连接；和包括在第一电极和第二电极之间的有机发光层的中间层。

