

(10) **Patent No.:** US 8,487,310 B2
(45) **Date of Patent:** Jul. 16, 2013

- | | | | | |
|--------------|------|--------|--------------------|---------|
| 2007/0031641 | A1 * | 2/2007 | Frisch et al. | 428/172 |
| 2007/0046186 | A1 * | 3/2007 | Kim | 313/504 |
| 2007/0200496 | A1 * | 8/2007 | Cok et al. | 313/512 |
| 2008/0012472 | A1 | 1/2008 | Uchida | |
| 2010/0007271 | A1 * | 1/2010 | Lee et al. | 313/504 |

- FOREIGN PATENT DOCUMENTS

- | | | |
|----|-----------------|--------|
| JP | 2010-118253 | 5/2010 |
| KR | 10-2004-0000629 | 1/2004 |
| KR | 2004000629 A * | 7/2004 |
| KR | 10-2006-0067049 | 6/2006 |
| KR | 10-2007-0079303 | 8/2007 |
| KR | 10-2009-0021443 | 3/2009 |

- ## OTHER PUBLICATIONS

- Lemmi, F., W. Chung, S. Lin, P.M. Smith, T. Sasagawa, B.C. Drews, A. Hua, J.R. Stern, and J.Y. Chen. "High-Performance TFTs Fabricated on Plastic Substrates." *IEEE Electron Device Letters* 25.7 (2004): 486-88.*

- * cited by examiner

- Primary Examiner* — Thomas L Dickey

- Assistant Examiner* — Joseph Schoenholtz

- (74) *Attorney, Agent, or Firm* — Robert E. Bushnell, Esq

- (57) **ABSTRACT**

- An organic light-emitting display apparatus comprises: a substrate in which a pixel region is defined; a thin film transistor (TFT) disposed on the substrate and spaced apart from the pixel region; a planarization pattern covering the TFT and spaced apart from the pixel region; a first electrode electrically connected to the TFT and formed so as to correspond to at least the pixel region; a pixel-defining layer formed on the first electrode so as to expose a predetermined region of the first electrode; an intermediate layer connected to the exposed region of the first electrode, including an organic emission layer, and formed to correspond to at least the pixel region; and a second electrode electrically connected to the intermediate layer.

- 20 Claims, 1 Drawing Sheet**

- U.S. PATENT DOCUMENTS

- | | | | | |
|--------------|------|--------|-----------------|---------|
| 2005/0116617 | A1 * | 6/2005 | Lee et al. | 313/500 |
| 2006/0097264 | A1 * | 5/2006 | Kim et al. | 257/72 |
| 2006/0125390 | A1 | 6/2006 | Oh | |




FIG. 1





FIG. 2



ORGANIC LIGHT-EMITTING DISPLAY APPARATUS

CLAIM OF PRIORITY

This application makes reference to, incorporates the same herein, and claims all benefits accruing under 35 U.S.C. § 119 from an application earlier filed in the Korean Intellectual Property Office on Oct. 26, 2010 and there duly assigned Serial No. 10-2010-0104742.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to an organic light-emitting display apparatus, and more particularly, to an organic light-emitting display apparatus capable of improving image quality.

2. Description of the Related Art

Recent display apparatuses tend to be replaced by thin portable flat panel display apparatuses. Organic electroluminescent display devices, as one of the self-emitting display devices from among flat panel display apparatuses, have drawn attention as next generation display devices due to advantages such as wide viewing angle, a good contrast, and fast response speeds.

An organic light-emitting display apparatus includes an organic light-emitting device having first and second electrodes. An intermediate layer includes an organic emission layer. When a voltage is applied to the first and second electrodes, the organic emission layer emits visible light.

A portion of the visible light emitted from the organic emission layer becomes extinct while sequentially passing through the first or second electrode and the other members, such as an insulating layer, a polarization layer, etc. Accordingly, the luminescent efficiency of organic light-emitting display apparatuses is decreased from the viewpoint of users, and thus there is a limit in improving the image quality of the organic light-emitting display apparatuses.

SUMMARY OF THE INVENTION

The present invention provides an organic light-emitting display apparatus in which image quality can be easily improved.

According to an aspect of the present invention, there is provided an organic light-emitting display apparatus comprising: a substrate in which a pixel region is defined; a thin film transistor (TFT) disposed on the substrate so as to be spaced apart from the pixel region; a planarization pattern covering the TFT and formed so as to be spaced apart from the pixel region; a first electrode electrically connected to the TFT and formed so as to correspond to at least the pixel region; a pixel-defining layer formed on the first electrode so as to expose a predetermined region of the first electrode; an intermediate layer connected to the exposed region of the first electrode, including an organic emission layer, and formed so as to correspond to at least the pixel region; and a second electrode electrically connected to the intermediate layer.

The TFT may include an active layer, a gate electrode insulated from the active layer, a source electrode, and a drain electrode, and the first electrode is connected to the drain electrode.

A gate insulating film may be disposed between the active layer and the gate electrode, and an interlayer insulating film is disposed between the gate electrode and the source electrode and between the gate electrode and the drain electrode.

In addition, the gate insulating film and the interlayer insulating film are covered by a planarization pattern within an area where the planarization pattern is formed.

An outer surface of the gate insulating film and an outer surface of the interlayer insulating film may be disposed on the same plane.

The pixel-defining layer may include projecting portions formed around the pixel region.

The projecting portion may project in a direction perpendicular to a thickness direction of the substrate.

The intermediate layer may contact side surfaces of the projecting portions.

The projecting portion may project toward the pixel region from a side of the planarization pattern.

The pixel-defining layer may be formed thinner than the planarization pattern.

The organic light-emitting display apparatus may further include an optical resonance insulating layer formed between the substrate and the first electrode in at least the pixel region.

The optical resonance insulating layer may be formed on the entire substrate.

The optical resonance insulating layer may have a structure in which a plurality of insulating layers are stacked.

The optical resonance insulating layer may have a structure in which a layer including SiO₂ and a layer including SiN_x are alternately stacked at least once.

The first electrode may be formed on the planarization pattern and include openings through which the planarization pattern is exposed.

The intermediate layer may be formed by using a printing method.

BRIEF DESCRIPTION OF THE DRAWINGS

A more complete appreciation of the invention, and many of the attendant advantages thereof, will be readily apparent as the same becomes better understood by reference to the following detailed description when considered in conjunction with the accompanying drawings, in which like reference symbols indicate the same or similar components, wherein:

FIG. 1 is a schematic cross-sectional view of an organic light-emitting display apparatus according to an embodiment of the present invention; and

FIG. 2 is a schematic cross-sectional view of an organic light-emitting display apparatus according to another embodiment of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

Hereinafter, exemplary embodiments of the present invention will be described in detail with reference to the accompanying drawings.

FIG. 1 is a schematic cross-sectional view of an organic light-emitting display apparatus according to an embodiment of the present invention.

Referring to FIG. 1, the organic light-emitting display apparatus 100 includes a substrate 101 in which a pixel region P is defined, a thin film transistor (TFT), a planarization pattern 109, and an organic light-emitting device 114. The organic light-emitting device 114 includes a first electrode 111, a second electrode 113, and an intermediate layer 112. The TFT includes an active layer 103, a gate electrode 105, a source electrode 107, and a drain electrode 108.

Hereinafter, each member will be described in detail.

The pixel region P is defined in the substrate 101. The pixel region P is where visible light is realized, and it overlaps the intermediate layer 112.

The substrate **101** may be formed of a transparent glass material, mainly including SiO₂. However, the present invention is not limited thereto, and thus the substrate **101** may be formed of a transparent plastic material. In this case, the plastic material for forming the substrate **101** may be an insulating organic material selected from the group consisting of polyethersulphone (PES), polyacrylate (PAR), polyetherimide (PEI), polyethylene naphthalate (PEN), polyethylene terephthalate (PET), polyphenylene sulfide (PPS), polyallylate, polyimide, polycarbonate (PC), cellulose triacetate (TAC), and cellulose acetate propionate (CAP).

An optical resonance insulating layer **102** is formed on the substrate **101**. The optical resonance insulating layer **102** may include SiO₂ or SiN_x. A part of light emitted from the intermediate layer **112** is reflected by an upper surface of the optical resonance insulating layer **102** toward the intermediate layer **112**, and the reflected light is reflected again by the second electrode **113**. Thus, optical resonance occurs in a space between the upper surface of the optical resonance insulating layer **102** and the second electrode **113**. In addition, a part of the light emitted from the intermediate layer **112** is also reflected by a lower surface of the optical resonance insulating layer **102**, that is, by a surface where the optical resonance insulating layer **102** contacts the substrate **101**. Thus, optical resonance occurs in a space between the lower surface of the optical resonance insulating layer **102** and the second electrode **113**. However, the present invention is not limited thereto, and the light emitted from the intermediate layer **112** generates optical resonance in a space between two interfaces from among the interfaces between two members selected from the group consisting of the substrate **101**, the optical resonance insulating layer **102**, the first electrode **111**, the intermediate layer **112**, and the second electrode **113**.

In addition, the optical resonance insulating layer **102** may have a structure in which a plurality of layers are stacked. That is, the optical resonance insulating layer **102** may be formed by alternately stacking two materials having different refractive indices. For example, the optical resonance insulating layer **102** may be formed by alternately stacking a layer including SiO₂ and a layer including SiN_x at least once. When the optical resonance insulating layer **102** has a structure in which a plurality of layers are stacked, each interface between the layers may function as a surface at which the light emitted from the intermediate layer **112** is reflected.

In addition, the optical resonance insulating layer **102** provides a flat surface on top of the substrate **101** and prevents moisture and foreign substances from penetrating into the substrate **101**.

The optical resonance insulating layer **102** may be formed on the entire substrate **101**.

The TFT is formed on the optical resonance insulating layer **102**. The TFT is formed so as to be spaced apart from the pixel region P.

The active layer **103** having a predetermined pattern is formed on the optical resonance insulating layer **102**. The active layer **103** may be formed of an inorganic semiconductor, such as amorphous silicon or polysilicon, or an organic semiconductor, and may include a source region, a drain region, and a channel region. A gate insulating film **104** is formed on the active layer **103**. The gate insulating film **104** is formed so as to be spaced apart from the pixel region P. The gate insulating film **104** is covered by the planarization pattern **109** within an area where the planarization pattern **109** is formed.

The gate electrode **105** is formed in a predetermined region on the gate insulating film **104**. The gate electrode **105** is connected to a gate line (not shown) for applying an ON/OFF

signal to the TFT. The gate electrode **105** may be formed of a metal, such as Au, Ag, Cu, Ni, Pt, Pd, Al, or Mo, or an alloy, such as Al:Nd or Mo:W, but the present invention is not limited thereto.

An interlayer insulating film **106** is formed on the gate electrode **105** so as to expose the source and drain regions of the active layer **103**. The source electrode **107** and the drain electrode **108** are formed so as to contact the exposed source region and the exposed drain region, respectively, of the active layer **103**.

The interlayer insulating film **106** is spaced apart from the pixel region P and is covered by the planarization pattern **109** within an area where the planarization pattern **109** is formed. The interlayer insulating film **106** also has the same pattern as the gate insulating film **104**. The patterns of the interlayer insulating film **106** and the gate insulating film **104** may be formed by performing a patterning process once. Thus, an outer surface of the interlayer insulating film **106** and an outer surface of the gate insulating film **104** may be positioned on the same plane. However, the present invention is not limited thereto, and thus the interlayer insulating film **106** and the gate insulating film **104** may be individually patterned.

The planarization pattern **109** is formed so as to cover the TFT and so as to be spaced apart from the pixel region P.

The planarization pattern **109** may be formed so as to have a thickness of more than 5000 Å in order to protect and insulate the TFT.

The planarization pattern **109** may also be formed so as to have a thickness of less than 2 μm in order to improve a patterning characteristic of the intermediate layer **112**.

The first electrode **111** is formed on the planarization pattern **109**. In detail, the planarization pattern **109** is formed so as to expose the drain electrode **108**, and the first electrode **111** is connected to the exposed drain electrode **108**. The first electrode **111** also extends so as to correspond to the pixel region P.

A pixel-defining layer **110** is formed on the first electrode **111**. The pixel-defining layer **110** includes various insulating materials and is formed so as to expose a predetermined region of the first electrode **111**. In detail, the pixel-defining layer **110** may be formed so as not to overlap the pixel region P. Thus, in the first electrode **111**, a region corresponding to the pixel region P is not covered by the pixel-defining layer **110**.

The pixel-defining layer **110** is formed so as to be thinner than the planarization pattern **109**. Grooves may be formed in a surface of the pixel-defining layer **110** so as to correspond to grooves formed below the pixel-defining layer **110** by forming the pixel-defining layer **110** relatively thin. The pixel-defining layer **110** is formed thin so as to facilitate patterning of the intermediate layer **112**. That is, the intermediate layer **112** may be exactly formed in a desired position by minimizing a difference in level between the pixel region P where the intermediate layer **112** is formed and an adjacent region.

In addition, the pixel-defining layer **110** is formed so as to have a thickness of more than 500 Å. When the pixel-defining layer **110** has a thickness of less than 500 Å, a problem of leakage current occurs in the organic light-emitting display apparatus **100**, and thus the pixel-defining layer **110** may be formed so as to have a thickness of more than 500 Å.

The pixel-defining layer **110** includes a projecting portion **110a**. The projecting portion **110a** projects in a direction perpendicular to a thickness direction of the substrate **101**. That is, the projecting portion **110a** projects toward the pixel region P from a side of the planarization pattern **109**. Also, the projecting portion **110a** may be formed around the pixel region P.

The intermediate layer 112 is formed on the first electrode 111. In detail, the intermediate layer 112 is formed so as to contact at least a region of the first electrode 111 corresponding to the pixel region P. The intermediate layer 112 includes an organic emission layer (not shown). The intermediate layer 112 may be formed by using any of various methods, for example, a printing method. As described above, the pixel-defining layer 110 is formed relatively thin so that a difference in level between the region where the intermediate layer 112 is to be formed and the other regions is reduced. Accordingly, the patterning of the intermediate layer 112 may be easily performed.

In addition, the intermediate layer 112 may be easily patterned so as to exactly correspond to the pixel region P due to the projecting portion 110a of the pixel-defining layer 110.

In particular, when the intermediate layer 112 is formed by using a printing method, the projecting portion 110a may prevent a material for forming the intermediate layer 112 from being disposed in an undesired region, that is, in portions corresponding to the side surfaces of the planarization pattern 109 adjacent to the pixel region P. Thus, the intermediate layer 112 may be easily disposed in the pixel region P. The intermediate layer 112 is formed so as to contact side surfaces of the projecting portion 110a.

In FIG. 1, the intermediate layer 112 is formed only on the side surfaces of the projecting portion 110a, but the present invention is not limited thereto. That is, the intermediate layer 112 may also be formed on an upper surface of the projecting portion 110a.

The second electrode 113 is formed on the intermediate layer 112. When a voltage is applied through the first electrode 111 and the second electrode 113, visible light is produced by the organic emission layer of the intermediate layer 112.

A sealing member (not shown) may be disposed on the second electrode 113. The sealing member may be formed so as to protect the intermediate layer 112 and other layers from external moisture or oxygen. The sealing member may be formed of a transparent material, such as a transparent glass or plastic, and the sealing member may be formed so as to have a structure in which an organic material and an inorganic material are stacked.

The organic light-emitting display apparatus 100 of the current embodiment includes the optical resonance insulating layer 102 corresponding to at least the pixel region P. A part of the light emitted from the intermediate layer 112 is reflected by an upper surface or a lower surface of the optical resonance insulating layer 102. Thus, optical resonance occurs in a space between the upper surface of the optical resonance insulating layer 102 and the second electrode 113, and in a space between the lower surface of the optical resonance insulating layer 102 and the second electrode 113. The optical resonance also occurs in a space between the optical resonance insulating layer 102 and the intermediate layer 112. Light amplified due to the optical resonance is extracted from the organic light-emitting display apparatus 100, and thus luminescent efficiency is improved, and consequently image quality is increased.

The organic light-emitting display apparatus 100 of the current embodiment may have a structure in which light is extracted toward a rear surface of the organic light-emitting display apparatus 100, that is, toward the substrate 101. The TFT is disposed so as to be spaced apart from the pixel region P from which the light is extracted, and the planarization pattern 109 covering the TFT is formed so as to be spaced apart from the pixel region P. Thus, optical resonance easily occurs in a space between the optical resonance insulating

layer 102 and the intermediate layer 112 without being interfered with by the planarization pattern 109 and the TFT, thereby improving image quality of the organic light-emitting display apparatus 100.

In addition, the pixel-defining layer 110 may be formed thin so that the intermediate layer 112 may be exactly disposed in a desired position. In particular, the intermediate layer 112 may be formed so as to completely fill a space where the intermediate layer 112 is to be formed. Thus, image quality of the organic light-emitting display apparatus 100 is improved.

In addition, the projecting portion 110a of the pixel-defining layer 110 prevents the intermediate layer 112 from being disposed in an undesired position, and thus the intermediate layer 112 may be uniformly formed in the entirety of the pixel region P, thereby realizing the organic light-emitting display apparatus 100 having uniform and improved image quality.

FIG. 2 is a schematic cross-sectional view of an organic light-emitting display apparatus 200 according to another embodiment of the present invention.

Referring to FIG. 2, the organic light-emitting display apparatus 200 includes a substrate 201 in which a pixel region P is defined, a TFT, a planarization pattern 209, and an organic light-emitting device 214. The organic light-emitting device 214 includes a first electrode 211, a second electrode 213, and an intermediate layer 212. The TFT includes an active layer 203, a gate electrode 205, a source electrode 207, and a drain electrode 208.

Hereinafter, each member will be described in detail.

The pixel region P is defined in the substrate 201. The pixel region P is where visible light is realized, and it overlaps at least the intermediate layer 212.

An optical resonance insulating layer 202 is formed on the substrate 201. The optical resonance insulating layer 202 may include SiO₂ or SiN_x. A part of light emitted from the intermediate layer 212 is reflected by an upper surface of the optical resonance insulating layer 202 toward the intermediate layer 212, and the reflected light is reflected again by the second electrode 213. Thus, optical resonance occurs in a space between the upper surface of the optical resonance insulating layer 202 and the second electrode 214. In addition, a part of the light emitted from the intermediate layer 212 is reflected by a lower surface of the optical resonance insulating layer 202, that is, by a surface where the optical resonance insulating layer 202 contacts the substrate 201. Thus, optical resonance occurs in a space between the lower surface of the optical resonance insulating layer 202 and the second electrode 214. However, the present invention is not limited thereto, and the light emitted from the intermediate layer 212 generates optical resonance in a space between two interfaces from among the interfaces between two members selected from the group consisting of the substrate 201, the optical resonance insulating layer 202, the first electrode 211, the intermediate layer 212, and the second electrode 213.

The optical resonance insulating layer 202 may have a structure in which a plurality of layers are stacked. That is, the optical resonance insulating layer 202 may be formed by alternately stacking two materials having different refractive indices. For example, the optical resonance insulating layer 202 may be formed by alternately stacking a layer including SiO₂ and a layer including SiN_x at least once. When the optical resonance insulating layer 202 has a structure in which a plurality of layers are stacked, each interface between the layers may function as a surface at which the light emitted from the intermediate layer 212 is reflected.

In addition, the optical resonance insulating layer **202** provides a flat surface on top of the substrate **201**, and prevents moisture and foreign substances from penetrating into the substrate **201**.

The optical resonance insulating layer **202** may be formed on the entire substrate **201**.

The TFT is formed on the optical resonance insulating layer **202**. The TFT is formed so as to be spaced apart from the pixel region P.

The active layer **203** having a predetermined pattern is formed on the optical resonance insulating layer **202**. A gate insulating film **204** is formed on the active layer **203** so as to be spaced apart from the pixel region P. The gate insulating film **204** is covered by the planarization pattern **209** within an area where the planarization pattern **209** is formed.

The gate electrode **205** is formed in a predetermined region on the gate insulating film **204**. The gate electrode **205** is connected to a gate line (not shown) for applying an ON/OFF signal to the TFT. The gate electrode **205** may be formed of a metal, such as Au, Ag, Cu, Ni, Pt, Pd, Al, or Mo, or an alloy, such as Al:Nd or Mo: W, but the present invention is not limited thereto.

An interlayer insulating film **206** is formed on the gate electrode **205** so as to expose the source and drain regions of the active layer **203**. The source electrode **207** and the drain electrode **208** are formed to contact the exposed source region and the exposed drain region, respectively, of the active layer **203**.

The interlayer insulating film **206** is spaced apart from the pixel region P and is covered by the planarization pattern **209** within an area where the planarization pattern **209** is formed. The interlayer insulating film **206** also has the same pattern as the gate insulating film **204**. The patterns of the interlayer insulating film **206** and the gate insulating film **204** may be formed by performing a patterning process once. Thus, an outer surface of the interlayer insulating film **206** and an outer surface of the gate insulating film **204** may be positioned on the same plane.

The planarization pattern **209** is formed so as to cover the TFT and so as to be spaced apart from the pixel region P.

The planarization pattern **209** may be formed so as to have a thickness of more than 5000 Å in order to protect and insulate the TFT. The planarization pattern **209** may also be formed to have a thickness of less than 2 μm in order to improve a patterning characteristic of the intermediate layer **212**.

The first electrode **211** is formed on the planarization pattern **209**. In detail, the planarization pattern **209** is formed so as to expose the drain electrode **208**, and the first electrode **211** is connected to the exposed drain electrode **208**. The first electrode **211** also extends so as to correspond to the pixel region P. The first electrode **211** includes openings **211a** through which the planarization pattern **209** is exposed. A high temperature process may be performed after forming the planarization pattern **209**. For example, the high temperature process may be performed when the intermediate layer **212** is formed by using a printing method. At this time, gas generated by the planarization pattern **209** may be easily discharged through the openings **211a**.

A pixel-defining layer **210** is formed on the first electrode **211**. The pixel-defining layer **210** includes various insulating materials and is formed so as to expose a predetermined region of the first electrode **211**. In detail, the pixel-defining layer **210** may be formed so as not to overlap the pixel region P. Thus, in first electrode **211**, a region corresponding to the pixel region P is not covered by the pixel-defining layer **210**.

The pixel-defining layer **210** is formed so as to be thinner than the planarization pattern **209**. Grooves may be formed in a surface of the pixel-defining layer **210** so as to correspond to grooves formed below the pixel-defining layer **210** by forming the pixel-defining layer **210** relatively thin. The pixel-defining layer **210** is formed thin so as to facilitate patterning of the intermediate layer **212**.

In addition, the pixel-defining layer **210** is formed so as to have a thickness of more than 500 Å. When the pixel-defining layer **210** has a thickness of less than 500 Å, a problem of leakage current occurs in the organic light-emitting display apparatus **200**, and thus the pixel-defining layer **210** may be formed so as to have a thickness of more than 500 Å.

The pixel-defining layer **210** includes a projecting portion **210a**. The projecting portion **210a** projects in a direction perpendicular to a thickness direction of the substrate **201**. That is, the projecting portion **210a** projects toward the pixel region P from a side of the planarization pattern **209**. Also, the projecting portion **210a** may be formed around the pixel region P.

The intermediate layer **212** is formed on the first electrode **211**. In detail, the intermediate layer **212** is formed so as to contact at least a region of the first electrode **211** corresponding to the pixel region P. The intermediate layer **212** includes an organic emission layer (not shown). The intermediate layer **212** may be formed by using any of various methods, for example, a printing method. As described above, the pixel-defining layer **210** is formed relatively thin so that a difference in level between the region where the intermediate layer **212** is to be formed and the other regions is reduced. Accordingly, the patterning of the intermediate layer **212** may be easily performed.

In addition, the intermediate layer **212** may be easily patterned so as to exactly correspond to the pixel region P due to the projecting portion **210a** of the pixel-defining layer **210**.

In particular, when the intermediate layer **212** is formed by using a printing method, the projecting portion **210a** may prevent a material for forming the intermediate layer **212** from being disposed in an undesired region, that is, in portions corresponding to the side surfaces of the planarization pattern **209** adjacent to the pixel region P. Thus, the intermediate layer **212** may be easily disposed in the pixel region P. The intermediate layer **212** is formed so as to contact side surfaces of the projecting portion **210a**.

In FIG. 2, the intermediate layer **212** is formed only on the side surfaces of the projecting portion **210a**, but the present invention is not limited thereto. That is, the intermediate layer **212** may also be formed on an upper surface of the projecting portion **210a**.

The second electrode **213** is formed on the intermediate layer **212**. When a voltage is applied through the first electrode **211** and the second electrode **213**, visible light is produced by the organic emission layer of the intermediate layer **212**.

A sealing member (not shown) may be disposed on the second electrode **213**. The sealing member may be formed so as to protect the intermediate layer **212** and other layers from external moisture or oxygen. The sealing member may be formed of a transparent material, such as a transparent glass or plastic, and the sealing member may be formed so as to have a structure in which an organic material and an inorganic material are stacked at least once.

The organic light-emitting display apparatus **200** of the current embodiment includes the optical resonance insulating layer **202** corresponding to at least the pixel region P. Light amplified due to the optical resonance is extracted from the

organic light-emitting display apparatus **200**, and thus luminescent efficiency is improved, and consequently, image quality is increased.

The organic light-emitting display apparatus **200** of the current embodiment may have a structure in which light is extracted toward a rear surface of the organic light-emitting display apparatus **200**, that is, toward the substrate **201**. The TFT is disposed so as to be spaced apart from the pixel region P from which the light is extracted, and the planarization pattern **209** covering the TFT is formed so as to be spaced apart from the pixel region P. Thus, optical resonance easily occurs in a space between the optical resonance insulating layer **202** and the intermediate layer **212** without being interfered with by the planarization pattern **209** and the TFT, thereby improving image quality of the organic light-emitting display apparatus **200**.

In addition, the pixel-defining layer **210** may be formed thin so that the intermediate layer **212** may be exactly disposed in a desired position. In particular, the intermediate layer **212** may be formed so as to completely fill a space where the intermediate layer **212** is to be formed. Thus, image quality of the organic light-emitting display apparatus **200** is improved.

In addition, the projecting portion **210a** of the pixel-defining layer **210** prevents the intermediate layer **212** from being disposed in an undesired position, and thus the intermediate layer **212** may be uniformly formed in the entirety of the pixel region P, thereby realizing the organic light-emitting display apparatus **200** having uniform and improved image quality.

In addition, openings **211a** may be formed in the first electrode **211** so as to easily perform out-gassing in the planarization pattern **209** in a high temperature process, and thus the organic light-emitting display apparatus **200** may be prevented from deteriorating due to impure gas.

The organic light-emitting display apparatus according to the present invention may easily improve image quality.

While the present invention has been particularly shown, and described with reference to exemplary embodiments thereof, it will be understood by those of ordinary skill in the art that various changes in form and detail may be made therein without departing from the spirit and scope of the present invention as defined by the following claims.

What is claimed is:

1. An organic light-emitting display apparatus, comprising:

- a substrate in which a pixel region is defined;
- a thin film transistor (TFT) disposed on the substrate and spaced apart from the pixel region;
- a planarization pattern covering the TFT and spaced apart from the pixel region, the planarization pattern having an opening and sidewalls about the opening, the pixel region being arranged within the opening;
- a first electrode electrically connected to the TFT and formed so as to correspond to at least the pixel region, the first electrode being arranged on the planarization pattern and on sidewalls of the opening;
- a pixel-defining layer formed on the first electrode so as to expose a predetermined region of the first electrode, the pixel-defining layer having projecting portions extending inward towards the pixel region from a bottom of the sidewalls of the opening of the planarization pattern;
- an intermediate layer connected to the exposed region of the first electrode, said intermediate layer comprising an organic emission layer and formed so as to correspond to at least the pixel region; and
- a second electrode electrically connected to the intermediate layer.

2. The organic light-emitting display apparatus of claim 1, wherein the TFT comprises an active layer, a gate electrode insulated from the active layer, a source electrode, and a drain electrode, and wherein the first electrode is connected to the drain electrode.

3. The organic light-emitting display apparatus of claim 2, further comprising a gate insulating film disposed between the active layer and the gate electrode, and an interlayer insulating film disposed between the gate electrode and the source electrode, and between the gate electrode and the drain electrode; and

wherein the gate insulating film and the interlayer insulating film are covered by the planarization pattern within an area where the planarization pattern is formed.

4. The organic light-emitting display apparatus of claim 2, wherein an outer surface of the gate insulating film and an outer surface of the interlayer insulating film are disposed on a same plane.

5. The organic light-emitting display apparatus of claim 1, wherein the projecting portions are arranged around the pixel region.

6. The organic light-emitting display apparatus of claim 5, wherein the projecting portions project in a direction perpendicular to a thickness direction of the substrate.

7. The organic light-emitting display apparatus of claim 5, wherein the intermediate layer contacts side surfaces of the projecting portions.

8. The organic light-emitting display apparatus of claim 1, wherein the pixel-defining layer is thinner than the planarization pattern.

9. An organic light-emitting display apparatus, comprising:

- a substrate in which a pixel region is defined;
- a thin film transistor (TFT) arranged on the substrate and spaced apart from the pixel region;
- a planarization pattern covering the TFT, the planarization pattern having an opening with sidewalls that are spaced apart from the pixel region;
- a first electrode electrically connected to the TFT and being arranged to correspond to at least the pixel region;
- a pixel-defining layer arranged on the first electrode and having an opening within the opening in the planarization pattern to expose a portion of the first electrode that corresponds to the pixel region;
- an intermediate layer being arranged only within the opening in the pixel-defining layer, the intermediate layer being connected to the exposed portion of the first electrode, said intermediate layer including an organic emission layer;
- a second electrode electrically connected to the intermediate layer; and
- an optical resonance insulating layer formed between the substrate and the first electrode in at least the pixel region.

10. The organic light-emitting display apparatus of claim 9, the intermediate layer being spaced-apart from portions of the pixel-defining layer that correspond to the sidewalls of the opening of the planarization layer.

11. The organic light-emitting display apparatus of claim 9, wherein the pixel-defining layer having a thickness of more than 500 Å and less than a thickness of the planarization pattern.

12. The organic light-emitting display apparatus of claim 9, the first electrode also being arranged on the sidewalls of the opening of the planarization pattern, the pixel-defining layer

11

having projecting portions extending inward towards the pixel region from a bottom of the sidewalls of the opening of the planarization pattern.

13. The organic light-emitting display apparatus of claim 1, wherein the first electrode is formed on the planarization pattern and comprises openings external to the pixel area through which the planarization pattern is exposed.

14. The organic light-emitting display apparatus of claim 1, wherein the intermediate layer is formed by using a printing method.

15. The organic light-emitting display apparatus of claim 1, the projecting portions have a top surface covered by the second electrode, end surfaces covered by the intermediate layer and a lower surface covering the first electrode.

16. The organic light-emitting display apparatus of claim 1, wherein the intermediate pattern is entirely arranged within the opening of the planarization pattern and is absent from the sidewalls of the opening of the planarization pattern.

17. The organic light-emitting display apparatus of claim 1, wherein the pixel-defining layer is thinner than the planarization pattern.

18. An organic light-emitting display apparatus, comprising:

- a substrate in which a pixel region is defined;
- a thin film transistor (TFT) disposed on the substrate and spaced apart from the pixel region;

12

a planarization pattern covering the TFT and forming an opening for the pixel region, the opening having sidewalls;

a first electrode electrically connected to the TFT and arranged to correspond to at least the pixel region;

a pixel-defining layer arranged on the sidewalls of the planarization pattern and exposing a region of the first electrode, the pixel defining layer also including projecting portions arranged on the first electrode at a location corresponding to the opening of the planarization pattern and adjacent to the sidewalls of the planarization pattern;

an intermediate layer arranged on the exposed region of the first electrode, said intermediate layer comprising an organic emission layer and formed so as to correspond to at least the pixel region; and

a second electrode electrically connected to the intermediate layer.

19. The organic light-emitting display apparatus of claim 18, wherein a thickness of the pixel defining layer is less than that of the planarization pattern.

20. The organic light-emitting display apparatus of claim 18, the intermediate layer being absent from the sidewalls of the planarization pattern.

* * * * *

专利名称(译)	有机发光显示装置		
公开(公告)号	US8487310	公开(公告)日	2013-07-16
申请号	US13/098046	申请日	2011-04-29
[标]申请(专利权)人(译)	三星显示有限公司		
申请(专利权)人(译)	三星移动显示器有限公司.		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	KANG JIN GOO KIM JI YOUNG KIM HYO SEOK		
发明人	KANG, JIN-GOO KIM, JI-YOUNG KIM, HYO-SEOK		
IPC分类号	H01L27/12 H01L27/32 H01L51/52		
CPC分类号	H01L27/1248 H01L27/3246 H01L27/3248 H01L51/5262 H01L51/5265		
优先权	1020100104742 2010-10-26 KR		
其他公开文献	US20120097952A1		
外部链接	Espacenet USPTO		

摘要(译)

一种有机发光显示装置，包括：基板，其中限定像素区域；薄膜晶体管（TFT）设置在基板上并与像素区域隔开；覆盖TFT并与像素区域隔开的平坦化图案；第一电极，电连接到TFT，并形成至少对应于像素区域；形成在第一电极上的像素限定层，以暴露第一电极的预定区域；中间层，连接到第一电极的暴露区域，包括有机发光层，并形成至少对应于像素区域；第二电极与中间层电连接。

