



US008890151B2

(12) **United States Patent**
Hong

(10) **Patent No.:** **US 8,890,151 B2**
(45) **Date of Patent:** **Nov. 18, 2014**

(54) **ORGANIC LIGHT-EMITTING DISPLAY APPARATUS**

(75) Inventor: **Sang-Min Hong**, Yongin (KR)

(73) Assignee: **Samsung Display Co., Ltd.**,
Giheung-Gu, Yongin, Gyeonggi-Do (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 2 days.

(21) Appl. No.: **13/490,273**

(22) Filed: **Jun. 6, 2012**

(65) **Prior Publication Data**

US 2013/0075737 A1 Mar. 28, 2013

(30) **Foreign Application Priority Data**

Sep. 22, 2011 (KR) 10-2011-0095822

(51) **Int. Cl.**
H01L 31/00 (2006.01)
H01L 27/32 (2006.01)

(52) **U.S. Cl.**
CPC **H01L 27/3246** (2013.01); **H01L 2251/5392** (2013.01)
USPC .. **257/59**; 257/72; 257/E27.119; 257/E27.12; 257/E27.121

(58) **Field of Classification Search**
USPC 438/152; 257/E27.119, 59, 72
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,005,344 A * 12/1999 Fleming 313/498
6,373,187 B1 * 4/2002 Nagayama et al. 313/506

6,414,432 B1 * 7/2002 Hieda et al. 313/506
7,573,195 B2 * 8/2009 Lifka et al. 313/507
8,029,850 B2 10/2011 Ishii
2001/0019133 A1 * 9/2001 Konuma et al. 257/79
2002/0024493 A1 * 2/2002 Ozawa et al. 345/92
2002/0163300 A1 * 11/2002 Duineveld et al. 313/505
2005/0140303 A1 * 6/2005 Lee et al. 315/169.3
2006/0023440 A1 * 2/2006 Miyazawa 361/792
2006/0223221 A1 * 10/2006 Ishii 438/99
2007/0052349 A1 * 3/2007 Giraldo et al. 313/506
2007/0069619 A1 * 3/2007 Lifka et al. 313/292
2007/0108889 A1 * 5/2007 Kim 313/503
2007/0188081 A1 * 8/2007 Lee et al. 313/504
2011/0121301 A1 5/2011 Kim et al.

FOREIGN PATENT DOCUMENTS

KR 10-0611161 8/2006
KR 10-2006-0105495 10/2006
KR 10-2007-0028122 3/2007
KR 10-2011-0058407 6/2011

* cited by examiner

Primary Examiner — Matthew W Such


Assistant Examiner — Samuel Lair

(74) Attorney, Agent, or Firm — Robert E. Bushnell, Esq.

(57) **ABSTRACT**

An organic light-emitting display apparatus having improved durability and image quality may include a substrate; a first electrode formed on the substrate; a first pixel definition layer formed to cover at least one lateral surface of the first electrode; a second pixel definition layer formed so as to be spaced apart from at least an upper surface of the first pixel definition layer; an intermediate layer formed on the first electrode and including an organic light-emitting layer; and a second electrode formed on the intermediate layer.

19 Claims, 4 Drawing Sheets







FIG. 3







FIG. 6



ORGANIC LIGHT-EMITTING DISPLAY APPARATUS

CLAIM OF PRIORITY

This application makes reference to, incorporates the same herein, and claims all benefits accruing under 35 U.S.C. § 119 from an application earlier filed in the Korean Intellectual Property Office on the 22nd of Sep. 2011 and there duly assigned Serial No. 10-2011-0095822.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to an organic light-emitting apparatus, and more particularly, to an organic light-emitting apparatus having improved durability and image quality.

2. Description of the Related Art

Developments in display technology have led to the replacement of conventional display apparatuses with portable, thin flat panel display devices. From among the flat panel devices, an organic light-emitting display apparatus, which is a self-emissive display apparatus, has a wide viewing angle, high contrast ratio, exceptional thinness, enhanced compactedness, and high response speed, and thus should probably be considered as the next-generation display apparatus.

An organic light-emitting display apparatus may be constructed with a first electrode, a second electrode, and an intermediate layer. The intermediate layer includes an organic emission layer that emits visible light when a voltage is applied to the first and second electrodes.

An electrical insulating layer, such as a pixel definition layer, is formed on a predetermined portion of the first electrode. Thus, the first electrode and the second electrode do not directly contact each other.

The edges of the first and second electrodes are likely to contact each other in response to the application of an external force or a transverse impulse, or by a shocks or the like, and thus create a short circuit between the first and second electrodes, thereby causing problems with image quality, such as a formation of a dark spot on the otherwise brilliant screen of the display apparatus.

Accordingly, any improvement of the durability and image quality of an organic light-emitting display apparatus is limited.

SUMMARY OF THE INVENTION

The present invention contemplates an organic light-emitting apparatus for improving durability and image quality.

According to an aspect of the present invention, there is provided an organic light-emitting display apparatus which may include a substrate, a first electrode formed on the substrate, a first pixel definition layer formed to cover at least one lateral surface of the first electrode, a second pixel definition layer formed so as to be spaced apart from at least an upper surface of the first pixel definition layer, an intermediate layer, including an organic light-emitting layer, formed on the first electrode, and a second electrode formed on the intermediate layer.

The first pixel definition layer may be spaced apart from an extension line of a top surface of the second pixel definition layer.

The first pixel definition layer may be shorter in height relative to the underlying substrate, than the second pixel definition layer.

A top surface of the first pixel definition layer may be positioned below an extension line of a top surface of the second pixel definition layer.

A thickness of at least a portion of the second pixel definition layer may be greater than a thickness of the first pixel definition layer.

The first pixel definition layer may be formed to cover a first lateral surface of the first electrode and a second lateral surface of the first electrode that faces the first lateral surface.

The first pixel definition layer may be formed to cover all lateral surfaces of the first electrode.

At least a portion of the first pixel definition layer may be spaced apart from the second pixel definition layer.

The intermediate layer may contact a lateral surface of the first pixel definition layer.

The intermediate layer may be formed so as not to be spaced apart from the first pixel definition layer.

The organic light-emitting display apparatus may further include a thin film transistor (TFT) that is electrically connected to the first electrode and which includes an active layer, a gate electrode, a source electrode, and a drain electrode.

The second pixel definition layer may include a first layer and a second layer formed on at least a portion of the first layer.

The first pixel definition layer may be formed to cover a lateral surfaces of the first electrode facing the second layer of the second pixel definition layer.

The first pixel definition layer may be spaced apart from the second layer of the second pixel definition layer.

The second layer of the second pixel definition layer may be formed to face a first lateral surface and a second lateral surface facing the first lateral surface from among lateral surfaces of the first electrode.

BRIEF DESCRIPTION OF THE DRAWINGS

A more complete appreciation of the invention, and many of the attendant advantages thereof, will be readily apparent as the same becomes better understood by reference to the following detailed description when considered in conjunction with the accompanying drawings, in which like reference symbols indicate the same or similar components, wherein:

FIG. 1 is a schematic cross-sectional view of an organic light-emitting display apparatus constructed as a first embodiment of the present invention;

FIG. 2 is a schematic cross-sectional view of an organic light-emitting display apparatus constructed as a second embodiment of the present invention;

FIG. 3 is a schematic plan view of an organic light-emitting display apparatus constructed as a third embodiment of the present invention;

FIG. 4 is a cross-sectional view of the organic light-emitting display apparatus taken along a sectional line IV-IV' in FIG. 3;

FIG. 5 is a cross-sectional view of the organic light-emitting display apparatus taken along a sectional line V-V' in FIG. 3; and

FIG. 6 is a detailed view illustrating the orientation of the various sides, surfaces and structural features described in the following description.

DETAILED DESCRIPTION OF THE INVENTION

Hereinafter, exemplary embodiments of the present invention will be described in detail with reference to the accompanying drawings simply by way of illustration. As used

herein, the term “and/or” includes any and all combinations of one or more of the associated listed items. As those skilled in the art would realize, the described embodiments may be modified in various different ways, all without departing from the spirit or scope of the present invention. Accordingly, the drawings and description are to be regarded as illustrative in nature and not restrictive. In addition, when an element is referred to a being “on” another element, it may be positioned directly upon the other element or be positioned indirectly upon the other element with one or more intervening elements interposed therebetween. Also, when an element is referred to as being “connected to” another element, it may be directly connected to the other element or be indirectly connected to the other element with one or more intervening elements interposed therebetween. Hereinafter, like reference numerals refer to like elements.

For convenience, in these exemplary embodiments of the present invention, the term “display panel” commonly refers to a panel in which the substrate (such as a substrate including an organic light emitting diode) and the encapsulation substrate for encapsulating at least some region of the substrate adhere to each other by the assistance of a sealing agent (i.e., a sealant) such as a frit.

FIG. 1 is a schematic cross-sectional view of an organic light-emitting display apparatus 100 constructed as a first embodiment of the principles of the present invention.

Referring to FIGS. 1 and 6 together, the organic light-emitting display apparatus 100 includes a substrate 101, a first electrode 110, a first pixel definition layer 120, a second pixel definition layer 130, an intermediate layer 140, and a second electrode 150.

The substrate 101 may be formed of a transparent glass material mainly including SiO_2 . Substrate 101 may, however, be formed of a transparent plastic material. A plastic substrate may be formed of an organic, electrically insulating material such as an organic material selected from a group of materials such as polyethersulphone (PES), polyacrylate (PAR), polyetherimide (PEI), polyethylene naphthalate (PEN), polyethylene terephthalate (PET), polyphenylene sulfide (PPS), polyarylate, polyimide, polycarbonate (PC), cellulose tri-acetate (TAC), and cellulose acetate propionate (CAP).

Alternatively, the substrate 101 may be formed of metal, for example, a metal foil.

The first electrode 110 is disposed on the substrate 101. The first electrode 110 may be formed so as to have a predetermined pattern by using a photolithography technique. Although not illustrated, a buffer layer (not shown) may be formed between the substrate 101 and the first electrode 110, may make the substrate 101 smooth, and may prevent impurities from penetrating into the substrate 101. The buffer layer may be formed of SiO_2 and/or SiN_x .

The first electrode 110 may be formed so as to contain various conductive materials.

The first pixel definition layer 120 is disposed on the first electrode 110. In detail, the first pixel definition layer 120 is formed to cover at least one lateral surface 122 of the first electrode 110. As shown in FIGS. 1 and 6, the first pixel definition layer 120 may be formed to cover a left lateral surface 122 of the first electrode 110 and a right lateral surface 124 of the first electrode 110, which faces, and is spaced apart from, the left lateral surface 122.

The present invention is not limited to the foregoing embodiments. That is, the first pixel definition layer 120 may be formed to cover the majority of an upper lateral surface 128 of the first electrode 110 and a lower lateral surface 121 of the first electrode 110. In addition, the first pixel definition layer

120 may be formed to cover all lateral surfaces 121, 122, 124 and 128 of the first electrode 110.

The first pixel definition layer 120 may not cover an entire upper surface of the first electrode 110, but may be formed to expose a major surface, namely a predetermined region 126 of an upper surface of the first electrode 110, as is illustrated by FIG. 1.

The second pixel definition layer 130 is formed on the substrate 101 so as to be spaced apart from an upper surface 120a of the first pixel definition layer 120. In addition, an extension line E of a top surface of the second pixel definition layer 130 is spaced apart from the first pixel definition layer 120. That is, the upper surface 120a of the first pixel definition layer 120 is positioned below the extension line E.

To this end, for example, a thickness D2 of at least a portion of the first pixel definition layer 120 is smaller than a thickness D1 of the second pixel definition layer 130.

In addition, at least a portion of the first pixel definition layer 120 is spaced apart from the second pixel definition layer 130 so as to form a space 132 between the first pixel definition layer 120 and the second pixel definition layer 130.

The first pixel definition layer 120 and the second pixel definition layer 130 may be formed of an electrically insulating material and may be formed of the same material. The present invention is not limited thereto, however. That is, the first pixel definition layer 120 and the second pixel definition layer 130 may be formed from different materials.

The intermediate layer 140 is formed on the first electrode 110. The intermediate layer 140 includes an organic light-emitting layer. The intermediate layer 140 is disposed so as to contact the lateral surface 126 of the first pixel definition layer 120. The intermediate layer 140 may be formed so as not to be spaced apart from the first pixel definition layer 120. Intermediate layer 140 may be disposed to overlay, or to overlay and directly contact a majority of the surface of first electrode 110 located between the spaced-apart side walls 134 of first pixel definition layer 120.

The organic light-emitting layer of the intermediate layer 140 may emit visible rays characterized by various colors, for example, red, green, and blue.

The second electrode 150 is disposed on the intermediate layer 140. The second electrode 150 may be formed so as to contain various electrically conductive materials.

The second electrode 150 may also be formed on, cover, and partially, or entirely, encase the first pixel definition layer 120, and the second pixel definition layer 130, and may not have a predetermined pattern.

Although not illustrated, an encapsulation member (not shown) may be disposed on the second electrode 150 so as to face, and be generally coplanar and substantially coextensive with, a major surface of the substrate 101. The encapsulation member is formed to protect the intermediate layer 140 from external moisture and from oxygen, and may be formed of glass or plastic, or it may be formed by stacking at least one layer made from other organic and inorganic materials.

The organic light-emitting display apparatus 100 includes the first pixel definition layer 120 and the second pixel definition layer 130. The extension line E of the top surface of the second pixel definition layer 130 is spaced apart from the first pixel definition layer 120 and from the upper surface 120a.

Accordingly, when an external force, impulse, or pressure, such as an external shock, is applied to the organic light-emitting display apparatus 100, the first electrode 110 and the second electrode 150 may be prevented from being damaged, as will be described in detail.

Conventionally, and in some embodiments, the first and second electrodes 110 and 150, respectively, of the organic

light-emitting display apparatus **100** may be expected to make electrical contact with each other in response to external force, impulse, or pressure, and thereby create an electrical short circuit, thus causing problems with image quality, such as by creating a dark spot. In particular, an insulating material of a pixel definition layer that covers a lateral surface of the first electrode **110** is pressed by external pressure, and thus the lateral surface of the first electrode **110** may deleteriously contact the second electrode **150**.

When an external pressure is applied to embodiments of the present invention however, the external pressure is transferred to the second pixel definition layer **130**. The second pixel definition layer **130** may be spaced electrically and physically apart from the upper surface **120a** of the first pixel definition layer **120**. That is, even if a pressure is applied to the second pixel definition layer **130**, the pressure is primarily transferred to the second pixel definition layer **130** and is barely transferred to the first pixel definition layer **120**. Thus, the first pixel definition layer **120** is not pressed or damaged. Accordingly, the first pixel definition layer **120** may effectively protect the lateral surfaces **121**, **122**, **124**, **128** that form the peripheral side walls, or edges of the first electrode **110**. In addition, even if external forces, impulses or shocks are applied to display apparatus **110**, the first electrode **110** may be prevented from electrically or physically contacting the second electrode **150**.

In particular, at least a portion of the first pixel definition layer **120** may be spaced apart from the second pixel definition layer **130**. Thus, when external pressure is applied to the second pixel definition layer **130**, the external pressure may be effectively prevented from being transferred to the first pixel definition layer **120** from the second pixel layer **130**.

As a result, the durability and image quality of organic light-emitting display apparatus **100** are improved.

FIG. **2** is a schematic cross-sectional view of an organic light-emitting display apparatus fabricated as a second embodiment of the present invention.

Referring to FIGS. **2** and **6**, the organic light-emitting display apparatus **200** includes a substrate **201**, a thin film transistor TFT, a first electrode **210**, a first pixel definition layer **220**, a second pixel definition layer **230**, an intermediate layer **240**, and a second electrode **250**. The thin film transistor TFT includes an active layer **203**, a gate electrode **205**, a source electrode **207**, and a drain electrode **208**.

Structures of these components may be described in detail.

A buffer layer **202** is formed on the substrate **201**. The buffer layer **202** may include SiO_2 or SiN_x . In addition, the buffer layer **202** may be formed by stacking a plurality of layers. The buffer layer **202** makes the substrate **201** smooth and prevents external moisture and impurities from penetrating into the thin film transistor TFT through a lower portion of the substrate **201**.

The active layer **203** has a predetermined pattern and is formed on the buffer layer **202**. The active layer **203** may be formed of an inorganic semiconductor such as amorphous silicon or poly silicon, or an organic semiconductor, and may include a source region, a drain region, and a channel region. A gate insulating layer **204** is formed on the active layer **203**. The gate insulating layer **204** may include various insulating materials.

The gate electrode **205** is formed on a predetermined portion of the gate insulating layer **204**. The gate electrode **205** is connected to a gate line (not shown) for applying TFT on/off signals. The gate electrode **205** may be formed of metal or a metal alloy such as gold (Au), silver (Ag), copper (Cu), nickel

(Ni), platinum (Pt), palladium (Pd), aluminum (Al), molybdenum (Mo), a Al:Nd alloy, a Mo:W alloy, or the like, but it is not limited thereto.

An interlayer electrical insulating layer **206** is formed on the gate electrode **205** so as to expose portions of the source and drain regions of the active layer **203**.

The source electrode **207** and the drain electrode **208** are formed so as to contact the exposed portions of the source and drain regions, respectively, of the active layer **203**.

A passivation layer **209** is formed to cover the thin film transistor TFT.

The first electrode **210** is formed on the passivation layer **209**. In detail, the passivation layer **209** may be formed to expose a portion of the drain electrode **208** therethrough, and the first electrode **210** is connected to the exposed portion of the drain electrode **208**.

The first electrode **210** may be formed so as to contain various electrically conductive materials.

The first pixel definition layer **220** is disposed on the first electrode **210**. In detail, the first pixel definition layer **220** is formed to cover at least one major lateral surface **226** of the first electrode **210**. As shown in FIG. **2**, the first pixel definition layer **220** may be formed to cover a left lateral surface **222** of the first electrode **210** and a right lateral surface **224** of the first electrode **210**, shown opposite from the left lateral surface **222**.

The present invention is not limited thereto. That is, the first pixel definition layer **220** may be formed to cover the opposite longitudinally extending edges, or side walls **221**, **222**, **224**, **228** of an upper lateral surface **226** of the first electrode **210** and a lower lateral surface **212** of the first electrode **210**. In addition, the first pixel definition layer **220** may be formed to cover all lateral surfaces **221**, **222**, **224**, **228** of the first electrode **210**.

The first pixel definition layer **220** may not cover an entirety of upper surface **226** of the first electrode **210**, but may be formed to expose a predetermined region of the upper surface **226** of the first electrode **210**.

The second pixel definition layer **230** is formed on passivation layer **209** for the substrate **201** so as to be spaced apart from an upper surface **220a** of the first pixel definition layer **220**. In addition, an extension line E of a top surface of the second pixel definition layer **230** is spaced apart from the first pixel definition layer **220**. That is, the upper surface **220a** of the first pixel definition layer **220** is positioned below the extension line E because first pixel definition layer **220** lacks the height of second pixel definition layer **230**.

To this end, for example, a thickness D2 of at least a portion of the first pixel definition layer **220** is smaller than a thickness D1 of the second pixel definition layer **230**.

The first pixel definition layer **220** and the second pixel definition layer **230** may be formed of an electrically insulating material, and may be formed of the same material. The present invention is not limited thereto, however. That is, the first pixel definition layer **220** and the second pixel definition layer **230** may also be formed of different materials.

The intermediate layer **240** is formed on the first electrode **210**. The intermediate layer **240** includes an organic light-emitting layer. The intermediate layer **240** is disposed so as to contact opposite lateral surfaces **222**, **224** of the first pixel definition layer **220**. The intermediate layer **240** may be formed so as not to be spaced apart from the first pixel definition layer **220**.

The organic light-emitting layer of the intermediate layer **240** may emit visible rays and may realize various colors, for example, red, green, and blue.

The second electrode **250** is disposed on the intermediate layer **240**. The second electrode **250** may be formed so as to contain various electrically conductive materials.

The second electrode **250** may also be formed on the first pixel definition layer **220** and the second pixel definition layer **230**, and may not have a predetermined pattern.

Although not illustrated, an encapsulation member (not shown) may be disposed on the second electrode **250** so as to face a surface of the substrate **201**. The encapsulation member is formed to protect the intermediate layer **240** from external moisture or oxygen, and may be formed of glass or plastic, or the encapsulation member may be formed by stacking at least one layer formed of other organic and inorganic materials.

The organic light-emitting display apparatus **200** is an active matrix (AM) type, but the display apparatus is not limited to an active matrix type display apparatus. That is, a passive material (PM) type organic light-emitting display apparatus may also be used.

FIG. 3 is a schematic plan view of an organic light-emitting display apparatus according to a third embodiment of the present invention, FIG. 4 is a cross-sectional view of the organic light-emitting display apparatus taken along a line IV-IV of FIG. 3, and FIG. 5 is a cross-sectional view of the organic light-emitting display apparatus taken along a line V-V of FIG. 3.

Referring to FIGS. 3 through 5, the organic light-emitting display apparatus **300** includes a substrate **301**, the thin film transistor TFT, a first electrode **310**, a first pixel definition layer **320**, a second pixel definition layer **330**, an intermediate layer **340**, and a second electrode **350**.

The thin film transistor TFT includes an active layer **303**, a gate electrode **305**, a source electrode **307**, and a drain electrode **308**.

The second pixel definition layer **330** includes a first layer **331** and a second layer **332** formed on the first layer **331**.

Structures of the components will be described in detail.

A buffer layer **302** is formed on the substrate **301**. The buffer layer **302** may include SiO_2 or SiN_x . In addition, the buffer layer **302** may be formed by stacking a plurality of layers. The buffer layer **302** makes the substrate **301** smooth and prevents external moisture and impurities from penetrating into the thin film transistor TFT through a lower portion of the substrate **301**.

The active layer **303** has a predetermined pattern and is formed on the buffer layer **302**. The active layer **303** may be formed of an inorganic semiconductor such as amorphous silicon or poly silicon, or an organic semiconductor, and may include a source region, a drain region, and a channel region. A gate insulating layer **304** is formed on the active layer **303**. The gate insulating layer **304** may include various insulating materials.

The gate electrode **305** is formed on a predetermined portion of the gate insulating layer **304**. The gate electrode **305** is connected to a gate line (not shown) for applying TFT on/off signals. The gate electrode **305** may be formed of metal or a metal alloy such as Au, Ag, Cu, Ni, Pt, Pd, Al, Mo, a Al:Nd alloy, a Mo:W alloy, or the like, but it is not limited thereto.

An interlayer insulating layer **306** is formed on the gate electrode **305** so as to expose portions of the source and drain regions of the active layer **303**.

The source electrode **307** and the drain electrode **308** are formed so as to contact the exposed portions of the source and drain regions, respectively, of the active layer **303**.

A passivation layer **309** is formed to cover the thin film transistor TFT.

The first electrode **310** is formed on the passivation layer **309**. In detail, the passivation layer **309** may be formed so as

to expose a portion of the drain electrode **308** therethrough, and the first electrode **310** is connected to the exposed portion of the drain electrode **308**.

The first electrode **310** may be formed so as to contain various conductive materials.

The first pixel definition layer **320** and the second pixel definition layer **330** are formed on the first electrode **310** and on the passivation layer **309**, respectively. The second pixel definition layer **330** includes the first layer **331** and the second layer **332**.

The second layer **332** of the second pixel definition layer **330** is formed on a predetermined portion of the first layer **331**. As shown in FIGS. 3 through 5, the second layer **332** may be disposed on the first layer **331** so as to face upper and lower lateral surfaces from among lateral surfaces of the first electrode **310**.

The first pixel definition layer **320** is formed to cover at least one lateral surface of the first electrode **310**. As shown in FIGS. 3 through 5, the first pixel definition layer **320** may be formed to cover an upper lateral surface of the first electrode **310** and a lower lateral surface of the first electrode **310**, which faces the upper lateral surface. That is, the first pixel definition layer **320** may be disposed to cover lateral surfaces facing the second layer **332** from among lateral surfaces of the first electrode **310**.

However, the present invention is not limited thereto. That is, the first pixel definition layer **320** may be formed to cover all lateral surfaces of the first electrode **310**. However, in order to prevent a reduction in the size of each sub-pixel, that is a reduction in an area for forming the intermediate layer **340**, the first pixel definition layer **320** may cover lateral surfaces facing the second layer **332** from among lateral surfaces of the first electrode **310**.

In addition, the first pixel definition layer **320** is formed so as to be spaced apart from the second layer **332**.

The first pixel definition layer **320** may not cover an entire upper surface of the first electrode **310**, but it may be formed so as to expose a predetermined region of an upper surface of the first electrode **310**. As shown in FIG. 5, the first layer **331** of second pixel definition layer **330** is formed to cover the right and left lateral surfaces of the first electrode **310**, which are not covered by the first pixel definition layer **320**, and to expose a predetermined portion of an upper surface of the first electrode **310**.

An upper surface **320a** of the first pixel definition layer **320** is spaced apart from the second pixel definition layer **330**. An extension line E of a top surface of the second pixel definition layer **330** is spaced apart from the first pixel definition layer **320**. That is, the upper surface **320a** of the first pixel definition layer **320** is positioned below the extension line E.

To this end, for example, a thickness D2 of at least a portion of the first pixel definition layer **320** is smaller than a thickness D1 of the second pixel definition layer **330**. In detail, the sum of the thicknesses of the first layer **331** and the second layer **332** of the second pixel definition layer **330** is greater than the thickness D2 of the first pixel definition layer **320**.

The first pixel definition layer **320** and the second pixel definition layer **330** may be formed of an insulating material and may be formed of the same material. However, the present invention is not limited thereto. That is, the first pixel definition layer **320** and the second pixel definition layer **330** may be formed of different materials.

The first layer **331** and the second layer **332** of the second pixel definition layer **330** may be formed of the same material or different materials.

The intermediate layer **340** is disposed on the first electrode **310**. The intermediate layer **340** includes an organic

light-emitting layer. The intermediate layer **340** is disposed so as to contact a lateral surface of the first pixel definition layer **320**. The intermediate layer **340** may be formed so as not to be spaced apart from the first pixel definition layer **320**. In addition, a portion of the intermediate layer **340**, on which the first pixel definition layer **320** is not formed, contacts a lateral surface of the second pixel definition layer **330**.

The organic light-emitting layer of the intermediate layer **340** may emit visible rays and may realize various colors, for example, red, green, and blue.

The second electrode **350** is disposed on the intermediate layer **340**. The second electrode **350** may be formed so as to contain various conductive materials.

The second electrode **350** may also be formed on the first pixel definition layer **320**, and the second pixel definition layer **330** and may not have a predetermined pattern.

Although not illustrated, an encapsulation member (not shown) may be disposed on the second electrode **350** so as to face a surface of the substrate **301**. The encapsulation member is formed to protect the intermediate layer **340** from external moisture or oxygen, and may be formed of glass or plastic, or it may be formed by stacking at least one layer formed of other organic and inorganic materials.

The organic light-emitting display apparatus **300** includes the first pixel definition layer **320** and the second pixel definition layer **330**. The extension line E of the top surface of the second pixel definition layer **330** is spaced apart from the upper surface **320a** of the first pixel definition layer **320**.

When an external pressure is applied, the external pressure is transferred to the second pixel definition layer **330**. In particular, the external pressure is mostly transferred to the second layer **332** of the second pixel definition layer **330**. The second pixel definition layer **330** is spaced apart from the upper surface **320a** of the first pixel definition layer **320**. That is, even if a pressure is applied to the second layer **332** of the second pixel definition layer **330**, the pressure is not transferred to the first pixel definition layer **320**, and thus the first pixel definition layer **320** is not pressed or damaged. Accordingly, the first pixel definition layer **320** may effectively protect lateral surfaces of the first electrode **310**. In addition, even if external shocks are applied, the first electrode **310** may be prevented from contacting the second electrode **350**. In particular, the first pixel definition layer **320** is spaced apart from the second layer **332**, thereby easily preventing pressure applied during external shocks from being transferred to the first pixel definition layer **320**.

In addition, the first pixel definition layer **320** is formed so as to face the second layer **332** of the second pixel definition layer **330** and to cover a lateral surface of the first electrode **310**, thereby easily performing processes and effectively preventing a reduction in areas of sub-pixels.

According to one or more embodiments of the present invention, an organic light-emitting display apparatus may have improved durability and image quality.

While the present invention has been particularly shown and described with reference to exemplary embodiments thereof, it will be understood by those of ordinary skill in the art that various changes in form and detail may be made therein without departing from the spirit and scope of the present invention as defined by the following claims.

What is claimed is:

1. An organic light-emitting display apparatus, comprising:

a substrate;

a first electrode formed on the substrate, said first electrode having a top horizontal surface, a bottom horizontal surface, a first vertical surface located at a first side of the

first electrode for connecting first ends of the top horizontal surface and the bottom horizontal surface to each other, and a second vertical surface located at a second side of the first electrode for connecting second ends of the top horizontal surface and the bottom horizontal surface to each other;

a first pixel definition layer having a first portion formed to cover the first vertical surface of the first electrode and a second portion formed to cover the second vertical surface of the first electrode;

a second pixel definition layer formed so as to be spaced apart from at least an upper surface of the first pixel definition layer and having a first portion disposed on a first side of the first portion of the first pixel definition layer and a second portion disposed on a second side of the second portion of the first pixel definition layer;

an intermediate layer formed on the first electrode, extending from the first side of the first electrode to the second side of the first electrode, and comprising an organic light-emitting layer; and

a second electrode formed on the intermediate layer and extending continuously over the first portion of the second pixel definition layer, the first portion of the first pixel definition layer, the intermediate layer, the second portion of the first pixel definition layer, and the second portion of the second pixel definition layer;

wherein the intermediate layer is formed so as to be separated from the second pixel definition layer.

2. The organic light-emitting display apparatus of claim 1, wherein the first pixel definition layer is spaced apart from an extension line of a top surface of the second pixel definition layer.

3. The organic light-emitting display apparatus of claim 1, wherein a top surface of the first pixel definition layer is positioned below an extension line of a top surface of the second pixel definition layer.

4. The organic light-emitting display apparatus of claim 1, wherein a thickness of at least a portion of the second pixel definition layer is greater than a thickness of the first pixel definition layer.

5. The organic light-emitting display apparatus of claim 1, wherein the first pixel definition layer is formed to cover all vertical surfaces of the first electrode.

6. The organic light-emitting display apparatus of claim 1, wherein at least a portion of the first pixel definition layer is spaced apart from the second pixel definition layer.

7. The organic light-emitting display apparatus of claim 1, wherein the intermediate layer contacts a vertical surface of the first pixel definition layer.

8. The organic light-emitting display apparatus of claim 1, wherein the intermediate layer is formed so as not to be spaced apart from the first pixel definition layer.

9. An organic light-emitting display apparatus, comprising:

a substrate;

a passivation layer formed on the substrate;

a first electrode formed on the passivation layer;

a first pixel definition layer formed to cover at least one vertical surface of the first electrode;

a second pixel definition layer formed so as to be spaced apart from at least an upper surface of the first pixel definition layer;

an intermediate layer formed on the first electrode and comprising an organic light-emitting layer;

a second electrode formed on the intermediate layer; and

11

a thin film transistor (TFT) electrically connected to the first electrode and including an active layer, a gate electrode, a source electrode, and a drain electrode;

wherein the first electrode is connected to the thin film transistor (TFT) through an opening formed in the passivation layer;

wherein the first pixel definition layer comprises a first portion formed to cover a first vertical surface of the first electrode and a second portion formed to cover a second vertical surface of the first electrode; and

wherein the first electrode comprises a top horizontal surface and a bottom horizontal surface, the first vertical surface being located at a first end of the first electrode for connecting the top horizontal surface and the bottom horizontal surface to each other, the second vertical surface being located at a second end of the first electrode for connecting the top horizontal surface and the bottom horizontal surface to each other.

10. The organic light-emitting display apparatus of claim 9, wherein the second pixel definition layer comprises a first layer and a second layer formed on at least a portion of the first layer.

11. The organic light-emitting display apparatus of claim 9, wherein the first pixel definition layer is formed to cover a vertical surface, facing the second layer of the second pixel definition layer, from among vertical surfaces of the first electrode.

12

12. The organic light-emitting display apparatus of claim 10, wherein the first pixel definition layer is spaced apart from the second layer of the second pixel definition layer.

13. The organic light-emitting display apparatus of claim 10, wherein the second layer of the second pixel definition layer is formed so as to face both a left vertical surface and a right vertical surface of the first electrode.

14. The organic light-emitting display apparatus of claim 9, further comprising an interlayer electrical insulation layer disposed between the passivation layer and the substrate.

15. The organic light-emitting display apparatus of claim 14, further comprising a gate insulation layer disposed between the interlayer electrical insulation layer and the substrate.

16. The organic light-emitting display apparatus of claim 15, further comprising a buffer layer disposed between the gate insulation layer and the substrate.

17. The organic light-emitting display apparatus of claim 14, further comprising a buffer layer disposed between the interlayer electrical insulation layer and the substrate.

18. The organic light-emitting display apparatus of claim 17, wherein the thin film transistor (TFT) is disposed on the buffer layer.

19. The organic light-emitting display apparatus of claim 16, wherein the thin film transistor (TFT) is disposed on the buffer layer.

* * * * *

专利名称(译)	有机发光显示装置		
公开(公告)号	US8890151	公开(公告)日	2014-11-18
申请号	US13/490273	申请日	2012-06-06
[标]申请(专利权)人(译)	HONG SANG MIN		
申请(专利权)人(译)	HONG , 尚民		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	HONG SANG MIN		
发明人	HONG, SANG-MIN		
IPC分类号	H01L27/32 H01L31/00		
CPC分类号	H01L2251/5392 H01L27/3246 H01L2251/558		
优先权	1020110095822 2011-09-22 KR		
其他公开文献	US20130075737A1		
外部链接	Espacenet USPTO		

摘要(译)

具有改善的耐用性和图像质量的有机发光显示装置可包括基板;形成在基板上的第一电极;形成第一像素限定层以覆盖第一电极的至少一个侧表面;形成第二像素限定层, 以与第一像素限定层的至少上表面间隔开;中间层, 形成在第一电极上并包括有机发光层;以及在中间层上形成的第二电极。

