



US010014354B2

(12) **United States Patent**
Kondo

(10) **Patent No.:** **US 10,014,354 B2**
(45) **Date of Patent:** **Jul. 3, 2018**

(54) **ORGANIC EL ELEMENT, ORGANIC EL DISPLAY PANEL USING SAME, AND ORGANIC EL DISPLAY PANEL MANUFACTURING METHOD**

(71) Applicants: **JOLED INC.**, Tokyo (JP); **JAPAN DISPLAY INC.**, Tokyo (JP)

(72) Inventor: **Tetsuro Kondo**, Tokyo (JP)

(73) Assignees: **JOLED INC.**, Tokyo (JP); **JAPAN DISPLAY INC.**, Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **15/252,463**

(22) Filed: **Aug. 31, 2016**

(65) **Prior Publication Data**

US 2017/0069696 A1 Mar. 9, 2017

(30) **Foreign Application Priority Data**

Sep. 7, 2015 (JP) 2015-175758

(51) **Int. Cl.**

H01L 27/32 (2006.01)

H01L 51/52 (2006.01)

H01L 51/56 (2006.01)

H01L 27/12 (2006.01)

(52) **U.S. Cl.**

CPC **H01L 27/3246** (2013.01); **H01L 27/1218** (2013.01); **H01L 27/3248** (2013.01); **H01L 27/3272** (2013.01); **H01L 27/3274** (2013.01); **H01L 27/3276** (2013.01);

(Continued)

(58) **Field of Classification Search**

CPC H01L 27/3246; H01L 27/3272; H01L 51/5271; H01L 51/56

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,443,922 A 8/1995 Nishizaki et al.
8,003,417 B2* 8/2011 Li H01L 27/3244
257/98

8,884,849 B2 11/2014 Masuda
(Continued)

FOREIGN PATENT DOCUMENTS

JP 05-163488 6/1993
JP 2008-176291 7/2008

(Continued)


Primary Examiner — Sophia Nguyen

(74) *Attorney, Agent, or Firm* — Greenblum & Bernstein, P.L.C.

(57) **ABSTRACT**

An organic EL display panel in which pixels are arranged in a matrix, including: light-emitting layers disposed above pixel electrode layers in intervals between adjacent ones of column banks; an opposing electrode layer disposed above the light-emitting layers, the opposing electrode layer including a light-transmissive material; column light-shielding layers disposed higher than the pixel electrode layers, extending in the column direction, arranged side-by-side in the row direction, and overlapping row-direction edge portions of the pixel electrode layers in plan view of a substrate; and row light-shielding layers disposed higher than the pixel electrode layers, extending in the row direction, arranged side-by-side in the column direction, overlapping column-direction edge portions of the pixel electrode layers and partially overlapping contact regions in plan view of the substrate.

11 Claims, 14 Drawing Sheets



- (52) **U.S. Cl.**
CPC *H01L 27/3297* (2013.01); *H01L 51/5271*
(2013.01); *H01L 51/56* (2013.01); *H01L*
27/3258 (2013.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

8,907,341 B2 12/2014 Kanegae et al.
8,952,365 B2 * 2/2015 Nishiyama C23C 14/083
257/40
9,006,758 B2 * 4/2015 Yoneda H01L 33/24
257/89
9,081,141 B2 7/2015 Tsukamoto et al.
9,224,956 B2 * 12/2015 Kawanami F04B 37/14
9,231,036 B2 * 1/2016 Oooka H01L 51/525
9,246,138 B2 * 1/2016 Nishiyama C23C 14/083
9,620,560 B2 * 4/2017 Isobe H01L 51/5234
9,722,006 B2 * 8/2017 Nishimura H01L 51/5209
9,761,638 B2 * 9/2017 Komatsu H01L 27/3213
2006/0139254 A1 * 6/2006 Hayakawa G09G 3/3216
345/76
2007/0200488 A1 * 8/2007 Ito F21K 2/06
313/500
2008/0024701 A1 * 1/2008 Abe G02F 1/133512
349/110
2008/0150421 A1 * 6/2008 Takata H01L 27/3244
313/504
2008/0231778 A1 * 9/2008 Tsao G02F 1/133516
349/106
2009/0109143 A1 * 4/2009 Yamazaki H01L 51/0003
345/76
2009/0174923 A1 * 7/2009 Nozawa H01L 27/3244
359/245
2011/0108859 A1 * 5/2011 Oosako H01L 27/3246
257/88
2012/0299116 A1 * 11/2012 Takeuchi G02F 1/13624
257/390
2013/0126839 A1 * 5/2013 Matsushima H01L 27/3246
257/40
2013/0234126 A1 * 9/2013 Nakatani H01L 27/3246
257/40
2013/0234129 A1 * 9/2013 Yamada H01L 51/5265
257/40

2014/0102877 A1 * 4/2014 Yamazaki C30B 23/005
204/192.15
2014/0127846 A1 * 5/2014 Yamada H01L 51/5088
438/46
2014/0151709 A1 * 6/2014 Nishiyama H01L 27/3211
257/72
2014/0284572 A1 * 9/2014 Oooka H01L 51/525
257/40
2014/0312329 A1 * 10/2014 Fujii H01L 51/5228
257/40
2014/0367675 A1 12/2014 Tsukamoto et al.
2015/0041813 A1 * 2/2015 Kim H01L 27/124
257/59
2015/0060827 A1 * 3/2015 Sasaki H01L 51/5284
257/40
2015/0090991 A1 * 4/2015 Ishii H01L 51/525
257/40
2015/0155347 A1 * 6/2015 Baek H01L 27/3272
257/40
2015/0226990 A1 * 8/2015 Miyazaki G02F 1/1339
349/123
2016/0078828 A1 * 3/2016 Tamaki G09G 3/3607
345/690
2016/0133675 A1 * 5/2016 Yata H01L 27/3218
257/89
2016/0181336 A1 * 6/2016 Tokuda H04N 9/30
257/40
2016/0211311 A1 * 7/2016 Sato H01L 27/3272
2016/0293676 A1 * 10/2016 Komatsu G02B 5/20
2016/0321982 A1 * 11/2016 Lee G09G 3/3607
2016/0322437 A1 * 11/2016 Sakamoto H01L 27/3246
2017/0033314 A1 * 2/2017 Matsusue H01L 51/5092
2017/0047381 A1 * 2/2017 Takata H01L 51/50
2017/0069696 A1 * 3/2017 Kondo H01L 27/3246
2017/0076654 A1 * 3/2017 Wang G09G 3/2074
2017/0117339 A1 * 4/2017 Takata H01L 51/50
2017/0207417 A1 * 7/2017 Ikeda H01L 51/5253

FOREIGN PATENT DOCUMENTS

JP 2013-165014 8/2013
JP 2015-050059 3/2015
JP 2015-072827 4/2015
WO 2013/108783 7/2013

* cited by examiner




FIG. 2




FIG. 3




FIG. 5




FIG. 6A




FIG. 6B




FIG. 6C




FIG. 6D




FIG. 6E




FIG. 7A




FIG. 7B




FIG. 7C




FIG. 8A



FIG. 8B




FIG. 8C




FIG. 8D




FIG. 8E




FIG. 8F



FIG. 9A





FIG. 9B






FIG. 11A




FIG. 11B




FIG. 11C




FIG. 12A




FIG. 12B




FIG. 12C




FIG. 13





FIG. 14



ORGANIC EL ELEMENT, ORGANIC EL DISPLAY PANEL USING SAME, AND ORGANIC EL DISPLAY PANEL MANUFACTURING METHOD

CROSS-REFERENCE TO RELATED APPLICATION

This application is based on application No. 2015-175758 filed in Japan, the contents of which are hereby incorporated by reference.

BACKGROUND OF THE DISCLOSURE

(1) Technical Field

The present disclosure relates to organic electroluminescence (EL) elements that use electroluminescence of organic material, organic EL display panels that use the organic EL elements, and organic EL display panel manufacturing methods.

(2) Description of Related Art

In recent years, as display panels used in display devices such as digital televisions, organic EL display panels are being implemented in which a plurality of organic EL elements are arrayed in a matrix on a substrate. Such organic EL display panels have high visibility, because each organic EL element is self-luminous.

In an organic EL display panel, each organic EL element typically has a structure in which a light-emitting layer that includes an organic light-emitting material is disposed between an anode and cathode pair of electrodes. When driven, a voltage is applied between the pair of electrodes, holes are injected to the light-emitting layer from the anode, electrons are injected to the light-emitting layer from the cathode, and the holes and the electrons recombine to emit light.

In the organic EL display panel, light-emitting layers are typically separated from adjacent organic EL elements by banks composed of an insulative material. In an organic EL display panel for color display, such organic EL elements form RGB color pixels, one pixel in a color display being formed by a combination of adjacent RGB pixels.

Typically, in an organic EL display panel, in order to prevent leaking of light between adjacent pixels and mixing of colors of light associated with this, a lattice-shaped light-shielding layer is provided above the banks at boundaries between adjacent pixels. For example, WO 2013/108783 discloses an organic EL element that suppresses a decrease in aperture ratio while also preventing color mixing between adjacent pixels, by using a matrix-shaped light-shielding member that has different thicknesses above a color filter substrate. Further, JP 2015-72827 discloses an organic EL display device that has an element substrate on which a light-emitting layer and a light-shielding member are disposed, and has a color filter layer that includes colored layers of multiple colors and an inter-pixel light-shielding member between colored layers. The light-shielding member is disposed more centrally in each pixel than the inter-pixel light-shielding member and thereby suppresses parallax mixed color due to light leakage to adjacent pixels and obtains high light extraction efficiency.

SUMMARY OF THE DISCLOSURE

(1) Problems to be Solved

However, as resolution of a display panel is increased, element area for each pixel is reduced, but width of a

shielding layer required to prevent light leakage to adjacent pixels is maintained regardless of reduction in element area. Thus, as resolution increases, aperture ratio of the shielding layer decreases, and a reduction in light emission efficiency based on a reduction in light emission area per pixel area becomes a technical problem. In contrast, when reducing the shielding layer in order to increase aperture ratio, there is a concern that display contrast decreases due to glare from external light reflected from reflective electrodes of the display panel.

In view of the above, the present disclosure aims to provide an organic EL element that improves suppression of glare from external light on a display surface and improves light emission efficiency, an organic EL display panel using the organic EL element, and a method of manufacturing the organic EL display panel.

(2) Means for Solving the Problems

In order to achieve this aim, an organic EL display panel pertaining to one aspect of the technology described in the present disclosure is an organic EL display panel in which a plurality of pixels are arranged in a row direction and a column direction in a matrix, the organic EL display panel including: a substrate; a plurality of pixel electrode layers arranged in the row direction and the column direction in a matrix on the substrate, the pixel electrode layers including a light-reflective material; a plurality of column banks disposed on the substrate and on the pixel electrode layers, covering row-direction edge portions of the pixel electrode layers, extending in the column direction, arranged side-by-side in the row direction, and defining row-direction edges of self-luminous regions of the pixels; a plurality of row banks disposed on the substrate and on the pixel electrode layers, covering column-direction edge portions of the pixel electrode layers and contact regions of the pixel electrode layers that are for electrically connecting the pixel electrode layers, extending in the row direction, arranged side-by-side in the column direction, and defining column-direction edges of the self-luminous regions; a plurality of light-emitting layers disposed above the pixel electrode layers in intervals between adjacent ones of the column banks; an opposing electrode layer disposed above the light-emitting layers, the opposing electrode layer including a light-transmissive material; a plurality of column light-shielding layers disposed higher than the pixel electrode layers, extending in the column direction, arranged side-by-side in the row direction, and overlapping the row-direction edge portions of the pixel electrode layers in plan view of the substrate; and a plurality of row light-shielding layers disposed higher than the pixel electrode layers, extending in the row direction, arranged side-by-side in the column direction, overlapping the column-direction edge portions of the pixel electrode layers and partially overlapping the contact regions in plan view of the substrate.

BRIEF DESCRIPTION OF THE DRAWINGS

These and other objects, advantages, and features of the technology pertaining to the present disclosure will become apparent from the following description thereof taken in conjunction with the accompanying drawings, which illustrate at least one specific embodiment of the technology pertaining to the present disclosure.

FIG. 1 is a schematic block diagram illustrating a configuration of a display device 1 pertaining to an embodiment.

FIG. 2 is a schematic circuit diagram showing a circuit configuration of a pixel 100e of an organic EL display panel 10 used in the display device 1.

FIG. 3 is a schematic plan view illustrating a portion of the organic EL display panel 10.

FIG. 4 is a schematic cross-sectional view of A-A in FIG. 3.

FIG. 5 is a schematic cross-sectional view of B-B in FIG. 3.

FIG. 6A, FIG. 6B, FIG. 6C, FIG. 6D, and FIG. 6E are schematic cross-sectional views illustrating states of processes in manufacturing the organic EL display panel 10.

FIG. 7A, FIG. 7B, and FIG. 7C are schematic cross-sectional views illustrating states of processes in manufacturing the organic EL display panel 10.

FIG. 8A, FIG. 8B, FIG. 8C, FIG. 8D, FIG. 8E, and FIG. 8F are schematic cross-sectional views illustrating states of processes in manufacturing the organic EL display panel 10.

FIG. 9A and FIG. 9B are schematic cross-sectional views illustrating states of processes in manufacturing the organic EL display panel 10.

FIG. 10 is an enlarged plan view of a portion A in FIG. 3.

FIG. 11A, FIG. 11B, and FIG. 11C are plan view photographs of the pixel 100e of the organic EL display panel 10, captured from above an upper substrate 130.

FIG. 12A, FIG. 12B, and FIG. 12C are plan view photographs of the pixel 100e of the organic EL display panel when emitting light, captured from above the upper substrate.

FIG. 13 is a schematic cross-sectional view at the same position as A-A in FIG. 3, of an organic EL display panel 10A pertaining to a modification.

FIG. 14 is a schematic cross-sectional view at the same position as B-B in FIG. 3, of the organic EL display panel 10A pertaining to a modification.

DESCRIPTION OF EMBODIMENT

Summary of Embodiment

An organic EL display panel pertaining to the present embodiment is an organic EL display panel in which a plurality of pixels are arranged in a row direction and a column direction in a matrix, the organic EL display panel including: a substrate; a plurality of pixel electrode layers arranged in the row direction and the column direction in a matrix on the substrate, the pixel electrode layers including a light-reflective material; a plurality of column banks disposed on the substrate and on the pixel electrode layers, covering row-direction edge portions of the pixel electrode layers, extending in the column direction, arranged side-by-side in the row direction, and defining row-direction edges of self-luminous regions of the pixels; a plurality of row banks disposed on the substrate and on the pixel electrode layers, covering column-direction edge portions of the pixel electrode layers and contact regions of the pixel electrode layers that are for electrically connecting the pixel electrode layers, extending in the row direction, arranged side-by-side in the column direction, and defining column-direction edges of the self-luminous regions; a plurality of light-emitting layers disposed above the pixel electrode layers in intervals between adjacent ones of the column banks; an opposing electrode layer disposed above the light-emitting layers, the opposing electrode layer including a light-transmissive material; a plurality of column light-shielding layers disposed higher than the pixel electrode layers, extending in the column direction, arranged side-by-side in the row

direction, and overlapping the row-direction edge portions of the pixel electrode layers in plan view of the substrate; and a plurality of row light-shielding layers disposed higher than the pixel electrode layers, extending in the row direction, arranged side-by-side in the column direction, overlapping the column-direction edge portions of the pixel electrode layers and partially overlapping the contact regions in plan view of the substrate.

Further, according to an example of the embodiment, a plurality of thin-film transistors are arranged in the row direction and the column direction in a matrix in the substrate, in positions corresponding to the pixels, wherein sources or drains of the thin-film transistors are connected to the pixel electrode layers via connecting recesses in which portions of the pixel electrode layers in the contact regions are recessed in the direction of the substrate, and in plan view of the substrate, the row light-shielding layers do not overlap with the connecting recesses.

According to an example of the embodiment, the light-emitting layers extend continuously in the column direction above the row banks.

According to an example of the embodiment, the light-emitting layers are interrupted by the row banks.

According to an example of the embodiment, any two of the light-emitting layers disposed in the intervals between the column banks that are adjacent to each other in the row direction emit different colors of light from each other.

According to an example of the embodiment, any one of the light-emitting layers interrupted by the row banks in the column direction emits the same color of light along its length in the column direction.

According to an example of the embodiment, an upper substrate is disposed above the opposing electrode, the upper substrate including a light-transmissive material, wherein the row light-shielding layers and the column light-shielding layers are disposed in direct contact with the upper substrate.

According to an example of the embodiment, an upper substrate is disposed above the opposing electrode, the upper substrate including a light-transmissive material, wherein the row light-shielding layers, the column light-shielding layers, or both the row light-shielding layers and the column light-shielding layers are disposed in direct contact with the upper substrate.

According to an example of the embodiment, an upper substrate is disposed above the opposing electrode, the upper substrate including a light-transmissive material, wherein the row light-shielding layers and the column light-shielding layers are disposed in direct contact with the upper substrate.

According to an example of the embodiment, the column light-shielding layers are disposed on upper surfaces of the column banks.

According to an example of the embodiment, the row light-shielding layers are disposed on upper surfaces of the row banks.

An organic EL element pertaining to the present embodiment is an organic EL element including: a substrate; a pixel electrode layer disposed on the substrate, the pixel electrode layer including a light-reflective material; banks disposed on the substrate and on the pixel electrode layer, covering edge portions of the pixel electrode layer and a portion of a contact region of the pixel electrode layer, the contact region being for electrically connecting the pixel electrode layer; a light-emitting layer disposed above the pixel electrode layer; an opposing electrode layer disposed above the light-emitting layer, the opposing electrode layer including a light-

transmissive material; and a light-shielding layer disposed higher than the pixel electrode layer, the light-shielding layer overlapping the edge portions of the pixel electrode layers and partially overlapping the contact region in plan view of the substrate.

A method of manufacturing an organic EL display panel pertaining to the present embodiment is a method including: preparing a substrate; disposing a plurality of pixel electrode layers in a row direction and a column direction in a matrix on the substrate, the pixel electrode layers including a light-reflective material; disposing a plurality of column banks on the substrate and on the pixel electrode layers, the column banks covering row-direction edge portions of the pixel electrode layers, extending in the column direction, and arranged side-by-side in the row direction; disposing a plurality of row banks on the substrate and on the pixel electrode layers, the row banks covering column-direction edge portions of the pixel electrode layers, extending in the row direction, and arranged side-by-side in the column direction; disposing a plurality of light-emitting layers above the pixel electrode layers in intervals between adjacent ones of the column banks; disposing an opposing electrode layer above the light-emitting layers, the opposing electrode layer including a light-transmissive material; disposing, higher than the pixel electrode layers, a plurality of row light-shielding layers extending in the row direction, arranged side-by-side in the column direction, and overlapping the column-direction edge portions of the pixel electrode layers in plan view of the substrate; and disposing, higher than the pixel electrode layers, a plurality of column light-shielding layers extending in the column direction, arranged side-by-side in the row direction, overlapping the row-direction edge portions of the pixel electrode layers and partially overlapping the contact regions in plan view of the substrate.

Embodiment

1. Overall Configuration of Display Device 1

The following describes an overall configuration of the display device 1 pertaining to the embodiment, with reference to FIG. 1.

As illustrated in FIG. 1, the display device 1 pertaining to the present embodiment includes an organic EL display panel 10 (hereinafter referred to as “display panel 10”) and a drive control circuit 20 connected thereto.

The display panel 10 is an organic electroluminescence (EL) panel that uses electroluminescence of organic material, in which a plurality of organic EL elements are, for example, arrayed in a matrix. The drive control circuit 20 comprises four drive circuits 21, 22, 23, 24 and a control circuit 25.

The arrangement of circuits of the drive control circuit 20 with respect to the display panel 10 in the display device 1 is not limited to the configuration illustrated in FIG. 1.

2. Circuit Configuration in Display Panel 10

The following describes circuit configuration of organic EL elements 100 included in pixels in the display panel 10, with reference to FIG. 2. FIG. 2 is a schematic circuit diagram showing a circuit configuration in each of the organic EL elements 100, which correspond to pixels 100e of the organic EL display panel 10 used in the display device 1. As shown in FIG. 2, in the display panel 10 pertaining to the present embodiment, each of the organic EL elements 100 in the pixels 100e includes two transistors Tr1, Tr2, a capacitor C, and an EL element portion EL as a light-emitter. Of the two transistors Tr1, Tr2, the transistor Tr1 is a drive transistor and the transistor Tr2 is a switching transistor.

A gate G2 of the switching transistor Tr2 is connected to a scan line Vscn and a source S2 is connected to a data line Vdat. A drain D2 of the switching transistor Tr2 is connected to a gate G1 of the drive transistor Tr1.

A drain D1 of the drive transistor Tr1 is connected to a power supply line Va, and a source S1 is connected to a pixel electrode layer (anode) of the EL element portion EL. An opposing electrode layer (cathode) of the EL element portion EL is connected to a ground line Vcat.

The capacitor C connects the drain D2 of the switching transistor Tr2, the gate G1 of the drive transistor Tr1, and the power supply line Va.

In the display panel 10, the organic EL elements 100 in the pixels 100e that each have the circuit configuration shown in FIG. 2 are disposed in a matrix to form a display region.

3. Overall Configuration of Organic EL Display Panel 10

The following describes the display device 10 pertaining to the embodiment, with reference to the drawings. The drawings are schematic diagrams, and scale may be different from an actual implementation.

FIG. 3 is a schematic plan view illustrating a portion of a display panel pertaining to the embodiment. The display panel 10 is an organic EL display panel that uses electroluminescence of an organic compound, and has a top-emission configuration emitting light from an upper surface thereof, in which a plurality of the organic EL elements 100 are arranged in a matrix on a substrate 100x (TFT substrate) on which thin film transistors (TFT) are disposed. As shown in FIG. 3, in the display panel 10, the organic EL elements 100 that make up pixels are disposed in a matrix.

In the display panel 10, in the pixels 100e, self-luminous regions 100a are formed, which are regions that emit light by using an organic compound. The self-luminous regions 100a are in three varieties, a region that emits red light 100aR, a region that emits green light 100aG, and a region that emits blue light 100aB (hereinafter, when 100aR, 100aG, 100aB are not distinguished they are referred to by “100a”). Three self-luminous regions 100aR, 100aG, 100aB lined up in a row direction are a set that make up one pixel in a color display.

As shown in FIG. 3, in the display panel 10, a plurality of pixel electrode layers 119 are arranged in a matrix on the substrate 100x. The pixel electrode layers 119 each have a rectangular shape in plan view and include a light-reflective material.

In the display panel 10, elongated banks are used, each bank of column banks 122Y extending in a column direction (direction 3Y in the drawings) and the column banks 122Y being arranged side-by-side in a row direction. Each of the column banks 122Y is disposed above row-direction edge portions of two of the pixel electrode layers 119 that are adjacent in the row direction.

When gaps between adjacent ones of the column banks 122Y are defined as intervals 122z, the display panel 10 has a configuration in which the column banks 122Y and the intervals 122z alternate in the row direction. The intervals are sub-divided into red intervals 122zR that correspond to the self-luminous regions 100aR, green intervals 122zG that correspond to the self-luminous regions 100aG, and blue intervals 122zB that correspond to the self-luminous regions 100aB (hereinafter, when the red intervals 122zR, the green intervals 122zG, and the blue intervals 122zB are not distinguished they are collectively referred to as the intervals 122z). Row-direction edges of the self-luminous regions 100a are defined by row-direction edges of the column banks 122Y.

In the intervals **122z**, each bank of row banks **122X** extends in a row direction (direction X in FIG. 3) and the row banks **122X** are arranged side-by-side in a column direction. Each of the row banks **122X** is disposed above column-direction edges of two adjacent ones of the pixel electrode layers **119** that are adjacent in the column direction. In the intervals **122z**, regions in which the row banks **122X** are disposed become not-self-luminous regions **100b**. Thus, edges of the self-luminous regions **100a** in the column direction are defined by column-direction edges of the row banks **122X**. In the intervals **122z**, the self-luminous regions **100a** and the not-self-luminous regions **100b** alternate in the column direction. In the not-self-luminous regions **100b** are disposed connection recesses **119c** that connect the pixel electrode layers **119** to the sources **S1** of the TFTs via connecting electrode layers **117**, and contact regions **119b** (contact windows) on the pixel electrode layers **119** for electrically connecting the pixel electrode layers **119**.

The column banks **122Y** and the row banks **122X** are orthogonal to each other, and the row banks **122X** overlap with the self-luminous regions **100a** in the column direction (hereinafter, when the row banks **122X** and the column banks **122Y** are not distinguished, they are referred to as the banks **122**). Further, above the pixel electrode layers **119**, column light-shielding layers **129Y** are disposed that overlap with row-direction edge portions of the pixel electrode layers **119**, and row light-shielding layers **129X** are disposed that overlap with column-direction edge portions of the pixel electrode layers **119** and do not overlap with portions of the contact regions **119b**.

4. Elements of Display Panel 10

The following describes configuration of the organic EL elements **100** in the display panel **10** with reference to the schematic cross-sectional views of FIG. 4 and FIG. 5. FIG. 4 is a schematic cross-sectional view of A-A in FIG. 3. FIG. 5 is a schematic cross-sectional view of B-B in FIG. 3.

The display panel **10** pertaining to the present embodiment is a top-emission type of organic EL display panel. In a Z axis direction at a lower end thereof is the substrate **100x** (TFT substrate) including thin film transistors. On the substrate **100x** is disposed an organic EL element portion.

4.1 Substrate 100x (TFT Substrate)

As illustrated in FIG. 4, gate electrodes **101**, **102** are disposed on a lower substrate **100p**, and a gate insulating layer **103** is disposed covering the gate electrodes **101**, **102** and a surface of the substrate **100x**. Channel layers **104**, **105** corresponding to the gate electrodes **101**, **102** are disposed on the gate insulating layer **103**. A channel protection layer **106** is disposed covering the channel layers **104**, **105** and a surface of the gate insulating layer **103**.

On the channel protection layer **106**, source electrodes **107** and drain electrodes **108** are disposed with intervals therebetween, corresponding to the gate electrodes **101** and the channel layers **104**. Similarly, source electrodes **110** and drain electrodes **109** are disposed with intervals therebetween, corresponding to the gate electrodes **102** and the channel layers **105**.

Under the source electrodes **107**, **110** and the drain electrodes **108**, **109** are disposed source lower electrodes **111**, **115** and drain lower electrodes **112**, **114**, penetrating the channel protection layer **106**. At Z axis direction lower portions thereof, the source lower electrodes **111** and the drain lower electrodes **112** are in contact with the channel layers **104**. At Z axis direction lower portions thereof, the drain lower electrodes **114** and the source lower electrodes are in contact with the channel layers **105**.

Further, the drain electrodes **108** and the gate electrodes **102** are connected to each other by connector plugs **113**, which penetrate the gate insulating layer **103** and the channel protection layer **106**.

The gate electrodes **101** correspond to the gate G2 in FIG. 2, the source electrodes **107** correspond to the source S2 in FIG. 2, and the drain electrodes **108** correspond to the drain D2 in FIG. 2. Similarly, the gate electrodes **102** correspond to the gate G1 in FIG. 1, the source electrodes **110** correspond to the source S1 in FIG. 1, and the drain electrodes **109** correspond to the drain D1 in FIG. 1. Accordingly, the switching transistor Tr2 is formed at a Y axis direction left-hand side of FIG. 4, and the drive transistor Tr1 is formed further right in the Y axis direction of FIG. 4.

However, the configuration described above is merely an example, and the transistors Tr1, Tr2 may be configured as top-gate type, bottom-gate type, channel etch type, etch stop type, etc., transistors, and are not limited to the configuration illustrated in FIG. 4.

A passivation layer **116** is disposed covering the source electrodes **107**, **110**, the drain electrodes **108**, **109**, and the channel protection layer **106**. Contact holes **116a** are formed in the passivation layer **116** above portions of the source electrodes **110**, and connecting electrode layers **117** are layered to follow the contours of the contact holes **116a**.

In the Z axis direction, lower portions of the connecting electrode layers **117** are connected to the source electrodes **110** and parts of upper portions of the connecting electrode layers **117** are on the passivation layer **116**. An interlayer insulating layer **118** is disposed on and covering the connecting electrode layers **117** and the passivation layer **116**.

4.2 Organic EL Element Portion

(1) Pixel Electrode Layers 119

For each pixel, one of the pixel electrode layers **119** is disposed on the interlayer insulating layer **118**. The pixel electrode layers **119** supply carriers to the light-emitting layers **123**; for example, when functioning as anodes they supply holes to the light-emitting layers **123**. Further, the panel **10** is a top-emission type, and therefore the pixel electrode layers **119** are light-reflective. Each of the pixel electrode layers **119** has a flat rectangular shape. The pixel electrode layers **119** are disposed on the substrate **100x** with intervals δX therebetween in the row direction and intervals δY therebetween in the column direction in the intervals **122z**. Further, the connecting recesses **119c** of the pixel electrode layers **119** are connected to the connecting electrode layers **117** via contact holes **118a** formed in the connecting electrode layers **117** and the interlayer insulating layer **118**. Thus, via the connecting electrode layers **117**, the pixel electrode layers **119** and the source S1 of the TFT are connected.

The connecting recesses **119c** are concavities in portions of the pixel electrode layers **119**, recessed towards the substrate **100x**, composed of bottom portions **119c1** and inner peripheral surface portions **119c2**. Surfaces of the inner peripheral surface portions **119c2** are preferably conical (tapered) inclined slopes. This is in order that a portion of light that leaks in the column direction from the light-emitting layers **123** can be reflected upwards.

(2) Hole Injection Layers 120, Hole Transport Layers 121

Hole injection layers **120** and hole transport layers **121** are disposed in this order on the pixel electrode layers **119**, the hole transport layers **121** being in contact with the hole injection layers **120**. The hole injection layers **120** and the hole transport layers **121** have the function of transporting holes injected from the pixel electrode layers **119** to the light-emitting layers **123**.

(3) Banks 122

The banks 122 are disposed covering edges of the pixel electrode layers 119, the hole injection layers 120, and the hole transport layers 121. The banks 122 include an insulative material. The banks 122 include column banks 122Y that extend in the column direction and are lined up in the row direction, and row banks 122X that extend in the row direction and are lined up in the column direction. The column banks 122Y and the row banks 122X form a lattice shape.

The column banks 122Y prevent flow in the row direction of ink containing an organic compound that is a material of the light-emitting layers 123, and define row-direction edges of the light-emitting layers 123. The column banks 122Y are disposed above edge portions 119a3, 119a4 in the row direction of the pixel electrode layers 119, covering portions of the pixel electrode layers 119.

The row banks 122X are for suppressing flow in the column direction of ink containing the organic compound that is a material of the light-emitting layers 123. The row banks 122X are disposed above edge portions 119a1, 119a2 in the column direction of the pixel electrode layers 119, covering portions of the pixel electrode layers 119. Thus, the row banks 122X define edges of self-luminous regions of pixels in the column direction, as described above. The row banks 122X linearly extend in the row direction and a cross-section taken parallel to the column direction shows a trapezoidal shape that tapers upwards. The row banks 122X pass through the column banks 122Y, following the row direction that is perpendicular to the column direction. The row banks 122X have upper surfaces that are lower than upper surfaces of the column banks 122Y. Thus, openings corresponding to the self-luminous regions 100a are formed by the rows banks 122X and the column banks 122Y.

(4) Light-Emitting Layers 123

The display panel 10 has a configuration in which the column banks 122Y and the intervals 122z alternate in the row direction. The light-emitting layers 123 are formed in the intervals 122z, which are defined by the column banks 122Y, and extend in the column direction. The light-emitting layers 123 that emit light of the following colors are disposed in the red intervals 122zR that correspond to the self-luminous regions 100aR, the green intervals 122zG that correspond to the self-luminous regions 100aG, and the blue intervals 122zB that correspond to the self-luminous regions 100aB.

The light-emitting layers 123 are layers including organic compounds and have a function of emitting light due to recombination of holes and electrons therein. In the intervals 122z, the light-emitting layers 123 extend linearly in the column direction.

The light-emitting layers 123 emit light only from portions thereof that are supplied with carriers from the pixel electrode layers 119, and therefore electroluminescence of organic compounds does not occur in areas in which the row banks 122X are present, the row banks 122X being inter-layer insulators. Thus, the light-emitting layers 123 emit light only from portions where the row banks 122X are not present, these portions are the self-luminous regions 100a, and edges of the self-luminous regions 100a in the column direction are defined by edges of the row banks 122X in the column direction.

Portions of the light-emitting layers 123 above the row banks 122X do not emit light and these portions are the not-self-luminous regions 100b. In other words, the not-self-luminous regions 100b are regions obtained by projecting the row banks 122X in a plan view direction. The light-

emitting layers 123 are disposed on upper surfaces of the hole transport layers 121 in the self-luminous regions 100a and on upper and side surfaces of the row banks 122X in the not-self-luminous regions 100b.

As illustrated in FIG. 4, the light-emitting layers 123 extend into the not-self-luminous regions 100b that are contiguous, and not only the self-luminous regions 100a. Thus, when forming the light-emitting layers 123, ink applied to the self-luminous regions 100a can flow in the column direction via ink applied to the not-self-luminous regions 100b, and film thickness thereof can be planarized between pixels in the column direction. However, in the not-self-luminous regions 100b, flow of ink is appropriately suppressed by the row banks 122X. Accordingly, large irregularities in film thickness in the column direction are unlikely to occur, and irregularity in luminance of each pixel is improved.

(5) Electron Transport Layer 124

The electron transport layer 124 is disposed on the banks 122 and on the light-emitting layers 123 in the openings defined by the banks 122. Further, in the present example, the electron transport layer 124 is also disposed on the column banks 122Y that are exposed above the light-emitting layers 123. The electron transport layer 124 has the function of transporting electrons injected from the opposing electrode layer 125 to the light-emitting layers 123.

(6) Opposing Electrode Layer 125

The opposing electrode layer 125 is disposed on the electron transport layer 124, covering the electron transport layer 124. The opposing electrode layer 125 is disposed continuously across an entire surface of the display panel 10 and may be connected to bus bar wiring per pixel, or per plurality of pixels (not illustrated). The opposing electrode layer 125 creates electrical paths by opposing the pixel electrode layers 119, sandwiching the light-emitting layers 123, and supplies carriers to the light-emitting layers 123. For example, when the opposing electrode layer 125 functions as a cathode, it supplies electrons to the light-emitting layers 123. The opposing electrode 125 conforms to the surface of the electron transport layer 124 and is a common electrode across the light-emitting layers 123.

The opposing electrode 125 uses a light-transmissive electrically conductive material, because the display panel 10 is a top-emission type. For example, indium tin oxide (ITO) or indium zinc oxide (IZO) may be used. Further, silver (Ag) or aluminium (Al) may be used as a thin film electrode.

(7) Sealing Layer 126

The sealing layer 126 is disposed on the opposing electrode layer 125, covering the opposing electrode layer 125. The sealing layer 126 is for suppressing degradation of the light-emitting layer 123 due to contact with moisture, air, etc. The sealing layer 126 is disposed across an entire surface of the display panel 10, covering an upper surface of the opposing electrode layer 125. As a material of the sealing layer 126, a light-transmissive material is used such as silicon nitride or silicon oxynitride, because the display panel 10 is a top-emission type.

(8) Joining Layer 127

Above the sealing layer 126 in the Z axis direction is disposed a CF substrate 131, joined to the sealing layer 126 by the joining layer 127. The CF substrate includes the upper substrate 130 and color filter layers 128 and the light-shielding layers 129 below the upper substrate in the Z axis direction. The joining layer 127 has a function of joining a back panel, in other words each layer from the substrate

100x to the sealing layer 126, to the CF substrate 131, and a function of preventing each layer from being exposed to moisture or air.

(9) Upper Substrate 130

The CF substrate 131 is disposed on and joined to the joining layer 127. The CF substrate 131 includes the upper substrate 130, the color filter layers 128, and the shielding layers 129. For the upper substrate 130, a light-transmissive material is used such as cover glass or light-transmissive resin film, because the display panel 10 is a top-emission type. Further, the upper substrate 130 can improve stiffness of the display panel 10 and prevent penetration of the display panel 10 by moisture or air.

(10) Color Filter Layers 128

Color filter layers 128 are disposed under the upper substrate 130 at locations corresponding to the self-luminous regions 100a of each color of pixel. The color filter layers 128 are light-transmissive layers for transmitting visible light of wavelengths corresponding to red, green, and blue, and have a function of transmitting light emitted from each color of pixel and correcting the chromaticity thereof. In the present example, above the self-luminous regions 100aR in the red intervals 122zR, the self-luminous regions 100aG in the green intervals 122zG, and the self-luminous regions 100aB in the blue intervals, are disposed red color filter layers 128R, green color filter layers 128G, and blue color filter layers 128B, respectively. The color filter layers 128 are formed, for example, by a process of applying ink containing a color filter material and a solvent to the upper substrate 130, the upper substrate 130 being made from cover glass that has openings corresponding to pixels in a matrix for forming color filters.

(11) Light-Shielding Layer 129

The light-shielding layer 129 is disposed under the upper substrate 130 in locations corresponding to boundaries between the self-luminous regions 100a of pixels.

The light-shielding layer 129 is a black resin layer for preventing transmission of visible light in wavelengths corresponding to red, green, and blue. For example, the light-shielding layer 129 is composed of a resin material that includes black pigment that has excellent light-absorbing and light-shielding properties. The light-shielding layer 129 is intended to prevent entry of external light into the display panel 10, prevent visibility of internal parts through the upper substrate 130, and improve contrast of the display panel 10 to suppress glare from external light. Glare from external light is a phenomenon caused by external light entering the display panel 10 from above the upper substrate 130, being reflected at the pixel electrode layers 119, and being emitted from the upper substrate 130.

Further, the light-shielding layer 129 has a function of preventing, by blocking a portion of light emitted from a pixel that leaks to adjacent pixels, boundaries between pixels becoming unclear, and has a function of increasing color purity of light emitted from pixels.

The light-shielding layer 129 includes column light-shielding layers 129Y that extend in the column direction and are lined up in the row direction, and row light-shielding layers 129X that extend in the row direction are lined up in the column direction, the column light-shielding layers 129Y and the row light-shielding layers 129X forming a matrix.

In the organic EL elements 100, the column light-shielding layers 129Y are disposed in positions overlapping row-direction edge portions 119a3, 119a4 of the pixel electrode layers 119 (hereinafter, when 119a3 and 119a4 are not distinguished, they are referred to as "edge portions 119a"),

as illustrated in FIG. 5, and the row light-shielding layers 129X are disposed in positions overlapping column-direction edge portions 119a1, 119a2 of the pixel electrode layers 119 (hereinafter, when 119a1 and 119a2 are not distinguished, they are referred to as "edge portions 119a"), as illustrated in FIG. 4. Thus, a width WX in the row direction of the column light-shielding layers 129Y is greater than a distance δX in the row direction between adjacent ones of the pixel electrode layers 119, and a width WY in the column direction of the row light-shielding layers 129X is greater than a distance δY in the column direction between adjacent ones of the pixel electrode layers 119. Thus, external light reflection in the display panel 10 can be effectively suppressed by arrangement of the light-shielding layer 129 above edge portions of the pixel electrode layers 119.

In the organic EL elements 100, as described above, the self-luminous regions 100a and the not-self-luminous regions 100b are arranged alternating with each other in the column direction. When regions where row banks 122X overlap with portions of the pixel electrode layers 119 nearest the edge portions 119a2 of the pixel electrode layers 119 on the side of the connecting recesses 119c are defined as contact regions 119b of the pixel electrode layers 119 for electrically connecting the pixel electrode layers 119, the row light-shielding layers 129X are disposed in positions that do not overlap with portions of the contact regions 119b of the pixel electrode layers 119, as illustrated in FIG. 4. According to this configuration, light emission efficiency of the organic EL elements 100 is improved. The improvement in light emission efficiency is described later.

4.3 Materials

The following illustrates one example of materials of elements shown in FIG. 4 and FIG. 5.

(1) Substrate 100x (TFT Substrate)

As the lower substrate 100p, for example, a glass substrate, a silica glass substrate, a metal substrate such as molybdenum sulfide, copper, zinc, aluminium, stainless steel, magnesium, iron, nickel, gold, or silver, a semiconductor substrate based on gallium arsenide, or a plastic substrate can be used.

As a plastic material, any thermoplastic or thermosetting resin may be used. For example, polyolefin such as polyethylene, polypropylene, ethylene-propylene copolymer, ethylene-vinyl acetate copolymer (EVA), cyclic polyolefin, modified polyolefin, polyvinyl chloride, polyvinylidene chloride, polystyrene, polyamide, polyimide (PI), polyamide-imide, polycarbonate, poly-(4-methyl-1-pentene), ionomer, acrylic resin, polymethyl methacrylate, styrene acrylonitrile copolymer (SAN), butadiene styrene copolymer, ethylene vinyl alcohol (EVOH), polyethylene terephthalate (PET), polybutylene terephthalate, polyethylene naphthalate (PEN), polyester such as polycyclohexylenedimethylene terephthalate (PCT), polyether, polyether ketone, polyether sulfone (PES), polyetherimide, polyacetal, polyphenylene oxide, modified polyphenylene oxide, polyarylate, aromatic polyester (liquid crystal polymer), polytetrafluoroethylene, polyvinylidene fluoride, other fluorine-based resins, various thermoplastic elastomers such as styrene-, polyolefin-, polyvinylidene chloride-, polyurethane-, fluorine rubber-, or chlorinated polyethylene-based thermoplastic elastomers, epoxy resin, phenol resin, urea resin, melamine resin, unsaturated polyester, silicone resin, polyurethane, or a copolymer, blend, polymer alloy, etc., primarily consisting of one of the above, or a layered body including layers of one or more of the above can be used.

As the gate electrodes 101, 102, a layered body of copper (Cu) and molybdenum (Mo) can be used, for example. The

material of the gate electrodes **101**, **102** is not limited to this example, and other metal material may be used.

As a material of the gate electrode layer **103**, as long as the material is electrically insulating a known organic material or inorganic material can be used, such as silicon oxide (SiO_2) or silicon nitride (SiN_x), for example.

As the channel layers **104**, **105**, an oxide semiconductor including at least one material selected from indium (In), gallium (Ga), and zinc (Zn) can be used.

As a material of the channel protection layer **106**, silicon oxynitride (SiON), silicon nitride (SiN), or aluminium oxide (AlOx) can be used, for example.

As the source electrodes **107**, **110**, and the drain electrodes **108**, **109**, layered bodies of copper-manganese (CuMn), copper (Cu), and molybdenum (Mo) can be used, for example.

Further, the source lower electrodes **111**, **115** and the drain lower electrodes **112**, **114** can be configured using the same materials as the source electrodes **107**, **110** and the drain electrodes **108**, **109**.

The passivation layer **116** may use silicon oxide (SiO_2), silicon nitride (SiN), or silicon oxynitride (SiON).

As the connecting electrode layers **117**, layered bodies of molybdenum (Mo), copper (Cu), and copper-manganese (CuMn) may be used (Mo approx. 20 nm, Cu approx. 375 nm, and CuMn approx. 65 nm). However, thickness of each layer is not limited to this example, and thickness of a molybdenum (Mo) layer may be in a range from 5 nm to 200 nm, thickness of a copper (Cu) layer may be in a range from 50 nm to 800 nm, and thickness of a copper-manganese (CuMn) layer may be in a range from 5 nm to 200 nm. Material used in the connecting electrode layers **117** is not limited to this example, and may be selected from appropriate electrically conductive materials.

The interlayer insulating layer is formed from an organic compound such as polyimide, polyamide, or an acrylic-based resin, and has a thickness of approx. 4000 nm. However, thickness is not limited to this example, and may be in a range from 2000 nm to 8000 nm, for example.

(2) Pixel Electrode Layers **119**

The pixel electrode layers **119** are made from metal material. In the case of the display panel **10** pertaining to the present embodiment, surfaces of the pixel electrode layers **119** are preferably highly reflective. In the display panel **10** pertaining to the present embodiment, the pixel electrode layers **119** may each be a structure in which a plurality of layers are selected from metal layers, alloy layers, and light-transmissive electrically-conductive layers. As a metal layer, a metal material including silver (Ag) or aluminium (Al) may be used, for example. As an alloy layer, silver palladium copper alloy (APC), silver palladium gold alloy (ARA), molybdenum chromium alloy (MoCr), or nickel chromium alloy (NiCr) may be used, for example. As a light-transmissive electrically-conductive material, indium tin oxide (ITO) or indium zinc oxide (IZO) may be used, for example.

(3) Hole Injection Layers **120**

The hole injection layers **120** are layers made from an oxide of silver (Ag), molybdenum (Mo), chromium (Cr), vanadium (V), tungsten (W), nickel (Ni), or iridium (Ir), or an electrically conductive polymer such as poly(3,4-ethylenedioxythiophene) polystyrene sulfonate (PEDOT:PSS).

In a case of the hole injection layers **120** being configured from a transition metal oxide, a plurality of energy levels can be obtained from a plurality of valences, and as a result hole injection becomes easier and drive voltage can be decreased.

(4) Hole Transport Layers **121**

For the hole transport layers **121**, a high molecular compound such as polyfluorene, a derivative thereof, poly arylamine, or a derivative thereof may be used, for example.

(5) Banks **122**

The banks **122** are formed from an organic material such as a resin and have insulating properties. As examples of organic materials that may be used in forming the banks **122**, acrylic-based resin, polyimide-based resin, or novalac-type phenolic resin may be used. The banks **122** preferably have organic solvent resistance. Further, during the production process, the banks **122** are subjected to an etching process, a baking process, etc., and therefore the banks **122** are preferably formed from a material having a high resistance to deformation, deterioration, etc., during such processes. Further, in order to impart water repellency to surfaces of the banks **122**, the surfaces may be fluorine-treated. Further, the banks **122** may be formed by using material that contains fluorine.

Further, structure of the banks **122** is not limited to the single-layer structure illustrated in FIG. 4, and may be a multi-layered structure having two or more layers. In such a case, each layer may be a combination of the materials above, or each layer may be an inorganic material and an organic material.

(6) Light-Emitting Layers **123**

The light-emitting layers **123**, as stated above, have a function of emitting light generated by an excited state due to recombination of holes and electrons injected thereto. As a material used in forming the light-emitting layers **123** it is necessary to use a light emitting organic material that can form a thin film by using a wet printing method.

For example, as disclosed in JP H5-163488, a phosphorescent material is preferably used, such as an oxinoid compound, perylene compound, coumarin compound, azacoumarin compound, oxazole compound, oxadiazole compound, perinone compound, pyrrole-pyrrole compound, naphthalene compound, anthracene compound, fluorene compound, fluoranthene compound, tetracene compound, pyrene compound, coronene compound, quinolone compound and azaquinolone compound, pyrazoline derivative and pyrazolone derivative, rhodamine compound, chrysene compound, phenanthrene compound, cyclopentadiene compound, stilbene compound, diphenylquinone compound, styryl compound, butadiene compound, dicyanomethylene pyran compound, dicyanomethylene thiopyran compound, fluorescein compound, pyrylium compound, thiapyrylium compound, selenapyrylium compound, telluropirylium compound, aromatic aldadiene compound, oligophenylene compound, thioxanthene compound, cyanine compound, acridine compound, metal complex of an 8-hydroxyquinoline compound, metal complex of a 2-bipyridine compound, complex of a Schiff base and a group III metal, metal complex of oxine, rare earth complex, or similar.

(7) Electron Transport Layer **124**

The electron transport layer **124** may be formed using an oxadiazole derivative (OXD), a triazole derivative (TAZ), or a phenanthroline derivative (BCP, Bphen), for example.

(8) Opposing Electrode Layer **125**

The opposing electrode layer **125** may be formed from indium tin oxide (ITO) or indium zinc oxide (IZO), for example. Further, silver (Ag) or aluminium (Al) may be used as a thin film electrode.

(9) Sealing Layer **126**

The sealing layer **126** has a function of suppressing exposure of organic layers such as the light-emitting layers **123** to moisture and air, and may be formed from a light-transmissive material such as silicon nitride (SiN) or silicon

oxynitride (SiON). Further, on a layer formed from a material such as silicon nitride (SiN) or silicon oxynitride (SiON), a sealing resin layer composed of resin material such as acrylic resin or silicone resin may be provided.

The sealing layer **126**, in the case of the display panel **10** pertaining to present embodiment, which is a top-emission type, is necessarily formed from a light-transmissive material.

(10) Joining Layer **127**

The joining layer **127** may be made from a resin adhesive, for example. The joining layer **127** may be made from a light-transmissive resin material such as acrylic resin, silicone resin, or epoxy resin.

(11) Upper Substrate **130**

As a material of the upper substrate **130**, a light-transmissive material may be used such as a glass substrate, silica glass substrate, or plastic substrate, for example.

(12) Color Filter Layers **128**

As a material of the color filter layers **128**, a known resin material may be used (examples of commercial products are color resists manufactured by JSR Co., Ltd).

(13) Light-Shielding Layer **129**

As a material of the light-shielding layer **129**, a resin material including an ultraviolet light curable resin (for example, an ultraviolet light curable acrylic resin) material as a main component and a black pigment as an additional component may be used. As the black pigment, a light-shielding material such as a carbon black pigment, titanium black pigment, metal oxide pigment, or organic pigment may be used.

5. Display Panel **10** Manufacturing Method

The following describes a method of manufacturing the display device **10**, with reference to drawings from FIG. **6A** to FIG. **9B**.

(1) Forming Substrate **100x** (TFT Substrate)

First, as illustrated in FIG. **6A**, a substrate **100x0** is prepared on which the source electrodes **107**, **110** and the drain electrodes **108**, **109** are formed. The substrate **100x0** can be manufactured by using a known TFT manufacturing method.

Subsequently, as illustrated in FIG. **6B**, the passivation layer **116** is layered on the source electrodes **107**, **110**, the drain electrodes **108**, **109**, and the channel protection layer **106**, by using a plasma CVD method or sputtering, for example.

Subsequently, as illustrated in FIG. **6C**, the contact holes **116a** are opened in the passivation layer **116** at locations above the source electrodes **110**, by using a dry etching method. Bottoms of the contact holes **116a** are formed to expose surfaces **110a** of the source electrodes **110**.

Subsequently, as illustrated in FIG. **6D**, the connecting electrode layers **117** are formed conforming to the contours of the side walls of the contact holes **116a** in the passivation layer **116**. Upper portions of the connecting electrode layers **117** are disposed on the passivation layer **116**. Sputtering may be used to forming the connecting electrode layers **117**, for example. After forming a metal film, patterning is performed by using photolithography and wet etching.

Further, the interlayer insulating layer **118** is formed covering the connecting electrode layers **117** and the passivation layer **116**, by applying the organic material and planarizing the surface thereof.

(2) Forming Pixel Electrode Layers **119**

As illustrated in FIG. **6E**, contact holes are opened in the interlayer insulating layer **118** above the connecting electrode layers **117**, and the pixel electrode layers **119** are formed.

Forming the pixel electrode layers **119** comprises forming a metal film by using a method such as sputtering or vacuum deposition, followed by patterning by using photolithography and etching. The pixel electrode layers **119** are electrically connected to the connecting electrode layers **117**.

(3) Forming Hole Injection Layers **120** and Banks **122**

As illustrated in FIG. **7A**, the hole injection layers **120** and the hole transport layers **121** are formed on the pixel electrode layers **119** and the banks **122** are formed covering edge portions of the hole transport layers **121**. The banks **122** surround the openings **122a** that define pixels, surfaces of the hole transport layers **121** being exposed by the openings **122a**.

The hole injection layers **120** and the hole transport layers **121** are formed by forming films from a metal oxide (for example, tungsten oxide) by using sputtering, then patterning to each pixel by using photolithography and etching.

The banks **122** are formed by first forming a layer composed of a bank **122** material (for example, a photosensitive resin material) on the hole transport layers **121** by using a spin coating method or similar. Subsequently, the resin layer is patterned to form the openings **122a**. Forming the openings **122a** includes arranging a mask above the resin layer, exposure to light, and developing.

(4) Forming Light-Emitting Layers **123** and Electron Transport Layer **124**

As illustrated in FIG. **7B**, from the hole transport layers **121** in the openings **122a** defined by the banks **122**, the light-emitting layers **123** and the electron transport layer **124** are formed in this order.

Forming the light-emitting layers **123** includes applying ink that contains component material into the openings **122a** defined by the banks **122**, and subsequently baking.

The electron transport layer **124** is formed by sputtering or similar.

(5) Forming Opposing Electrode Layer **125** and Sealing Layer **126**

As illustrated in FIG. **7C**, the opposing electrode layer **125** and the sealing layer **126** are formed in this order, covering the electron transport layer **124**.

The opposing electrode layer **125** and the sealing layer **126** are formed by using CVD or sputtering, for example.

(6) Forming CF Substrate **131**

The following describes a process of manufacturing the CF substrate **131**, with reference to drawings from FIG. **8A** to FIG. **8F**.

Material of the light-shielding layer **129**, including an ultraviolet-curable resin (for example, an ultraviolet-curable acrylic resin) as a primary component and a black pigment added thereto is dispersed in a solvent, adjusted to a light-shielding layer paste **129X**, and applied to one surface of the upper substrate **130**, which is light-transmissive (FIG. **8A**).

After application, the light-shielding layer paste **129X** is dried, and after the solvent has to some extent vaporized a pattern mask **PM1** that has predefined openings is overlaid on the light-shielding layer paste **129X** and irradiated with ultraviolet light from above (FIG. **8B**).

Subsequently, the light-shielding layer paste **129X** is baked, the pattern mask **PM1** and uncured **BM** paste **120X** are removed and developed, and, when cured, the light-shielding layer **129** that is rectangular in cross-section is completed (FIG. **8C**).

Subsequently, a paste **129X** is applied on a surface of the upper substrate **130** on which the light-shielding layer **129** is complete. The paste **128X** is material of the color filter layers **128**, a primary component of which is ultraviolet-curable resin, dispersed in a solvent. After application, an

amount of the solvent is removed, and a predefined pattern mask PM2 is overlaid thereon and irradiated with ultraviolet light (FIG. 8D).

Subsequently curing is performed, the pattern mask PM2 and uncured paste 128X are removed and developed to form color filter layers 128(G) (FIG. 8E).

The processes of FIG. 8D and FIG. 8E are repeated for color filter materials of each color to form color filter layers 128(R) and color filter layers 128(B). Instead of using the paste 128X, a commercial color filter product may be used.

Thus, the CF substrate 131 is formed.

(7) Attachment of CF Substrate 131 and Rear Panel

Subsequently, material of the joining layer 127, which is primarily a light-transmissive ultraviolet-curable resin such as acrylic resin, silicone resin, or epoxy resin, is applied to a rear panel, which consists of each layer from the substrate 100x to the sealing layer 126 (FIG. 9A).

Subsequently, the applied material is irradiated by ultraviolet light and the rear panel and the CF substrate 131 are then bonded to each other, maintaining their positional relationship with each other. At this time, care is taken to ensure that no gas enters between the rear panel and the CF substrate 131. Subsequently, both substrates are baked and sealed, completing the organic EL display panel 1 (FIG. 9B).

6. Effects of Display Panel 10

6.1 Improved Light Emission Efficiency

FIG. 10 is an enlarged plan view of a portion A in FIG. 3. In the organic EL elements 100, the self-luminous regions 100a and the not-self-luminous regions 100b are arranged alternating with each other in the column direction. The row light-shielding layers 129X, as shown in FIG. 4, are disposed in positions that do not overlap with portions of the contact regions 119b.

As above, according to the organic EL elements 100, only portions of the light-emitting layers 123 that are supplied carriers from the pixel electrode layers 119 emit light, and in the not-self-luminous regions 100b where the row banks 122X are present, which are inter-layer insulators, electroluminescence of organic compounds does not occur. However, light emitted from the self-luminous regions 100a of the light-emitting layers 123 is partially transmitted in all directions within the light-emitting layers 123, and therefore light that leaks in the column direction from the light-emitting layers 123 is transmitted into the row banks 122X that are adjacent, into the not-self-luminous regions 100b. A portion of such light is reflected upwards at the contact regions 119b of the pixel electrode layers 119 in the not-self-luminous regions 100b.

Thus, by arranging the row light-shielding layers 129X in positions that do not overlap with the contact regions 119b in the not-self-luminous regions 100b, while avoiding being above the pixel electrode layers 119, light that leaks in the column direction from the light-emitting layers 123 can be emitted upwards in the not-self-luminous regions 100b, improving light emission efficiency of the organic EL elements 100.

6.2 Suppressing Glare on Display Panel Surface Caused by Glare from External Light

According to the organic EL elements 100, the column light-shielding layers 129Y, as shown in FIG. 5, are disposed in positions overlapping the row-direction edge portions 119a3, 119a4 of the pixel electrode layers 119, and the row light-shielding layers 129X, as shown in FIG. 4, are disposed in positions overlapping the column-direction edge portions 119a1, 119a2 of the pixel electrode layers 119.

According to investigation by the inventors, upper surfaces of the pixel electrode layers 119 are smooth because

they are formed by a process such as sputtering or vacuum deposition, and external light glare from upper surfaces other than the edge portions 119a of the pixel electrode layers 119 is not as visible as from the edge portions 119a. In contrast, the edge portions 119a of the pixel electrode layers 119 are formed by patterning by etching, and therefore edge surfaces of the edge portions 119a are rougher than the upper surfaces and the edge surfaces become inclined away from the vertical to form trapezoidal shapes. Thus, irregular reflection occurs when external light is incident on the edge portions 119a of the pixel electrode layers 119, which are finely patterned in all directions as internal surfaces of the display panel. Light reflected in all directions that is incident on the eyes of an observer is recognized as glare on the surface of the display panel, and becomes a factor in degradation of quality of a displayed image.

According to the organic EL elements 100, the light-shielding layer 129 is disposed above the edge portions 119a of the pixel electrode layers 119, and therefore can prevent direct incidence of external light on the edge portions 119a of the pixel electrode layers 119 as well as interrupt emission of light reflected at the edge portions 119a. Thus, external light glare on the display panel 10 is effectively suppressed.

Further, even when the row light-shielding layers 129X are not above portions of the not-self-luminous regions 100b, light reflected from the edge portions 119a of the pixel electrode layer 119, which is most noticeable, is shielded by disposing the light-shielding layer 129 that includes the row light-shielding layers 129X above the edge portions 119a of the pixel electrode layers 119, and therefore external light glare does not become a problem.

6.3 Other

As described above, the light-shielding layer 129 has a function of preventing boundaries between pixels becoming unclear by blocking a portion of light emitted from a pixel that leaks to adjacent pixels, and has a function of increasing color purity of light emitted from pixels.

According to the organic EL elements 100, the width WX in the row direction of the column light-shielding layers 129Y is greater than the distance δX in the row direction between adjacent ones of the pixel electrode layers 119, and the width WY in the column direction of the row light-shielding layers 129X is greater than the distance δY in the column direction between adjacent ones of the pixel electrode layers 119. The distance δX and the distance δY between the pixel electrode layers 119 are determined by the accuracy of etching in a manufacturing process of patterning the pixel electrode layers 119, and are equivalent to each other.

Thus, the width WX in the row direction of the column light-shielding layers 129Y and the width WY in the column direction of the row light-shielding layers 129X can be made equivalent to each other, and therefore a decrease in color purity of light emitted from pixels does not occur when the decrease in color purity would be caused by color mixing between adjacent pixels when pixel boundaries become unclear as a result of emitted light leaking to adjacent pixels when the row light-shielding layers 129X are not above portions of the not-self-luminous regions 100b.

6.4 Lighting Test

Lighting tests were performed on the display panel 10 incorporating the organic EL elements 100 and luminance was measured.

FIG. 11A, FIG. 11B, and FIG. 11C are photographs captured from above the upper substrate 130, showing the pixels 100e of the display panel 10 in plan view. FIG. 11A shows one of the self-luminous regions 100a and one of the

not-self-luminous regions **100b** of one of the organic EL elements **100** in one of the red intervals **122zR**, FIG. **11B** shows one of the green intervals **122zG**, and FIG. **11C** shows one of the blue intervals **122zB**.

FIG. **12A**, FIG. **12B**, and FIG. **12C** are photographs captured from above the upper substrate **130**, showing the pixels **100e** of the display panel **10** in plan view. FIG. **12A**, FIG. **12B**, and FIG. **12C** show the same pixels shown in FIG. **11A**, FIG. **11B**, and FIG. **11C**, in a state of emitting light. In each of the red intervals **122zR**, the green intervals **122zG**, and the blue intervals **122zB**, it was confirmed that a small amount of luminance was obtained from the not-self-luminous regions **100b**. Luminance per unit area of the not-self-luminous regions **100b** of each of the intervals was approximately 8% of luminance per unit area of the self-luminous regions **100a** of the same intervals. According to the present embodiment, for each interval, the area of the not-self-luminous region **100b** is approximately 20% of the area of the self-luminous region **100a**, and therefore an increase in luminance of approximately 1.6% (0.2×0.08) was confirmed over a conventional configuration for which light is extracted from only the self-luminous region **100a**. When viewed quantitatively, this is considered to be a sufficiently significant amount for a rate of improvement in element levels of luminance.

Further, according to FIG. **12A**, FIG. **12B**, and FIG. **12C**, a significant increase in luminance can be seen in the connecting recesses **119c** on the pixel electrode layers **119** in the not-self-luminous regions **100b** when compared with peripheral regions. As above, the connecting recesses **119c** are concavities in portions of the pixel electrode layers **119**, recessed towards the substrate **100x**, composed of bottom portions **119c1** and inner peripheral surface portions **119c2**. Surfaces of the inner peripheral surface portions **119c2** are conical inclined slopes. Thus, lights that leaks in the column direction from the light-emitting layers **123** is thought to have been effectively reflected upwards towards the not-self-luminous regions **100b**.

Accordingly, it is preferable that, in plan view of the substrate **100x**, the row light-shielding layers **129X** do not overlap with the connecting recesses **119c** of the pixel electrode layers **119**, which are for connecting thin film transistor sources and the pixel electrode layers **119**.

<Modifications>

The Embodiment describes the display panel **10** pertaining to the present embodiment, but the present invention is not limited to the embodiment described above, except for essential characteristic features thereof. For example, configurations obtained by applying various modifications that could occur to a person having ordinary skill in the art or configurations of the embodiment implementing any combination of components and functions that do not depart from the scope of the present invention are included in the scope of the present invention. The following describes modifications of the display panel **10** as examples of such configurations.

(1) According to the display panel **10** pertaining to the embodiment, the CF substrate **131** including the row light-shielding layers **129X** and the column light-shielding layers **129Y** is disposed on and attached to the rear panel that comprises each layer from the substrate **100x** to the sealing layer **126**. However, according to the display panel **10** exemplified here, the row light-shielding layers **129X** and the column light-shielding layers **129Y** may be directly disposed on the rear panel.

FIG. **13** and FIG. **14** are schematic cross-sectional views at the same positions as A-A and B-B in FIG. **3**, of an organic

EL display panel **10A** pertaining to this modification. As shown in FIG. **13** and FIG. **14**, in organic EL elements **100A** pertaining to this modification, the row light-shielding layers **129X** and the column light-shielding layers **129Y** are not formed on the upper substrate **130**. Light-shielding layers **129YA** are disposed on the sealing layer **126** above peaks **122Yb** of the column banks **122Y**, extending in the column direction. Light-shielding layers **129XA** are disposed on the sealing layer **126** above peaks **122Xb** of the row banks **122X**, extending in the row direction.

According to Modification 1, as with the embodiment, the light-shielding layers **129XA** and the light-shielding layers **129YA** are disposed above peripheral portions of the pixel electrode layers **119**, and therefore glare from external light is suppressed. Further, by arranging the light-shielding layers **129XA** in positions that do not overlap with the contact regions **119b** in the not-self-luminous regions **100b**, while avoiding being above the pixel electrode layers **119**, light that leaks in the column direction from the light-emitting layers **123** can be emitted upwards in the not-self-luminous regions **100b**, improving light emission efficiency of the organic EL elements **100A**.

Further, according to this modification, high-precision positional adjustment for aligning the pixels of the rear panel and the light-shielding layer **129** of the CF substrate **131** with each other is not required. In particular, alignment between the rear panel and the CF substrate **131** can be eliminated in a configuration in which the color filter layers **128**, which are different colors for different pixels, are not disposed in the CF substrate **131**. Further, according to this modification, the display panel **10A** achieves suppression of glare from external light and improves light emission efficiency even in a configuration that does not include the CF substrate **131**, such as a transparent display.

Further, in a configuration in which the upper substrate **130**, composed of light-transmissive material, is disposed above the opposing electrode layer **125**, the row light-shielding layers **129X** may be disposed on the upper substrate **130** and the light-shielding layers **129YA** disposed on upper surfaces of the column banks **122Y**. Alternatively, the column light-shielding layers **129Y** may be disposed on the upper substrate **130** and the light-shielding layers **129XA** disposed on upper surfaces of the row banks **122X**. Thus, in addition to suppression of glare from external light and improvement of light emission efficiency, manufacturing cost can be reduced. According to this configuration, the row light-shielding layers **129X** or the column light-shielding layers **129Y** form stripes on the upper substrate **130**, and therefore, for example, die coating can be used to apply paste for the row light-shielding layers **129X** or the column light-shielding layers **129Y** onto the upper substrate **130**, which is then baked to manufacture light-shielding layers. Thus, the processes according to the embodiment described above, in which light-shielding layer paste applied onto the upper substrate **130** is exposed to ultraviolet light through the pattern mask **PM1**, become unnecessary.

(2) According to the display panel **10**, the light-emitting layers **123** extend continuously in the column direction above the row banks. However, the light-emitting layers **123** may be interrupted above the row banks to form discrete pixels. This configuration also suppresses glare from external light and improves light emission efficiency.

(3) According to the display panel **10**, any two of the light-emitting layers **123** disposed in the intervals **122z** between the column banks **122Y** that are adjacent to each other in the row direction emit different colors of light from each other and any two of the light-emitting layers **123**

disposed in the intervals **122z** between the row banks **122X** that are adjacent to each other in the column direction emit the same color of light. However, any two of the light-emitting layers **123** that are adjacent to each other in the row direction may emit the same color of light and any two of the light-emitting layers **123** that are adjacent to each other in the column direction may emit different colors of light from each other. Further, any of the light-emitting layers **123** that are adjacent to each other in the row direction and/or the column direction may emit different colors of light from each other. This configuration also suppresses glare from external light and improves light emission efficiency. Further, loss of clarity due to light emitted from pixels leaking into adjacent pixels does not occur and a decrease in color purity of light emitted from pixels caused by color mixing between adjacent pixels does not occur.

(4) According to the display panel **10**, the CF substrate **131** is, via the joining layer **127**, disposed on and attached to the rear panel that comprises each layer from the substrate **100x** to the sealing layer **126**. Further, photo spacers may be disposed between the rear panel and the CF substrate **131**.

The photo spacers (not illustrated) are primarily used for the purpose of adjusting spacing between the CF substrate **131** and the rear panel. For example, the photo spacers may each have a cylindrical shape with an axis along the Z direction, each end of the cylindrical shape in the Z axis direction being in direct contact with the CF substrate **131** or the rear panel. The photo spacers are not limited to being cylindrical shapes and may be rectangular solids, spheres, etc., and may be elongated shapes like the light-shielding layers **129XA** or the light-shielding layers **129YA**. When the photo spacers have elongated shapes along the XY plane, an effect for each organic EL element of preventing light entering adjacent ones of the light-emitting layers **123** can be achieved. A known material can be used as material of the photo spacers, exemplified by a high transparency resin material such as a methacrylic acid ester. The photo spacers may be disposed at the intersections between the light-shielding layers **129XA** and the light-shielding layers **129YA** in each pixel, but are not limited to this disposition. For example, the photo spacers may be disposed at intersections of pixels in a color display comprising sets of three colors of the color filter layers **128**.

(5) Other Modifications.

According to the display panel **10** pertaining to the embodiment there are three colors of the pixels **100e**—red pixels, green pixels, and blue pixels—but the present invention is not limited to this. For example, one type of light-emitting layer may be used, or four types of light-emitting layer emitting red, green, blue, and yellow light may be used.

Further, according to the embodiment, the pixels **100e** are arranged in a matrix, but the present invention is not limited to this. For example, when the interval of pixel regions is one pitch, adjacent pixel regions may be shifted by a half pitch in the column direction. In a high-definition display panel, shifting in the column direction becomes difficult to determine by visual inspection and for straight lines (or zigzags) of a certain width, even irregularity in film thickness is perceived as being regular. Accordingly, variation in luminance can be suppressed by a zigzag alignment, improving display quality of the display panel.

Further, according to the display panel **10**, the pixel electrode layers **119** are disposed in all of the intervals **122z**, but the present invention is not limited to this configuration.

For example, when a bus bar or similar is present, intervals **122z** in which the pixel electrode layers **119** are not present may exist.

Further, according to the display panel **10**, the color filter layers **128** are formed above the intervals **122z** of the pixels **100e** of each color. However, the display panel **10** may be configured without the color filter layers **128** above the intervals **122z**.

Further, according to the embodiment, the hole injection layers **120**, the hole transport layers **121**, the light-emitting layers **123**, and the electron transport layer **124** are formed between the pixel electrode layers **119** and the opposing electrode layer **125**, but the present invention is not limited to this. For example, a configuration may be used in which only the light-emitting layers **123** are between the pixel electrode layers **119** and the opposing electrode layer **125**, without using the hole injection layers **120**, the hole transport layers **121**, or the electron transport layer **124**. Further, for example, a configuration may include hole injection layers, hole transport layers, an electron transport layer, an electron injection layer, or some or all of these. Further, these layers need not all be composed of organic compounds, and may be composed of inorganic materials, etc.

Further, according to the embodiment, as methods of forming the light-emitting layers **123**, wet processes such as printing, spin coating, and inkjets are used, but the present invention is not limited to these. For example, dry processes such as vacuum deposition, electron beam deposition, sputtering, reactive sputtering, ion plating, and vapor phase growth may be used. Further, known materials may be appropriately applied as materials of each element.

According to the embodiment, the pixel electrode layers **119**, which are anodes, are disposed in lower portions of EL elements and TFT source electrodes **110** are connected to the pixel electrode layers **119**. However, a configuration may be applied in which the opposing electrode layer may be disposed in the lower portions of the EL elements and an anode disposed at the upper portions. In this case, the drains of the TFT are connected to the cathode disposed in the lower portion.

Further, according to the embodiment, a configuration is used in which two transistors Tr1, Tr2 are supplied for each of the pixels **100e**, but the present invention is not limited to this. For example, a configuration may be used in which one transistor is supplied for each sub-pixel, or three or more transistors are supplied for each sub-pixel.

Further, according to the embodiment, a top-emission type of EL display panel is given as one example, but the present invention is not limited to this. For example, a bottom-emission type of display panel may be used. In such cases each configuration may be modified as appropriate.

Further, according to the embodiment, the display panel **10** is an active matrix, but the present invention is not limited in this way. For example, a passive matrix may be used. More specifically, straight line electrodes parallel to the column direction and straight line electrodes parallel to the row direction may surround the light-emitting layers **123**. In such cases each configuration may be modified as appropriate. According to the embodiment, the substrate **100x** includes a TFT layer but as described above in the example of a passive matrix, the substrate **100x** may be configured without a TFT layer.

<<Review>>

The organic EL display panel pertaining to the present embodiment is an organic EL display panel in which a plurality of pixels are arranged in a row direction and a column direction in a matrix, the organic EL display panel

including: a substrate **100x**; a plurality of pixel electrode layers **119** arranged in the row direction and the column direction in a matrix on the substrate **100x**, the pixel electrode layers **119** including a light-reflective material; a plurality of column banks **122Y** disposed on the substrate **100x** and on the pixel electrode layers **119**, covering row-direction edge portions **119a3**, **119a4** of the pixel electrode layers **119**, extending in the column direction, arranged side-by-side in the row direction, and defining row-direction edges of self-luminous regions **100a** of the pixels; a plurality of row banks **122X** disposed on the substrate **100x** and on the pixel electrode layers **119**, covering column-direction edge portions **119a1**, **119a2** of the pixel electrode layers **119** and contact regions **119b** of the pixel electrode layers **119** that are for electrically connecting the pixel electrode layers **119**, extending in the row direction, arranged side-by-side in the column direction, and defining column-direction edges of the self-luminous regions **100a**; a plurality of light-emitting layers **123** disposed above the pixel electrode layers **119** in intervals **122Z** between adjacent ones of the column banks **122Y**; an opposing electrode layer **125** disposed above the light-emitting layers **123**, the opposing electrode layer **125** including a light-transmissive material; a plurality of column light-shielding layers **129Y** disposed higher than the pixel electrode layers **119**, extending in the column direction, arranged side-by-side in the row direction, and overlapping the row-direction edge portions **119a3**, **119a4** of the pixel electrode layers **119** in plan view of the substrate **100x**; and a plurality of row light-shielding layers **129X** disposed higher than the pixel electrode layers **119**, extending in the row direction, arranged side-by-side in the column direction, overlapping the column-direction edge portions **119a1**, **119a2** of the pixel electrode layers **119** and partially overlapping the contact regions **119b** in plan view of the substrate **100x**.

According to this configuration, an organic EL element that improves suppression of glare from external light on a display surface and improves light emission efficiency and an organic EL display panel using the organic EL element can be provided.

<Supplement>

The embodiment described above represents one preferred example of the present invention. Values, shapes, materials, components, component positions and connections, processes, process sequences, etc., exemplified by the embodiment are all examples, and are not intended to limit the present invention. Further, elements of the embodiment that are not recited in independent claims that represent topmost concepts of the present invention are described as optional elements constituting a preferred embodiment.

Further, the sequence in which processes are described as being executed is an illustrative example for describing the present invention, and sequences other than those described may be used. Further, a portion of the processes described may be executed simultaneously (in parallel) with another process or other processes.

Further, in order to aid understanding of the invention, the scale of elements in the drawings referenced by the embodiment may differ from actual implementation. Further, the present invention is not limited to the description of the embodiment and may be modified appropriately without departing from the scope of the present invention.

Further, at least a portion of the functionality of the embodiment and the modifications may be combined.

Further, various modifications to the embodiment that may occur to a person having ordinary skill in the art are also included in the scope of the present invention.

Although the present invention has been fully described by way of examples with reference to the accompanying drawings, it is to be noted that various changes and modifications will be apparent to those skilled in the art. Therefore, unless such changes and modifications depart from the scope of the present invention, they should be construed as being included therein.

The invention claimed is:

1. An organic EL display panel in which a plurality of pixels are arranged in a row direction and a column direction in a matrix, the organic EL display panel comprising:

- a substrate;
- a plurality of pixel electrode layers arranged in the row direction and the column direction in a matrix on the substrate, the pixel electrode layers including a light-reflective material;
- a plurality of column banks disposed on the substrate and on the pixel electrode layers, covering row-direction edge portions of the pixel electrode layers, extending in the column direction, arranged side-by-side in the row direction, and defining row-direction edges of self-luminous regions of the pixels;
- a plurality of row banks disposed on the substrate and on the pixel electrode layers, covering column-direction edge portions of the pixel electrode layers and contact regions of the pixel electrode layers that are for electrically connecting the pixel electrode layers, extending in the row direction, arranged side-by-side in the column direction, and defining column-direction edges of the self-luminous regions;
- a plurality of light-emitting layers disposed above the pixel electrode layers in intervals between adjacent ones of the column banks;
- an opposing electrode layer disposed above the light-emitting layers, the opposing electrode layer including a light-transmissive material;
- a plurality of column light-shielding layers disposed higher than the pixel electrode layers, extending in the column direction, arranged side-by-side in the row direction, and overlapping the row-direction edge portions of the pixel electrode layers in a plan view of the substrate; and
- a plurality of row light-shielding layers disposed higher than the pixel electrode layers, extending in the row direction, arranged side-by-side in the column direction, overlapping the column-direction edge portions of the pixel electrode layers and partially overlapping the contact regions in the plan view of the substrate.

2. The organic EL display panel of claim 1, further comprising:

- a plurality of thin-film transistors arranged in the row direction and the column direction in a matrix in the substrate, in positions corresponding to the pixels, wherein sources or drains of the thin-film transistors are connected to the pixel electrode layers via connecting recesses in which portions of the pixel electrode layers in the contact regions are recessed in a direction of the substrate, and

in the plan view of the substrate, the row light-shielding layers do not overlap with the connecting recesses.

3. The organic EL display panel of claim 1, wherein the light-emitting layers extend continuously in the column direction above the row banks.

4. The organic EL display panel of claim 1, wherein the light-emitting layers are interrupted by the row banks.

25

5. The organic EL display panel of claim 1, wherein any two of the light-emitting layers disposed in the intervals between the column banks that are adjacent to each other in the row direction emit different colors of light from each other.
6. The organic EL display panel of claim 4, wherein any one of the light-emitting layers interrupted by the row banks in the column direction emits a same color of light along a length in the column direction.
7. The organic EL display panel of claim 1, further comprising:
 an upper substrate disposed above the opposing electrode, the upper substrate including a light-transmissive material, wherein
 the row light-shielding layers, the column light-shielding layers, or both the row light-shielding layers and the column light-shielding layers are disposed in direct contact with the upper substrate.
8. The organic EL display panel of claim 1, wherein the column light-shielding layers are disposed on upper surfaces of the column banks.
9. The organic EL display panel of claim 1, wherein the row light-shielding layers are disposed on upper surfaces of the row banks.
10. An organic EL element, comprising:
 a substrate;
 a thin film transistor disposed in the substrate;
 a pixel electrode layer disposed on the substrate, the pixel electrode layer including a light-reflective material;
 banks disposed on the substrate and on the pixel electrode layer, covering edge portions of the pixel electrode layer and a portion of a contact region of the pixel electrode layer, the contact region being for electrically connecting the pixel electrode layer;
 a light-emitting layer disposed above the pixel electrode layer;
 an opposing electrode layer disposed above the light-emitting layer, the opposing electrode layer including a light-transmissive material; and
 a light-shielding layer disposed higher than the pixel electrode layer, the light-shielding layer overlapping the edge portions of the pixel electrode layers and partially overlapping the contact region in a plan view of the substrate, wherein

26

- a source or a drain of the thin-film transistor is connected to the pixel electrode layer via a connecting recess in which a portion of the pixel electrode layer in the contact region is recessed in a direction of the substrate, and
 in the plan view of the substrate, the light-shielding layer does not overlap with the connecting recess.
11. A method of manufacturing an organic EL display panel, the method comprising:
 preparing a substrate;
 disposing a plurality of pixel electrode layers in a row direction and a column direction in a matrix on the substrate, the pixel electrode layers including a light-reflective material;
 disposing a plurality of column banks on the substrate and on the pixel electrode layers, the column banks covering row-direction edge portions of the pixel electrode layers, extending in the column direction, and arranged side-by-side in the row direction;
 disposing a plurality of row banks on the substrate and on the pixel electrode layers, the row banks covering column-direction edge portions of the pixel electrode layers, extending in the row direction, and arranged side-by-side in the column direction;
 disposing a plurality of light-emitting layers above the pixel electrode layers in intervals between adjacent ones of the column banks;
 disposing an opposing electrode layer above the light-emitting layers, the opposing electrode layer including a light-transmissive material;
 disposing, higher than the pixel electrode layers, a plurality of column light-shielding layers extending in the column direction, arranged side-by-side in the row direction, and overlapping the row-direction edge portions of the pixel electrode layers in a plan view of the substrate; and
 disposing, higher than the pixel electrode layers, a plurality of row light-shielding layers extending in the row direction, arranged side-by-side in the column direction, overlapping the column-direction edge portions of the pixel electrode layers and partially overlapping contact regions of the pixel electrode layers in the plan view of the substrate.

* * * * *

专利名称(译)	有机EL元件，使用其的有机EL显示面板，以及有机EL显示面板的制造方法		
公开(公告)号	US10014354	公开(公告)日	2018-07-03
申请号	US15/252463	申请日	2016-08-31
[标]申请(专利权)人(译)	株式会社日本显示器		
申请(专利权)人(译)	JOLED INC. 日本展示INC.		
当前申请(专利权)人(译)	JOLED INC. 日本展示INC.		
[标]发明人	KONDO TETSURO		
发明人	KONDO, TETSURO		
IPC分类号	H01L27/32 H01L27/12 H01L51/52 H01L51/56		
CPC分类号	H01L27/3246 H01L27/1218 H01L27/3248 H01L27/3272 H01L27/3276 H01L27/3297 H01L51/5271 H01L51/56 H01L27/3274 H01L27/3258 H01L27/32		
代理机构(译)	GREENBLUM与伯恩斯坦，P.L.C.		
优先权	2015175758 2015-09-07 JP		
其他公开文献	US20170069696A1		
外部链接	Espacenet		

摘要(译)

一种有机EL显示板，其中像素排列成矩阵，包括：发光层，设置在相邻的列组之间的间隔中的像素电极层上方;相对电极层设置在发光层上方，相对电极层包括透光材料;柱状遮光层设置在像素电极层的上方，在列方向上延伸，在行方向上并排布置，并且在基板的平面图中与像素电极层的行方向边缘部分重叠;行列遮光层设置在像素电极层的上方，在行方向上延伸，在列方向上并排布置，与像素电极层的列方向边缘部分重叠，在平面图中部分重叠的接触区域基材

