



US009318723B2

(12) **United States Patent**
Kang et al.

(10) **Patent No.:** **US 9,318,723 B2**
(45) **Date of Patent:** **Apr. 19, 2016**

(54) **ORGANIC LIGHT-EMITTING DISPLAY
DEVICE**

(71) Applicant: **Samsung Display Co., Ltd.**, Yongin-si,
Gyeonggi-Do (KR)

(72) Inventors: **Tae-Wook Kang**, Yongin (KR);
Young-Seo Choi, Yongin (KR); **Jin-Ho
Kwack**, Yongin (KR)

(73) Assignee: **Samsung Display Co., Ltd.**,
Samsung-ro, Giheung-Gu, Yongin-si,
Gyeonggi-Do (KR)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/706,371**

(22) Filed: **May 7, 2015**

(65) **Prior Publication Data**

US 2015/0236299 A1 Aug. 20, 2015

Related U.S. Application Data

(63) Continuation of application No. 14/010,681, filed on
Aug. 27, 2013, now Pat. No. 9,054,060.

(30) **Foreign Application Priority Data**

Sep. 4, 2012 (KR) 10-2012-0097865

(51) **Int. Cl.**
H01L 51/00 (2006.01)
H01L 51/52 (2006.01)
H01L 27/32 (2006.01)

(52) **U.S. Cl.**
CPC **H01L 51/5256** (2013.01); **H01L 27/3276**
(2013.01)

(58) **Field of Classification Search**

CPC H01L 51/0545; H01L 51/0036; H01L
51/0541; H01L 51/5012

USPC 257/40, 642, 643, 759
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,510,913 B2	3/2009	Moro et al.
7,612,498 B2	11/2009	Sano et al.
7,648,925 B2	1/2010	Moro et al.
7,727,601 B2	6/2010	Burrows et al.
8,030,841 B2	10/2011	Kwack et al.
8,084,794 B2 *	12/2011	Kamada et al. 257/276
8,115,537 B2	2/2012	Chung et al.
8,599,112 B2	12/2013	Yamashita et al.
8,729,634 B2	5/2014	Shen et al.

(Continued)

FOREIGN PATENT DOCUMENTS

JP	2005-157141 A	6/2005
KR	10-0730220 B1	6/2007
KR	10-2009-0112387 A	10/2009


Primary Examiner — Quoc Hoang

(74) *Attorney, Agent, or Firm* — Robert E. Bushnell, Esq.

(57) **ABSTRACT**

An organic light-emitting display device including a substrate on which a display region and a non-display region are defined is described, the organic light-emitting display device comprising: a first electrode disposed on a substrate; an intermediate layer disposed on the first electrode and including an organic light-emitting layer; a second electrode disposed on the intermediate layer; an encapsulation layer disposed on the substrate; a plurality of pad units disposed on the non-display region; a wiring unit disposed on the display region; and a bridge wiring that is disposed across the display region and the non-display region and connects one of the plurality of pad units and the wiring unit to each other.

19 Claims, 6 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

9,054,060 B2 * 6/2015 Kang et al.
2007/0049155 A1 3/2007 Moro et al.

2009/0191342 A1 7/2009 Chu et al.
2009/0208754 A1 8/2009 Chu et al.
2010/0156277 A1 6/2010 Visser et al.
2010/0159792 A1 6/2010 Visser et al.

* cited by examiner

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6





FIG. 9



ORGANIC LIGHT-EMITTING DISPLAY DEVICE

CLAIM OF PRIORITY

Any and all applications for which a foreign or domestic priority claim is identified in the Application Data Sheet as filed with the present application are hereby incorporated by reference under 37 CFR 1.57. For example, this application is a continuation of U.S. application Ser. No. 14/010,681 filed on Aug. 27, 2013, which claims the benefit of Korean Patent Application No. 10-2012-0097865, filed on Sep. 4, 2012, in the Korean Intellectual Property Office, the disclosure of each of which is incorporated herein in its entirety by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to an organic light-emitting display device and a means of more effectively isolating it from external materials that might damage it.

2. Description of the Related Art

Organic light-emitting display devices using an organic light-emitting device may provide a superior moving image such as a video because they have a faster response time than liquid crystal display (LCD) devices that are currently in widespread use and may offer a wide viewing angle and a high brightness because they themselves emit light. Accordingly, organic light-emitting display devices are spotlighted as next-generation display devices.

An organic light-emitting device includes a pixel electrode and a counter electrode facing each other and an emission layer including an organic material that is disposed between the pixel electrode and the counter electrode. When the organic light-emitting device, which is highly vulnerable to moisture, oxygen, and light, comes into contact with moisture, oxygen, or light, the organic light-emitting device may be degraded. Also, when oxygen or moisture diffuses into the emission layer including the organic material, charges migrate during an electrochemical reaction at an interface between the pixel electrode and the emission layer or between the counter electrode and the emission layer, the emission layer including the organic material, to produce an oxide. The oxide then separates the emission layer including the organic material from either the pixel electrode or the counter electrode to generate dark spots or the like, thereby reducing the lifetime of the organic light-emitting device. Accordingly, a sealing technology for preventing external moisture, oxygen, or light from penetrating into the organic light-emitting device is typically used to protect the organic light-emitting device.

SUMMARY OF THE INVENTION

The present invention provides an organic light-emitting display device that prevents impurities from penetrating into the organic light-emitting display device through a boundary between an encapsulation unit, which includes the display region of the device, and a pad unit, which is located in the non-display region of the device and includes wiring and circuitry that supports the device.

According to one embodiment of the present invention, there is provided an organic light-emitting display device including a substrate on which a display region and a non-display region are defined; a first electrode disposed on the substrate; an intermediate layer disposed on the first electrode and including an organic light-emitting layer; a second elec-

trode disposed on the intermediate layer; an encapsulation layer disposed on the substrate; a plurality of pad units disposed on the non-display region; a wiring unit disposed on the display region; and a bridge wiring that is disposed across the display region and the non-display region and connects one of the plurality of pad units and the wiring unit to each other.

The pad units and the wiring unit may be formed at the same layer level.

The bridge wiring may be formed on a different layer from the pad unit and the wiring unit.

The pad unit and the wiring unit may be formed on an interlevel insulating layer formed on the substrate.

The organic light-emitting display device may further include a gate insulating layer formed between the substrate and the interlevel insulating layer, and the bridge wiring may be formed on the gate insulating layer.

The wiring unit may be connected to the bridge wiring through a via hole in the display region.

One of the plurality of pad units may be connected to the bridge wiring through a second via hole in the second non-display region.

The encapsulation layer may include a first portion including a first thin film and a second thin film that are alternately stacked on each other, the first portion being on the substrate and the encapsulation layer further comprising a second portion including the first thin film.

The first portion may be disposed on the display region, and the second portion may be disposed on the non-display region and cover one of the plurality of pad units.

The second portion may include an opening through which a portion of one of the plurality of pad units may be exposed outward.

An end of the second thin film may be surrounded by the first thin film.

The first thin film may be formed of an inorganic material.

The second thin film may be formed of an organic material.

The organic light-emitting display device may further include a thin film transistor (TFT) that is disposed on the substrate, is electrically connected to the first electrode, and may include an active layer, a source electrode, a drain electrode, and a gate electrode.

One of the plurality of pad units or the wiring unit may be formed of the same material as the source electrode or the drain electrode, and may be formed at the same layer level as the source electrode or the drain electrode.

The first electrode and the gate electrode may be formed at the same layer level.

The gate electrode may include a first conductive layer and a second conductive layer formed on the first conductive layer, and the first electrode may be formed of the same material as the first conductive layer.

The bridge wiring may be formed of the same material as the gate electrode and is formed at the same layer level as the gate electrode.

The first electrode may include a transmissive conductive material.

According to another embodiment of the present invention, there is provided an organic light-emitting display device including a substrate on which a display region and a non-display region are defined; a first electrode disposed on the substrate; an intermediate layer disposed on the first electrode and including an organic light-emitting layer; a second electrode disposed on the intermediate layer; an encapsulation layer disposed on the substrate, the encapsulation layer comprising an encapsulation unit; a plurality of pad units disposed on the non-display region; a wiring unit disposed on the display region; and a bridge wiring that is disposed across the

display region and the non-display region and connects one of the plurality of pad units and the wiring unit to each other, the wiring unit being connected to the bridge wiring through a first via hole on the display region, the pad unit being connected to the bridge wiring through a second via hole on the non-display region, the encapsulation unit including a first portion including a first thin film and a second thin film that are alternately stacked on the substrate the encapsulation unit further including a second portion including the first thin film.

The first via hole may include a first inner surface portion facing the display region and a second inner surface portion facing the non-display region.

The second inner surface portion may be formed closer to a central portion of the display region than is an external side surface of the second thin film that is positioned at an outermost portion of a plurality of the second thin films.

The second via hole may include a third inner surface portion facing the display region and a fourth inner surface portion facing the non-display region.

The third inner surface portion may be formed closer to a central portion of the display region than is an external side surface of the second thin film that is positioned at an outermost portion of a plurality of the second thin films.

BRIEF DESCRIPTION OF THE DRAWINGS

A more complete appreciation of the invention and many of the attendant advantages thereof will be readily apparent as the same becomes better understood by reference to the following detailed description when considered in conjunction with the accompanying drawings, in which like reference symbols indicate the same or similar components, wherein:

FIG. 1 is a plan view of an organic light-emitting display device according to an embodiment of the present invention;

FIG. 2 is a cross-sectional view of the organic light-emitting display device taken along a line I-I' of FIG. 1, according to an embodiment of the present invention;

FIG. 3 is an enlarged cross-sectional view of a portion 'A' of FIG. 2, according to an embodiment of the present invention;

FIG. 4 is a cross-sectional view of the organic light-emitting display device taken along a line II-II' of FIG. 1, according to an embodiment of the present invention;

FIG. 5 is a cross-sectional view of a conventional organic light-emitting display device;

FIG. 6 is a cross-sectional view of the conventional organic light-emitting display device taken along a line III-III' of FIG. 5;

FIG. 7 is a cross-sectional view of an organic light-emitting display device that is a modified example of the organic light-emitting display device of FIG. 4;

FIG. 8 is a cross-sectional view of an organic light-emitting display device that is another modified example of the organic light-emitting display device of FIG. 4;

FIG. 9 is a schematic plan view of an organic light-emitting display device according to another embodiment of the present invention; and

FIG. 10 is a cross-sectional view of the organic light-emitting display device taken along lines IX-IX and IX'-IX' of FIG. 9.

DETAILED DESCRIPTION OF THE INVENTION

The present invention will now be described more fully with reference to the accompanying drawings, in which exemplary embodiments of the invention are shown.

FIG. 1 is a plan view of an organic light-emitting display device 100 according to an embodiment of the present invention. FIG. 2 is a cross-sectional view of the organic light-emitting display device 100 taken along a line I-I' of FIG. 1, according to an embodiment of the present invention. FIG. 3 is an enlarged cross-sectional view of a portion 'A' of FIG. 2, according to an embodiment of the present invention. FIG. 4 is a cross-sectional view of the organic light-emitting display device 100 taken along a line II-II' of FIG. 1, according to an embodiment of the present invention.

Referring to FIGS. 1 through 4, the organic light-emitting display device 100 includes a substrate 101, an organic light-emitting unit 110, and an encapsulation unit 120.

The substrate 101 may be formed of a glass material having SiO₂ as a main component. The substrate 101 is not limited thereto and may be formed of a transparent plastic material. A plastic substrate may be formed of an insulating organic material that is selected from polyethersulphone (PES), polyacrylate (PAR), polyetherimide (PEI), polyethylene naphthalate (PEN), polyethylene terephthalate (PET), polyphenylene sulfide (PPS), polyallylate, polyimide, polycarbonate (PC), cellulose triacetate (TAC), and cellulose acetate propionate (CAP).

Alternatively, the substrate 101 may be formed of metal and may be in the form of a foil.

A display region A1 and a non-display region A2 are defined on the substrate 101. FIG. 1 shows a case where the non-display region A2 is positioned at one side edge of the display region A1. However, the present invention is not limited thereto. That is, the non-display region A2 may be positioned at one side edge and its opposite side edge of the display region A1, or, alternatively, may be positioned to surround the display region A1.

The organic light-emitting unit 110 including a plurality of organic light-emitting devices 52 that emit rays visible to a user may be disposed on the display region A1. In addition, each of the organic light-emitting devices 52 may include a first electrode 111, an intermediate layer 112, and a second electrode 113, which are shown in FIG. 3 and will be described below.

A pad unit 118 is disposed on the non-display region A2. The pad unit 118 transfers electrical signals or power to the display region A1. For example, an electrical signal generated from a driving circuit unit (not shown) is transmitted to the display region A1 through the pad unit 118, which is shown in FIG. 4 in detail and will be described below.

The encapsulation unit 120 may be disposed on the substrate 101 so as to prevent external moisture, air, or the like from penetrating into a thin film transistor (TFT), a light-emitting pixel, and the like included on the substrate 101. The encapsulation unit 120 seals the organic light-emitting unit 110 on the substrate 101. The encapsulation unit 120 may be formed as a plurality of thin films, which will be described below.

FIG. 2 is a cross-sectional view of the organic light-emitting display device 100 taken along a line I-I' of FIG. 1, according to an embodiment of the present invention. FIG. 3 is an enlarged cross-sectional view of a portion 'A' of FIG. 2, according to an embodiment of the present invention.

Referring to FIGS. 2 and 3, the organic light-emitting display device 100 includes the substrate 101, the organic light-emitting unit 110, and the encapsulation unit 120.

The organic light-emitting unit 110 including a light-emitting device is disposed on the substrate 101. The organic light-emitting unit 110 may include the plurality of organic light-emitting devices 52.

Each of the organic light-emitting devices **52** includes the first electrode **111**, the intermediate layer **112**, and the second electrode **113**.

The first electrode **111** and the second electrode **113** may be used as an anode and a cathode, respectively. However, the present invention is not limited thereto, and polarities of the first electrode **111** and the second electrode **113** may be switched and thus the first electrode **111** and the second electrode **113** may be used as a cathode and an anode, respectively.

If the organic light-emitting display device **100** is a bottom emission organic light-emitting display device in which an image is formed toward the substrate **101**, the first electrode **111** is a transparent electrode and the second electrode **113** is a reflective electrode. Alternatively, if the organic light-emitting display device **100** is a top emission organic light-emitting display device in which an image is formed toward the encapsulation unit **120**, the first electrode **111** is a reflective electrode and the second electrode **113** is a transparent electrode.

The transparent electrode may include at least one selected from indium tin oxide (ITO), indium zinc oxide (IZO), zinc oxide (ZnO), indium oxide (In_2O_3), indium gallium oxide (IGO), and aluminum zinc oxide (AZO).

The reflective electrode may be formed by thinly depositing a metal having a low work function, such as one of silver (Ag), magnesium (Mg), aluminum (Al), platinum (Pt), palladium (Pd), gold (Au), nickel (Ni), neodymium (Nd) iridium (Ir), chromium (Cr), lithium (Li), LiF/Ca, LiF/Al, an alloy thereof, and a compound thereof.

A surface of the first electrode **111** is exposed by a pixel defining film **114**. The pixel defining film **114** formed of at least one organic insulating material selected from polyimide, polyamide, acrylic resin, benzocyclobutene, and phenol resin may be formed by using spin coating or the like. Alternatively, the pixel defining film **114** may be formed of an inorganic insulating material selected from SiO_2 , SiN_x , Al_2O_3 , CuO_x , Tb_4O_7 , Y_2O_3 , Nb_2O_5 , and Pr_2O_3 . Alternatively, the pixel defining film **114** may be formed to have a multi-layer structure in which an organic insulating material and an inorganic insulating material are alternately stacked.

The intermediate layer **112** is disposed between the first electrode **111** and the second electrode **113**. The intermediate layer **112** may be formed to have a single-layer structure or a multi-layer structure in which one or more layers selected from an organic emissive layer (EML), a hole transport layer (HTL), a hole injection layer (HIL), an electron transport layer (ETL), and an electron injection layer (EIL) are stacked.

The organic EML may include a low molecular weight or a high molecular weight organic material.

If the organic EML is formed of a low molecular weight organic material, the intermediate layer **112** is configured such that, with respect to the organic EML, the HTL and the HIL are stacked toward the first electrode **111**, and the ETL and the EIL are stacked toward the second electrode **113**. If necessary, various other layers may be stacked. In this case, examples of the low molecular weight organic material may include copper phthalocyanine (CuPc), N,N'-Di(naphthalene-1-yl)-N,N'-diphenyl-benzidine (NPB), and tris-8-hydroxyquinoline aluminum (Alq_3).

If the organic EML is formed of a high molecular weight organic material, the intermediate layer **112** may include only the HTL stacked toward the first electrode **111** with respect to the organic EML. An HTL formed of poly(3,4-ethylenedioxythiophene) (PEDOT) or polyaniline (PANI) may be formed on the first electrode **111** by using inkjet printing or spin coating. Examples of the high molecular weight organic

material may include polyphenylene vinylene (PPV)-based high molecular weight organic material and polyfluorene-based high molecular weight organic material. A color pattern may be formed by using a typical method such as inkjet printing, spin coating, or laser-induced thermal imaging.

A first layer **115a** and a second layer **115b** may be stacked on the second electrode **113**. The first layer **115a** protects the intermediate layer **112** from plasma damage or ultra violet damage during a subsequent thin film process. The second layer **115b** increases extraction efficiency of light generated from the organic light-emitting devices **52**.

The encapsulation unit **120** seals the organic light-emitting unit **110**. The encapsulation unit **120** may include a first portion **120a** formed on the display region **A1** and a second portion **120b** formed on the non-display region **A2**.

The first portion **120a** may include first thin films **1201** and second thin films **1202** that are alternately stacked on each other and the second portion **120b** may include first thin films **1211**, **1221**, and **1231** that are stacked.

The first thin films **1201** may be formed to surround ends of the second thin films **1202**. That is, second thin films **1212** and **1222** may be interposed between the first thin films **1211**, **1221**, and **1231**, respectively, and the second thin films **1212** and **1222** may be completely surrounded by the first thin films **1211**, **1221**, and **1231**.

The first thin films **1211**, **1221**, and **1231** may be formed of an inorganic material and may function as barrier layers. For example, the first thin films **1211**, **1221**, and **1231** may be formed of AlO_x , Al_2O_3 , SiN_x , Si_3N_4 , ZrO , Al-doped zinc oxide (AZO), or SiO_x . In addition, each of the first thin films **1211**, **1221**, and **1231** may be formed as two or more layers formed of these materials. The first thin films **1211**, **1221**, and **1231** may be formed by thermal evaporation, E-beam evaporation, radio-frequency (RF) sputtering, reactive sputtering, atomic layer deposition (ALD), plasma enhanced chemical vapor deposition (PECVD), or the like.

The second thin films **1212** and **1222** may be formed of an organic material and may be formed as a planarization layer. For example, the second thin films **1212** and **1222** may be formed of acrylic monomer, silicon-based monomer, epoxy-based monomer, or a polymer formed by hardening of monomer formed by mixing at least one of the foregoing with a hardening agent. The second thin films **1212** and **1222** formed of a polymer formed by hardening acrylic monomer may be formed by thermal evaporation. The second thin films **1212** and **1222** may be formed to have a greater thickness than that of the first thin films **1211**, **1221**, and **1231**.

FIG. 4 is a cross-sectional view of the organic light-emitting display device **100** taken along a line II-II' of FIG. 1, according to an embodiment of the present invention. In detail, FIG. 4 is a cross-sectional view showing a display region **A1** and a non-display region **A2**.

Referring to FIG. 4, a buffer layer **102** is formed on the substrate **101** and a bridge wiring **116** is formed on the buffer layer **102**. The bridge wiring **116** may be formed across the display region **A1** and the non-display region **A2** on the buffer layer **102**. That is, a portion of the bridge wiring **116** is disposed on the display region **A1** and another portion is disposed on the non-display region **A2**.

An insulating layer **114** may be formed on the buffer layer **102** so as to cover the bridge wiring **116**. The insulating layer **114** may be an interlevel insulating layer.

A wiring unit **117** and the pad unit **118** are formed on the insulating layer **114**. The wiring unit **117** is formed on the display region **A1** and the pad unit **118** is formed on the non-display region **A2**. The wiring unit **117** and the pad unit **118** are formed so as to be disconnected from each other but

are electrically connected through the bridge wiring 116. That is, the wiring unit 117 and the pad unit 118 are connected to the bridge wiring 116 through first and second via holes H1 and H2, respectively. The first via hole H1 is formed in the insulating layer 114 in the display region A1 so as to connect the wiring unit 117 and the bridge wiring 116 to each other and the second via hole H2 is formed in the insulating layer 114 in the non-display region A2 so as to connect the pad unit 118 and the bridge wiring 116 to each other.

Likewise, the pad unit 118 and the wiring unit 117 are not connected directly to each other at a boundary between the display region A1 and the non-display region A2 but are connected to each other through the bridge wiring 116 that is formed as a different layer from the pad unit 118 and the wiring unit 117, thereby preventing a liquid-state material of the second thin film 1212 or a diffused component of the second thin film 1212 from being introduced through the wiring unit 117 at the boundary between the display region A1 and the non-display region A2. Such incursion of a second thin film 1212 component through the wiring unit 117 would damage the organic light-emitting devices 52 (i.e., the intermediate layer 112 including an emissive layer during the formation of the second thin film 1212).

Advantages of the present invention will be described below with reference to FIGS. 5 and 6.

FIG. 5 is a cross-sectional view of a conventional organic light-emitting display device, and, in detail, shows a boundary between the display region A1 and the non-display region A2. FIG. 6 is a cross-sectional view of the conventional organic light-emitting display device taken along a line III-III' of FIG. 5.

Referring to FIGS. 5 and 6, the conventional organic light-emitting display device includes a buffer layer 12, an insulating layer 13, a wiring unit 14, and encapsulation units 21, 22, and 23, which are formed on a substrate 11. In the conventional organic light-emitting display device, the wiring unit 14 is formed across the display region A1 and the non-display region A2 on the insulating layer 13, and the wiring unit 14 functions as a pad unit on the non-display region A2. As shown in FIG. 6, the wiring unit 14 may include three layers, 14a, 14b, and 14c. For example, layers 14a, 14b and 14c may be Ti—Al—Ti layers.

When three layers, that is, wiring units 14a, 14b, and 14c are formed and then a photolithography process is performed in order to form a pixel defining film or a spacer, the wiring units 14a, 14b, and 14c may have an overhang structure formed by etching a portion of the wiring unit 14b formed of Al, as shown in FIG. 6. When the encapsulation unit 21 is formed on the wiring units 14a, 14b, and 14c having the overhang structure, the encapsulation unit 21 does not completely cover the wiring units 14a, 14b, and 14c, that is, a partial encapsulation unit 21a is formed on the insulating layer 13, another partial encapsulation unit 21b is formed on the wiring unit 14b, and the encapsulation unit 21 is not formed on the wiring unit 14b. Likewise, an organic material for forming the encapsulation unit 22 or a diffused component of the encapsulation unit 22 may penetrate into an organic light-emitting device through the wiring unit 14b that is not covered by the encapsulation unit 21, with damage to the organic light-emitting device. The arrows labeled "B" in FIG. 6 show the direction of possible incursion of encapsulating layer components into wiring unit 14 in the conventional art.

However, in the organic light-emitting display device 100 according to an embodiment of the present invention, the pad unit 118 and the wiring unit 117 are not connected directly to each other at a boundary between the display region A1 and the non-display region A2 but are connected to each other

through the bridge wiring 116 that is formed as a different layer from the pad unit 118 and the wiring unit 117, thereby preventing a liquid-state material of the second thin film 1212 or a diffused component of the second thin film 1212 from being introduced through the wiring unit 117 at the boundary between the display region A1 and the non-display region A2. Such an incursion of a component of second thin film 1212 through wiring unit 117 would damage the organic light-emitting devices 52, that is, the intermediate layer 112 including an emissive layer, during the formation of the second thin film 1212, as described above.

FIG. 7 is a cross-sectional view of an organic light-emitting display device 100' that is a modified example of the organic light-emitting display device 100 of FIG. 4.

The organic light-emitting display device 100' of FIG. 7 is different from the organic light-emitting display device 100 of FIG. 4 in terms of a position of a first via hole H1'. That is, the first via hole H1' of the organic light-emitting display device 100' of FIG. 7 may be formed under the second thin film 1222, not under the second thin film 1212 whose end portion is closer to a central portion of the display region A1 than the end portion of the second thin film 1222. In more detail, the first via hole H1' may include a first inner surface portion H1'a facing the display region A1 and a second inner surface portion H1'b facing the non-display region A2. The second inner surface portion H1'b may be formed closer to a central portion of the display region A1 than an external side surface 1222b of the second thin film 1222 that is positioned at an outermost portion of the second thin films 1212 and 1222. As another modified example, the second inner surface portion H1'b may be disposed between the external side surface 1222b of the second thin film 1222 and an external side surface 1212b of the second thin film 1212 that is disposed inside the second thin film 1222.

FIG. 8 is a cross-sectional view of an organic light-emitting display device 100" that is another modified example of the organic light-emitting display device 100 of FIG. 4.

The organic light-emitting display device 100" of FIG. 8 is different from the organic light-emitting display device 100 of FIG. 4 in terms of a position of a second via hole H2'. That is, the second via hole H2' of the organic light-emitting display device 100" of FIG. 8 may be formed under the second thin film 1222. In more detail, the second via hole H2' may include a third inner surface portion H2'a facing the display region A1 and a fourth inner surface portion H2'b facing the non-display region A2. The third inner surface portion H2'a may be formed closer to a central portion of the display region A1 than the external side surface 1222b of the second thin film 1222 that is positioned at an outermost portion of the second thin films 1212 and 1222. As another modified example, the third inner surface portion H2'a may be disposed between the external side surface 1222b of the second thin film 1222 and the external side surface 1212b of the second thin films 1212 that is disposed inside the second thin film 1222.

As described above, although the second inner surface portion H1'b of the first via hole H1' and the third inner surface portion H2'a of the second via hole H2' are disposed inside the external side surface 1222b of the second thin film 1222 that is an outermost portion, since the second thin film 1212 is disposed inside the second thin film 1222, impurities such as external moisture and so on may be prevented from penetrating.

FIG. 9 is a schematic plan view of an organic light-emitting display device 200 according to another embodiment of the present invention. FIG. 10 is a cross-sectional view of the organic light-emitting display device 200 taken along lines

IX-IX and IX'-IX' of FIG. 9. For convenience of description, the organic light-emitting display device **200** will be described with respect to features that are different from those of the aforementioned embodiment.

Referring to the embodiment of the invention represented by FIGS. 9 and 10, an organic light-emitting display device **200** includes a substrate **201**, a first electrode **210**, an intermediate layer **212**, a second electrode **216**, a wiring unit **221**, a pad unit **220**, a bridge wiring **223**, an insulating layer **215**, and an encapsulation unit **120**.

The display region **A1** and the non-display region **A2** are defined on the substrate **201**. FIG. 9 shows a case where the non-display region **A2** is positioned at one side edge of the display region **A1**. However, the present invention is not limited thereto. That is, the non-display region **A2** may be positioned at one side edge and the opposite side edge of the display region **A1**, or alternatively, may be positioned to surround the display region **A1**.

The display region **A1** includes a plurality of organic light-emitting devices (not shown) generating light rays that are visible to a user. In addition, each of the organic light-emitting devices includes the first electrode **210**, the intermediate layer **212**, and the second electrode **216**. A thin film transistor (TFT) that is electrically connected to the first electrode **210** is disposed on the display region **A1**. The TFT includes an active layer **203**, a gate electrode **205**, a source electrode **207**, and a drain electrode **208**. In addition, a capacitor **214** is disposed on the display region **A1** and includes a first capacitor electrode **211** and a second capacitor electrode **213**, which will be described below.

The pad unit **220** is disposed on the non-display region **A2**. The pad unit **220** transfers electrical signals or power to the display region **A1**. For example, an electrical signal generated from a driving circuit unit (not shown) is transmitted to the display region **A1** through the pad unit **220**.

A buffer layer **202** may be formed on the substrate **201**. The buffer layer **202** may be formed across the display region **A1** and the non-display region **A2**.

The active layer **203** may be formed on the buffer layer **202**. In addition, the first capacitor electrode **211** may be formed on the buffer layer **202**. The first capacitor electrode **211** may be formed of the same material as the active layer **203**.

A gate insulating layer **204** may be formed on the buffer layer **202** so as to cover the active layer **203** and the first capacitor electrode **211**. The gate insulating layer **204** may be formed across the display region **A1** and the non-display region **A2**.

The gate electrode **205**, the first electrode **210**, the second capacitor electrode **213**, and the bridge wiring **223** may be formed on the gate insulating layer **204**.

The gate electrode **205** may include a first conductive layer **205a** and a second conductive layer **205b**. The first conductive layer **205a** may include a transmissive conductive material, and, in detail, may include at least one selected from indium tin oxide (ITO), indium zinc oxide (IZO), zinc oxide (ZnO), indium oxide (In₂O₃), indium gallium oxide (IGO), and aluminum zinc oxide (AZO). The second conductive layer **205b** may be formed on the first conductive layer **205a** and may include, but is not limited to, one of a metal such as Mo, MoW, an Al-based alloy and an alloy of metal.

The first electrode **210** may include a light transmissive, conductive material and may be formed of the same material as the first conductive layer **205a**. A conductive unit **210a** is disposed on a predetermined portion of the first electrode **210** and is formed of the same material as the second conductive layer **205b**.

The second capacitor electrode **213** may include a first layer **213a** and a second layer **213b**. The first layer **213a** may be formed of the same material as the first conductive layer **205a**, and the second layer **213b** may be formed of the same material as the second conductive layer **205b**.

The bridge wiring **223** may include a first wiring layer **223a** and a second wiring layer **223b**. The first wiring layer **223a** may be formed of the same material as the first conductive layer **205a** and the second wiring layer **223b** may be formed of the same material as the second conductive layer **205b**. The bridge wiring **223** may be formed on the gate insulating layer **204** across the display region **A1** and the non-display region **A2**. That is, an end of the bridge wiring **223** may be positioned on the display region **A1** and the other end of the bridge wiring **223** may be positioned on the non-display region **A2**. The wiring unit **221** and the pad unit **220** may be electrically connected to each other through the bridge wiring **223**. The bridge wiring **223** may be connected to the wiring unit **221** on the display region **A1** and may be connected to the pad unit **220** on the non-display region **A2**, which will be described below.

An interlevel insulating layer **206** may be formed on the first electrode **210**, the gate electrode **205**, and the second capacitor electrode **213**. The interlevel insulating layer **206** may include various insulating materials such as organic materials or inorganic materials. The interlevel insulating layer **206** may be formed across the display region **A1** and the non-display region **A2**.

The source electrode **207**, the drain electrode **208**, and the wiring unit **221** may be formed on the interlevel insulating layer **206** of the display region **A1**. The source electrode **207** and the drain electrode **208** may be formed to be connected to the active layer **203**.

In addition, any one of the source electrode **207** and the drain electrode **208** may be electrically connected to the first electrode **210**. In this regard, FIG. 10 shows a case where the drain electrode **208** is electrically connected to the first electrode **210**. In detail, the drain electrode **208** contacts the conductive unit **210a**.

The wiring unit **221** may be formed of the same material as the source/drain electrodes **207** and **208**. The source/drain electrodes **207** and **208** and the wiring unit **221** may each include three layers. For example, the source/drain electrodes **207** and **208** and the wiring unit **221** may each include three layers, that is, Ti—Al—Ti layers.

The wiring unit **221** may be simultaneously formed with the source electrode **207** or the drain electrode **208** by using a patterning process.

The wiring unit **221** may be connected to the bridge wiring **223** on the display region **A1**. That is, since the wiring unit **221** may be disposed on the interlevel insulating layer **206**, and the bridge wiring **223** may be disposed on the gate insulating layer **204**, the interlevel insulating layer **206** may be positioned between the wiring unit **221** and the bridge wiring **223**. A via hole **H4** may be formed in the interlevel insulating layer **206**, and thus, the wiring unit **221** and the bridge wiring **223** may be electrically connected to each other through the via hole **H4** on the display region **A1**.

The pad unit **220** may be disposed on the interlevel insulating layer **206** of the non-display region **A2**. The pad unit **220** may be formed of various conductive materials and may be formed of the same material as the source electrode **207**, the drain electrode **208**, and the wiring unit **221**. The pad unit **220** may include three layers like the wiring unit **221**. For example, the pad unit **220** may include three layers, that is, Ti—Al—Ti layers.

In addition, the pad unit **220** may be simultaneously formed with the source electrode **207** or the drain electrode **208** by using a patterning process.

The pad unit **220** may be connected to the bridge wiring **223** disposed on the non-display region **A2**. That is, since the pad unit **220** may be disposed on the interlevel insulating layer **206** and the bridge wiring **223** may be disposed on the gate insulating layer **204**, the interlevel insulating layer **206** may be disposed between the pad unit **220** and the bridge wiring **223**. A via hole **H5** may be formed in the interlevel insulating layer **206**, and, thus, the pad unit **220** and the bridge wiring **223** may be electrically connected to each other through the via hole **H5** on the non-display region **A2**.

The pad unit **220** and the wiring unit **221** may be formed so as to be disconnected from each other but may be electrically connected to each other through the bridge wiring **223**, as described above.

The insulating layer **215** may be formed on the interlevel insulating layer **206** so as to cover a TFT. The insulating layer **215** may include an opening **215a** that is formed to overlap with a predetermined region of an upper surface of the first electrode **210**.

The intermediate layer **212** may be formed to correspond to the opening **215a**. The second electrode **216** may be formed on the intermediate layer **212**.

The encapsulation unit **120** may be formed on the second electrode **216** so as to face one surface of the substrate **201**. The encapsulation unit **120** may be formed to protect the intermediate layer **212** and the like from external moisture, air, or the like. As described above, the encapsulation unit **120** may include the first portion **120a** formed on the display region **A1** and the second portion **120b** formed on the non-display region **A2**.

The first portion **120a** may be formed by alternately stacking the first thin films **1201** and the second thin films **1202** on each other, and the second portion **120b** may be formed by alternately stacking the first thin films **1211**, **1221**, and **1231** on each other.

The first thin films **1201** may be formed to surround ends of the second thin films **1202**. That is, the second thin films **1212** and **1222** may be interposed between the first thin films **1211**, **1221**, and **1231**, respectively, and may be respectively surrounded by the first thin films **1211**, **1221**, and **1231**.

The first thin films **1211**, **1221**, and **1231** may be formed of an inorganic material and may function as a barrier layer. For example, the first thin films **1211**, **1221**, and **1231** may be formed of one of AlO_x , Al_2O_3 , SiN_x , Si_3N_4 , ZrO , Al-doped zinc oxide (AZO), and SiO_x . In addition, the first thin films **1211**, **1221**, and **1231** may be formed as two or more layers of these materials. The first thin films **1211**, **1221**, and **1231** may be formed by one of thermal evaporation, E-beam evaporation, radio-frequency (RF) sputtering, reactive sputtering, atomic layer deposition (ALD), plasma enhanced chemical vapor deposition (PECVD), and the like.

The second thin films **1212** and **1222** may be formed of an organic material and may be formed as a planarization layer. For example, the second thin films **1212** and **1222** may be formed of one of an acrylic monomer, a silicon-based monomer, an epoxy-based monomer, and a polymer formed by hardening of the monomer formed by mixing at least one of the foregoing with a hardening agent. The second thin films **1212** and **1222** formed of a polymer formed by hardening acrylic monomer may be formed by thermal evaporation. The second thin films **1212** and **1222** may be formed to have a greater thickness than that of the first thin films **1211**, **1221**, and **1231**.

According to an embodiment of the present invention, the pad unit **118** and the wiring unit **117** may not be connected directly to each other at a boundary between the display region **A1** and the non-display region **A2** but may be connected to each other through the bridge wiring **116** that is formed as a different layer from the pad unit **118** and the wiring unit **117**, thereby preventing a liquid-state material of the second thin film **1212** or a diffused component of the second thin film **1212** from being introduced through the wiring unit **117** at the boundary between the display region **A1** and the non-display region **A2**. This would damage the organic light-emitting devices **52**, that is, the intermediate layer **112** including an emissive layer, during the formation of the second thin film **1212**. In particular, embodiments of the present invention do not require any disconnection in the inorganic encapsulation layer **21**, which is shown in FIG. 6 and may correspond to first thin film **1211** in the embodiments of FIGS. 4, 7, 8 and 10. Thus, unwanted intrusion of organic components or environmental contaminants through gaps in the inorganic encapsulation layer **21** may be prevented.

In addition, the pad unit **220** is simultaneously formed with the source electrode **207** or the drain electrode **208**, thereby simplifying a manufacturing process and easily reducing the thickness of the organic light-emitting display device **200**.

In addition, the first electrode **210** is formed of the same material at the same layer level as the first conductive layer **205a** of the gate electrode **205**, thereby simplifying a manufacturing process and reducing errors during the formation of the first electrode **210** and the gate electrode **205**. In addition, the thickness of the organic light-emitting display device **200** may be easily reduced in comparison to more traditional designs in which the first electrode is formed above a TFT comprising a gate electrode and formed in a layer that is distinct from the one including the gate electrode.

According to the one or more embodiments of the present invention, impurities may be prevented from penetrating into an organic light-emitting display device through a boundary between an encapsulation unit and a pad unit.

While the present invention has been particularly shown and described with reference to exemplary embodiments thereof, it will be understood by those of ordinary skill in the art that various changes in form and details may be made therein without departing from the spirit and scope of the present invention as defined by the following claims.

What is claimed is:

1. An organic light-emitting display device, comprising: a substrate on which a first region including a display region and a second region including a non-display region outside the first region are defined; a first electrode disposed on the substrate; an intermediate layer disposed on the first electrode and comprising an organic light-emitting layer; a second electrode disposed on the intermediate layer; an encapsulation layer disposed on the substrate; a pad unit disposed on the second region; a wiring unit disposed on the first region; and a bridge wiring that is disposed across the first region and the second region and connects the pad unit and the wiring unit to each other, the bridge wiring including a first wiring layer and a second wiring, layer on the first wiring layer.

2. The organic light-emitting display device of claim 1, the pad unit and the wiring unit being, formed on a first insulating layer formed on the substrate.

3. The organic light-emitting display device of claim 2, further comprising a second insulating layer formed between

13

the substrate and the first insulating layer, the bridge wiring being formed on the second insulating layer.

4. The organic light-emitting display device of claim 3, the wiring unit being connected to the bridge wiring through a first via hole in the first region, and the pad unit being connected to the bridge wiring through a second via hole in the second region.

5. The organic light-emitting display device of claim 1, further comprising a thin film transistor (TFT) that is disposed on the substrate, is electrically connected to the first electrode, and comprises an active layer, a source electrode, a drain electrode, and a gate electrode.

6. The organic light-emitting display device of claim 5, the pad unit and the wiring unit being formed of the same material as one of the source electrode and the drain electrode, the pad unit and the wiring unit being formed at the same layer level as one of the source electrode and the drain electrode.

7. The organic light-emitting display device of claim 5, the first electrode and the gate electrode being formed at the same layer level.

8. The organic light-emitting display device of claim 5, the gate electrode comprising a first conductive layer and a second conductive layer formed on the first conductive layer.

9. The organic light-emitting display device of claim 8, the first wiring layer being formed of the same material as the first conductive layer, the second wiring layer being formed of the same material as the second conductive layer.

10. The organic light-emitting display device of claim 9, the first electrode being formed of the same material as the first conductive layer.

11. The organic light-emitting display device of claim 10, the first electrode comprising a transmissive conductive material.

12. An organic light-emitting display device, comprising:
a substrate on which a first region including a display region and a second region including a non-display region outside the first region are defined;
a first electrode disposed on the substrate;
an intermediate layer disposed on the first electrode and comprising an organic light-emitting layer;
a second electrode disposed on the intermediate layer;
a first insulating layer formed on the substrate;
a pad unit disposed on the second region, the pad unit being formed on the first insulating layer;
a wiring unit disposed on the first region, the wiring unit being formed on the first insulating layer;
a second insulating layer formed between the substrate and the first insulating layer;

14

a bridge wiring that is disposed across the first region and the second region, the bridge wiring being formed on the second insulating layer, the wiring unit being connected to the bridge wiring through a first via hole in the first region, and the pad unit being connected to the bridge wiring through a second via hole in the second region; and

an encapsulation layer disposed on the substrate, the encapsulation layer comprising a first portion comprising a first thin film and a second thin film that are alternately stacked on each other, the first portion being disposed on the substrate, the encapsulation layer further comprising a second portion comprising the first thin film,

wherein a lowest thin film of the encapsulation layer has a first part corresponding to a central portion of the bridge wiring and a second part in the wiring unit and corresponding to the first via hole, the first part has a first surface facing the bridge wiring, the second part has a second surface facing the wiring unit, and the first surface is closer to the substrate than the second surface.

13. The organic light-emitting display device of claim 12, the first portion being disposed on the first region, the second portion being disposed on the second region and covering the pad unit.

14. The organic light-emitting display device of claim 13, the second portion comprising an opening through which a portion of the pad unit is exposed outward.

15. The organic light-emitting display device of claim 12, an end of the second thin film being surrounded by the first thin film.

16. The organic light-emitting display device of claim 12, the first thin film being formed of an inorganic material.

17. The organic light-emitting display device of claim 12, the second thin film being formed of an organic material.

18. The organic light-emitting display device of claim 12, wherein the lowest thin film of the encapsulation layer further has a third part on the pad unit and corresponding to the second via hole, the third part has a third surface facing the pad unit, and the first surface is closer to the substrate than the third surface.

19. The organic light-emitting display device of claim 18, a distance between the second surface and the substrate is identical to a distance between the third surface and the substrate.

* * * * *

专利名称(译)	有机发光显示装置		
公开(公告)号	US9318723	公开(公告)日	2016-04-19
申请号	US14/706371	申请日	2015-05-07
[标]申请(专利权)人(译)	三星显示有限公司		
申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	KANG TAE WOOK CHOI YOUNG SEO KWACK JIN HO		
发明人	KANG, TAE-WOOK CHOI, YOUNG-SEO KWACK, JIN-HO		
IPC分类号	H01L51/00 H01L51/52 H01L27/32		
CPC分类号	H01L27/3276 H01L51/5256 H01L27/3272		
审查员(译)	HOANG , QUOC		
优先权	1020120097865 2012-09-04 KR		
其他公开文献	US20150236299A1		
外部链接	Espacenet USPTO		

摘要(译)

描述了一种有机发光显示装置，包括其上限定显示区域和非显示区域的基板，该有机发光显示装置包括：设置在基板上的第一电极；中间层，设置在第一电极上并包括有机发光层；第二电极设置在中间层上；封装层设置在基板上；多个焊盘单元设置在非显示区域上；布线单元设置在显示区域上；以及跨越显示区域和非显示区域设置的桥接布线，并且将多个焊盘单元和布线单元中的一个彼此连接。

