



US009461263B2

(12) **United States Patent**
You et al.

(10) **Patent No.:** **US 9,461,263 B2**
(45) **Date of Patent:** **Oct. 4, 2016**

(54) **ORGANIC LIGHT EMITTING DISPLAY APPARATUS AND METHOD OF MANUFACTURING THE SAME**

USPC 257/E51.001, 40; 438/99, 46
See application file for complete search history.

(71) Applicants: **Chun-Gi You**, Yongin (KR); **Joon-Hoo Choi**, Yongin (KR); **Jong-Hyun Park**, Yongin (KR); **Kyung-Hoon Park**, Yongin (KR); **Jeong-Hwan Kim**, Yongin (KR); **Seong-Kweon Heo**, Yongin (KR)

(56)

References Cited

U.S. PATENT DOCUMENTS

7,022,591	B2 *	4/2006	Chang	438/482
7,132,716	B2 *	11/2006	Moon et al.	257/347
2005/0161680	A1	7/2005	Kawakami et al.	
2006/0238115	A1 *	10/2006	Lee et al.	313/504
2011/0042678	A1 *	2/2011	Kim et al.	257/72
2011/0062434	A1 *	3/2011	Eguchi et al.	257/43
2011/0108848	A1	5/2011	Lee et al.	

(Continued)

FOREIGN PATENT DOCUMENTS

CN	100372099	C	2/2008
CN	102117826	A	7/2011

(Continued)

OTHER PUBLICATIONS

Taiwanese Office Action dated Jul. 11, 2016 for corresponding Taiwan Patent Application No. 101139158; Chun-Gi You, et al.

Primary Examiner — Thao X Le

Assistant Examiner — J. R. Oakley

(74) *Attorney, Agent, or Firm* — Lee & Morse, P.C.

(72) Inventors: **Chun-Gi You**, Yongin (KR); **Joon-Hoo Choi**, Yongin (KR); **Jong-Hyun Park**, Yongin (KR); **Kyung-Hoon Park**, Yongin (KR); **Jeong-Hwan Kim**, Yongin (KR); **Seong-Kweon Heo**, Yongin (KR)

(73) Assignee: **SAMSUNG DISPLAY CO., LTD.**, Yongin, Gyeonggi-do (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 8 days.

(21) Appl. No.: **13/676,707**

(22) Filed: **Nov. 14, 2012**

(65) **Prior Publication Data**

US 2013/0292651 A1 Nov. 7, 2013

(30) **Foreign Application Priority Data**

May 3, 2012 (KR) 10-2012-0047121

(51) **Int. Cl.**
H01L 27/32 (2006.01)
H01L 51/50 (2006.01)
H01L 51/52 (2006.01)

(52) **U.S. Cl.**
CPC **H01L 51/5092** (2013.01); **H01L 27/326** (2013.01); **H01L 27/3248** (2013.01); **H01L 51/5206** (2013.01); **H01L 51/5212** (2013.01); **H01L 27/3265** (2013.01); **H01L 2251/5392** (2013.01)


(58) **Field of Classification Search**
CPC H01L 27/3248; H01L 27/326–27/3265

(57)

ABSTRACT

The organic light emitting display apparatus includes a substrate; a buffer film on the substrate, the buffer film including a via hole, a thin film transistor (TFT) on the buffer film, the TFT including an active layer, a gate electrode, a source electrode, and a drain electrode, a first electrode electrically connected to one of the source electrode and the drain electrode and corresponding to the via hole; an intermediate layer on the first electrode, the intermediate layer including an organic emission layer, and a second electrode on the intermediate layer.

13 Claims, 11 Drawing Sheets



(56)

References Cited**FOREIGN PATENT DOCUMENTS****U.S. PATENT DOCUMENTS**

2011/0127499 A1* 6/2011 Yoon et al. 257/40
2011/0204369 A1* 8/2011 Ha et al. 257/59
2011/0260605 A1* 10/2011 Adachi et al. 313/506
2012/0032207 A1* 2/2012 Nishiyama et al. 257/89
2012/0097952 A1* 4/2012 Kang et al. 257/59
2012/0168761 A1* 7/2012 Park et al. 257/59
2013/0069107 A1* 3/2013 Nozaki et al. 257/103

KR 10-2004-0000629 A 1/2004
KR 1020040000629 * 1/2004 H04B 33/22
KR 10-2004-0037889 A 5/2004
KR 10-2006-0028251 A 3/2006
KR 10-2007-0068092 A 6/2007
KR 101189137 * 6/2007 H05B 33/10

* cited by examiner

FIG. 2A




FIG. 2B




FIG. 2D




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 3D




FIG. 3E





FIG. 3F



ORGANIC LIGHT EMITTING DISPLAY APPARATUS AND METHOD OF MANUFACTURING THE SAME

CROSS-REFERENCE TO RELATED PATENT APPLICATION

This application claims the benefit under 35 U.S.C. §119 of Korean Patent Application No. 10-2012-0047121, filed on May 3, 2012, in the Korean Intellectual Property Office, the disclosure of which is incorporated herein in its entirety by reference.

BACKGROUND

1. Field of the Invention

Embodiments relate to an organic light emitting display apparatus, and a method of manufacturing the same.

2. Description of the Related Art

Recently, display apparatuses have been replaced with portable thin film flat panel display apparatuses. An organic light emitting display apparatus is a self-emitting display apparatus that has a large viewing angle, improved contrast characteristics, and a fast response speed. Thus, the organic light emitting display apparatus has drawn attention as a next-generation display apparatus.

An organic light-emitting display apparatus includes an intermediate layer, a first electrode, and a second electrode. The intermediate layer includes an organic emission layer. When a voltage is applied to the first and second electrodes, visible light is emitted from the organic emission layer.

SUMMARY

Embodiments are directed to an organic light emitting display apparatus including a substrate, a buffer film on the substrate, the buffer film including a via hole, a thin film transistor (TFT) on the buffer film, the TFT including an active layer, a gate electrode, a source electrode, and a drain electrode, a first electrode electrically connected to one of the source electrode and the drain electrode and corresponding to the via hole, an intermediate layer on the first electrode, the intermediate layer including an organic emission layer, and a second electrode on the intermediate layer.

The organic light emitting display apparatus may further include a gate insulating film disposed to insulate the gate electrode and the active layer from each other. The first electrode may be on the gate insulating film. The gate insulating film may fill the via hole. The via hole may be larger than the first electrode.

The first electrode may contain indium tin oxide (ITO), indium zinc oxide (IZO), zinc oxide (ZnO), indium oxide (In_2O_3), indium gallium oxide (IGO), or aluminum zinc oxide (AZO).

The first electrode may be on a layer on which the gate electrode is disposed, and may contain at least one material selected from among materials forming the gate electrode.

The gate electrode may include a first conductive layer and a second conductive layer, the second conductive layer being on the first conductive layer. The first electrode may be on a layer on which the first conductive layer is disposed. The first electrode may include a same material as the first conductive layer.

The intermediate layer may be disposed apart from the TFT to not overlap with the TFT.

The organic light emitting display apparatus may further include a capacitor including a first capacitor electrode on a

layer on which the active layer is disposed, and a second capacitor electrode on a layer on which the gate electrode is disposed.

Embodiments are also directed to a method of manufacturing an organic light emitting display apparatus, the method including forming a buffer film on a substrate to include a via hole, forming a thin film transistor (TFT) on the buffer film, the TFT including an active layer, a gate electrode, a source electrode, and a drain electrode, forming a first electrode to be electrically connected to one of the source electrode and the drain electrode and to correspond to the via hole, forming an intermediate layer on the first electrode, the intermediate layer including an organic emission layer, and forming a second electrode on the intermediate layer.

The buffer film and the active layer may be formed according to a patterning process using a halftone mask.

The forming of the buffer film may include forming a buffer film material layer on the substrate, forming the active layer on the buffer film material layer, forming an etch mask to cover the active layer and to not cover a region in which the via hole is to be formed, and forming the via hole by performing an etch process by using the etch mask.

The method may further include performing an ashing process after the etch process is performed, the ashing process being performed before the etch mask is removed.

The forming of the active layer may include at least a crystallization process.

The method may further include forming a gate insulating film between the gate electrode and the active layer, and forming the first electrode on the gate insulating film.

The gate insulating film may be formed to fill the via hole. The via hole may be larger than the first electrode.

BRIEF DESCRIPTION OF THE DRAWINGS

Features will become apparent by describing in detail exemplary embodiments thereof with reference to the attached drawings in which:

FIG. 1 is a schematic cross-sectional view of an organic light emitting display apparatus according to an embodiment;

FIGS. 2A to 2D are schematic cross-sectional views depicting stages in a method of manufacturing an organic light emitting display apparatus, according to an embodiment; and

FIGS. 3A to 3F are schematic cross-sectional views depicting stages in a method of manufacturing an organic light emitting display apparatus, according to another embodiment.

DETAILED DESCRIPTION

Example embodiments will now be described more fully hereinafter with reference to the accompanying drawings; however, they may be embodied in different forms and should not be construed as limited to the embodiments set forth herein. Rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope thereof to those skilled in the art.

As used herein, expressions such as “at least one of,” when preceding a list of elements, modify the entire list of elements and do not modify the individual elements of the list.

FIG. 1 is a schematic cross-sectional view of an organic light emitting display apparatus 100 according to an embodiment. Referring to FIG. 1, the organic light emitting display

apparatus **100** includes a substrate **101**, a buffer film **102**, a first electrode **108**, a thin film transistor (TFT), an intermediate layer **140**, a second electrode **150**, and a capacitor **110**.

The TFT includes an active layer **103**, a gate electrode **107**, a source electrode **111**, and a drain electrode **112**.

The capacitor **110** includes a first capacitor electrode **113** and a second capacitor electrode **117**.

The elements of the organic light emitting display apparatus **100** are described in detail below.

The substrate **101** may be formed of any suitable material such as a SiO₂-based transparent glass material, or a transparent plastic material. The transparent plastic material may include at least one material selected from among various organic materials.

The buffer film **102** is formed on the substrate **101**. The buffer film **102** provides a flat surface on the substrate **101** and protects the substrate **101** against moisture and foreign substances. The buffer film **102** may be formed of any of various materials for providing such functions. For example, the buffer film **102** may contain an inorganic material, e.g., a silicon oxide, a silicon nitride, a silicon oxynitride, an aluminum oxide, an aluminum nitride, a titanium oxide, or a titanium nitride; an organic material, e.g., polyimide, polyester, or acryl, or a stacked structure including at least one from among these materials.

The buffer film **102** includes a via hole **102a**. A predetermined region of the substrate **101** is not covered by the buffer film **102** due to the via hole **102a**. The buffer film **102** has a predetermined thickness, and the via hole **102a** has a side surface corresponding to the thickness of the buffer film **102**.

The active layer **103** and the first capacitor electrode **113** are formed on the buffer film **102**. The active layer **103** and the first capacitor electrode **113** may be formed of the same material. The active layer **103** and the first capacitor electrode **113** may contain a semiconductor material, e.g., a silicon material.

A gate insulating film **104** is formed on the buffer film **102** to cover the active layer **103** and the first capacitor electrode **113**. In this case, the gate insulating film **104** is disposed to fill the via hole **102a** of the buffer film **102**.

The gate electrode **107**, the first electrode **108** and the second capacitor electrode **117** are formed on the gate insulating film **104**.

The gate electrode **107** includes a first conductive layer **105** and a second conductive layer **106**. The first conductive layer **105** contains a transmissive conductive material, e.g., indium tin oxide (ITO), indium zinc oxide (IZO), zinc oxide (ZnO), indium oxide (In₂O₃), indium gallium oxide (IGO), or aluminum zinc oxide (AZO).

The second conductive layer **106** may be formed on the first conductive layer **105** to contain metal or an alloy, e.g., molybdenum (Mo), tungsten molybdenum (MoW), or an aluminum (Al)-based alloy, as examples. For example, the second conductive layer **106** may have a stacked structure of molybdenum (Mo), aluminum (Al), and molybdenum (Mo).

The first electrode **108** contains a transmissive conductive material, e.g., the transmissive conductive material used to form the first conductive layer **105**. A conductive portion **108a** is disposed on an upper region of the first electrode **108**. The conductive portion **108a** may be formed of the material used to form the second conductive layer **106**.

The first electrode **108** is formed to correspond to the via hole **102a** of the buffer film **102**. Specifically, the via hole **102a** may be larger than the first electrode **108**.

The second capacitor electrode **117** may be formed of the material used to form the first conductive layer **105**.

Although FIG. 1 illustrates that the second capacitor electrode **117** has a single-layered structure, the present invention is not limited thereto. The second capacitor electrode **117** may have a multi-layered structure, similar to the gate electrode **107**.

An interlayer insulating layer **109** is formed on the first electrode **108**, the gate electrode **107**, and the second capacitor electrode **117**. The interlayer insulating layer **109** may contain any of various insulating materials, e.g., an organic material and an inorganic material. In this case, the interlayer insulating layer **109** is formed not to cover at least one upper region of the second capacitor electrode **117**. In detail, the interlayer insulating layer **109** may include an aperture **109a** corresponding to the second capacitor electrode **117**.

The interlayer insulating layer **109** is also formed not to cover at least one upper region of the first electrode **108**.

The source electrode **111** and the drain electrode **112** are formed on the interlayer insulating layer **109**. The source electrode **111** and the drain electrode **112** are connected to the active layer **103**. The source electrode **111** and the drain electrode **112** may be formed of any of various conductive materials, e.g., at least one metal selected from the group consisting of gold (Au), palladium (Pd), platinum (Pt), nickel (Ni), rhodium (Rh), ruthenium (Ru), iridium (Ir), osmium (Os), aluminum (Al), molybdenum (Mo), neodymium (Nd), and tungsten (W).

One of the source electrode **111** and the drain electrode **112** is electrically connected to the first electrode **108**. Referring to FIG. 1, the drain electrode **112** is electrically connected to the first electrode **108**. Specifically, the drain electrode **112** contacts the conductive portion **108a** and is thus electrically connected to the first electrode **108**.

A pixel defining film **130** is formed on the interlayer insulating layer **109** to cover the source electrode **111**, the drain electrode **112**, and the second capacitor electrode **117**. The pixel defining film **130** is formed not to cover at least one upper region of the first electrode **108**.

The intermediate layer **140** is formed on the first electrode **108**. In detail, the intermediate layer **140** is formed to contact the at least one upper region of the first electrode **108** that is not covered with the pixel defining film **130**.

The intermediate layer **140** includes an organic emission layer to emit visible light.

The intermediate layer **140** may be formed of a low-molecular weight organic film or a high-molecular weight organic film. If the organic emission layer of the intermediate layer **140** is formed of a low-molecular weight organic film, then the intermediate layer **140** may include a hole injection layer (HIL), a hole transport layer (HTL), the organic emission layer, an electron transport layer (ETL), an electron injection layer (EIL), and the like.

The HIL may be formed of a phthalocyanine compound, e.g., copper phthalocyanine (CuPc), or a starburst amine, e.g., TCTA, m-MTDATA, or m-MTDAPB.

The HTL may be formed of N,N-bis(3-methylphenyl)-N,N-diphenyl-[1,1-biphenyl]-4,4'-diamine (TPD), N,N'-di(naphthalene-1-yl)-N,N-diphenyl-benzidine (α -NPD), or the like.

The ETL may be formed of LiF, NaCl, CsF, Li₂O, BaO, Liq, or the like.

The ETL may be formed of tris(8-hydroxy-quinolino) aluminum (Alq3).

The organic emission layer may include a host material and a dopant material.

Examples of the host material may include tris(8-hydroxy-quinolino) aluminum (Alq3), 9,10-di(naphth-2-yl)anthracene (AND), 3-tert-butyl-9,10-di(naphth-2-yl) anthra-

cene (TBADN), 4,4'-bis(2,2-diphenyl-ethene-1-yl)-4,4'-dimethylphenyl (DPVBi), 4,4'-bis(2,2-diphenyl-ethene-1-yl)-4,4'-dimethylphenyl (p-DMDPVBi), tert(9,9-diarylfluorene)s (TDAF), 2-(9,9'-spirobifluorene-2-yl)-9,9'-Spirobifluorene (BSDF), 2,7-bis(9,9'-spirobifluorene-2-yl)-9,9'-spirobifluorene (TSDF), bis(9,9-diarylfluorene)s (BDAF), 4,4'-bis(2,2-diphenyl-ethene-1-yl)-4,4'-di-(tert-butyl)phenyl (p-TDPVBi), 1,3-bis(carbazol-9-yl)benzene (mCP), 1,3,5-tris(carbazol-9-yl)benzene (tCP), 4,4',4''-tris(carbazol-9-yl)triphenylamine (TcTa), 4,4'-bis(carbazol-9-yl)biphenyl (CBP), 4,4'-bis(9-carbazolyl)-2,2'-dimethylbiphenyl (CBDP), 4,4'-bis(carbazol-9-yl)-9,9-dimethylfluorene (DMFL-CBP), 4,4'-bis(carbazol-9-yl)-9,9-bis(9-phenyl-9H-carbazol)fluorene (FL-4CBP), 4,4'-bis(carbazol-9-yl)-9,9-di-tolyl-fluorene (DPFL-CBP), 9,9-bis(9-phenyl-9H-carbazol)fluorene (FL-2CBP), or the like.

Examples of the dopant material may include 4,4'-bis[4-(di-p-tolylamino)styryl]biphenyl (DPAVB), 9,10-di(naph-2-yl)anthracene (ADN), 3-tert-butyl-9,10-di(naphthalen-2-yl)anthracene (TBADN), and the like.

The second electrode 150 is formed on the intermediate layer 140.

Although not shown, an encapsulating member (not shown) may be formed on the second electrode 150. The encapsulating member may be formed of an organic material or an inorganic material.

Operations and advantages of the organic light emitting display apparatus 100 according to the current embodiment will be now briefly described.

When voltage is applied to the first electrode 108 and the second electrode 150, visible light is emitted from the intermediate layer 140 that are electrically connected to the first electrode 108 and the second electrode 150.

The organic light emitting display apparatus 100 includes the buffer film 102 to prevent impurity elements from penetrating into the TFT, the capacitor 110, and the other elements of the organic light emitting display apparatus 100. Also, the buffer film 102 provides a flat surface on the substrate 101 so that the TFT and the like may be formed to have uniform characteristics.

In this case, the first electrode 108 is formed to correspond to the via hole 102a of the buffer film 102. Thus, the gate insulating film 104 is present between the first electrode 108 and the substrate 101, instead of the buffer film 102.

The active layer 103 is formed on the buffer film 102 by using a crystallization process. During the crystallization process, energy is also supplied to the buffer film 102, thus forming protrusions on an upper surface of the buffer film 102. If the first electrode 108 were formed on the buffer film, the protrusions might lower the surface flatness of the first electrode 108 on the buffer film 102, thereby degrading electrical characteristics of the first electrode 108. In particular, protrusions that are similar to the protrusions on the buffer film 102 might be formed on an upper surface of the first electrode 108 to correspond to the protrusions on the buffer film 102, thereby causing a short circuit to occur between the first electrode 108 and the second electrode 150. The short circuit may cause a failure, e.g., a dim spot, to occur, thereby degrading the image quality characteristics of the organic light emitting display apparatus 100.

However, according to the current embodiment, the first electrode 108 is formed to correspond to the via hole 102a of the buffer film 102. Accordingly, it may be possible to help prevent the surface flatness of the first electrode 108 from being degraded due to the buffer film 102. Thus, the image quality characteristics of the organic light emitting display apparatus 100 may be easily improved.

Visible light emitted from the intermediate layer 140 has a relatively low directionality. Accordingly, the visible light does not travel only toward a user, i.e., a direction parallel to a direction of measuring the thickness of the substrate 101. In this case, the via hole 102a of the buffer film 102 functions as a reflective wall. The visible light is reflected from side surfaces of the via hole 102a of the buffer film 102 and may thus be effectively transmitted in the direction parallel to the direction of the thickness of the substrate 101. That is, the visible light penetrates through the first electrode 108 and is then effectively transmitted toward the via hole 102a.

Thus, the luminous efficiency of the organic light emitting display apparatus 100 may be increased, thereby improving image quality characteristics thereof. In particular, the via hole 102a may be formed to be larger than the first electrode 108 so as to increase the reflectivity of the visible light on the side surfaces of the via hole 102a.

In particular, if the organic light emitting display apparatus 100 according to the current embodiment is a bottom-emission type organic light emitting display apparatus that transmits visible light toward the substrate 101, then the image quality characteristics thereof may be remarkably improved. In the current embodiment, as illustrated in FIG. 1, the intermediate layer 140 is disposed not to overlap with the TFT. Thus, visible light emitted from the intermediate layer 140 may be easily transmitted toward the substrate 101 without being interrupted by the TFT.

FIGS. 2A to 2D are schematic cross-sectional views sequentially illustrating a method of manufacturing an organic light emitting display apparatus, according to an embodiment.

In particular, FIGS. 2A to 2D illustrate a method of manufacturing the organic light emitting display apparatus 100 of FIG. 1, according to an embodiment.

First, referring to FIG. 2A, a substrate 101 is prepared. Then, a buffer film material layer 102' is formed on the substrate 101 to form a buffer film 102. Then, an active layer material layer 103' is formed on the buffer film material layer 102' to form an active layer 103.

The buffer film material layer 102' may contain an inorganic material, e.g., a silicon oxide, a silicon nitride, a silicon oxynitride, an aluminum oxide, an aluminum nitride, a titanium oxide, or a titanium nitride; or an organic material, e.g., polyimide, polyester, or acryl.

The active layer material layer 103' contains silicon. When the active layer material layer 103' is formed of amorphous silicon and the crystallization process is performed on the active layer material layer 103', then the active layer material layer 103' contains polysilicon. During the crystallization process, protrusions (not shown) may be formed on an upper surface of the active layer material layer 103', and protrusions corresponding to the protrusions formed on the upper surface of the active layer material layer 103' may also be formed on an upper surface of the buffer film material layer 102'. In particular, when the active layer material layer 103' is formed according to a laser crystallization process, such protrusions are highly likely to be formed.

Then, referring to FIG. 2B, a patterning process is performed to form the buffer film 102, the active layer 103, and a first capacitor electrode 113. The patterning process may be performed using one mask. For example, the patterning process may be performed using a halftone mask to simultaneously form the buffer film 102, the active layer 103, and the first capacitor electrode 113.

The buffer film **102** includes a via hole **102a**. A region of the substrate **101** is exposed via the via hole **102a**. Each of the active layer **103** and the first capacitor electrode **113** is formed on the buffer film **102** in a predetermined pattern.

Then, referring to FIG. 2C, a gate insulating film **104** is formed on the buffer film **102** to cover the active layer **103** and the first capacitor electrode **113**. In this case, the gate insulating film **104** is disposed to fill the via hole **102a** of the buffer film **102**.

Then, a gate electrode **107**, a first electrode **108**, and a second capacitor electrode **117** are formed on the gate insulating film **104**.

The gate electrode **107** includes a first conductive layer **105** and a second conductive layer **106**. The first electrode **108** may be formed of a material used to form the first conductive layer **105**. A conductive portion **108a** is disposed on an upper region of the first electrode **108**. The conductive portion **108a** may be formed of a material used to form the second conductive layer.

The second capacitor electrode **117** may be formed of a material used to form the first conductive layer **105**.

Then, an interlayer insulating layer **109** is formed on the first electrode **108**, the gate electrode **107**, and the second capacitor electrode **117**. A source electrode **111** and a drain electrode **112** are formed on the interlayer insulating layer **109**. One of the source electrode **111** and the drain electrode **112** is electrically connected to the first electrode **108**.

Then, referring to FIG. 2D, a pixel defining film **130** is formed on the interlayer insulating layer **109** to cover the source electrode **111**, the drain electrode **112**, and the second capacitor electrode **117**. The pixel defining film **130** is formed not to cover at least one upper region of the first electrode **108**.

Then, an intermediate layer **140** is formed on the first electrode **108**. Specifically, the intermediate layer **140** is formed to contact the at least one upper region of the first electrode **108** that is not covered with the pixel defining film **130**. The intermediate layer **140** includes an organic emission layer to emit visible light.

A second electrode **150** is formed on the intermediate layer **140**.

In the current embodiment, a patterning process may be used with one mask to simultaneously form the buffer film **102**, the active layer **103**, and the first capacitor electrode **113**, thereby simplifying the manufacture of the organic light emitting display apparatus **100**.

FIGS. 3A to 3F are schematic cross-sectional views depicting stages of a method of manufacturing the organic light emitting display apparatus **100** of FIG. 1, according to another embodiment.

First, referring to FIG. 3A, a substrate **101** is prepared. Then, a buffer film material layer **102'** is formed on the substrate **101** to form a buffer film **102**. Then, an active layer material layer **103'** is formed on the buffer film material layer **102'** to form an active layer **103**.

The buffer film material layer **102'** may contain an inorganic material, e.g., a silicon oxide, a silicon nitride, a silicon oxynitride, an aluminum oxide, an aluminum nitride, a titanium oxide, or a titanium nitride; or an organic material, e.g., polyimide, polyester, or acryl.

The active layer material layer **103'** contains silicon. When the active layer material layer **103'** is formed of amorphous silicon and the crystallization process is performed on the active layer material layer **103'**, then the active layer material layer **103'** contains polysilicon. During the crystallization process, protrusions (not shown) may be formed on an upper surface of the active layer material layer

103', and protrusions corresponding to the protrusions formed on the upper surface of the active layer material layer **103'** may also be formed on an upper surface of the buffer film material layer **102'**. In particular, when the active layer material layer **103'** is formed according to a laser crystallization process, such protrusions are highly likely to be formed.

Then, referring to FIG. 3B, a patterning process is performed to form the active layer **103** and a first capacitor electrode **113**.

Then, referring to FIGS. 3C and 3D, the buffer film material layer **102'** is patterned to form the buffer film **102**.

Specifically, referring to FIG. 3C, an etch mask **180** is formed on the resultant structure. The etch mask **180** may be formed of any of various materials, e.g., a photoresist. The etch mask **180** is formed to cover the entire resultant structure, except for a portion of the resultant structure which is to be used as a via hole **102a**. In detail, the etch mask **180** is formed to cover the active layer **103** and the first capacitor electrode **113**.

Then, referring to FIG. 3D, a portion of the buffer film material layer **102'** that is not covered with the etch mask **180** is etched to form the buffer film **102**. In detail, the via hole **102a** is formed by etching the portion of the buffer film material layer **102'**. A region of the substrate **101** is exposed via the via hole **102a**. After the etching process is performed, the etch mask **180** is removed according to a strip process.

After the etching process, an ashing process is additionally performed so that the etch mask **180** may be easily completely removed, before the strip process is performed.

Then, referring to FIG. 3E, a gate insulating film **104** is formed on the buffer film **102** to cover the active layer **103** and the first capacitor electrode **113**. The gate insulating film **104** is disposed to fill the via hole **102a** of the buffer film **102**.

A gate electrode **107**, a first electrode **108**, and a second capacitor electrode **117** are formed on the gate insulating film **104**.

The gate electrode **107** includes a first conductive layer **105** and a second conductive layer **106**. The first electrode **108** may be formed of a material used to form the first conductive layer **105**. A conductive portion **108a** is disposed on a region of first electrode **108**. The conductive portion **108a** may be formed of a material used to form the second conductive layer **106**.

The second capacitor electrode **117** may be formed of a material used to form the first conductive layer **105**.

An interlayer insulating layer **109** is formed on the first electrode **108**, the gate electrode **107**, and the second capacitor electrode **117**. Then, a source electrode **111** and a drain electrode **112** are formed on the interlayer insulating layer **109**. One of the source electrode **111** and the drain electrode **112** is electrically connected to the first electrode **108**.

Then, referring to FIG. 3F, a pixel defining film **130** is formed on the interlayer insulating layer **109** to cover the source electrode **111**, the drain electrode **112**, and the second capacitor electrode **117**. The pixel defining film **130** is formed not to cover at least one upper region of the first electrode **108**.

Then, an intermediate layer **140** is formed on the first electrode **108**. In detail, the intermediate layer **140** is formed to contact the at least one upper region of the first electrode **108** that is not covered with the pixel defining film **130**. The intermediate layer **140** includes an organic emission layer to emit visible light.

Then, a second electrode **150** is formed on the intermediate layer **140**.

By way of summation and review, if the surface of a first electrode of an organic light emitting display is rough, the electrical characteristics of the organic light emitting display apparatus may be degraded. In particular, when protrusions are present on a top surface of the first electrode, the protrusions may be connected to the intermediate layer and the second electrode, thereby causing an electrical failure, e.g., a short circuit, to occur. Accordingly, there may be limitations to improving image quality characteristics of the organic light emitting display apparatus.

Embodiments may provide an organic light emitting display apparatus that is capable of easily improving image quality and a method of manufacturing the same. Embodiments may include an organic light emitting display apparatus in which a first electrode corresponds to a via hole of a buffer layer.

Example embodiments have been disclosed herein, and although specific terms are employed, they are used and are to be interpreted in a generic and descriptive sense only and not for purpose of limitation. Accordingly, it will be understood by those of skill in the art that various changes in form and details may be made without departing from the spirit and scope thereof as set forth in the following claims.

What is claimed is:

1. An organic light emitting display apparatus, comprising:

a substrate;

a buffer film directly on the substrate, the buffer film including a via hole;

a thin film transistor (TFT) directly on the buffer film, the TFT including an active layer, a gate electrode, a source electrode, and a drain electrode;

a first electrode on a gate insulating layer on which the gate electrode is disposed and electrically connected to one of the source electrode and the drain electrode and corresponding to the via hole, the via hole in the buffer film directly on the substrate being larger than the first electrode;

an intermediate layer on the first electrode, the intermediate layer including an organic emission layer; and a second electrode on the intermediate layer, wherein the gate insulating layer between the gate electrode and the active layer insulating the gate electrode and the active layer from each other,

a portion of the gate insulating layer disposed between the substrate and the first electrode fills the via hole, and the portion of the gate insulating layer directly contacts the substrate and the first electrode.

2. The organic light emitting display apparatus of claim 1, wherein the first electrode contains indium tin oxide (ITO), indium zinc oxide (IZO), zinc oxide (ZnO), indium oxide (In_2O_3), indium gallium oxide (IGO), or aluminum zinc oxide (AZO).

3. The organic light emitting display apparatus of claim 1, wherein the first electrode contains at least one material selected from among materials forming the gate electrode.

4. The organic light emitting display apparatus of claim 1, wherein:

the gate electrode includes a first conductive layer and a second conductive layer, the second conductive layer being on the first conductive layer, the first conductive layer being on the layer, and the first electrode including a same material as the first conductive layer.

5. The organic light emitting display apparatus of claim 1, wherein the intermediate layer is spaced apart laterally from the TFT to be in a laterally non-overlapping relationship with the TFT.

6. The organic light emitting display apparatus of claim 1, wherein:

the first electrode is directly on and only on the layer on which the gate electrode is disposed; and the intermediate layer is directly on and only on an uppermost surface of the first electrode.

7. A method of manufacturing an organic light emitting display apparatus, the method comprising:

forming a buffer film directly on a substrate to include a via hole;

forming a thin film transistor (TFT) directly on the buffer film, the TFT including an active layer, a gate electrode, a source electrode, and a drain electrode;

forming a first electrode on a gate insulating layer on which the gate electrode is disposed and to be electrically connected to one of the source electrode and the drain electrode and to correspond to the via hole, the via hole in the buffer film directly on the substrate being larger than the first electrode;

forming an intermediate layer on the first electrode, the intermediate layer including an organic emission layer; and

forming a second electrode on the intermediate layer, wherein

the gate insulating layer between the gate electrode and the active layer insulating the gate electrode and the active layer from each other,

a portion of the gate insulating layer disposed between the substrate and the first electrode fills the via hole, and the portion of the gate insulating layer directly contacts the substrate and the first electrode.

8. The method of claim 7, wherein the forming of the buffer film includes:

forming a buffer film material layer on the substrate;

forming the active layer directly on the buffer film material layer;

forming an etch mask to cover the active layer and to not cover a region in which the via hole is to be formed; and forming the via hole by performing an etch process by using the etch mask.

9. The method of claim 7, wherein the forming of the active layer includes at least a crystallization process.

10. The method of claim 7, wherein:

forming the first electrode on the layer on which the gate electrode is disposed includes forming the first electrode directly on and only on the layer on which the gate electrode is disposed; and

forming the intermediate layer on the first electrode includes forming the intermediate layer directly on and only on an uppermost surface of the first electrode.

11. An organic light emitting display apparatus, comprising:

a substrate;

a buffer film directly on the substrate, the buffer film including a via hole;

a thin film transistor (TFT) directly on the buffer film, the TFT including an active layer, a gate electrode, a source electrode, and a drain electrode;

a gate insulating layer, a portion of the gate insulating layer that fills the via hole;

a first electrode on the gate insulating layer that fills the via hole and electrically connected to one of the source electrode and the drain electrode and corresponding to

11

the via hole, the via hole in the buffer film directly on the substrate being larger than the first electrode; an intermediate layer on the first electrode, the intermediate layer including an organic emission layer; and a second electrode on the intermediate layer, wherein 5 the gate insulating layer between the gate electrode and the active layer insulating the gate electrode and the active layer from each other, the portion of the gate insulating layer that fills the via hole being between the substrate and the first electrode, 10 and the portion of the gate insulating layer directly contacts the substrate and the first electrode.

12. The organic light emitting display apparatus of claim 11, wherein the first electrode is directly on the layer that fills 15 the via hole, does not overlap the layer directly contacted by and underlying the active layer, and overlaps the active layer in a direction parallel to a direction of measuring a thickness of the substrate.

13. The organic light emitting display apparatus of claim 20 11, wherein:

the first electrode is directly on and only on the layer on which the gate electrode is disposed; and the intermediate layer is directly on and only on an uppermost surface of the first electrode. 25

* * * * *

12

专利名称(译)	有机发光显示装置及其制造方法		
公开(公告)号	US9461263	公开(公告)日	2016-10-04
申请号	US13/676707	申请日	2012-11-14
[标]申请(专利权)人(译)	游春GI CHOI JOON HOO 朴钟HYUN 朴敬勋 金桢HWAN HEO SEONG KWEON		
申请(专利权)人(译)	YOU , CHUN-GI 崔俊HOO PARK , JONG-HYUN PARK , 京勋 KIM , 郑某焕 HEO , 晟KWEON		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	YOU CHUN GI CHOI JOON HOO PARK JONG HYUN PARK KYUNG HOON KIM JEONG HWAN HEO SEONG KWEON		
发明人	YOU, CHUN-GI CHOI, JOON-HOO PARK, JONG-HYUN PARK, KYUNG-HOON KIM, JEONG-HWAN HEO, SEONG-KWEON		
IPC分类号	H01L27/32 H01L51/50 H01L51/52		
CPC分类号	H01L51/5092 H01L27/326 H01L27/3248 H01L51/5206 H01L51/5212 H01L27/3265 H01L2251/5392		
优先权	1020120047121 2012-05-03 KR		
其他公开文献	US20130292651A1		
外部链接	Espacenet USPTO		

摘要(译)

有机发光显示装置包括基板;基板上的缓冲膜,包括通孔的缓冲膜,缓冲膜上的薄膜晶体管(TFT),包括有源层的TFT,栅电极,源电极和漏电极,第一电极电连接到源电极和漏电极中的一个并对应于通孔;第一电极上的中间层,中间层包括有机发光层,中间层上的第二电极。

