

(10) **Patent No.:** US 9,543,544 B2
(45) **Date of Patent:** Jan. 10, 2017

(56)

References Cited

U.S. PATENT DOCUMENTS


2003/0137325	A1 *	7/2003	Yamazaki	H01L 27/322 327/80
2004/0217704	A1 *	11/2004	Iwase	H01L 51/5237 313/518
2006/0091396	A1	5/2006	Lee et al.	
2006/0267885	A1	11/2006	Kwak et al.	
2007/0194313	A1 *	8/2007	Jung	G02F 1/13454 257/59
2008/0309233	A1	12/2008	Hasegawa et al.	
2009/0058290	A1	3/2009	Matsuura et al.	
2013/0056784	A1	3/2013	Lee et al.	
2013/0082249	A1 *	4/2013	Kawanami	H01L 51/50 257/40
2013/0082270	A1	4/2013	Ono et al.	
2013/0119392	A1 *	5/2013	Park	H01L 27/326 257/72
2013/0141317	A1 *	6/2013	Choi	G09G 3/20 345/84

JP 2008135325 A1 6/2008
Primary Examiner — Phuc Dang
 (74) *Attorney, Agent, or Firm* — Dentons US LLP

(57) **ABSTRACT**

Disclosed is an organic light emitting display apparatus in which an anode electrode, an organic emission layer, a cathode electrode, and an auxiliary electrode connected to the cathode electrode and disposed on the same layer as that of the anode electrode are disposed in an active area of the substrate, a signal pad and a pad electrode connected to the signal pad and covering a top of the signal pad are disposed in a pad area of the substrate, and a top of the pad electrode has lower oxidation rate than the top of the signal pad.

11 Claims, 11 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2014/0159002	A1 *	6/2014	Lee		H01L 27/3246	257/40
2014/0225071	A1 *	8/2014	Park		H01L 51/5203	257/40
2014/0346448	A1	11/2014	You et al.			
2015/0008398	A1 *	1/2015	Lee		H01L 51/5212	257/40

* cited by examiner

FIG. 4D




FIG. 4E




FIG. 4F




FIG. 4G




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 5D




FIG. 5E




FIG. 5F




FIG. 5G




FIG. 5H





FIG. 5I



ORGANIC LIGHT EMITTING DISPLAY

CROSS-REFERENCE TO RELATED
APPLICATIONS

This application claims the benefit of the Korean Patent Application No. 10-2015-0075393 filed on May 28, 2015, which is hereby incorporated by reference for all purposes as if fully set forth herein.

BACKGROUND

Field of the Invention

The present invention relates to an organic light emitting display apparatus. More particularly, the present invention relates to a top emission type organic light emitting display apparatus and a method of manufacturing the same.

Discussion of the Related Art

Organic light emitting display apparatuses are self-emitting apparatuses, have low power consumption, a fast response time, high emission efficiency, high luminance, and a wide viewing angle.

The organic light emitting display apparatuses are classified into a top emission type and a bottom emission type, based on a transmission direction of light emitted from an organic light emitting device. In the bottom emission type, a circuit element is disposed between an emission layer and an image displaying surface, and for this reason, an aperture ratio is lowered. On the other hand, in the top emission type, the circuit element is not disposed between the emission layer and the image displaying surface, and thus, an aperture ratio is enhanced.

FIG. 1 is a schematic cross-sectional view of a related art top emission type organic light emitting display apparatus.

As illustrated in FIG. 1, a thin film transistor (TFT) layer T which includes an active layer 11, a gate insulation layer 12, a gate electrode 13, an interlayer dielectric 14, a source electrode 15, and a drain electrode 16 formed in an active area AA on a substrate 10, and a passivation layer 20 and a planarization layer 30 are sequentially formed on the TFT layer T.

An anode electrode 40 and an auxiliary electrode 50 are formed on the planarization layer 30. The auxiliary electrode 50 decreases a resistance of a cathode electrode 80 to be described below.

A bank 60 is formed on the anode electrode 40 and the auxiliary electrode 50 and defines a pixel area. An organic emission layer 70 is formed in the pixel area defined by the bank 60, and the cathode electrode 80 is formed on the organic emission layer 70.

In the top emission type, light emitted from the organic emission layer 70 passes through the cathode electrode 80. Therefore, the cathode electrode 80 is formed of a transparent conductive material, and a resistance of the cathode electrode 80 increases. In order to decrease the resistance of the cathode electrode 80, the cathode electrode 80 is connected to the auxiliary electrode 50.

The gate insulation layer 12 and the interlayer dielectric 14 are formed in a pad area PA on the substrate 10, a signal pad 90 is formed on the interlayer dielectric 14, and the passivation layer 20 is formed on the signal pad 90. A hole is provided in the passivation layer 20, and the signal pad 90 is exposed to the outside through the hole. Since the signal pad 90 should be connected to an external driving circuit, the signal pad 90 is exposed to the outside by forming the hole in the passivation layer 20.

The related art top emission type organic light emitting display apparatus has the following problems.

Since the signal pad 90 should be connected to the external driving circuit, a top of the signal pad 90 is exposed to the outside. For this reason, the top of the signal pad 90 is corroded, and the corrosion is spread to another area. A metal layer which is excellent in corrosion resistance may be further formed on the top of the signal pad 90 so as to prevent the top of the signal pad 90 from being corroded, but in this case, the number of processes increases. Also, an electrode layer which is the same as the anode electrode 40 may be formed on the signal pad 90 through the same process so as to prevent the top of the signal pad 90 from being corroded without an increase in number of processes, but even in this case, it is unable to prevent corrosion from being spread through a side surface of the electrode layer.

Moreover, in order to connect the signal pad 90 to the external driving circuit, the top of the signal pad 90 is exposed by forming the hole in the passivation layer 20. But when the hole of the passivation layer 20 is previously formed, an etchant for pattern-forming the anode electrode 40 flows through the hole and damages the signal pad 90. In order to prevent the damage, a process of forming the hole of the passivation layer 20 for exposing the top of the signal pad 90 may be separately performed after a process of pattern-forming the anode electrode 40 is completed, but in this case, a separate mask process is added.

SUMMARY OF THE INVENTION

Accordingly, the present invention is directed to provide a top emission type organic light emitting display apparatus and a method of manufacturing the same that substantially obviate one or more problems due to limitations and disadvantages of the related art.

An advantage of the present invention is directed to a top emission type organic light emitting display apparatus and a method of manufacturing the same, in which the number of additional processes is minimized, and a signal pad is prevented from being corroded.

Additional advantages and features of the invention will be set forth in part in the description which follows and in part will become apparent to those having ordinary skill in the art upon examination of the following or may be learned from practice of the invention. The objectives and other advantages of the invention may be realized and attained by the structure particularly pointed out in the written description and claims hereof as well as the appended drawings.

To achieve these and other advantages and in accordance with the purpose of the invention, as embodied and broadly described herein, there is provided an organic light emitting display apparatus in which an anode electrode, an organic emission layer, a cathode electrode, and an auxiliary electrode connected to the cathode electrode and disposed on the same layer as that of the anode electrode are disposed in an active area of the substrate, a signal pad and a pad electrode connected to the signal pad and covering a top of the signal pad are disposed in a pad area of the substrate, and a top of the pad electrode is lower in oxidation rate than the top of the signal pad.

In another aspect of the present invention, there is provided a method of manufacturing an organic light emitting display apparatus including: forming a source electrode, a drain electrode and a signal pad on a substrate; forming a passivation layer on the source electrode, the drain electrode and the signal pad; simultaneously forming a contact hole externally exposing the source electrode or the drain elec-

trode, and a contact hole externally exposing the signal pad, by removing predetermined regions of the passivation layer; and forming an anode electrode connected to the source electrode or the drain electrode, an auxiliary electrode separated from the anode electrode, and a pad electrode connected to the signal pad to cover the exposed signal pad.

It is to be understood that both the foregoing general description and the following detailed description of the present invention are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this application, illustrate embodiments of the invention and together with the description serve to explain the principle of the invention. In the drawings:

FIG. 1 is a schematic cross-sectional view of a related art top emission type organic light emitting display apparatus;

FIG. 2 is a cross-sectional view of an organic light emitting display apparatus according to an embodiment of the present invention;

FIG. 3 is a cross-sectional view of an organic light emitting display apparatus according to another embodiment of the present invention;

FIGS. 4A to 4H are cross-sectional views illustrating a method of manufacturing an organic light emitting display apparatus according to an embodiment of the present invention; and

FIGS. 5A to 5I are cross-sectional views illustrating a method of manufacturing an organic light emitting display apparatus according to another embodiment of the present invention.

DETAILED DESCRIPTION OF THE ILLUSTRATED EMBODIMENTS

Reference will now be made in detail to the exemplary embodiments of the present invention, examples of which are illustrated in the accompanying drawings. Wherever possible, the same reference numbers will be used throughout the drawings to refer to the same or like parts.

Advantages and features of the present invention, and implementation methods thereof will be clarified through following embodiments described with reference to the accompanying drawings. The present invention may, however, be embodied in different forms and should not be construed as limited to the embodiments set forth herein. Rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the present invention to those skilled in the art. Further, the present invention is only defined by scopes of claims.

A shape, a size, a ratio, an angle, and a number disclosed in the drawings for describing embodiments of the present invention are merely an example, and thus, the present invention is not limited to the illustrated details. Like reference numerals refer to like elements throughout. In the following description, when the detailed description of the relevant known function or configuration is determined to unnecessarily obscure the important point of the present invention, the detailed description will be omitted. In a case where 'comprise', 'have', and 'include' described in the present specification are used, another part may be added

unless 'only~' is used. The terms of a singular form may include plural forms unless referred to the contrary.

In construing an element, the element is construed as including an error range although there is no explicit description.

In describing a position relationship, for example, when a position relation between two parts is described as 'on~', 'over~', 'under~', and 'next~', one or more other parts may be disposed between the two parts unless 'just' or 'direct' is used.

In describing a time relationship, for example, when the temporal order is described as 'after~', 'subsequent', 'next~', and 'before~', a case which is not continuous may be included unless 'just' or 'direct' is used.

It will be understood that, although the terms "first", "second", etc. may be used herein to describe various elements, these elements should not be limited by these terms. These terms are only used to distinguish one element from another. For example, a first element could be termed a second element, and, similarly, a second element could be termed a first element, without departing from the scope of the present invention.

Features of various embodiments of the present invention may be partially or overall coupled to or combined with each other, and may be variously inter-operated with each other and driven technically as those skilled in the art can sufficiently understand. The embodiments of the present invention may be carried out independently from each other, or may be carried out together in co-dependent relationship.

Hereinafter, exemplary embodiments of the present invention will be described in detail with reference to the accompanying drawings.

FIG. 2 is a cross-sectional view of an organic light emitting display apparatus according to an embodiment of the present invention.

As illustrated in FIG. 2, the organic light emitting display apparatus according to an embodiment of the present invention may include an active area AA and a pad area PA provided on a substrate 100.

A thin film transistor (TFT) T, a passivation layer 165, a planarization layer 170, a first anode electrode 180, a second anode electrode 200, a first auxiliary electrode 190, a second auxiliary electrode 210, a bank 220, a partition wall 230, an organic emission layer 240, and a cathode electrode 250 formed in the active area AA on the substrate 100.

The TFT T may include an active layer 110, a gate insulation layer 120, a gate electrode 130, an interlayer dielectric 140, a source electrode 150, and a drain electrode 160.

The active layer 110 may be formed on the substrate 100 to overlap the gate electrode 130. The active layer 110 may be formed of a silicon-based semiconductor material, or may be formed of an oxide-based semiconductor material. Although not shown, a light shielding layer may be further formed between the substrate 100 and the active layer 110, and in this case, external light incident through a bottom of the substrate 100 is blocked by the light shielding layer, thereby preventing the active layer 110 from being damaged by the external light.

The gate insulation layer 120 may be formed on the active layer 110. The gate insulation layer 120 may insulate the active layer 110 from the gate electrode 130. The gate insulation layer 120 may be formed of an inorganic insulating material, for example, silicon oxide (SiOx), silicon nitride (SiNx), or a multilayer thereof, but is not limited thereto. The gate insulation layer 120 may extend to the pad area PA.

The gate electrode **130** may be formed on the gate insulation layer **120**. The gate electrode **130** may be formed to overlap the active layer **110** with the gate insulation layer **120** therebetween. The gate electrode **130** may be formed of a single layer or a multilayer formed of one of molybdenum (Mo), aluminum (Al), chromium (Cr), gold (Au), titanium (Ti), nickel (Ni), neodymium (Nd), and copper (Cu) or an alloy thereof, but is not limited thereto.

The interlayer dielectric **140** may be formed on the gate electrode **130**. The interlayer dielectric **140** may be formed of the same inorganic insulating material as that of the gate insulation layer **120**, for example, silicon oxide (SiOx), silicon nitride (SiNx), or a multilayer thereof, but is not limited thereto. The interlayer dielectric **140** may extend to the pad area PA.

The source electrode **150** and the drain electrode **160** may be formed to face each other on the interlayer dielectric **140**. A first contact hole CH1 exposing one end region of the active layer **110** and a second contact hole CH2 exposing the other end region of the active layer **110** may be provided in the gate insulation layer **120** and the interlayer dielectric **140**. The source electrode **150** may be connected to the other end region of the active layer **110** through the second contact hole CH2, and the drain electrode **160** may be connected to the one end region of the active layer **110** through the first contact hole CH1.

The source electrode **150** may include a lower source electrode **151** and an upper source electrode **152**.

The lower source electrode **151** may be formed between the interlayer dielectric **140** and the upper source electrode **152** and may enhance an adhesive force between the interlayer dielectric **140** and the upper source electrode **152**. Also, the lower source electrode **151** protects a bottom of the upper source electrode **152**, thereby preventing the bottom of the upper source electrode **152** from being corroded. Therefore, an oxidation rate of the lower source electrode **151** may be lower than that of the upper source electrode **152**. That is, the lower source electrode **151** may be formed of a material which is stronger in corrosion resistance than a material forming the upper source electrode **152**. As described above, the lower source electrode **151** may act as an adhesion enhancement layer or an anti-corrosion layer and may be formed of an alloy (MoTi) of Mo and Ti, but is not limited thereto.

The upper source electrode **152** may be formed on a top of the lower source electrode **151**. The upper source electrode **152** may be formed of Cu which is metal having a low resistance, but is not limited thereto. The upper source electrode **152** may be formed of metal which is relatively lower in resistance than the lower source electrode **151**. In order to lower a total resistance of the source electrode **150**, a thickness of the upper source electrode **152** may be formed thicker than that of the lower source electrode **151**.

Similar to the above-described source electrode **150**, the drain electrode **160** may include a lower drain electrode **161** and an upper drain electrode **162**.

The lower drain electrode **161** may be formed between the interlayer dielectric **140** and the upper drain electrode **162**. The lower drain electrode **161** enhances an adhesive force between the interlayer dielectric **140** and the upper drain electrode **162** and moreover prevents a bottom of the upper drain electrode **162** from being corroded. Therefore, an oxidation rate of the lower drain electrode **161** may be lower than that of the upper drain electrode **162**. That is, the lower drain electrode **161** may be formed of a material which is stronger in corrosion resistance than a material forming the upper drain electrode **162**. As described above, the lower

drain electrode **161** may be formed of an alloy (MoTi) of Mo and Ti which is the same as the above-described material of the lower source electrode **151**, but is not limited thereto.

The upper drain electrode **162** may be formed on a top of the lower drain electrode **161** and may be formed of Cu which is the same as the above-described material of the upper source electrode **152**, but is not limited thereto. A thickness of the upper drain electrode **162** may be formed thicker than that of the lower drain electrode **161**, thereby lowering a total resistance of the drain electrode **160**.

The upper drain electrode **162** may be formed of the same material as that of the upper source electrode **152** to have the same thickness as that of the upper source electrode **152**, and the lower drain electrode **161** may be formed of the same material as that of the lower source electrode **151** to have the same thickness as that of the lower source electrode **151**. In this case, the drain electrode **160** and the source electrode **150** may be simultaneously formed through the same process.

A structure of the TFT T is not limited to the illustrated structure, and may be variously modified to structures known to those skilled in the art. For example, a top gate structure where the gate electrode **130** is formed on the active layer **110** is illustrated in the drawing, but the TFT T may be formed in a bottom gate structure where the gate electrode **130** is formed under the active layer **110**.

The passivation layer **165** may be formed on the TFT T, and in more detail, may be formed on tops of the source electrode **150** and the drain electrode **160**. The passivation layer **165** protects the TFT T. The passivation layer **165** may be formed of an inorganic insulating material (for example, SiOx and SiNx), but is not limited thereto. The passivation layer **165** may extend to the pad area PA.

The planarization layer **170** may be formed on the passivation layer **165**. The planarization layer **170** may planarize an upper surface of the substrate **100** including the TFT T. The planarization layer **170** may be formed of an organic insulating material such as acryl resin, epoxy resin, phenolic resin, polyamide resin, polyimide resin, or the like, but is not limited thereto. The planarization layer **170** may not extend to the pad area PA.

The first anode electrode **180** and the first auxiliary electrode **190** may be formed on the planarization layer **170**. That is, the first anode electrode **180** and the first auxiliary electrode **190** may be formed on the same layer. A third contact hole CH3 exposing the source electrode **150** may be provided in the passivation layer **165** and the planarization layer **170**, and the source electrode **150** may be connected to the first anode electrode **180** through the third contact hole CH3. In one or more embodiments, the first anode electrode **180** is connected with the source electrode **150**. However, the source electrode **150** and the drain electrode **160** can be switched based on the mode of the transistor. Accordingly, in one or more embodiments, the first anode electrode **180** may be connected with the drain electrode **160** instead of the source electrode **150**. As a result, the first anode electrode **180** may be connected with the source electrode **150** or the drain electrode **160**.

The first anode electrode **180** may include a first lower anode electrode **181** and a first upper anode electrode **182**.

The first lower anode electrode **181** may be formed between the planarization layer **170** and the first upper anode electrode **182** and may enhance an adhesive force between the planarization layer **170** and the first upper anode electrode **182**. Also, the first lower anode electrode **181** protects a bottom of the first upper anode electrode **182**, thereby preventing the bottom of the first upper anode electrode **182**

from being corroded. Therefore, an oxidation rate of the first lower anode electrode **181** may be lower than that of the first upper anode electrode **182**. That is, the first lower anode electrode **181** may be formed of a material which is stronger in corrosion resistance than a material forming the first upper anode electrode **182**. Also, the first upper anode electrode **181** protects a top of the upper source electrode **152**, thereby preventing the top of the upper source electrode **152** from being corroded. Therefore, an oxidation rate of the first lower anode electrode **181** may be lower than that of the upper source electrode **152**. That is, the first lower anode electrode **181** may be formed of a material which is stronger in corrosion resistance than a material forming the upper source electrode **152**. As described above, the first lower anode electrode **181** prevents the top of the upper source electrode **152** from being corroded, and thus, the source electrode **150** may be formed in the above-described two-layer structure. The first lower anode electrode **181** may act as an adhesion enhancement layer or an anti-corrosion layer and may be formed of an alloy (MoTi) of Mo and Ti, but is not limited thereto.

The first upper anode electrode **182** may be formed on a top of the first lower anode electrode **181**. The first upper anode electrode **182** may be formed of Cu which is metal having a low resistance, but is not limited thereto. The first upper anode electrode **182** may be formed of metal which is relatively lower in resistance than the first lower anode electrode **181**. In order to lower a total resistance of the first anode electrode **180**, a thickness of the first upper anode electrode **182** may be formed thicker than that of the first lower anode electrode **181**.

Similar to the above-described first anode electrode **180**, the first auxiliary electrode **190** may include a first lower auxiliary electrode **191** and a first upper auxiliary electrode **192**.

The first lower auxiliary electrode **191** may be formed between the planarization layer **170** and the first upper auxiliary electrode **192**. The first lower auxiliary electrode **191** enhances an adhesive force between the planarization layer **170** and the first upper auxiliary electrode **192** and moreover prevents a bottom of the first upper auxiliary electrode **192** from being corroded. Therefore, an oxidation rate of the first lower auxiliary electrode **191** may be lower than that of the first upper auxiliary electrode **192**. That is, the first lower auxiliary electrode **191** may be formed of a material which is stronger in corrosion resistance than a material forming the first upper auxiliary electrode **192**. As described above, the first lower auxiliary electrode **191** may be formed of an alloy (MoTi) of Mo and Ti which is the same as the above-described material of the first lower anode electrode **181**, but is not limited thereto.

The first upper auxiliary electrode **192** may be formed on a top of the first lower auxiliary electrode **191** and may be formed of Cu which is the same as the above-described material of the first upper anode electrode **182**, but is not limited thereto. A thickness of the first upper auxiliary electrode **192** which is relatively low in resistance may be formed thicker than that of the first lower auxiliary electrode **191** which is relatively high in resistance, thereby lowering a total resistance of the first auxiliary electrode **190**.

The first upper auxiliary electrode **192** may be formed of the same material as that of the first upper anode electrode **182** to have the same thickness as that of the first upper anode electrode **182**, and the first lower auxiliary electrode **191** may be formed of the same material as that of the first lower anode electrode **181** to have the same thickness as that of the first lower anode electrode **181**. In this case, the first

auxiliary electrode **190** and the first anode electrode **180** may be simultaneously formed through the same process.

The second anode electrode **200** may be formed on a top of the first anode electrode **180**. The second anode electrode **200** may be formed to contact a whole top and side surface of the first anode electrode **180**. That is, a separate insulation layer may not be formed between the second anode electrode **200** and the first anode electrode **180**. Thus, a process of forming an insulation layer and a contact hole is not needed. The second anode electrode **200** may reflect light, emitted from the organic emission layer **240**, in an upward direction, and to this end, the second anode electrode **200** may be formed of a material having good reflectivity. Also, the second anode electrode **200** may be formed to cover the top and side surface of the first anode electrode **180** and prevents the top and side surface of the first anode electrode **180** from being corroded.

The second anode electrode **200** may include a second lower anode electrode **201**, a second center anode electrode **202**, and a second upper anode electrode **203**.

The second lower anode electrode **201** may be formed between the first anode electrode **180** and the second center anode electrode **202**. The second lower anode electrode **201** may be formed to cover a top and a side surface of the first anode electrode **180**, thereby preventing the first anode electrode **180** from being corroded. To this end, an oxidation rate of the second lower anode electrode **201** may be lower than that of each of the first lower anode electrode **181** and the first upper anode electrode **182** which configure the first anode electrode **180**. That is, the second lower anode electrode **201** may be formed of a material which is stronger in corrosion resistance than a material forming the first lower anode electrode **181** and the first upper anode electrode **182**. Also, the second lower anode electrode **201** protects a bottom of the second center anode electrode **202**, thereby preventing the bottom of the second center anode electrode **202** from being corroded. To this end, an oxidation rate of the second lower anode electrode **201** may be lower than that of the second center anode electrode **202**. That is, the second lower anode electrode **201** may be formed of a material which is stronger in corrosion resistance than a material forming the second center anode electrode **202**. The second lower anode electrode **201** may be formed of a transparent conductive material such as indium tin oxide (ITO) or the like, but is not limited thereto.

The second center anode electrode **202** may be formed between the second lower anode electrode **201** and the second upper anode electrode **203**. The second center anode electrode **202** may be formed of a material which is lower in resistance than and better in reflectivity than the second lower anode electrode **201** and the second upper anode electrode **203**, and for example, may be formed of silver (Ag). However, the present embodiment is not limited thereto. A thickness of the second center anode electrode **202** which is relatively low in resistance may be formed thicker than that of each of the second lower anode electrode **201** and the second upper anode electrode **203** which are relatively high in resistance, thereby lowering a total resistance of the second anode electrode **200**.

The second upper anode electrode **203** may be formed on a top of the second center anode electrode **202**, thereby preventing the top of the second center anode electrode **202** from being corroded. To this end, an oxidation rate of the second upper anode electrode **203** may be lower than that of the second center anode electrode **202**. That is, the second upper anode electrode **203** may be formed of a material which is stronger in corrosion resistance than a material

forming the second center anode electrode **202**. The second upper anode electrode **203** may be formed of a transparent conductive material such as ITO or the like, but is not limited thereto.

The second auxiliary electrode **210** may be formed on a top of the first auxiliary electrode **190**. The second auxiliary electrode **210** may be formed on the same layer as a layer on which the second anode electrode **200** is disposed. The second auxiliary electrode **210** may be formed to contact a whole top and side surface of the first auxiliary electrode **190**. That is, a separate insulation layer may not be formed between the second auxiliary electrode **210** and the first auxiliary electrode **190**, and thus, a process of forming an insulation layer and a contact hole is not needed. The second auxiliary electrode **210** lowers a resistance of the cathode electrode **250** along with the first auxiliary electrode **190**. According to an embodiment of the present invention, two auxiliary electrodes (for example, the first and second auxiliary electrodes **190** and **210**) may be stack-formed for lowering the resistance of the cathode electrode **250**, and thus, the desired resistance characteristic of the auxiliary electrodes is more easily adjusted. To provide a more detailed description, since the first auxiliary electrode **190** is formed on the same layer as a layer on which the first anode electrode **180** is formed, there is a limitation in increasing a size of the first auxiliary electrode **190**. Therefore, according to an embodiment of the present invention, the second auxiliary electrode **210** may be stacked on the first auxiliary electrode **190**, and thus, the resistance of the cathode electrode **250** is effectively lowered. Also, the second auxiliary electrode **210** may be formed to cover the top and side surface of the first auxiliary electrode **190**, thereby preventing the top and side surface of the first auxiliary electrode **190** from being corroded.

The second auxiliary electrode **210** may include a second lower auxiliary electrode **211**, a second center auxiliary electrode **212**, and a second upper auxiliary electrode **213**.

The second lower auxiliary electrode **211** may be formed between the first auxiliary electrode **190** and the second center auxiliary electrode **212**. The second lower auxiliary electrode **211** may be formed to cover a top and a side surface of the first auxiliary electrode **190**, thereby preventing the first auxiliary electrode **190** from being corroded. To this end, an oxidation rate of the second lower auxiliary electrode **211** may be lower than that of each of the first lower auxiliary electrode **191** and the first upper auxiliary electrode **192** which configure the first auxiliary electrode **190**. That is, the second lower auxiliary electrode **211** may be formed of a material which is stronger in corrosion resistance than a material forming the first lower auxiliary electrode **191** and the first upper auxiliary electrode **192**. Also, the second lower auxiliary electrode **211** protects a bottom of the second center auxiliary electrode **212**, thereby preventing the bottom of the second center auxiliary electrode **212** from being corroded. To this end, an oxidation rate of the second lower auxiliary electrode **211** may be lower than that of the second center auxiliary electrode **212**. That is, the second lower auxiliary electrode **211** may be formed of a material which is stronger in corrosion resistance than a material forming the second center auxiliary electrode **212**. The second lower auxiliary electrode **211** may be formed of a transparent conductive material such as ITO or the like, but is not limited thereto.

The second center auxiliary electrode **212** may be formed between the second lower auxiliary electrode **211** and the second upper auxiliary electrode **213**. The second center auxiliary electrode **212** may be formed of a material which

is lower in resistance than and better in reflectivity than the second lower auxiliary electrode **211** and the second upper auxiliary electrode **213**, and for example, may be formed of silver (Ag). However, the present embodiment is not limited thereto. A thickness of the second center auxiliary electrode **212** which is relatively low in resistance may be formed thicker than that of each of the second lower auxiliary electrode **211** and the second upper auxiliary electrode **213** which are relatively high in resistance, thereby lowering a total resistance of the second auxiliary electrode **210**.

The second upper auxiliary electrode **213** may be formed on a top of the second center auxiliary electrode **212**, thereby preventing the top of the second center auxiliary electrode **212** from being corroded. To this end, an oxidation rate of the second upper auxiliary electrode **213** may be lower than that of the second center auxiliary electrode **212**. That is, the second upper auxiliary electrode **213** may be formed of a material which is stronger in corrosion resistance than a material forming the second center auxiliary electrode **212**. The second upper auxiliary electrode **213** may be formed of a transparent conductive material such as ITO or the like, but is not limited thereto.

The second upper auxiliary electrode **213** may be formed of the same material as that of the second upper anode electrode **203** to have the same thickness as that of the second upper anode electrode **203**, the second center auxiliary electrode **212** may be formed of the same material as that of the second center anode electrode **202** to have the same thickness as that of the second center anode electrode **202**, and the second lower auxiliary electrode **211** may be formed of the same material as that of the second lower anode electrode **201** to have the same thickness as that of the second lower anode electrode **201**. In this case, the second auxiliary electrode **210** and the second anode electrode **200** may be simultaneously formed through the same process.

The bank **220** may be formed on the second anode electrode **200** and the second auxiliary electrode **210**.

The bank **220** may be formed on one side and the other side of the second anode electrode **200** to expose a top of the second anode electrode **200**. Since the bank **220** is formed to expose the top of the second anode electrode **200**, an area where an image is displayed is secured. Also, since the bank **220** is formed on the one side and the other side of the second anode electrode **200**, a side of the second center anode electrode **202** vulnerable to corrosion is prevented from being exposed to the outside, thereby preventing the side of the second center anode electrode **202** from being corroded.

The bank **220** may be formed on one side and the other side of the second auxiliary electrode **210** to expose a top of the second auxiliary electrode **210**. Since the bank **220** is formed to expose the top of the second auxiliary electrode **210**, an electrical connection space between the second auxiliary electrode **210** and the cathode electrode **250** is secured. Also, since the bank **220** is formed on the one side and the other side of the second auxiliary electrode **210**, a side of the second center auxiliary electrode **212** vulnerable to corrosion is prevented from being exposed to the outside, thereby preventing the side of the second center auxiliary electrode **212** from being corroded.

Moreover, the bank **220** may be formed between the second anode electrode **200** and the second auxiliary electrode **210** and may insulate the second anode electrode **200** from the second auxiliary electrode **210**. The bank **220** may be formed of an organic insulating material such as polyimide resin, acryl resin, benzocyclobutene (BCB), or the like, but is not limited thereto.

The partition wall **230** may be formed on the second auxiliary electrode **210**. The partition wall **230** may be separated from the bank **220** by a certain distance, and the second auxiliary electrode **210** may be electrically connected to the cathode electrode **250** through a separation space between the partition wall **230** and the bank **220**. The second auxiliary electrode **210** may be electrically connected to the cathode electrode **250** without forming the partition wall **230**. However, if the partition wall **230** is formed, the organic emission layer **240** is more easily deposition-formed. This will be described below in more detail.

If the partition wall **230** is not formed, a mask pattern which covers a top of the second auxiliary electrode **210** is needed to deposit the organic emission layer **240** so that the top of the second auxiliary electrode **210** is not covered by the organic emission layer **240**. However, if the partition wall **230** is formed, a top of the partition wall **230** may act as eaves in depositing the organic emission layer **240**. Thus, since the organic emission layer **240** is not deposited under the eaves, a mask pattern to cover the top of the second auxiliary electrode **210** is not needed. That is, with respect to a case where the organic light emitting display apparatus is seen from the front thereof, when the top of the partition wall **230** that acts as eaves is formed to cover a separation space between the partition wall **230** and the bank **220**, the organic emission layer **240** cannot penetrate into the separation space between the partition wall **230** and the bank **220**. Thus, the second auxiliary electrode **210** may be exposed in the separation space between the partition wall **230** and the bank **220**. Particularly, the organic emission layer **240** may be formed by a deposition process such as an evaporation process which is excellent in straightness of a deposited material. Thus, the organic emission layer **240** is not deposited in the separation space between the partition wall **230** and the bank **220**.

As described above, a width of the top of the partition wall **230** may be formed greater than that of a bottom of the partition wall **230**, in order for the top of the partition wall **230** to act as eaves. The partition wall **230** may include a lower first partition wall **231** and an upper second partition wall **232**. The lower first partition wall **231** may be formed on a top of the second auxiliary electrode **210** and may be formed of the same material as that of the bank **220** through the same process as that of the bank **220**. The upper second partition wall **232** may be formed on a top of the lower first partition wall **231**. A width of a top of the upper second partition wall **232** may be formed greater than that of a bottom of the upper second partition wall **232**. More specifically, the top of the upper second partition wall **232** may be formed to cover the separation space between the partition wall **230** and the bank **220** and may act as eaves.

The organic emission layer **240** may be formed on the second anode electrode **200**. The organic emission layer **240** may include a hole injection layer, a hole transport layer, an emission layer, an electron transport layer, and an electron injection layer. The organic emission layer **240** may be modified to have various structures known to those skilled in the art.

The organic emission layer **240** may extend to the top of the bank **220**. However, the organic emission layer **240** may not extend to the top of the second auxiliary electrode **210** in a state of covering the top of the second auxiliary electrode **210**. This is because when the organic emission layer **240** covers the top of the second auxiliary electrode **210**, it is difficult to electrically connect the second auxiliary electrode **210** to the cathode electrode **250**. As described

above, the organic emission layer **240** may be formed by a deposition process without a mask that covers the top of the second auxiliary electrode **210**, and in this case, the organic emission layer **240** may be formed on the top of the partition wall **230**.

The cathode electrode **250** may be formed on the organic emission layer **240**. The cathode electrode **250** may be formed on a surface from which light is emitted, and thus may be formed of a transparent conductive material. Since the cathode electrode **250** is formed of a transparent conductive material, a resistance of the cathode electrode **250** is high, and for this reason, in order to lower the resistance of the cathode electrode **250**, the cathode electrode **250** may be connected to the second auxiliary electrode **210**. That is, the cathode electrode **250** may be connected to the second auxiliary electrode **210** via the separation space between the partition wall **230** and the bank **220**. The cathode electrode **250** may be formed by a deposition process such as a sputtering process which is not good in straightness of a deposited material. Thus, the cathode electrode **250** may be deposited in the separation space between the partition wall **230** and the bank **220** in a process of depositing the cathode electrode **250**.

Although not shown, an encapsulation layer may be further formed on the cathode electrode **250** and prevents penetration of water. The encapsulation layer may use various materials known to those skilled in the art. Also, although not shown, a color filter may be further formed for each pixel and on the cathode electrode **250**, and in this case, white light may be emitted from the organic emission layer **240**.

The gate insulation layer **120**, the interlayer dielectric **140**, the signal pad **300**, the passivation layer **165**, and the pad electrode **400** may be formed in the pad area PA on the substrate **100**.

The gate insulation layer **120** may be formed on the substrate **100**, and the interlayer dielectric **140** may be formed on the gate insulation layer **120**. The gate insulation layer **120** and the interlayer dielectric **140** may be formed all over the pad area PA by extending from the active area AA.

The signal pad **300** may be formed on the interlayer dielectric **140**. The signal pad **300** may be formed on the same layer as a layer where the source electrode **150** and the drain electrode **160** in the active area AA are disposed.

The signal pad **300** may include a lower signal pad **301** and an upper signal pad **302**.

The lower signal pad **301** may be formed between the interlayer dielectric **140** and the upper signal pad **302** and may enhance an adhesive force between the interlayer dielectric **140** and the upper signal pad **302**. Also, the lower signal pad **301** prevents a bottom of the upper signal pad **302** from being corroded. Therefore, an oxidation rate of the lower signal pad **301** may be lower than that of the upper signal pad **302**. That is, the lower signal pad **301** may be formed of a material which is stronger in corrosion resistance than a material forming the upper signal pad **302**. As described above, the lower signal pad **301** may be formed of an alloy (MoTi) of Mo and Ti which is the same as the above-described material of the lower source electrode **151** or the lower drain electrode **161**, but is not limited thereto.

The upper signal pad **302** may be formed on a top of the lower signal pad **301**. The upper signal pad **302** may be formed of Cu which is metal having a low resistance, but is not limited thereto. The upper signal pad **302** may be formed of metal which is relatively lower in resistance than the lower signal pad **301**. In order to lower a total resistance of

the signal pad 300, a thickness of the upper signal pad 302 may be formed thicker than that of the lower signal pad 301.

The upper signal pad 302 may be formed of the same material as that of the upper source electrode 152 and/or the upper drain electrode 162 to have the same thickness as that of the upper source electrode 152 and/or the upper drain electrode 162, and the lower signal pad 301 may be formed of the same material as that of the lower source electrode 151 and/or the lower drain electrode 161 to have the same thickness as that of the lower source electrode 151 and/or the lower drain electrode 161. In this case, the signal pad 300 and the source electrode 150, the signal pad 300 and the drain electrode 160 or the signal pad 300, the source electrode 150, and the drain electrode 160 may be simultaneously formed through the same process.

The passivation layer 165 may be formed on the signal pad 300. The passivation layer 165 may extend from the active area AA. A fourth contact hole CH4 exposing a portion of the signal pad 300 may be provided in the passivation layer 165.

The pad electrode 400 may be formed on the passivation layer 165. The pad electrode 400 may be connected to the signal pad 300 through the fourth contact hole CH4. The pad electrode 400 may be exposed to the outside and connected to an external driver.

The pad electrode 400 protects a top of the signal pad 300. The top of the signal pad 300 may be configured by the upper signal pad 302 which is relatively vulnerable to corrosion, and thus, the pad electrode 400 may be formed to cover the top of the upper signal pad 302 exposed through the fourth contact hole CH4, thereby preventing the upper signal pad 302 from being corroded. As described above, since the pad electrode 400 prevents the top of the upper signal pad 302 from being corroded, the signal pad 300 may be formed in the above-described two-layer structure. An oxidation rate of the pad electrode 400 may be lower than that of the upper signal pad 302. That is, the pad electrode 400 may be formed of a material which is stronger in corrosion resistance than a material forming the upper signal pad 302. Also, since the pad electrode 400 is exposed to the outside, the pad electrode 400 may be formed of a material which is strong in corrosion resistance. The pad electrode 400 may be formed of an alloy (MoTi) of Mo and Ti which is the same as the above-described material of the first lower anode electrode 181 and/or the first lower auxiliary electrode 191, but is not limited thereto. The pad electrode 400 may be formed of the same material as that of the first lower anode electrode 181 and/or the first lower auxiliary electrode 191 to have the same thickness as that of the first lower anode electrode 181 and/or the first lower auxiliary electrode 191. In this case, the pad electrode 400 and the first lower anode electrode 181, or the pad electrode 400 and the first lower auxiliary electrode 191, or the pad electrode 400, the first lower anode electrode 181, and the first lower auxiliary electrode 191 may be pattern-formed through the same mask process, and thus, a separate process is not added.

FIG. 3 is a cross-sectional view of an organic light emitting display apparatus according to another embodiment of the present invention. A structure of a pad electrode 400 is changed from that of FIG. 2. Otherwise, the organic light emitting display apparatus of FIG. 3 is the same as the above-described organic light emitting display apparatus of FIG. 2. Thus, like reference numerals refer to like elements. Hereinafter, only elements different from the above-described elements of FIG. 2 will be described in detail.

As illustrated in FIG. 3, according to another embodiment of the present invention, a pad electrode 400 may include a lower pad electrode 401, an upper pad electrode 402, and a cover pad electrode 403.

The lower pad electrode 401 may be formed to cover a top of the upper signal pad 302 exposed through the fourth contact hole CH4 and prevents the upper signal pad 302 from being corroded. To this end, an oxidation rate of the lower pad electrode 401 may be lower than that of the upper signal pad 302. That is, the lower pad electrode 401 may be formed of a material which is stronger in corrosion resistance than a material forming the upper signal pad 302. As described above, since the lower pad electrode 401 prevents the top of the upper signal pad 302 from being corroded, the signal pad 300 may be formed in the above-described two-layer structure. The lower pad electrode 401 may be formed of an alloy (MoTi) of Mo and Ti which is the same as the above-described material of the first lower anode electrode 181 and/or the first lower auxiliary electrode 191, but is not limited thereto. The lower pad electrode 401 may be formed of the same material as that of the first lower anode electrode 181 and/or the first lower auxiliary electrode 191 to have the same thickness as that of the first lower anode electrode 181 and/or the first lower auxiliary electrode 191. In this case, the lower pad electrode 401 and the first lower anode electrode 181, the lower pad electrode 401 and the first lower auxiliary electrode 191, or the lower pad electrode 401, the first lower anode electrode 181, and the first lower auxiliary electrode 191 may be pattern-formed through the same mask process.

The upper pad electrode 402 may be formed between the lower pad electrode 401 and the cover pad electrode 403. The upper pad electrode 402 may be formed of Cu which is a metal having a low resistance, but is not limited thereto. The upper pad electrode 402 may be formed of a metal which is relatively lower in resistance than the lower pad electrode 401 and the cover pad electrode 403. In order to lower a total resistance of the pad electrode 400, a thickness of the upper pad electrode 402 may be formed thicker than that of each of the lower pad electrode 401 and the cover pad electrode 403. The upper pad electrode 402 may be formed of the same material as that of the first upper anode electrode 182 and/or the first upper auxiliary electrode 192 to have the same thickness as that of the first upper anode electrode 182 and/or the first upper auxiliary electrode 192. In this case, the upper pad electrode 402 and the first upper anode electrode 182, the upper pad electrode 402 and the first upper auxiliary electrode 192, or the upper pad electrode 402, the first upper anode electrode 182, and the first upper auxiliary electrode 192 may be pattern-formed through the same process.

The cover pad electrode 403 may be formed on the upper pad electrode 402. The cover pad electrode 403 may be formed to cover a top and a side surface of the upper pad electrode 402, thereby preventing the upper pad electrode 402 from being corroded. That is, the cover pad electrode 403 prevents the upper pad electrode 402 from being exposed to the outside. To this end, an oxidation rate of the cover pad electrode 403 may be lower than that of the upper pad electrode 402. That is, the cover pad electrode 403 may be formed of a material which is stronger in corrosion resistance than a material forming the upper pad electrode 402.

The cover pad electrode 403 may cover up to a side surface of the lower pad electrode 401. In this case, an oxidation rate of the cover pad electrode 403 may be lower than that of the lower pad electrode 401. That is, the cover

15

pad electrode **403** may be formed of a material which is stronger in corrosion resistance than a material forming the lower pad electrode **401**. The cover pad electrode **403** may be formed of a transparent conductive material such as ITO or the like, but is not limited thereto. The cover pad electrode **403** may be formed of the same material as that of the second lower anode electrode **201** and/or the second lower auxiliary electrode **211** to have the same thickness as that of the second lower anode electrode **201** and/or the second lower auxiliary electrode **211**. In this case, the cover pad electrode **403** and the second lower anode electrode **201**, the cover pad electrode **403** and the second lower auxiliary electrode **211**, the cover pad electrode **403**, the second lower anode electrode **201**, and the second lower auxiliary electrode **211** may be pattern-formed through the same mask process.

FIGS. **4A** to **4H** are cross-sectional views illustrating a method of manufacturing an organic light emitting display apparatus according to an embodiment of the present invention and relate to a method of manufacturing the above-described organic light emitting display apparatus of FIG. **2**. Thus, like reference numerals refer to like elements, and in a material and a structure of each element, the same or similar descriptions are not repeated.

First, as illustrated in FIG. **4A**, an active layer **110**, a gate insulation layer **120**, a gate electrode **130**, an interlayer dielectric **140**, a source electrode **150**, a drain electrode **160**, and a signal pad **300** may be sequentially formed on a substrate **100**.

To provide a more detailed description, the active layer **110** may be formed on the substrate **100**, the gate insulation layer **120** may be formed on the active layer **110**, the gate electrode **130** may be formed on the gate insulation layer **120**, the interlayer dielectric **140** may be formed on the gate electrode **130**, and a first contact hole **CH1** and a second contact hole **CH2** may be formed in the gate insulation layer **120** and the interlayer dielectric **140**. Subsequently, the drain electrode **160** which is connected to one end region of the active layer **110** through the first contact hole **CH1**, the source electrode **150** which is connected to the other end region of the active layer **110** through the second contact hole **CH2**, and the signal pad **300** may be formed.

The active layer **110**, the gate electrode **130**, the source electrode **150**, and the drain electrode **160** may be formed in an active area **AA**. The gate insulation layer **120** and the interlayer dielectric **140** may be formed to extend from the active area **AA** to a pad area **PA**, and the signal pad **300** may be formed in the pad area **AA**. Through such a process, a TFT **T** may be formed in the active area **AA**, and the signal pad **300** may be formed in the pad area **PA**.

The source electrode **150** may be configured with a lower source electrode **151** and an upper source electrode **152**. The drain electrode **160** may be configured with a lower drain electrode **161** and an upper drain electrode **162**. And, the signal pad **300** may be configured with a lower signal pad **301** and an upper signal pad **302**. The source electrode **150**, the drain electrode **160**, and the signal pad **300** may be simultaneously formed of the same material by the same patterning process.

Subsequently, as illustrated in FIG. **4B**, a passivation layer **165** may be formed on the source electrode **150**, the drain electrode **160**, and the signal pad **300**, and a planarization layer **170** may be formed on the passivation layer **165**. The planarization layer **170** may include a third contact hole **CH3**.

The passivation layer **165** may be formed to extend from the active area **AA** to the pad area **PA**, and the planarization layer **170** may be formed in the active area **AA**. Since a TFT

16

is not formed in the pad area **PA**, the necessity for planarizing a surface of the pad area **PA** is small, and thus, the planarization layer **170** may not be formed in the pad area **PA**.

Subsequently, as illustrated in FIG. **4C**, by removing partial regions of the passivation layer **165**, a third contact hole **CH3** and a fourth contact hole **CH4** may be formed in the passivation layer **165**. The source electrode **150** may be exposed to the outside by the third contact hole **CH3** which is included in the passivation layer **165** and the planarization layer **170**, and the signal pad **300** may be exposed to the outside by the fourth contact hole **CH4** included in the passivation layer **165**. According to an embodiment of the present invention, the third contact hole **CH3** of the passivation layer **165** for externally exposing the source electrode **150** and the fourth contact hole **CH4** of the passivation layer **165** for externally exposing the signal pad **300** may be simultaneously formed. Thus, the third contact hole **CH3** and the fourth contact hole **CH4** may be formed through one mask process, thereby preventing the number of mask processes from increasing. To provide a more detailed description, since the upper signal pad **302** exposed by the fourth contact hole **CH4** is vulnerable to corrosion, it is required for an etchant not to be brought in contact with the upper signal pad **302**. According to an embodiment of the present invention, the exposed upper signal pad **302** may be covered by a lower pad electrode **401** in a process of FIG. **4D** to be described below. Thus, the etchant does not contact the upper signal pad **302**. For the same reason as this, the fourth contact hole **CH4** and the third contact hole **CH3** may be simultaneously formed. In another embodiment, instead of the source electrode **150**, the drain electrode **160** may be exposed to the outside by a third contact hole **CH3** which is included in the passivation layer **165** and the planarization layer **170**.

Subsequently, as illustrated in FIG. **4D**, a first anode electrode **180** and a first auxiliary electrode **190** may be formed to be separated from each other on the planarization layer **170** in the active area **AA**, and a first pad electrode **400a** may be formed on the passivation layer **165** in the pad area **PA**.

The first anode electrode **180** may be formed to be connected to the source electrode **150** through the third contact hole **CH3**, and the first pad electrode **400a** may be formed to be connected to the signal pad **300** through the fourth contact hole **CH4**.

The first anode electrode **180** may be configured with a first lower anode electrode **181** and a first upper anode electrode **182**, and the first auxiliary electrode **190** may be configured with a first lower auxiliary electrode **191** and a first upper auxiliary electrode **192**. The first pad electrode **400a** may be configured with a lower pad electrode **401** and an upper pad electrode **402**.

The first anode electrode **180**, the first auxiliary electrode **190**, and the first pad electrode **400a** may be simultaneously formed of the same material through the same patterning process.

Subsequently, as illustrated in FIG. **4E**, a second anode electrode **200** may be formed on a first anode electrode **180** in the active area **AA**, and a second auxiliary electrode **210** may be formed on a first auxiliary electrode **190** in the active area **AA**.

The second anode electrode **200** may be pattern-formed to cover a top and a side surface of the first anode electrode **180**, and the second auxiliary electrode **210** may be pattern-formed to cover a top and a side surface of the first auxiliary electrode **190**. The second anode electrode **200** and the

second auxiliary electrode **210** may be simultaneously formed of the same material through the same patterning process.

The second anode electrode **200** may include a second lower anode electrode **201**, a second center anode electrode **202**, and a second upper anode electrode **203**. The second auxiliary electrode **210** may include a second lower auxiliary electrode **211**, a second center auxiliary electrode **212**, and a second upper auxiliary electrode **213**.

A process of pattern-forming the second anode electrode **200** and the second auxiliary electrode **210** may include an etching process using an etchant. An upper pad electrode **402** formed in the pad area PA may be etched together in the etching process, and thus, a manufacturing process is simplified. That is, the upper pad electrode **402** may be removed in the process of pattern-forming the second anode electrode **200** and the second auxiliary electrode **210**, and thus, a pad electrode **400** including only the lower pad electrode **401** may be finished. Since the upper pad electrode **402** is formed of a material vulnerable to corrosion, the pad electrode **400** including only the lower pad electrode **401** which is excellent in corrosion resistance may be obtained by removing the upper pad electrode **402**.

Subsequently, as illustrated in FIG. 4F, a bank **220** may be formed on one side and the other side of the second anode electrode **200** to expose a top of the second anode electrode **200**. Also, the bank **220** may be formed on one side and the other side of the second auxiliary electrode **210** to expose a top of the second auxiliary electrode **210**.

Moreover, a first partition wall **231** and a second partition wall **232** may be sequentially formed on the exposed top of the second auxiliary electrode **210**. The first partition wall **231** may be formed of the same material as that of the bank **220** through the same pattern forming process as that of the bank **220** simultaneously with the bank **220**. The partition wall **230** may be formed to be separated from the bank **220** by a certain distance. Thus, a separation space may be provided between the partition wall **230** and the bank **220**.

In order for a top of the partition wall **230** to act as eaves, a width of a top of the second partition wall **232** may be formed greater than that of a bottom of the second partition wall **232**. Particularly, with respect to a case where the organic light emitting display apparatus is seen from the front thereof, the top of the second partition wall **232** may cover the separation space between the partition wall **230** and the bank **220**, and thus, in a below-described process of depositing an organic emission layer **240**, the organic emission layer **240** is not deposited in the separation space between the partition wall **230** and the bank **220**.

Subsequently, as illustrated in FIG. 4G, the organic emission layer **240** may be formed on the second anode electrode **200**. The organic emission layer **240** may be formed by a deposition process such as an evaporation process which is excellent in straightness of a deposited material, and thus, the organic emission layer **240** may be deposited on tops of the bank **220** and the partition wall **230**, but the organic emission layer **240** is not deposited in the separation space between the partition wall **230** and the bank **220**. That is, the top of the partition wall **230** may act as eaves in depositing the organic emission layer **240**, and thus, even when the organic emission layer **240** is deposited without a mask pattern which covers the top of the second auxiliary electrode **210**, the organic emission layer **240** is not deposited in the separation space between the partition wall **230** and the bank **220**.

Subsequently, as illustrated in FIG. 4H, a cathode electrode **250** may be formed on the organic emission layer **240**.

The cathode electrode **250** may be formed to be connected to the second auxiliary electrode **210** through the separation space between the partition wall **230** and the bank **220**. The cathode electrode **250** may be formed by a deposition process such as a sputtering process which is not good in straightness of a deposited material, and thus, the cathode electrode **250** may be deposited in the separation space between the partition wall **230** and the bank **220** in a process of depositing the cathode electrode **250**.

FIGS. 5A to 5I are cross-sectional views illustrating a method of manufacturing an organic light emitting display apparatus according to another embodiment of the present invention and relates to a method of manufacturing the above-described organic light emitting display apparatus of FIG. 3. Hereinafter, descriptions repetitive of the above-described embodiment are omitted.

First, as illustrated in FIG. 5A, an active layer **110**, a gate insulation layer **120**, a gate electrode **130**, an interlayer dielectric **140**, a source electrode **150**, a drain electrode **160**, and a signal pad **300** may be sequentially formed on a substrate **100**. Therefore, a TFT T may be formed in the active area AA, and the signal pad **300** may be formed in the pad area PA.

Subsequently, as illustrated in FIG. 5B, a passivation layer **165** may be formed on the source electrode **150**, the drain electrode **160**, and the signal pad **300**, and a planarization layer **170** may be formed on the passivation layer **165**. The planarization layer **170** may include a third contact hole CH3.

Subsequently, as illustrated in FIG. 5C, the third contact hole CH3 and a fourth contact hole CH4 may be formed in the passivation layer **165**. The source electrode **150** may be exposed to the outside by the third contact hole CH3 which is included in the passivation layer **165** and the planarization layer **170**, and the signal pad **300** may be exposed to the outside by the fourth contact hole CH4 included in the passivation layer **165**.

Subsequently, as illustrated in FIG. 5D, a first anode electrode **180** and a first auxiliary electrode **190** may be formed on the planarization layer **170** in the active area AA, and a first pad electrode **400a** may be formed on the passivation layer **165** in the pad area PA.

The first anode electrode **180** may be configured with a first lower anode electrode **181** and a first upper anode electrode **182**, and the first auxiliary electrode **190** may be configured with a first lower auxiliary electrode **191** and a first upper auxiliary electrode **192**. The first pad electrode **400a** may be configured with a lower pad electrode **401** and an upper pad electrode **402**.

Subsequently, as illustrated in FIG. 5E, a second anode electrode **200** may be formed on a first anode electrode **180** in the active area AA, a second auxiliary electrode **210** may be formed on a first auxiliary electrode **190** in the active area AA, and a second pad electrode **400b** may be formed on the first pad electrode **400a** in the pad area PA.

The second anode electrode **200** may be pattern-formed to cover a top and a side surface of the first anode electrode **180**, and the second auxiliary electrode **210** may be pattern-formed to cover a top and a side surface of the first auxiliary electrode **190**. The second pad electrode **400b** may be pattern-formed to cover a top and a side surface of the first pad electrode **400a**.

The second pad electrode **400b** may act as a cover pad electrode of the first pad electrode **400a** and may include a lower cover pad electrode **403**, a center cover pad electrode **404**, and an upper cover pad electrode **405**.

The second anode electrode **200**, the second auxiliary electrode **210**, and the second pad electrode **400b** may be simultaneously formed of the same material through the same patterning process.

Subsequently, as illustrated in FIG. 5F, by removing the center cover pad electrode **404** and the upper cover pad electrode **405**, only the lower cover pad electrode **403** may be left as a cover pad electrode. Therefore, a pad electrode **400** including a lower pad electrode **401**, an upper pad electrode **402**, and a lower cover pad electrode **403** may be finished.

A process of removing the center cover pad electrode **404** and the upper cover pad electrode **405** may be performed by using a laser irradiation process using a laser irradiation apparatus **500**.

Subsequently, as illustrated in FIG. 5G, a bank **220** may be formed on one side and the other side of the second anode electrode **200** to expose a top of the second anode electrode **200**. Also, the bank **220** may be formed on one side and the other side of the second auxiliary electrode **210** to expose a top of the second auxiliary electrode **210**. Also, a first partition wall **231** and a second partition wall **232** may be sequentially formed on the exposed top of the second auxiliary electrode **210**. The partition wall **230** may be formed to be separated from the bank **220** by a certain distance, and thus, a separation space may be provided between the partition wall **230** and the bank **220**.

Subsequently, as illustrated in FIG. 5H, an organic emission layer **240** may be formed on the second anode electrode **200**. The organic emission layer **240** may be deposited on tops of the bank **220** and the partition wall **230**, but is not deposited in the separation space between the partition wall **230** and the bank **220**.

Subsequently, as illustrated in FIG. 5I, a cathode electrode **250** may be formed on the organic emission layer **240**. The cathode electrode **250** may be formed to be connected to the second auxiliary electrode **210** through the separation space between the partition wall **230** and the bank **220**.

In the embodiments of the present invention, the pad electrode may be formed to cover the top of the signal pad. Particularly, the top of the pad electrode may be formed lower in oxidation rate than the top of the signal pad, thereby preventing the signal pad from being corroded. Accordingly, the signal pad may be formed in a two-layer structure which includes the lower signal pad and the upper signal pad not being vulnerable to corrosion.

Moreover, according to the embodiments of the present invention, the contact hole for externally exposing the source electrode and the contact hole for externally exposing the signal pad may be simultaneously formed in the passivation layer. Thus, one mask process does not increase (e.g. the number of masking steps does not have to be increased).

Moreover, according to the embodiments of the present invention, the two auxiliary electrodes (for example, the first and second auxiliary electrodes) may be stack-formed for lowering the resistance of the cathode electrode. Thus, the desired resistance characteristic of the auxiliary electrode is more easily adjusted. That is, since the auxiliary electrode is formed on the same layer as a layer on which the anode electrode is formed, there is a limitation in increasing a size of the auxiliary electrode. Therefore, according to the embodiments of the present invention, the auxiliary electrode may be stacked in two layers, and thus, provided is a structure of the auxiliary electrode which is more effective to lower the resistance of the cathode electrode.

It will be apparent to those skilled in the art that various modifications and variations can be made in the present

invention without departing from the spirit or scope of the invention. Thus, it is intended that the present invention cover the modifications and variations of this invention provided they come within the scope of the appended claims and their equivalents.

What is claimed is:

1. An organic light emitting display apparatus, comprising:

a substrate including an active area and a pad area;
an anode electrode in the active area of the substrate;
an organic emission layer on the anode electrode;
a cathode electrode on the organic emission layer;
an auxiliary electrode on a same layer as the anode electrode and connected to the cathode electrode;
a signal pad in the pad area of the substrate; and
a pad electrode connected to the signal pad through a contact hole and covering a top of the signal pad, wherein a top of the pad electrode has a lower oxidation rate than the top of the signal pad,
wherein the signal pad comprises a lower signal pad and an upper signal pad,
wherein an oxidation rate of the lower signal pad is lower than an oxidation rate of the upper signal pad, and
wherein a resistance of the upper signal pad is lower than a resistance of the lower signal pad.

2. The organic light emitting display apparatus of claim 1, wherein the anode electrode comprises:

a first anode electrode; and
a second anode electrode covering a top and a side surface of the first anode electrode.

3. The organic light emitting display apparatus of claim 2, wherein the first anode electrode comprises a first lower anode electrode and a first upper anode electrode, and wherein the second anode electrode comprises a second lower anode electrode, a second center anode electrode, and a second upper anode electrode.

4. The organic light emitting display apparatus of claim 3, wherein the pad electrode is a same material as that of the first lower anode electrode.

5. The organic light emitting display apparatus of claim 3, wherein the pad electrode comprises a lower pad electrode, an upper pad electrode, and a cover pad electrode, the cover pad electrode covering a top surface and a side surface of the upper pad electrode,

wherein the lower pad electrode is a same material as that of the first lower anode electrode,
wherein the upper pad electrode is a same material as that of the first upper anode electrode, and
wherein the cover pad electrode is a same material as that of the second lower anode electrode.

6. The organic light emitting display apparatus of claim 3, wherein an oxidation rate of the first lower anode electrode is lower than an oxidation rate of the first upper anode electrode,

wherein a resistance of the first upper anode electrode is lower than a resistance of the first lower anode electrode,

wherein an oxidation rate of each of the second lower anode electrode and the second upper anode electrode is lower than an oxidation rate of the second center anode electrode, and

wherein a resistance of the second center anode electrode is lower than a resistance of each of the second lower anode electrode and the second upper anode electrode.

7. The organic light emitting display apparatus of claim 1, wherein the auxiliary electrode comprises:

a first auxiliary electrode; and

a second auxiliary electrode covering a top and a side surface of the first auxiliary electrode.

8. The organic light emitting display apparatus of claim 7, wherein the pad electrode comprises a lower pad electrode, an upper pad electrode, and a cover pad electrode, the cover pad electrode covering a top and a side surface of the upper pad electrode, 5

wherein the first auxiliary electrode includes a first lower auxiliary electrode and the second auxiliary electrode comprises a second lower auxiliary electrode, and 10 wherein the lower pad electrode is a same material as that of the first lower auxiliary electrode and the cover pad electrode is a same material as that of the second lower auxiliary electrode.

9. The organic light emitting display apparatus of claim 7, further comprising: 15

a bank on one side and the other side of the second auxiliary electrode; and

a partition wall on the second auxiliary electrode and separated from the bank, 20

wherein the cathode electrode is connected to the second auxiliary electrode through a separation space between the bank and the partition wall.

10. The organic light emitting display apparatus of claim 1, further comprising a passivation layer over a source electrode and the signal pad, wherein the contact hole is a contact hole through the passivation layer. 25

11. The organic light emitting display apparatus of claim 10, wherein the pad electrode covers a portion of the top of the signal pad exposed by the contact hole. 30

* * * * *

专利名称(译)	有机发光显示器		
公开(公告)号	US9543544	公开(公告)日	2017-01-10
申请号	US14/984561	申请日	2015-12-30
[标]申请(专利权)人(译)	乐金显示有限公司		
申请(专利权)人(译)	LG DISPLAY CO. , LTD.		
当前申请(专利权)人(译)	LG DISPLAY CO. , LTD.		
[标]发明人	LEE JOON SUK KIM SE JUNE LEE SO JUNG JANG JIN HEE IM JONG HYEOK LEE JAE SUNG		
发明人	LEE, JOON SUK KIM, SE JUNE LEE, SO JUNG JANG, JIN-HEE IM, JONG HYEOK LEE, JAE SUNG		
IPC分类号	H01L51/52 H01L27/32 H01L51/56		
CPC分类号	H01L51/5253 H01L27/3246 H01L27/3258 H01L51/5228 H01L51/56 H01L21/77 H01L27/3241 H01L51/5203 H01L27/3218 H01L27/3248 H01L27/326 H01L27/3276 H01L27/3279 H01L51/5209 H01L2227/323		
代理机构(译)	DENTONS美国律师事务所		
优先权	1020150075393 2015-05-28 KR		
其他公开文献	US20160351851A1		
外部链接	Espacenet USPTO		

摘要(译)

公开了一种有机发光显示装置，其中阳极电极，有机发射层，阴极电极以及连接到阴极电极并且设置在与阳极电极相同的层上的辅助电极设置在有源区，在所述基板的焊盘区域中设置信号焊盘和连接到所述信号焊盘并覆盖所述信号焊盘的顶部的焊盘电极，并且所述焊盘电极的顶部的氧化速率低于所述基板的顶部信号焊盘。

