



US 20190207153A1

(19) **United States**(12) **Patent Application Publication**
Hou(10) **Pub. No.: US 2019/0207153 A1**(43) **Pub. Date: Jul. 4, 2019**(54) **DISPLAY PANEL, METHOD FOR
FABRICATING THE SAME AND DISPLAY
DEVICE***H01L 51/56* (2006.01)*B01J 20/04* (2006.01)(52) **U.S. Cl.**CPC *H01L 51/5246* (2013.01); *H01L 27/3244*
(2013.01); *H01L 51/5259* (2013.01); *H01L*
2251/303 (2013.01); *B01J 20/041* (2013.01);
B01J 20/046 (2013.01); *H01L 51/56*
(2013.01)(71) Applicant: **BOE TECHNOLOGY GROUP CO.,
LTD.**, Beijing (CN)(72) Inventor: **Wenjun Hou**, Beijing (CN)(21) Appl. No.: **16/089,727**(22) PCT Filed: **Jan. 26, 2018**(86) PCT No.: **PCT/CN2018/074347**


§ 371 (c)(1),

(2) Date: **Sep. 28, 2018**(30) **Foreign Application Priority Data**

May 11, 2017 (CN) 201710329212.8

Publication Classification(51) **Int. Cl.***H01L 51/52* (2006.01)*H01L 27/32* (2006.01)(57) **ABSTRACT**

The disclosure discloses a display panel, a method for fabricating the same and a display device. The display panel includes: a base substrate and a cover plate arranged opposite to each other, an organic light emitting display arranged between the base substrate and the cover plate, a frame sealant arranged between the base substrate and the cover plate and located around the organic light emitting display, and a filler arranged in a sealing space constituted by the base substrate, the cover plate and the frame sealant. The display panel further comprises: an elastic component arranged between the frame sealant and the organic light emitting display.






Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10A




Fig. 10B




Fig. 11




Fig. 12

DISPLAY PANEL, METHOD FOR FABRICATING THE SAME AND DISPLAY DEVICE

[0001] The present application claims priority to Chinese Patent Application No. 201710329212.8, filed with the Chinese Patent Office on May 11, 2017 and entitled “A display panel and a display device”, the content of which is incorporated by reference in the entirety.

TECHNICAL FIELD

[0002] The disclosure relates to the field of display technologies and particularly to a display panel, a method for fabricating the same and a display device.

BACKGROUND

[0003] Compared with a Liquid Crystal Display (LCD), an Organic Light Emitting Display (OLED) has advantages such as self-illuminating, fast response, wide angle of view, high brightness, vivid color, light weight and the like, and is considered as a next generation display technology.

[0004] However, the organic materials and the metal materials in an OLED display panel are highly sensitive to the water oxygen and are easy to be oxidized and denatured, to thereby cause defects such as dark dots, pixel contraction, reduced lifetime and the like. Thus the OLED display panel requires a higher demand on the encapsulation.

SUMMARY

[0005] Embodiments of the disclosure provide a display panel, includes: a cover plate, a base substrate arranged opposite to the cover plate, an organic light emitting display arranged between the base substrate and the cover plate, a frame sealant arranged between the base substrate and the cover plate and located around the organic light emitting display, a filler arranged in a sealing space constituted by the base substrate, the cover plate and the frame sealant, and an elastic component arranged between the frame sealant and the organic light emitting display.

[0006] In a possible implementation, in the display panel above according to the embodiments of the disclosure, the elastic component contacts with the base substrate and the cover plate.

[0007] In a possible implementation, in the display panel above according to the embodiments of the disclosure, the elastic component is arranged around the organic light emitting display.

[0008] In a possible implementation, in the display panel above according to the embodiments of the disclosure, the elastic component is arranged at intervals around the organic light emitting display.

[0009] In a possible implementation, in the display panel above according to the embodiments of the disclosure, a gap is arranged between the frame sealant and the elastic component.

[0010] In a possible implementation, in the display panel above according to the embodiments of the disclosure, an absorbent compound is included in the gap.

[0011] In a possible implementation, in the display panel above according to the embodiments of the disclosure, the elastic component contacts with the frame sealant.

[0012] In a possible implementation, in the display panel above according to the embodiments of the disclosure, the elastic component includes the absorbent compound.

[0013] In a possible implementation, in the display panel above according to the embodiments of the disclosure, the display panel further includes: an encapsulation layer arranged between the organic light emitting display and the cover plate and completely covering the organic light emitting display.

[0014] In a possible implementation, in the display panel above according to the embodiments of the disclosure, the material of the elastic component includes any one or more of a rubber, an ABS resin or a polysiloxane.

[0015] In a possible implementation, in the display panel above according to the embodiments of the disclosure, the absorbent compound includes any one or more of a calcium oxide, a sodium oxide, a barium oxide, a magnesium oxide, a lithium oxide or a lithium bromide.

[0016] Accordingly, embodiments of the disclosure further provide a display device, which includes any one of the display panel above according to the embodiments of the disclosure.

[0017] In another aspect, embodiments of the disclosure further provide a method for fabricating the display panel, which includes: providing a base substrate on which an organic light emitting display is formed; providing a cover plate, fabricating a frame sealant at a position of a frame of the cover plate, and forming an elastic component at an inner side of the frame sealant; filling an area surrounded by the elastic component with the filler; fitting the base substrate with the cover plate in the vacuum environment, and curing the frame sealant and the filler via the ultraviolet light or heating.

[0018] In a possible implementation, in the method above according to the embodiments of the disclosure, after forming the elastic component and before filling the area surrounded by the elastic component with the filler, the method further includes: forming an absorbent compound between the elastic component and the frame sealant.

[0019] In a possible implementation, in the method above according to the embodiments of the disclosure, when forming the elastic component, the method further includes: mixing the absorbent compound in an elastic material for forming the elastic component.

BRIEF DESCRIPTION OF THE DRAWINGS

[0020] FIG. 1 is a schematic structural diagram of a display panel;

[0021] FIG. 2 is a schematic structural diagram of a display panel according to embodiments of the disclosure;

[0022] FIG. 3 is a schematic structural diagram of a display panel according to the embodiments of the disclosure;

[0023] FIG. 4 is a schematic structural diagram of a display panel according to the embodiments of the disclosure;

[0024] FIG. 5 is a schematic structural diagram of a display panel according to the embodiments of the disclosure;

[0025] FIG. 6 is a schematic structural diagram of a display panel according to the embodiments of the disclosure;

[0026] FIG. 7 is a schematic structural diagram of a display panel according to the embodiments of the disclosure;

[0027] FIG. 8 is a schematic structural diagram of a display panel according to the embodiments of the disclosure;

[0028] FIG. 9 is a schematic structural diagram of a display panel according to the embodiments of the disclosure;

[0029] FIG. 10a and FIG. 10b are schematic structural diagrams of a display panel according to the embodiments of the disclosure respectively;

[0030] FIG. 11 is a schematic structural diagram of a display panel according to the embodiments of the disclosure;

[0031] FIG. 12 is a schematic structural diagram of a display panel according to the embodiments of the disclosure.

DETAILED DESCRIPTION OF THE EMBODIMENTS

[0032] In order to make the objects, technical solutions, and advantages of the embodiments of the disclosure more apparent, the technical solutions according to the embodiments of the disclosure will be described below clearly and fully with reference to the drawings in the embodiments of the disclosure, and apparently the embodiments described below are only a part but not all of the embodiments of the disclosure. Based upon the embodiments here of the disclosure, all the other embodiments which can occur to those skilled in the art without any inventive effort shall fall into the scope of the disclosure.

[0033] According to the technology known by the inventor, as illustrated in FIG. 1, an OLED display panel includes: a base substrate **01**, a cover plate **02**, an organic light emitting display **03** arranged between the base substrate **01** and the cover plate **02**, and a frame sealant **04** arranged between the base substrate **01** and the cover plate **02**, where the frame sealant **04** is used for sealing the organic light emitting display **03**. When the sealed display panel is filled with the filler, cracks may be generated at the edge(s) of the cured frame sealant **04** due to the pressure effect, to thereby cause an increased water oxygen transmittance and influence the reliability of the OLED display panel.

[0034] The embodiments of the disclosure provide a display panel, a method for fabricating the same and a display device, so as to reduce the pressure applied on the frame sealant and increase the airtightness of the display panel.

[0035] The implementations of the display panel, the method for fabricating the same and the display device according to the embodiments of the disclosure will be illustrated below in details with reference to the accompanying drawings.

[0036] The thicknesses and shapes of respective film layers in the accompanying drawings do not reflect the actual proportions, and are merely intended to illustrate the content of the embodiments of the disclosure.

[0037] As illustrated in FIG. 2, the embodiments of the disclosure provide a display panel **10**, which includes: a base substrate **01** and a cover plate **02** arranged opposite to each other, an organic light emitting display **03** arranged between the base substrate **01** and the cover plate **02**, a frame sealant **04** arranged between the base substrate **01** and the cover plate **02** and located around the organic light emitting

display **03**, and filler **07** arranged in a sealing space constituted by the base substrate **01**, the cover plate **02** and the frame sealant **04**; where the display panel **10** further includes an elastic component **05** arranged between the frame sealant **04** and the organic light emitting display **03**.

[0038] Particularly, the main effect of the elastic component **05** in the embodiments of the disclosure is to buffer the pressure of the filler on the frame sealant **04**, so the elastic component **05** in the embodiments of the disclosure can be arranged continuously around an inner side of the frame sealant **04** in one or more rounds or arranged at intervals at an inner side of the frame sealant **04**, which is not limited herein. Furthermore, the elastic component **05** according to the embodiments of the disclosure fits closely onto the frame sealant **04** or has a fixed distance from the frame sealant **04**, which is not limited herein. The structure of the display panel **10** illustrated in FIG. 2 is only an optional implementation, and does not represent that the display panel only has the structure illustrated in FIG. 2.

[0039] With the display panel according to the embodiments of the disclosure, when the sealing area surrounded by the frame sealant **04** is filled with the filler **07**, due to the elastic component **05** arranged between the frame sealant **04** and the organic light emitting display **03** and the elastic effect of the elastic component **05**, the pressure of the filler **07** is buffered, the pressure applied on the frame sealant **04** is reduced, the crack problem caused by the frame sealant **04** is avoided, and the airtightness of the display panel **10** is further increased.

[0040] Optionally, in the display panel above according to the embodiments of the disclosure, as illustrated in FIG. 3, the elastic component **05** contacts with the base substrate **01**, and at the same time, the elastic component **05** contacts with the cover plate **02**. Particularly the elastic component **05** is arranged between the base substrate **01** and the cover plate **02**, and as illustrated in FIG. 2, a height of the elastic component **05** is set to be smaller than a height of the frame sealant **04**. Or, as illustrated in FIG. 3, the height of the elastic component **05** is set to be the same as the height of the frame sealant **04**. When the elastic component **05** is subjected to the pressure of the filler **07**, the pressure can be buffered to a larger extent, to reduce the pressure applied on the frame sealant **04**.

[0041] Optionally, in the display panel above according to the embodiments of the disclosure, as illustrated in FIG. 4 which is a top view of the display panel **10**, the organic light emitting display **03** of the display panel **10** is arranged at a display area of the display panel **10**; and a non-display area is provided with the frame sealant **04** around the organic light emitting display **03**, and the elastic component **05** arranged between the frame sealant **04** and the organic light emitting display **03**, where the elastic component **05** is arranged around the organic light emitting display **03**.

[0042] Particularly, as illustrated in FIG. 4, the elastic component **05** is arranged around the organic light emitting display **03** to form a continuous round, for example, a shape thereof is the same as a shape of the frame sealant **04**, which surrounds the organic light emitting display **03** to form a closed round. It shall be noted that the elastic component **05** according to the embodiments of the disclosure can further be arranged to be multiple continuous rounds around the organic light emitting display **03**, to thereby further reduce the pressure applied on the frame sealant **04**. Or, as illustrated in FIG. 5, the elastic component **05** can also be

arranged at intervals around the organic light emitting display 03, that is, the elastic component 05 is discontinuous.

[0043] As illustrated in FIG. 4 or FIG. 5, when the elastic component 05 is arranged around the organic light emitting display 03, the elastic component 05 contacts with both the base substrate 01 and the cover plate 02, or contacts with only the base substrate 01, which is not limited herein. When the elastic component 05 contacts with both the base substrate 01 and the cover plate 02, the sealing space can be formed among the elastic component 05, the base substrate 01 and the cover plate 02, and the sealing space is filled with the filler 07. Due to the extrusion of the filler 07, the elastic component 05 is subjected to the pressure of the extrusion to an extreme, to thereby reduce the pressure applied on the frame sealant 04 to the utmost extent.

[0044] Optionally, as illustrated in FIG. 6, when the elastic component 05 is arranged at intervals around the organic light emitting display 03, elastic components 05 can be arranged at intervals on the base substrate 01, and at the same time, a lower surface of the cover plate 02 can also include elastic components 05 arranged at intervals, and the elastic components 05 on the base substrate 01 and the elastic components 05 of the lower surface of the cover plate 02 are arranged in a staggered manner. That is, the elastic components 05 arranged on the base substrate 01 and the elastic components 05 arranged at the lower surface of the cover plate 02 are spaced apart from each other, to thereby play a buffer role and reduce the pressure applied on the frame sealant 04. FIG. 6 only illustrates an arrangement of the elastic components 05, but the elastic components are not limited to the arranging in a direction as illustrated in FIG. 6. For example, elastic components 05 between the base substrate 01 and the cover plate 02 are arranged at intervals respectively, and the elastic components 05 on the base substrate 01 can correspond to the elastic components 05 of the lower surface of the cover plate 02 in a one-to-one manner, that is, the staggered arrangement manner is not presented. It shall be noted that, as illustrated in FIG. 6, orthographic projections of the elastic components 05 arranged on the base substrate 01 onto a plane perpendicular to the cross section in FIG. 6 and orthographic projections of the elastic components 05 arranged at the lower surface of the cover plate 02 onto the plane perpendicular to the cross section in FIG. 6 have no overlapping area, but in a practical application, there can be the case that their orthographic projections may have the overlapping area, which can further play a role of buffering.

[0045] Optionally, in order to further reduce the influence caused by the deformation generated when the elastic component 05 is subjected to the pressure on the frame sealant 04, in the display panel above 10 according to the embodiments of the disclosure, as illustrated in FIG. 7, there is a gap between the frame sealant 04 and the elastic component 05. Particularly, when the sealing space formed among the base substrate 1, the cover plate 02 and the frame sealant 04 is filled with the filler 07, due to the effect of the elastic component 05 which plays a buffer role, the pressure caused by the extrusion of the filler 07 is applied on the elastic component 05, and the deformation of the elastic component 05 will occur. Since the gap is arranged between the elastic component 05 and the frame sealant 04, the deformation of the elastic component 05 will not influence the frame sealant 04, to further avoid the problem that the deformation of the frame sealant 04 causes the cracks.

[0046] Optionally, since the organic light emitting display 03 is easily to be oxidized and denatured by the water oxygen, in order to avoid the organic light emitting display 03 from being oxidized, in the display panel above 10 according to the embodiments of the disclosure, as illustrated in FIG. 8, an absorbent compound M is included in the gap. Here, the absorbent compound M can absorb the water vapor, to avoid the external water vapor from entering the organic light emitting display 03 when the display panel 10 is being filled or after the filling of the display panel 10. In the embodiments of the disclosure, after the absorbent compound M is arranged in the gap between the frame sealant 04 and the elastic component 05 and after the absorbent compound M reacts with the penetrated water, the volume of the absorbent compound M will increase. Since the absorbent compound M is not arranged inside the frame sealant 04, that is, the absorbent compound M and the frame sealant 04 are independent components, the absorbent compound M with an increased volume will only extrudes the elastic component 05 to make the elastic component 05 deform, and will not influence the shape of the frame sealant 04 to thereby protect the frame sealant 04. Where the absorbent compound M can be formed by coating or filled in the gap by filling.

[0047] Optionally, the absorbent compound M can be provided in the gap between the frame sealant 04 and the elastic component 05, or can be provided inside the elastic component 05, or can be provided both in the gap between the frame sealant 04 and the elastic component 05 and inside the elastic component 05. Since the absorbent compound M is arranged in order to absorb the water vapor, any kind of arrangement is feasible.

[0048] Optionally, in the display panel above 10 according to the embodiments of the disclosure, as illustrated in FIG. 9, the elastic component 05 can contact with the frame sealant 04. Particularly, the elastic component 05 can fit closely onto the frame sealant 04.

[0049] Optionally, in the display panel above 10 according to the embodiments of the disclosure, as illustrated in FIG. 10a, the elastic component 05 can include the absorbent compound M when there is no gap between the elastic component 05 and the frame sealant 04. Or, as illustrated in FIG. 10b, when there is the gap between the elastic component 05 and the frame sealant 04, the elastic component 05 can also include the absorbent compound M; and the gap between the elastic component 05 and the frame sealant 04 can also include the absorbent compound M. By arranging the absorbent compound M in the elastic component 05, the penetrated water vapor reacts with the absorbent compound M, to thereby reduce the permeability of the water vapor and avoid the problem that the organic light emitting display 03 is oxidized. Here, when the absorbent compound M is included in the elastic component 05, the absorbent compound M can be doped in the elastic material.

[0050] Optionally, in the display panel above according to the embodiments of the disclosure, as illustrated in FIG. 11, the display panel 10 further includes: an encapsulation layer 06 arranged between the organic light emitting display 03 and the cover plate 02 and completely covering the organic light emitting display. The encapsulation layer 06 is used for encapsulating the organic light emitting display 03, and the encapsulation layer 06 includes: a first inorganic film layer, a second inorganic film layer, and a film layer arranged between the first inorganic film layer and the second inor-

ganic film layer and consists of a plurality of inorganic film layers and organic film layers which are superimposed on each other. For example, along a direction away from the organic light emitting display, the encapsulation layer **06** includes five film layers, such as the first inorganic film layer, a first organic film layer, a third inorganic film layer, a second organic film layer and a second inorganic film layer, which are arranged in that order sequentially. Or, along the direction away from the organic light emitting display, the encapsulation layer **06** includes three film layers, such as the first inorganic film layer, the first organic film layer and the second inorganic film layer, which are arranged in that order sequentially, which is not limited herein.

[0051] Optionally, in the display panel above according to the embodiments of the disclosure, a material of the elastic component **05** can be any one or more of a rubber, an ABS resin (acrylonitrile-butadiene-styrene copolymer, which is the terpolymer consists of the acrylonitrile, butadiene and styrene) or a polysiloxane.

[0052] Optionally, in the display panel above according to the embodiments of the disclosure, the absorbent compound M can be any one or more of a calcium oxide, a sodium oxide, a barium oxide, a magnesium oxide, a lithium oxide or a lithium bromide.

[0053] It shall be noted that, any features in the embodiments of the disclosure can be combined with each other to thereby form a new embodiment, and a detailed description thereof will be omitted herein.

[0054] In conclusion, in the embodiments of the disclosure, the elastic component **05** is arranged between the frame sealant **04** and the organic light emitting display **03**, to thereby avoid the problem of the cracks caused by the pressure generated for the frame sealant **04** when the display panel is filled with the filler **07**, and further ensure the airtightness of the display panel. Further, the absorbent compound M is added in the elastic component **05** and/or in the gap between the elastic component **05** and the frame sealant **04**, to thereby reduce the permeability of the water oxygen and avoid the problem that the organic light emitting display **03** in the display panel is oxidized, thus improving the reliability of the display panel, and increasing the display lifetime of the display panel.

[0055] Based upon a same inventive concept, the embodiments of the disclosure further provide a method for fabricating the display panel, where the method includes following operations.

[0056] Providing a base substrate on which an organic light emitting display is formed. Where the formation of the light emitting display includes: forming an ITO on the base substrate and patterning the ITO as an anode of the OLED, via a patterning process; fabricating a hole injection layer, a hole transmission layer, a light emitting layer, an electron transmission layer, an electron injection layer and a cathode on the ITO sequentially.

[0057] Providing a cover plate, fabricating a frame sealant at a position of a frame of the cover plate, and forming an elastic component at an inner side of the frame sealant.

[0058] Filling an area surrounded by the elastic component with the filler.

[0059] Fitting the base substrate with the cover plate in a vacuum environment, and curing the frame sealant and the filler via an ultraviolet (UV) light or heating.

[0060] Optionally, in the method for fabricating the display panel according to the embodiments of the disclosure,

after forming the elastic component and before filling the area surrounded by the elastic component with the filler, the method further includes: forming an absorbent compound between the elastic component and the frame sealant.

[0061] Optionally, in the method for fabricating the display panel according to the embodiments of the disclosure, when forming the elastic component, the method further includes: mixing the absorbent compound in an elastic material for forming the elastic component, so that the absorbent compound is included in a formed elastic component.

[0062] Therefore, in the display panel formed by the method for fabricating the display panel according to the embodiments of the disclosure, when the sealing area surrounded by the frame sealant is filled with the filler, due to the elastic component arranged between the frame sealant and the organic light emitting display and the elastic effect of the elastic component, the pressure of the filler is buffered, the pressure applied on the frame sealant is reduced, the crack problem caused by the frame sealant is avoided, and the airtightness of the display panel is further increased.

[0063] Based upon a same inventive concept, the embodiments of the disclosure further provide a display device, and as illustrated in FIG. 12, the display device **11** includes any display panel **10** above according to the embodiments of the disclosure. And the embodiments and beneficial effects of the display device are the same as the embodiments of the display panel, so that a repeated description thereof will be omitted herein.

[0064] Evidently those skilled in the art can make various modifications and variations to the disclosure without departing from the spirit and scope of the disclosure. Thus the disclosure is also intended to encompass these modifications and variations to the disclosure as long as these modifications and variations come into the scope of the claims of the disclosure and their equivalents.

1. A display panel, wherein the display panel comprises:
 - a cover plate;
 - a base substrate arranged opposite to the cover plate;
 - an organic light emitting display arranged between the base substrate and the cover plate;
 - a frame sealant arranged between the base substrate and the cover plate and located around the organic light emitting display;
 - a filler arranged in a sealing space constituted by the base substrate, the cover plate and the frame sealant; and
 - an elastic component arranged between the frame sealant and the organic light emitting display.
2. The display panel according to claim 1, wherein the elastic component contacts with the base substrate and the cover plate.
3. The display panel according to claim 1, wherein the elastic component is arranged around the organic light emitting display.
4. The display panel according to claim 3, wherein the elastic component is arranged at intervals around the organic light emitting display.
5. The display panel according to claim 1, wherein a gap is arranged between the frame sealant and the elastic component.
6. The display panel according to claim 5, wherein an absorbent compound is comprised in the gap.
7. The display panel according to claim 1, wherein the elastic component contacts with the frame sealant.

8. The display panel according to claim 1, wherein the elastic component comprises an absorbent compound.

9. The display panel according to claim 1, wherein the display panel further comprises: an encapsulation layer arranged between the organic light emitting display and the cover plate and completely covering the organic light emitting display.

10. The display panel according to claim 1, wherein a material of the elastic component comprises any one or more of a rubber, an ABS resin or a polysiloxane.

11. The display panel according to claim 6, wherein the absorbent compound comprises any one or more of a calcium oxide, a sodium oxide, a barium oxide, a magnesium oxide, a lithium oxide or a lithium bromide.

12. A display device comprising a display panel, wherein the display panel comprises:

a cover plate;

a base substrate arranged opposite to the cover plate;

an organic light emitting display arranged between the base substrate and the cover plate;

a frame sealant arranged between the base substrate and the cover plate and located around the organic light emitting display;

a filler arranged in a sealing space constituted by the base substrate, the cover plate and the frame sealant; and

an elastic component arranged between the frame sealant and the organic light emitting display.

13. A method for fabricating the display panel according to claim 1, comprising:

providing a base substrate on which an organic light emitting display is formed;

providing a cover plate, fabricating a frame sealant at a position of a frame of the cover plate, and forming an elastic component at an inner side of the frame sealant; filling an area surrounded by the elastic component with a filler;

fitting the base substrate with the cover plate in a vacuum environment, and curing the frame sealant and the filler via an ultraviolet light or heating.

14. The method according to claim 13, wherein after forming the elastic component and before filling the area surrounded by the elastic component with the filler, the method further comprises:

forming an absorbent compound between the elastic component and the frame sealant.

15. The method according to claim 13, wherein when forming the elastic component, the method further comprises:

mixing an absorbent compound in an elastic material for forming the elastic component.

16. The display device according to claim 12, wherein the elastic component contacts with the base substrate and the cover plate.

17. The display device according to claim 12, wherein the elastic component is arranged around the organic light emitting display.

18. The display device according to claim 12, wherein a gap is arranged between the frame sealant and the elastic component.

19. The display device according to claim 12, wherein the elastic component contacts with the frame sealant.

20. The display device according to claim 12, wherein the elastic component comprises an absorbent compound.

* * * * *

专利名称(译)	显示面板，其制造方法和显示装置		
公开(公告)号	US20190207153A1	公开(公告)日	2019-07-04
申请号	US16/089727	申请日	2018-01-26
[标]申请(专利权)人(译)	京东方科技集团股份有限公司		
申请(专利权)人(译)	京东方科技集团股份有限公司.		
当前申请(专利权)人(译)	京东方科技集团股份有限公司.		
[标]发明人	HOU WENJUN		
发明人	HOU, WENJUN		
IPC分类号	H01L51/52 H01L27/32 H01L51/56 B01J20/04		
CPC分类号	H01L51/5246 H01L27/3244 H01L51/5259 H01L51/56 B01J20/041 B01J20/046 H01L2251/303 H01L27/32		
优先权	201710329212.8 2017-05-11 CN		
其他公开文献	US10707440		
外部链接	Espacenet USPTO		

摘要(译)

本发明公开了一种显示面板，其制造方法以及显示装置。显示面板包括：基板和盖板，彼此相对设置，有机发光显示器，设置在基板和盖板之间；框架密封剂，设置在基板和盖板之间，位于有机物周围发光显示器和填料设置在由基础基板，盖板和框架密封剂构成的密封空间中。显示面板还包括：弹性元件，设置在框架密封剂和有机发光显示器之间。

