



US010008677B2

(12) **United States Patent**
Xia et al.

(10) **Patent No.:** **US 10,008,677 B2**
(45) **Date of Patent:** **Jun. 26, 2018**

(54) **MATERIALS FOR ORGANIC LIGHT
EMITTING DIODE**

(71) Applicant: **Universal Display Corporation**,
Ewing, NJ (US)

(72) Inventors: **Chuanjun Xia**, Lawrenceville, NJ
(US); **Bin Ma**, Plainsboro, NJ (US);
David Zenan Li, Princeton, NJ (US);
Bert Alleyne, Newtown, PA (US); **Alan**
DeAngelis, Pennington, NJ (US);
James Fiordeliso, Yardley, PA (US);
Vadim Adamovich, Yardley, PA (US)

(73) Assignee: **UNIVERSAL DISPLAY
CORPORATION**, Ewing, NJ (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 809 days.

(21) Appl. No.: **13/932,546**

(22) Filed: **Jul. 1, 2013**

(65) **Prior Publication Data**

US 2013/0299795 A1 Nov. 14, 2013

Related U.S. Application Data

(63) Continuation-in-part of application No. 13/006,016,
filed on Jan. 13, 2011, now Pat. No. 9,130,177.

(51) **Int. Cl.**
H01L 51/00 (2006.01)
C07F 15/00 (2006.01)

(52) **U.S. Cl.**
CPC **H01L 51/0085** (2013.01); **C07F 15/0033**
(2013.01)

(58) **Field of Classification Search**
CPC H01L 51/0085
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,769,292 A	9/1988	Tang et al.
5,061,569 A	10/1991	VanSlyke et al.
5,247,190 A	9/1993	Friend et al.
5,554,220 A	9/1996	Forrest et al.
5,703,436 A	12/1997	Forrest et al.
5,707,745 A	1/1998	Forrest et al.
5,834,893 A	11/1998	Bulovic et al.
5,844,363 A	12/1998	Gu et al.

(Continued)

FOREIGN PATENT DOCUMENTS

CN	1589307 A	3/2005
DE	102005057963	6/2007

(Continued)

OTHER PUBLICATIONS

Adachi, Chihaya et al., "Organic Electroluminescent Device Having
a Hole Conductor as an Emitting Layer," Appl. Phys. Lett., 55(15):
1489-1491 (1989).

(Continued)


Primary Examiner — Alex A Rolland

(74) *Attorney, Agent, or Firm* — Duane Morris LLP

(57) **ABSTRACT**

Compounds are provided that comprise a ligand having a
5-substituted 2-phenylquinoline. In particular, the 2-phe-
nylquinoline may be substituted with a cycloalkyl contain-
ing group at the 5-position. These compounds may be used
in organic light emitting devices, in particular as red emitters
in the emissive layer of such devices, to provide devices
having improved properties.

23 Claims, 3 Drawing Sheets



Formula III

(56)

References Cited

U.S. PATENT DOCUMENTS

5,929,194	A	7/1999	Woo et al.	
5,986,401	A	11/1999	Thompson et al.	
6,013,982	A	1/2000	Thompson et al.	
6,087,196	A	7/2000	Sturm et al.	
6,091,195	A	7/2000	Forrest et al.	
6,097,147	A	8/2000	Baldo et al.	
6,166,489	A	12/2000	Thompson et al.	
6,294,398	B1	9/2001	Kim et al.	
6,303,238	B1	10/2001	Thompson et al.	
6,337,102	B1	1/2002	Forrest et al.	
6,468,819	B1	10/2002	Kim et al.	
6,528,187	B1	3/2003	Okada	
6,687,266	B1	2/2004	Ma et al.	
6,821,645	B2	11/2004	Igarashi et al.	
6,835,469	B2 *	12/2004	Kwong	C07D 215/04 313/504
6,911,271	B1	6/2005	Lamansky et al.	
6,913,710	B2	7/2005	Farrand et al.	
6,921,915	B2	7/2005	Takiguchi et al.	
6,939,624	B2	9/2005	Lamansky et al.	
6,939,625	B2	9/2005	Marks et al.	
7,001,536	B2	2/2006	Thompson et al.	
7,071,615	B2	7/2006	Lu et al.	
7,084,273	B2	8/2006	Stossel et al.	
7,087,321	B2	8/2006	Kwong et al.	
7,090,928	B2	8/2006	Thompson et al.	
7,094,897	B2	8/2006	Stossel et al.	
7,147,935	B2	12/2006	Kamatani et al.	
7,154,114	B2	12/2006	Brooks et al.	
7,198,859	B2	4/2007	Kwong et al.	
7,250,226	B2	7/2007	Tokito et al.	
7,261,954	B2	8/2007	Thompson et al.	
7,279,704	B2	10/2007	Walters et al.	
7,329,896	B2	2/2008	Tierney et al.	
7,332,232	B2	2/2008	Ma et al.	
7,338,722	B2	3/2008	Thompson et al.	
7,378,162	B2	5/2008	Jeong et al.	
7,393,599	B2	7/2008	Thompson et al.	
7,396,598	B2	7/2008	Takeuchi et al.	
7,429,426	B2	9/2008	Brown et al.	
7,431,968	B1	10/2008	Shtein et al.	
7,445,855	B2	11/2008	Mackenzie et al.	
7,470,928	B2	12/2008	Jeong et al.	
7,534,505	B2	5/2009	Lin et al.	
7,534,853	B2	5/2009	Stossel et al.	
7,560,176	B2	7/2009	Cheng et al.	
7,629,061	B2	12/2009	Gupta et al.	
7,740,957	B2	6/2010	Kim et al.	
7,799,917	B2	9/2010	Samuel et al.	
7,851,072	B2	12/2010	Kwong et al.	
7,883,785	B2	2/2011	Stossel et al.	
8,017,774	B2	9/2011	Kamatani et al.	
8,431,243	B2	4/2013	Kwong et al.	
9,130,177	B2	9/2015	Ma et al.	
2002/0034656	A1	3/2002	Thompson et al.	
2002/0134984	A1	9/2002	Igarashi	
2002/0158242	A1	10/2002	Son et al.	
2003/0059646	A1	3/2003	Kamatani et al.	
2003/0072964	A1	4/2003	Kwong et al.	
2003/0138657	A1	7/2003	Li et al.	
2003/0151042	A1	8/2003	Marks et al.	
2003/0152802	A1	8/2003	Tsuboyama et al.	
2003/0162053	A1	8/2003	Marks et al.	
2003/0175553	A1	9/2003	Thompson et al.	
2003/0230980	A1	12/2003	Forrest et al.	
2004/0036077	A1	2/2004	Ise	
2004/0137267	A1	7/2004	Igarashi et al.	
2004/0137268	A1	7/2004	Igarashi et al.	
2004/0174116	A1	9/2004	Lu et al.	
2005/0025993	A1	2/2005	Thompson et al.	
2005/0112407	A1	5/2005	Ogasawara et al.	
2005/0238919	A1	10/2005	Ogasawara	
2005/0244673	A1	11/2005	Satoh et al.	
2005/0260441	A1	11/2005	Thompson et al.	
2005/0260449	A1	11/2005	Walters et al.	

2006/0008670	A1	1/2006	Lin et al.	
2006/0008671	A1	1/2006	Kwong et al.	
2006/0127696	A1	6/2006	Stossel et al.	
2006/0134459	A1	6/2006	Hou et al.	
2006/0202194	A1	9/2006	Jeong et al.	
2006/0204785	A1	9/2006	Kim et al.	
2006/0228581	A1	10/2006	Seo et al.	
2006/0240279	A1	10/2006	Adamovich et al.	
2006/0251923	A1	11/2006	Lin et al.	
2006/0263635	A1	11/2006	Ise	
2006/0280965	A1	12/2006	Kwong et al.	
2007/0004918	A1	1/2007	Jeong et al.	
2007/0104980	A1	5/2007	Kim et al.	
2007/0190359	A1	8/2007	Knowles et al.	
2007/0224450	A1	9/2007	Kim et al.	
2007/0278936	A1	12/2007	Herron et al.	
2007/0278938	A1	12/2007	Yabunouchi et al.	
2008/0015355	A1	1/2008	Schafer et al.	
2008/0018221	A1	1/2008	Egen et al.	
2008/0106190	A1	5/2008	Yabunouchi et al.	
2008/0124572	A1	5/2008	Mizuki et al.	
2008/0220265	A1	9/2008	Xia et al.	
2008/0261076	A1	10/2008	Kwong et al.	
2008/0297033	A1	12/2008	Knowles et al.	
2009/0008605	A1	1/2009	Kawamura et al.	
2009/0009065	A1	1/2009	Nishimura et al.	
2009/0017330	A1	1/2009	Iwakuma et al.	
2009/0030202	A1	1/2009	Iwakuma et al.	
2009/0039776	A1	2/2009	Yamada et al.	
2009/0045730	A1	2/2009	Nishimura et al.	
2009/0045731	A1	2/2009	Nishimura et al.	
2009/0078317	A1	3/2009	Kim et al.	
2009/0085476	A1	4/2009	Park et al.	
2009/0101870	A1	4/2009	Pakash et al.	
2009/0104472	A1	4/2009	Je et al.	
2009/0108737	A1	4/2009	Kwong et al.	
2009/0115316	A1	5/2009	Zheng et al.	
2009/0153037	A1	6/2009	Kim et al.	
2009/0159130	A1	6/2009	Eum et al.	
2009/0165846	A1	7/2009	Johannes et al.	
2009/0165860	A1	7/2009	Kim et al.	
2009/0167162	A1	7/2009	Lin et al.	
2009/0179554	A1	7/2009	Kuma et al.	
2010/0090591	A1	4/2010	Alleyne et al.	
2012/0153816	A1 *	6/2012	Takizawa	C07D 215/04 313/504
2014/0246656	A1	9/2014	Inoue et al.	

FOREIGN PATENT DOCUMENTS

EP	0650955	5/1995
EP	1239526	9/2002
EP	1348711	10/2003
EP	1725079	11/2006
EP	1783132	5/2007
EP	2034538	3/2009
EP	2055710	5/2009
EP	2080795	7/2009
EP	2085450	8/2009
JP	H09-279136	10/1997
JP	2003073387	3/2003
JP	200511610	1/2005
JP	2007123392	5/2007
JP	2007254297	10/2007
JP	2008074939	4/2008
KR	100662379	1/2007
KR	10-2007-0079009	8/2007
WO	199921935	5/1999
WO	200057676	9/2000
WO	200070655	11/2000
WO	2001039234	5/2001
WO	200141512	6/2001
WO	200159030	8/2001
WO	2002002714	1/2002
WO	200215645	2/2002
WO	2002066552	8/2002
WO	2003033617	4/2003
WO	2003040256	5/2003
WO	2003040257	5/2003

(56) References Cited

FOREIGN PATENT DOCUMENTS

WO	2003060956	7/2003
WO	2004026886	4/2004
WO	2004041962	5/2004
WO	2004093207	10/2004
WO	2004107822	12/2004
WO	2005014551	2/2005
WO	2005019373	3/2005
WO	2005021678	3/2005
WO	2005027583	3/2005
WO	2005030900	4/2005
WO	2005089025	9/2005
WO	2005123873	12/2005
WO	2005124889	12/2005
WO	2006000544	1/2006
WO	2006001150	1/2006
WO	2006009024	1/2006
WO	2006014599	2/2006
WO	2006035997	4/2006
WO	2006056418	6/2006
WO	2006072002	7/2006
WO	2006082742	8/2006
WO	2006098120	9/2006
WO	2006100298	9/2006
WO	2006103874	10/2006
WO	2006114966	11/2006
WO	2006132173	12/2006
WO	2007002683	1/2007
WO	2007004113	1/2007
WO	2007004380	1/2007
WO	2007063754	6/2007
WO	2007063796	6/2007
WO	2008056746	5/2008
WO	2008101842	8/2008
WO	2008109824	9/2008
WO	20080109824	9/2008
WO	2008132085	11/2008
WO	2009000673	12/2008
WO	2009003898	1/2009
WO	2009008311	1/2009
WO	2009018009	2/2009
WO	2009050290	4/2009
WO	2009021126	5/2009
WO	2009062578	5/2009
WO	2009063833	5/2009
WO	2009066778	5/2009
WO	2009066779	5/2009
WO	2009086028	7/2009
WO	2009100991	8/2009
WO	20120148511	11/2012

OTHER PUBLICATIONS

Adachi, Chihaya et al., "Nearly 100% Internal Phosphorescence Efficiency in an Organic Light Emitting Device," *J. Appl. Phys.*, 90(10): 5048-5051 (2001).

Adachi, Chihaya et al., "High-Efficiency Red Electrophosphorescence Devices," *Appl. Phys. Lett.*, 78(11):1622-1624 (2001).

Aonuma, Masaki et al., "Material Design of Hole Transport Materials Capable of Thick-Film Formation in Organic Light Emitting Diodes," *Appl. Phys. Lett.*, 90:183503-1-183503-3.

Baldo et al., "Highly Efficient Phosphorescent Emission from Organic Electroluminescent Devices," *Nature*, vol. 395, 151-154, (1998).

Baldo et al., "Very high-efficiency green organic light-emitting devices based on electrophosphorescence," *Appl. Phys. Lett.*, vol. 75, No. 3, 4-6 (1999).

Gao, Zhiqiang et al., "Bright-Blue Electroluminescence From a Silyl-Substituted ter-(phenylene-vinylene) derivative," *Appl. Phys. Lett.*, 74(6): 865-867 (1999).

Guo, Tzung-Fang et al., "Highly Efficient Electrophosphorescent Polymer Light-Emitting Devices," *Organic Electronics*, 115-20 (2000).

Hamada, Yuji et al., "High Luminance in Organic Electroluminescent Devices with Bis(10-hydroxybenzo[h]quinolinato) beryllium as an Emitter," *Chem. Lett.*, 905-906 (1993).

Holmes, R.J. et al., "Blue Organic Electrophosphorescence Using Exothermic Host-Guest Energy Transfer," *Appl. Phys. Lett.*, 82(15):2422-2424 (2003).

Hu, Nan-Xing et al., "Novel High Tg Hole-Transport Molecules Based on Indolo[3,2-b]carbazoles for Organic Light-Emitting Devices," *Synthetic Metals*, 111-112:421-424 (2000).

Huang, Jinsong et al., "Highly Efficient Red-Emission Polymer Phosphorescent Light-Emitting Diodes Based on Two Novel Tris(1-phenylisoquinolinato-C2,N)iridium(III) Derivates," *Adv. Mater.*, 19:739-743 (2007).

Huang, Wei-Sheng et al., "Highly Phosphorescent Bis-Cyclometalated Iridium Complexes Containing Benzoimidazole-Based Ligands," *Chem. Mater.*, 16(12):2480-2488 (2004).

Hung, L.S. et al., "Anode Modification in Organic Light-Emitting Diodes by Low-Frequency Plasma Polymerization of CHF₃," *Appl. Phys. Lett.*, 78(5):673-675 (2001).

Ikai, Masamichi and Tokito, Shizuo, "Highly Efficient Phosphorescence From Organic Light-Emitting Devices with an Exciton-Block Layer," *Appl. Phys. Lett.*, 79(2):156-158 (2001).

Ikeda, Hisao et al., "P-185 Low-Drive-Voltage OLEDs with a Buffer Layer Having Molybdenum Oxide," *SID Symposium Digest*, 37:923-926 (2006).

Inada, Hiroshi and Shirota, Yasuhiko, "1,3,5-Tris[4-(diphenylamino)phenyl]benzene and its Methylsubstituted Derivatives as a Novel Class of Amorphous Molecular Materials," *J. Mater. Chem.*, 3(3):319-320 (1993).

Kanno, Hiroshi et al., "Highly Efficient and Stable Red Phosphorescent Organic Light-Emitting Device Using bis[2-(2-benzothiazoyl)phenolato]zinc(II) as host material," *Appl. Phys. Lett.*, 90:123509-1-123509-3 (2007).

Kido, Junji et al., "1,2,4-Triazole Derivative as an Electron Transport Layer in Organic Electroluminescent Devices," *Jpn. J. Appl. Phys.*, 32:L917-L920 (1993).

Kuwabara, Yoshiyuki et al., "Thermally Stable Multilayered Organic Electroluminescent Devices Using Novel Starburst Molecules, 4,4',4"-Tri(N-carbazolyl)triphenylamine (TCTA) and 4,4',4"-Tris(3-methylphenylphenyl-amino) triphenylamine (m-MTDATA), as Hole-Transport Materials," *Adv. Mater.*, 6(9):677-679 (1994).

Kwong, Raymond C. et al., "High Operational Stability of Electrophosphorescent Devices," *Appl. Phys. Lett.*, 81(1) 162-164 (2002).

Lamansky, Sergey et al., "Synthesis and Characterization of Phosphorescent Cyclometalated Iridium Complexes," *Inorg. Chem.*, 40(7):1704-1711 (2001).

Lee, Chang-Lyoul et al., "Polymer Phosphorescent Light-Emitting Devices Doped with Tris(2-phenylpyridine) Iridium as a Triplet Emitter," *Appl. Phys. Lett.*, 77(15):2280-2282 (2000).

Lo, Shih-Chun et al., "Blue Phosphorescence from Iridium(III) Complexes at Room Temperature," *Chem. Mater.*, 18(21):5119-5129 (2006).

Ma, Yuguang et al., "Triplet Luminescent Dinuclear-Gold(I) Complex-Based Light-Emitting Diodes with Low Turn-On voltage," *Appl. Phys. Lett.*, 74(10):1361-1363 (1999).

Mi, Bao-Xiu et al., "Thermally Stable Hole-Transporting Material for Organic Light-Emitting Diode an Isoindole Derivative," *Chem. Mater.*, 15(16):3148-3151 (2003).

Nishida, Jun-ichi et al., "Preparation, Characterization, and Electroluminescence Characteristics of α -Diimine-type Platinum(II) Complexes with Perfluorinated Phenyl Groups as Ligands," *Chem. Lett.*, 34(4): 592-593 (2005).

Niu, Yu-Hua et al., "Highly Efficient Electrophosphorescent Devices with Saturated Red Emission from a Neutral Osmium Complex," *Chem. Mater.*, 17(13):3532-3536 (2005).

Noda, Tetsuya and Shirota, Yasuhiko, "5,5'-Bis(dimesitylboryl)-2,2'-bithiophene and 5,5'-Bis(dimesitylboryl)-2,2',2"-terthiophene as a Novel Family of Electron-Transporting Amorphous Molecular Materials," *J. Am. Chem. Soc.*, 120 (37):9714-9715 (1998).

(56)

References Cited

OTHER PUBLICATIONS

- Okumoto, Kenji et al., "Green Fluorescent Organic Light-Emitting Device with External Quantum Efficiency of Nearly 10%," *Appl. Phys. Lett.*, 89:063504-1-063504-3 (2006).
- Palilis, Leonidas C., "High Efficiency Molecular Organic Light-Emitting Diodes Based on Silole Derivatives and Their Exciplexes," *Organic Electronics*, 4:113-121 (2003).
- Paulose, Betty Marie Jennifer S. et al., "First Examples of Alkenyl Pyridines as Organic Ligands for Phosphorescent Iridium Complexes," *Adv. Mater.*, 16(22):2003-2007 (2004).
- Ranjan, Sudhir et al., "Realizing Green Phosphorescent Light-Emitting Materials from Rhenium(I) Pyrazolato Diimine Complexes," *Inorg. Chem.*, 42(4):1248-1255 (2003).
- Sakamoto, Youichi et al., "Synthesis, Characterization, and Electron-Transport Property of Perfluorinated Phenylene Dendrimers," *J. Am. Chem. Soc.*, 122(8):1832-1833 (2000).
- Salbeck, J. et al., "Low Molecular Organic Glasses for Blue Electroluminescence," *Synthetic Metals*, 91209-215 (1997).
- Shirot, Yasuhiko et al., "Starburst Molecules Based on p-Electron Systems as Materials for Organic Electroluminescent Devices," *Journal of Luminescence*, 72-74:985-991 (1997).
- Sotoyama, Wataru et al., "Efficient Organic Light-Emitting Diodes with Phosphorescent Platinum Complexes Containing NCN-Coordinating Tridentate Ligand," *Appl. Phys. Lett.*, 86:153505-1-153505-3 (2005).
- Sun, Yiru and Forrest, Stephen R., "High-Efficiency White Organic Light Emitting Devices with Three Separate Phosphorescent Emission Layers," *Appl. Phys. Lett.*, 91:263503-1-263503-3 (2007).
- T. Östergård et al., "Langmuir-Blodgett Light-Emitting Diodes of Poly(3-Hexylthiophene) Electro-Optical Characteristics Related to Structure," *Synthetic Metals*, 87:171-177 (1997).
- Takizawa, Shin-ya et al., "Phosphorescent Iridium Complexes Based on 2-Phenylimidazo[1,2- α]pyridine Ligands Tuning of Emission Color toward the Blue Region and Application to Polymer Light-Emitting Devices," *Inorg. Chem.*, 46(10):4308-4319 (2007).
- Tang, C.W. and VanSlyke, S.A., "Organic Electroluminescent Diodes," *Appl. Phys. Lett.*, 51(12):913-915 (1987).
- Tung, Yung-Liang et al., "Organic Light-Emitting Diodes Based on Charge-Neutral Ru II Phosphorescent Emitters," *Adv. Mater.*, 17(8):1059-1064 (2005).
- Van Slyke, S. A. et al., "Organic Electroluminescent Devices with Improved Stability," *Appl. Phys. Lett.*, 69 (15):2160-2162 (1996).
- Wang, Y. et al., "Highly Efficient Electroluminescent Materials Based on Fluorinated Organometallic Iridium Compounds," *Appl. Phys. Lett.*, 79(4):449-451 (2001).
- Wong, Keith Man-Chung et al., A Novel Class of Phosphorescent Gold(III) Alkynyl-Based Organic Light-Emitting Devices with Tunable Colour, *Chem. Commun.*, 2906-2908 (2005).
- Wong, Wai-Yeung, "Multifunctional Iridium Complexes Based on Carbazole Modules as Highly Efficient Electrophosphors," *Angew. Chem. Int. Ed.*, 45:7800-7803 (2006).
- International Search Report in related PCT/US2012/020991 application.
- State Intellectual Property Office of the People's Republic of China, Notification and English Version of Chinese Office Action regarding corresponding Chinese Application No. 201210371182.4 dated Jan. 9, 2015, pp. 1-4.
- State Intellectual Property Office of the People's Republic of China, Chinese Search Report and English Abstract regarding corresponding Chinese Application No. 201210371182.4 dated Jan. 9, 2015, pp. 1-4.
- Foreign Office Action dated Mar. 4, 2014 for corresponding Chinese Application No. 201210371182.4.
- Notice of Reasons for Rejection dated Aug. 14, 2014 for corresponding Japanese Application No. 2013-179125.
- Japanese Patent Office, Notification of the First Office Action—English Version of Japanese Office Action regarding corresponding Japanese Application No. 2013-549526 dated Apr. 27, 2015, pp. 1-6.
- Decision of Rejection dated Mar. 28, 2016 for corresponding JP Patent Application No. 2013-549526.
- Burroughes et al., *Nature*, 1990, 347, 539.
- Baldo, et al., *Phys. Rev. B*, 1999, 60, 14422.
- Adachi et al., *Appl. Phys. Lett.* 2000, 77, 904.
- Lamansky et al., *J. Am. Chem. Soc.*, 2001, 123, 4304.
- Cotton and Wilkinson, *Advanced Inorganic Chemistry*, 4th Edition, John Wiley & Sons, New York 1980.
- Shoustikov et al., *IEEE Journal of selected topics in quantum electronics*, 1998, 4, 3.
- Dartnall et al., *Proceedings of the Royal Society of London B*, 1983, 220, 115.
- Gupta et al., *Journal of Photochemistry*, 1985, 30, 173.
- Dolorimetry, Second Edition, Publication CIE Feb. 15, 1986 (ISBN 3-900-734-00-3).
- Miyaura et al., *Chem. Rev.* 1995, 2457.
- Haworth, R. D. et al., *J. Chem. Soc.*, 1948, 777.
- Lepeltier et al., "Tris-Cyclometalated iridium (III) styryl complexes and their saturated analogues; direct functionalization of IR(4-Me-ppy)₃ and hydrogen transfer process," *Organometallics*, 2005, 24(24) p. 6069-6072.
- Jung et al., "Effect of substitution of methyl groups on the luminescence performance of Ir complexes: preparation, structures, electrochemistry, photophysical properties and their applications in organic light-emitting diodes (OLEDs)," *European Journal of Inorganic Chem.*, 2004, 17:3415-3423.
- Yang, et al., "High efficiency mer-iridium complexes for organic light-emitting diodes," *Chem. Comm.*, 2004-19:2232-2233.
- Lo et al., "Green phosphorescent dendrimer for light-emitting diodes," *Adv. Materials* 2002, 14: 975-979.
- Kawa et al., "Enhanced luminescence of lanthanide within lanthanide-cored dendrimer complexes", *Thin Solid Films* 331, (1998) p. 259-263.
- Lupton et al., "Control of electrophosphorescence in conjugated dendrimer light-emitting diodes", *Advanced Functional Materials* 2001, 11, No. 4, p. 287-294.
- U.S. Appl. No. 60/811533, filed Jun. 6, 2006, Ma Bin et al.
- Vang et al., "Polymer Based Tris(2-Phenylpyridine)Iridium Complexes", *Macromolecules*: 39(9): 3140-3146. 2006.
- Takayama et al., "Soluble Polymer Complexes Having AlQ₃-Type Pendant Groups", *Macromolecular Rapid Communications*, 25:1171-1174. 2004.
- Lafolet et al., "Iridium complexes containing p-phenylene units. The influence of the conjugation on the excited state properties", *J. of Materials Chemistry*. 15(12):2820-2828. 2005.
- Bacher et al., Photo-Cross-Linked Triphenylenes as Novel Insoluble Hole Transport Materials in Organic LEDs, *Macromolecules* 32:4551-4557. 1999.
- Bacher et al., "Synthesis and Characterization of Photo-Cross-Linkable Hole-Conducting Polymers". *Macromolecules* 1640-1647, 2005.
- Gellman et al., "New Triarylamine-Containing Polymers as Hole Transport Materials in Organic Light Emitting Diodes: Effect of Polymer Structure and Cross-Linking on Device Characteristics", *Chem. Mater.* 10:1668-1676. 1998.
- Ding et al., "Highly Efficient Green-Emitting Phosphorescent Iridium Dendrimers Based on Carbazole Dendrons", *Adv. Funct. Mater.* 16:575-58. 2006.
- Domercq et al., "Organic Light-Emitting Diodes with Multiple Photocrosslinkable Hole-Transport Layers", *J. of Polymer Science: Part B: Polymer Physics*. 41:2726-2732. 2003.
- Domercq et al., "Photo-Patternable Hole Transport Polymers for Organic Light Emitting Diodes". *Chem. Mater.* 15:1491-1496. 2003.
- Evans et al., "Triplet Energy Back Transfer in Conjugated Polymers with Pendant Phosphorescent Iridium Complexes". *J. Am. Chem. Soc.* 128:6647-6656. 2006.
- Jiang et al., "High Efficiency Electrophosphorescent Fluorene-alt-carbazole Copolymers N-Grafted with Cyclometalated Ir Complexes", *Macromolecules* 38:4072-4080. 2005.
- Jiang et al., "Perfluorocyclobutane-based arylamine Hole-Transporting Materials for Organic and Polymer Light Emitting Diodes", *Adv. Funct. Mater.* 12(11-12): 745-751.

(56)

References Cited

OTHER PUBLICATIONS

- Li et al., "Multifunctional platinum porphyrin dendrimers as emitters in undoped phosphorescent based light emitting devices", *Appl. Phys. Lett.* 89:061125-1-061125-3. 2006.
- Liu et al., "Red Phosphorescent Iridium Complex Containing Carbazole-Functionalized β -Diketone for Highly Efficient Nondoped Organic Light-Emitting Diodes", *Adv. Funct. Mater.* 16:1441-1448. 2006.
- Nuyken et al., "Crosslinkable hole- and electron-transport materials for application in organic light emitting diodes (OLEDs)", *Designed Monomers and Polymers* 5(2): 195-210. 2002.
- Sandee et al., "Solution Processible Conjugated Electrophosphorescent Polymers", *J. Am. Chem. Soc.* 126:7041-7048. 2004.
- Schultz et al., "Enhancement of Phosphorescence of Ir Complexes Bound to Conjugated Polymers: Increasing the Triplet Level of the Main Chain", *Macromolecules* 39:9157-9165. 2006.
- Yong et al., "A multifunctional platinum based triplet emitter for OLED applications", *Organometallics* 24:4079-4082. 2005.
- You et al., "Blue electrophosphorescence from Iridium Complex Covalently Bonded to the Poly (9-dodecyl-3-vinylcarbazole): Suppressed Phase Segregation and Enhanced Energy Transfer", *Macromolecules* 39:349-356. 2006.
- Zhang et al., "Highly Efficient polymer light-emitting diodes using color-tunable carbazole based iridium complexes", *Chem. Phys. Lett.* 422:386-390. 2006.

* cited by examiner




FIG. 1






FIG. 2



Formula I



Formula III

FIG. 3

1

MATERIALS FOR ORGANIC LIGHT EMITTING DIODE

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation-in-part of U.S. patent application Ser. No. 13/006,016, filed on Jan. 13, 2011, the entire contents of which is incorporated herein by reference.

PARTIES TO A JOINT RESEARCH AGREEMENT

The claimed invention was made by, on behalf of, and/or in connection with one or more of the following parties to a joint university corporation research agreement: Regents of the University of Michigan, Princeton University, The University of Southern California, and the Universal Display Corporation. The agreement was in effect on and before the date the claimed invention was made, and the claimed invention was made as a result of activities undertaken within the scope of the agreement.

FIELD OF THE INVENTION

The present invention relates to organic light emitting devices (OLEDs). More specifically, the present invention is related to phosphorescent materials comprising a ligand having 2-phenylquinoline substituted with a cyloalkyl group at the 5-position. These materials may be used in OLEDs to provide devices having improved performance.

BACKGROUND


Opto-electronic devices that make use of organic materials are becoming increasingly desirable for a number of reasons. Many of the materials used to make such devices are relatively inexpensive, so organic opto-electronic devices have the potential for cost advantages over inorganic devices. In addition, the inherent properties of organic materials, such as their flexibility, may make them well suited for particular applications such as fabrication on a flexible substrate. Examples of organic opto-electronic devices include organic light emitting devices (OLEDs), organic phototransistors, organic photovoltaic cells, and organic photodetectors. For OLEDs, the organic materials may have performance advantages over conventional materials. For example, the wavelength at which an organic emissive layer emits light may generally be readily tuned with appropriate dopants.

OLEDs make use of thin organic films that emit light when voltage is applied across the device. OLEDs are becoming an increasingly interesting technology for use in applications such as flat panel displays, illumination, and backlighting. Several OLED materials and configurations are described in U.S. Pat. Nos. 5,844,363, 6,303,238, and 5,707,745, which are incorporated herein by reference in their entirety.

One application for phosphorescent emissive molecules is a full color display. Industry standards for such a display call for pixels adapted to emit particular colors, referred to as "saturated" colors. In particular, these standards call for saturated red, green, and blue pixels. Color may be measured using CIE coordinates, which are well known to the art.

One example of a green emissive molecule is tris(2-phenylpyridine) iridium, denoted Ir(ppy)₃, which has the structure:

2



In this, and later figures herein, we depict the dative bond from nitrogen to metal (here, Ir) as a straight line.

As used herein, the term "organic" includes polymeric materials as well as small molecule organic materials that may be used to fabricate organic opto-electronic devices. "Small molecule" refers to any organic material that is not a polymer, and "small molecules" may actually be quite large. Small molecules may include repeat units in some circumstances. For example, using a long chain alkyl group as a substituent does not remove a molecule from the "small molecule" class. Small molecules may also be incorporated into polymers, for example as a pendent group on a polymer backbone or as a part of the backbone. Small molecules may also serve as the core moiety of a dendrimer, which consists of a series of chemical shells built on the core moiety. The core moiety of a dendrimer may be a fluorescent or phosphorescent small molecule emitter. A dendrimer may be a "small molecule," and it is believed that all dendrimers currently used in the field of OLEDs are small molecules.

As used herein, "top" means furthest away from the substrate, while "bottom" means closest to the substrate. Where a first layer is described as "disposed over" a second layer, the first layer is disposed further away from substrate. There may be other layers between the first and second layer, unless it is specified that the first layer is "in contact with" the second layer. For example, a cathode may be described as "disposed over" an anode, even though there are various organic layers in between.

As used herein, "solution processible" means capable of being dissolved, dispersed, or transported in and/or deposited from a liquid medium, either in solution or suspension form.

A ligand may be referred to as "photoactive" when it is believed that the ligand directly contributes to the photoactive properties of an emissive material. A ligand may be referred to as "ancillary" when it is believed that the ligand does not contribute to the photoactive properties of an emissive material, although an ancillary ligand may alter the properties of a photoactive ligand.

As used herein, and as would be generally understood by one skilled in the art, a first "Highest Occupied Molecular Orbital" (HOMO) or "Lowest Unoccupied Molecular Orbital" (LUMO) energy level is "greater than" or "higher than" a second HOMO or LUMO energy level if the first energy level is closer to the vacuum energy level. Since ionization potentials (IP) are measured as a negative energy relative to a vacuum level, a higher HOMO energy level corresponds to an IP having a smaller absolute value (an IP that is less negative). Similarly, a higher LUMO energy level corresponds to an electron affinity (EA) having a smaller absolute value (an EA that is less negative). On a conventional energy level diagram, with the vacuum level at the top, the LUMO energy level of a material is higher than the HOMO energy level of the same material. A "higher"

3


HOMO or LUMO energy level appears closer to the top of such a diagram than a “lower” HOMO or LUMO energy level.

As used herein, and as would be generally understood by one skilled in the art, a first work function is “greater than” or “higher than” a second work function if the first work function has a higher absolute value. Because work functions are generally measured as negative numbers relative to vacuum level, this means that a “higher” work function is more negative. On a conventional energy level diagram, with the vacuum level at the top, a “higher” work function is illustrated as further away from the vacuum level in the downward direction. Thus, the definitions of HOMO and LUMO energy levels follow a different convention than work functions.

More details on OLEDs, and the definitions described above, can be found in U.S. Pat. No. 7,279,704, which is incorporated herein by reference in its entirety.


SUMMARY OF THE INVENTION

Compounds comprising a 5-substituted 2-phenylquinoline containing ligand are provided. The compounds comprise a ligand L having the formula:



A is a 5-membered or 6-membered carbocyclic or heterocyclic ring. Preferably, A is phenyl. R_A may represent mono, di, tri, or tetra substitutions. Each of R_A is independently selected from the group consisting of hydrogen, deuterium, alkyl, silyl, alkoxy, amino, alkenyl, alkynyl, arylkyl, aryl and heteroaryl. R_B is selected from the group consisting of alkyl having at least 2 carbon atoms, amino, alkenyl, alkynyl, arylkyl, and silyl. The ligand L is coordinated to a metal M having an atomic number greater than 40. Preferably, M is Ir.


In one aspect, the compound has the formula:



L' is an ancillary ligand. m is 1, 2, or 3.


4

In another aspect, L' is a monoanionic bidentate ligand. In yet another aspect, L' is



R_1 , R_2 , and R_3 are independently selected from the group consisting of hydrogen, deuterium, alkyl, alkoxy, amino, alkenyl, alkynyl, arylkyl, aryl and heteroaryl.

In one aspect, the compound has the formula:



wherein R_1 , R_2 , R_3 , R_5 , R_6 and R_7 are independently selected from the group consisting of hydrogen, deuterium, alkyl, silyl, alkoxy, amino, alkenyl, alkynyl, arylkyl, aryl and heteroaryl. R_4 is selected from the group consisting of alkyl having at least 2 carbon atoms, amino, alkenyl, alkynyl, arylkyl, and silyl. m is 1, 2, or 3. Preferably, each of R_1 and R_3 are a branched alkyl with branching at a position further than the α position to the carbonyl group.

In one aspect, each of R_5 , R_6 and R_7 are independently selected from methyl and hydrogen, and at least one of R_5 , R_6 and R_7 is methyl. In another aspect, each of R_5 and R_7 are methyl, and R_6 is hydrogen. In yet another aspect, each of R_5 and R_6 are methyl, and R_7 is hydrogen. In a further aspect, each of R_5 , R_6 and R_7 are methyl.

In one aspect, R_4 is an alkyl group having at least 4 carbon atoms. In another aspect, R_4 is an alkyl group having at least 3 carbon atoms.

Specific, non-limiting examples of the 5-substituted 2-phenylquinoline containing compounds are provided. In one aspect, the compound is selected from the group consisting of Compound 1-Compound 50.

In one aspect, R_4 comprises a cycloalkyl group having at least 4 carbon atoms. Specific, non-limiting examples of the 5-substituted 2-phenylquinoline containing compound having Formula III wherein R_4 comprises a cycloalkyl group having at least 4 carbon atoms is selected from the group consisting of Compound II-1-Compound II-72.


Additionally, a first device comprising an organic light emitting device is provided. The organic light emitting device further comprises an anode, a cathode; and an organic layer, disposed between the anode and the cathode. The organic layer comprises a compound comprising a ligand L having Formula I.

A is a 5-membered or 6-membered carbocyclic or heterocyclic ring. Preferably, A is phenyl. R_A may represent mono, di, tri, or tetra substitutions. Each of R_A is independently selected from the group consisting of hydrogen, alkyl, alkoxy, amino, alkenyl, alkynyl, arylkyl, aryl and heteroaryl. R_B is selected from the group consisting of alkyl having at least 2 carbon atoms, amino, alkenyl, alkynyl, arylkyl, and silyl. The ligand L is coordinated to a metal M having an atomic number greater than 40. Preferably, M is Ir.

Specific, non-limiting examples of devices comprising the compounds are provided. In one aspect, the compound used in the first device is selected from the group consisting of Compound 1-Compound 50.

The various specific aspects discussed above for compounds comprising a ligand L having Formula I are also applicable to a compound comprising a ligand L having Formula I that is used in the first device. In particular, specific aspects of R_A , R_B , A, L', M, m, R_1 , R_2 , R_3 , R_4 , R_5 , R_6 , and R_7 of the compound comprising a ligand L having Formula I discussed above are also applicable to a compound comprising a ligand L having Formula I that is used in a first device.

In one aspect, the organic layer is an emissive layer and the compound is an emissive dopant. In another aspect, the organic layer further comprises a host. In yet another aspect, the host is a metal 8-hydroxyquinolate. Preferably, the host is:



In one aspect, the first device is a consumer product. In another aspect, the first device is an organic light emitting device.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows an organic light emitting device.

FIG. 2 shows an inverted organic light emitting device that does not have a separate electron transport layer.

FIG. 3 shows an exemplary compound comprising a 5-substituted 2-phenylquinoline ligand (top) and a preferred embodiment of the 5-substituted 2-phenylquinoline compound (bottom).

DETAILED DESCRIPTION

Generally, an OLED comprises at least one organic layer disposed between and electrically connected to an anode and a cathode. When a current is applied, the anode injects holes and the cathode injects electrons into the organic layer(s). The injected holes and electrons each migrate toward the oppositely charged electrode. When an electron and hole localize on the same molecule, an "exciton," which is a localized electron-hole pair having an excited energy state, is formed. Light is emitted when the exciton relaxes via a photoemissive mechanism. In some cases, the exciton may be localized on an excimer or an exciplex. Non-radiative mechanisms, such as thermal relaxation, may also occur, but are generally considered undesirable.

The initial OLEDs used emissive molecules that emitted light from their singlet states ("fluorescence") as disclosed, for example, in U.S. Pat. No. 4,769,292, which is incorporated by reference in its entirety. Fluorescent emission generally occurs in a time frame of less than 10 nanoseconds.

More recently, OLEDs having emissive materials that emit light from triplet states ("phosphorescence") have been demonstrated. Baldo et al., "Highly Efficient Phosphorescent Emission from Organic Electroluminescent Devices," *Nature*, vol. 395, 151-154, 1998; ("Baldo-I") and Baldo et al., "Very high-efficiency green organic light-emitting devices based on electrophosphorescence," *Appl. Phys. Lett.*, vol. 75, No. 3, 4-6 (1999) ("Baldo-II"), which are incorporated by reference in their entireties. Phosphorescence is described in more detail in U.S. Pat. No. 7,279,704 at cols. 5-6, which are incorporated by reference.

FIG. 1 shows an organic light emitting device 100. The figures are not necessarily drawn to scale. Device 100 may include a substrate 110, an anode 115, a hole injection layer 120, a hole transport layer 125, an electron blocking layer 130, an emissive layer 135, a hole blocking layer 140, an electron transport layer 145, an electron injection layer 150, a protective layer 155, and a cathode 160. Cathode 160 is a compound cathode having a first conductive layer 162 and a second conductive layer 164. Device 100 may be fabricated by depositing the layers described, in order. The properties and functions of these various layers, as well as example materials, are described in more detail in U.S. Pat. No. 7,279,704 at cols. 6-10, which are incorporated by reference.

More examples for each of these layers are available. For example, a flexible and transparent substrate-anode combination is disclosed in U.S. Pat. No. 5,844,363, which is incorporated by reference in its entirety. An example of a p-doped hole transport layer is m-MTDATA doped with F.sub.4-TCNQ at a molar ratio of 50:1, as disclosed in U.S. Patent Application Publication No. 2003/0230980, which is incorporated by reference in its entirety. Examples of emissive and host materials are disclosed in U.S. Pat. No. 6,303,238 to Thompson et al., which is incorporated by reference in its entirety. An example of an n-doped electron transport layer is BPhen doped with Li at a molar ratio of 1:1, as disclosed in U.S. Patent Application Publication No. 2003/0230980, which is incorporated by reference in its entirety. U.S. Pat. Nos. 5,703,436 and 5,707,745, which are incorporated by reference in their entireties, disclose examples of cathodes including compound cathodes having a thin layer of metal such as Mg:Ag with an overlying transparent, electrically-conductive, sputter-deposited ITO layer. The theory and use of blocking layers is described in more detail in U.S. Pat. No. 6,097,147 and U.S. Patent Application Publication No. 2003/0230980, which are incorporated by reference in their entireties. Examples of injection layers are provided in U.S. Patent Application Publication No. 2004/0174116, which is incorporated by reference in its entirety. A description of protective layers may be found in U.S. Patent Application Publication No. 2004/0174116, which is incorporated by reference in its entirety.

FIG. 2 shows an inverted OLED 200. The device includes a substrate 210, a cathode 215, an emissive layer 220, a hole transport layer 225, and an anode 230. Device 200 may be fabricated by depositing the layers described, in order. Because the most common OLED configuration has a cathode disposed over the anode, and device 200 has cathode 215 disposed under anode 230, device 200 may be referred

to as an “inverted” OLED. Materials similar to those described with respect to device **100** may be used in the corresponding layers of device **200**. FIG. **2** provides one example of how some layers may be omitted from the structure of device **100**.

The simple layered structure illustrated in FIGS. **1** and **2** is provided by way of non-limiting example, and it is understood that embodiments of the invention may be used in connection with a wide variety of other structures. The specific materials and structures described are exemplary in nature, and other materials and structures may be used. Functional OLEDs may be achieved by combining the various layers described in different ways, or layers may be omitted entirely, based on design, performance, and cost factors. Other layers not specifically described may also be included. Materials other than those specifically described may be used. Although many of the examples provided herein describe various layers as comprising a single material, it is understood that combinations of materials, such as a mixture of host and dopant, or more generally a mixture, may be used. Also, the layers may have various sublayers. The names given to the various layers herein are not intended to be strictly limiting. For example, in device **200**, hole transport layer **225** transports holes and injects holes into emissive layer **220**, and may be described as a hole transport layer or a hole injection layer. In one embodiment, an OLED may be described as having an “organic layer” disposed between a cathode and an anode. This organic layer may comprise a single layer, or may further comprise multiple layers of different organic materials as described, for example, with respect to FIGS. **1** and **2**.

Structures and materials not specifically described may also be used, such as OLEDs comprised of polymeric materials (PLEDs) such as disclosed in U.S. Pat. No. 5,247,190 to Friend et al., which is incorporated by reference in its entirety. By way of further example, OLEDs having a single organic layer may be used. OLEDs may be stacked, for example as described in U.S. Pat. No. 5,707,745 to Forrest et al, which is incorporated by reference in its entirety. The OLED structure may deviate from the simple layered structure illustrated in FIGS. **1** and **2**. For example, the substrate may include an angled reflective surface to improve out-coupling, such as a mesa structure as described in U.S. Pat. No. 6,091,195 to Forrest et al., and/or a pit structure as described in U.S. Pat. No. 5,834,893 to Bulovic et al., which are incorporated by reference in their entireties.

Unless otherwise specified, any of the layers of the various embodiments may be deposited by any suitable method. For the organic layers, preferred methods include thermal evaporation, ink-jet, such as described in U.S. Pat. Nos. 6,013,982 and 6,087,196, which are incorporated by reference in their entireties, organic vapor phase deposition (OVPD), such as described in U.S. Pat. No. 6,337,102 to Forrest et al., which is incorporated by reference in its entirety, and deposition by organic vapor jet printing (OVJP), such as described in U.S. patent application Ser. No. 10/233,470, which is incorporated by reference in its entirety. Other suitable deposition methods include spin coating and other solution based processes. Solution based processes are preferably carried out in nitrogen or an inert atmosphere. For the other layers, preferred methods include

thermal evaporation. Preferred patterning methods include deposition through a mask, cold welding such as described in U.S. Pat. Nos. 6,294,398 and 6,468,819, which are incorporated by reference in their entireties, and patterning associated with some of the deposition methods such as ink jet and OVJD. Other methods may also be used. The materials to be deposited may be modified to make them compatible with a particular deposition method. For example, substituents such as alkyl and aryl groups, branched or unbranched, and preferably containing at least 3 carbons, may be used in small molecules to enhance their ability to undergo solution processing. Substituents having 20 carbons or more may be used, and 3-20 carbons is a preferred range. Materials with asymmetric structures may have better solution processability than those having symmetric structures, because asymmetric materials may have a lower tendency to recrystallize. Dendrimer substituents may be used to enhance the ability of small molecules to undergo solution processing.

Devices fabricated in accordance with embodiments of the invention may be incorporated into a wide variety of consumer products, including flat panel displays, computer monitors, televisions, billboards, lights for interior or exterior illumination and/or signaling, heads up displays, fully transparent displays, flexible displays, laser printers, telephones, cell phones, personal digital assistants (PDAs), laptop computers, digital cameras, camcorders, viewfinders, micro-displays, vehicles, a large area wall, theater or stadium screen, or a sign. Various control mechanisms may be used to control devices fabricated in accordance with the present invention, including passive matrix and active matrix. Many of the devices are intended for use in a temperature range comfortable to humans, such as 18 degrees C. to 30 degrees C., and more preferably at room temperature (20-25 degrees C.).


The materials and structures described herein may have applications in devices other than OLEDs. For example, other optoelectronic devices such as organic solar cells and organic photodetectors may employ the materials and structures. More generally, organic devices, such as organic transistors, may employ the materials and structures.

The terms halo, halogen, alkyl, cycloalkyl, alkenyl, alkynyl, arylkyl, heterocyclic group, aryl, aromatic group, and heteroaryl are known to the art, and are defined in U.S. Pat. No. 7,279,704 at cols. 31-32, which are incorporated herein by reference.

Novel organometallic 2-phenylquinoline Ir complexes are provided. In particular, the compounds comprise an alkyl having at least 2 carbon atoms. It is believed that compounds containing a bulky alkyl at the 5-position on the phenylquinoline is novel. In addition, it is believed that the presence of a bulky alkyl at the 5-position may increase efficiency by preventing self-quenching. Notably, placing the bulky alkyl at the 5-position on the 2-phenylquinoline does not shift the emission wavelength or change the color. Therefore, these compounds may provide improved efficiency and maintain saturated red emission. These compounds may be useful in organic light emitting devices, in particular as red emitters in the emissive layer of such devices.


Compounds comprising a 5-substituted 2-phenylquinoline containing ligand are provided. The compounds comprise a ligand L having the formula:

9




A is a 5-membered or 6-membered carbocyclic or heterocyclic ring. Preferably, A is phenyl. R_A may represent mono, di, tri, or tetra substitutions. Each of R_A is independently selected from the group consisting of hydrogen, deuterium, alkyl, silyl, alkoxy, amino, alkenyl, alkynyl, arylkyl, aryl and heteroaryl. These compounds may be fully or partially deuterated. R_B is selected from the group consisting of alkyl having at least 2 carbon atoms, amino, alkenyl, alkynyl, arylkyl, and silyl. The ligand L is coordinated to a metal M having an atomic number greater than 40. Preferably, M is Ir.

In one aspect, the compound has the formula:



L' is an ancillary ligand. m is 1, 2, or 3.

In another aspect, L' is a monoanionic bidentate ligand. In yet another aspect, L' is




R_1 , R_2 , and R_3 are independently selected from the group consisting of hydrogen, deuterium, alkyl, alkoxy, amino, alkenyl, alkynyl, arylkyl, aryl and heteroaryl.

10

In one aspect, the compound has the formula:

Formula I



Formula III

R_1 , R_2 , R_3 , R_5 , R_6 and R_7 are independently selected from the group consisting of hydrogen, deuterium, alkyl, silyl, alkoxy, amino, alkenyl, alkynyl, arylkyl, aryl and heteroaryl. R_4 is selected from the group consisting of alkyl having at least 2 carbon atoms, amino, alkenyl, alkynyl, arylkyl, and silyl. m is 1, 2, or 3.

Preferably, each of R_1 and R_3 are a branched alkyl with branching at a position further than the α position to the carbonyl group. Without being bound by theory, it is believed that a branched alkyl substituent at R_1 and R_3 may provide high device efficiency and stability, and a very narrow emission spectrum.





The placement of substituents on the compound having Formula III may improve efficiency while maintaining a desirable spectrum. In particular, it is believed that substitution on the position ortho to the R_5 next to quinoline with a substituent other than hydrogen, as shown in Formula III, may result in broadening the compound's spectrum. In addition, alkyl substitution on quinoline at the 3-position may broaden the emission spectrum. Alkyl substitution at the 4, 6, or 7-position may slightly blue shift the emission spectrum, thereby making the emission less saturated. Therefore, the substitution pattern of the 5-substituted 2-phenylquinoline compounds described herein may provide highly desirable compound and device characteristics.

In one aspect, each of R_5 , R_6 and R_7 are independently selected from methyl and hydrogen, and at least one of R_5 , R_6 and R_7 is methyl. In another aspect, each of R_5 and R_7 are methyl, and R_6 is hydrogen. In yet another aspect, each of R_5 and R_6 are methyl, and R_7 is hydrogen. In a further aspect, each of R_5 , R_6 and R_7 are methyl.

In one aspect, R_4 is an alkyl group having at least 4 carbon atoms. In another aspect, R_4 is an alkyl group having at least 3 carbon atoms.

Alkyl substitutions may be particularly important because they offer a wide range of tunability in terms of evaporation temperature, solubility, energy levels, device efficiency and narrowness of the emission spectrum. Additionally, alkyl groups can be stable functional groups chemically and in device operation.

Specific, non-limiting examples of the 5-substituted 2-phenylquinoline containing compounds are provided. In one aspect, the compound is selected from the group consisting of:

11**12**

-continued

Compound 1

5

10

15

Compound 2

20

25

30

Compound 3

35

40

45

50


Compound 4

55


60

65


Compound 5




Compound 6



Compound 7




Compound 8



13

-continued

**14**

-continued

Compound 9

Compound 13

Compound 10

Compound 14

Compound 11


Compound 15

Compound 12

Compound 16

15

-continued



Compound 17


16

-continued


5

10

15



Compound 21




Compound 18


20

25

30



Compound 22




Compound 19

35


40

45

50



Compound 23




Compound 20

55

60

65




Compound 24

17


-continued

Compound 25


**18**

-continued


Compound 29




Compound 26




Compound 30




Compound 27




Compound 31



Compound 28




Compound 32



19


-continued



Compound 33


20

-continued




Compound 37

Compound 34




Compound 34




Compound 38

Compound 35




Compound 35




Compound 39

Compound 36




Compound 36



Compound 40

21


-continued



Compound 41


22

-continued




Compound 45


Compound 42




Compound 43




Compound 46



Compound 44




Compound 47



50

Compound 44



Compound 48



55

60


65

23

-continued



In another aspect, R_4 in compound having Formula III comprises a cycloalkyl group having at least 4 carbon atoms. The inventors have discovered that provision of cycloalkyl substituent at 5-position of the 2-phenylquinoline provides further improvement in the phosphorescent characteristics of the compound over linear or branched alkyl group substituents. This improved compound is suitable as red emitters in Phosphorescent OLEDs. Specific, non-limiting examples of the 5-substituted 2-phenylquinoline containing compound having Formula III wherein R_4 comprises a cycloalkyl group having at least 4 carbon atoms is selected from the group consisting of Compound II-1-Compound II-72 shown below.




Compound 49

5

10

15

**24**

-continued


Compound II-2

20

25


30

35



Compound II-3

Compound II-4




Compound II-1

55

60


65



Compound II-5

25


-continued



Compound II-6


26

-continued




Compound II-10


Compound II-7




Compound II-8





Compound II-11



Compound II-9



Compound II-12




Compound II-13


27

-continued


Compound II-14




Compound II-15



Compound II-16






Compound II-17

**28**


-continued

Compound II-18



29


-continued




Compound II-21

30


-continued




Compound II-24




Compound II-22



Compound II-25




Compound II-23




Compound II-26

31
-continued




Compound II-27


32
-continued




Compound II-30




Compound II-28



Compound II-31




Compound II-29



Compound II-32

33


-continued




Compound II-33

34


-continued




Compound II-36




Compound II-34




Compound II-37



Compound II-35



Compound II-38




Compound II-39


35

-continued


Compound II-40




Compound II-41



Compound II-42




Compound II-43


**36**

-continued


Compound II-44



Compound II-45




Compound II-46



50


Compound II-47




37

-continued


Compound II-48




Compound II-49



Compound II-50




Compound II-51

**38**

-continued

Compound II-52



Compound II-53

20

25

30

35

40

45


50

Compound II-54

55


60

65



39


-continued




Compound II-55

40


-continued




Compound II-58




Compound II-56 25



Compound II-59



Compound II-57 50




Compound II-60

41

-continued


Compound II-61




42

-continued


Compound II-64




Compound II-62 25




Compound II-65



Compound II-63




Compound II-66



43


-continued

Compound II-67

**44**



-continued

Compound II-70





Compound II-71

Compound II-68




Compound II-72

Compound II-69




Additionally, a first device comprising an organic light emitting device is provided. The organic light emitting device further comprises an anode, a cathode, and an organic layer, disposed between the anode and the cathode. The organic layer comprises a compound comprising a ligand L having the formula:

45




A is a 5-membered or 6-membered carbocyclic or heterocyclic ring. Preferably, A is phenyl. R_A may represent mono, di, tri, or tetra substitutions. Each of R_A is independently selected from the group consisting of hydrogen, deuterium, alkyl, silyl, alkoxy, amino, alkenyl, alkynyl, arylkyl, aryl and heteroaryl. R_B is selected from the group consisting of alkyl having at least 2 carbon atoms, amino, alkenyl, alkynyl, arylkyl, and silyl. The ligand L is coordinated to a metal M having an atomic number greater than 40. Preferably, M is Ir.

In one aspect, the compound has the formula:



L' is an ancillary ligand. m is 1, 2, or 3.

In one aspect, L' is a monoanionic bidentate ligand. In another aspect, L' is




R_1 , R_2 , and R_3 are independently selected from the group consisting of hydrogen, deuterium, alkyl, alkoxy, amino, alkenyl, alkynyl, arylkyl, aryl and heteroaryl.

46

In one aspect, the compound has the formula:

Formula I




Formula III

R_1 , R_2 , R_3 , R_5 , R_6 and R_7 are independently selected from the group consisting of hydrogen, deuterium, alkyl, silyl, alkoxy, amino, alkenyl, alkynyl, arylkyl, aryl and heteroaryl. R_4 is selected from the group consisting of alkyl having at least 2 carbon atoms, amino, alkenyl, alkynyl, arylkyl, and silyl. m is 1, 2, or 3.

Specific, non-limiting examples of devices comprising the compounds are provided. In one aspect, the first device comprises a compound selected from the group consisting of Compound 1-Compound 50.

In another aspect, the organic layer comprises a compound having Formula III wherein R_4 is a cycloalkyl group having at least 4 carbon atoms. Specific, non-limiting examples of the compound having Formula III wherein R_4 is a cycloalkyl group having at least 4 carbon atoms is selected from the group consisting of Compound II-1-Compound II-72 disclosed herein.

In one aspect, the organic layer is an emissive layer and the compound is an emissive dopant. In another aspect, the organic layer further comprises a host. In yet another aspect, the host is a metal 8-hydroxyquinolate. Preferably, the host is:



In one aspect, the first device is a consumer product. In another aspect, the first device is an organic light emitting device.


55 Combination with Other Materials

The materials described herein as useful for a particular layer in an organic light emitting device may be used in combination with a wide variety of other materials present in the device. For example, emissive dopants disclosed herein may be used in conjunction with a wide variety of hosts, transport layers, blocking layers, injection layers, electrodes and other layers that may be present. The materials described or referred to below are non-limiting examples of materials that may be useful in combination with the compounds disclosed herein, and one of skill in the art can readily consult the literature to identify other materials that may be useful in combination.

HIL/HTL:

A hole injecting/transporting material to be used in embodiments of the present invention is not particularly limited, and any compound may be used as long as the compound is typically used as a hole injecting/transporting material. Examples of the material include, but are not limited to: a phthalocyanine or porphyrin derivative; an aromatic amine derivative; an indolocarbazole derivative; a polymer containing fluorohydrocarbon; a polymer with conductivity dopants; a conducting polymer, such as PEDOT/PSS; a self-assembly monomer derived from compounds such as phosphonic acid and silane derivatives; a metal oxide derivative, such as MoO_3 ; a p-type semiconducting organic compound, such as 1,4,5,8,9,12-Hexaazatriphenylenehexacarbonitrile; a metal complex, and a cross-linkable compounds.


Examples of aromatic amine derivatives used in the HIL or HTL include, but are not limited to, the following general structures:



Each of Ar^1 to Ar^9 is selected from the group consisting of aromatic hydrocarbon cyclic compounds such as benzene, biphenyl, triphenyl, triphenylene, naphthalene, anthracene, phenylene, phenanthrene, fluorene, pyrene, chrysene, perylene, azulene; group consisting of aromatic heterocyclic compounds such as dibenzothiophene, dibenzofuran, dibenzoselenophene, furan, thiophene, benzofuran, benzothio-
 phene, benzoselenophene, carbazole, indolocarbazole, pyridylindole, pyrrolidopyridine, pyrazole, imidazole, triazole, oxazole, thiazole, oxadiazole, oxatriazole, dioxazole, thiadiazole, pyridine, pyridazine, pyrimidine, pyrazine, triazine, oxazine, oxathiazine, oxadiazine, indole, benzimidazole, indazole, indoxazine, benzoxazole, benzisoxazole, benzothiazole, quinoline, isoquinoline, cinnoline, quinazoline, quinoxaline, naphthyridine, phthalazine, pteridine, xanthene, acridine, phenazine, phenothiazine, phenoxazine, benzofurofuran, furodipyrindine, benzothienopyridine, thienodipyrindine, benzoselenophenopyridine, and selenophenodipyrindine; and group consisting of 2 to 10 cyclic structural units which are groups of the same type or different types selected from the aromatic hydrocarbon cyclic group and the aromatic heterocyclic group and are bonded to each other directly or via at least one of oxygen atom, nitrogen atom, sulfur atom, silicon atom, phosphorus atom, boron


atom, chain structural unit and the aliphatic cyclic group. Wherein each Ar is further substituted by a substituent selected from the group consisting of hydrogen, deuterium, alkyl, alkoxy, amino, alkenyl, alkynyl, arylalkyl, heteroalkyl, aryl and heteroaryl.

In one aspect, Ar^1 to Ar^9 is independently selected from the group consisting of:



k is an integer from 1 to 20; X^1 to X^8 is CH or N; Ar^1 has the same group defined above.

Examples of metal complexes used in the HIL or HTL include, but are not limited to, the following general formula:



M is a metal, having an atomic weight greater than 40; (Y^1-Y^2) is a bidentate ligand, Y^1 and Y^2 are independently selected from C, N, O, P, and S; L is an ancillary ligand; m is an integer value from 1 to the maximum number of ligands that may be attached to the metal; and $m+n$ is the maximum number of ligands that may be attached to the metal.

In one aspect, (Y^1-Y^2) is a 2-phenylpyridine derivative. In another aspect, (Y^1-Y^2) is a carbene ligand.

In another aspect, M is selected from Ir, Pt, Os, and Zn.

In a further aspect, the metal complex has a smallest oxidation potential in solution vs. Fc^+/Fc couple less than about 0.6 V.


Host:

The light emitting layer of the organic EL device in some embodiments the present invention preferably contains at

49


least a metal complex as light emitting material, and may contain a host material using the metal complex as a dopant material. Examples of the host material are not particularly limited, and any metal complexes or organic compounds may be used as long as the triplet energy of the host is larger than that of the dopant.

Examples of metal complexes used as hosts are preferred to have the following general formula:



M is a metal; (Y³—Y⁴) is a bidentate ligand, Y³ and Y⁴ are independently selected from C, N, O, P, and S; L is an ancillary ligand; m is an integer value from 1 to the maximum number of ligands that may be attached to the metal; and m+n is the maximum number of ligands that may be attached to the metal.

In one aspect, the metal complexes are:



(O—N) is a bidentate ligand, having metal coordinated to atoms O and N.


In another aspect, M is selected from Ir and Pt.

In a further aspect, (Y³—Y⁴) is a carbene ligand.

Examples of organic compounds used as hosts are selected from the group consisting aromatic hydrocarbon cyclic compounds such as benzene, biphenyl, triphenyl, triphenylene, naphthalene, anthracene, phenalene, phenanthrene, fluorene, pyrene, chrysene, perylene, azulene; group consisting aromatic heterocyclic compounds such as dibenzothiophene, dibenzofuran, dibenzoselenophene, furan, thiophene, benzofuran, benzothiophene, benzoselenophene, carbazole, indolocarbazole, pyridylindole, pyrrolodipyridine, pyrazole, imidazole, triazole, oxazole, thiazole, oxadiazole, oxatriazole, dioxazole, thiadiazole, pyridine, pyridazine, pyrimidine, pyrazine, triazine, oxazine, oxathiazine, indole, benzimidazole, indazole, indoxazine, benzoxazole, benzisoxazole, benzothiazole, quinoxaline, isoquinoline, cinnoline, quinazoline, quinoxaline, naphthyridine, phthalazine, pteridine, xanthene, acridine, phenazine, phenothiazine, phenoxazine, benzofuopyridine, furodipyridine, benzothienopyridine, thienodipyridine, benzoselenophenopyridine, and selenophenodipyridine; and group consisting 2 to 10 cyclic structural units which are groups of the same type or different types selected from the aromatic hydrocarbon cyclic group and the aromatic heterocyclic group and are bonded to each other directly or via at least one of oxygen atom, nitrogen atom, sulfur atom, silicon atom, phosphorus atom, boron atom, chain structural unit and the aliphatic cyclic group. Wherein each group is further substituted by a substituent selected from the group consisting of hydrogen, deuterium, alkyl, alkoxy, amino, alkenyl, alkynyl, arylalkyl, heteroalkyl, aryl and heteroaryl.

50

In one aspect, the host compound contains at least one of the following groups in the molecule:



R¹ to R⁷ is independently selected from the group consisting of hydrogen, deuterium, alkyl, alkoxy, amino, alk-

51

enyl, alkynyl, arylalkyl, heteroalkyl, aryl and heteroaryl, when it is aryl or heteroaryl, it has the similar definition as Ar's mentioned above.

k is an integer from 0 to 20.


X¹ to X⁸ is selected from CH or N.

HBL:

A hole blocking layer (HBL) may be used to reduce the number of holes and/or excitons that leave the emissive layer. The presence of such a blocking layer in a device may result in substantially higher efficiencies as compared to a similar device lacking a blocking layer. Also, a blocking layer may be used to confine emission to a desired region of an OLED.

In one aspect, the compound used in the HBL contains the same molecule used as host described above.

In another aspect, the compound used in the HBL contains at least one of the following groups in the molecule:




k is an integer from 0 to 20; L is an ancillary ligand, m is an integer from 1 to 3.

ETL:


Electron transport layer (ETL) may include a material capable of transporting electrons. Electron transport layer may be intrinsic (undoped), or doped. Doping may be used to enhance conductivity. Examples of the ETL material are not particularly limited, and any metal complexes or organic compounds may be used as long as they are typically used to transport electrons.

In one aspect, the compound used in the ETL contains at least one of the following groups in the molecule:



52

-continued




R¹ is selected from the group consisting of hydrogen, deuterium, alkyl, alkoxy, amino, alkenyl, alkynyl, arylalkyl, heteroalkyl, aryl and heteroaryl, when it is aryl or heteroaryl, it has the similar definition as Ar's mentioned above.

Ar¹ to Ar⁹ has the similar definition as Ar's mentioned above.

k is an integer from 0 to 20.

X¹ to X⁸ is selected from CH or N.

In another aspect, the metal complexes used in the ETL contain, but are not limited to, the following general formula:



(O—N) or (N—N) is a bidentate ligand, having metal coordinated to atoms O, N or N,N; L is an ancillary ligand; m is an integer value from 1 to the maximum number of ligands that may be attached to the metal.

In any above-mentioned compounds used in each layer of OLED device, the hydrogen atoms can be partially or fully deuterated.

In addition to and/or in combination with the materials disclosed herein, many hole injection materials, hole transporting materials, host materials, dopant materials, exciton/hole blocking layer materials, electron transporting and electron injecting materials may be used in an OLED. Non-limiting examples of the materials that may be used in an OLED in combination with materials disclosed herein are listed in Table 1 below. Table 1 lists non-limiting classes of materials, non-limiting examples of compounds for each class, and references that disclose the materials.

TABLE 1





MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
Hole injection materials		
Phthalocyanine and porphyrin compounds		Appl. Phys. Lett. 69, 2160 (1996)
Starburst triaryl amines		J. Lumin. 72-74, 985 (1997)
CF _x Fluorohydrocarbon polymer	$\text{---}[\text{CH}_2\text{F}_y]_n\text{---}$	Appl. Phys. Lett. 78, 673 (2001)
Conducting polymers (e.g., PEDOT:PSS, polyaniline, polythiophene)		Synth. Met. 87, 171 (1997) WO2007002683
Phosphonic acid and silane SAMs		US20030162053

TABLE 1-continued





MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
Triarylamine or polythiophene polymers with conductivity dopants		EA01725079A1
	and	
		
		
Arylamines complexed with metal oxides such as molybdenum and tungsten oxides	 + MoO _x	SID Symposium Digest, 37, 923 (2006) WO2009018009

TABLE 1-continued






MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
Semiconducting organic complexes		US20020158242
Metal organometallic complexes		US20060240279
Cross-linkable compounds		US20080220265
Hole transporting materials		
Triarylaminines (e.g., TPD, -NPD)		Appl. Phys. Lett. 51, 913 (1987)
		US5061569

TABLE 1-continued




MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
		EP650955
		J. Mater. Chem. 3, 319 (1993)
		Appl. Phys. Lett. 90, 183503 (2007)

TABLE 1-continued




MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
Triarylamine on spirofluorene core		Appl. Phys. Lett. 90, 183503 (2007)
Arylamine carbazole compounds		Adv. Mater. 6, 677 (1994), US20080124572
Triarylamine with (di)benzothiophene/(di)benzofuran		US20070278938, US20080106190

TABLE 1-continued





MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
Indolocarbazoles		Synth. Met. 111, 421 (2000)
Isoindole compounds		Chem. Mater. 15, 3148 (2003)
Metal carbene complexes		US20080018221
Phosphorescent OLED host materials		
Red hosts		
Arylcarbazoles		Appl. Phys. Lett. 78, 1622 (2001)

TABLE 1-continued








MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
Metal 8-hydroxyquinolates (e.g., Alq ₃ , BAlq)		Nature 395, 151 (1998)
		US20060202194
		WO2005014551
		WO2006072002
Metal phenoxybenzothiazole compounds		Appl. Phys. Lett. 90, 123509 (2007)
Conjugated oligomers and polymers (e.g., polyfluorene)		Org. Electron. 1, 15 (2000)
Aromatic fused rings		WO2009066779, WO2009066778, WO2009063833, US20090045731, US20090045730, WO2009008311, US2009008605, US2009009065

TABLE 1-continued






MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
Zinc complexes		WO2009062578
Green hosts		
Arylcarbazoles		Appl. Phys. Lett. 78, 1622 (2001)
		US20030175553
		WO2001039234
Aryltriphenylene compounds		US20060280965

TABLE 1-continued






MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
		US20060280965
		WO2009021126
Donor acceptor type molecules		WO2008056746
Aza-carbazole/DBT/DBF		JP2008074939
Polymers (e.g., PVK)		Appl. Phys. Lett. 77, 2280 (2000)

TABLE 1-continued






MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
Spirofluorene compounds		WO2004093207
Metal phenoxybenzoxazole compounds		WO2005089025
		WO2006132173
		JP200511610
Spirofluorene-carbazole compounds		JP2007254297

TABLE 1-continued






MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
Indolocarbazoles		JP2007254297
5-member ring electron deficient heterocycles (e.g., triazole, oxadiazole)		WO2007063796
5-member ring electron deficient heterocycles (e.g., triazole, oxadiazole)		WO2007063754
5-member ring electron deficient heterocycles (e.g., triazole, oxadiazole)		J. Appl. Phys. 90, 5048 (2001)
5-member ring electron deficient heterocycles (e.g., triazole, oxadiazole)		WO2004107822

TABLE 1-continued






MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
Tetraphenylene complexes		US20050112407
Metal phenoxypyridine compounds		WO2005030900
Metal coordination complexes (e.g., Zn, Al with N ^ N ligands)		US20040137268, US20040137267
Blues hosts		
Arylcarbazoles		Appl. Phys. Lett, 82, 2422 (2003)
		US20070190359

TABLE 1-continued







MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
Dibenzothiophene/Dibenzo- furan-carbazole compounds		WO2006114966, US20090167162
		US20090167162
		WO2009086028
		US20090030202, US20090017330
Silicon aryl compounds		US20050238919
		WO2009003898

TABLE 1-continued






MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
Silicon/Germanium aryl compounds		EP2034538A
Aryl benzoyl ester		WO2006100298
High triplet metal organometallic complex		US7154114
	Phosphorescent dopants Red dopants	
Heavy metal porphyrins (e.g., PtOEP)		Nature 395, 151 (1998)
Iridium(III) organometallic complexes		Appl. Phys. Lett. 78, 1622 (2001)

TABLE 1-continued






MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
		US2006835469
		US2006835469
		US20060202194
		US2006020194
		US20070087321

TABLE 1-continued






MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
		US20070087321
		Adv. Mater. 19, 739 (2007)
		WO2009100991
		WO2008101842
Platinum(II) organometallic complexes		WO2003040257

TABLE 1-continued






MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
Osmium(III) complexes		Chem. Mater. 17, 3532 (2005)
Ruthenium(II) complexes		Adv. Mater. 17, 1059 (2005)
Rhenium (I), (II), and (III) complexes		US20050244673
Green dopants		
Iridium(III) organometallic complexes	 and its derivative 	Inorg. Chem. 40, 1704 (2001) US20020034656

TABLE 1-continued





MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
		US7332232
		US20090108737
		US20090039776
		US6921915

TABLE 1-continued






MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
		US6687266
		Chem. Mater. 16, 2480 (2004)
		US20070190359
		US20060008670 JP2007123392
		Adv. Mater. 16, 2003 (2004)

TABLE 1-continued






MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
		Agnew. Chem. Int. Ed. 2006, 45, 7800
		WO2009050290
		US20090165846
		US20080015355
Monomer for polymeric metal organometallic compounds		US7250226, US7396598

TABLE 1-continued






MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
Pt(II) organometallic complexes, including polydenated ligands		Appl. Phys. Lett. 86, 153505 (2005)
		Appl. Phys. Lett. 86, 153505 (2005)
		Chem. Lett. 34, 592 (2005)
		WO2002015645
		US20060263635

TABLE 1-continued





MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
Cu complexes		WO2009000673
Gold complexes		Chem. Commun. 2906 (2005)
Rhenium(III) complexes		Inorg. Chem. 42, 1248 (2003)
Deuterated organometallic complexes		US20030138657

TABLE 1-continued






MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
Organometallic complexes with two or more metal centers		US210030152802
		US7090928
	Blue dopants	
Iridium(III) organometallic complexes		WO2002002714
		WO2006009024
		US20060251923

TABLE 1-continued







MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
		US7393599, WO2006056418, US20050260441, WO2005019373
		US7354505
		US7445855
		US20070190359, US20080297033
		US7338722
		US20020134984

TABLE 1-continued







MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
		Agnew. Chem. Int. Ed. 47, 1 (2008)
		Chem. Mater. 18, 5119 (2006)
		Inorg. Chem. 46, 4308 (2007)
		WO2005132873
		WO2005123873
		WO2007004380

TABLE 1-continued






MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
Osmium(II) complexes	  	WO2006082742 US7279704 Organometallics 23, 3745 (2004)
Gold complexes		Appl. Phys. Lett. 74, 1361 (1999)
Platinum(II) complexes		WO2006098120, WO2006103874

TABLE 1-continued

MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
Exciton/hole blocking layer materials		
Bathocurpine compounds (e.g., BCP, BPhen)	The structure shows a central triazine ring with two phenyl groups at the 2 and 4 positions and two methyl groups at the 6 and 8 positions.	Appl. Phys. Lett. 75, 4 (1999)
	The structure shows a central benzene ring with two phenyl groups at the 1 and 3 positions and two phenyl groups at the 4 and 6 positions.	Appl. Phys. Lett. 79, 449 (2001)
Metal 8-hydroxyquinolates (e.g., BAlq)	The structure shows an aluminum atom coordinated to three 8-quinolinolato ligands, which are represented as a quinoline ring with an oxygen atom at the 8-position, all enclosed in brackets with a subscript 2.	Appl. Phys. Lett. 81, 162 (2002)
5-member ring electron deficient heterocycles, such as triazole, oxadiazole, imidazole, benzoimidazole	The structure shows a central benzene ring with two triazole rings at the 1 and 3 positions, each substituted with a phenyl group.	Appl. Phys. Lett. 81, 162 (2002)
Triphenylene compounds	The structure shows a central triphenylene core with four phenyl groups at the 1, 3, 9, and 10 positions.	US20050025993

TABLE 1-continued




MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
Fluorinated aromatic compounds		Appl. Phys. Lett. 79, 156 (2001)
Phenothiazine-S-oxide		WO2008132085
Electron transporting materials		
Anthracene-benzimidazole compounds		WO2003060956

TABLE 1-continued







MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
		US20090179554
Aza triphenylene derivatives		US20090115316
Anthracene-benzothiazole compounds		Appl. Phys. Lett. 89, 063504 (2006)
Metal 8-hydroxyquinolates (e.g., Alq ₃ , Zrqq ₄)		Appl. Phys. Lett. 51, 913 (1987) US7230107
Metal hydroxybenzoquinolates		Chem. Lett. 5, 905 (1993)
Bathocuprine compounds such as BCP, BPhen, etc		Appl. Phys. Lett. 91, 263503 (2007)

TABLE 1-continued











MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
5-member ring electron deficient heterocycles (e.g., triazole, oxadiazole, imidazole, benzoimidazole)		Appl. Phys. Lett. 79, 449 (2001)
		Appl. Phys. Lett. 74, 865 (1999)
		Appl. Phys. Lett. 55, 1489 (1989)
Silole compounds		Jpn. J. Apply. Phys. 32, L917 (1993)
		Org. Electron. 4, 113 (2003)
Arylborane compounds		J. Am. Chem. Soc. 120, 9714 (1998)

TABLE 1-continued

MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
Fluorinated aromatic compounds		J. Am. Chem. Soc. 122, 1832 (2000)
Fullerene (e.g., C60)		US20090101870
Triazine complexes		US20040036077
Zn (N ^ N) complexes		US6528187


EXPERIMENTAL

50

Synthesis of (2-amino-6-chlorophenyl)methanol

Compound Examples

Example 1. Synthesis of Compound 1




55

60

65

2-Amino-6-chlorobenzoic acid (25.0 g, 143 mmol) was dissolved in 120 mL of anhydrous THF in a 500 mL 2 neck round bottom flask. The solution was cooled in an ice-water bath. 215 mL of 1.0 M lithium aluminum hydride (LAH) THF solution was then added dropwise. After all of the LAH was added, the reaction mixture was allowed to warm up to room temperature and then stirred at room temperature overnight. ~10 mL of water was added to the reaction mixture followed by 7 g 15% NaOH. An additional 20 g of water was added to the reaction mixture. The organic THF phase was decanted and ~200 mL of ethyl acetate was added to the solid with stirring. Na₂SO₄ was added as a drying agent to the combined ethyl acetate organic portion and THF portion. The mixture was filtered and evaporated. ~20 g yellow solid was obtained and taken on to the next step without further purification.




Synthesis of
5-chloro-2-(3,5-dimethylphenyl)quinoline


(2-Amino-6-chlorophenyl)methanol (16 g, 102 mmol), 3,5-dimethylacetophenone (22.6 g, 152 mmol), $\text{RuCl}_2(\text{PPh}_3)_3$ (0.973 g, 1.015 mmol), and KOH (10.25 g, 183 mmol) were refluxed in 270 mL of toluene for 18 h. Water was collected from the reaction using a Dean-stark trap. The reaction mixture was allowed to cool to room temperature, filtered through a silica gel plug and eluted with 5% ethyl acetate in hexanes. The product was further purified by

116

Kugelrohr distillation to give 23.5 g of crude product, which was crystallized from 60 mL of MeOH to give 8.6 g (32% yield) of the desired product.



5-Chloro-2-(3,5-dimethylphenyl)quinoline (4.3 g, 16.06 mmol), isobutylboronic acid (3.2 g, 31.4 mmol), dicyclohexyl(2',6'-dimethoxy-[1,1'-biphenyl]-2-yl)phosphine (0.538 g, 1.31 mmol), and potassium phosphate monohydrate (18.3 g, 79 mmol) were mixed in 114 mL of toluene. The system was degassed for 20 minutes. $\text{Pd}_2(\text{dba})_3$ was then added and the system was refluxed overnight. After cooling to room temperature, the reaction mixture was filtered through a Celite® plug and eluted with dichloromethane. The product was further purified by a Kugelrohr distillation and then further purified by column chromatography using 5% ethyl acetate in hexanes. This was followed by another Kugelrohr distillation to give 3.2 g (72% yield) of product.





117

Synthesis of Iridium Dimer.

A mixture of 2-(3,5-dimethylphenyl)-5-isobutylquinoline (3.2 g, 11.06 mmol), $\text{IrCl}_3 \cdot 4\text{H}_2\text{O}$ (1.79 g, 4.83 mmol), 2-ethoxyethanol (45 mL) and water (105 mL) was refluxed

118

under nitrogen overnight. The reaction mixture was filtered and washed with MeOH (3×10 mL). ~2.9 g of dimer was obtained after vacuum drying. The dimer was used for the next step without further purification.




119

Synthesis of Compound 1.

Dimer (2.9 g, 1.80 mmol), pentane-2,4-dione (1.80 g, 18.02 mmol), K_2CO_3 (2.49 g, 18.02 mmol) and 2-ethoxyethanol (22 mL) were stirred at room temperature for 24 h. The precipitate was filtered and washed with methanol. The solid was further purified by passing it through a silica gel plug (that was pretreated with 15% triethylamine (TEA) in hexanes and eluted with methylene chloride. 2-Propanol was added to the filtrate. The filtrate was concentrated, but not to dryness. 1.6 g of product was obtained after filtration. The solid was sublimed twice under high vacuum at 240° C. to give 1.0 g (64%) of Compound 1.

Synthesis of Compound II-2


Synthesis of
5-cyclopentyl-2-(3,5-dimethylphenyl)quinoline

5-Chloro-2-(3,5-dimethylphenyl)quinoline (14.0 g, 52.3 mmol) and [1,3-bis(diphenylphosphino)propane]-dichloronickel (II) (0.10 g, 0.19 mmol) were dissolved in 250 mL of anhydrous diethyl ether under N_2 atm. The reaction mixture was degassed and solution of cyclopentylmagnesium iodide

120

(2 M solution in ether, 52 mL, 105 mmol) was added dropwise. The reaction mixture was stirred for 1 h, quenched with 20% aq. solution of ammonium chloride and extracted with ethyl acetate. The organic solution was dried over sodium sulfate, filtered and evaporated, providing yellow solid. Purification with column chromatography on silica gel, eluted with hexane/ethyl acetate 9/1 (v/v) mixture followed by crystallization from heptanes provided 5-cyclopentyl-2-(3,5-dimethylphenyl)quinoline as colorless crystals (12 g, 76% yield).


Synthesis of Ir(III) Dimer



5-Cyclopentyl-2-(3,5-dimethylphenyl)quinoline (3.56 g, 11.8 mmol) and iridium(III) chloride trihydrate (1.30 g, 3.69 mmol) were dissolved in the mixture of ethoxyethanol (90 mL) and water (30 mL). Reaction mixture was degassed and heated to 105° C. for 24 h. The reaction mixture was then cooled down to room temperature and filtered through filter paper. The filtrate was washed with methanol and dried in vacuum, providing iridium complex dimer as dark solid 1.60 g (54% yield).

121

Synthesis of Compound II-2



122

Iridium complex dimer (2.17 g, 1.31 mmol), acetylacetonate (1.31 g, 13.1 mmol) and potassium carbonate (1.81 g, 13.1 mmol) were suspended in 70 mL of ethoxyethanol, and stirred overnight under N₂ at room temperature. The reaction mixture was then filtered through a pad of Celite®, washed with MeOH. Most of the red material was solubilized and passed through the Celite®. The Celite® was suspended in DCM, containing 10% of triethylamine and this suspension was combined with filtrate and evaporated. The residue was purified by column chromatography on silica gel, pre-treated with Et₃N, eluted with hexane/dichloromethane mixture, providing a dark red solid. The product was further purified by recrystallizing from dichloromethane and isopropanol mixture to give desired product (1.67 g, 72% yield).


Device Examples

All example devices were fabricated by high vacuum (<10⁻⁷ Torr) thermal evaporation. The anode electrode is 1200 Å of indium tin oxide (ITO). The cathode consisted of 10 Å of LiF followed by 1000 Å of Al. All devices are encapsulated with a glass lid sealed with an epoxy resin in a nitrogen glove box (<1 ppm of H₂O and O₂) immediately after fabrication, and a moisture getter was incorporated inside the package.


The organic stack of the device examples consisted of sequentially, from the 1200 Å ITO surface, 100 Å of Compound A as the hole injection layer (HIL), 400 Å of 4,4'-bis[N-(1-naphthyl)-N-phenylamino]biphenyl (α-NPD) as the hole transporting layer (HTL), 300 Å of the 7 wt % invention compound doped into BAQ host as the emissive layer (EML), 550 Å of Alq₃ (tris-8-hydroxyquinoline aluminum) as the ETL.

Comparative Examples were fabricated similarly to the Device Examples except that Compound B, C or D was used as the emitter in the EML.

As used herein, the following compounds have the following structures:




Compound A



Compound B

123

-continued



Compound C

Compound D

124

the same as the FWHM of Compound C (58 nm). The color saturation (CIE) of Compound 1 and Compound B are also the same. These results indicate that Compound 1 is a more efficient red emitter than Compounds B, C and D with a desirable narrower FWHM.

Compound 1 also has almost a double lifetime at room temperature compared to Compound D. The only difference between these two compounds is that Compound 1 has a bulkier group at 5-position. This clearly indicates that a bulkier group than methyl in the 5-position of 2-phenylquinoline may indeed provide a significant improvement in overall device performance.

Additional Device Examples

Additional device examples were fabricated to evaluate the compound having Formula III wherein R₄ comprises a cycloalkyl group. These additional example devices were fabricated by high vacuum (<10⁻⁷ Torr) thermal evaporation. The anode electrode is 1200 Å of ITO. The cathode consisted of 10 Å of LiF followed by 1,000 Å of Al. All devices are encapsulated with a glass lid sealed with an epoxy resin in a nitrogen glove box (<1 ppm of H₂O and O₂) immediately after fabrication, and a moisture getter was incorporated inside the package.

The organic stack of the additional device examples consisted of sequentially, from the ITO surface, 100 Å of Compound A as the HIL, 400 Å of 4,4'-bis[N-(1-naphthyl)-N-phenylamino]biphenyl (α-NPD) as the HTL, 300 Å of the

Particular emissive dopants for the emissive layer of an OLED are provided. These compounds may lead to devices having particularly good properties.

The device structures and device data are summarized in Table 2.

TABLE 2

Emitter	1931 CIE		λ_{max} [nm]	FWHM [nm]	V [V]	At 1,000 nits				At 40 mA/cm ²		
	x	y				L ₀ [nits]	RT	70° C.	LT _{80%} [h]			
Compound 1 (Device Example)	0.665	0.331	622	58	7.8	22.2	20.5	9.0	1.08	6,852	600	66
Compound B (Comparative Example)	0.667	0.331	622	62	8.1	19.9	18.8	7.7	1.06	6,447	878	70
Compound C (Comparative Example)	0.662	0.335	620	58	7.4	21.9	18.9	9.3	1.16	6,927	565	73
Compound D (Comparative Example)	0.664	0.334	620	64	8.1	21.1	19.4	8.1	1.09	6,666	321	44

As seen from the Table 2, the EQE of Compound 1 at 1000 nits is up to 10% higher than Compounds B, C, and D. Additionally, the EL spectral full width at half maximum (FWHW) of Compound 1 (58 nm) is also narrower than Compound B (62 nm) and Compound D (64 nm), which is a desirable device property. The FWHM of Compound 1 is

invention compound doped in Balq as host with 6 wt % of an Ir phosphorescent compound as the EML, 550 Å of Alq₃ (tris-8-hydroxyquinoline aluminum) as the ETL.

The device structures and device data from the additional device examples are summarized in Table 3 below.

TABLE 3

Emitter	Alq	1931 CIE		λ max	FWHM	At 1000 nits						
		x	y			[nm]	[nm]	Volt	LE	EQE	PE	cd/Aper
	[Å]			[nm]	[nm]	[V]	[cd/A]	[%]	[lm/W]	EQE		
Compound II-2	550 Å	0.662	0.335	620	60	8.3	23.2	20.4	8.8	1.1		


125

As can be seen from Table 3, the example device with Compound II-2 showed saturated red color and high luminous efficiency. The LE was measured at 23.2 cd/A compared to 22.2 cd/A for Compound 1.

It is understood that the various embodiments described herein are by way of example only, and are not intended to limit the scope of the invention. For example, many of the materials and structures described herein may be substituted with other materials and structures without deviating from the spirit of the invention. The present invention as claimed may therefore include variations from the particular examples and preferred embodiments described herein, as will be apparent to one of skill in the art. It is understood that various theories as to why the invention works are not intended to be limiting.

The invention claimed is:

1. A compound having the formula:



wherein R_1 , R_2 , R_3 , R_5 , R_6 and R_7 are independently selected from the group consisting of hydrogen, deuterium, alkyl, silyl, alkoxy, amino, alkenyl, alkynyl, arylkyl, aryl and heteroaryl;

wherein R_4 comprises an unsubstituted cycloalkyl group selected from the group consisting of cyclobutyl, cyclopentyl, cyclohexyl, and cycloheptyl; and

wherein m is 1, 2, or 3.

2. The compound of claim 1, wherein R_4 is an unsubstituted cyclobutyl moiety.

3. The compound of claim 1, wherein R_4 is an unsubstituted cyclopentyl moiety.

4. The compound of claim 1, wherein R_4 is an unsubstituted cyclohexyl moiety.

5. The compound of claim 1, wherein R_4 is an unsubstituted cycloheptyl moiety.

6. The compound of claim 1, wherein R_4 is an unsubstituted cycloalkyl group selected from the group consisting of cyclobutyl, cyclopentyl, cyclohexyl, and cycloheptyl.

7. The compound of claim 1, wherein each of R_1 and R_3 is a branched alkyl with branching at a position further than the α position to the carbonyl group.

8. The compound of claim 1, wherein each of R_5 and R_7 are methyl, and R_6 is hydrogen.


9. The compound of claim 1, wherein each of R_5 and R_6 are methyl, and R_7 is hydrogen.

10. The compound of claim 1, wherein each of R_5 , R_6 and R_7 are methyl.


11. The compound of claim 1, wherein the compound is selected from the group consisting of:

126


Compound II-1




Compound II-2



Compound II-3




Compound II-4



127


-continued




Compound II-5

128


-continued




Compound II-9




Compound II-6




Compound II-10




Compound II-7



Compound II-11




Compound II-8



Compound II-12

129

-continued




Compound II-13

5

10

15

Compound II-14




20

25

30

Compound II-15




35

40

45

Compound II-16



50


55

60


65

130


-continued



Compound II-17




Compound II-18




Compound II-19

131
-continued




Compound II-20


132
-continued




Compound II-23




Compound II-21



Compound II-24




Compound II-22



Compound II-25

133


-continued




Compound II-26

134


-continued




Compound II-29




Compound II-27



Compound II-30



Compound II-28




Compound II-31

135


-continued

Compound II-32


**136**

-continued


Compound II-35




Compound II-33




Compound II-36



Compound II-34




Compound II-37



137


-continued




Compound II-38

138


-continued




Compound II-42




Compound II-39




Compound II-43




Compound II-40



Compound II-44




Compound II-41




Compound II-45

139


-continued




Compound II-46



Compound II-47




Compound II-48




Compound II-49

140


-continued



Compound II-50




Compound II-51



Compound II-52

141


-continued



Compound II-53


142

-continued




Compound II-56


Compound II-54




Compound II-57



Compound II-55




Compound II-58



143

-continued

Compound II-59



5

10


15

20

144

-continued

Compound II-62



25


30

35


40

45


Compound II-60



Compound II-63



Compound II-61




55

60

65


Compound II-64



145

-continued

Compound II-65



5

10


15

20

146

-continued

Compound II-68



25


30

35


40

45


Compound II-66




Compound II-69



Compound II-67



Compound II-70



50

55


60

65


147

-continued


Compound II-71



Compound II-72



12. A first device comprising:
 an anode;
 a cathode; and
 an organic layer, disposed between the anode and the
 cathode, comprising a compound having the formula:



wherein R_1 , R_2 , R_3 , R_5 , R_6 and R_7 are independently
 selected from the group consisting of hydrogen, deu-
 terium, alkyl, silyl, alkoxy, amino, alkenyl, alkynyl,
 arylkyl, aryl and heteroaryl;

148

wherein R_4 comprises an unsubstituted cycloalkyl group
 selected from the group consisting of cyclobutyl, cyclo-
 pentyl, cyclohexyl, and cycloheptyl; and

wherein m is 1, 2, or 3.

13. The first device of claim 12, wherein each of R_1 and
 R_3 is a branched alkyl with branching at a position further
 than the α position to the carbonyl group.

14. The first device of claim 12, wherein each of R_5 , R_6
 and R_7 are independently selected from methyl and hydro-
 gen, and at least one of R_5 , R_6 and R_7 is methyl.


15. The first device of claim 12, wherein each of R_5 and
 R_7 are methyl, and R_6 is hydrogen.

16. The first device of claim 12, wherein each of R_5 and
 R_6 are methyl, and R_7 is hydrogen.


17. The first device of claim 12, wherein each of R_5 , R_6 ,
 and R_7 are methyl.

18. The first device of claim 12, wherein the compound is
 selected from the group consisting of:


Compound II-1



Compound II-2




Compound II-3



149


-continued



Compound II-4


150

-continued




Compound II-5

Compound II-8





Compound II-6

Compound II-9





Compound II-7

Compound II-10



50


Compound II-11




151

-continued


Compound II-12




Compound II-13



Compound II-14



Compound II-15

**152**


-continued

Compound II-16

5

10

15



20

25


30

Compound II-17

35

40

45




50

Compound II-18

55


60

65



153


-continued




Compound II-19

154


-continued




Compound II-22




Compound II-20



Compound II-23




Compound II-21




Compound II-24

155
-continued




Compound II-25


156
-continued




Compound II-28




Compound II-26



Compound II-29




Compound II-27



Compound II-30


157
-continued

Compound II-31




158
-continued


Compound II-34




Compound II-32




Compound II-35



Compound II-33




Compound II-36



159


-continued



Compound II-37


160

-continued




Compound II-41

Compound II-38





Compound II-42





Compound II-43

Compound II-39




Compound II-44

Compound II-40



161


-continued




Compound II-45

162


-continued




Compound II-49




Compound II-46




Compound II-50




Compound II-47



Compound II-51




Compound II-48



Compound II-52

163


-continued



Compound II-53


164

-continued




Compound II-56


Compound II-54




Compound II-57



Compound II-55




Compound II-58



165

-continued

Compound II-59

**166**

-continued


Compound II-62

5


10

15

20



Compound II-60 25




Compound II-63

30


35

40

45



Compound II-61 50




Compound II-64

55

60


65



167


-continued

Compound II-65


**168**

-continued


Compound II-68




Compound II-66




Compound II-69



Compound II-67




Compound II-70




169

-continued

Compound II-71



Compound II-72




170

19. The first device of claim 12, wherein the organic layer is an emissive layer and the compound is an emissive dopant.

20. The first device of claim 19, wherein the organic layer further comprises a host.

21. The first device of claim 20, wherein the host is a metal 8-hydroxyquinolate.

22. The first device of claim 21, wherein the host is



23. The first device of claim 12, wherein the first device is selected from the group consisting of a consumer product, an organic light emitting device, and combinations thereof.

* * * * *

专利名称(译)	有机发光二极管材料		
公开(公告)号	US10008677	公开(公告)日	2018-06-26
申请号	US13/932546	申请日	2013-07-01
[标]申请(专利权)人(译)	环球展览公司		
申请(专利权)人(译)	通用显示器公司		
当前申请(专利权)人(译)	通用显示器公司		
[标]发明人	XIA CHUANJUN MA BIN LI DAVID ZENAN ALLEYNE BERT DEANGELIS ALAN FIORDELISO JAMES ADAMOVICH VADIM		
发明人	XIA, CHUANJUN MA, BIN LI, DAVID ZENAN ALLEYNE, BERT DEANGELIS, ALAN FIORDELISO, JAMES ADAMOVICH, VADIM		
IPC分类号	H01L51/00 C07F15/00		
CPC分类号	C07F15/0033 H01L51/0085		
代理机构(译)	DUANE MORRIS LLP		
其他公开文献	US20130299795A1		
外部链接	Espacenet		

摘要(译)

提供了包含具有5-取代的2-苯基喹啉的配体的化合物。特别地，2-苯基喹啉可以在5-位被含环烷基的基团取代。这些化合物可以用于有机发光器件中，特别是用作这种器件的发射层中的红色发射体，以提供具有改进性能的器件。

