



US009847492B2

**(12) United States Patent
Jung****(10) Patent No.: US 9,847,492 B2****(45) Date of Patent: Dec. 19, 2017****(54) ORGANIC COMPOUND AND ORGANIC
LIGHT EMITTING DIODE DEVICE
INCLUDING THE SAME****51/0055** (2013.01); **H01L 51/0058** (2013.01);
H01L 51/0072 (2013.01); **H01L 51/5072**
(2013.01)**(71) Applicant: SAMSUNG DISPLAY CO., LTD.,**
Yongin, Gyeonggi-Do (KR)**(58) Field of Classification Search**

None

See application file for complete search history.

(72) Inventor: Ji Yun Jung, Seoul (KR)**(56) References Cited****(73) Assignee: Samsung Display Co., Ltd.**, Yongin,
Gyeonggi-do (KR)**U.S. PATENT DOCUMENTS**2008/0220285 A1* 9/2008 Vestweber C07C 13/62
428/690
2013/0053558 A1* 2/2013 Pflumm C07D 403/10
544/180**(*) Notice:** Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 271 days.**FOREIGN PATENT DOCUMENTS**JP 10-017860 1/1998
JP 11-087067 3/1999

(Continued)

(21) Appl. No.: 14/595,345**(22) Filed: Jan. 13, 2015****(65) Prior Publication Data**

US 2016/0013420 A1 Jan. 14, 2016

(30) Foreign Application Priority Data



Jul. 10, 2014 (KR) 10-2014-0086973

Primary Examiner — Gregory Clark**(74) Attorney, Agent, or Firm** — Lee & Morse, P.C.**(57) ABSTRACT**

An organic compound is represented by Formula 1.

(51) Int. Cl.**H01L 51/50** (2006.01)
H01L 51/00 (2006.01)
C07D 251/24 (2006.01)
C07D 401/04 (2006.01)
C07D 239/26 (2006.01)
C07D 401/14 (2006.01)
C07D 213/16 (2006.01)
C07D 471/04 (2006.01)**(52) U.S. Cl.**CPC **H01L 51/0067** (2013.01); **C07D 213/16**
(2013.01); **C07D 239/26** (2013.01); **C07D**
251/24 (2013.01); **C07D 401/04** (2013.01);
C07D 401/14 (2013.01); **C07D 471/04**
(2013.01); **H01L 51/0052** (2013.01); **H01L**

[Formula 1]

where X₁, X₂, L, A₁, A₂, R₁, R₂, R₃, R₄, and Het are as
defined in the specification.**2 Claims, 1 Drawing Sheet**


(56)

References Cited

FOREIGN PATENT DOCUMENTS

JP	11-345686	12/1999
KR	10-2011-0122129	11/2011
KR	10-2012-0103551	1/2012

* cited by examiner



ORGANIC COMPOUND AND ORGANIC LIGHT EMITTING DIODE DEVICE INCLUDING THE SAME

CROSS-REFERENCE TO RELATED APPLICATION

Korean Patent Application No. 10-2014-0086973 filed on Jul. 10, 2014, in the Korean Intellectual Property Office, and entitled: "Organic Compound and Organic Light Emitting Diode Device Including the Same," is incorporated by reference herein in its entirety.

BACKGROUND

1. Field

Embodiments relate to an organic compound and an organic light emitting diode device including the same.


2. Description of the Related Art

Recent trends toward lightweight and thin personal computers and televisions sets also require lightweight and thin display devices, and flat panel displays satisfying such requirements are being substituted for conventional cathode ray tubes (CRTs.)

However, since the LCD is a passive display device, an additional back-light as a light source is needed, and the LCD has various problems such as a slow response time and a narrow viewing angle. In this connection, an organic light emitting diode (OLED) display has recently been spotlighted as a display device that has merits such as a wide viewing angle, outstanding contrast, and a fast response time. In the organic light emitting diode device, electrons injected from one electrode and holes injected from another electrode are combined with each other in an emission layer, thereby generating excitons, and energy is outputted from the excitons to thereby emit light.

SUMMARY

Embodiments are directed to an organic compound represented by Formula 1:



Wherein, Formula 1,

X₁ and X₂ are CR₅ or N,

R₁ to R₅ are independently hydrogen, deuterium, a halogen, a C1 to C40 alkyl group, a C5 to C40 aryl group, a C5 to C40 heteroaryl group, a C5 to C40 aryloxy group, a C1 to C40 alkyloxy group, a C5 to C40 arylamino group, a C5 to C40 diarylamino group, a C6 to C40 arylalkyl group, a C3 to C40 cycloalkyl group, or a C3 to C40 heterocycloalkyl group, and any of R₁ to R₅ may form a fused aliphatic ring, a fused aromatic ring, a fused heteroaliphatic ring, or a fused heteroaromatic ring with an adjacent group or a combination thereof,

L is a single-bond, a substituted or unsubstituted C5 to C30 arylene group, a substituted or unsubstituted C10 to C30 fused arylene group, a substituted or unsubstituted C2 to C30 heteroarylene group including at least one of N, S, and O, or a substituted or unsubstituted C5 to C30 fused heteroarylene group including at least one of N, S, and O,

Het is a substituted or unsubstituted C3 to C20 heteroarylene group including N, and

A₁ and A₂ are hydrogen, a substituted or unsubstituted C5 to C40 aryl group and, or a substituted or unsubstituted C5 to C40 heteroaryl group.

The compound represented by Formula 1 may include at least one of Compounds 1 to 72 (reproduced below).

Embodiments are also directed to an organic light emitting diode device including an anode, a cathode, and an organic layer provided between the anode and the cathode, wherein the organic layer includes an organic compound represented by Formula 1.

The organic layer may include an emission layer. The organic compound represented by Formula 1 may be included in the emission layer.

BRIEF DESCRIPTION OF THE DRAWING

Features will become apparent to those of skill in the art by describing in detail exemplary embodiments with reference to the attached drawing in which:

FIG. 1 illustrates a cross-sectional view of a configuration of an organic light emitting diode device according to an exemplary embodiment.

DETAILED DESCRIPTION

Example embodiments will now be described more fully hereinafter with reference to the accompanying drawing; however, they may be embodied in different forms and should not be construed as limited to the embodiments set forth herein. Rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey exemplary implementations to those skilled in the art.

In the drawing FIGURES, the dimensions of layers and regions may be exaggerated for clarity of illustration. It will also be understood that when a layer or element is referred to as being "on" another layer or substrate, it can be directly on the other layer or substrate, or intervening layers may also be present. In addition, it will also be understood that when a layer is referred to as being "between" two layers, it can be the only layer between the two layers, or one or more intervening layers may also be present. Like reference numerals refer to like elements throughout.

In the present specification, the term "substituted," unless separately defined otherwise, indicates a substitution of at least one hydrogen atom with a substituent selected from deuterium, a C1 to C30 alkyl group, a C6 to C36 aryl group, a C2 to C30 heteroaryl group, a C1 to C30 alkoxy group, a C2 to C30 alkenyl group, a C6 to C30 aryloxy group, a C3 to C40 silyloxy group, a C1 to C30 acyl group, a C2 to C30 acyloxy group, a C2 to C30 heteroacyloxy group, a C1 to C30 sulfonyl group, a C1 to C30 alkylthiol group, a C6 to C30 arylthiol group, a C1 to C30 heterocyclothiol group, a C1 to C30 phosphoric acid amide group, a C3 to C40 silyl group, NRR' (where R and R' are respectively substituents selected from a hydrogen atom, a C1 to C30 alkyl group, and a C6 to C30 aryl group), a carboxylic acid group, a halogen group, a cyano group, a nitro group, an azo group, a fluorene group, and a hydroxyl group.

Further, the C6 to C36 aryl group, the C2 to C30 heteroaryl group, and the fluorene group from among the substituents may be further substituted with deuterium, a halogen, a cyano group, a methyl group, a tri-fluoromethyl group, or a phenyl group.

As used herein, the term “hetero,” unless separately defined otherwise, indicates that a single ring contains one to three heteroatoms selected from the group consisting of N, O, S, and P, with carbon atoms as the remainder.

Also in the present specification, the term “organic layer” generally refers to layers including an organic material. Such an organic layer may further include an inorganic material and a metal complex in addition to the organic material. The organic layer may include at least one layer.

Further, among groups used in chemical formulae of the present specification, definition of a representative group is as follows (the number of carbons that limits substituents is not restrictive, and does not limit characteristics of the constituents).

An unsubstituted C1 to C30 alkyl group may be a linear type or a branched type. Examples of the unsubstituted C1 to C30 alkyl include methyl, ethyl, propyl, iso-propyl, sec-butyl, hexyl, iso-amyl, hexyl, heptyl, octyl, nonanyl, dodecyl, and the like.

An unsubstituted C2 to C30 alkenyl group has at least one carbon-carbon bond in the center or at a terminal of the unsubstituted alkyl group. Examples include ethenyl, propenyl, butenyl, or the like.

The term “unsubstituted C2 to C30 alkynyl group” refers to an alkyl group having at least one carbon-carbon triple bond in the center or at a terminal of the alkyl group. Examples of the unsubstituted C2-C30 alkynyl group include acetylene, propylene, phenylacetylene, naphthylacetylene, isopropylacetylene, t-butylacetylene, diphenylacetylene, or the like.

The term “unsubstituted C3 to C30 cycloalkyl group” refers to a C3 to C30 cyclic alkyl group.

The term “unsubstituted C1 to C30 alkoxy group” refers to a group having a structure of —OA (wherein A is an unsubstituted C1 to C30 alkyl group as described above). Examples of the unsubstituted C1 to C30 include a methoxy group, an ethoxy group, a propoxy group, an isopropoxy group, a butoxy group, and a pentoxy group.

The term “unsubstituted C6 to C30 aryl group” refers to a carbocyclic aromatic system containing at least one ring. At least two rings may be fused to each other or linked to each other by a single bond. The term “aryl” refers to an aromatic system, such as phenyl, naphthyl, or anthracenyl. Examples of the unsubstituted C6 to C30 aryl group include a phenyl group, a tolyl group, a naphthyl group, an anthracenyl group, a terphenyl group, a phenanthrenyl group, a pyrenyl group, a diphenylanthracenyl group, a dinaphthylanthracenyl group, a pentacenyl group, a bromophenyl group, a hydroxyphenyl group, a stilbene group, an azobenzenyl group, or a ferrocenyl group.

An unsubstituted C2 to C30 heteroaryl group includes one, two, or three hetero atoms selected from B, N, O, S, and P. At least two rings may be fused to each other or linked each other by a single bond. Examples of the unsubstituted C2 to C30 heteroaryl group include a pyrazolyl group, an imidazolyl group, an oxazolyl group, a triazolyl group, a triazinyl group, a triazolyl group, a tetrazolyl group, an oxadiazole group, a thiadiazole group, a pyridinyl group, a pyridazinyl group, a pyrimidinyl group, a triazinyl group, a

carbazole group, an indolyl group, a quinolyl group, an isoquinolyl group, a thiophene group, a dibenzothiophene group, a dibenzofuran group, and a benzimidazolyl group.


An unsubstituted C6 to C30 aryloxy group is a group represented by —OA₁, wherein A₁ is the same type of functional group as the C6 to C30 aryl group, having a different number of carbons. Examples of the aryloxy group may include a phenoxy group.

An unsubstituted C6 to C30 arylthio group is a group represented by —SA₁, where A₁ is the same type of functional group as the C6 to C30 aryl group, having a different number of carbons. Examples of the arylthio group include a benzenethio group, a naphthylthio group, or the like.

An organic compound according to an exemplary embodiment will now be described in detail.

The organic compound may be represented by Formula 1.

[Formula 1]



Here,

X₁ and X₂ are CR₅ or N,

R₁ to R₅ are independently H, D, a halogen, a C1 to C40 alkyl group, a C5 to C40 aryl group, a C5 to C40 heteroaryl group, a C5 to C40 aryloxy group, a C1 to C40 alkyloxy group, a C5 to C40 arylamino group, a C5 to C40 diarylamino group, a C6 to C40 arylalkyl group, a C3 to C40 cycloalkyl group, and a C3 to C40 heterocycloalkyl group, and any of R₁ to R₅ form a fused aliphatic ring, a fused aromatic ring, a fused heteroaliphatic ring, or a fused heteroaromatic ring with an adjacent group, or a combination thereof,

L is a single-bond, a substituted or unsubstituted C5 to C30 arylene group, a substituted or unsubstituted C10 to C30 fused arylene group, a substituted or unsubstituted C2 to C30 heteroarylene group including at least one of N, S, and O, or a substituted or unsubstituted C5 to C30 fused heteroarylene group including at least one of N, S, and O,

Het is a substituted or unsubstituted C3 to C20 heteroarylene group including N, and

A₁ and A₂ are H, a substituted or unsubstituted C5 to C40 aryl group, or a substituted or unsubstituted C5 to C40 heteroaryl group.








As a detailed example of the compound represented by Formula 1, at least one of the Compounds 1 to 72 shown below may be provided.

The compounds 1 to 72 shown below may be used independently, at least two may be mixed and used, or they may be mixed with another compound and be used.

5




6

-continued






7

-continued






8

-continued







9

-continued


**10**

-continued




11

-continued

**12**


-continued



13

-continued

29



5

10


15

20

14

-continued


32



33


25

30




35

40




45

50



55






60






65

15

-continued


**16**

-continued








17

-continued


**18**

-continued



19

-continued




49

5

10

15

20




50

25

30

35

40



51

50


55

60


65

20


-continued



52




53




54

21

-continued


**22**

-continued




23

-continued




**24**

-continued



25

-continued



An organic light emitting diode device to which the above-described organic compound is applied according to an exemplary embodiment will be described with reference to FIG. 1.

FIG. 1 illustrates a cross-sectional view of an organic light emitting diode device according to an exemplary embodiment.

Referring to FIG. 1, the organic light emitting diode device may include an anode 1, a cathode 2 facing the anode 1, and an organic layer 10 provided between the anode 1 and the cathode 2.

26


The substrate (not shown) may be disposed on the side of the anode 1 or the cathode 2. The substrate may be made of, e.g., an inorganic material such as glass, an organic material such as polycarbonate, (PC), polymethylmethacrylate (PMMA), polyethylene terephthalate (PET), polyamide (PA), polyethersulfone (PES), or a combination thereof, a silicon wafer, or the like.

At least one of the anode 1 and the cathode 2 may be a transparent electrode formed by processing a conductive oxide such as indium tin oxide (ITO), indium zinc oxide (IZO), tin oxide (SnO₂), zinc oxide (ZnO), or a combination thereof, or a metal such as Al, Ag, or Mg to be thin.


The organic layer 10 may include an emission layer 5, a hole auxiliary layer 3 provided between the anode 1 and the emission layer 5, and an electron auxiliary layer 4 provided between the cathode 2 and the emission layer 5. At least one of the hole auxiliary layer 3 and the electron auxiliary layer 4 may be omitted.

The emission layer 5 may include anthracene, arylamine, styryl, a derivative thereof, or a combination thereof. The emission layer 5 may function as a fluorescent or phosphorescent host and may include a suitable dopant.

Examples of a suitable red dopant include PtOEP, Ir(piq)₃, Btp₂Ir(acac), DCJTb, or the like.




PtOEP




Examples of a suitable green dopant include Ir(ppy)₃ (ppy=phenylpyridine), Ir(ppy)₂(acac), Ir(mppy)₃, C545T, or the like.

27


Ir(ppy)₃

28



-continued



C545T

Ir(ppy)₂(acac)Ir(mpyp)₃

Examples of a suitable-known blue dopant include F₂Irpic, (F₂ppy)₂Ir(tmd), Ir(dfppz)₃, ter-fluorene, 4,4'-bis(4-diphenylaminostyryl) biphenyl (DPAVBi), 2,5,8,11-tetra-tert-butyl perylene (TBP), or the like.

F₂Irpic(F₂ppy)₂Ir(tmd)Ir(dfppz)₃

DPAVBi

TBP

29

A content of the dopant may be selected, for example, within a range of 0.1 to 15 parts by weight with respect to 100 parts by weight of the emission layer forming material (i.e., the total weight of the host and the dopant is set to be 100 parts by weight).

The emission layer **5** may emit white light by a combination of the primary colors such as three primary colors of red, green, and blue. The white light may be emitted by combining the colors of neighboring subpixels or by combining colors that are deposited in the vertical direction.

The electron auxiliary layer **4** may be provided between the emission layer **5** and the cathode **2**. The electron auxiliary layer **4** may increase electron mobility. The electron auxiliary layer **4** may include at least one layer selected from the electron injection layer, the electron transport layer, and the hole blocking layer.


The electron auxiliary layer **4** may include the above-described organic compound.

The hole blocking layer may include any suitable material to form a hole blocking layer. The suitable material used to form the hole blocking layer may be randomly selected. For example, oxadiazole derivatives, triazole derivatives, phenanthroline derivatives, Balq, BCP, or the like may be used.

The electron transport layer may include the organic compound represented by Formula 1.

The hole auxiliary layer **3** may be provided between the emission layer **5** and the anode **1** to increase hole mobility. The hole auxiliary layer **3** may exemplarily include at least one layer selected from among the hole injection layer, the hole transport layer, and the electron blocking layer.


A suitable hole injection material may be for the hole injection layer. For example, the hole injection material may be a phthalocyanine compound such as copper phthalocyanine or the like, m-MTDATA (4,4',4''-tris(3-methylphenylphenylamino)triphenylamine), NPB (N,N'-di(1-naphthyl)-N,N'-diphenylbenzidine), TDATA, 2T-NATA, Pani/DB SA (polyaniline/dodecylbenzene sulfonic acid; polyaniline/dodecylbenzene sulfonic acid), PEDOT/PSS (poly(3,4-ethylene dioxythiophene)/poly(4-styrene sulfonate); poly(3,4-ethylene dioxythiophene)/poly(4-styrene sulfonate)), Pani/CSA (polyaniline/camphor sulfonic acid; polyaniline/camphor sulfonic acid), or Pani/PSS (((polyaniline)/poly(4-styrene sulfonate); polyaniline)/poly(4-styrene sulfonate))).




m-MTDATA

30

-continued




TDATA



2T-NATA


The hole transport layer may include a suitable hole transport material, for example, a carbazole derivative such as N-phenylcarbazole, polyvinylcarbazole, or the like, and an amine derivative having an aromatic condensed ring such as NPB, N,N'-bis(3-methylphenyl)-N,N'-diphenyl-[1,1-biphenyl]-4,4'-diamine (TPD), or the like. For example, the hole transport material may transport holes and prevent the excitons from spreading from the emission layer.



TPD

31

-continued



NPB

The organic light emitting diode device may be configured in the form of anode/hole injection layer/emission layer/electron transport layer/cathode, anode/hole injection layer/hole transport layer/emission layer/electron transport layer/cathode, or anode/hole injection layer/hole transport layer/emission layer/electron transport layer/electron injection layer/cathode.

The organic layer **10** may be formed by various methods, for example, a vacuum deposition method, a spin coating method, a cast method, or an LB method.

When the organic layer is formed by the vacuum deposition method, deposition conditions may depend on the compound used as a material of the organic layer, the structure of the target organic layer, and thermal characteristics. For example, deposition conditions may include a deposition temperature 100 to 500° C., a vacuum degree 10⁻⁸ to 10⁻³ torr, and a deposition speed 0.01 to 100 Å/sec.

When the organic layer is formed by the spin coating method, coating conditions may depend on the compound used as a material of the organic layer, the structure of the target organic layer, and thermal characteristics. For example, deposition conditions may include a coating speed of about 2,000 rpm to about 5,000 rpm, and a heat treatment temperature for removing a solvent after the coating in a temperature range of about 80° C. to 200° C.

The organic layer **10** may include a first layer including the organic compound represented by Formula 1. The first layer may be the electron transport layer.

The organic layer **10** may further include at least one of the hole injection layer, the hole transport layer, the electron blocking layer, the hole blocking layer, the electron transport layer, and the electron injection layer in addition to the electron transport layer.

The organic light emitting diode device may be electrically connected to a thin film transistor. The thin film transistor may be disposed between the substrate and the electrode.


The following Examples and Comparative Examples are provided in order to highlight characteristics of one or more embodiments, but it will be understood that the Examples and Comparative Examples are not to be construed as limiting the scope of the embodiments, nor are the Comparative Examples to be construed as being outside the scope of the embodiments. Further, it will be understood that the embodiments are not limited to the particular details described in the Examples and Comparative Examples.

32


SYNTHESIS EXAMPLES

Synthesis Example 1


Synthesis of Compound 1



Intermediate 1A



Intermediate 1B



Compound 1

Synthesis of Compound 1


In a nitrogen atmosphere, the intermediate 1A (2.1 g, 6 mmol), the intermediate 1B (1.6 g, 5 mmol), Pd(PPh₃)₄ (0.23 g, 0.2 mmol), 3 mL of a 2 M K₂CO₃ aqueous solution, 10 mL of toluene, and 5 mL of ethanol were provided and then refluxed and agitated for twelve hours. A resultant material was rinsed with distilled water, and an organic material was extracted by using ethyl acetate. The extracted organic material was dried with anhydride MgSO₄, decompressed, and distilled. 1.1 g (41%) of the intermediate compound 1 was acquired by column-separating the resultant material.

¹H-NMR (CDCl₃, 300 MHz, ppm): 8.4-8.3 (m, 4H), 8.2-8.1 (m, 2H), 7.8-7.9 (m, 3H), 7.7-7.4 (m, 10H), 1.7 (s, 12H).

33


Synthesis Example 2

Synthesis of Compound 4




Synthesis of Intermediate 4C

The intermediate 4C (1.4 g, 63%) was synthesized using the same method as the synthesis method of the compound 1, except for the usage of the intermediate 4A instead of the intermediate 1B and usage of the intermediate 4B instead of the intermediate 1A.



34

-continued




Synthesis of Compound 4

The compound 4 (0.9 g, 58%) was synthesized using the same method as the synthesis method of the compound 1, except for the usage of the intermediate 4C instead of the intermediate 1B.

H-NMR (CDCl₃, 300 MHz, ppm): 9.0-8.9 (m, 2H), 8.5-8.1 (m, 9H), 7.9-7.8 (m, 5H), 7.7-7.6 (m, 4H), 7.5-7.4 (m, 7H), 1.7 (s, 12H).

Synthesis Example 3

Synthesis of Compound 7





Synthesis of Intermediate 7C

The intermediate 7C (2.7 g, 43%) was synthesized using the same method as the synthesis method of the compound 1, except for the usage of the intermediate 7A instead of the intermediate 1B and usage of the intermediate 7B instead of the intermediate 1A.

35

Synthesis of Intermediate 7D




At room temperature, the intermediate 7C (5.1 g, 20 mmol) was melted in a flask in which 100 mL tetrahydrofuran was provided. The temperature of the flask was reduced to -78°C ., n-butyllithium (18 mL, 30.0 mol) was slowly added at the temperature, and triisopropyl borate (5.5 mL, 25.0 mmol) was added at the same temperature. The temperature of the flask was gradually increased to reach room temperature overnight to progress a reaction. When the reaction was finished, a 1N-hydrochloric acid aqueous solution was added to the flask until reaching pH 2 to acidify the reaction solution. The acidified reaction solution was extracted with ethyl acetate and the extracted organic layer was rinsed with purified water. The organic layer was separated from the ethyl acetate to be dried with sulfuric acid anhydride magnesium and filtered. A filtrate was concentrated to recrystallize the same with dichloromethane and n-hexane, such that the intermediate 7D (3.8 g, 74%) was acquired.



Synthesis of Intermediate 7F

The intermediate 7F (1.2 g, 38%) was synthesized using the same method as the synthesis method of the compound 1, except for the usage of the intermediate 7E instead of the intermediate 1B and usage of the intermediate 7D instead of the intermediate 1A.

36



Synthesis of Compound 7


The compound 7 (0.8 g, 60%) was synthesized using the same method as the synthesis method of the compound 1, except for the usage of the intermediate 7F instead of the intermediate 1B.

¹H-NMR (CDCl_3 , 300 MHz, ppm): 9.0-8.9 (m, 3H), 8.5 (s, 1H), 8.4 (s, 1H), 8.3-8.1 (m, 7H), 7.9-7.8 (m, 6H), 7.7-7.4 (m, 8H), 2.7 (s, 3H), 1.7 (s, 12H).

37


Synthesis Example 4

Synthesis of Compound 11




Synthesis of Intermediate 11A

The intermediate 11A (1.8 g, 69%) was synthesized using the same method as the synthesis method of the compound 1, except for the usage of the intermediate 4A instead of the intermediate 1B and usage of the intermediate 7D instead of the intermediate 1A.



38

-continued




Synthesis of Compound 11

The compound 11 (0.9 g, 64%) was synthesized by using the same method as the synthesis method of the compound 1, except for the usage of the intermediate 11A instead of the intermediate 1B.

¹H-NMR (CDCl₃, 300 MHz, ppm): 9.0-8.9 (m, 3H), 8.5 (s, 1H), 8.3-8.1 (m, 7H), 7.9-7.8 (m, 6H), 7.7-7.3 (m, 8H), 2.7 (s, 3H), 1.7 (s, 12H).


Synthesis Example 5

Synthesis of Compound 17




Synthesis of Intermediate 17B

The intermediate 17B (2.3 g, 56%) was synthesized using the same method as the synthesis method of the compound 1, except for the usage of the intermediate 17A instead of the intermediate 7C.





39

-continued



Synthesis of Intermediate 17E



The intermediate 17E (1.1 g, 17%) was synthesized by using the same method as the synthesis method of the compound 1, except for the usage of the intermediate 17C instead of the intermediate 1B and usage of the intermediate 17D instead of the intermediate 1A.




Synthesis of Intermediate 17F

The intermediate 17E (1.2 g, 27%) was synthesized by using the same method as the synthesis method of the compound 1, except for the usage of the intermediate 17E instead of the intermediate 1B and usage of the intermediate 17B instead of the intermediate 1A.

40



Intermediate 17F



Synthesis of Compound 17




The compound 17 (0.6 g, 51%) was synthesized using the same method as the synthesis method of the compound 1, except for the usage of the intermediate 17F instead of the intermediate 1B.

¹H-NMR (CDCl₃, 300 MHz, ppm): 9.1 (d, 1H), 8.9-8.8 (m, 3H), 8.6-8.5 (m, 3H), 8.3-8.1 (m, 5H), 7.9-7.7 (m, 9H), 7.6-7.4 (m, 5H), 1.7 (s, 12H).

41

Synthesis Example 6

Synthesis of Compound 22



Synthesis of Compound 22

The compound 22 (0.8 g, 42%) was synthesized by using the same method as the synthesis method of the compound 1, except for the usage of the intermediate 22A instead of the intermediate 1B.

H-NMR (CDCl_3 , 300 MHz, ppm): 8.4-8.2 (m, 3H), 8.1-7.9 (m, 10H), 7.7-7.4 (m, 9H), 1.7 (s, 12H).

42

Synthesis Example 7

Synthesis of Compound 28

5

10

15

20

25

30

35

40




45

50

55

60

65




Synthesis of Compound 28

The compound 28 (1.1 g, 65%) was synthesized by using the same method as the synthesis method of the compound 1, except for the usage of the intermediate 28A instead of the intermediate 1B.

H-NMR (CDCl_3 , 300 MHz, ppm): 8.9-8.6 (m, 4H), 8.3-8.1 (m, 6H), 8.0-7.7 (m, 5H), 7.6-7.4 (m, 4H), 1.7 (s, 12H).


Synthesis Example 8

Synthesis of Compound 39





43


-continued




Intermediate 3B




Intermediate 39C




Intermediate 39D



Intermediate 39E



Intermediate 39F



Intermediate 39G

Synthesis of Intermediate 39A

The intermediate 39A was synthesized by using the same method as the synthesis method of the compound 1, except for the usage of 1,4-dibromo-3,5-dimethylbenzene instead

44

of the intermediate 1B and usage of 2-pyridylboronic acid in the 3.0 equivalence instead of the intermediate 1A.

Synthesis of Intermediate 39B

The intermediate 39A (2.60 g, 10.0 mmole), 7.40 g potassium permanganate, and 5 ml water were put into pyridine (50 ml) and refluxed for two hours. After this, 10 ml water and 3.00 g potassium permanganate were added every thirty minutes. After six additions, 50 ml water was added and refluxed for twelve hours. A MnO_2 precipitate formed after the reaction was finished was removed using hot water, and celite and activated carbon was used to filter the resultant again. A solid generated by adding heavy HCl was filtered, taken, and dried with an oven, such that the intermediate 39B (2.90 g, and a 90% yield) was acquired.

Synthesis of Intermediate 39C

The intermediate 39B (2.90 g, 9.0 mmole) was melted in 100 ml H_2SO_4 and was agitated for two hours at room temperature. The flask was moved to an ice bath after the reaction was finished, a formed solid was neutralized by using a potassium carbonate aqueous solution, and the solid was filtered and gathered, so that the intermediate 39C (2.07 g, a 81% yield) was acquired.

Synthesis of Intermediate 39D

The intermediate 39C (2.07 g, 7.3 mmole) and hydrazine monohydrate (98%, 10 ml) were put into 150 ml ethylene glycol, and 8.6 g KOH was added thereto, and the reaction solution was refluxed for 24 hours. A hot reaction solution was poured into an ice-added HCl solution and a formed solid was filtered. The acquired solid was recrystallized to provide the intermediate 39D (1.65 g, a 90% yield).

Synthesis of Intermediate 39E

In a nitrogen atmosphere, the intermediate 39D (1.65 g, 6.44 mmole) was put into a flask including 200 mL THF, and cooled at -78°C . N-BuLi (1.6 M in Hex.) (9.0 ml, 14.4 mmole) was slowly added and the solution was agitated for one hour at -78°C . CH_3I (1.08 ml, 17.3 mmole) was added, the temperature was slowly controlled to reach room temperature, and the solution was then agitated for one and a half hours. Then, the solution was cooled down again to -78°C , n-BuLi (1.6 M in Hex.) (10.8 ml, 17.3 mmole) was slowly added, the solution was agitated for one hour at -78°C , and CH_3I (1.25 ml, 20.1 mmole) was added, the solution was controlled to reach room temperature, and agitated for an hour. When the reaction was finished, the resultant was rinsed with distilled water, extracted with CH_2Cl_2 , dried with anhydride MgSO_4 , decompressed, and distilled. The acquired solid was put into the flask with 200 mL hexane which was agitated and boiled. In this instance, materials that were not melted after the hexane was boiled were filtered and dried, such that the intermediate 39E (1.13 g, a 56% yield) was acquired.

Synthesis of Intermediate 39F


The intermediate 39E (1.13 g, 3.6 mmol) was put into a 30 mL round-bottomed flask, which was vacuum-dried and filled with nitrogen gas. 10 mL chloroform was put into the flask and the flask was then wrapped with foil to exclude light. The flask was cooled to 0°C , 10 mg FeCl_3 (58 μmol)

45

was put into the flask, and 3 mL chloroform and 0.7 g (4.0 mmol) bromine were melted and provided for half an hour. The temperature was raised to reach room temperature and the flask was agitated for five hours. When the reaction was finished, the above-noted mixture was poured into a 15 mL saturated sodium thiosulfate aqueous solution, which was agitated until a red color disappeared. The resultant was extracted with chloroform, dried with anhydride MgSO_4 , decompressed, and distilled. The acquired material was put into a flask with 200 mL hexane, agitated and boiled. In this instance, after the hexane was heated, the materials that were not melted were filtered and dried, such that the intermediate 39F (0.7 g, a 51% yield) was acquired.

Synthesis of Intermediate 39G

The intermediate 39G (0.5 g, 76%) was synthesized by using the same method as the synthesis method of the compound 7D, except for the usage of the intermediate 39F instead of the intermediate 7C.



Synthesis of Compound 39

The compound 39 (0.8 g, 48%) was synthesized by using the same method as the synthesis method of the compound


46

1, except for the usage of the intermediate 39G instead of the intermediate 1A and usage of the intermediate 39H instead of the intermediate 1B.

H-NMR (CDCl_3 , 300 MHz, ppm): 9.1-8.9 (m, 2H), 8.5-8.3 (m, 6H), 8.2-8.0 (m, 3H), 7.8-7.3 (m, 7H), 6.8 (t, 1H), 1.7 (s, 12H).

Synthesis Example 9

Synthesis of Compound 43



Synthesis of Compound 43




The compound 43 (0.5 g, 34%) was synthesized by using the same method as the synthesis method of the compound 39, except for the usage of the intermediate 7F instead of the intermediate 39H.

H-NMR (CDCl_3 , 300 MHz, ppm): 9.0-8.9 (m, 4H), 8.5-8.3 (m, 7H), 8.2-8.0 (m, 6H), 7.8-7.3 (m, 6H), 6.7 (t, 1H), 2.7 (s, 3H), 1.7 (s, 12H).

47

Synthesis Example 10

Synthesis of Compound 47



Synthesis of Compound 47

The compound 47 (0.6 g, 41%) was synthesized by using the same method as the synthesis method of the compound 39, except for the usage of the intermediate 11A instead of the intermediate 39H.


H-NMR (CDCl_3 , 300 MHz, ppm): 9.0-8.9 (m, 4H), 8.5-8.0 (m, 12H), 7.8-7.3 (m, 6H), 6.7 (t, 1H), 2.7 (s, 3H), 1.7 (s, 12H).

48


Synthesis Example 11

Synthesis of Compound 51


5



15



35



55

Synthesis of Compound 51




The compound 51 (0.5 g, 37%) was synthesized by using the same method as the synthesis method of the compound 39, except for the usage of the intermediate 17F instead of the intermediate 39H.

H-NMR (CDCl_3 , 300 MHz, ppm): 9.1-8.5 (m, 7H), 8.4-8.1 (m, 6H), 8.0-7.3 (m, 9H), 6.7 (t, 1H), 1.7 (s, 12H).

49

Synthesis Example 12

Synthesis of Compound 57





Synthesis of Compound 57

The compound 57 (0.9 g, 67%) was synthesized by using the same method as the synthesis method of the compound 39, except for the usage of the intermediate 57A instead of the intermediate 39H.

H-NMR (CDCl₃, 300 MHz, ppm): 9.0-8.8 (m, 3H), 8.4*8.0 (m, 8H), 7.7-7.3 (m, 4H), 6.7 (t, 1H), 1.7 (s, 12H).


Synthesis Example 13

Synthesis of Compound 72



50

-continued



Synthesis of Compound 72


The compound 72 (1.1 g, 72%) was synthesized by using the same method as the synthesis method of the compound 39, except for the usage of the intermediate 72A instead of the intermediate 39H.

H-NMR (CDCl₃, 300 MHz, ppm): 9.3 (s, 1H), 8.4-8.3 (m, 3H), 8.1-8.0 (m, 3H), 7.8-7.3 (m, 9H), 6.7 (t, 1H), 1.7 (s, 12H).

EXEMPLARY EMBODIMENTS


Exemplary Embodiment 1

A 15 Ω/cm² 500 Å ITO glass substrate (manufactured by Corning) was incised to the size of 50 mm×50 mm×0.5 mm, an ultrasonic wave cleaning process was performed for ten minutes by using isopropyl alcohol and pure water, ultraviolet rays were irradiated thereto for ten minutes. Then, the substrate was exposed to ozone to be cleaned, and was installed in a vacuum deposition device. Then, 2-TNATA (4,4',4''-tris(N-(2-naphthyl)-N-phenyl-amino)-triphenylamine) was vacuum-deposited on an upper portion of the ITO glass substrate to form a 600 Å thick hole injection layer, and NPB (4,4'-bis(naphthalene-1-yl)-N—N'-bis(phenyl)-benzidine) was vacuum-deposited with a 300 Å thickness with a hole transporting compound to form a hole transport layer.



51


-continued



NPB


Sequentially, ADN (9,10-di(naphth-2-yl)anthracene) and DNTPD (N1,N1'-(biphenyl-4,4'-diyl)bis(N1-phenyl-N4,N4-di-m-tolylbenzene-1,4-diamine)) as a blue fluorescent host were simultaneously deposited with a weight ratio 96:4 at an upper portion of the hole transport layer, such that a 300 Å thick emission layer was formed. Compound 1 was deposited to be 300 Å thick, forming an electron transport layer, and Al was vacuum-deposited to be 1,200 Å (cathode electrode) thick, forming an Al electrode, such that an organic light emitting diode device was manufactured.

Exemplary Embodiment 2



The organic light emitting diode device was manufactured in a like manner as exemplary embodiment 1, except for formation of the electron transport layer by use of compound 4 instead of compound 1.

Exemplary Embodiment 3




52

The organic light emitting diode device was manufactured in a like manner as exemplary embodiment 1, except for formation of the electron transport layer by use of compound 7 instead of compound 1.

5

10 Exemplary Embodiment 4



25

1

30

The organic light emitting diode device was manufactured in a like manner as exemplary embodiment 1, except for formation of the electron transport layer by use of compound 11 instead of compound 1.

35

40 Exemplary Embodiment 5

45

4

50

55


60

65

The organic light emitting diode device was manufactured in a like manner as exemplary embodiment 1, except for formation of the electron transport layer by use of compound 17 instead of compound 1.


53

Exemplary Embodiment 6




The organic light emitting diode device was manufactured in a like manner as the exemplary embodiment 1, except for formation of the electron transport layer by use of compound 22 instead of compound 1.

Exemplary Embodiment 7



The organic light emitting diode device was manufactured in a like manner as exemplary embodiment 1, except for formation of the electron transport layer by use of compound 28 instead of compound 1.


Exemplary Embodiment 8



54


The organic light emitting diode device was manufactured in a like manner as exemplary embodiment 1, except for formation of the electron transport layer by use of compound 39 instead of compound 1.

Exemplary Embodiment 9




The organic light emitting diode device was manufactured in a like manner as exemplary embodiment 1, except for formation of the electron transport layer by use of compound 43 instead of compound 1.

Exemplary Embodiment 10



The organic light emitting diode device was manufactured in a like manner as exemplary embodiment 1, except for formation of the electron transport layer by use of compound 47 instead of compound 1.


Exemplary Embodiment 11



55


The organic light emitting diode device was manufactured in a like manner as exemplary embodiment 1, except for formation of the electron transport layer by use of compound 51 instead of compound 1.

Exemplary Embodiment 12




The organic light emitting diode device was manufactured in a like manner as exemplary embodiment 1, except for formation of the electron transport layer by use of compound 57 instead of compound 1.

Exemplary Embodiment 13




The organic light emitting diode device was manufactured in a like manner as exemplary embodiment 1, except for formation of the electron transport layer by use of compound 72 instead of compound 1.

Comparative Example 1



56

An organic light emitting element was manufactured in a like manner as exemplary embodiment 1, except for usage of Alq3(tris(8-hydroxy-quinolato)aluminum) instead of compound 1 when the electron transport layer is formed.



Estimation

Characteristics of the organic light emitting diode device according to the exemplary embodiments 1 to 18 and the comparative example 1 were estimated.

The results are expressed in Table 1.

TABLE 1

	Electron Transport Layer	Voltage (V)	Efficiency (cd/A)	T90 (hr)
Exemplary Embodiment 1	Compound 1	6.0	6.1	356
Exemplary Embodiment 2	Compound 4	5.4	5.9	268
Exemplary Embodiment 3	Compound 7	5.3	5.4	394
Exemplary Embodiment 4	Compound 11	5.1	6.3	316
Exemplary Embodiment 5	Compound 17	5.6	5.1	267
Exemplary Embodiment 6	Compound 22	4.8	6.1	316
Exemplary Embodiment 7	Compound 28	4.7	8.4	282
Exemplary Embodiment 8	Compound 39	5.3	5.2	315
Exemplary Embodiment 9	Compound 43	5.36	6.7	326
Exemplary Embodiment 10	Compound 47	5.9	5.4	293
Exemplary Embodiment 11	Compound 51	5.4	5.2	264
Exemplary Embodiment 12	Compound 57	5.3	4.9	342
Exemplary Embodiment 13	Compound 72	4.7	7.1	316
Comparative Example 1	Alq3	6.4	4.8	243

Referring to Table 1, when the compounds having the structures of exemplary embodiment 1 to exemplary embodiment 13 are used as an electron transport layer in the organic light emitting diode device, the driving voltage is reduced compared to Alq3, and an excellent I-V-L characteristic with improved efficiency is provided. Particularly, the exemplary embodiments 6, 7, 17, 18, and 19 reduce the

57


driving voltage by more than 1.5 V, and the exemplary embodiments 7 and 13 provide about a 50% efficiency improvement.

By way of summation and review, embodiments provide a compound that provides an organic material with excellent optical and electrical performance. An organic electroluminescence device with a low driving voltage and improved light emission efficiency and lifespan may be manufactured by using the same.



Example embodiments have been disclosed herein, and although specific terms are employed, they are used and are to be interpreted in a generic and descriptive sense only and not for purpose of limitation. In some instances, as would be apparent to one of ordinary skill in the art as of the filing of the present application, features, characteristics, and/or elements described in connection with a particular embodiment may be used singly or in combination with features, characteristics, and/or elements described in connection with other embodiments unless otherwise specifically indicated. Accordingly, it will be understood by those of skill in the art that various changes in form and details may be made without departing from the spirit and scope thereof as set forth in the following claims.

What is claimed is:

1. An organic compound represented by Formula 1:






wherein the compound represented by Formula 1 includes at least one of the following Compounds 2 to 72:




58

-continued



59

-continued



7

5

10

15

20

25

8

30

35

40

45

9

50


55

60

65

60

-continued




10

11

12

61

-continued




5

10

15

20




25

30

35

40



50


55

60


65

62


-continued




17



18




19



20

63

-continued




20

5

10

21

15




20

25

22


30

35



23


40



45

50

24




55

60


65

64


-continued




25



26






27







28

65

-continued


**66**

-continued



67

-continued



36

5

10

15

37

20

25

30




35

38

40

45

50



39


55

60


65

68


-continued



40




41








42

69

-continued

**70**


-continued



71

-continued

49



5

10

15

20

50 25

30

35



40

51 50

55


60

65


**72**

-continued


52




53



54




55




73

-continued




**74**

-continued







75

-continued




76

-continued



77

-continued



72


5

10


15

2. An organic light emitting diode device, comprising: an anode; a cathode; and an organic layer between the anode and the cathode; the organic layer includes an electron transport layer, and the organic compound is included in the electron transport layer; wherein the organic compound is represented by Formula 1:

[Formula 1] 25




wherein the compound represented by Formula 1 includes at least one of the following Compounds 2 to 72:



2

45

50



3


55

60


65

78


-continued



4




5








6

79

-continued


**80**

-continued








81

-continued








82

-continued







83

-continued


**84**

-continued




85

-continued


**86**

-continued



87


-continued



5

10


15



20

25

30




35

40

45

50






55

60

65


88

-continued








89

-continued



90


-continued



91

-continued

49



5

10

15

20

50 25

30

35



40

51 50

55


60

65


**92**

-continued


52




53



54




55



93

-continued




5

10

57

15



20

25


58

30

35

59


40



45

60

55




60


65

94


-continued




61



62




63



64

-continued




5

10

15

20



66

30

35

40

67 50

50


55

60


65

-continued

68



69




25

66

30

35

70




45

67 50

55

60


71



97

-continued

98



专利名称(译)	有机化合物和包括其的有机发光二极管器件		
公开(公告)号	US9847492	公开(公告)日	2017-12-19
申请号	US14/595345	申请日	2015-01-13
[标]申请(专利权)人(译)	三星显示有限公司		
申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	JUNG JI YUN		
发明人	JUNG, JI YUN		
IPC分类号	H01L51/50 C07D471/04 C07D239/26 C07D401/14 C07D213/16 C07D251/24 H01L51/00 C07D401/04		
CPC分类号	H01L51/0067 C07D213/16 C07D239/26 C07D251/24 C07D401/04 C07D471/04 H01L51/0052 H01L51/0055 H01L51/0058 H01L51/0072 C07D401/14 H01L51/5072		
审查员(译)	CLARK , GREGORY		
优先权	1020140086973 2014-07-10 KR		
其他公开文献	US20160013420A1		
外部链接	Espacenet USPTO		

摘要(译)

有机化合物由式1表示。其中X 1 , X 2 , L , A 1 , A 2 , R 1 , R 2 , R 3 , R 4 和Het如说明书中所定义。

