



US010340474B2

(12) **United States Patent**
Lee

(10) **Patent No.:** **US 10,340,474 B2**
(45) **Date of Patent:** ***Jul. 2, 2019**

(54) **DISPLAY APPARATUS**

(71) Applicant: **Samsung Display Co., Ltd.**, Yongin-si (KR)

(72) Inventor: **Sangshin Lee**, Yongin-si (KR)

(73) Assignee: **Samsung Display Co., Ltd.**, Yongin-si (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **15/916,558**

(22) Filed: **Mar. 9, 2018**

(65) **Prior Publication Data**

US 2018/0198085 A1 Jul. 12, 2018

Related U.S. Application Data

(63) Continuation of application No. 15/421,608, filed on Feb. 1, 2017, now Pat. No. 9,917,275, which is a (Continued)

(30) **Foreign Application Priority Data**

Jul. 21, 2015 (KR) 10-2015-0103011

(51) **Int. Cl.**

H01L 51/52 (2006.01)

H01L 23/544 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **H01L 51/524** (2013.01); **H01L 23/544** (2013.01); **H01L 27/3244** (2013.01);

(Continued)

(58) **Field of Classification Search**

None

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

9,917,275 B2* 3/2018 Lee H01L 51/524
2006/0141737 A1 6/2006 Gaidis
(Continued)

FOREIGN PATENT DOCUMENTS

KR 10-2006-0060931 6/2006
KR 10-2007-0036188 4/2007

(Continued)

OTHER PUBLICATIONS

Non-Final Office Action dated Jun. 16, 2017 in U.S. Appl. No. 15/421,608.

(Continued)



Primary Examiner — Dung A. Le

(74) *Attorney, Agent, or Firm* — H.C. Park & Associates, PLC

(57) **ABSTRACT**

A display apparatus including a substrate having an active area and a sealing area surrounding the active area; a display unit disposed on the active area of the substrate and including a plurality of organic light-emitting devices; and a sealing member including a first portion, a second portion, and a third portion, the third portion disposed between the first portion and the second portion and connecting the first portion to the second portion.

8 Claims, 8 Drawing Sheets



Related U.S. Application Data

continuation of application No. 15/012,391, filed on
Feb. 1, 2016, now Pat. No. 9,595,690.

(51) **Int. Cl.**

H01L 27/32 (2006.01)

H01L 51/00 (2006.01)

(52) **U.S. Cl.**

CPC ... *H01L 51/0011* (2013.01); *H01L 2223/5442*
(2013.01); *H01L 2223/54426* (2013.01); *H01L*
2223/54486 (2013.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

2006/0292833	A1	12/2006	Matsushita
2007/0126334	A1	6/2007	Nakamura et al.
2012/0320502	A1	12/2012	Jung et al.
2014/0033974	A1	2/2014	Hong et al.
2014/0159078	A1	6/2014	Kim

FOREIGN PATENT DOCUMENTS

KR	10-2012-0139392	12/2012
KR	10-2014-0017767	2/2014
KR	10-2014-0075467	6/2014

OTHER PUBLICATIONS

Notice of Allowance dated Nov. 2, 2017 in U.S. Appl. No. 15/421,608.

Notice of Allowance dated Nov. 1, 2016 in U.S. Appl. No. 15/012,391.

* cited by examiner

FIG. 1




FIG. 2




FIG. 3




FIG. 5




FIG. 6




FIG. 7





FIG. 8



DISPLAY APPARATUS

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 15/421,608, filed on Feb. 1, 2017, now issued as U.S. Pat. No. 9,917,275, which is a continuation of U.S. patent application Ser. No. 15/012,391, filed on Feb. 1, 2016, now issued as U.S. Pat. No. 9,595,690, and claims priority from and the benefit of Korean Patent Application No. 10-2015-0103011, filed on Jul. 21, 2015, all of which are hereby incorporated by reference for all purposes as if fully set forth herein.

BACKGROUND

Field

Exemplary embodiments relate to a display apparatus.

Discussion of the Background

The market for display apparatuses, which may include media that allow users to communicate with each other and access information, has expanded with the development of information technology. Various kinds of display apparatuses have been developed, and organic light-emitting display (OLED) apparatuses have particularly attracted attention due to their good performance, small thickness, light weight, and low power consumption.

An organic light-emitting display apparatus may include pixels and OLEDs. The degree of light emission of each OLED may be controlled by a thin-film transistor (TFT). Such OLEDs may include a pixel electrode electrically connected to a TFT, a counter electrode facing the pixel electrode, and an intermediate layer between the pixel electrode and the counter electrode and including an organic emission layer.

One of the methods for forming the organic emission layer included in the intermediate layer may include a deposition method using a mask. That is, organic materials evaporated from vapor deposition sources may pass through openings in the mask to be deposited on a substrate, thereby forming the organic emission layer. Therefore, in order for the organic materials to be deposited at the proper position in the deposition process, it is very important to precisely position the mask with regard to the substrate.

The above information disclosed in this Background section is only for enhancement of understanding of the background of the inventive concept, and, therefore, it may contain information that does not form the prior art that is already known in this country to a person of ordinary skill in the art.

SUMMARY

Exemplary embodiments provide an organic light-emitting display apparatus that may secure a precise mask position with regard to a substrate.

Additional aspects will be set forth in part in the description which follows and, in part, will be apparent from the disclosure, or may be learned by practice of the inventive concept.

An exemplary embodiment discloses a display apparatus including a substrate having an active area and a sealing area surrounding the active area; a display unit disposed on the

active area of the substrate; a sealing member having a recess formed in the sealing area of the substrate and being concave in a direction from an edge of the substrate to the active area of the substrate or from the active area of the substrate to the edge of the substrate; and an alignment mark disposed between the recess and the edge of the substrate or between the recess and the active area of the substrate.

The foregoing general description and the following detailed description are exemplary and explanatory and are intended to provide further explanation of the claimed subject matter.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are included to provide a further understanding of the inventive concept, and are incorporated in and constitute a part of this specification, illustrate exemplary embodiments of the inventive concept, and, together with the description, serve to explain principles of the inventive concept.

FIG. 1 is a schematic perspective view of a substrate for a display apparatus, according to an exemplary embodiment.

FIG. 2 is a schematic cross-sectional view of a pixel on a substrate shown in FIG. 1.

FIG. 3 is a schematic enlarged view of region A illustrated in FIG. 1.

FIG. 4 is an enlarged schematic view of a portion of a display apparatus according to another exemplary embodiment of the inventive concept.

FIG. 5 is an enlarged schematic view of a portion of a display apparatus according to still another exemplary embodiment of the inventive concept.

FIG. 6 is an enlarged schematic view of a portion of a display apparatus according to still another exemplary embodiment of the inventive concept.

FIG. 7 is an enlarged schematic view of a portion of a display apparatus according to still another exemplary embodiment of the inventive concept.

FIG. 8 is an enlarged schematic view of a portion of a display apparatus according to still another exemplary embodiment of the inventive concept.

DETAILED DESCRIPTION OF THE ILLUSTRATED EMBODIMENTS

In the following description, for the purposes of explanation, numerous specific details are set forth in order to provide a thorough understanding of various exemplary embodiments. It is apparent, however, that various exemplary embodiments may be practiced without these specific details or with one or more equivalent arrangements. In other instances, well-known structures and devices are shown in block diagram form in order to avoid unnecessarily obscuring various exemplary embodiments.

In the accompanying figures, the size and relative sizes of layers, films, panels, regions, etc., may be exaggerated for clarity and descriptive purposes. Also, like reference numerals denote like elements.

When an element or layer is referred to as being “on,” “connected to,” or “coupled to” another element or layer, it may be directly on, connected to, or coupled to the other element or layer or intervening elements or layers may be present. When, however, an element or layer is referred to as being “directly on,” “directly connected to,” or “directly coupled to” another element or layer, there are no intervening elements or layers present. For the purposes of this disclosure, “at least one of X, Y, and Z” and “at least one

selected from the group consisting of X, Y, and Z” may be construed as X only, Y only, Z only, or any combination of two or more of X, Y, and Z, such as, for instance, XYZ, XYY, YZ, and ZZ. Like numbers refer to like elements throughout. As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items.

Although the terms first, second, etc. may be used herein to describe various elements, components, regions, layers, and/or sections, these elements, components, regions, layers, and/or sections should not be limited by these terms. These terms are used to distinguish one element, component, region, layer, and/or section from another element, component, region, layer, and/or section. Thus, a first element, component, region, layer, and/or section discussed below could be termed a second element, component, region, layer, and/or section without departing from the teachings of the present disclosure.

Spatially relative terms, such as “beneath,” “below,” “lower,” “above,” “upper,” and the like, may be used herein for descriptive purposes, and, thereby, to describe one element or feature’s relationship to another element(s) or feature(s) as illustrated in the drawings. Spatially relative terms are intended to encompass different orientations of an apparatus in use, operation, and/or manufacture in addition to the orientation depicted in the drawings. For example, if the apparatus in the drawings is turned over, elements described as “below” or “beneath” other elements or features would then be oriented “above” the other elements or features. Thus, the exemplary term “below” can encompass both an orientation of above and below. Furthermore, the apparatus may be otherwise oriented (e.g., rotated 90 degrees or at other orientations), and, as such, the spatially relative descriptors used herein interpreted accordingly.

The terminology used herein is for the purpose of describing particular embodiments and is not intended to be limiting. As used herein, the singular forms, “a,” “an,” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. Moreover, the terms “comprises,” “comprising,” “includes,” and/or “including,” when used in this specification, specify the presence of stated features, integers, steps, operations, elements, components, and/or groups thereof, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

Various exemplary embodiments are described herein with reference to sectional illustrations that are schematic illustrations of idealized exemplary embodiments and/or intermediate structures. As such, variations from the shapes of the illustrations as a result, for example, of manufacturing techniques and/or tolerances, are to be expected. Thus, exemplary embodiments disclosed herein should not be construed as limited to the particular illustrated shapes of regions, but are to include deviations in shapes that result from, for instance, manufacturing. The regions illustrated in the drawings are schematic in nature and their shapes are not intended to illustrate the actual shape of a region of a device and are not intended to be limiting.

Unless otherwise defined, all terms (including technical and scientific terms) used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this disclosure is a part. Terms, such as those defined in commonly used dictionaries, should be interpreted as having a meaning that is consistent with their meaning in the

context of the relevant art and will not be interpreted in an idealized or overly formal sense, unless expressly so defined herein.

FIG. 1 is a schematic perspective view of a substrate for a display apparatus **1000**, according to an exemplary embodiment.

Referring to FIG. 1, the display apparatus **1000** may include a substrate **100**, a display unit **200**, and an alignment mark **300**.

The substrate **100** may include an active area AA and a sealing area SA.

The active area AA is an area in which an image is displayed to the outside of the display apparatus **1000**, and the sealing area SA is an area in which an image is not displayed and which may surround the active area AA.

The alignment mark **300** may be disposed on at least one portion of the sealing area SA. That is, the alignment mark **300** may be disposed on the sealing area SA, or may be disposed over the sealing area SA and outside the sealing area SA.

The display unit **200** may be disposed on the active area AA. The display unit **200** may include one or more thin film transistors (TFTs) and display devices electrically connected to the TFTs. The display devices may be one or more suitable display devices according to the type of the display apparatus **1000**. However, hereinafter the use of organic light-emitting devices (OLEDs) will be described.

FIG. 2 is a schematic cross-sectional view of a pixel on the substrate **100** shown in FIG. 1.

The substrate **100** may include various materials, e.g., a glass material, a metal material, or a plastic material. When the display apparatus **1000** is a bottom emission-type display apparatus, in which an image is displayed to the direction of the substrate **100**, the substrate **100** may include a transparent material. On the other hand, when the display apparatus **1000** is a top emission-type display apparatus, in which an image is displayed away from the substrate **100**, the substrate **100** may not necessarily include a transparent material.

A buffer layer **212** may be formed on the substrate **100**. The buffer layer **212** may prevent impure elements from permeating the substrate **100**, may provide a flat surface on the substrate **100**, and may include various materials capable of performing such functions. For example, the buffer layer **212** may include inorganic materials, such as silicon oxide (SiO_x), silicon nitride (SiN_x), and silicon oxynitride (SiO_xN_y).

An active layer **221** may be formed on the buffer layer **212** of an inorganic semiconductor material, such as silicon, or an organic semiconductor material. The active layer **221** may include a source area, a drain area, and a channel area between the source area and drain area. For example, when the active layer **221** is formed of amorphous silicon, the active layer **221** including the source area, the drain area, and the channel area between the source area and drain area may be formed by forming and crystallizing an amorphous silicon layer on an entire surface of the substrate **100**, forming a polycrystalline silicon layer, patterning the polycrystalline silicon layer, and respectively doping a source area and a drain area at respective edges of the polycrystalline silicon layer with impurities.

A gate insulating film **213** may be formed on the active layer **221**. The gate insulating film **213** may be used to insulate the active layer **221** from a gate electrode **222**. The gate insulating film **213** may include an inorganic material, such as SiN_x , SiO_2 , etc.

The gate electrode **222** may be formed on the gate insulating film **213**. The gate electrode **222** may be connected to a gate line (not shown) transmitting on/off signals of the TFT.

The gate electrode **222** may contain gold (Au), silver (Ag), copper (Cu), nickel (Ni), platinum (Pt), palladium (Pd), aluminum (Al), and molybdenum (Mo), and may include an alloy, such as an Al:Nd alloy, an Mo:W alloy, etc., but is not limited thereto. The gate electrode **222** may include various materials by taking into account various design considerations.

An interlayer insulating film **214**, formed on the gate electrode **222**, may be used to insulate the gate electrode **222**, a source electrode **223**, and a drain electrode **224** from one another. The interlayer insulating film **214** may include an inorganic material such as SiN_x, SiO₂, etc.

The source electrode **223** and the drain electrode **224** may be formed on the interlayer insulating film **214**. In more detail, the interlayer insulating film **214** and the gate insulating film **213** may expose parts of the source area and the drain area of the active layer **221**, and the source electrode **223** and the drain electrode **224** may respectively contact the exposed parts of the source area and the drain area of the active layer **221**.

Although a top gate-type TFT, in which the gate electrode **222**, the source electrode **223**, and the drain electrode **224** are sequentially formed, is illustrated in FIG. 2, the exemplary embodiments are not limited thereto. The gate electrode **222** may be disposed below the active layer **221**.

A TFT **200a** may be electrically connected to OLEDs **200b** to drive the OLEDs **200b**, and may be protected by being covered by a protective film **215**.

The protective film **215** may include a general-purpose polymer, such as polymethyl methacrylate (PMMA) or polystyrene (PS), a polymeric derivative having a phenol-based group, an acryl-based polymer, an imide-based polymer, an aryl ether-based polymer, an amide-based polymer, a fluorine-based polymer, a p-xylene-based polymer, a vinyl alcohol-based polymer, or a mixture thereof.

The OLEDs **200b** may each include a pixel electrode **231**, an intermediate layer **232**, and a counter electrode **233**.

The pixel electrode **231** may be formed on the protective film **215**, and may be electrically connected to the drain electrode **224** via a contact hole **230** which is formed in the protective film **215**.

The pixel electrode **231** may be a transparent (translucent) electrode or a reflective electrode. When the pixel electrode **231** is the transparent (translucent) electrode, the pixel electrode **231** may include indium tin oxide (ITO), indium zinc oxide (IZO), zinc oxide (ZnO), indium oxide (In₂O₃), indium gallium oxide (IGO), or aluminum zinc oxide (AZO). When the pixel electrode **231** is a reflective electrode, the pixel electrode **231** may include a reflective layer including silver (Ag), magnesium (Mg), aluminum (Al), platinum (Pt), palladium (Pd), gold (Au), nickel (Ni), neodymium (Nd), iridium (Ir), chromium (Cr), or a compound thereof, and a layer including ITO, IZO, ZnO, In₂O₃, IGO, or AZO. However, the pixel electrode **231** is not limited thereto and may include various other materials. Also, the pixel electrode **231** may have either a single-layer structure or a multilayer structure.

The counter electrode **233** facing the pixel electrode **231** may be a transparent (translucent) electrode or a reflective electrode. When the counter electrode **233** is a transparent (translucent) electrode, the counter electrode **233** may include a layer including metals having a low work function, such as lithium (Li), calcium (Ca), lithium fluoride/calcium

(LiF/Ca), lithium fluoride/aluminum (LiF/Al), aluminum (Al), magnesium (Mg), or a combination thereof, and a transparent (translucent) layer including ITO, IZO, ZnO, In₂O₃, or the like. When the counter electrode **233** is a reflective electrode, the counter electrode **233** may include a layer including Li, Ca, LiF/Ca, LiF/Al, Al, Mg, or a combination thereof. Structures and materials of the counter electrode **233** are not limited thereto and may vary.

Thus, the counter electrode **233** may allow light emitted from an organic emission layer (not shown) included in the intermediate layer **232** to pass through. That is, the light emitted from the organic emission layer (not shown) may be reflected directly or via the pixel electrode **231**, which is a reflective electrode, and may be emitted toward the counter electrode **233**.

However, the display apparatus **1000** of the present exemplary embodiment is not limited to a top emission-type, and may instead be a bottom emission-type in which the light emitted from the organic emission layer (not shown) is emitted toward the substrate **100**. In this case, the pixel electrode **231** may be a transparent or semi-transparent electrode, and the counter electrode **233** may be a reflective electrode. The organic light-emitting display apparatus **1000** of the present embodiment may also be a dual emission-type in which light is emitted in both directions of front and bottom surfaces thereof.

A pixel-defining film **216** may be formed on the first electrode **231** as an insulating material. The pixel-defining film **216** may include at least one organic insulating material selected from polyimide, polyamide, acryl resin, benzocyclobutene (BCB), and phenol resin, by spin coating, or the like. The pixel-defining film **216** may expose a region of the pixel electrode **231**, and the intermediate layer **232** with the organic emission layer may be located on the exposed region of the pixel electrode **231**.

The intermediate layer **232** may selectively further include a functional layer, such as a hole transport layer (HTL), a hole injection layer (HIL), an electron transport layer (ETL), an electron injection layer (EIL), etc., in addition to the organic emission layer.

The organic emission layer (not shown) included in the intermediate layer **232** may include a low molecular weight organic material or a high molecular weight organic material. Examples of the low molecular weight organic material may include copper phthalocyanine (CuPc), N,N'-Di(naphthalene-1-yl)-N,N'-diphenyl-benzidine (NPB), and tris-8-hydroxyquinoline aluminum (Alq3). Examples of the high molecular weight organic material may include a polyphenylenevinylene (PPV)-based material and a polyfluorene-based material.

There are various methods of forming the organic emission layer. For example, the low molecular weight organic material or the high molecular weight organic material may be vacuum-deposited to form the organic emission layer. The organic emission layer may be formed along with the pixel electrode **231** and the counter electrode **233**, and various functional layers of the intermediate layer **232**, or separately. Hereinafter it will be described that the organic emission layer is formed separately from an electrode layer and a functional layer for convenience of explanation.

In order to form the organic emission layer by vacuum deposition, a deposition mask having openings corresponding to the pattern of the organic emission layer may be used. The deposition mask may be disposed in close contact with the substrate **100** via a supporting implement, such as a vacuum suction implement and a magnet unit. In order to align the deposition mask with the substrate **100**, the align-

ment mark **300** may be disposed on a surface of the substrate **100**, as shown in FIG. 1. The alignment mark **300** will be described in detail with reference to FIG. 3.

The deposition mask may be a plate-shape member that has openings corresponding to the pattern of the object to be deposited. A material of the deposition mask may be a metal material, such as a metal of an alloy, a functional polymer, or a mixture of a polymer and a metal. The openings of the deposition mask may penetrate the deposition mask and include one or more slits.

The pixel electrode **231**, the intermediate layer **232**, and the counter electrode **233** may be sequentially formed, followed by sealing the substrate **100** and an encapsulation substrate (not shown). The method of sealing the substrate **100** and the encapsulation substrate may include disposing a sealing member **400** between the substrate **100** and the encapsulation substrate, and then compressing the substrate **100** and the encapsulation substrate. The encapsulation substrate may have a form similar to that of the substrate **100**. Hereinafter, the sealing member will be described with reference to FIGS. 3 to 5.

FIG. 3 is a schematic enlarged view of region A illustrated in FIG. 1. FIG. 4 is a schematic enlarged view of a portion of a display apparatus according to another exemplary embodiment of the inventive concept.

For convenience of explanation, the length direction of the sealing member **400** is indicated as the Y direction, and the width direction of the sealing member **400**, which is perpendicular to the length direction, is indicated as the X direction.

Referring to FIG. 3, the sealing member **400** may be located on the sealing area SA, which is outside the active area AA of the substrate **100**. The sealing member **400** seals a display unit from outside of the active area AA to thereby prevent impurities, such as moisture or air from outside, from permeating into the display unit.

For example, the sealing member **400** may include frit. The sealing member **400** may be formed by forming a paste including frit at the sealing area SA of the substrate **100**, and then melting and hardening the paste including the frit. The frit may include vanadium oxide (VO_2) or bismuth oxide (Bi_2O_3), and may further include various materials, such as at least one of tellurium dioxide (TeO_2), zinc oxide (ZnO), barium oxide (BaO), niobium pentoxide (Nb_2O_5), silicon oxide (SiO_2), aluminum oxide (Al_2O_3), zirconium oxide (ZrO_2), and phosphorus pentoxide (P_2O_5). The sealing member **400** may also include fillers including various materials to improve sealing properties.

The sealing member **400** may include a recess **411**, which is concave in a direction from an edge E of the substrate **100** to the active area AA. For convenience of explanation, with regard to the sealing member **400**, a portion where the recess **411** is located is referred to as a first portion **401**, a portion adjacent to the first portion **401** is referred to as a second portion **402**, and a portion between the first portion **401** and the second portion **402** is referred to as a third portion **403**.

As shown in FIG. 3, a width W1 of the first portion **401** may be the same as a width W2 of the second portion **402**. As the sealing member **400** is first curved from the Y direction to the X direction, and then curved from the X direction to the Y direction, a width W3 of the third portion **403** connecting the first portion **401** and second portion **402** may be greater than the width W1 of the first portion **401** and the width W2 of the second portion **402**.

When the sealing member **400** is formed in such a shape, the alignment mark **300** for aligning the substrate **100** with a deposition mask (not shown) may be disposed between the

concave recess **411** of the sealing member **400** and the edge E of the substrate **100**. Regarding the method of preparation, first, the substrate **100** having the alignment mark **300** formed thereon at a predetermined position may be prepared. After completely forming the display unit **200** on the substrate **100**, the sealing member **400** between the alignment mark **300** and the display unit **200** may be formed. Accordingly, at least one portion of the alignment mark **300** may be on the sealing area SA, thus reducing a dead space, which is unnecessary and outside the sealing area SA.

The alignment mark **300** may include a plurality of marks. For example, the alignment mark **300** may include a rod-shape first mark **301** including two long sides parallel to the X direction and/or a rod-shape second mark **302** including two long sides parallel to the Y direction. The first mark **301** and the second mark **302** may be spaced apart. Accordingly, a central line L1 of the first mark **301** and a central line L2 of the second mark **302** may be perpendicular to each other.

The alignment mark **300** may further include a third mark **303**. The third mark **303** may be an organic material pattern for testing, which may be formed prior to or simultaneously with the formation of an organic emission layer. The third mark **303** may include a same material as that of the organic emission layer. One or more third marks **303** may be formed for each color pixel.

In relation to the third mark **303**, by using the position relationship between the first mark **301** and the second mark **302**, the alignment error between the substrate **100** and a deposition mask may be determined. For example, distance differences in the X direction and the Y direction, between the point where the central line L1 of the first mark **301** intersects the central line L2 of the second mark **302** and the center of the third mark **303**, may be defined as the alignment error between the substrate **100** and the deposition mask. In order to detect the alignment error between the substrate **100** and the deposition mask, an opening corresponding to the third mark **303** may be formed in the deposition mask, which is an organic material pattern for testing, in addition to the openings corresponding to the organic emission layer. The opening corresponding to the third mark **303** may have the same size, shape, and alignment direction as the openings corresponding to the organic emission layer.

The alignment mark **300** may further include a fourth mark **304**, in addition to the first to third marks **301** to **303**. The fourth mark **304** is for verifying the alignment between the substrate **100** and measuring equipment, and may have a cross shape.

The above described plurality of marks may be disposed to be parallel to the Y direction, which is a length direction of the sealing member **400**. The plurality of marks may constitute one or more columns, which are each perpendicular to the Y direction. For example, as shown in FIG. 3, the first mark **301** and the second mark **302** may be in different columns and spaced apart from each other. Accordingly, several third marks **303**, which are organic material patterns for testing, may be formed outside of the active area AA.

In this regard, the position, number, shape of the plurality of marks are not limited to the described exemplary embodiments, but may vary depending on a design.

FIG. 3 illustrates that the sealing member **400** includes the recess **411**, which is concave in a direction from the edge E of the substrate **100** to the active area AA. However, the sealing member **400** may include a recess formed in the opposite direction.

Referring to FIG. 4, the sealing member **400** may include the recess **411**, which is concave in a direction from the

active area AA of the substrate **100** to the edge E of the substrate **100**. The shape of the sealing member **400** may be the same as the shape of the sealing member where the sealing member **400** illustrated in FIG. **3** is symmetrically rotated about a central line LS of the sealing area SA. Therefore, the alignment mark **300** may be disposed between the concave recess **411** of the sealing member **400** and the active area AA.

FIGS. **5** and **6** are schematic enlarged views of a portion of a display apparatus according to still another exemplary embodiment of the inventive concept. Hereinafter, with reference to FIGS. **3** and **4**, descriptions of portions that are the same or similar to the above described portions will not be repeated for convenience. The same is applied to the following examples and modifications.

Referring to FIG. **5**, the sealing member **400** may include the recess **411**, which is concave in a direction from the edge E of the substrate **100** to the active area AA. For convenience of explanation, with regard to the sealing member **400**, a portion where the recess **411** is located is referred to as the first portion **401**, a portion adjacent to the first portion **401** is referred to as the second portion **402**, and a portion between the first portion **401** and the second portion **402** is referred to as the third portion **403**.

The width W1 of the first portion **401**, the width W2 of the second portion **402**, and the width W3 of the third portion **403** may be the same as one another. In other words, the width of the sealing member **400** may be constant along the whole length of the sealing member **400**. FIG. **5s** illustrates that both edges of the third portion **403** of the sealing member **400** are curved, but the exemplary embodiments are not limited thereto. That is, both edges of the third portion **403** may be straight.

The alignment mark **300** may be disposed between the concave recess **411** of the sealing member **400** and the edge E of the substrate **100**. Accordingly, at least one portion of the alignment mark **300** may be disposed on the sealing area SA, helping to align the substrate **100** with a deposition mask and reduce a dead space.

FIG. **5** illustrates that the sealing member **400** includes the recess **411**, which is concave in a direction from the edge E of the substrate **100** to the active area AA. However, the sealing member **400** may include a recess formed in the opposite direction.

Referring to FIG. **6**, the sealing member **400** may include the recess **411**, which is concave in a direction from the active area AA of the substrate **100** to the edge E of the substrate **100**. The shape of the sealing member **400** may be the same as that of the sealing member **400** illustrated in FIG. **5**, where the sealing member **400** is symmetrically rotated about the central line LS of the sealing area SA. Therefore, the alignment mark **300** may be disposed between the concave recess **411** of the sealing member **400** and the active area AA.

FIGS. **7** and **8** are schematic enlarged views of a portion of a display apparatus according to still another exemplary embodiment of the inventive concept. Hereinafter, with reference to FIGS. **3** and **6**, descriptions of portions the same or similar to the above described portions will not be repeated for convenience.

Referring to FIG. **7**, the sealing member **400** may include the recess **411**, which is concave in a direction from the edge E of the substrate **100** to the active area AA. For convenience of explanation, with regard to the sealing member **400**, a portion where the recess **411** is located is referred to as the first portion **401** and a portion adjacent to the first portion **401** is referred to as the second portion **402**

The width W1 of the first portion **401** may be less than the width W2 of the second portion **402**.

The alignment mark **300** may be disposed between the concave recess **411** of the sealing member **400** and the edge E of the substrate **100**. In the sealing member, the edges of the first portion **401** and the second portion **402** on a side of the active area AA may be aligned in a straight line. Accordingly, the width W1 of the first portion **401** may correspond to the difference between the width W2 of the second portion **402** and a width W4, which is a width in the X direction of the recess **411**.

Accordingly, at least one portion of the alignment mark **300** may be disposed on the sealing area SA, helping to align the substrate **100** with a deposition mask and to reduce a dead space. Because the alignment mark **300** is formed on a portion of the substrate **100**, the length (in the Y direction) of the first portion **401**, which may have a decreased width of the sealing member **400** due to the alignment mark **300**, may be much less than the entire length of the sealing member **400**. Therefore, even if the sealing member **400** has the first portion **401**, problems, such as a decrease of adhesion between the substrate **100** and an encapsulation substrate, may not arise.

In FIG. **7** illustrates that the sealing member **400** includes the recess **411**, which is concave in a direction from the edge E of the substrate **100** to the active area AA. However, the sealing member **400** may include a recess formed in the opposite direction.

Referring to FIG. **8**, the sealing member **400** may include the recess **411**, which is concave in a direction from the active area AA of the substrate **100** to the edge E of the substrate **100**. The shape of the sealing member **400** may be the same as that of the sealing member **400** illustrated in FIG. **7**, where the sealing member **400** is symmetrically rotated about the central line LS of the sealing area SA. Therefore, the alignment mark **300** may be disposed between the concave recess **411** of the sealing member **400** and the active area AA.

As described above, the display apparatus according to an exemplary embodiment may have increased mask position precision with regard to a substrate, and have a decreased dead space on the substrate.

Although certain exemplary embodiments and implementations have been described herein, other embodiments and modifications will be apparent from this description. Accordingly, the inventive concept is not limited to such embodiments, but rather to the broader scope of the presented claims and various obvious modifications and equivalent arrangements.

What is claimed is:

1. A display apparatus comprising:

- a substrate comprising an active area and a sealing area surrounding the active area;
- a display unit disposed in the active area of the substrate, and comprising a plurality of organic light-emitting devices; and
- a sealing member disposed in the sealing area, the sealing member comprising:
 - a lower sealing member extending in a first direction;
 - an upper sealing member positioned at an opposite side of the active area from the lower sealing member; and
 - a right sealing member and a left sealing member extending in a second direction intersecting the first direction,

11

wherein:

the upper sealing member comprises a first portion, a second portion, and a third portion, the third portion disposed between the first portion and the second portion and connecting the first portion to the second portion;

the first portion and the second portion extend in the first direction; and

the first portion is located closer to the lower sealing member than the second portion.

2. The display apparatus of claim 1, wherein a width of the third portion is substantially equal to a width of the first portion and a width of the second portion.

3. The display apparatus of claim 1, wherein the upper sealing member is first curved from the first direction to the second direction substantially perpendicular to the first direction, and then curved from the second direction to the first direction.

12

4. The display apparatus of claim 3, wherein the first direction is a length direction of the upper sealing member, and the second direction is a width direction of the upper sealing member.

5. The display apparatus of claim 1, further comprising an alignment mark disposed between the first portion and the edge of the substrate.

6. The display apparatus of claim 5, wherein the alignment mark comprises a plurality of marks, and at least one of the marks is arranged parallel to the first direction.

7. The display apparatus of claim 5, wherein the alignment mark comprises an organic material.

8. The display apparatus of claim 1, wherein the third portion extends in a third direction different from the first direction and the second direction.

* * * * *

专利名称(译)	显示装置		
公开(公告)号	US10340474	公开(公告)日	2019-07-02
申请号	US15/916558	申请日	2018-03-09
[标]申请(专利权)人(译)	三星显示有限公司		
申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	LEE SANGSHIN		
发明人	LEE, SANGSHIN		
IPC分类号	H01L51/52 H01L23/544 H01L27/32 H01L51/00		
CPC分类号	H01L51/524 H01L23/544 H01L27/3244 H01L2223/54486 H01L2223/5442 H01L2223/54426 H01L51/0011		
优先权	1020150103011 2015-07-21 KR 15/012391 2017-03-14 US		
其他公开文献	US20180198085A1		
外部链接	Espacenet		

摘要(译)

一种显示装置，包括具有有源区的基板和围绕有源区的密封区域；显示单元，设置在基板的有源区上，并包括多个有机发光装置；密封件包括第一部分，第二部分和第三部分，第三部分设置在第一部分和第二部分之间，并将第一部分连接到第二部分。

