



US009786721B1

(12) **United States Patent**
Tang

(10) **Patent No.:** **US 9,786,721 B1**
(45) **Date of Patent:** **Oct. 10, 2017**

(54) **OLED DISPLAY PANEL**

(71) Applicant: **Wuhan China Star Optoelectronics Technology Co., Ltd.**, Wuhan, Hubei (CN)

(72) Inventor: **Yuejun Tang**, Shenzhen (CN)

(73) Assignee: **Wuhan China Star Optoelectronics Technology Co., Ltd.**, Wuhan, Hubei (CN)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **15/186,466**

(22) Filed: **Jun. 18, 2016**

(30) **Foreign Application Priority Data**

May 18, 2016 (CN) 2016 2 0456894 U

(51) **Int. Cl.**
H01L 27/32 (2006.01)
H01L 51/52 (2006.01)

(52) **U.S. Cl.**
CPC **H01L 27/322** (2013.01); **H01L 27/3246** (2013.01); **H01L 27/3248** (2013.01); **H01L 51/5256** (2013.01); **H01L 51/5259** (2013.01)

(58) **Field of Classification Search**
CPC H01L 27/322; H01L 27/3246; H01L 27/3248; H01L 51/5256; H01L 51/5259
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,649,311 B2 * 1/2010 Park H01L 27/322 257/E31.095
8,604,687 B2 * 12/2013 Wang H01L 27/322 313/504

8,969,904 B2 * 3/2015 Chao H01L 51/0024 257/40
9,508,779 B2 * 11/2016 Cheng H01L 51/0024
2006/0146033 A1 * 7/2006 Chen G02F 1/13338 345/173
2014/0190621 A1 * 7/2014 Kawata B32B 38/10 156/155
2015/0123085 A1 * 5/2015 Kim H01L 51/5284 257/40
2015/0194392 A1 * 7/2015 Kawata H01L 21/022 257/644
2015/0249120 A1 * 9/2015 Cheng H01L 51/56 257/40
2015/0325632 A1 * 11/2015 Cheng H01L 51/0024 257/40
2015/0380671 A1 * 12/2015 Shu G02F 1/133617 257/13
2016/0020259 A1 * 1/2016 Cheng H01L 27/326 257/40
2016/0036004 A1 * 2/2016 Cheng H01L 51/5253 257/40
2016/0087018 A1 * 3/2016 Shim H01L 51/5284 257/40
2016/0093677 A1 * 3/2016 Tseng G02B 5/201 362/84

(Continued)



Primary Examiner — Ida M Soward

(74) *Attorney, Agent, or Firm* — Andrew C. Cheng

(57) **ABSTRACT**

The utility model provides an OLED display panel, by disposing a color filter layer on an array substrate, an alignment process of an upper with a lower substrate can be omitted, the manufacturing process of the OLED display panel can be simplified, and a thin film packaging can be carried out on the color filter layer so that the OLED display panel can become more lightweight and thin.

2 Claims, 4 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2016/0116794 A1* 4/2016 Song G02F 1/133345
349/43
2016/0246111 A1* 8/2016 Chen H04N 9/12
2016/0276617 A1* 9/2016 Qi H01L 51/5212
2016/0315283 A1* 10/2016 Kim H01L 27/3246
2016/0322437 A1* 11/2016 Sakamoto H01L 27/3246
2016/0372532 A1* 12/2016 Song H01L 27/322
2017/0016930 A1* 1/2017 Qiu G01P 15/0802

* cited by examiner




FIG. 1




FIG. 4




FIG. 5

1

OLED DISPLAY PANEL

TECHNICAL FIELD

The utility model relates to the field of display technology, and more particularly to an OLED display panel.

DESCRIPTION OF RELATED ART

An organic light-emitting diode (OLED) has self-luminous capability and therefore there is no need of a backlight source and meanwhile has outstanding characteristics of high contrast, thinness, wide viewing angle, fast response, applicable to flexible panels, wide operating temperature range, simple structure and so on and thus is known as a new technology for the next generation of flat panel display device.

At present, a conventional OLED display panel includes an array substrate and a color filter. A light-emitting layer is disposed on the array substrate, and white light emitted from a light-emitting device located in the light-emitting layer would pass through the color filter so as to achieve a RGB three-primary color display. Therefore, the conventional white light OLED display panel needs to be used in conjunction with the upper substrate of color filter so as to achieve the RGB three-primary color display, the upper substrate and the lower substrate need to be aligned and bonded together with each other, which go against the thin film encapsulation of OLED display panel to realize the purpose of lightweight and thin, so that the thickness of the OLED display panel is relatively large.

SUMMARY

Accordingly, the utility model provides an OLED display panel, by disposing a color filter layer on an array substrate, an alignment process of an upper substrate with a lower substrate can be omitted and the OLED display panel can reach to be lightweight and thin.

In order to solve the above technical issues, the utility model provides an OLED display panel including an array substrate and a color filter layer, and the color filter layer being disposed on the array substrate.

In an embodiment, the array substrate includes a cathode layer disposed on the top of the array substrate, and the color filter layer is disposed on the cathode layer.

In an embodiment, a second thin film layer is disposed on a surface of the color filter layer away from the cathode layer.

In an embodiment, a first thin film layer further is disposed between the cathode layer and the color filter layer.

In an embodiment, the first thin film layer and the second thin film layer each are a plurality of organic and inorganic layers being alternately stacked.

In an embodiment, the organic layer includes a single layer or a stacked layer formed by polyethylene terephthalate, polyimide, polycarbonate, an epoxy resin, polyethylene and/or polyacrylate. The inorganic layer includes a single layer or a stacked layer formed by a metal oxide(s) or a metal nitride(s).

In an embodiment, the color filter layer includes an R photoresist, a G photoresist and a B photoresist adjacent to one after another.

In an embodiment, the array substrate includes: a base substrate; a buffer layer disposed on the base substrate; a plurality of TFTs disposed on the buffer layer; a planarization layer disposed on the plurality of TFTs and disposed

2

with via holes; an anode layer disposed discontinuously on the planarization layer and connected to the plurality of TFTs by the via holes; a light-emitting layer disposed on the anode layer, and a pixel defining layer disposed adjacent to the light-emitting layer.

In an embodiment, any adjacent two of the R photoresist, the G photoresist and the B photoresist have a black matrix disposed therebetween, and the black matrix is disposed opposite to the pixel defining layer.

In an embodiment, the array substrate further includes a package cover plate disposed on the second thin film layer.

By way of the above solutions, efficacy can be achieved by the utility model is that: distinguished from the prior art, the OLED display panel associated with the utility model, by disposing the color filter layer on the cathode layer of the array substrate, the OLED display panel can omit/avoid an alignment process of an upper substrate with a lower substrate, the manufacturing process thereof can be simplified, and a thin film packaging can be performed on the color filter layer so that the OLED display panel can become more lightweight and thin.

BRIEF DESCRIPTION OF THE DRAWINGS

The above and other aspects, features and advantages of embodiments of the utility model will be more apparent from the following detailed description taken in conjunction with the accompanying drawings, in which:

FIG. 1 is a schematic sectional view of an OLED display panel according to a first embodiment of the utility model;

FIG. 2 is a schematic sectional view of an OLED display panel according to a second embodiment of the utility model;

FIG. 3 is a schematic sectional view of an OLED display panel according to a third embodiment of the utility model; and

FIG. 4 is a schematic sectional view of an OLED display panel according to a fourth embodiment of the utility model.

FIG. 5 is a schematic sectional view of the first thin film layer 140 or the second thin film layer 130 according to an embodiment of the utility model.

DETAILED DESCRIPTION OF EMBODIMENTS

In the following, various embodiments of the utility model will be described in detail with reference to accompanying drawings. The utility model may be embodied in many different forms and should not be construed as limiting to the embodiments set forth herein. Rather, these embodiments are provided to explain the principles of the utility model and its practical applications, so that other skilled in the art can understand various embodiments of the utility model and various modifications suitable for specific intended applications.

Please refer to FIG. 1, which is a schematic sectional view of an OLED display panel according to a first embodiment of the utility model. As shown in FIG. 1, the OLED display panel of the illustrated embodiment includes an array substrate 110 and a color filter layer 120 disposed on the array substrate 110 e.g., as a part of the array substrate 110. A material of the color filter layer 120 includes but is not limited to a resin. The resin is an organic material, can play a role of color filtering and has a high elasticity. A cathode layer 116 is disposed on the top of the array substrate 110, and the color filter layer 120 is disposed on the cathode layer 116.

In the illustrated embodiment, the array substrate **110** is a conventional top-gate type TFT (thin film transistor) array substrate and includes: a base substrate **101**, a buffer layer **102** disposed on the base substrate **101** and a plurality of TFTs **103** disposed on the buffer layer **102**. Herein, the TFTs **103** refer to a thin film transistor active matrix. The TFTs **103** each include a semiconductor layer **104** disposed on the buffer layer **102**, a gate insulating layer **105** disposed on the buffer layer **102** and covering the semiconductor layer **104**, a gate electrode **107** disposed on the gate insulating layer **105**, and a source electrode **108** and a drain electrode **109** respectively disposed on two sides of the semiconductor layer **104**.

In other embodiment, the TFTs **103** each may be a conventional thin film transistor with bottom-gate structure instead and thus will not be repeated herein.

In addition, the array substrate **110** further includes a planarization layer **111**, an anode layer **113**, a light-emitting layer **114**, a pixel defining layer **115** and the cathode layer **116** all disposed on the plurality of TFTs **103**. An interlayer insulating layer **106** is disposed between the planarization layer **111** and the gate insulating layer **105**. The interlayer insulating layer **106** is disposed covering a gate electrode **107** and on the gate insulating layer **105**. The planarization layer **111** is disposed on the interlayer insulating layer **106** and covering the source electrode **108** as well as the drain electrode **109**. A plurality of via holes are formed/disposed on the planarization layer **111**. The anode layer **113** is discontinuously disposed on (e.g., penetrating through) the planarization layer **111**, and the anode layer **113** is electrically connected to the drain electrode **109** of each TFT **103** by a corresponding one of the via holes **112** disposed on the planarization layer **111**. In some embodiment, the anode layer **113** is a reflective film formed by one or more than one of gold (Au), platinum (Pt), nickel (Ni), tungsten (W), chromium (Cr), molybdenum (Mo), iron (Fe), cobalt (Co), copper (Cu), palladium (Pd), titanium (Ti) and their compounds. In other embodiment, the anode layer **113** may include at least one transparent film formed by a compound with high work function such as ITO (indium tin oxide), IZO (indium zinc oxide), AZO (aluminum-doped zinc oxide) or ZnO (zinc oxide). The array substrate **110** is disposed with the plurality of TFTs **103**, the planarization layer **111** is disposed with the plurality of via holes **112**, and the anode layer **113** is electrically connected to the TFTs **103** by respective via holes **112**.

The light-emitting layer **114** correspondingly is disposed above the anode layer **113**. The pixel defining layer **115** and the light-emitting layer **114** are disposed adjacent to and alternate with each other. In some embodiment, the cathode layer **116** is formed on the light-emitting layer **114** and the pixel defining layer **115**. The cathode layer **116** contains a transparent metal, and the transparent metal may be constituted by a metal mixture with low work function of Mg (magnesium) and Ag (silver), LiF (lithium fluoride) and Al (aluminum), or Li (lithium) and Al (aluminum), or constituted by metals such as Li (lithium), Ca (calcium), Ag (silver) and Al (aluminum).

The color filter layer **120** is disposed on the cathode layer **160**. The color filter layer **120** includes an R photoresist (red photoresist) **121**, a G photoresist (green photoresist) **122** and a B photoresist (blue photoresist) **123** disposed adjacent to one after another. The R photoresist **121**, the G photoresist **122** and the B photoresist **123** are disposed corresponding to respective discrete portions of the light-emitting layer **114**. Preferably, a thickness of the color filter layer **120** is greater than or equal to a thickness of the pixel defining layer **115**.

In addition, in other embodiment, in order to increase the brightness of the OLED display panel **100**, the color filter layer **120** may further include a white light transmissive region (not shown in the drawings).

The OLED display panel **100** further includes a second thin film layer **130** disposed on a surface of the color filter layer **120** away from the cathode layer **116**. The second thin film layer **130** is used for encapsulating/packaging the OLED display panel **100**, so as to avoid the OLED display panel **110** to be affected by external environment and relieve performance degradation of the OLED display panel caused by moisture and oxygen.

Sum up, the illustrated embodiment disposes the color filter layer **120** on the cathode layer **116** of the array substrate **110**, which can omit/avoid an alignment process of an upper substrate with a lower substrate, simplify the manufacturing process of the OLED display panel **100**, and realize a thin film encapsulation/packaging on the color filter layer **120** to thereby make the OLED display panel **100** be more lightweight and thin.

Referring to FIG. 2, which is a schematic sectional view of an OLED display panel according to a second embodiment of the utility model. A main difference between the present embodiment and the first embodiment is that a first thin film layer **140** is disposed between the cathode layer **116** and the color filter layer **120**.

As shown in FIG. 1 and FIG. 2, the first thin film layer **140** and the second thin film layer **130** of the OLED display panels **100** in the first embodiment and the second embodiment each are a plurality of organic layers (**140a** and **130a**, or alternatively, **140b** and **130b** shown in FIG. 5) and inorganic layers (**140b** and **130b**, or alternatively, **140a** and **130a** shown in FIG. 5) being alternately stacked. The organic layer includes a single layer or a stacked layer formed by polyethylene terephthalate, polyimide, polycarbonate, an epoxy resin, polyethylene and/or polyacrylate. The inorganic layer includes a single layer or a stacked layer formed by a metal oxide(s) or a metal nitride(s), for example, the inorganic layer may include any one of SiN_x (silicon nitride), Al₂O₃ (aluminum oxide), SiO₂ (silicon oxide) and TiO₂ (titanium dioxide). Therefore, by disposing the first thin film layer **140** and the second thin film layer **130** on the OLED display panel **100**, which can avoid the OLED display panel **100** to be affected by external environment and relieve performance degradation of the OLED display panel caused by moisture and oxygen.

In addition, a buffer layer (not shown in the drawing) may be disposed between the cathode layer **116** and the color filter layer **120**. A material of the buffer layer includes but is not limited to any one of TiO₂ (titanium dioxide), SiN_x (silicon nitride) and SiO_x (silicon oxide) or a combination thereof. By setting the buffer layer, the first thin film layer **140** is not easy to be damage during a process of forming the color filter layer **120**.

Please further refer to FIG. 3, which is a schematic sectional view of an OLED display panel according to a third embodiment of the utility model. A main difference between the OLED display panel **100** as shown in FIG. 3 and the OLED display panel **100** of the embodiment associated with FIG. 2 is that: in the OLED display panel **100** of the embodiment associated with FIG. 3, each adjacent two of the R photoresist **121**, the G photoresist **122** and the B photoresist **123** of the color filter layer **120** are disposed with a black matrix **170** therebetween. The black matrix **170** and the pixel defining layer **115** are disposed opposite to each other, and the effect of the black matrix **170** is for blocking light rays directed to two sides of each photoresist in the

5

color filter layer **120** and emitted from a light-emitting region of a white organic light-emitting diode in the light-emitting layer **114**, and thereby avoiding a color mixing phenomenon. Preferably, a thickness of the black matrix **170** is less than or equal to a thickness of the color filter layer **120**.

Please further refer to FIG. 2 and FIG. 4 together, FIG. 4 is a schematic sectional view of an OLED display panel according to a fourth embodiment of the utility model. A main difference between the embodiment of FIG. 4 and the embodiment of FIG. 2 is that: a package cover plate **150** further is disposed on the second thin film layer **130**, and a desiccant **160** is disposed between the package cover plate **150** and the second thin film layer **130**. The desiccant **160** is used for absorbing moisture of the OLED display panel **100**, and a material of the desiccant **160** may be anhydrous copper sulfate, anhydrous cobalt chloride, glycerol, trimethylolpropane, triethanolamine, ethylene glycol or any other material can absorb moisture. The package cover plate **150** is used for blocking penetration of external moisture and oxygen.

The OLED display panel of any one of the above embodiments may be applied to mobile phones, tablet PCs, televisions, monitors, navigators and other display devices with displaying function.

In summary, as to the OLED display panel of the utility model, by disposing the color filter layer on the array substrate, the OLED display panel can omit/avoid an alignment process of upper and lower substrates, a manufacturing process thereof can be simplified, and a thin film encapsu-

6

lation/packaging can be performed on the color filter layer so that the OLED display panel can become more lightweight and thin.

While the invention has been described in terms of what is presently considered to be the most practical and preferred embodiments, it is to be understood that the invention needs not be limited to the disclosed embodiment. On the contrary, it is intended to cover various modifications and similar arrangements included within the spirit and scope of the appended claims which are to be accorded with the broadest interpretation so as to encompass all such modifications and similar structures.

What is claimed is:

1. An OLED display panel comprising an array substrate and a color filter layer, the color filter layer being disposed on the array substrate, wherein the array substrate comprises a cathode layer disposed on the top of the array substrate, the color filter layer is disposed on the cathode layer, a surface of the color filter layer away from the cathode layer is disposed with a second thin film layer thereon, a first thin film layer is disposed between the cathode layer and the color filter layer, and the first thin film layer and the second thin film layer each are a plurality of organic and inorganic layers being alternately stacked.

2. The OLED display panel according to claim 1, wherein the organic layer comprises a single layer or a stacked layer formed by polyethylene terephthalate, polyimide, polycarbonate, an epoxy resin, polyethylene, and/or polyacrylate; the inorganic layer comprises a single layer or a stacked layer formed by a metal oxide(s) or a metal nitride(s).

* * * * *

本实用新型提供一种OLED显示面板，通过在阵列基板上设置滤色层，可以省略上部与下部基板的对准过程，可以简化OLED显示面板的制造工艺，以及薄膜可以在滤色器层上进行封装，使得OLED显示面板可以变得更轻和更薄。

