



US 20200219957A1

(19) **United States**(12) **Patent Application Publication**
Yi et al.(10) **Pub. No.: US 2020/0219957 A1**
(43) **Pub. Date: Jul. 9, 2020**(54) **AMOLED DOUBLE-SIDE DISPLAY**(71) Applicant: **Wuhan China Star Optoelectronics Technology Co., Ltd.**, Wuhan City (CN)(72) Inventors: **Shijuan Yi**, Wuhan City (CN); **Shuang Li**, Wuhan City (CN)(21) Appl. No.: **16/819,199**(22) Filed: **Mar. 16, 2020****Related U.S. Application Data**

(63) Continuation of application No. 15/505,098, filed on Feb. 20, 2017, now Pat. No. 10,636,856.

(30) **Foreign Application Priority Data**

Nov. 17, 2016 (CN) 201611032735.8

Publication Classification(51) **Int. Cl.**

H01L 27/32	(2006.01)
H01L 51/50	(2006.01)
G09G 3/3225	(2006.01)
H01L 51/56	(2006.01)
H01L 51/52	(2006.01)


(52) **U.S. Cl.**

CPC **H01L 27/3267** (2013.01); **H01L 51/50** (2013.01); **G09G 3/3225** (2013.01); **H01L 27/3244** (2013.01); **H01L 51/56** (2013.01); **H01L 51/5234** (2013.01); **H01L 2251/533** (2013.01); **G09G 2320/0686** (2013.01); **H01L 2251/5323** (2013.01); **G09G 2300/02** (2013.01); **G09G 2300/0439** (2013.01); **H01L 2251/5315** (2013.01); **H01L 51/5218** (2013.01)

(57)

ABSTRACT

An AMOLED doubled-sided display includes an OLED array layer that includes a plurality of top-emitting OLED units and a plurality of bottom-emitting OLED units arranged alternate with each other to form an array. Each of the top-emitting OLED units and the bottom-emitting OLED units has different thickness for respective anodes and cathodes, to realize the top-emitting characteristics of the top-emitting OLED units and the bottom-emitting characteristics of the bottom-emitting OLED units. As such, by designing an algorithm for a single IC to control image displaying, only a display panel and a control IC are sufficient to achieve double-sided displaying, and ensure an observer standing in front of the display panel will not see mirrored image or directional distorted image, as well as achieve low-cost and quality display result.






Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8

AMOLED DOUBLE-SIDE DISPLAY

[0001] This is a continuation application of co-pending patent application Ser. No. 15/505,098, filed on Feb. 20, 2017, which is a national stage of PCT Application No. PCT/CN2016/112248, filed on Dec. 27, 2016, claiming foreign priority of Chinese Patent Application NO. 201611032735.8, filed on Nov. 17, 2016.

BACKGROUND OF THE INVENTION

1. Field of the Invention

[0002] The present invention relates to the field of display techniques, and in particular to an AMOLED double-sided display.

2. The Related Arts

[0003] The active-matrix organic light emitting diode (AMOLED) display provides the advantages of active light-emitting, low driving voltage, high emission efficiency, quick response time, high resolution and contrast, wide viewing angle, wide operation temperature range, and capability to realize flexible display and large-area full-color display, and is regarded as the most promising display technology. The AMOLED is a self-luminous type display, wherein the OLED device usually comprises the pixel electrode and the common electrode operating respectively on the anode and the cathode, and the organic functional layers disposed between the pixel electrode and the common electrode. When a current flowing through, these functional layers will emit light.

[0004] With the development of display technology, the demands from the consumers on the display, other than fast response, high resolution and fine display, also include the pursuit of the breakthrough in functions and display modes. Therefore, AMOLED double-sided display device came into existence. The AMOLED double-sided display, in addition to common AMOLED display features, can also extend the screen space, fast switching and processing of a plurality of screens, and have a huge application potential in advertisement promotion and portable products.

[0005] At present, the common design of the AMOLED double-sided display usually adopts a technique to make the anode and the cathode thin and transparent so that the OLED device can display simultaneously on the front and back sides of the panel. However, an obvious disadvantage in this design is that the image displayed on the back side of the panel is a mirrored image of the front side of the panel. That is, the observer on the opposite sides of the panel sees the opposite image. As shown in FIG. 1, the AMOLED display 10 adopts the above design, and when the observer stands on the right, the observer sees an F displayed on the front side of the AMOLED display screen 10; when the observer is on the left, the observer sees a flipped F displayed on the front side of the AMOLED display screen 10, which results in great inconvenience, especially when a map type of image is displayed, the disadvantage is even more prominent.

[0006] Another common technique in the AMOLED double-sided display design is to attach the two top-emitting AMOLED panels together, and signals are transmitted through two integrated circuits (ICs) respectively so that no directional distortion of the image displayed on the front and back sides will occur. As shown in FIG. 2, an AMOLED double-sided display screen employing the above design

comprises: a first AMOLED panel 21 and a second AMOLED panel 22, which are attached back-to-back together. The observer standing on the right sees an F displayed on the first AMOLED panel 21; and the observer standing on the left also sees an F displayed on the second AMOLED panel 22. However, the obvious drawbacks of such a design include: the need for two AMOLED panels, and the two separate ICs controlling the respective AMOLED panel, the relatively heavy structure, the relatively complex process, high production costs, not meeting consumer expectations of thinness and valuable cost/performance.

SUMMARY OF THE INVENTION

[0007] The object of the present invention is to provide an AMOLED double-sided display, requiring only a display panel and a control IC to effectively realize double-sided displaying, and able to ensure an observer standing in front of the display panel will not see mirrored image or directional distorted image, as well as achieve low-cost and quality display result.

[0008] To achieve the above object, the present invention provides an AMOLED double-sided display, which comprises: a substrate, and an OLED array layer disposed on the substrate;

[0009] the OLED array layer comprising a plurality of top-emitting OLED units and a plurality of bottom-emitting OLED units arranged in an array, wherein the top emitting OLED units and the bottom-emitting OLED units being arranged alternately in at least one of the horizontal direction or vertical direction;

[0010] the top-emitting OLED unit and the bottom-emitting OLED unit both comprising an anode, an organic layer and a cathode from the bottom up in a stack structure;

[0011] the anode of the top-emitting OLED unit and the anode of the bottom-emitting OLED unit being the first anode and the second anode respectively, the first anode being thicker than the second anode, the first anode being reflective and the second cathode being light-transmissive;

[0012] the cathode of the top-emitting OLED unit and the cathode of the bottom-emitting OLED unit being the first cathode and the second cathode respectively, the second cathode being thicker than the first cathode, the first cathode being light-transmissive and the second cathode being reflective.

[0013] According to a preferred embodiment of the present invention, the first anode and the second anode are formed respectively by two vacuum evaporation processes with mask.

[0014] According to a preferred embodiment of the present invention, the first anode and the second anode are formed by the same vacuum evaporation process with a grey-tone, or a half-tone mask.

[0015] According to a preferred embodiment of the present invention, the OLED array layer comprises a first cathode film and a second cathode film, and the second cathode film is formed on an upper surface of the first cathode film corresponding to the plurality of bottom-emitting OLED units by a vacuum evaporation process with a mask;

[0016] the first cathode is formed by a part of the first cathode film corresponding to the top-emitting OLED unit, and the second cathode is formed by a part of the first cathode film and the second cathode film corresponding to the bottom-emitting OLED unit.

[0017] Optionally, in the OLED array layer, the top-emitting OLED units and the bottom-emitting units are alternately arranged in both the horizontal and vertical directions;

[0018] the plurality of top-emitting OLED units and the plurality of bottom-emitting OLED units together form an OLED unit array, wherein the top-emitting OLED units and the bottom-emitting OLED units are arranged alternately in each row and each column.

[0019] According to a preferred embodiment of the present invention, during displaying, in the OLED unit array, for a positive integer i , the i -th top-emitting OLED unit from left in each row receives the same image signal as the i -th bottom-emitting OLED unit from right in the same row.

[0020] Optionally, in the OLED array layer, the top-emitting OLED units and the bottom-emitting units are alternately arranged in the horizontal direction but not in the vertical direction;

[0021] the plurality of top-emitting OLED units and the plurality of bottom-emitting OLED units together form an OLED unit array, wherein each odd-numbered column comprises the top-emitting OLED units and each even-numbered column comprises the bottom-emitting OLED units;

[0022] or, each odd-numbered column comprises the bottom-emitting OLED units and each even-numbered column comprises the top-emitting OLED units.

[0023] According to a preferred embodiment of the present invention, during displaying, in the OLED unit array, for a positive integer i , the i -th top-emitting OLED unit from left in each row receives the same image signal as the i -th bottom-emitting OLED unit from right in the same row.

[0024] Optionally, in the OLED array layer, the top-emitting OLED units and the bottom-emitting units are alternately arranged in the vertical direction but not in the horizontal direction;

[0025] the plurality of top-emitting OLED units and the plurality of bottom-emitting OLED units together form an OLED unit array, wherein each odd-numbered row comprises the top-emitting OLED units and each even-numbered row comprises the bottom-emitting OLED units;

[0026] or, each odd-numbered row comprises the bottom-emitting OLED units and each even-numbered row comprises the top-emitting OLED units.

[0027] According to a preferred embodiment of the present invention, during displaying, in the OLED unit array, for positive integers i and j , the j -th top-emitting OLED unit in the i -th column from left receives the same image signal as the j -th bottom-emitting OLED unit in the i -th column from right.

[0028] Another embodiment of the present invention provides an AMOLED double-sided display, which comprises: a substrate, and an OLED array layer disposed on the substrate; the OLED array layer comprising a plurality of top-emitting OLED units and a plurality of bottom-emitting OLED units arranged in an array, wherein the top emitting OLED units and the bottom-emitting OLED units being arranged alternately in at least one of the horizontal direction or vertical direction;

[0029] the top-emitting OLED unit and the bottom-emitting OLED unit both comprising an anode, an organic layer and a cathode from the bottom up in a stack structure;

[0030] the anode of the top-emitting OLED unit and the anode of the bottom-emitting OLED unit being the first anode and the second anode respectively, the first anode

being thicker than the second anode, the first anode being reflective and the second cathode being light-transmissive;

[0031] the cathode of the top-emitting OLED unit and the cathode of the bottom-emitting OLED unit being the first cathode and the second cathode respectively, the second cathode being thicker than the first cathode, the first cathode being light-transmissive and the second cathode being reflective;

[0032] wherein the first anode and the second anode being formed respectively by two vacuum evaporation processes with mask;

[0033] wherein the OLED array layer comprising a first cathode film and a second cathode film, and the second cathode film being formed on an upper surface of the first cathode film corresponding to the plurality of bottom-emitting OLED units by a vacuum evaporation process with a mask;

[0034] the first cathode being formed by a part of the first cathode film corresponding to the top-emitting OLED unit, and the second cathode being formed by a part of the first cathode film and the second cathode film corresponding to the bottom-emitting OLED unit.

[0035] Compared to the known techniques, the present invention provides the following advantages. The present invention provides an AMOLED double-sided display, which comprises: a substrate, and an OLED array layer disposed on the substrate; the OLED array layer comprising a plurality of top-emitting OLED units arranged in an array, and a plurality of bottom-emitting OLED units arranged in an array, wherein the top emitting OLED units and the bottom-emitting OLED units being arranged alternately in at least one of the horizontal direction or vertical direction; the top-emitting OLED unit having an anode thicker than bottom-emitting OLED unit, and bottom-emitting OLED unit having a cathode thicker than the top-emitting OLED unit to increase the reflectivity of the anode of the top-emitting OLED unit and the cathode of the bottom-emitting OLED unit to realize the top-emitting characteristics of the top-emitting OLED units and the bottom-emitting characteristics of the bottom-emitting OLED units; as such, by designing an algorithm for a single IC to control image displaying, only a display panel and a control IC are sufficient to achieve double-sided displaying, and able to ensure an observer standing in front of the display panel will not see mirrored image or directional distorted image, as well as achieve low-cost and quality display result.

BRIEF DESCRIPTION OF THE DRAWINGS

[0036] To make the technical solution of the embodiments according to the present invention, a brief description of the drawings that are necessary for the illustration of the embodiments will be given as follows. Apparently, the drawings described below show only example embodiments of the present invention and for those having ordinary skills in the art, other drawings may be easily obtained from these drawings without paying any creative effort. In the drawings:

[0037] FIG. 1 is a schematic view showing a double-sided displaying effect by a known AMOLED double-sided display;

[0038] FIG. 2 is a schematic view showing a double-sided displaying effect by another known AMOLED double-sided display;

[0039] FIG. 3 is a cross-sectional view showing an AMOLED double-sided display provided by an embodiment of the present invention;

[0040] FIG. 4 is a planar view showing an AMOLED double-sided display provided by an embodiment of the present invention;

[0041] FIG. 5 is an enlarged view of the area A in FIG. 4 showing a first layout arrangement of the top-emitting OLED units and the bottom-emitting OLED units of the OLED array layer;

[0042] FIG. 6 is an enlarged view of the area A in FIG. 4 showing a second layout arrangement of the top-emitting OLED units and the bottom-emitting OLED units of the OLED array layer;

[0043] FIG. 7 is an enlarged view of the area A in FIG. 4 showing a third layout arrangement of the top-emitting OLED units and the bottom-emitting OLED units of the OLED array layer;

[0044] FIG. 8 is a schematic view showing the double-sided displaying effect of the AMOLED double-sided display provided by an embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0045] Referring to FIGS. 3-4, the present invention provides an AMOLED double-sided display, which comprises: a substrate 100, and an OLED array layer 200 disposed on the substrate 100; the OLED array layer 200 comprising a plurality of top-emitting OLED units 210 and a plurality of bottom-emitting OLED units 220 arranged in an array, wherein the top emitting OLED units 210 and the bottom-emitting OLED units 220 being arranged alternately in at least one of the horizontal direction or vertical direction.

[0046] The top-emitting OLED unit 210 and the bottom-emitting OLED unit 220 both comprise an anode, an organic layer 230 and a cathode from the bottom up in a stack structure.

[0047] In the present invention, the anode of the top-emitting OLED unit 210 and the anode of the bottom-emitting OLED unit 220 are the first anode 211 and the second anode 221 respectively, and the first anode 211 is thicker than the second anode 22; the cathode of the top-emitting OLED unit 210 and the cathode of the bottom-emitting OLED unit 220 are the first cathode 212 and the second cathode 222 respectively, the second cathode 222 is thicker than the first cathode 212; as such, the reflectivity of the anode of the top-emitting OLED unit 210 and the cathode of the bottom-emitting OLED unit 220 is enhanced to avoid the light transmittance. As a result, the first anode 211 is reflective and the second node 221 is light-transmissive; the first cathode 212 light-transmissive and the second cathode 222 is reflective, so as to realize the top-emitting characteristics of the top-emitting OLED unit 210 and the bottom-emitting characteristics of the bottom-emitting OLED unit 220. IN the context of the present invention, the terminology "light-transmissive" implies the property of transmitting at least the light generated by the OLED array layer 200, and the terminology "reflective" implies the property of reflecting at least the light generated by the OLED array layer 200.

[0048] Specifically, to realize different thickness for the first anode 211 and the second anode 221, the first anode 211 and the second anode 221 are formed respectively by two vacuum evaporation processes with mask; alternatively, the

first anode 211 and the second anode 221 are formed by the same vacuum evaporation process with a grey-tone mask, or a half-tone mask. For example, the process can use a mask with pixel pattern to vapor-deposit a thin light-transmissive first anode film 206, and another mask with pixel pattern to vapor-deposit a thicker second anode film 207, which is reflective to prevent light from transmitting, on the first anode film 206 at locations corresponding to top-emitting OLED units 210. As such, the part of the first anode film 206 and the second anode film 207 corresponding to the top-emitting OLED units 210 together forms the first anode 211, and the part of the first anode film 206 corresponding to the bottom-emitting OLED units 220 forms the second anode 221.

[0049] Specifically, to realize different thickness for the first cathode 212 and the second cathode 222, the process can use a mask with pixel pattern to vapor-deposit a thin light-transmissive first cathode film 208, and another mask with pixel pattern to vapor-deposit a thicker second cathode film 209, which is reflective to prevent light from transmitting, on the first cathode film 208 at locations corresponding to top-emitting OLED units 210. As such, the part of the first cathode film 208 corresponding to the top-emitting OLED units 210 forms the first cathode 212, and the part of the first cathode film 208 and the second cathode film 209 corresponding to the bottom-emitting OLED units 220 together forms the second cathode 222.

[0050] Specifically, the OLED array layer 200 further comprises pixel spacer layer 250 for defining pixel areas, the top-emitting OLED units 210 and the bottom-emitting OLED units 220 are formed in the pixel areas defined by the pixel spacer layer 250 correspondingly.

[0051] Specifically, the organic layer 203 comprises a hole injection layer, a hole transport layer, a light-emission layer, and electron injection/transport layer from the bottom up in a stack structure.

[0052] Specifically, the substrate 100 is a TFT array substrate, comprising a base substrate, and a TFT array layer disposed on the base substrate, wherein the TFT array layer comprises a plurality of TFT devices arranged in an array. Because the top-emitting OLED units 210 and the bottom-emitting OLED units 220 emit light facing away from and facing towards the substrate 100 respectively, the bottom-emitting OLED units 220 should be disposed in the non light-blocking areas of the substrate 100, while the top-emitting OLED units 210 can be disposed in the non light-blocking areas or light-blocking areas; for example, the top-emitting OLED units 210 can be disposed at the TFT devices, which usually do not allow light to transmit, so as to enhance the light-emitting area and pixel aperture ratio.

[0053] In the AMOLED double-sided display, the OLED array layer 200 comprises a plurality of top-emitting OLED units 210 and a plurality of bottom-emitting OLED units 220 arranged in an array, wherein the top emitting OLED units 210 and the bottom-emitting OLED units 220 are arranged alternately in at least one of the horizontal direction or vertical direction. As such, by designing an algorithm for a single IC to control image displaying, only a display panel and a control IC are sufficient to achieve double-sided displaying, and able to ensure an observer standing in front of the display panel will not see mirrored image or directional distorted image, as well as achieve low-cost and quality display result.

[0054] Specifically, as shown in FIG. 5, in the OLED array layer 200, the top-emitting OLED units 210 and the bottom-emitting units 220 are alternately arranged in both the horizontal and vertical directions; and the plurality of top-emitting OLED units 210 and the plurality of bottom-emitting OLED units 220 together form an OLED unit array, wherein the top-emitting OLED units 210 and the bottom-emitting OLED units 220 are arranged alternately in each row and each column.

[0055] In this case, by designing an algorithm for a single IC to control image displaying, only a display panel and a control IC are sufficient to achieve double-sided displaying, and able to ensure an observer standing in front of the display panel will not see mirrored image or directional distorted image, as well as achieve low-cost and quality display result. Specifically, the algorithm is as follows. During displaying, in the OLED unit array, for a positive integer i , the i -th top-emitting OLED unit 210 from left in each row receives the same image signal as the i -th bottom-emitting OLED unit 220 from right in the same row. For example, if the OLED unit array is an array of m rows and $2n$ columns, with both m and n positive integers. When the 1^{st} , 2^{nd} , 3^{rd} , $\dots$, n -th top-emitting OLED units 210, counting from left to right, of the first row receive image signals $S11$, $S12$, $S13$, $\dots$, $S1n$, respectively, and the 1^{st} , 2^{nd} , 3^{rd} , $\dots$, n -th top-emitting OLED units 210, counting from left to right, of the second row receive image signals $S21$, $S22$, $S23$, $\dots$, $S2n$, respectively, then, the 1^{st} , 2^{nd} , 3^{rd} , $\dots$, n -th bottom-emitting OLED units 220, counting from right to left, of the first row receive image signals $S11$, $S12$, $S13$, $\dots$, $S1n$, respectively, and the 1^{st} , 2^{nd} , 3^{rd} , $\dots$, n -th bottom-emitting OLED units 220, counting from right to left, of the second row receive image signals $S21$, $S22$, $S23$, $\dots$, $S2n$, respectively. In other words, the i -th (counting from left to right) top-emitting OLED unit 210 of the j -th row receives an image signal Sji , and the i -th (counting from right to left) bottom-emitting OLED unit 220 of the j -th row receives an image signal Sji . As a result, by following the above algorithm, only a display panel and a control IC are sufficient to achieve double-sided displaying, and able to ensure an observer standing in front of the display panel will not see mirrored image or directional distorted image.

[0056] Alternatively, as shown in FIG. 6, in the OLED array layer 200, the top-emitting OLED units 210 and the bottom-emitting units 220 are alternately arranged in the horizontal direction but not in the vertical direction; and the plurality of top-emitting OLED units 210 and the plurality of bottom-emitting OLED units 220 together form an OLED unit array, wherein each odd-numbered column comprises the top-emitting OLED units 210 and each even-numbered column comprises the bottom-emitting OLED units 220; or, each odd-numbered column comprises the bottom-emitting OLED units 220 and each even-numbered column comprises the top-emitting OLED units 210.

[0057] Accordingly, the corresponding algorithm for single IC controlling image is as follows. During displaying, in the OLED unit array, for a positive integer i , the i -th top-emitting OLED unit 210 from left in each row receives the same image signal as the i -th bottom-emitting OLED unit 220 from right in the same row. For example, if the OLED unit array is an array of m rows and $2n$ columns, with both m and n positive integers. When the 1^{st} , 2^{nd} , 3^{rd} , $\dots$, n -th top-emitting OLED units 210, counting from left to right, of the first row receive image signals $S11$, $S12$, $S13$,

$\dots$, $S1n$, respectively, and the 1^{st} , 2^{nd} , 3^{rd} , $\dots$, n -th top-emitting OLED units 210, counting from left to right, of the second row receive image signals $S21$, $S22$, $S23$, $\dots$, $S2n$, respectively, then, the 1^{st} , 2^{nd} , 3^{rd} , $\dots$, n -th bottom-emitting OLED units 220, counting from right to left, of the first row receive image signals $S11$, $S12$, $S13$, $\dots$, $S1n$, respectively, and the 1^{st} , 2^{nd} , 3^{rd} , $\dots$, n -th bottom-emitting OLED units 220, counting from right to left, of the second row receive image signals $S21$, $S22$, $S23$, $\dots$, $S2n$, respectively.

[0058] Or, as shown in FIG. 7, in the OLED array layer 200, the top-emitting OLED units 210 and the bottom-emitting units 220 are alternately arranged in the vertical direction but not in the horizontal direction; and the plurality of top-emitting OLED units 210 and the plurality of bottom-emitting OLED units 220 together form an OLED unit array, wherein each odd-numbered row comprises the top-emitting OLED units 210 and each even-numbered row comprises the bottom-emitting OLED units 220; or, each odd-numbered row comprises the bottom-emitting OLED units 220 and each even-numbered row comprises the top-emitting OLED units 210.

[0059] Accordingly, the corresponding algorithm for single IC controlling image is as follows. During displaying, in the OLED unit array 200, for positive integers i and j , the j -th top-emitting OLED unit 210 from top in the i -th column receives the same image signal as the j -th bottom-emitting OLED unit 220 from bottom in the i -th column. For example, if the OLED unit array is an array of $2m$ rows and n columns, with both m and n positive integers, and each odd-numbered row comprising top-emitting OLED units 210 while the even-numbered row comprising bottom-emitting OLED units 220. When the 1^{st} , 2^{nd} , 3^{rd} , $\dots$, n -th top-emitting OLED units 210, counting from left to right, of the first row receive image signals $S11$, $S12$, $S13$, $\dots$, $S1n$, respectively, and the 1^{st} , 2^{nd} , 3^{rd} , $\dots$, n -th top-emitting OLED units 210, counting from left to right, of the third row receive image signals $S21$, $S22$, $S23$, $\dots$, $S2n$, respectively, then, the 1^{st} , 2^{nd} , 3^{rd} , $\dots$, n -th bottom-emitting OLED units 220, counting from right to left, of the second row receive image signals $S11$, $S12$, $S13$, $\dots$, $S1n$, respectively, and the 1^{st} , 2^{nd} , 3^{rd} , $\dots$, n -th bottom-emitting OLED units 220, counting from right to left, of the fourth row receive image signals $S21$, $S22$, $S23$, $\dots$, $S2n$, respectively.

[0060] The AMOLED double-sided display of the present invention, by designing an algorithm for a single IC to control image displaying, requires only a display panel and a control IC to achieve double-sided displaying, and able to ensure an observer standing in front of the display panel will not see mirrored image or directional distorted image, as well as achieve low-cost and quality display result. As shown in FIG. 8, the observer standing on the right sees an F displayed on the AMOLED double-sided display, and the observer standing on the left also sees an F displayed on the AMOLED double-sided display.

[0061] In summary, the present invention provides an AMOLED double-sided display, comprising: a substrate, and an OLED array layer disposed on the substrate; the OLED array layer comprising a plurality of top-emitting OLED units arranged in an array, and a plurality of bottom-emitting OLED units arranged in an array, wherein the top emitting OLED units and the bottom-emitting OLED units being arranged alternately in at least one of the horizontal direction or vertical direction; the top-emitting OLED unit having an anode thicker than bottom-emitting OLED unit,

and bottom-emitting OLED unit having a cathode thicker than the top-emitting OLED unit to increase the reflectivity of the anode of the top-emitting OLED unit and the cathode of the bottom-emitting OLED unit to realize the top-emitting characteristics of the top-emitting OLED units and the bottom-emitting characteristics of the bottom-emitting OLED units; as such, by designing an algorithm for a single IC to control image displaying, only a display panel and a control IC are sufficient to achieve double-sided displaying, and able to ensure an observer standing in front of the display panel will not see mirrored image or directional distorted image, as well as achieve low-cost and quality display result.

[0062] It should be noted that in the present disclosure the terms, such as, first, second are only for distinguishing an entity or operation from another entity or operation, and does not imply any specific relation or order between the entities or operations. Also, the terms “comprises”, “include”, and other similar variations, do not exclude the inclusion of other non-listed elements. Without further restrictions, the expression “comprises a . . .” does not exclude other identical elements from presence besides the listed elements.

[0063] Embodiments of the present invention have been described, but not intending to impose any unduly constraint to the appended claims. Any modification of equivalent structure or equivalent process made according to the disclosure and drawings of the present invention, or any application thereof, directly or indirectly, to other related fields of technique, is considered encompassed in the scope of protection defined by the claims of the present invention.

What is claimed is:

1. An active matrix organic light-emitting diode (AMOLED) double-sided display, which comprises: a substrate, and an OLED array layer disposed on the substrate; the OLED array layer comprising a plurality of top-emitting OLED units and a plurality of bottom-emitting OLED units arranged in an array, wherein the plurality of top-emitting OLED units and the plurality of bottom-emitting OLED units are alternate with each other;

wherein each of the plurality of top-emitting OLED units comprises a first anode, an organic layer, and a first cathode arranged in a stacked structure and each of the plurality of bottom-emitting OLED units comprises a second anode, an organic layer and a second cathode arranged in a stacked structure;

wherein the first anode is thicker than the second anode, the first anode being reflective and the second cathode being light-transmissive, wherein the second anode is formed of a first anode film that is transmissive to light and the first anode is formed of the first anode film and a second anode film located on the first anode film at a location corresponding to each of the plurality of the top-emitting OLED units, the second anode film being reflective and thicker than the first anode film; and

wherein the second cathode is thicker than the first cathode, the first cathode being light-transmissive and the second cathode being reflective.

2. The AMOLED double-sided display as claimed in claim 1, wherein the first anode and the second anode are formed respectively by two vacuum evaporation processes each of which is carried out with a mask.

3. The AMOLED double-sided display as claimed in claim 1, wherein the first anode and the second anode are

formed by one vacuum evaporation process with one of a grey-tone mask and a half-tone mask.

4. The AMOLED double-sided display as claimed in claim 1, wherein the OLED array layer comprises a first cathode film and a second cathode film, and the second cathode film is formed on an upper surface of the first cathode film corresponding to the plurality of bottom-emitting OLED units; and

wherein the first cathode is formed of a part of the first cathode film corresponding to the top-emitting OLED unit, and the second cathode is formed of a part of the first cathode film and the second cathode film corresponding to the bottom-emitting OLED unit.

5. The AMOLED double-sided display as claimed in claim 1, wherein the plurality of top-emitting OLED units and the plurality of bottom-emitting OLED units together form an OLED unit array having rows and columns, wherein the plurality of top-emitting OLED units and the plurality of bottom-emitting OLED units are arranged alternate in each of the rows and each of the columns.

6. The AMOLED double-sided display as claimed in claim 5, wherein during displaying, in the OLED unit array, for a positive integer i, an i-th top-emitting OLED unit from left in each row of the rows receives a same image signal as an i-th bottom-emitting OLED unit from right in said each row of the rows.

7. The AMOLED double-sided display as claimed in claim 1, wherein the plurality of top-emitting OLED units and the plurality of bottom-emitting units together form an OLED unit array having rows and columns, wherein the plurality of top-emitting OLED units and the plurality of bottom-emitting OLED units are arranged alternate with each other in a row-wise direction; and

wherein each odd-numbered column of the columns comprises a number of top-emitting OLED units of the plurality of top-emitting OLED units and each even-numbered column of the columns comprises a number of bottom-emitting OLED units of the plurality of bottom-emitting OLED units; or alternatively, each odd-numbered column of the columns comprises a number of bottom-emitting OLED units of the plurality of bottom-emitting OLED units and each even-numbered column of the columns comprises a number of top-emitting OLED units of the plurality of top-emitting OLED units.

8. The AMOLED double-sided display as claimed in claim 7, wherein during displaying, in the OLED unit array, for a positive integer i, an i-th top-emitting OLED unit from left in each row of the rows receives a same image signal as an i-th bottom-emitting OLED unit from right in said each row of the rows.

9. The AMOLED double-sided display as claimed in claim 1, wherein the plurality of top-emitting OLED units and the plurality of bottom-emitting OLED units together form an OLED unit array having rows and columns, wherein the plurality of top-emitting OLED units and the plurality of bottom-emitting units are arranged alternate with each other in a column-wise direction; and

wherein each odd-numbered row of the rows comprises a number of top-emitting OLED units of the plurality of top-emitting OLED units and each even-numbered row of the rows comprises a number of bottom-emitting OLEDs of the plurality of bottom-emitting OLED units; or alternatively, each odd-numbered row of the

rows comprises a number of bottom-emitting OLEDs of the plurality of bottom-emitting OLED units and each even-numbered row of the rows comprises a number of top-emitting OLED units of the plurality of top-emitting OLED units.

10. The AMOLED double-sided display as claimed in claim 9, wherein during displaying, in the OLED unit array, for positive integers i and j , a j -th top-emitting OLED unit in an i -th column from left receives a same image signal as a j -th bottom-emitting OLED unit in the i -th column from right.

11. An active matrix organic light-emitting diode (AMOLED) doubled-sided display, which comprises: a substrate, and an OLED array layer disposed on the substrate; the OLED array layer comprising a plurality of top-emitting OLED units and a plurality of bottom-emitting OLED units arranged in an array, wherein the plurality of top-emitting OLED units and the plurality of bottom-emitting OLED units are alternate with each other;

wherein each of the plurality of top-emitting OLED units comprises a first anode, an organic layer, and a first cathode arranged in a stacked structure and each of the plurality of bottom-emitting OLED units comprises a second anode, an organic layer and a second cathode arranged in a stacked structure;

wherein the first anode is thicker than the second anode, the first anode being reflective and the second cathode being light-transmissive, wherein the second anode is formed of a first anode film that is transmissive to light and the first anode is formed of the first anode film and a second anode film located on the first anode film at a location corresponding to each of the plurality of the top-emitting OLED units, the second anode film being reflective and thicker than the first anode film;

wherein the second cathode is thicker than the first cathode, the first cathode being light-transmissive and the second cathode being reflective;

wherein the OLED array layer comprises a first cathode film and a second cathode film, and the second cathode film is formed on an upper surface of the first cathode film corresponding to the plurality of bottom-emitting OLED units; and

wherein the first cathode is formed of a part of the first cathode film corresponding to the top-emitting OLED unit, and the second cathode is formed of a part of the first cathode film and the second cathode film corresponding to the bottom-emitting OLED unit.

12. The AMOLED double-sided display as claimed in claim 11, wherein the plurality of top-emitting OLED units and the plurality of bottom-emitting OLED units together form an OLED unit array having rows and columns, wherein the plurality of top-emitting OLED units and the plurality of bottom-emitting OLED units are arranged alternate in each of the rows and each of the columns.

13. The AMOLED double-sided display as claimed in claim 12, wherein during displaying, in the OLED unit array,

for a positive integer i , an i -th top-emitting OLED unit from left in each row of the rows receives a same image signal as an i -th bottom-emitting OLED unit from right in said each row of the rows.

14. The AMOLED double-sided display as claimed in claim 11, wherein the plurality of top-emitting OLED units and the plurality of bottom-emitting units together form an OLED unit array having rows and columns, wherein the plurality of top-emitting OLED units and the plurality of bottom-emitting OLED units are arranged alternate with each other in a row-wise direction; and

wherein each odd-numbered column of the columns comprises a number of top-emitting OLED units of the plurality of top-emitting OLED units and each even-numbered column of the columns comprises a number of bottom-emitting OLED units of the plurality of bottom-emitting OLED units; or alternatively, each odd-numbered column of the columns comprises a number of bottom-emitting OLED units of the plurality of bottom-emitting OLED units and each even-numbered column of the columns comprises a number of top-emitting OLED units of the plurality of top-emitting OLED units.

15. The AMOLED double-sided display as claimed in claim 14, wherein during displaying, in the OLED unit array, for a positive integer i , an i -th top-emitting OLED unit from left in each row of the rows receives a same image signal as an i -th bottom-emitting OLED unit from right in said each row of the rows.

16. The AMOLED double-sided display as claimed in claim 11, wherein the plurality of top-emitting OLED units and the plurality of bottom-emitting OLED units together form an OLED unit array having rows and columns, wherein the plurality of top-emitting OLED units and the plurality of bottom-emitting units are arranged alternate with each other in a column-wise direction; and

wherein each odd-numbered row of the rows comprises a number of top-emitting OLED units of the plurality of top-emitting OLED units and each even-numbered row of the rows comprises a number of bottom-emitting OLEDs of the plurality of bottom-emitting OLED units; or alternatively, each odd-numbered row of the rows comprises a number of bottom-emitting OLEDs of the plurality of bottom-emitting OLED units and each even-numbered row of the rows comprises a number of top-emitting OLED units of the plurality of top-emitting OLED units.

17. The AMOLED double-sided display as claimed in claim 16, wherein during displaying, in the OLED unit array, for positive integers i and j , a j -th top-emitting OLED unit in an i -th column from left receives a same image signal as a j -th bottom-emitting OLED unit in the i -th column from right.

* * * * *

专利名称(译)	Amoled双面显示器		
公开(公告)号	US20200219957A1	公开(公告)日	2020-07-09
申请号	US16/819199	申请日	2020-03-16
[标]申请(专利权)人(译)	武汉华星光电技术有限公司		
申请(专利权)人(译)	中国武汉恒星光电科技有限公司.		
当前申请(专利权)人(译)	中国武汉恒星光电科技有限公司.		
[标]发明人	YI SHIJUAN LI SHUANG		
发明人	YI, SHIJUAN LI, SHUANG		
IPC分类号	H01L27/32 H01L51/50 G09G3/3225 H01L51/56 H01L51/52		
CPC分类号	H01L51/56 H01L2251/533 H01L2251/5323 H01L27/3267 G09G2300/02 G09G2320/0686 G09G2300/0439 H01L51/5218 H01L27/3244 G09G3/3225 H01L51/50 H01L2251/5315 H01L51/5234 H01L51/5206 H01L51/5221 H01L2251/558		
优先权	201611032735.8 2016-11-17 CN 15/505098 2017-02-20 US		
外部链接	Espacenet USPTO		

摘要(译)

AMOLED双面显示器包括OLED阵列层,该OLED阵列层包括彼此交替布置以形成阵列的多个顶部发射OLED单元和多个底部发射OLED单元。顶部发射的OLED单元和底部发射的OLED单元中的每个阳极和阴极具有不同的厚度,以实现顶部发射的OLED单元的顶部发射特性和底部发射的OLED的底部发射特性。单位。这样,通过设计用于单个IC的算法来控制图像显示,仅显示面板和控制IC就足以实现双面显示,并确保站在显示面板前面的观察者不会看到镜像图像或图像。方向失真的图像,以及实现低成本和高质量的显示效果。

