



US010454046B2

(12) United States Patent
Ma et al.**(10) Patent No.: US 10,454,046 B2****(45) Date of Patent: Oct. 22, 2019****(54) ORGANIC ELECTROLUMINESCENT MATERIALS AND DEVICES****(71) Applicant: Universal Display Corporation,**
Ewing, NJ (US)**(72) Inventors: Bin Ma,** Plainsboro, NJ (US); **Alan Deangelis,** Pennington, NJ (US); **Chuanjun Xia,** Lawrenceville, NJ (US)**(73) Assignee: Universal Display Corporation,**
Ewing, NJ (US)**(*) Notice:** Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.**(21) Appl. No.: 15/336,201****(22) Filed: Oct. 27, 2016****(65) Prior Publication Data**
US 2017/0047531 A1 Feb. 16, 2017**Related U.S. Application Data****(63)** Continuation of application No. 13/316,162, filed on Dec. 9, 2011, now Pat. No. 9,512,355.**(51) Int. Cl.**
H01L 51/54 (2006.01)
C09K 11/06 (2006.01)
H01L 51/00 (2006.01)
C07F 15/00 (2006.01)
H05B 33/14 (2006.01)
C09K 11/02 (2006.01)
H01L 51/50 (2006.01)**(52) U.S. Cl.**
CPC **H01L 51/0085** (2013.01); **C07F 15/0033** (2013.01); **C09K 11/025** (2013.01); **C09K 11/06** (2013.01); **H01L 51/0072** (2013.01); **H05B 33/14** (2013.01); **C09K 2211/1029** (2013.01); **C09K 2211/1029** (2013.01)(2013.01); **C09K 2211/185** (2013.01); **H01L 51/5016** (2013.01); **H01L 51/5024** (2013.01); **H01L 51/5056** (2013.01); **H01L 51/5072** (2013.01); **H01L 51/5088** (2013.01); **H01L 51/5092** (2013.01); **H01L 51/5096** (2013.01)**(58) Field of Classification Search**

None

See application file for complete search history.

(56) References Cited**U.S. PATENT DOCUMENTS**4,769,292 A 9/1988 Tang et al.
5,061,569 A 10/1991 VanSlyke et al.
5,247,190 A 9/1993 Friend et al.
5,703,436 A 12/1997 Forrest et al.
5,707,745 A 1/1998 Forrest et al.

(Continued)

FOREIGN PATENT DOCUMENTSCN 100375749 3/2008
CN 100584811 1/2010

(Continued)


OTHER PUBLICATIONS

Notice of Reasons for Rejection dated Sep. 4, 2017 for corresponding JP Application No. 2016-198043.

(Continued)

Primary Examiner — Marie R. Yamnitzky**(74) Attorney, Agent, or Firm** — Duane Morris LLP**(57) ABSTRACT**

Novel phosphorescent metal complexes containing 2-phenylisoquinoline ligands with at least two substituents on the isoquinoline ring are provided. The disclosed compounds have low sublimation temperatures that allow for ease of purification and fabrication into a variety of OLED devices.

15 Claims, 3 Drawing Sheets**Formula I**

(56)

References Cited

U.S. PATENT DOCUMENTS

5,834,893	A	11/1998	Bulovic et al.
5,844,363	A	12/1998	Gu et al.
6,013,982	A	1/2000	Thompson et al.
6,087,196	A	7/2000	Sturm et al.
6,091,195	A	7/2000	Forrest et al.
6,097,147	A	8/2000	Baldo et al.
6,294,398	B1	9/2001	Kim et al.
6,303,238	B1	10/2001	Thompson et al.
6,337,102	B1	1/2002	Forrest et al.
6,468,819	B1	10/2002	Kim et al.
6,528,187	B1	3/2003	Okada
6,687,266	B1	2/2004	Ma et al.
6,835,469	B2	12/2004	Kwong et al.
6,893,743	B2 *	5/2005	Sato et al. H01L 51/0059 257/102
6,921,915	B2	7/2005	Takiguchi et al.
7,087,321	B2	8/2006	Kwong et al.
7,090,928	B2	8/2006	Thompson et al.
7,154,114	B2	12/2006	Brooks et al.
7,250,226	B2	7/2007	Tokito et al.
7,279,704	B2	10/2007	Walters et al.
7,332,232	B2	2/2008	Ma et al.
7,338,722	B2	3/2008	Thompson et al.
7,393,599	B2	7/2008	Thompson et al.
7,396,598	B2	7/2008	Takeuchi et al.
7,431,968	B1	10/2008	Shtein et al.
7,445,855	B2	11/2008	Mackenzie et al.
7,534,505	B2	5/2009	Lin et al.
8,492,006	B2	7/2013	Ma et al.
9,287,515	B2	3/2016	Fukuzaki
9,512,355	B2	12/2016	Ma et al.
2002/0034656	A1	3/2002	Thompson et al.
2002/0134984	A1	9/2002	Igarashi
2002/0158242	A1	10/2002	Son et al.
2003/0138657	A1	7/2003	Li et al.
2003/0152802	A1	8/2003	Tsuyoyama et al.
2003/0162053	A1	8/2003	Marks et al.
2003/0175553	A1	9/2003	Thompson et al.
2003/0230980	A1	12/2003	Forrest et al.
2004/0036077	A1	2/2004	Ise
2004/0137267	A1	7/2004	Igarashi et al.
2004/0137268	A1	7/2004	Igarashi et al.
2004/0174116	A1	9/2004	Lu et al.
2005/0025993	A1	2/2005	Thompson et al.
2005/0112407	A1	5/2005	Ogasawara et al.
2005/0238919	A1	10/2005	Ogasawara
2005/0244673	A1	11/2005	Satoh et al.
2005/0260441	A1	11/2005	Thompson et al.
2005/0260449	A1	11/2005	Walters et al.
2006/0008670	A1	1/2006	Lin et al.
2006/0202194	A1	9/2006	Jeong et al.
2006/0240279	A1	10/2006	Adamovich et al.
2006/0251923	A1	11/2006	Lin et al.
2006/0263635	A1	11/2006	Ise
2006/0280965	A1	12/2006	Kwong et al.
2007/0190359	A1	8/2007	Knowles et al.
2007/0278938	A1	12/2007	Yabunouchi et al.
2008/0015355	A1	1/2008	Schafer
2008/0018221	A1	1/2008	Egen et al.
2008/0074033	A1	3/2008	Ionkin et al.
2008/0106190	A1	5/2008	Yabunouchi et al.
2008/0124572	A1	5/2008	Mizuki et al.
2008/0206596	A1 *	8/2008	Jung et al. C07F 15/0033 428/690
2008/0220265	A1	9/2008	Xia et al.
2008/0261076	A1	10/2008	Kwong et al.
2008/0297033	A1	12/2008	Knowles et al.
2009/0008605	A1	1/2009	Kawamura et al.
2009/0009065	A1	1/2009	Nishimura et al.
2009/0017330	A1	1/2009	Iwakuma et al.
2009/0030202	A1	1/2009	Iwakuma et al.
2009/0039776	A1	2/2009	Yamada et al.
2009/0045730	A1	2/2009	Nishimura et al.
2009/0045731	A1	2/2009	Nishimura et al.
2009/0048415	A1	2/2009	Buesing et al.

2009/0085476	A1	4/2009	Park et al.
2009/0101870	A1	4/2009	Prakash et al.
2009/0104472	A1	4/2009	Je et al.
2009/0108737	A1	4/2009	Kwong et al.
2009/0115316	A1	5/2009	Zheng et al.
2009/0165846	A1	7/2009	Johannes et al.
2009/0167162	A1	7/2009	Lin et al.
2009/0179554	A1	7/2009	Kuma et al.
2010/0090591	A1 *	4/2010	Alleyne et al. H01L 51/0085 313/504
2011/0127501	A1	6/2011	Lecloux et al.

FOREIGN PATENT DOCUMENTS

CN	102187491	9/2011
EP	0650955	5/1995
EP	1535981	6/2005
EP	1725079	11/2006
EP	1784057	5/2007
EP	2034538	3/2009
JP	200511610	1/2005
JP	2007123392	5/2007
JP	2007254297	10/2007
JP	2008074939	4/2008
JP	2009507865	2/2009
JP	2011-91355	5/2011
JP	2013-121957	6/2013
KR	20110077350	7/2011
KR	1020110077173	7/2011
WO	01/39234	5/2001
WO	02/02714	1/2002
WO	02/15645	2/2002
WO	03040257	5/2003
WO	03060956	7/2003
WO	2004093207	10/2004
WO	2004107822	12/2004
WO	2005014551	2/2005
WO	2005019373	3/2005
WO	2005030900	4/2005
WO	2005089025	9/2005
WO	2005123873	12/2005
WO	2006009024	1/2006
WO	2006056418	6/2006
WO	2006072002	7/2006
WO	2006082742	8/2006
WO	2006098120	9/2006
WO	2006100298	9/2006
WO	2006103874	10/2006
WO	2006114966	11/2006
WO	2006132173	12/2006
WO	2007002683	1/2007
WO	2007004380	1/2007
WO	2007063754	6/2007
WO	2007063796	6/2007
WO	2008056746	5/2008
WO	2008101842	8/2008
WO	2008109824	A2 9/2008
WO	2008132085	11/2008
WO	2009000673	12/2008
WO	2009003898	1/2009
WO	2009008311	1/2009
WO	2009018009	2/2009
WO	2009021126	2/2009
WO	2009050290	4/2009
WO	2009062578	5/2009
WO	2009063833	5/2009
WO	2009066778	5/2009
WO	2009066779	5/2009
WO	2009086028	7/2009
WO	2009100991	8/2009
WO	2010033550	3/2010

OTHER PUBLICATIONS

Adachi, Chihaya et al., "Organic Electroluminescent Device Having a Hole Conductor as an Emitting Layer," Appl. Phys. Lett., 55(15): 1489-1491 (1989).

(56)

References Cited

OTHER PUBLICATIONS

- Adachi, Chihaya et al., "Nearly 100% Internal Phosphorescence Efficiency in an Organic Light Emitting Device," *J. Appl. Phys.*, 90(10): 5048-5051 (2001).
- Adachi, Chihaya et al., "High-Efficiency Red Electrophosphorescence Devices," *Appl. Phys. Lett.*, 78(11):1622-1624 (2001).
- Aonuma, Masaki et al., "Material Design of Hole Transport Materials Capable of Thick-Film Formation in Organic Light Emitting Diodes," *Appl. Phys. Lett.*, 90, Apr. 30, 2007, 183503-1-183503-3.
- Baldo et al., "Highly Efficient Phosphorescent Emission from Organic Electroluminescent Devices," *Nature*, vol. 395, 151-154, (1998).
- Baldo et al., "Very high-efficiency green organic light-emitting devices based on electrophosphorescence," *Appl. Phys. Lett.*, vol. 75, No. 1, 4-6 (1999).
- Gao, Zhiqiang et al., "Bright-Blue Electroluminescence From a Silyl-Substituted ter-(phenylene-vinylene) derivative," *Appl. Phys. Lett.*, 74(6): 865-867 (1999).
- Guo, Tzung-Fang et al., "Highly Efficient Electrophosphorescent Polymer Light-Emitting Devices," *Organic Electronics*, 1: 15-20 (2000).
- Hamada, Yuji et al., "High Luminance in Organic Electroluminescent Devices with Bis(10-hydroxybenzo[h]quinolino) beryllium as an Emitter," *Chem. Lett.*, 905-906 (1993).
- Holmes, R.J. et al., "Blue Organic Electrophosphorescence Using Exothermic Host-Guest Energy Transfer," *Appl. Phys. Lett.*, 82(15):2422-2424 (2003).
- Hu, Nan-Xing et al., "Novel High Tg Hole-Transport Molecules Based on Indolo[3,2-b]carbazoles for Organic Light-Emitting Devices," *Synthetic Metals*, 111-112:421-424 (2000).
- Huang, Jinsong et al., "Highly Efficient Red-Emission Polymer Phosphorescent Light-Emitting Diodes Based on Two Novel Tris(1-phenylisoquinolino-C2,N)indium(III) Derivatives," *Adv. Mater.*, 19:739-743 (2007).
- Huang, Wei-Sheng et al., "Highly Phosphorescent Bis-Cyclometalated Iridium Complexes Containing Benzoimidazole-Based Ligands," *Chem. Mater.*, 16(12):2480-2488 (2004).
- Hung, L.S. et al., "Anode Modification in Organic Light-Emitting Diodes by Low-Frequency Plasma Polymerization of CHF₃," *Appl. Phys. Lett.*, 78(5):673-675 (2001).
- Ikai, Masamichi et al., "Highly Efficient Phosphorescence From Organic Light-Emitting Devices with an Exciton-Block Layer," *Appl. Phys. Lett.*, 79(2):156-158 (2001).
- Ikeda, Hisao et al., "P-185 Low-Drive-Voltage OLEDs with a Buffer Layer Having Molybdenum Oxide," *SID Symposium Digest*, 37:923-926 (2006).
- Inada, Hiroshi and Shirota, Yasuhiko, "1,3,5-Tris[4-(diphenylamino)phenyl]benzene and its Methylsubstituted Derivatives as a Novel Class of Amorphous Molecular Materials," *J. Mater. Chem.*, 3(3):319-320 (1993).
- Kanno, Hiroshi et al., "Highly Efficient and Stable Red Phosphorescent Organic Light-Emitting Device Using bis[2-(2-benzothiazoyl)phenolato]zinc(II) as host material," *Appl. Phys. Lett.*, 90:123509-1-123509-3 (2007).
- Kido, Junji et al., "1,2,4-Triazole Derivative as an Electron Transport Layer in Organic Electroluminescent Devices," *Jpn. J. Appl. Phys.*, 32:L917-L920 (1993).
- Kuwabara, Yoshiyuki et al., "Thermally Stable Multilayered Organic Electroluminescent Devices Using Novel Starburst Molecules, 4,4',4"-Tri(N-carbazolyl)triphenylamine (TCTA) and 4,4',4"-Tris(3-methylphenylphenyl-amino)triphenylamine (m-MTDATA), as Hole-Transport Materials," *Adv. Mater.*, 6(9):677-679 (1994).
- Kwong, Raymond C. et al., "High Operational Stability of Electrophosphorescent Devices," *Appl. Phys. Lett.*, 81(1) 162-164 (2002).
- Lamansky, Sergey et al., "Synthesis and Characterization of Phosphorescent Cyclometalated Iridium Complexes," *Inorg. Chem.*, 40(7):1704-1711 (2001).
- Lee, Chang-Lyoul et al., "Polymer Phosphorescent Light-Emitting Devices Doped with Tris(2-phenylpyridine) Iridium as a Triplet Emitter," *Appl. Phys. Lett.*, 77(15):2280-2282 (2000).
- Lo, Shih-Chun et al., "Blue Phosphorescence from Indium(III) Complexes at Room Temperature," *Chem. Mater.*, 18 (21):5119-5129 (2006).
- Ma, Yuguang et al., "Triplet Luminescent Dinuclear-Gold(I) Complex-Based Light-Emitting Diodes with Low Turn-On voltage," *Appl. Phys. Lett.*, 74(10):1361-1363 (1999).
- Mi, Bao-Xiu et al., "Thermally Stable Hole-Transporting Material for Organic Light-Emitting Diode an Isoindole Derivative," *Chem. Mater.*, 15(16):3148-3151 (2003).
- Nishida, Jun-ichi et al., "Preparation, Characterization, and Electroluminescence Characteristics of α -Diimine-type Platinum(II) Complexes with Perfluorinated Phenyl Groups as Ligands," *Chem. Lett.*, 34(4): 592-593 (2005).
- Niu, Yu-Hua et al., "Highly Efficient Electrophosphorescent Devices with Saturated Red Emission from a Neutral Osmium Complex," *Chem. Mater.*, 17(13):3532-3536 (2005).
- Noda, Tetsuya and Shirota, Yasuhiko, "5,5'-Bis(dimesitylboryl)-2,2'-bithiophene and 5,5'-Bis(dimesitylboryl)-2,2':5,2'-terthiophene as a Novel Family of Electron-Transporting Amorphous Molecular Materials," *J. Am. Chem. Soc.*, 120 (37):9714-9715 (1998).
- Okumoto, Kenji et al., "Green Fluorescent Organic Light-Emitting Device with External Quantum Efficiency of Nearly 10%," *Appl. Phys. Lett.*, 89:063504-1-063504-3 (2006).
- Palilis, Leonidas C., "High Efficiency Molecular Organic Light-Emitting Diodes Based on Slide Derivatives and Their Exciplexes," *Organic Electronics*, 4:113-121 (2003).
- Paulose, Betty Marie Jennifer S. et al., "First Examples of Alkenyl Pyridines as Organic Ligands for Phosphorescent Iridium Complexes," *Adv. Mater.*, 16(22):2003-2007 (2004).
- Ranjan, Sudhir et al., "Realizing Green Phosphorescent Light-Emitting Materials from Rhenium(I) Pyrazolato Diimine Complexes," *Inorg. Chem.*, 42(4):1248-1255 (2003).
- Sakamoto, Youichi et al., "Synthesis, Characterization, and Electron-Transport Property of Perfluorinated Phenylene Dendrimers," *J. Am. Chem. Soc.*, 122(8):1832-1833 (2000).
- Salbeck, J. et al., "Low Molecular Organic Glasses for Blue Electroluminescence," *Synthetic Metals*, 91: 209-215 (1997).
- Shirota, Yasuhiko et al., "Starburst Molecules Based on π -Electron Systems as Materials for Organic Electroluminescent Devices," *Journal of Luminescence*, 72-74:985-991 (1997).
- Sotoyama, Wataru et al., "Efficient Organic Light-Emitting Diodes with Phosphorescent Platinum Complexes Containing NCN-Coordinating Tridentate Ligand," *Appl. Phys. Lett.*, 86:153505-1-153505-3 (2005).
- Sun, Yiru and Forrest, Stephen R., "High-Efficiency White Organic Light Emitting Devices with Three Separate Phosphorescent Emission Layers," *Appl. Phys. Lett.*, 91:263503-1-263503-3 (2007).
- T. Ostergard et al., "Langmuir-Blodgett Light-Emitting Diodes of Poly(3-Hexylthiophene) Electro-Optical Characteristics Related to Structure," *Synthetic Metals*, 88:171-177 (1997).
- Takizawa, Shin-ya et al., "Phosphorescent Iridium Complexes Based on 2-Phenylimidazo[1,2- α]pyridine Ligands Tuning of Emission Color toward the Blue Region and Application to Polymer Light-Emitting Devices," *Inorg. Chem.*, 46(10):4308-4319 (2007).
- Tang, C.W. and VanSlyke, S.A., "Organic Electroluminescent Diodes," *Appl. Phys. Lett.*, 51(12):913-915 (1987).
- Tung, Yung-Liang et al., "Organic Light-Emitting Diodes Based on Charge-Neutral Ru II Phosphorescent Emitters," *Adv. Mater.*, 17(8):1059-1064 (2005).
- Van Slyke, S. A. et al., "Organic Electroluminescent Devices with Improved Stability," *Appl. Phys. Lett.*, 69 (15):2160-2162 (1996).
- Wang, Y. et al., "Highly Efficient Electroluminescent Materials Based on Fluorinated Organometallic Iridium Compounds," *Appl. Phys. Lett.*, 79(4):449-451 (2001).
- Wong, Keith Man-Chung et al., "A Novel Class of Phosphorescent Gold(III) Alkynyl-Based Organic Light-Emitting Devices with Tunable Colour," *Chem. Commun.*, 2906-2908 (2005).
- Wong, Wai-Yeung, "Multifunctional Iridium Complexes Based on Carbazole Modules as Highly Efficient Electrophosphors," *Angew. Chem. Int. Ed.*, 45:7800-7803 (2006).
- Notice of Reasons for Rejection dated Mar. 12, 2018 for corresponding Japanese Patent Application No. 2016-198043.

* cited by examiner




FIGURE 1





FIGURE 2



Formula I

FIGURE 3

1

ORGANIC ELECTROLUMINESCENT
MATERIALS AND DEVICESCROSS-REFERENCE TO RELATED
APPLICATION

This application is a continuation application of U.S. Non-Provisional application Ser. No. 13/316,162, filed Dec. 9, 2011, the entirety of which is incorporated herein by reference.

PARTIES TO A JOINT RESEARCH
AGREEMENT

The claimed invention was made by, on behalf of, and/or in connection with one or more of the following parties to a joint university corporation research agreement: Regents of the University of Michigan, Princeton University, The University of Southern California, and the Universal Display Corporation. The agreement was in effect on and before the date the claimed invention was made, and the claimed invention was made as a result of activities undertaken within the scope of the agreement.

FIELD OF THE INVENTION

The present invention relates to metal complexes containing heterocyclic ligands with at least two substituents on the heterocyclic ligand. These metal complexes are suitable for use in OLED devices.

BACKGROUND


Opto-electronic devices that make use of organic materials are becoming increasingly desirable for a number of reasons. Many of the materials used to make such devices are relatively inexpensive, so organic opto-electronic devices have the potential for cost advantages over inorganic devices. In addition, the inherent properties of organic materials, such as their flexibility, may make them well suited for particular applications such as fabrication on a flexible substrate. Examples of organic opto-electronic devices include organic light emitting devices (OLEDs), organic phototransistors, organic photovoltaic cells, and organic photodetectors. For OLEDs, the organic materials may have performance advantages over conventional materials. For example, the wavelength at which an organic emissive layer emits light may generally be readily tuned with appropriate dopants.

OLEDs make use of thin organic films that emit light when voltage is applied across the device. OLEDs are becoming an increasingly interesting technology for use in applications such as flat panel displays, illumination, and backlighting. Several OLED materials and configurations are described in U.S. Pat. Nos. 5,844,363, 6,303,238, and 5,707,745, which are incorporated herein by reference in their entirety.

One application for phosphorescent emissive molecules is a full color display. Industry standards for such a display call for pixels adapted to emit particular colors, referred to as "saturated" colors. In particular, these standards call for saturated red, green, and blue pixels. Color may be measured using CIE coordinates, which are well known to the art.

One example of a green emissive molecule is tris(2-phenylpyridine) iridium, denoted Ir(ppy)₃, which has the following structure:

2



In this, and later figures herein, we depict the dative bond from nitrogen to metal (here, Ir) as a straight line.

As used herein, the term "organic" includes polymeric materials as well as small molecule organic materials that may be used to fabricate organic opto-electronic devices. "Small molecule" refers to any organic material that is not a polymer, and "small molecules" may actually be quite large. Small molecules may include repeat units in some circumstances. For example, using a long chain alkyl group as a substituent does not remove a molecule from the "small molecule" class. Small molecules may also be incorporated into polymers, for example as a pendent group on a polymer backbone or as a part of the backbone. Small molecules may also serve as the core moiety of a dendrimer, which consists of a series of chemical shells built on the core moiety. The core moiety of a dendrimer may be a fluorescent or phosphorescent small molecule emitter. A dendrimer may be a "small molecule," and it is believed that all dendrimers currently used in the field of OLEDs are small molecules.

As used herein, "top" means furthest away from the substrate, while "bottom" means closest to the substrate. Where a first layer is described as "disposed over" a second layer, the first layer is disposed further away from substrate. There may be other layers between the first and second layer, unless it is specified that the first layer is "in contact with" the second layer. For example, a cathode may be described as "disposed over" an anode, even though there are various organic layers in between.

As used herein, "solution processible" means capable of being dissolved, dispersed, or transported in and/or deposited from a liquid medium, either in solution or suspension form.

A ligand may be referred to as "photoactive" when it is believed that the ligand directly contributes to the photoactive properties of an emissive material. A ligand may be referred to as "ancillary" when it is believed that the ligand does not contribute to the photoactive properties of an emissive material, although an ancillary ligand may alter the properties of a photoactive ligand.

As used herein, and as would be generally understood by one skilled in the art, a first "Highest Occupied Molecular Orbital" (HOMO) or "Lowest Unoccupied Molecular Orbital" (LUMO) energy level is "greater than" or "higher than" a second HOMO or LUMO energy level if the first energy level is closer to the vacuum energy level. Since ionization potentials (IP) are measured as a negative energy relative to a vacuum level, a higher HOMO energy level corresponds to an IP having a smaller absolute value (an IP that is less negative). Similarly, a higher LUMO energy level corresponds to an electron affinity (EA) having a smaller absolute value (an EA that is less negative). On a conventional energy level diagram, with the vacuum level at the top, the LUMO energy level of a material is higher than the HOMO energy level of the same material. A "higher" HOMO or LUMO energy level appears closer to the top of such a diagram than a "lower" HOMO or LUMO energy level.

As used herein, and as would be generally understood by one skilled in the art, a first work function is "greater than"


3

or “higher than” a second work function if the first work function has a higher absolute value. Because work functions are generally measured as negative numbers relative to vacuum level, this means that a “higher” work function is more negative. On a conventional energy level diagram, with the vacuum level at the top, a “higher” work function is illustrated as further away from the vacuum level in the downward direction. Thus, the definitions of HOMO and LUMO energy levels follow a different convention than work functions.

More details on OLEDs, and the definitions described above, can be found in U.S. Pat. No. 7,279,704, which is incorporated herein by reference in its entirety.

SUMMARY OF THE INVENTION

In one aspect, a compound having the formula:




Formula I is provided.

In the compound of Formula I, M is a metal having an atomic weight higher than 40, L is a second ligand, m is the maximum coordination number of the metal M, d is the denticity of L, and n is at least 1. R₁ is independently selected for each ligand and represents di, tri, tetra, penta substitutions, or no substitution. Each of R₁ is independently selected from the group consisting of hydrogen, deuterium, halide, alkyl, cycloalkyl, heteroalkyl, arylalkyl, alkoxy, aryloxy, amino, silyl, germynyl, alkenyl, cycloalkenyl, heteroalkenyl, alkynyl, aryl, heteroaryl, acyl, carbonyl, carboxylic acids, ester, nitrile, isonitrile, sulfanyl, sulfinyl, sulfonyl, phosphino, and combinations thereof.

At least two of R₁ is independently selected from two to six carbon containing alkyl, silyl, germynyl, cycloalkyl, and combinations thereof. R₂ may represent mono, di, tri, tetra substitutions, or no substitution, and each of R₂ is independently selected from the group consisting of hydrogen, deuterium, halide, alkyl, cycloalkyl, heteroalkyl, arylalkyl, alkoxy, aryloxy, amino, silyl, alkenyl, cycloalkenyl, heteroalkenyl, alkynyl, aryl, heteroaryl, acyl, carbonyl, carboxylic acids, ester, nitrile, isonitrile, sulfanyl, sulfinyl, sulfonyl, phosphino, and combinations thereof.

In one aspect, R₁ represents di-substitution. In one aspect, R₁ represents di-alkyl substitution. In another aspect, R₁ represents silyl or germynyl substitution.

In one aspect, the compound has the formula:




wherein R₃ and R₄ are alkyl.

4


In one aspect, the compound has the formula:

Formula III



In one aspect, R₁ is independently selected from the group consisting of CH(CH₃)₂, CH₂CH(CH₃)₂, CH₂C(CH₃)₃, cyclopentyl, cyclohexyl, ethyl, trimethylsilyl, triethylsilyl, triisopropylsilyl, trimethylgermyl, triethylgermyl, and triisopropylgermyl.

In one aspect, n M is Ir. In one aspect, n is 2. In one aspect, L is a monoanionic bidentate ligand. In one aspect, L is



and


R₁, R₃, and R₄ are each independently selected from the group consisting of hydrogen, deuterium, halide, alkyl, cycloalkyl, heteroalkyl, arylalkyl, alkoxy, aryloxy, amino, silyl, alkenyl, cycloalkenyl, heteroalkenyl, alkynyl, aryl, heteroaryl, acyl, carbonyl, carboxylic acids, ester, nitrile, isonitrile, sulfanyl, sulfinyl, sulfonyl, phosphino, and combinations thereof.

In one aspect, R₁, R₃, and R₄ are independently selected from the group consisting of alkyl, hydrogen, deuterium, and combinations thereof.

In one aspect, R₂ is hydrogen or deuterium, and R₃ and R₄ are independently selected from the group consisting of methyl, CH(CH₃)₂, and CH₂CH(CH₃)₂.

In one aspect, the compound has the formula:


Formula IV



In one aspect, the compound is selected from Compound 1-Compound 50.

In one aspect, a first device is provided. The first device comprises a first organic light emitting device, further comprising an anode, a cathode, and an organic layer, disposed between the anode and the cathode, comprising a compound having the formula:

5



Formula I


In the compound of Formula I, M is a metal having an atomic weight higher than 40, L is a second ligand, m is the maximum coordination number of the metal M, d is the denticity of L, and n is at least 1. R₁ is independently selected for each ligand and represents di, tri, tetra, penta substitutions, or no substitution. Each of R₁ is independently selected from the group consisting of hydrogen, deuterium, halide, alkyl, cycloalkyl, heteroalkyl, arylalkyl, alkoxy, aryloxy, amino, silyl, germynl, alkenyl, cycloalkenyl, heteroalkenyl, alkynyl, aryl, heteroaryl, acyl, carbonyl, carboxylic acids, ester, nitrile, isonitrile, sulfanyl, sulfinyl, sulfonyl, phosphino, and combinations thereof.

At least two of R₁ is independently selected from two to six carbon containing alkyl, silyl, germynl, cycloalkyl, and combinations thereof. R₂ may represent mono, di, tri, tetra substitutions, or no substitution, and each of R₂ is independently selected from the group consisting of hydrogen, deuterium, halide, alkyl, cycloalkyl, heteroalkyl, arylalkyl, alkoxy, aryloxy, amino, silyl, alkenyl, cycloalkenyl, heteroalkenyl, alkynyl, aryl, heteroaryl, acyl, carbonyl, carboxylic acids, ester, nitrile, isonitrile, sulfanyl, sulfinyl, sulfonyl, phosphino, and combinations thereof.

In one aspect, the first device is a consumer product. In one aspect, the first device is an organic light-emitting device. In one aspect, the organic layer is an emissive layer and the compound is a non-emissive dopant. In one aspect, the organic layer further comprises a host.

In one aspect, the host is a metal 8-hydroxyquinolate.

In one aspect, the host is selected from the group consisting of:



6


-continued

5

10

15

20



and combinations thereof.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows an organic light emitting device.

FIG. 2 shows an inverted organic light emitting device that does not have a separate electron transport layer.

FIG. 3 shows a compound of Formula I.

DETAILED DESCRIPTION

Generally, an OLED comprises at least one organic layer disposed between and electrically connected to an anode and a cathode. When a current is applied, the anode injects holes and the cathode injects electrons into the organic layer(s). The injected holes and electrons each migrate toward the oppositely charged electrode. When an electron and hole localize on the same molecule, an "exciton," which is a localized electron-hole pair having an excited energy state, is formed. Light is emitted when the exciton relaxes via a photoemissive mechanism. In some cases, the exciton may be localized on an excimer or an exciplex. Non-radiative mechanisms, such as thermal relaxation, may also occur, but are generally considered undesirable.

The initial OLEDs used emissive molecules that emitted light from their singlet states ("fluorescence") as disclosed, for example, in U.S. Pat. No. 4,769,292, which is incorporated by reference in its entirety. Fluorescent emission generally occurs in a time frame of less than 10 nanoseconds.

More recently, OLEDs having emissive materials that emit light from triplet states ("phosphorescence") have been demonstrated. Baldo et al., "Highly Efficient Phosphorescent Emission from Organic Electroluminescent Devices," *Nature*, vol. 395, 151-154, 1998; ("Baldo-I") and Baldo et al., "Very high-efficiency green organic light-emitting devices based on electrophosphorescence," *Appl. Phys. Lett.*, vol. 75, No. 3, 4-6 (1999) ("Baldo-II"), which are incorporated by reference in their entireties. Phosphorescence is described in more detail in U.S. Pat. No. 7,279,704 at cols. 5-6, which are incorporated by reference.

FIG. 1 shows an organic light emitting device 100. The figures are not necessarily drawn to scale. Device 100 may include a substrate 110, an anode 115, a hole injection layer 120, a hole transport layer 125, an electron blocking layer 130, an emissive layer 135, a hole blocking layer 140, an electron transport layer 145, an electron injection layer 150,

a protective layer **155**, and a cathode **160**. Cathode **160** is a compound cathode having a first conductive layer **162** and a second conductive layer **164**. Device **100** may be fabricated by depositing the layers described, in order. The properties and functions of these various layers, as well as example materials, are described in more detail in U.S. Pat. No. 7,279,704 at cols. 6-10, which are incorporated by reference.

More examples for each of these layers are available. For example, a flexible and transparent substrate-anode combination is disclosed in U.S. Pat. No. 5,844,363, which is incorporated by reference in its entirety. An example of a p-doped hole transport layer is m-MTDATA doped with F.sub.4-TCNQ at a molar ratio of 50:1, as disclosed in U.S. Patent Application Publication No. 2003/0230980, which is incorporated by reference in its entirety. Examples of emissive and host materials are disclosed in U.S. Pat. No. 6,303,238 to Thompson et al., which is incorporated by reference in its entirety. An example of an n-doped electron transport layer is BPhen doped with Li at a molar ratio of 1:1, as disclosed in U.S. Patent Application Publication No. 2003/0230980, which is incorporated by reference in its entirety. U.S. Pat. Nos. 5,703,436 and 5,707,745, which are incorporated by reference in their entireties, disclose examples of cathodes including compound cathodes having a thin layer of metal such as Mg:Ag with an overlying transparent, electrically-conductive, sputter-deposited ITO layer. The theory and use of blocking layers is described in more detail in U.S. Pat. No. 6,097,147 and U.S. Patent Application Publication No. 2003/0230980, which are incorporated by reference in their entireties. Examples of injection layers are provided in U.S. Patent Application Publication No. 2004/0174116, which is incorporated by reference in its entirety. A description of protective layers may be found in U.S. Patent Application Publication No. 2004/0174116, which is incorporated by reference in its entirety.

FIG. 2 shows an inverted OLED **200**. The device includes a substrate **210**, a cathode **215**, an emissive layer **220**, a hole transport layer **225**, and an anode **230**. Device **200** may be fabricated by depositing the layers described, in order. Because the most common OLED configuration has a cathode disposed over the anode, and device **200** has cathode **215** disposed under anode **230**, device **200** may be referred to as an "inverted" OLED. Materials similar to those described with respect to device **100** may be used in the corresponding layers of device **200**. FIG. 2 provides one example of how some layers may be omitted from the structure of device **100**.

The simple layered structure illustrated in FIGS. 1 and 2 is provided by way of non-limiting example, and it is understood that embodiments of the invention may be used in connection with a wide variety of other structures. The specific materials and structures described are exemplary in nature, and other materials and structures may be used. Functional OLEDs may be achieved by combining the various layers described in different ways, or layers may be omitted entirely, based on design, performance, and cost factors. Other layers not specifically described may also be included. Materials other than those specifically described may be used. Although many of the examples provided herein describe various layers as comprising a single material, it is understood that combinations of materials, such as a mixture of host and dopant, or more generally a mixture, may be used. Also, the layers may have various sublayers. The names given to the various layers herein are not intended to be strictly limiting. For example, in device **200**,

hole transport layer **225** transports holes and injects holes into emissive layer **220**, and may be described as a hole transport layer or a hole injection layer. In one embodiment, an OLED may be described as having an "organic layer" disposed between a cathode and an anode. This organic layer may comprise a single layer, or may further comprise multiple layers of different organic materials as described, for example, with respect to FIGS. 1 and 2.

Structures and materials not specifically described may also be used, such as OLEDs comprised of polymeric materials (PLEDs) such as disclosed in U.S. Pat. No. 5,247,190 to Friend et al., which is incorporated by reference in its entirety. By way of further example, OLEDs having a single organic layer may be used. OLEDs may be stacked, for example as described in U.S. Pat. No. 5,707,745 to Forrest et al, which is incorporated by reference in its entirety. The OLED structure may deviate from the simple layered structure illustrated in FIGS. 1 and 2. For example, the substrate may include an angled reflective surface to improve out-coupling, such as a mesa structure as described in U.S. Pat. No. 6,091,195 to Forrest et al., and/or a pit structure as described in U.S. Pat. No. 5,834,893 to Bulovic et al., which are incorporated by reference in their entireties.

Unless otherwise specified, any of the layers of the various embodiments may be deposited by any suitable method. For the organic layers, preferred methods include thermal evaporation, ink-jet, such as described in U.S. Pat. Nos. 6,013,982 and 6,087,196, which are incorporated by reference in their entireties, organic vapor phase deposition (OVPD), such as described in U.S. Pat. No. 6,337,102 to Forrest et al., which is incorporated by reference in its entirety, and deposition by organic vapor jet printing (OVJP), such as described in U.S. Pat. No. 7,431,968, which is incorporated by reference in its entirety. Other suitable deposition methods include spin coating and other solution based processes. Solution based processes are preferably carried out in nitrogen or an inert atmosphere. For the other layers, preferred methods include thermal evaporation. Preferred patterning methods include deposition through a mask, cold welding such as described in U.S. Pat. Nos. 6,294,398 and 6,468,819, which are incorporated by reference in their entireties, and patterning associated with some of the deposition methods such as ink-jet and OVJD. Other methods may also be used. The materials to be deposited may be modified to make them compatible with a particular deposition method. For example, substituents such as alkyl and aryl groups, branched or unbranched, and preferably containing at least 3 carbons, may be used in small molecules to enhance their ability to undergo solution processing. Substituents having 20 carbons or more may be used, and 3-20 carbons is a preferred range. Materials with asymmetric structures may have better solution processability than those having symmetric structures, because asymmetric materials may have a lower tendency to recrystallize. Dendrimer substituents may be used to enhance the ability of small molecules to undergo solution processing.


Devices fabricated in accordance with embodiments of the invention may be incorporated into a wide variety of consumer products, including flat panel displays, computer monitors, medical monitors, televisions, billboards, lights for interior or exterior illumination and/or signaling, heads up displays, fully transparent displays, flexible displays, laser printers, telephones, cell phones, personal digital assistants (PDAs), laptop computers, digital cameras, camcorders, viewfinders, micro-displays, vehicles, a large area wall, theater or stadium screen, or a sign. Various control mechanisms may be used to control devices fabricated in accor-

dance with the present invention, including passive matrix and active matrix. Many of the devices are intended for use in a temperature range comfortable to humans, such as 18 degrees C. to 30 degrees C., and more preferably at room temperature (20-25 degrees C.).

The materials and structures described herein may have applications in devices other than OLEDs. For example, other optoelectronic devices such as organic solar cells and organic photodetectors may employ the materials and structures. More generally, organic devices, such as organic transistors, may employ the materials and structures.

The terms halo, halogen, alkyl, cycloalkyl, alkenyl, alkynyl, arylkyl, heterocyclic group, aryl, aromatic group, and heteroaryl are known to the art, and are defined in U.S. Pat. No. 7,279,704 at cols. 31-32, which are incorporated herein by reference.

In one embodiment, a compound having the formula:



Formula I is provided.

In the compound of Formula I, M is a metal having an atomic weight higher than 40, L is a second ligand, m is the maximum coordination number of the metal M, d is the denticity of L, and n is at least 1. By "denticity" it is meant that d numerically represents the number of bonds a second ligand L makes with metal M. Thus, if L is a monodentate ligand, then d is 1, if L is a bidentate ligand, d is 2, etc. L can be one or more ligands, and when L represents more than one ligand, the ligands can be the same or different.

R₁ is independently selected for each ligand and represents di, tri, tetra, penta substitutions, or no substitution. Each of R₁ is independently selected from the group consisting of hydrogen, deuterium, halide, alkyl, cycloalkyl, heteroalkyl, arylalkyl, alkoxy, aryloxy, amino, silyl, germly, alkenyl, cycloalkenyl, heteroalkenyl, alkynyl, aryl, heteroaryl, acyl, carbonyl, carboxylic acids, ester, nitrile, isonitrile, sulfanyl, sulfinyl, sulfonyl, phosphino, and combinations thereof.

At least two of R₁ is independently selected from two to six carbon containing alkyl, silyl, germly, cycloalkyl, and combinations thereof. R₂ may represent mono, di, tri, tetra substitutions, or no substitution, and each of R₂ is independently selected from the group consisting of hydrogen, deuterium, halide, alkyl, cycloalkyl, heteroalkyl, arylalkyl, alkoxy, aryloxy, amino, silyl, alkenyl, cycloalkenyl, heteroalkenyl, alkynyl, aryl, heteroaryl, acyl, carbonyl, carboxylic acids, ester, nitrile, isonitrile, sulfanyl, sulfinyl, sulfonyl, phosphino, and combinations thereof.


It has been unexpectedly discovered that substitution at two or more of positions (i.e. R₁ represents at least di-substitution) on the heterocyclic ring in the compound of Formula I results in compounds with desirable properties. These properties enable OLED devices that incorporate compounds of Formula I to have improved properties such as higher efficiency and longer lifetime. Substitution of two or more positions as described above also results in compounds with lowered sublimation temperatures despite the fact that these compounds have higher molecular weights

than unsubstituted or mono-substituted compounds, where the mono-substitution is on the heterocyclic ring. Without being bound by theory, it is believed that this decrease in sublimation temperature may be the result of decreased or less efficient molecular stacking in the solid state, thereby decreasing the energy required to disrupt the crystal lattice and resulting in decreased sublimation temperatures. Lower sublimation temperatures advantageously allow for easier purification of compounds of Formula I and better thermal stability in manufacturing.

In one embodiment, R₁ represents di-substitution. In one embodiment, R₁ represents di-alkyl substitution. In another embodiment, R₁ represents silyl or germly substitution.

In one embodiment, the compound has the formula:


Formula II



wherein R₃ and R₄ are alkyl.


In one embodiment, the compound has the formula:

Formula III



In one embodiment, R₁ is independently selected from the group consisting of CH(CH₃)₂, CH₂CH(CH₃)₂, CH₂C(CH₃)₃, cyclopentyl, cyclohexyl, ethyl, trimethylsilyl, triethylsilyl, triisopropylsilyl, trimethylgermyl, triethylgermyl, and triisopropylgermyl.

In one embodiment, n M is Ir. In one embodiment, n is 2. In one embodiment, L is a monoanionic bidentate ligand. In one embodiment, L is




and R_x, R_y, and R_z are each independently selected from the group consisting of hydrogen, deuterium, halide, alkyl, cycloalkyl, heteroalkyl, arylalkyl, alkoxy, aryloxy, amino, silyl, alkenyl, cycloalkenyl, heteroalkenyl, alkynyl, aryl, heteroaryl, acyl, carbonyl, carboxylic acids, ester, nitrile, isonitrile, sulfanyl, sulfinyl, sulfonyl, phosphino, and combinations thereof.

11


In one embodiment, R_x , R_y , and R_z are independently selected from the group consisting of alkyl, hydrogen, deuterium, and combinations thereof.

In one embodiment, R_z is hydrogen or deuterium, and R_x and R_y are independently selected from the group consisting of methyl, $\text{CH}(\text{CH}_3)_2$, and $\text{CH}_2\text{CH}(\text{CH}_3)_2$.

In one embodiment, the compound has the formula:








In one embodiment, the compound is selected from the group consisting of:



12


-continued

Compound 4



13


-continued



Compound 9


14

-continued




Compound 13


Compound 10




Compound 14




Compound 11




Compound 15



Compound 12




Compound 16



15

-continued

Compound 17



5


10

15

16


-continued

Compound 21



Compound 22

Compound 18




20

25


30

35



Compound 23


Compound 19



40


45

50



Compound 24


Compound 20



55

60


65



17

-continued


Compound 25




18

-continued


Compound 29



Compound 26





Compound 30





Compound 31

Compound 27



Compound 32


Compound 28



19

-continued

Compound 33



5


10

15

20

-continued

Compound 37




20

25


30

Compound 34




35

Compound 34




50

Compound 36




65


Compound 38



Compound 39




Compound 40




21

-continued


Compound 41




Compound 42



Compound 43




Compound 44


**22**

-continued


Compound 45




Compound 46



Compound 47




Compound 48



23


-continued

Compound 49




, and

Compound 50



In one embodiment, a first device is provided. The first device comprises a first organic light emitting device, further comprising an anode, a cathode, and an organic layer, disposed between the anode and the cathode, comprising a compound having the formula:



Formula I

In the compound of Formula I, M is a metal having an atomic weight higher than 40, L is a second ligand, m is the maximum coordination number of the metal M, d is the denticity of L, and n is at least 1. R₁ is independently selected for each ligand and represents di, tri, tetra, penta substitutions, or no substitution. Each of R₁ is independently selected from the group consisting of hydrogen, deuterium, halide, alkyl, cycloalkyl, heteroalkyl, arylalkyl, alkoxy, aryloxy, amino, silyl, germlyl, alkenyl, cycloalkenyl, heteroalkenyl, alkynyl, aryl, heteroaryl, acyl, carbonyl, carboxylic acids, ester, nitrile, isonitrile, sulfanyl, sulfinyl, sulfonyl, phosphino, and combinations thereof.

At least two of R₁ is independently selected from two to six carbon containing alkyl, silyl, germlyl, cycloalkyl, and


24

combinations thereof. R₂ may represent mono, di, tri, tetra substitutions, or no substitution, and each of R₂ is independently selected from the group consisting of hydrogen, deuterium, halide, alkyl, cycloalkyl, heteroalkyl, arylalkyl, alkoxy, aryloxy, amino, silyl, alkenyl, cycloalkenyl, heteroalkenyl, alkynyl, aryl, heteroaryl, acyl, carbonyl, carboxylic acids, ester, nitrile, isonitrile, sulfanyl, sulfinyl, sulfonyl, phosphino, and combinations thereof.

In one embodiment, the first device is a consumer product. In one embodiment, the first device is an organic light-emitting device. In one embodiment, the organic layer is an emissive layer and the compound is a non-emissive dopant. In one embodiment, the organic layer further comprises a host.

In one embodiment, the host is a metal 8-hydroxyquinolate.

In one embodiment, the host is selected from the group consisting of:



and combinations thereof.




Device Examples

All example devices were fabricated by high vacuum (<10⁻⁷ Torr) thermal evaporation (VTE). The anode electrode is 1200 Å of indium tin oxide (ITO). The cathode consisted of 10 Å of LiF followed by 1000 Å of Al. All devices are encapsulated with a glass lid sealed with an epoxy resin in a nitrogen glove box (<1 ppm of H₂O and O₂) immediately after fabrication, and a moisture getter was incorporated inside the package.


25

The organic stack of the device examples consisted of sequentially, from the ITO surface, 100 Å of Compound A as the hole injection layer (HIL), 400 Å of 4,4'-bis[N-(1-naphthyl)-N-phenylamino]biphenyl (NPD) as the hole transporting layer (HTL), 300 Å of the compound of Formula I doped in with BA1q as host with from 4 to 12 wt % of an iridium-containing phosphorescent compound as the emissive layer (EML), 450 or 550 Å of Alq₃ (tris-8-hydroxyquinoline aluminum) as the electron transport layer (ETL). Comparative Examples with Compound B and C were fabricated similarly to the Device Examples except that the Compound B and C were used as the emitters in the EML.


The device results and data are summarized in Tables 1, 2, and 3 from those devices. As used herein, Compounds A, B, and C have the following structures:



Compound A



Compound B



26

-continued

Compound C




TABLE 1

Device structures of invention compounds and comparative compounds

Example	HIL	HTL	EML (300 Å, doping %)		BL	ETL
Comparative Example 1	Compound A 100 Å	NPD 400 Å	BA1q 6%	Compound B	None	Alq 550 Å
Comparative Example 2	Compound A 100 Å	NPD 400 Å	BA1q 9%	Compound B	None	Alq 550 Å
Comparative Example 3	Compound A 100 Å	NPD 400 Å	BA1q 12%	Compound B	None	Alq 550 Å
Comparative Example 4	Compound A 100 Å	NPD 400 Å	BA1q 6%	Compound C	None	Alq 550 Å
Comparative Example 5	Compound A 100 Å	NPD 400 Å	BA1q 9%	Compound C	None	Alq 550 Å
Comparative Example 6	Compound A 100 Å	NPD 400 Å	BA1q 12%	Compound C	None	Alq 550 Å
Example 1	Compound A 100 Å	NPD 400 Å	BA1q 4%	Compound 1	None	Alq 550 Å
Example 2	Compound A 100 Å	NPD 400 Å	BA1q 6%	Compound 1	None	Alq 550 Å
Example 3	Compound A 100 Å	NPD 400 Å	BA1q 8%	Compound 1	None	Alq 550 Å
Example 4	Compound A 100 Å	NPD 400 Å	BA1q 6%	Compound 1	BA1q 100 Å	Alq 450 Å
Example 5	Compound A 100 Å	NPD 400 Å	BA1q 5%	Compound 2	None	Alq 550 Å
Example 6	Compound A 100 Å	NPD 400 Å	BA1q 7%	Compound 2	None	Alq 550 Å
Example 7	Compound A 100 Å	NPD 400 Å	BA1q 10%	Compound 2	None	Alq 550 Å
Example 8	Compound A 100 Å	NPD 400 Å	BA1q 7%	Compound 2	BA1q 100 Å	Alq 450 Å
Example 9	Compound A 100 Å	NPD 400 Å	BA1q 5%	Compound 3	None	Alq 550 Å
Example 10	Compound A 100 Å	NPD 400 Å	BA1q 7%	Compound 3	None	Alq 550 Å
Example 11	Compound A 100 Å	NPD 400 Å	BA1q 10%	Compound 3	None	Alq 550 Å
Example 12	Compound A 100 Å	NPD 400 Å	BA1q 7%	Compound 3	BA1q 100 Å	Alq 450 Å
Example 13	Compound A 100 Å	NPD 400 Å	BA1q 4%	Compound 22	None	Alq 550 Å
Example 14	Compound A 100 Å	NPD 400 Å	BA1q 6%	Compound 22	None	Alq 550 Å
Example 15	Compound A 100 Å	NPD 400 Å	BA1q 8%	Compound 22	None	Alq 550 Å
Example 16	Compound A 100 Å	NPD 400 Å	BA1q 6%	Compound 22	BA1q 100 Å	Alq 450 Å

TABLE 2

VTE device results									
	x	y	λ_{max} (nm)	FWHM (nm)	Voltage (V)	LE (Cd/A)	EQE (%)	PE (lm/W)	LT80 % (h)
Comparative Example 1	0.693	0.304	635	63	10	10.8	18.3	3.4	606
Compound B									
Comparative Example 2	0.695	0.303	637	66	9.9	10.5	18.5	3.3	799
Compound B									
Comparative Example 3	0.693	0.304	637	66	9.5	10.0	17.7	3.3	948
Compound B									
Comparative Example 4	0.690	0.306	633	63	10.3	12.2	19.1	3.7	650
Compound C									
Comparative Example 5	0.692	0.306	635	65	9.4	11.8	19.3	3.9	475
Compound C									
Comparative Example 6	0.691	0.306	635	66	8.9	11.5	19.0	4.1	700
Compound C									
Example 1	0.687	0.309	628	52	10.1	12.5	17.8	3.9	178
Compound 1									
Example 2	0.689	0.307	630	56	9.9	12.6	18.7	4.0	174
Compound 1									
Example 3	0.691	0.306	632	56	9.5	12.4	19.0	4.1	171
Compound 1									
Example 4	0.690	0.307	630	56	10.9	12.5	18.6	3.6	160
Compound 1									
Example 5	0.687	0.311	630	58	9.5	13.8	19.6	4.6	350
Compound 2									
Example 6	0.688	0.310	630	60	9.5	13.8	19.9	4.5	360
Compound 2									
Example 7	0.688	0.310	632	62	8.8	13.1	19.4	4.7	400
Compound 2									
Example 8	0.687	0.309	630	58	10.5	12.9	18.7	3.9	360
Compound 2									
Example 9	0.685	0.313	626	58	9.5	14.8	19.8	4.9	232
Compound 3									
Example 10	0.687	0.311	628	62	8.9	14.5	20.5	5.1	260
Compound 3									
Example 11	0.688	0.310	630	64	8.1	14.0	20.3	5.4	235
Compound 3									
Example 12	0.687	0.311	628	60	9.7	14.5	20.2	4.7	280
Compound 3									
Example 13	0.684	0.313	626	48	9.3	14.8	18.8	5.0	192
Compound 22									
Example 14	0.686	0.311	626	52	8.8	14.3	19.1	5.1	170
Compound 22									
Example 15	0.686	0.311	628	52	8.2	14.2	19.2	5.4	122
Compound 22									
Example 16	0.686	0.312	626	50	9.3	14.8	19.6	5.0	210
Compound 22									

Table 2 is a summary of the device data. The luminous efficiency (LE), external quantum efficiency (EQE) and power efficiency (PE) were measured at 1000 nits, while the lifetime (LT_{80%}) was defined as the time required for the device to decay to 80% of its initial luminance under a constant current density of 40 mA/cm².

From Table 2, it can be seen that the EQE, LE and PE of Compounds 1, 2, 3, and 22, which are compounds of Formula I, at three different doping concentrations (without a hole blocking layer) are all higher than those of Comparative Compounds B and C. For example, when the device has the same 6% emitter doping concentration without the hole blocking layer, Compound 22 has EQE of 19.1%, LE of 14.3 Cd/A, and PE of 5.1 lm/W, respectively. This compares to

Comparative Compounds B and C which have EQE of 18.3 and 19.1%, LE of 10.8 and 12.2 Cd/A, and PE of 3.4 and 3.7 lm/W, respectively. The device results indicate that, surprisingly, the di-alkyl substituted Compounds 1, 2, 3 and 22 are more efficient than comparative compound B and mono-substituted compound C. It can also be seen from Table 2 that the FWHM (full width at half maximum) values of Compound 1, 2, 3, and 22 under different device structures are in the range of 48-64 nm, which is significantly narrower than those of Compounds B and C, which are in the range of 63-66 nm. Smaller FWHM values are often desirable in display applications. Thus, the use of compounds of Formula I, which are at least di-substituted on the heterocyclic ring contained therein can improve device performance, because these compounds have high EQE, LE, PE values and low FWHM values.

TABLE 3







Comparison of Sublimation Temperatures		
Compounds	Sublimation Temperature (° C.)	Temperature Difference Relative to Compound B
 Compound B	210	
 Compound C	218	-8
 Compound 1	197	13
 Compound 2	202	8

TABLE 3-continued

Comparison of Sublimation Temperatures		
Compounds	Sublimation Temperature (° C.)	Temperature Difference Relative to Compound B
	204	6
Compound 3		
	194	16
Compound 22		

It can be seen that di-substitution on the heteroaromatic ring in compounds of Formula I can decrease the sublimation temperature of complex as shown in Table 3. It was surprisingly discovered that di-substituted compounds of Formula I had lower sublimation temperatures than unsubstituted or mono-substituted compounds. For example, Compound 22 had a significantly lower sublimation temperature than Comparative Compound B (194° C. vs 210° C.) despite the fact that Compound 22 has a higher molecular weight than Comparative Compound B.

Combination with Other Materials


The materials described herein as useful for a particular layer in an organic light emitting device may be used in combination with a wide variety of other materials present in the device. For example, emissive dopants disclosed herein may be used in conjunction with a wide variety of hosts, transport layers, blocking layers, injection layers, electrodes and other layers that may be present. The materials described or referred to below are non-limiting examples of materials that may be useful in combination with the compounds disclosed herein, and one of skill in the art can readily consult the literature to identify other materials that may be useful in combination.

HIL/HTL:


A hole injecting/transporting material to be used in the present invention is not particularly limited, and any compound may be used as long as the compound is typically used as a hole injecting/transporting material. Examples of the material include, but not limit to: a phthalocyanine or

porphyrin derivative; an aromatic amine derivative; an indolocarbazole derivative; a polymer containing fluorohydrocarbon; a polymer with conductivity dopants; a conducting polymer, such as PEDOT/PSS; a self-assembly monomer derived from compounds such as phosphonic acid and silane derivatives; a metal oxide derivative, such as MoO₃; a p-type semiconducting organic compound, such as 1,4,5,8,9,12-Hexaazatriphenylenehexacarbonitrile; a metal complex, and a cross-linkable compounds.

Examples of aromatic amine derivatives used in HIL or HTL include, but not limit to the following general structures:




33




Each of Ar¹ to Ar⁹ is selected from the group consisting aromatic hydrocarbon cyclic compounds such as benzene, biphenyl, triphenyl, triphenylene, naphthalene, anthracene, phenalene, phenanthrene, fluorene, pyrene, chrysene, perylene, azulene; group consisting aromatic heterocyclic compounds such as dibenzothiophene, dibenzofuran, dibenzoselenophene, furan, thiophene, benzofuran, benzothio-
 15 phenone, benzoselenophene, carbazole, indolocarbazole, pyridylindole, pyrrolodipyridine, pyrazole, imidazole, triazole, oxazole, thiazole, oxadiazole, oxatriazole, dioxazole, thiadiazole, pyridine, pyridazine, pyrimidine, pyrazine, tri-
 20 azine, oxazine, oxathiazine, oxadiazine, indole, benzimidazole, indazole, indoxazine, benzoxazole, benzisoxazole, benzothiazole, quinoline, isoquinoline, cinnoline, quinoxaline, naphthyridine, phthalazine, pteridine, xan-
 25 thene, acridine, phenazine, phenothiazine, phenoxazine, benzofuropyridine, fuorodipyridine, benzothienopyridine, thienodipyridine, benzoselenophenopyridine, and seleno-
 30 phenodipyridine; and group consisting 2 to 10 cyclic structural units which are groups of the same type or different types selected from the aromatic hydrocarbon cyclic group and the aromatic heterocyclic group and are bonded to each
 other directly or via at least one of oxygen atom, nitrogen atom, sulfur atom, silicon atom, phosphorus atom, boron atom, chain structural unit and the aliphatic cyclic group. Wherein each Ar is further substituted by a substituent
 35 selected from the group consisting of hydrogen, deuterium, halide, alkyl, cycloalkyl, heteroalkyl, arylalkyl, alkoxy, aryloxy, amino, silyl, alkenyl, cycloalkenyl, heteroalkenyl, alkynyl, aryl, heteroaryl, acyl, carbonyl, carboxylic acids, ester, nitrile, isonitrile, sulfanyl, sulfinyl, sulfonyl, phosphino, and combinations thereof.

In one aspect, Ar¹ to Ar⁹ is independently selected from the group consisting of:




34

-continued



k is an integer from 1 to 20; X¹ to X⁸ is C (including CH) or N; Ar¹ has the same group defined above.

Examples of metal complexes used in HIL or HTL include, but not limit to the following general formula:



M is a metal, having an atomic weight greater than 40; (Y¹-Y²) is a bidentate ligand, Y¹ and Y² are independently selected from C, N, O, P, and S; L is an ancillary ligand; m is an integer value from 1 to the maximum number of
 35 ligands that may be attached to the metal; and m+n is the maximum number of ligands that may be attached to the metal.

In one aspect, (Y¹-Y²) is a 2-phenylpyridine derivative.

In another aspect, (Y¹-Y²) is a carbene ligand.

In another aspect, M is selected from Ir, Pt, Os, and Zn.


In a further aspect, the metal complex has a smallest oxidation potential in solution vs. Fc⁺/Fc couple less than about 0.6 V.

Host:

The light emitting layer of the organic EL device of the present invention preferably contains at least a metal complex as light emitting material, and may contain a host material using the metal complex as a dopant material.

45 Examples of the host material are not particularly limited, and any metal complexes or organic compounds may be used as long as the triplet energy of the host is larger than that of the dopant. While the Table below categorizes host materials as preferred for devices that emit various colors, any host material may be used with any dopant so long as the triplet criteria is satisfied.


Examples of metal complexes used as host are preferred to have the following general formula:



M is a metal; (Y³-Y⁴) is a bidentate ligand, Y³ and Y⁴ are independently selected from C, N, O, P, and S; L is an ancillary ligand; m is an integer value from 1 to the
 60 maximum number of ligands that may be attached to the metal; and m+n is the maximum number of ligands that may be attached to the metal.

35

In one aspect, the metal complexes are:




(O—N) is a bidentate ligand, having metal coordinated to atoms O and N.

In another aspect, M is selected from Ir and Pt.

In a further aspect, (Y³-Y⁴) is a carbene ligand.


Examples of organic compounds used as host are selected from the group consisting aromatic hydrocarbon cyclic compounds such as benzene, biphenyl, triphenyl, triphenylene, naphthalene, anthracene, phenalene, phenanthrene, fluorene, pyrene, chrysene, perylene, azulene; group consisting aromatic heterocyclic compounds such as dibenzothiophene, dibenzofuran, dibenzoselenophene, furan, thiophene, benzofuran, benzothiophene, benzoselenophene, carbazole, indolocarbazole, pyridylindole, pyrrolodipyridine, pyrazole, imidazole, triazole, oxazole, thiazole, oxadiazole, oxatriazole, dioxazole, thiadiazole, pyridine, pyridazine, pyrimidine, pyrazine, triazine, oxazine, oxathiazine, oxadiazine, indole, benzimidazole, indazole, indoxazine, benzoxazole, benzisoxazole, benzothiazole, quinoxaline, isoquinoline, cinnoline, quinazoline, quinoxaline, naphthyridine, phthalazine, pteridine, xanthene, acridine, phenazine, phenothiazine, phenoxazine, benzofuropyridine, furodipyridine, benzothienopyridine, thenodipyridine, benzoselenophenopyridine, and selenophenodipyridine; and group consisting 2 to 10 cyclic structural units which are groups of the same type or different types selected from the aromatic hydrocarbon cyclic group and the aromatic heterocyclic group and are bonded to each other directly or via at least one of oxygen atom, nitrogen atom, sulfur atom, silicon atom, phosphorus atom, boron atom, chain structural unit and the aliphatic cyclic group. Wherein each group is further substituted by a substituent selected from the group consisting of hydrogen, deuterium, halide, alkyl, cycloalkyl, heteroalkyl, arylalkyl, alkoxy, aryloxy, amino, silyl, alkenyl, cycloalkenyl, heteroalkenyl, alkynyl, aryl, heteroaryl, acyl, carbonyl, carboxylic acids, ester, nitrile, isonitrile, sulfanyl, sulfinyl, sulfonyl, phosphino, and combinations thereof.

In one aspect, host compound contains at least one of the following groups in the molecule:



36

-continued



R¹ to R⁷ is independently selected from the group consisting of hydrogen, deuterium, halide, alkyl, cycloalkyl, heteroalkyl, arylalkyl, alkoxy, aryloxy, amino, silyl, alkenyl, cycloalkenyl, heteroalkenyl, alkynyl, aryl, heteroaryl, acyl, carbonyl, carboxylic acids, ester, nitrile, isonitrile, sulfanyl, sulfinyl, sulfonyl, phosphino, and combinations thereof, when it is aryl or heteroaryl, it has the similar definition as Ar's mentioned above.

37

k is an integer from 0 to 20.

X^1 to X^8 is selected from C (including CH) or N.


Z^1 and Z^2 is selected from NR^1 , O, or S.

HBL:

A hole blocking layer (HBL) may be used to reduce the number of holes and/or excitons that leave the emissive layer. The presence of such a blocking layer in a device may result in substantially higher efficiencies as compared to a similar device lacking a blocking layer. Also, a blocking layer may be used to confine emission to a desired region of an OLED.

In one aspect, compound used in HBL contains the same molecule or the same functional groups used as host described above.

In another aspect, compound used in HBL contains at least one of the following groups in the molecule:




k is an integer from 0 to 20; L is an ancillary ligand, m is an integer from 1 to 3.

ETL:


Electron transport layer (ETL) may include a material capable of transporting electrons. Electron transport layer may be intrinsic (undoped), or doped. Doping may be used to enhance conductivity. Examples of the ETL material are not particularly limited, and any metal complexes or organic compounds may be used as long as they are typically used to transport electrons.

In one aspect, compound used in ETL contains at least one of the following groups in the molecule:



38

-continued




R^1 is selected from the group consisting of hydrogen, deuterium, halide, alkyl, cycloalkyl, heteroalkyl, arylalkyl, alkoxy, aryloxy, amino, silyl, alkenyl, cycloalkenyl, heteroalkenyl, alkynyl, aryl, heteroaryl, acyl, carbonyl, carboxylic acids, ester, nitrile, isonitrile, sulfanyl, sulfinyl, sulfonyl, phosphino, and combinations thereof, when it is aryl or heteroaryl, it has the similar definition as Ar's mentioned above.

Ar^1 to Ar^3 has the similar definition as Ar's mentioned above.

k is an integer from 0 to 20.

X^1 to X^8 is selected from C (including CH) or N.

In another aspect, the metal complexes used in ETL contains, but not limit to the following general formula:



(O—N) or (N—N) is a bidentate ligand, having metal coordinated to atoms O, N or N, N; L is an ancillary ligand; m is an integer value from 1 to the maximum number of ligands that may be attached to the metal.

In any above-mentioned compounds used in each layer of the OLED device, the hydrogen atoms can be partially or fully deuterated.

In addition to and/or in combination with the materials disclosed herein, many hole injection materials, hole transporting materials, host materials, dopant materials, exciton/hole blocking layer materials, electron transporting and electron injecting materials may be used in an OLED. Non-limiting examples of the materials that may be used in an OLED in combination with materials disclosed herein are listed in Table 4 below. Table 4 lists non-limiting classes of materials, non-limiting examples of compounds for each class, and references that disclose the materials.

TABLE 4





MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
Hole injection materials		
Phthalocyanine and porphyrin compounds		Appl. Phys. Lett. 69, 2160 (1996)
Starburst triarylamines		J. Lumin. 72-74, 985 (1997)
CF _x Fluorohydrocarbon polymer	$\text{---}[\text{CH}_2\text{CF}_y]_n\text{---}$	Appl. Phys. Lett. 78, 673 (2001)
Conducting polymers (e.g., PEDOT:PSS, polyaniline, polythiophene)		Synth. Met. 87, 171 (1997) WO2007002683
Phosphonic acid and silane SAMs		US20030162053

TABLE 4-continued





MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
Triarylamine or polythiophene polymers with conductivity dopants		EP1725079A1
		
		
Organic compounds with conductive inorganic compounds, such as molybdenum and tungsten oxides		US20050123751 SID Symposium Digest, 37, 923 (2006) WO2009018009

TABLE 4-continued





MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
n-type semiconducting organic complexes		US20020158242
Metal organometallic complexes		US20060240279
Cross-linkable compounds		US20080220265
Polythiophene based polymers and copolymers		WO 2011075644 EP2350216

TABLE 4-continued





MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
Hole transporting materials		
Triarylamines (e.g., TPD, α -NPD)		Appl. Phys. Lett. 51, 913 (1987)
		U.S. Pat. No. 5,061,569
		EP650955
		J. Mater. Chem. 3, 319 (1993)

TABLE 4-continued





MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
		Appl. Phys. Lett. 90, 183503 (2007)
		Appl. Phys. Lett. 90, 183503 (2007)
Triaylamine on spirofluorene core		Synth. Met. 91, 209 (1997)
Arylamine carbazole compounds		Adv. Mater. 6, 677 (1994), US20080124572

TABLE 4-continued





MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
Triarylamine with (di)benzothiophene/(di)benzofuran		US20070278938, US20080106190 US20110163302
Indolocarbazoles		Synth. Met. 111, 421 (2000)
Isoindole compounds		Chem. Mater. 15, 3148 (2003)
Metal carbene complexes		US20080018221

TABLE 4-continued








MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
	Phosphorescent OLED host materials Red hosts	
Arylcarbazoles		Appl. Phys. Lett. 78, 1622 (2001)
Metal 8-hydroxyquinolates (e.g., Alq ₃ , BALq)		Nature 395, 151 (1998)
		US20060202194
		WO2005014551
		WO2006072002
Metal phenoxybenzothiazole compounds		Appl. Phys. Lett. 90, 123509 (2007)
Conjugated oligomers and polymers (e.g., polyfluorene)		Org. Electron. 1, 15 (2000)

TABLE 4-continued







MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
Aromatic fused rings		WO2009066779, WO2009066778, WO2009063833, US20090045731, US20090045730, WO2009008311, US20090008605, US20090009065
Zinc complexes		WO2010056066
Chrysene based compounds		WO2011086863
Green hosts		
Arylcarbazoles		Appl. Phys. Lett. 78, 1622 (2001)
		US20030175553
		WO2001039234

TABLE 4-continued






MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
Aryltriphenylene compounds		US20060280965
		US20060280965
		WO2009021 126
Poly-fused heteroaryl compounds		US20090309488 US20090302743 US20100012931
Donor acceptor type molecules		WO2008056746

TABLE 4-continued






MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
		WO2010107244
Aza-carbazole/DBT/DBF		JP2008074939
		US20100187984
Polymers (e.g., PVK)		Appl. Phys. Lett. 77, 2280 (2000)
Spirofluorene compounds		WO2004093207

TABLE 4-continued






MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
Metal phenoxybenzoxazole compounds		WO2005089025
		WO2006132173
		JP200511610
Spirofluorene-carbazole compounds		JP2007254297
		JP2007254297

TABLE 4-continued






MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
Indolocabazoles		WO2007063796
		WO2007063754
5-member ring electron deficient heterocycles (e.g., triazole, oxadiazole)		J. Appl. Phys. 90, 5048 (2001)
		WO2004107822
Tetraphenylene complexes		US20050112407

TABLE 4-continued







MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
Metal phenoxypyridine compounds		WO2005030900
Metal coordination complexes (e.g., Zn, Al with N'N ligands)	 <p>Blue hosts</p>	US20040137268, US20040137267
Arylcarbazoles		Appl. Phys. Lett, 82, 2422 (2003)
		US20070190359
Dibenzothiophene/ Dibenzofuran-carbazole compounds		WO2006114966, US20090167162
		US20090167162

TABLE 4-continued







MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
		WO2009086028
		US20090030202, US20090017330
		US20100084966
Silicon aryl compounds		US20050238919
		WO2009003898
Silicon/Germanium aryl compounds		EP2034538A

TABLE 4-continued







MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
Aryl benzoyl ester		WO2006100298
Carbazole linked by non-conjugated groups		US20040115476
Aza-carbazoles		US20060121308
High triplet metal organometallic complex	 <p>Phosphorescent dopants Red dopants</p>	U.S. Pat. No. 7,154,114
Heavy metal porphyrins (e.g., PtOEP)		Nature 395, 151 (1998)
Iridium(III) organometallic complexes		Appl. Phys. Lett. 78, 1622 (2001)

TABLE 4-continued






MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
		US2006835469
		US2006835469
		US20060202194
		US20060202194
		US20070087321

TABLE 4-continued






MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
		US20080261076 US20100090591
		US20070087321
		Adv. Mater. 19, 739 (2007)
		WO2009100991
		WO2008101842

TABLE 4-continued







MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
Platinum(II) organometallic complexes		U.S. Pat. No. 7,232,618
		WO2003040257
		US20070103060
Osmium(III) complexes		Chem. Mater. 17, 3532 (2005)
Ruthenium(II) complexes		Adv. Mater. 17, 1059 (2005)
Rhenium (I), (II), and (III) complexes		US20050244673

TABLE 4-continued





MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
Green dopants		
Iridium(III) organometallic complexes	 <p data-bbox="707 786 839 808">and its derivatives</p>	Inorg. Chem. 40, 1704 (2001)
		US20020034656
		U.S. Pat. No. 7,332,232
		US20090108737

TABLE 4-continued






MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
		WO2010028151
		EP1841834B
		US20060127696
		US20090039776
		U.S. Pat. No. 6,921,915

TABLE 4-continued







MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
		US20100244004
		U.S. Pat. No. 6,687,266
		Chem. Mater. 16, 2480 (2004)
		US20070190359
		US 20060008670 JP2007123392
		WO2010086089, WO2011044988

TABLE 4-continued







MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
		Adv. Mater. 16, 2003 (2004)
		Angew. Chem. Int. Ed. 2006, 45, 7800
		WO2009050290
		US20090165846
		US20080015355
		US20010015432

TABLE 4-continued






MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
Monomer for polymeric metal organometallic compounds		US20100295032
		U.S. Pat. No. 7,250,226, U.S. Pat. No. 7,396,598
Pt(II) organometallic complexes, including polydentate ligands		Appl. Phys. Lett. 86, 153505 (2005)
		Appl. Phys. Lett. 86, 153505 (2005)
		Chem. Lett. 34, 592 (2005)

TABLE 4-continued





MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
		WO2002015645
		US20060263635
		US20060182992 US20070103060
Cu complexes		WO2009000673

TABLE 4-continued





MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
		US20070111026
Gold complexes		Chem. Commun. 2906 (2005)
Rhenium(III) complexes		Inorg. Chem. 42, 1248 (2003)
Osmium(II) complexes		U.S. Pat. No. 7,279,704

TABLE 4-continued





MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
Deuterated organometallic complexes		US20030138657
Organometallic complexes with two or more metal centers		US20030152802
	 <p data-bbox="730 1749 820 1765">Blue dopant</p>	U.S. Pat. No. 7,090,928
Iridium(III) organometallic complexes		WO2002002714

TABLE 4-continued

MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
		WO2006009024
		US20060251923 US20110057559 US20110204333
		U.S. Pat. No. 7,393,599, WO2006056418, US20050260441, WO2005019373
		U.S. Pat. No. 7,534,505
		WO2011051404
		U.S. Pat. No. 7,445,855

TABLE 4-continued






MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
		US20070190359, US20080297033 US20100148663
		U.S. Pat. No. 7,338,722
		US20020134984
		Angew. Chem. Int. Ed. 47, 1 (2008)
		Chem. Mater. 18, 5119 (2006)

TABLE 4-continued






MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
		Inorg. Chem. 46, 4308 (2007)
		WO2005123873
		WO2005123873
		WO2007004380
		WO2006082742

TABLE 4-continued







MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
Osmium(II) complexes		U.S. Pat. No. 7,279,704
		Organometallics 23, 3745 (2004)
Gold complexes		Appl. Phys. Lett. 74, 1361 (1999)
Platinum(II) complexes		WO2006098120, WO2006103874
Pt tetradentate complexes with at least one metal-carbene bond		U.S. Pat. No. 7,655,323
Exciton/hole blocking layer materials		
Bathocuprine compounds (e.g., BCP, BPhen)		Appl. Phys. Lett. 75, 4 (1999)

TABLE 4-continued





MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
		Appl. Phys. Lett. 79, 449 (2001)
Metal 8-hydroxyquinolates (e.g., BALq)		Appl. Phys. Lett. 81, 162 (2002)
5-member ring electron deficient heterocycles such as triazole, oxadiazole, imidazole, benzoimidazole		Appl. Phys. Lett. 81, 162 (2002)
Triphenylene compounds		US20050025993

TABLE 4-continued





MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
Fluorinated aromatic compounds		Appl. Phys. Lett. 79, 156 (2001)
Phenothiazine-S-oxide		WO2008132085
Silylated five-membered nitrogen, oxygen, sulfur or phosphorus dibenzoheterocycles		WO2010079051
Aza-carbazoles		US20060121308

TABLE 4-continued






MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
Electron transporting materials		
Anthracene-benzimidazole compounds		WO2003060956
		US20090179554
Aza triphenylene derivatives		US20090115316
Anthracene-benzothiazole compounds		Appl. Phys. Lett. 89, 063504 (2006)
Metal 8-hydroxyquinolates (e.g., Alq ₃ , Zr _q ₄)		Appl. Phys. Lett. 51, 913 (1987) U.S. Pat. No. 7,230,107

TABLE 4-continued







MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
Metal hydroxybenzoquinolates		Chem. Lett. 5, 905 (1993)
Bathocuprine compounds such as BCP, BPhen, etc		Appl. Phys. Lett. 91, 263503 (2007)
		Appl. Phys. Lett. 79, 449 (2001)
5-member ring electron deficient heterocycles (e.g., triazole, oxadiazole, imidazole, benzimidazole)		Appl. Phys. Lett. 74, 865 (1999)
		Appl. Phys. Lett. 55, 1489 (1989)
		Jpn. J. Apply. Phys. 32, L917 (1993)

TABLE 4-continued







MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
Silole compounds		Org. Electron. 4, 113 (2003)
Arylborane compounds		J. Am. Chem. Soc. 120, 9714 (1998)
Fluorinated aromatic compounds		J. Am. Chem. Soc. 122, 1832 (2000)
Fullerene (e.g., C60)		US20090101870
Triazine complexes		US20040036077

TABLE 4-continued


MATERIAL	EXAMPLES OF MATERIAL	PUBLICATIONS
Zn (N'N) complexes		U.S. Pat. No. 6,528,187

EXPERIMENTAL



-continued

Chemical abbreviations used throughout this document are as follows: Cy is cyclohexyl, dba is dibenzylideneacetone, EtOAc is ethyl acetate, DME is dimethoxyethane, dppe is 1,2-bis(diphenylphosphino)ethane, THF is tetrahydrofuran, DCM is dichloromethane, DMF is dimethylformamide, S-Phos is dicyclohexyl(2',6'-dimethoxy-[1,1'-biphenyl]-2-yl)phosphine.


Synthesis of Compound 1



Synthesis of N-(3,5-dichlorobenzylidene)-2,2-diethoxyethanamine. 3,5-dichlorobenzaldehyde (51.2 g, 284 mmol), 2,2-diethoxyethanamine (38.6 g, 284 mmol) and 270 mL toluene were charged in a 500 mL three-necked flask. The mixture was heated to reflux for 24 hours under N₂ with Dean-Stark apparatus to collect water by-product. 86 g (100%) light yellow liquid was obtained after evaporated solvent. The product was confirmed by GC-MS and NMR and taken on to the next step without further purification.




Synthesis of 5, 7-dichloroisoquinoline. Trifluoromethanesulfonic acid (15.83 g, 103 mmol) was charged in a three-necked 100 mL flask which was equipped with a Dean-Stark apparatus and an addition funnel. The trifluoromethanesulfonic acid was first heated to 120° C. and to the acid, N-(3,5-dichlorobenzylidene)-2,2-diethoxyethanamine (4 g, 13.78 mmol) dissolved in 4 mL DCM was added dropwise. After addition, the mixture was heated for another 2 hours at 120° C., then cooled to room temperature, and 8 mL of MeOH was added to quench the reaction. The reaction mixture was poured into aqueous ammonium hydroxide (120 mmol) solution, made basic with additional aqueous ammonium hydroxide, and stirred and filtered. A white solid (2.1 g, 77%) was obtained after distillation. The identity of the product was confirmed by GC and HPLC. A larger scale reaction with 32.2 g of N-(3,5-dichlorobenzylidene)-2,2-diethoxyethanamine was conducted in a same way and 16.5 g (75%) of the product was obtained for next step.





111

Synthesis of 5,7-diisobutylyisoquinoline. 5,7-Dichloroisoquinoline (5.8 g, 29.3 mmol), isobutylboronic acid (8.96 g, 88 mmol), dicyclohexyl(2',6'-dimethoxy-[1,1'-biphenyl]-2-yl)phosphine (0.962 g, 2.34 mmol), $\text{Pd}_2(\text{dba})_3$ (0.536 g, 0.586 mmol), K_3PO_4 (21.8 g, 103 mmol), 150 mL toluene and 15 mL water were charged in a flask. The reaction mixture was purged by bubbling N_2 for 30 minutes then heated to reflux overnight. GC-MS analysis showed that the reaction was complete. Silica gel chromatography with 15% ethyl acetate in hexane (v/v) as eluent resulted in 6.7 g (95%) of the product.



15


Synthesis of 1-(3,5-dimethylphenyl)-5,7-diisobutylyisoquinoline. 5,7-Diisobutylyisoquinoline (7.4 g, 30.7 mmol) in 50 mL dry THF and was added to (3,5-dimethylphenyl)magnesium bromide (100 mL, 50.0 mmol) dropwise at room temperature and allowed to stir for 16 hours, after which the reaction mixture was heated to reflux for 5 hours. GC and HPLC analysis indicated the reaction was complete, but contained a small amount of reduced byproducts which were converted to the desired product by treatment with DDQ in THF for few minutes. After aqueous workup, 6.5 g (61.4%) of product was obtained.



Synthesis of iridium dimer. 1-(3,5-dimethylphenyl)-5,7-diisobutylyisoquinoline (6.0 g, 17.37 mmol) and $\text{IrCl}_3 \cdot \text{H}_2\text{O}$ (2.57 g, 6.95 mmol), 90 mL 2-ethoxyethanol and 30 mL water were charged in a 250 mL flask. The reaction mixture was heated to reflux under nitrogen for 19 hours. 3.1 g (24.3%) of dimer was obtained after filtration and washing with methanol, which was used for next step without further purification.


112

-continued




113

114




Synthesis of Compound 1 2-(3,5-dimethylphenyl)-5,7-diisobutylquinoline iridium dimer (1.5 g, 0.82 mmol), 2,4-pentanedione (1.63 g, 16.36 mmol), Na_2CO_3 (1.73 g, 16.36 mmol) and 2-ethoxyethanol (60 mL) were charged in a 250 mL flask and stirred at room temperature for 72 hours. The resulting precipitate was filtered and washed with methanol. The solid was further purified by passing it through a silica gel plug (that was pretreated with 15% triethylamine in hexanes). 0.55 g (34.3%) of product was obtained after workup. The identity of the product was confirmed by LC-MS.


overnight. GC-MS analysis showed that the reaction was complete. 5.1 g (91%) of product was obtained after silica gel column chromatography and confirmed by GC-MS.



Synthesis of Compound 2




Synthesis of 5,7-diisopropylisoquinoline: 5,7-Di(prop-1-en-2-yl)isoquinoline (5.1 g, 24.37 mmol) was dissolved in 50 mL EtOH in a glass bottle and purged with N_2 for 30 minutes. To the solution, 10% Pd/C (1.3 g, 1.218 mmol) was added into the bottle under nitrogen. Hydrogenation was conducted for 4 hours, after which GC-MS analysis indicated the reaction was complete.



Synthesis of 5,7-di(prop-1-en-2-yl)isoquinoline: 5,7-Dichloroisoquinoline (5.1 g, 25.8 mmol), 4,4,5,5-tetramethyl-2-(prop-1-en-2-yl)-1,3,2-dioxaborolane (9.95 g, 59.2 mmol), dicyclohexyl(2',6'-dimethoxy-[1,1'-biphenyl]-2-yl)phosphine (0.846 g, 2.06 mmol), $\text{Pd}_2(\text{dba})_3$ (0.472 g, 0.515 mmol), K_3PO_4 (19.13 g, 90 mmol), 100 mL toluene and 10 mL water were charged in a flask. The reaction mixture was purged by bubbling N_2 for 30 minutes then heated to reflux

115


Synthesis of 1-(3,5-dimethylphenyl)-5,7-diisopropylisoquinoline. 5,7-diisopropylisoquinoline (3.1 g, 14.5 mmol) in 50 mL dry THF and was added with 0.5 M (3,5-dimethylphenyl)magnesium bromide THF solution (50 mL, 25.0 mmol) dropwise at room temperature and allowed to stir for 16 hours, after which the reaction mixture was heated to



116

reflux for 5 hours. GC and HPLC analysis indicated the reaction was complete, but contained a small amount of reduced byproducts which were converted to the desired product by treatment with DDQ in THF for few minutes. After aqueous workup, 2.4 g (52%) of product was obtained.


Synthesis of iridium dimer. 1-(3,5-Dimethylphenyl)-5,7-diisopropylisoquinoline (2.4 g, 7.56 mmol) and $\text{IrCl}_3 \cdot \text{H}_2\text{O}$ (1.167 g, 3.15 mmol), 45 mL 2-ethoxyethanol and 15 mL water were charged in a 250 mL flask. The reaction mixture was heated to reflux under nitrogen for 19 hours. After cooling the reaction, filtration, and washing with methanol, 1.2 g (44.2%) of dimer was obtained, which was used for next step without further purification.




Synthesis of Compound 2 2-(3,5-Dimethylphenyl)-5,7-diisopropylquinoline iridium dimer (1.2 g, 0.697 mmol), 2,4-pentanedione (0.697 g, 6.97 mmol), Na_2CO_3 (0.739 g, 6.97 mmol) and 2-ethoxyethanol (40 mL) were stirred at room temperature for 48 hours. The precipitate was filtered and washed with methanol. The solid was further purified by passing it through a silica gel plug (pretreated with 15% triethylamine in hexanes). After workup of the reaction 0.68 g (52.8%) of product was obtained, which was confirmed by LC-MS.

117


Synthesis of Compound 3



Synthesis of 4-Chloro-2-methylbenzoyl chloride. To a mixture of 4-chloro-2-methylbenzoic acid (24.0 g, 141 mmol) in dichloromethane (20 mL) and dimethylformamide (4 mL) at room temperature was added dropwise oxalyl chloride (26.8 g, 258 mmol). The reaction was stirred room temperature for 2 hours. Hexanes were added and the reaction mass was concentrated to give 4-chloro-2-methylbenzoyl chloride (26.6 g, quantitative) and used in the next step without purification.




Synthesis of 4-Chloro-2-methylbenzamide. 30% Ammonium hydroxide (300 mL, 4.76 mol) was cooled in a salt ice bath. 4-chloro-2-methylbenzoyl chloride (26.4 g, 140 mmol) in tetrahydrofuran (150 mL) added and stirred for 1 hr. Water was added. Crystals were filtered off and washed with water and dried under vacuum to give 4-chloro-2-methylbenzamide (20.0 g, 84% yield).




Synthesis of 4-Chloro-N-((dimethylamino)methylene)-2-methylbenzamide. A mixture of 4-chloro-2-methylbenzamide (20.8 g, 123 mmol) and 1,1-dimethylmethaneamine (17.5 g, 147 mmol) in tetrahydrofuran (250 mL) was refluxed for 2.5 hours and then concentrated. The resulting

118


crystals were triturated in hexanes and filtered to give 4-chloro-N-((dimethylamino)methylene)-2-methylbenzamide (25.7 g, 93% yield).



Synthesis of 6-Chloroisoquinolin-1-ol. A mixture of 4-chloro-N-((dimethylamino)methylene)-2-methylbenzamide (25.7 g, 114 mmol), sodium tert-butoxide (25.7 g, 267 mmol) and tetrahydrofuran (450 mL) was refluxed under N_2 for 3 hours and then poured into water (1 L). The pH was adjusted to 4 with aqueous HCl. The solids were filtered off and washed with water and dried under vacuum to give 6-chloroisoquinolin-1-ol (14.7 g, 71.6% yield).




Synthesis of 4,6-Dichloroisoquinolin-1-ol. A mixture of 6-chloroisoquinolin-1-ol (13.5 g, 75 mmol) and acetonitrile (400 mL) was heated to reflux. N-Chlorosuccinimide (10.57 g, 79 mmol) in acetonitrile (110 mL) was added dropwise. The mixture was refluxed overnight. Crystals were filtered off. The filtrate was concentrated and the resulting crystals were washed with water and combined with the above crystals and dried under vacuum to give 4,6-dichloroisoquinolin-1-ol (14.2 g, 88% yield). It was taken on without analysis to the next step.




119

Synthesis of 4,6-Dichloroisoquinolin-1-yl trifluoromethanesulfonate. A mixture of 4, 6-dichloroisoquinolin-1-ol (14.2 g, 66.5 mmol), pyridine (10.8 mL, 133 mmol) and dichloromethane (200 mL) was cooled in an ice bath. Trifluoromethanesulfonic anhydride (22.4 mL, 133 mmol) was added dropwise. The mixture was stirred overnight at room temperature. Water was added and NaHCO_3 (20 g) was added slowly. The organic layer was dried over Na_2SO_4 , concentrated and flash chromatographed using silica gel chromatography (4:1 hexanes: dichloromethane, v/v) to give 4,6-dichloroisoquinolin-1-yl trifluoromethanesulfonate (3.7 g, 16% yield).




Synthesis of 4,6-Dichloro-1-(3,5-dimethylphenyl)isoquinoline. A mixture of 4,6-dichloroisoquinolin-1-yl trifluoromethanesulfonate (4.0 g, 11.6 mmol), 3,5-dimethylphenyl boronic acid (1.6 g, 10.8 mmol), $\text{Pd}(\text{PPh}_3)_4$ (0.67 g, 0.58 mmol), potassium carbonate (4.79 g, 34.7 mmol), toluene (100 mL) and water (10 mL) was purged with nitrogen and refluxed overnight. The concentrated toluene layer was chromatographed using silica gel chromatography (100% dichloromethane to 4:1 dichloromethane:ethyl acetate, v/v) to give 4,6-dichloro-1-(3,5-dimethylphenyl)isoquinoline (3.3 g, 90% yield).



120

graphed using silica gel chromatography (2:1 hexanes:dichloromethane, v/v) to give 4,6-dichloro-1-(3,5-dimethylphenyl)isoquinoline (3.0 g, 92% yield).




Synthesis of 1-(3,5-Dimethylphenyl)isoquinoline. A mixture of 4,6-dichloro-1-(3,5-dimethylphenyl)isoquinoline (3.2 g, 10.59 mmol), isobutylboronic acid (4.32 g, 42.4 mmol), PdAdba_3 (0.388 g, 0.424 mmol), dicyclohexyl(2',6'-dimethoxy-[1,1'-biphenyl]-2-yl)phosphine (0.696 g, 1.694 mmol), $\text{K}_3\text{PO}_4 \cdot \text{H}_2\text{O}$ (24.38 g, 106 mmol), toluene (133 mL) and water (11 mL) were purged with nitrogen for 30 minutes and refluxed overnight. The toluene layer was chromatographed using silica gel chromatography (100% dichloromethane to 4:1 dichloromethane:ethyl acetate, v/v) to give 1-(3,5-dimethylphenyl)isoquinoline (3.3 g, 90% yield).

Synthesis of 1-(3,5-Dimethylphenyl)isoquinoline Iridium dimer. A mixture of 1-(3,5-dimethylphenyl)-4,6-diisobutylisoquinoline (3.3 g, 9.55 mmol), $\text{IrCl}_3 \cdot 3\text{H}_2\text{O}$ (1.475 g, 3.98 mmol), 2-ethoxyethanol (45 mL) and water (15 mL) were refluxed overnight and then filtered and washed with methanol to give 1-(3,5-dimethylphenyl)isoquinoline iridium dimer (2.0 g, 54.8% yield).

121

122




30

Synthesis of Compound 3 A mixture of 1-(3,5-dimethylphenyl)isoquinoline iridium dimer (1.2 g, 0.655 mmol), pentane-2,4-dione (0.655 g, 6.55 mmol), potassium carbonate (0.905 g, 6.55 mmol) and 2-ethoxyethanol (60 mL) was stirred at room temperature overnight and filtered, washed with methanol and chromatographed using silica gel chromatography (4:1 hexanes:dichloromethane, v/v, silica gel

35

pre-treated with triethylamine). The residue was dissolved in dichloromethane and 2-propanol. The dichloromethane was removed on a rotoevaporator and 0.68 g of crystals were filtered off and then sublimed at 230° C. to give Compound 3 (0.32 g, 24.9%), which was confirmed by LC-MS.

Synthesis of Compound 22




123

Synthesis of Compound 22 A mixture of 1-(3,5-dimethylphenyl)isoquinoline iridium dimer (0.8 g, 0.436 mmol), 2,6-dimethylheptane-3,5-dione (0.682 g, 4.36 mmol), potassium carbonate (0.603 g, 4.36 mmol) and 2-ethoxyethanol (60 mL) were stirred at room temperature overnight and filtered, washed with methanol and chromaographed on silica gel (4:1 hexanes:dichloromethane, v/v, silica gel pre-treated with triethylamine). The residue was dissolved in dichloromethane and 2-propanol. The dichloromethane was removed on a rotoevaporator and 0.60 g of crystals were obtained after filtration. It was confirmed by LC-MS.

It is understood that the various embodiments described herein are by way of example only, and are not intended to limit the scope of the invention. For example, many of the materials and structures described herein may be substituted with other materials and structures without deviating from the spirit of the invention. The present invention as claimed may therefore include variations from the particular examples and preferred embodiments described herein, as will be apparent to one of skill in the art. It is understood that various theories as to why the invention works are not intended to be limiting.

The invention claimed is:

1. A compound having the formula:



wherein M is Ir;

wherein m is 6;

wherein d is 2;

wherein n is 1 or 2;


wherein each of R_{13} , R_{14} , R_{15} , R_{16} , and R_{17} is independently selected from the group consisting of hydrogen, deuterium, halide, alkyl, cycloalkyl, heteroalkyl, arylalkyl, alkoxy, aryloxy, amino, silyl, germly, alkenyl, cycloalkenyl, heteroalkenyl, alkynyl, aryl, heteroaryl, acyl, carbonyl, carboxylic acids, ester, nitrile, isonitrile, sulfanyl, sulfinyl, sulfonyl, phosphino, and combinations thereof;

wherein at least two of R_{13} , R_{14} , R_{15} , R_{16} , R_{17} , and R_{18} are alkyl with two to three carbon atoms;

wherein up to five of R_{13} , R_{14} , R_{15} , R_{16} , R_{17} , and R_{18} are other than hydrogen;

wherein R_{18} is alkyl with two to three carbon atoms;

wherein L is



and

wherein R_z is selected from the group consisting of hydrogen, deuterium, halide, alkyl, cycloalkyl, het-

124

eroalkyl, arylalkyl, alkoxy, aryloxy, amino, silyl, alkenyl, cycloalkenyl, heteroalkenyl, alkynyl, aryl, heteroaryl, acyl, carbonyl, carboxylic acids, ester, nitrile, isonitrile, sulfanyl, sulfinyl, sulfonyl, phosphino, and combinations thereof, and

wherein R_x and R_y are independently selected from the group consisting of $\text{CH}(\text{CH}_3)_2$ and $\text{CH}_2\text{CH}(\text{CH}_3)_2$.

2. The compound of claim 1, wherein n is 2.


3. A first device comprising a first organic light emitting device, comprising:

an anode;

a cathode; and

an organic layer, disposed between the anode and the cathode, comprising a compound having the formula:

Formula II



wherein M is Ir;

wherein m is 6;

wherein d is 2;

wherein n is 1 or 2;


wherein each of R_{13} , R_{14} , R_{15} , R_{16} , and R_{17} is independently selected from the group consisting of hydrogen, deuterium, halide, alkyl, cycloalkyl, heteroalkyl, arylalkyl, alkoxy, aryloxy, amino, silyl, germly, alkenyl, cycloalkenyl, heteroalkenyl, alkynyl, aryl, heteroaryl, acyl, carbonyl, carboxylic acids, ester, nitrile, isonitrile, sulfanyl, sulfinyl, sulfonyl, phosphino, and combinations thereof;

wherein at least two of R_{13} , R_{14} , R_{15} , R_{16} , R_{17} , and R_{18} are alkyl with two to three carbon atoms;

wherein up to five of R_{13} , R_{14} , R_{15} , R_{16} , R_{17} , and R_{18} are other than hydrogen;

wherein R_{18} is alkyl with two to three carbon atoms;

wherein L is



and

wherein R_z is selected from the group consisting of hydrogen, deuterium, halide, alkyl, cycloalkyl, heteroalkyl, arylalkyl, alkoxy, aryloxy, amino, silyl, alkenyl, cycloalkenyl, heteroalkenyl, alkynyl, aryl, heteroaryl, acyl, carbonyl, carboxylic acids, ester, nitrile, isonitrile, sulfanyl, sulfinyl, sulfonyl, phosphino, and combinations thereof, and

wherein R_x and R_y are independently selected from the group consisting of $\text{CH}(\text{CH}_3)_2$ and $\text{CH}_2\text{CH}(\text{CH}_3)_2$.

125


4. The first device of claim 3, wherein the first device is a consumer product.

5. The first device of claim 3, wherein the first device is an organic light-emitting device.


6. The first device of claim 3, wherein the organic layer is an emissive layer and the compound is a non-emissive dopant.

7. The first device of claim 3, wherein the organic layer further comprises a host, wherein the host is a metal 8-hydroxyquinolate.

8. The first device of claim 3, wherein the organic layer further comprises a host, wherein the host is selected from the group consisting of:



126



and combinations thereof.

9. The compound of claim 1, wherein R_z is selected from the group consisting of halide, alkyl, cycloalkyl, heteroalkyl, arylalkyl, alkoxy, aryloxy, amino, silyl, alkenyl, cycloalkenyl, heteroalkenyl, alkynyl, aryl, heteroaryl, acyl, carbonyl, carboxylic acids, ester, nitrile, isonitrile, sulfanyl, sulfinyl, sulfonyl, phosphino, and combinations thereof.

10. The device of claim 3, wherein R_z is selected from the group consisting of halide, alkyl, cycloalkyl, heteroalkyl, arylalkyl, alkoxy, aryloxy, amino, silyl, alkenyl, cycloalkenyl, heteroalkenyl, alkynyl, aryl, heteroaryl, acyl, carbonyl, carboxylic acids, ester, nitrile, isonitrile, sulfanyl, sulfinyl, sulfonyl, phosphino, and combinations thereof.

11. The compound of claim 1, wherein R_{13} is alkyl with two to three carbon atoms.

12. The compound of claim 1, wherein R_{14} is alkyl with two to three carbon atoms.

13. The compound of claim 1, wherein R_{15} is alkyl with two to three carbon atoms.

14. The compound of claim 1, wherein R_{16} is alkyl with two to three carbon atoms.


15. The compound of claim 1, wherein R_{17} is alkyl with two to three carbon atoms.

* * * * *

专利名称(译)	有机电致发光材料和器件		
公开(公告)号	US10454046	公开(公告)日	2019-10-22
申请号	US15/336201	申请日	2016-10-27
[标]申请(专利权)人(译)	环球展览公司		
申请(专利权)人(译)	通用显示器公司		
当前申请(专利权)人(译)	通用显示器公司		
[标]发明人	MA BIN DEANGELIS ALAN XIA CHUANJUN		
发明人	MA, BIN DEANGELIS, ALAN XIA, CHUANJUN		
IPC分类号	H01L51/54 C07F15/00 H01L51/00 C09K11/06 H05B33/14 C09K11/02 H01L51/50		
CPC分类号	C09K11/06 C07F15/0033 H01L51/0072 H05B33/14 H01L51/0085 C09K11/025 H01L51/5088 H01L51/5096 H01L51/5056 C09K2211/185 H01L51/5016 H01L51/5072 C09K2211/1029 H01L51/5024 H01L51/5092		
代理机构(译)	DUANE MORRIS LLP		
其他公开文献	US20170047531A1		
外部链接	Espacenet		

摘要(译)

提供了新颖的磷光金属络合物，其包含在异喹啉环上具有至少两个取代基的2-苯基异喹啉配体。所公开的化合物具有低的升华温度，这使得易于纯化和制造各种OLED器件。



Formula I