

(19)



(11)

EP 2 588 177 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:

01.01.2020 Bulletin 2020/01

(21) Application number: **11800020.7**

(22) Date of filing: **29.06.2011**

(51) Int Cl.:

A61M 16/00 ^(2006.01) **A61M 16/04** ^(2006.01)
A61M 16/12 ^(2006.01) **A61B 5/0488** ^(2006.01)
A61M 16/20 ^(2006.01) **A61M 16/16** ^(2006.01)
A61B 5/087 ^(2006.01) **A61B 5/00** ^(2006.01)

(86) International application number:

PCT/CA2011/000765

(87) International publication number:

WO 2012/000096 (05.01.2012 Gazette 2012/01)

(54) **SYSTEM FOR PATIENT-SYNCHRONIZED VENTILATORY ASSIST WITH ENDOTRACHEAL THROUGH-FLOW**

SYSTEM ZUR MIT DEM PATIENTEN SYNCHRONISIERTEN ATMUNGSUNTERSTÜTZUNG MIT
ENDOTRACHEALEM DURCHFLUSS

SYSTÈME D'ASSISTANCE RESPIRATOIRE SYNCHRONISÉE AU PATIENT AVEC ÉCOULEMENT
ENDOTRACHÉAL

(84) Designated Contracting States:

**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR**

(30) Priority: **30.06.2010 US 359951 P**

(43) Date of publication of application:
08.05.2013 Bulletin 2013/19

(73) Proprietor: **St. Michael's Hospital
Toronto, ON M5B 1W8 (CA)**

(72) Inventors:

• **SINDERBY, Christer
Toronto
Ontario M6S 1W6 (CA)**

• **BECK, Jennifer**

**Toronto
Ontario M6S 1W6 (CA)**

(74) Representative: **Ipside**

**7-9 Allées Haussmann
33300 Bordeaux Cedex (FR)**

(56) References cited:

**CA-A1- 2 575 939 US-A- 5 291 882
US-A- 5 429 123 US-A- 5 540 220
US-A- 5 671 752 US-A- 5 820 560
US-A- 5 820 560 US-A1- 2004 221 854
US-B1- 6 588 423 US-B1- 6 901 286**

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

EP 2 588 177 B1

Description

TECHNICAL FIELD

5 **[0001]** The present disclosure relates to the field of ventilatory assist systems. More specifically, the present disclosure relates to a method and a system for patient-synchronized ventilatory assist with endotracheal throughflow.

BACKGROUND

10 **[0002]** A recurring problem in patients with impaired function of the respiratory system is that the volume of air-exchanging lung parenchyma is reduced. This may be due to either edema, lung collapse and/or other factors. If a volume of air-transporting parenchyma/airways, comprising for example the main bronchi, trachea, and upper airways is maintained, the volume of air-exchanging parenchyma decreases relative to that of the air-transporting parenchyma/airways. In situations of increased need for CO₂ removal, a ventilatory contribution may be hampered if a dead space, or dead volume, in an air-transporting parenchyma/airways and in a respiratory circuit for a mechanical ventilator, becomes abnormally large relative to a proportion of the lungs with intact air-exchanging parenchyma. Consequently, CO₂ removal is hampered and arterial CO₂ (PaCO₂) may increase. This causes the tidal volume and ventilation to increase in order to maintain a tolerable level of arterial pressure (PaCO₂).

15 **[0003]** Until today, efforts have been made to minimize dead space, or dead volume, introduced in the respiratory circuit of mechanical ventilators. However actual tubes, for example endotracheal tubes, and other devices of conventional mechanical ventilators used to administer respiratory assist to a patient use single lumen designs and contribute to dead space ventilation. For that reason, CO₂ removal cannot be optimized.

20 **[0004]** Previous attempts to improve CO₂ removal from endotracheal tubes include multi-lumen designs aimed at introducing an air flow through a side lumen to eliminate CO₂ from a main lumen. An example of such design may be found in U.S. Patent No. 5,291,882. The proposed approach, which uses parallel lumens, does not eliminate completely the volume of air re-breathed by the patient during inspiration. Thus the proposed approach reduces, but does not optimize the CO₂ removal and minimize the CO₂ rebreathing problem. Moreover, problems of dynamic hyperinflation due to constant inspiratory flow has also complicated this approach. Other approaches using tube lumens with valve functions may increase risk of occlusion.

25 **[0005]** Other examples of prior art systems are disclosed in US 2004/221854 A1, US 5 820 560 A and US 5 429 123 A.

30 **[0006]** Therefore, there is a need for improvements leading to further reduction or elimination of dead space induced by the respiratory circuit of a mechanical ventilator.

SUMMARY

35 **[0007]** According to the present disclosure, there is provided a patient-synchronized ventilatory assist system. The ventilatory assist system comprises a tube for connection to a patient's airway, an inspiratory tube lumen connected to the tube, an expiratory tube lumen connected to the tube, an inspiratory air source connected to the inspiration tube lumen, and a controller of the pressure in the expiratory tube lumen. The pressure controller is responsive to a physiological breathing signal representative of patient's inspiratory effort. Based on the physiological breathing signal, the pressure controller allows an unrestricted air flow through the expiratory tube lumen during a patient's expiration phase and partially restricts the air flow through the expiratory tube lumen to a minimum air flow during a patient's inspiration phase. During both the patient's inspiration and expiration phases, a unidirectional air flow is produced through the inspiratory tube lumen and the expiratory tube lumen to prevent air expired by the patient from being breathed again.

40 **[0008]** Further, there is disclosed a patient-synchronized ventilatory assist method. The method comprises supplying an air flow in an inspiratory tube lumen of a tube connected to a patient's airway and, in response to a physiological breathing signal representative of patient's inspiratory effort, controlling an air flow in an expiratory tube lumen of the tube connected to the patient's airway. Controlling the air flow allows an unrestricted air flow through the expiratory tube lumen during a patient's expiration phase. Controlling the air flow also partially restricts the air flow through the expiratory tube lumen to a minimum air flow during a patient's inspiration phase. During both the patient's inspiration and expiration phases, a unidirectional air flow is produced through the inspiratory tube lumen and the expiratory tube lumen to prevent air expired by the patient from being breathed again.

45 **[0009]** The problem of the prior arts systems are solved with the features of claim 1.

50 **[0010]** The foregoing and other features will become more apparent upon reading of the following non-restrictive description of illustrative embodiments thereof, given by way of example only with reference to the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0011] Embodiments of the disclosure will be described by way of example only with reference to the accompanying drawings, in which:

Figure 1 is a side cross sectional, partial view of an example of double-lumen endotracheal tube showing intratracheal pulmonary ventilation;

Figure 2 is block diagram of an exemplary pressure control system for use with the double-lumen endotracheal tube of Figure 1;

Figure 3 is an example of connection of the double-lumen endotracheal tube of Figure 1 with the pressure control system of Figure 2;

Figure 4a is a graph of experimental recordings of physiological respiratory parameters illustrating operation of a conventional ventilator system;

Figure 4b is a graph of experimental recordings of physiological respiratory parameters using the double-lumen endotracheal tube and pressure control system of Figures 1 and 2;

Figure 5 is a flow chart of exemplary steps of a ventilatory assist method, capable of reducing neural inspiratory drive of a patient; and

Figure 6 is a flow chart of other aspects of the ventilatory assist method of Figure 5.

DETAILED DESCRIPTION

[0012] Various aspects of the present disclosure generally address one or more of the problems related to the presence of dead space induced by respiratory circuits of mechanical ventilators. The present disclosure also relates to a ventilatory assist system including a feature of reduction of anatomical dead space in a patient's airways.

[0013] The following terminology is used throughout the present disclosure:

Ventilatory assist system:	Apparatus adapted for medical use for assisting a patient in need of respiratory support.
Airway:	Of a patient, lungs, bronchi, trachea, pharynx, nose and mouth, through which air is breathed.
Air:	Any gas composition suitable for use in a ventilatory assist system. In the context of the present disclosure, the term "air" may refer to natural air, pure oxygen, natural air enriched with added oxygen, oxygen mixed with another gases such as water vapor, or any combination thereof. This term may also refer to air expelled from a patient's lungs, for example natural air containing additional CO ₂ and humidity.
Lumen:	A bore of a tube, for example a respiratory tube. A given tube may comprise a plurality of lumens.
Physiological signal:	A measurable biometric quantity capable of being transmitted, for example as an electrical signal. such as the physiological breathing signal, generated by respiratory muscles.
Inspiratory effort:	Voluntary or involuntary exertion of a breathing patient. This may be quantified as a neural measure.
Restricted/unrestricted:	In the context of the present disclosure, an air flow present in a tube, lumen, or like conduit may be subject to a variable resistance, or restriction. It is well-known to those skilled in the art of fluid mechanics that any conduit will apply at least a minimum resistance to a flow. The terms "unrestricted" and "restricted" should be understood as relative terms expressing, respectively, a lower and a higher resistance to an air flow.
Minimum air flow:	A partially restricted, non-zero air flow.
Endotracheal:	Of a tube adapted for placement into a patient's trachea.
Synchrony:	Time-wise correspondence between events.

[0014] A result of the reduction and elimination of dead space induced by the respiratory circuit of a mechanical ventilator is a reduction of respiratory drive, tidal volumes and ventilation, for example in critically ill patients. In this manner, mechanical ventilation may be used to efficiently unload the patient's respiratory system and respiratory muscles. Also, ventilatory CO₂ removal is optimized due to the reduction of dead space, limiting CO₂ rebreathing, which in turn reduces metabolic load.

[0015] The ventilatory assist system introduced herein supply ventilatory assist during inspiration via an endotracheal tube structured for delivering a separate, unidirectional inspiratory air flow into the patient's trachea via a first inspiratory

tube lumen and a separate, unidirectional expiratory air flow from the patient's trachea through a second expiratory tube lumen. Also, a unidirectional flow of air is produced and maintained through the inspiratory tube lumen and the expiratory tube lumen; in this manner, ventilatory circuit dead space is eliminated, anatomical dead space is substantially reduced and washing out of CO₂ is optimized.

[0016] In an aspect, mechanical ventilation may be synchronized with patient's effort to breathe. For example, a physiological breathing signal is used to regulate the ventilatory assist in synchrony with patient's neural inspiration effort, thereby unloading and compensating for weak respiratory muscles.

[0017] Turning now to the appended drawings, Figure 1 is a side cross sectional, partial view of an example of double-lumen endotracheal tube showing intratracheal pulmonary ventilation. A double-lumen endotracheal tube 103 shown on Figure 1 forms part of a mechanical ventilator system for delivering air to the lungs 110 of a patient via the trachea 112. Schematically shown in Figure 1 are an inspiratory flow in direction 106 toward the patient's lungs 110 and an expiratory flow in direction 107 away from the patient's lungs 110, through the double-lumen endotracheal tube 103 inserted into the trachea 112. Direction 106 is shown as a narrow arrow while direction 107 is shown as a thick arrow; this should be understood as a schematic manner of illustrating that the inspiratory flow in direction 106 originates from a smaller-diameter inspiratory tube lumen (also shown in Figure 3) while the expiratory flow in direction 107 is directed through a larger-diameter expiratory tube lumen (also shown in Figure 3).

[0018] Figure 2 is block diagram of an exemplary pressure control system for use with the double-lumen endotracheal tube of Figure 1. Figure 3 is an example of connection of the double-lumen endotracheal tube of Figure 1 with the pressure control system of Figure 2. Therefore, the following description will refer to Figures 2 and 3 concurrently.

[0019] One inspiratory air source 100 is connected to an inspiratory line 101 and generates an air pressure, volume or flow to produce a target air flow through the inspiratory line 101. The inspiratory line 101 is in turn connected to an inspiratory tube lumen 102 of the double-lumen endotracheal tube 103 that is inserted into the patient's trachea 112. The inspiratory tube lumen 102 may be a single or multiple lumen.

[0020] A second lumen of the double-lumen endotracheal tube 103, hereinafter referred to as an expiratory tube lumen 104, is connected to an expiratory line 105 connected to a pressure controller 200. The pressure controller 200 may include a pressure sensor 201 and a valve 202 connected to an exhaust 204. A similar system for regulating air flow through the expiratory tube lumen 104 and the expiratory line 105 may be used instead of the controller 200 as shown. The pressure controller 200 may be feedback operated to produce and maintain a given pressure in the expiratory tube lumen 104 and the expiratory line 105. As will be described in more detail in the following description, the valve 202 may be controlled by a physiological breathing signal 250 for synchronizing the air flow through the expiratory tube lumen 104 and the expiratory line 105 with this physiological breathing signal 250. The pressure controller 200 operates in such a manner that the valve 202 restricts, but does not completely occlude the expiratory line 105 such that a minimum outward air flow remains present in the expiratory tube lumen 104 and the expiratory line 105 during the patient's inspiratory phase. Modulation of the restriction of the air flow through the expiratory tube lumen 104 allows adjustment of the pressure in the respiratory circuit of the mechanical ventilator to be proportional to the physiological breathing signal 250. A lowest pressure limit may be manually set to ensure sufficient positive end-expiratory pressure (PEEP) to maintain lung recruitment during neural expiration.

[0021] More specifically, the inspiratory air source 100 generates a target air flow through the inspiratory line 101 and the inspiratory tube lumen 102. In turn, the pressure controller 200 regulates a pressure for controlling air flow escaping the trachea 112 and the patient's lungs 110 through the expiratory tube lumen 104 and the expiratory line 105; more specifically, the pressure controller uses the valve 202 to alter a resistance to air flow of the expiratory tube lumen 104 and expiratory line 105.

[0022] The problem of limiting air flow resistance through the expiratory tube lumen 104 and the expiratory line 105 is resolved by providing the expiratory tube lumen 104 with a diameter larger than that of the inspiratory tube lumen 102. The larger resistance to air flow of the smaller-diameter inspiratory tube lumen 102 causes a larger pressure drop. However, the effect of this larger pressure drop is compensated for by using the inspiratory air source 100 to generate a target air flow through the inspiratory tube lumen 102.

[0023] A feedback system 300 between the pressure controller 200 and the inspiratory air source 100 ensures that the target air flow through the inspiratory line 101 and inspiratory tube lumen 102 is adjusted to generate a preset target pressure in the trachea 112, the expiratory tube lumen 104 and the expiratory line 105. The feedback system 300 comprises a first comparator 301 and an optional second comparator used as a minimum flow detector 302. The comparator 301 may receive a target pressure signal from a target pressure adjuster 270.

[0024] The target pressure adjuster 270 is responsive to the physiological breathing signal 250 to adjust the level of a target pressure. The physiological breathing signal 250 is a physiological signal as defined hereinabove. It may be reliably obtained as a measure of the electrical activation of the patient's diaphragm (EAdi), obtained for example using a method as described in US patents No. 5,671,752, 5,820,560, 6,588,423 and 6,901,286. The physiological breathing signal 250 may alternatively take the form of an electromyogram (EMG) signal obtained at the level of the alea of the nose (EMG-AN) of the patient, or at the thorax level (EMG-THO) of the patient. Biometric signals from the phrenical

nerve of the patient, surface EMG, or measures of chest wall movements of the patient may also be used. Of course any other suitable physiological breathing signal 250 indicative of inspiratory effort including onset detection of the inspiratory effort, before the generation of inspiratory flow occurs, may be used. For example, the target pressure adjuster 270 may increase the level of the target pressure when the level of the physiological breathing signal 250 increases, indicating an increase of the patient's inspiratory effort. In the same manner, the adjuster 270 may decrease the level of the target pressure when the level of the physiological breathing signal 250 decreases, indicating a decrease of the patient's inspiratory effort. In fact, the target pressure may be adjusted by the target pressure adjuster 270 in proportion to the level of patient's inspiratory activity as indicated by the level of the physiological breathing signal 250 or in any other manner beneficial to patient's inspiratory assist. In an embodiment, the target pressure may further be set to ensure sufficient positive end-expiratory pressure (PEEP). Obviously, the target pressure adjuster 270 may also be set at a single level independent of the physiological breathing signal 250.

[0025] Operation of the feedback system 300 follows the following rules:

- The target air flow through the inspiratory line 101 and inspiratory tube lumen 102 is increased when the comparator 301 detects that the pressure reading 203 from the pressure sensor 201 of the pressure controller 200, indicative of the pressure in the trachea 112, expiratory tube lumen 104 and expiratory line 105 during the patient's inspiration phase is lower than a target pressure, which may be set according to a target pressure signal from the target pressure adjuster 270.
- The target air flow through the inspiratory line 101 and inspiratory tube lumen 102 is decreased when the comparator 301 detects that the pressure reading 203 from the pressure sensor 201 of the pressure controller 200, indicative of the pressure in the trachea 112, expiratory tube lumen 104 and expiratory line 105 during the patient's inspiration phase is higher than the target pressure from the target pressure adjuster 270, and also if it is higher than the manually set PEEP level. Before decreasing the target air flow through the inspiratory line 101 and inspiratory tube lumen 102, the minimum flow detector 302 ensures that the inspiratory air source 100 maintains a target air flow, through the inspiratory line 101 and inspiratory tube lumen 102, that is at least equal to or higher than a minimum value. If not, the target air flow through the inspiratory line 101 and inspiratory tube lumen 102 is maintained. The minimum value used in the minimum flow detector 302 for the target air flow is selected to be sufficient to ensure continuous washing out of CO₂.

[0026] Operation of the pressure control system 300 may be synchronized using the physiological breathing signal 250. More specifically, the valve 202 of the pressure controller 200 will partially close when the physiological breathing signal 250 indicates patient's inspiratory effort to allow the target air flow from the inspiratory line 101 and the inspiratory tube lumen 102 to build up a pressure in the endotracheal tube 103, the expiratory tube lumen 104 and the expiratory line 105 in order to assist inspiration of the patient. The valve 202 is partially closed to maintain a minimum air flow through the expiratory tube lumen 104 and the expiratory line 105 to contribute to, if not completely eliminate, substantially reduce ventilatory circuit dead space and anatomical dead space, and ensure continuous washing out of CO₂. When the physiological breathing signal 250 no longer indicates inspiratory effort of the patient, the valve 202 is opened to an extent that allows the patient to expire through the double-lumen endotracheal tube 103, the expiratory tube lumen 104, the expiratory line 105, the valve 202 and the exhaust 204 while maintaining a certain level of expiratory pressure to prevent, for example, collapse of the lungs.

[0027] It should be understood that, during both the inspiration and expiration phases, a unidirectional air flow is produced through the inspiratory line 101, the inspiratory tube lumen 102, the expiratory tube lumen 104 and the expiratory line 105 to prevent air expired by the patient to be breathed again. In this manner, ventilatory circuit dead space and anatomical dead space are, if not completely eliminated, substantially reduced and continuous washing out of CO₂ is ensured.

[0028] In an embodiment, a gain adjuster 260 may alter the physiological breathing signal 250 to adjust the level of the pressure in the trachea 112, expiratory tube lumen 104 and expiratory line 105, and thereby adjust the level of ventilatory assistance to the patient. For example, the adjustable gain 260 may be manually set by the medical personnel. Automatic adjustment of the gain 260 may also be contemplated, for example to obtain a target level of ventilatory assistance or physiological breathing signal 250.

[0029] Some options, amongst others, to deliver inspiratory assist to the patient are the following:

- A target pressure or volume may be supplied to the patient during inspiration.
- As explained in the foregoing description, the target pressure may be adjusted by the target pressure adjuster 270 in proportion to the level of patient's inspiratory activity as indicated by the level of the physiological breathing signal 250 or in any other manner beneficial to patient's inspiratory assist.

- A mathematical model may be used for calculating a pressure loss within the endotracheal tube 103 based on a known air flow resistance and the diameters of the endotracheal tube 103, the expiratory tube lumen 104 and the expiratory line 105, and on a measurement of the air flow through these endotracheal tube 103, the expiratory tube lumen 104 and the expiratory line 105. The calculated pressure loss may then serve as the target pressure used by the comparator 301.
- Another option is to directly measure a pressure at the free, proximal end of the endotracheal tube 103 inserted into the patient's trachea 112, near the tracheal bifurcation 150 (Figure 1), and use this pressure as the target pressure of the comparator 301.

[0030] Oxygen from an oxygen source 356 may be injected in the inspiratory line 101 through a gas mixer 350 to enrich the target air flow through the inspiratory line 101 and inspiratory tube lumen 102.

[0031] To ensure adequate humidification, a humidity sensor (hygrometer) 352 may be used to detect humidity in the expiratory line 105 and, in response to the detected humidity, control a humidifier 354 connected to the gas mixer 350 to humidify, whenever needed, the target air flow through the inspiratory line 101 and the inspiratory tube lumen 102.

[0032] Figure 4a is a graph of experimental recordings of physiological respiratory parameters illustrating operation of a conventional ventilator system. The graph of Figure 4a may be compared with the graph of Figure 4b, which is a graph of experimental recordings of physiological respiratory parameters using the double-lumen endotracheal tube and pressure control system of Figures 1 and 2. Both Figures 4a and 4b show recordings of air flow (402a, 402b), pressure (404a, 404b), and endtidal carbon dioxide (406a, 406b), measured in the expiratory line 105. Figures 4a and 4b also show recordings of diaphragm electrical activity (EAdi (408a, 408b)).

[0033] In the case of Figure 4a, the air flow is bidirectional (inspiration and expiration) during each breathing cycle. It may be observed that the flow (402a) is above a zero line (403a) during inspiration phases and below the zero line (403a) during expiration phases. This produces a dead space in a breathing tube (not shown) of the conventional ventilator system, corresponding to a volume of an expiratory line and tube lumen. Consequently, a volume of expired air from the lungs is returned to the lungs during the next inspiration.

[0034] The graph of Figure 4b illustrates recordings obtained using the double-lumen endotracheal tube 103 and pressure control system 300 of Figures 1 and 2, wherein no air from the expiratory tube lumen 104 and the expiratory line 105 is returned to the patient's lungs 110. The air flow (402b) is unidirectional from the patient's lungs 110 towards the atmosphere and constantly remains below a zero line (403b). No volume of expired air from the patient's lungs 110 is returned to the lungs during the next inspiration.

[0035] It may be observed that, in Figure 4b, the endtidal carbon dioxide (406b) level is markedly reduced, compared to the corresponding level (406a) of Figure 4a, during respiratory assist with the double-lumen endotracheal tube 103 and pressure control system 300 of Figures 1 and 2. It may also be observed that the diaphragm electrical activity (408b) and delivered pressure (404b) are reduced in Figure 4b, compared to corresponding readings (408a, 404a) of Figure 4a, although the ventilator system settings are the same. It may further be observed that generation of the pressure (404b) is synchronized with the diaphragm electrical activity (408b).

[0036] A comparison of the graphs of Figures 4a and 4b shows that the double-lumen endotracheal tube 103 and pressure control system 300 of Figures 1 and 2 may unload the patient's respiratory muscles by delivering ventilatory assist that is synchronized to the neural inspiratory effort (EAdi (408b)) both in terms of timing and pressure generation. Moreover, dead space may be minimized, and the metabolic load may be reduced (lower ETCO₂, 406b) thereby further reducing respiratory drive (EAdi (408b)).

[0037] Figure 5 is a flow chart of exemplary steps of a ventilatory assist method, capable of reducing neural inspiratory drive of a patient. Steps of a sequence 500 may be applied to a ventilatory assist system disclosed in the foregoing description given in relation to Figures 1, 2 and 3. In operation 510, an air flow is supplied in the inspiration tube lumen 102 of the tube 103 connected to the patient's airways. In response to a physiological signal representative of the patient's inspiratory effort, received in operation 520, control of the air flow in an expiratory tube lumen 102 of the tube 103 connected to the patient's airway is made in operation 530. The control made in operation 530 is such that during the patient's inspiratory phase, the air flow through the expiratory tube lumen 104 connected to the patient's airways is partially restricted. In contrast, during the patient's expiratory phase, the air flow is unrestricted to allow expiratory flow from the patient's trachea 112 to evacuate through the endotracheal tube 103, the expiratory tube lumen 104, and thereby through the expiratory line 105.

[0038] A result of the control made in operation 530 is that during both the patient's inspiration and expiration phases, a unidirectional air flow is produced through the inspiratory tube lumen 102 and the expiratory tube lumen 104 to prevent air expired by the patient from being breathed again.

[0039] Control of the air flow made in operation 530 may for example be made by actuating the valve 202 of Figure 2.

[0040] Figure 6 is a flow chart of other aspects of the ventilatory assist method of Figure 5. It should be understood that the operations of the sequence 600 of Figure 6 may also be applied in a ventilatory assist system as described in

connection with the description of Figures 1, 2 and 3. More specifically, the sequence 600 comprises:

- Operation 610: A target air flow is produced by the inspiratory air source 100 through the inspiratory tube lumen 101 and the inspiratory line 102.
- Operation 620: The physiological breathing signal 250 representative of inspiratory effort of the patient is received by the pressure control system 300.
- Operation 630: The target pressure adjuster 270 adjusts a target pressure in response to the physiological breathing signal 250.
- Operation 640: Pressure in the endotracheal tube 103, the expiratory tube lumen 104 and the expiratory line 105 is sensed, or detected, through pressure sensor 201.
- Operation 650: The target air flow produced by the inspiratory air source 100 in the inspiratory line 101 and the inspiratory tube lumen 102 is adjusted, or controlled, as a function of a comparison by the comparator 301 between the pressure detected in the endotracheal tube 103, the expiratory tube lumen 104 and the expiratory line 105 and the target pressure from the adjuster 270.
- Operation 660: The physiological breathing signal 250 is used to control air flow through the expiratory tube lumen 104 and the expiratory line 105 by controlling opening of the valve 202, thereby altering a pressure in the double-lumen endotracheal tube 103, the expiratory tube lumen 104 and the expiratory line 105 in synchrony with the patient's inspiratory effort as indicated by the physiological breathing signal 250. In operation 660, when the physiological breathing signal 250 indicates an expiratory phase, the valve 202 is opened to an extent to allow the patient to expire through the double-lumen endotracheal tube 103, the expiratory tube lumen 104, the expiratory line 105, the valve 202 and the exhaust 204 while maintaining a certain level of expiratory pressure to prevent, for example, collapse of the lungs during that expiratory phase.
- Operation 670: When the physiological breathing signal 250 indicates an inspiratory phase, the valve 202 will partially close to increase resistance to air flow through the expiratory tube lumen 104 and the expiratory line 105 to allow the target air flow from the inspiratory line 101 and the inspiratory tube lumen 102 to build up a pressure in the endotracheal tube 103, the expiratory tube lumen 104 and the expiratory line 105 in order to assist inspiration of the patient. The valve 202 is partially closed to maintain a minimum air flow through the endotracheal tube 103, the expiratory tube lumen 104 and the expiratory line 105 to contribute to eliminate ventilatory circuit dead space and substantially reduce anatomical dead space, and ensure continuous washing out of CO₂.

[0041] Those of ordinary skill in the art will realize that the description of the devices and not claimed methods for patient-synchronized ventilatory assist are illustrative only and are not intended to be in any way limiting. Other embodiments will readily suggest themselves to such persons with ordinary skill in the art having the benefit of the present disclosure. Furthermore, the disclosed patient-synchronized ventilatory assist may be customized to offer valuable solutions to existing needs and problems of ventilatory assist systems.

[0042] In the interest of clarity, not all of the routine features of the implementations of patient-synchronized ventilatory assist systems and not claimed methods are shown and described. It will, of course, be appreciated that in the development of any such actual implementation of the patient-synchronized ventilatory assist systems and methods, numerous implementation-specific decisions may need to be made in order to achieve the developer's specific goals, such as compliance with application-, system- and business-related constraints, and that these specific goals will vary from one implementation to another and from one developer to another. Moreover, it will be appreciated that a development effort might be complex and time-consuming, but would nevertheless be a routine undertaking of engineering for those of ordinary skill in the field of ventilatory assist systems having the benefit of the present disclosure.

[0043] In accordance with the present disclosure, the components, process steps, and/or signal structures described herein may be implemented using various types of operating systems, computing platforms, network devices, computer programs, and/or general purpose machines. In addition, those of ordinary skill in the art will recognize that devices of a less general purpose nature, such as hardwired devices, field programmable gate arrays (FPGAs), application specific integrated circuits (ASICs), or the like, may also be used. Where a not claimed method comprising a series of process steps is implemented by a computer or a machine and those process steps may be stored as a series of instructions readable by the machine, they may be stored on a tangible medium.

[0044] Systems and modules described herein may comprise software, firmware, hardware, or any combination(s) of software, firmware, or hardware suitable for the purposes described herein. Software and other modules may reside on

servers, workstations, personal computers, computerized tablets, personal digital assistants (PDA), and other devices suitable for the purposes described herein. Software and other modules may be accessible via local memory, via a network, via a browser or other application or via other means suitable for the purposes described herein. Data structures described herein may comprise computer files, variables, programming arrays, programming structures, or any electronic information storage schemes or not claimed methods, or any combinations thereof, suitable for the purposes described herein.

[0045] Although the present disclosure has been described hereinabove by way of non-restrictive, illustrative embodiments thereof, these embodiments may be modified at will within the scope of the appended claims without departing from the nature of the present disclosure.

Claims

1. A ventilatory assist system, comprising:

a tube (103) for connection to an airway (112) of a patient;
 an inspiratory tube lumen (102) connected to the tube (103);
 an expiratory tube lumen (104) connected to the tube (103);
 one inspiratory air source (100) connected to the inspiratory tube lumen (102) and adapted to generate a target air flow through the inspiratory tube lumen (102); and
 a pressure controller (200) adapted to regulate a pressure in the expiratory tube lumen (104),
characterized in that:

the pressure controller (200) is responsive to a physiological breathing signal (250) representative of an inspiratory effort of the patient for allowing an expiratory air flow to pass without restriction through the expiratory tube lumen (104) during an expiration phase of the patient and for partially restricting the expiratory air flow through the expiratory tube lumen (104) to maintain a minimum of the expiratory air flow through the expiratory tube lumen (104) during an inspiration phase of the patient;
 wherein, during both the inspiration and expiration phases of the patient, a unidirectional flow of air is produced and maintained by the inspiratory air source (100) through the inspiratory tube lumen (102) and the expiratory tube lumen (104) to prevent air expired by the patient from being breathed again.

2. The ventilatory assist system of claim 1, wherein the pressure controller (200) comprises a valve (202) controlled and synchronized using the physiological breathing signal (250).

3. The ventilatory assist system of claim 2, wherein the valve (202) is for partially restricting the expiratory air flow through the expiratory tube lumen (104).

4. The ventilatory assist system of claim 1, wherein the physiological breathing signal (250) is a measure of electrical activation of a diaphragm (EAdi) of the patient.

5. The ventilatory assist system of claim 1, further comprising:

a pressure sensor (201) for sensing a pressure in the expiratory tube lumen (104); and
 a feedback system (300) interposed between the pressure sensor (201) and the inspiratory air source (100).

6. The ventilatory assist system of claim 5, wherein the feedback system (300) comprises a comparator (301) of the pressure sensed by the pressure sensor in the expiratory tube lumen (104) to a target pressure.

7. The ventilatory assist system of claim 6, further comprising a target pressure adjuster (270) for setting the target pressure.

8. The ventilatory assist system of claim 6, wherein the inspiratory air source (100) is for increasing the target air flow through the inspiratory tube lumen (102) based on a low pressure detection from the comparator (301).

9. The ventilatory assist system of claim 5, wherein the feedback system (300) comprises a minimum flow detector (302) for maintaining at least the minimum of the expiratory air flow through the expiratory tube lumen (104).

10. The ventilatory assist system of claim 9, wherein the inspiratory air source (100) is for maintaining at least the minimum of the expiratory air flow through the expiratory tube lumen (104) based on a signal from the minimum flow detector (302).

11. The ventilatory assist system of claim 1, wherein the tube (103) is an endotracheal tube.

12. The ventilatory assist system of claim 1, wherein the inspiratory tube lumen (102) is a smaller-diameter tube lumen and the expiratory tube lumen (104) is a larger-diameter tube lumen.

13. The ventilatory assist system of claim 1, further comprising a gas mixer (350) connected to the inspiration tube lumen (102).

14. The ventilatory assist system of claim 13, further comprising an oxygen source (356) connected to the gas mixer (350).

15. The ventilatory assist system of claim 13, further comprising:

a hygrometer (352) connected to the expiratory tube lumen (104); and
a humidifier (354) controlled by the hygrometer (352) and connected to the gas mixer (350).

16. The ventilatory assist system of claim 1, further comprising a gain adjuster (260) interposed between a source of the physiological breathing signal (250) and the pressure controller (200) for adjusting a level of ventilatory assistance to the patient.

Patentansprüche

1. Atemunterstützungssystem, Folgendes umfassend:

einen Schlauch (103) zur Verbindung mit einem Atemweg (112) eines Patienten;
ein Einatmungsschlauchlumen (102), verbunden mit dem Schlauch (103);
ein Ausatmungsschlauchlumen (104), verbunden mit dem Schlauch (103);
eine Einatmungsluftquelle (100), verbunden mit dem Einatmungsschlauchlumen (102) und dafür geeignet, einen Zielluftstrom durch das Einatmungsschlauchlumen (102) zu erzeugen; und
eine Drucksteuerung (200), dafür geeignet, einen Druck in dem Ausatmungsschlauchlumen (104) zu regulieren,
dadurch gekennzeichnet, dass:

die Drucksteuerung (200) auf ein physiologisches Atemsignal (250) anspricht, repräsentativ für eine respiratorische Anstrengung des Patienten, um es einem Ausatmungsluftstrom zu ermöglichen, während einer Ausatmungsphase des Patienten ohne Beschränkung durch das Ausatmungsschlauchlumen (104) zu passieren, und um den Ausatmungsluftstrom durch das Ausatmungsschlauchlumen (104) teilweise zu beschränken, um während einer Einatmungsphase des Patienten ein Minimum des Ausatmungsluftstroms durch das Ausatmungsschlauchlumen (104) aufrechtzuerhalten;
wobei sowohl während der Einatmungs- als auch der Ausatmungsphasen des Patienten von der Einatmungsluftquelle (100) ein unidirektionaler Luftstrom durch das Einatmungsschlauchlumen (102) und das Ausatmungsschlauchlumen (104) erzeugt und aufrechterhalten wird, um zu verhindern, dass von dem Patienten ausgeatmete Luft erneut geatmet wird.

2. Atemunterstützungssystem nach Anspruch 1, wobei die Drucksteuerung (200) ein Ventil (202) umfasst, gesteuert und synchronisiert unter Verwendung des physiologischen Atemsignals (250).

3. Atemunterstützungssystem nach Anspruch 2, wobei das Ventil (202) zum teilweisen Beschränken des Ausatmungsluftstroms durch das Ausatmungsschlauchlumen (104) dient.

4. Atemunterstützungssystem nach Anspruch 1, wobei das physiologische Atemsignal (250) eine Messung von elektrischer Aktivierung eines Zwerchfells (EAdi) des Patienten ist.

5. Atemunterstützungssystem nach Anspruch 1, weiter umfassend:

einen Drucksensor (201) zum Wahrnehmen eines Drucks in dem Ausatmungsschlauchlumen (104); und ein Rückmeldesystem (300), zwischengeschaltet zwischen dem Drucksensor (201) und der Einatemungsluftquelle (100).

- 5 6. Atemunterstützungssystem nach Anspruch 5, wobei das Rückmeldesystem (300) einen Vergleich (301) des von dem Drucksensor wahrgenommenen Drucks in dem Ausatmungsschlauchlumen (104) mit einem Zieldruck umfasst.
7. Atemunterstützungssystem nach Anspruch 6, weiter umfassend einen Zieldruckanpasser (270) zum Einstellen des Zieldrucks.
- 10 8. Atemunterstützungssystem nach Anspruch 6, wobei die Einatemungsluftquelle (100) zum Erhöhen des Zielluftstroms durch das Einatemungsschlauchlumen (102) basierend auf einer Niederdruckerkenung von dem Vergleich (301) dient.
- 15 9. Atemunterstützungssystem nach Anspruch 5, wobei das Rückmeldesystem (300) einen Mindeststromdetektor (302) zum Aufrechterhalten wenigstens des Minimums des Ausatemungsluftstroms durch das Ausatemungsschlauchlumen (104) umfasst.
- 20 10. Atemunterstützungssystem nach Anspruch 9, wobei die Einatemungsluftquelle (100) zum Aufrechterhalten wenigstens des Minimums des Ausatemungsluftstroms durch das Ausatemungsschlauchlumen (104) basierend auf einem Signal von dem Mindeststromdetektor (302) dient.
11. Atemunterstützungssystem nach Anspruch 1, wobei der Schlauch (103) ein endotrachealer Schlauch ist.
- 25 12. Atemunterstützungssystem nach Anspruch 1, wobei das Einatemungsschlauchlumen (102) ein Schlauchlumen mit kleinerem Durchmesser ist und das Ausatemungsschlauchlumen (104) ein Schlauchlumen mit einem größeren Durchmesser ist.
- 30 13. Atemunterstützungssystem nach Anspruch 1, weiter umfassend einen Gasmischer (250), verbunden mit dem Einatemungsschlauchlumen (102).
14. Atemunterstützungssystem nach Anspruch 13, weiter umfassend eine Sauerstoffquelle (356), verbunden mit dem Gasmischer (350).
- 35 15. Atemunterstützungssystem nach Anspruch 13, weiter umfassend:
ein Hygrometer (352), verbunden mit dem Ausatemungsschlauchlumen (104); und
einen Befeuchter (354), gesteuert von dem Hygrometer (352) und verbunden mit dem Gasmischer (350).
- 40 16. Atemunterstützungssystem nach Anspruch 1, weiter umfassend einen Verstärkungsanpasser (260), zwischengeschaltet zwischen einer Quelle des physiologischen Atemsignals (250) und der Drucksteuerung (200) zum Anpassen eines Niveaus an Atemunterstützung für den Patienten.

45 Revendications

1. Système d'assistance ventilatoire, comprenant :

- 50 un tube (103) pour raccordement à des voies respiratoires (112) d'un patient ;
une lumière de tube inspiratoire (102) raccordée au tube (103) ;
une lumière de tube expiratoire (104) raccordée au tube (103) ;
une source d'air inspiratoire (100) raccordée à la lumière de tube inspiratoire (102) et adaptée pour générer un flux d'air cible à travers la lumière de tube inspiratoire (102) ; et
un régulateur de pression (200) adapté pour réguler une pression dans la lumière de tube expiratoire (104),
55 **caractérisé en ce que :**

le régulateur de pression (200) est réactif à un signal de respiration physiologique (250) représentatif d'un effort inspiratoire du patient pour permettre à un flux d'air expiratoire de passer sans restriction à travers

la lumière de tube expiratoire (104) pendant une phase d'expiration du patient et pour restreindre partiellement le flux d'air expiratoire à travers la lumière de tube expiratoire (104) en vue de maintenir un minimum du flux d'air expiratoire à travers la lumière de tube expiratoire (104) pendant une phase d'inspiration du patient ;

dans lequel, pendant les phases à la fois d'inspiration et d'expiration du patient, un flux d'air unidirectionnel est produit et maintenu par la source d'air inspiratoire (100) à travers la lumière de tube inspiratoire (102) et la lumière de tube expiratoire (104) pour empêcher l'air expiré par le patient d'être à nouveau respiré.

2. Système d'assistance ventilatoire selon la revendication 1, dans lequel le régulateur de pression (200) comprend une vanne (202) régulée et synchronisée à l'aide du signal de respiration physiologique (250).

3. Système d'assistance ventilatoire selon la revendication 2, dans lequel la vanne (202) est destinée à restreindre partiellement le flux d'air expiratoire à travers la lumière de tube expiratoire (104).

4. Système d'assistance ventilatoire selon la revendication 1, dans lequel le signal de respiration physiologique (250) est une mesure d'activation électrique d'un diaphragme (EAdi) du patient.

5. Système d'assistance ventilatoire selon la revendication 1, comprenant en outre :

un capteur de pression (201) destiné à capter une pression dans la lumière de tube expiratoire (104) ; et un système de rétroaction (300) interposé entre le capteur de pression (201) et la source d'air inspiratoire (100).

6. Système d'assistance ventilatoire selon la revendication 5, dans lequel le système de rétroaction (300) comprend un comparateur (301) de la pression captée par le capteur de pression dans la lumière de tube expiratoire (104) à une pression cible.

7. Système d'assistance ventilatoire selon la revendication 6, comprenant en outre un ajusteur de pression cible (270) destiné à régler la pression cible.

8. Système d'assistance ventilatoire selon la revendication 6, dans lequel la source d'air inspiratoire (100) est destinée à augmenter le flux d'air cible à travers la lumière de tube inspiratoire (102) d'après une détection de basse pression de la part du comparateur (301).

9. Système d'assistance ventilatoire selon la revendication 5, dans lequel le système de rétroaction (300) comprend un détecteur de flux minimal (302) destiné à maintenir au moins le minimum du flux d'air expiratoire à travers la lumière de tube expiratoire (104).

10. Système d'assistance ventilatoire selon la revendication 9, dans lequel la source d'air inspiratoire (100) est destinée à maintenir au moins le minimum du flux d'air expiratoire à travers la lumière de tube expiratoire (104) d'après un signal de la part du détecteur de flux minimal (302).

11. Système d'assistance ventilatoire selon la revendication 1, dans lequel le tube (103) est un tube endotrachéal.

12. Système d'assistance ventilatoire selon la revendication 1, dans lequel la lumière de tube inspiratoire (102) est une lumière de tube de plus petit diamètre et la lumière de tube expiratoire (104) est une lumière de tube de plus grand diamètre.

13. Système d'assistance ventilatoire selon la revendication 1, comprenant en outre un mélangeur de gaz (350) raccordé à la lumière de tube inspiratoire (102).

14. Système d'assistance ventilatoire selon la revendication 13, comprenant en outre une source d'oxygène (356) raccordée au mélangeur de gaz (350).

15. Système d'assistance ventilatoire selon la revendication 13, comprenant en outre :

un hygromètre (352) raccordé à la lumière de tube expiratoire (104) ; et un humidificateur (354) régulé par l'hygromètre (352) et raccordé au mélangeur de gaz (350).

- 16.** Système d'assistance ventilatoire selon la revendication 1, comprenant en outre un ajusteur de gain (260) interposé entre une source du signal de respiration physiologique (250) et le régulateur de pression (200) en vue d'ajuster un niveau d'assistance ventilatoire prodiguée au patient.

5

10

15

20

25

30

35

40

45

50

55




Figure 1




Figure 2




Figure 3




Figure 4b

Figure 4a




Figure 5




Figure 6

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US 5291882 A [0004]
- US 2004221854 A1 [0005]
- US 5820560 A [0005] [0024]
- US 5429123 A [0005]
- US 5671752 A [0024]
- US 6588423 B [0024]
- US 6901286 B [0024]

专利名称(译)	用于患者同步通气辅助与气管内通流的方法和系统		
公开(公告)号	EP2588177A4	公开(公告)日	2016-11-30
申请号	EP2011800020	申请日	2011-06-29
[标]申请(专利权)人(译)	圣米歇尔医院		
申请(专利权)人(译)	ST.米高医院		
当前申请(专利权)人(译)	ST.米高医院		
[标]发明人	SINDERBY CHRISTER BECK JENNIFER		
发明人	SINDERBY, CHRISTER BECK, JENNIFER		
IPC分类号	A61M16/00 A61M16/04 A61B5/00 A61B5/0488 A61B5/087 A61M16/12 A61M16/16 A61M16/20		
CPC分类号	A61B5/0488 A61B5/087 A61B5/4836 A61M16/0012 A61M16/024 A61M16/04 A61M16/042 A61M16/0486 A61M16/12 A61M16/125 A61M16/16 A61M16/161 A61M16/202 A61M16/205 A61M2016/0021 A61M2016/0027 A61M2202/0208 A61M2210/1014 A61M2230/08 A61M2230/60 A61M16/0003		
代理机构(译)	MAUPILIER , DIDIER		
优先权	61/359951 2010-06-30 US		
其他公开文献	EP2588177B1 EP2588177A1		
外部链接	Espacenet		

摘要(译)

公开了一种通气辅助系统和方法。该系统包括用于连接到患者气道的管，连接到管的吸气和呼气管腔，连接到吸气管内腔的吸气空气源，以及呼气管腔中的空气压力的控制器。压力控制器响应于代表患者吸气努力的生理呼吸信号，以允许空气在患者呼气阶段期间流过呼气管腔，在患者呼吸期间部分地将通过呼气管腔的空气流限制为这样最小的气流相。在两个呼吸阶段期间，产生通过吸气和呼气管腔的单向空气流，以防止患者呼出的空气再次呼吸。生理呼吸信号允许通气辅助与患者的呼吸努力同步。