



US008790257B2

(12) **United States Patent**
Libbus et al.

(10) **Patent No.:** **US 8,790,257 B2**
(45) **Date of Patent:** **Jul. 29, 2014**

(54) **MULTI-SENSOR PATIENT MONITOR TO
DETECT IMPENDING CARDIAC
DECOMPENSATION**

(56) **References Cited**

U.S. PATENT DOCUMENTS

(75) Inventors: **Imad Libbus**, Saint Paul, MN (US);
Mark J. Bly, Falcon Heights, MN (US);
Kristofer J. James, Eagan, MN (US);
Scott T. Mazar, Woodbury, MN (US);
Jerry S. Wang, Blaine, MN (US)

834,261 A	10/1906	Chambers
2,087,124 A	7/1937	Smith et al.
2,184,511 A	12/1939	Bagno et al.
3,170,459 A	2/1965	Phipps et al.
3,232,291 A	2/1966	Parker
3,370,459 A	2/1968	Cescati
3,517,999 A	6/1970	Weaver
3,620,216 A	11/1971	Szymanski
3,677,260 A	7/1972	Funfstuck et al.
3,805,769 A	4/1974	Sessions

(Continued)

(73) Assignee: **Corventis, Inc.**, San Jose, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 464 days.

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **12/209,279**

AU	2003-220574 A8	10/2003
EP	1487535	12/2004

(22) Filed: **Sep. 12, 2008**

(Continued)

(65) **Prior Publication Data**

US 2009/0076344 A1 Mar. 19, 2009

OTHER PUBLICATIONS

International Search Report and Written Opinion of PCT Application No. PCT/US08/76243, dated Nov. 12, 2008, 12 pages total.

(Continued)

Related U.S. Application Data

(60) Provisional application No. 60/972,512, filed on Sep. 14, 2007, provisional application No. 60/972,537, filed on Sep. 14, 2007, provisional application No. 61/055,666, filed on May 23, 2008.

Primary Examiner — Gary Jackson

Assistant Examiner — Davin K Sands

(74) *Attorney, Agent, or Firm* — Kilpatrick Townsend & Stockton LLP

(51) **Int. Cl.**

A61B 5/00 (2006.01)

A61B 5/053 (2006.01)

(52) **U.S. Cl.**

CPC **A61B 5/0537** (2013.01); **A61B 5/0535** (2013.01); **A61B 5/4875** (2013.01)

USPC **600/301**; **600/547**

(58) **Field of Classification Search**

None


See application file for complete search history.

(57)

ABSTRACT

Systems and methods of detecting an impending cardiac decompensation of a patient measure at least two of an electrocardiogram signal of the patient, a hydration signal of the patient, a respiration signal of the patient or an activity signal of the patient. The at least two of the electrocardiogram signal, the hydration signal, the respiration signal or the activity signal are combined with an algorithm to detect the impending cardiac decompensation.

31 Claims, 10 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

3,845,757 A	11/1974	Weyer	5,362,069 A	11/1994	Hall-Tipping
3,874,368 A	4/1975	Asrican	5,375,604 A	12/1994	Kelly et al.
3,882,853 A	5/1975	Gofman et al.	5,411,530 A	5/1995	Akhtar
3,942,517 A	3/1976	Bowles et al.	5,437,285 A	8/1995	Verrier et al.
3,972,329 A	8/1976	Kaufman	5,443,073 A	8/1995	Wang et al.
4,008,712 A	2/1977	Nyboer	5,449,000 A	9/1995	Libke et al.
4,024,312 A	5/1977	Korpman	5,450,845 A	9/1995	Axelgaard
4,077,406 A	3/1978	Sandhage et al.	5,454,377 A	10/1995	Dzwonczyk et al.
4,121,573 A	10/1978	Crovella et al.	5,464,012 A	11/1995	Falcone
4,141,366 A	2/1979	Cross, Jr. et al.	5,469,859 A	11/1995	Tsoglin et al.
RE30,101 E	9/1979	Kubicek et al.	5,482,036 A	1/1996	Diab et al.
4,185,621 A	1/1980	Morrow	5,496,361 A	3/1996	Moberg et al.
4,216,462 A	8/1980	McGrath et al.	5,503,157 A	4/1996	Sramek
4,300,575 A	11/1981	Wilson	5,511,548 A	4/1996	Riazzi et al.
4,308,872 A	1/1982	Watson et al.	5,511,553 A	4/1996	Segalowitz
4,358,678 A	11/1982	Lawrence	5,518,001 A	5/1996	Snell
4,409,983 A	10/1983	Albert	5,523,742 A	6/1996	Simkins et al.
4,450,527 A	5/1984	Sramek	5,529,072 A	6/1996	Sramek
4,451,254 A	5/1984	Dinius et al.	5,544,661 A	8/1996	Davis et al.
4,478,223 A	10/1984	Allor	5,558,638 A	9/1996	Evers et al.
4,498,479 A	2/1985	Martio et al.	5,560,368 A	10/1996	Berger
4,522,211 A	6/1985	Bare et al.	5,564,429 A	10/1996	Bornn et al.
4,661,103 A	4/1987	Harman	5,564,434 A	10/1996	Halperin et al.
4,664,129 A	5/1987	Helzel et al.	5,566,671 A	10/1996	Lyons
4,669,480 A	6/1987	Hoffman	5,575,284 A	11/1996	Athan et al.
4,673,387 A	6/1987	Phillips et al.	5,607,454 A	3/1997	Cameron et al.
4,681,118 A	7/1987	Asai et al.	5,632,272 A	5/1997	Diab et al.
4,692,685 A	9/1987	Blaze	5,634,468 A	6/1997	Platt et al.
4,699,146 A	10/1987	Sieverding	5,642,734 A	7/1997	Ruben et al.
4,721,110 A	1/1988	Lampadius	5,673,704 A	10/1997	Marchlinski et al.
4,730,611 A	3/1988	Lamb	5,678,562 A	10/1997	Sellers
4,733,107 A	3/1988	O'Shaughnessy et al.	5,687,717 A	11/1997	Halpern et al.
4,781,200 A	11/1988	Baker	5,710,376 A	1/1998	Weber
4,793,362 A	12/1988	Tedner	5,718,234 A	2/1998	Warden et al.
4,838,273 A	6/1989	Cartmell	5,724,025 A	3/1998	Tavori
4,838,279 A	6/1989	Fore	5,738,107 A	4/1998	Martinsen et al.
4,850,370 A	7/1989	Dower	5,748,103 A	5/1998	Flach et al.
4,880,004 A	11/1989	Baker, Jr. et al.	5,767,791 A	6/1998	Stoop et al.
4,895,163 A	1/1990	Libke et al.	5,769,793 A	6/1998	Pincus et al.
4,911,175 A	3/1990	Shizgal	5,772,508 A	6/1998	Sugita et al.
4,945,916 A	8/1990	Kretschmer et al.	5,772,586 A	6/1998	Heinonen et al.
4,955,381 A	9/1990	Way et al.	5,778,882 A	7/1998	Raymond et al.
4,966,158 A	10/1990	Honma et al.	5,788,643 A	8/1998	Feldman
4,981,139 A	1/1991	Pfohl	5,788,682 A	8/1998	Maget
4,988,335 A	1/1991	Prindle et al.	5,803,915 A	9/1998	Kremenchugsky et al.
4,989,612 A	2/1991	Fore	5,807,272 A	9/1998	Kun
5,001,632 A	3/1991	Hall-Tipping	5,814,079 A	9/1998	Kieval et al.
5,012,810 A	5/1991	Strand et al.	5,817,035 A	10/1998	Sullivan
5,025,791 A	6/1991	Niwa	5,833,603 A	11/1998	Kovacs et al.
5,027,824 A	7/1991	Dougherty et al.	5,836,990 A	11/1998	Li
5,050,612 A	9/1991	Matsumura	5,855,614 A	1/1999	Stevens et al.
5,063,937 A	11/1991	Ezenwa et al.	5,860,860 A	1/1999	Clayman
5,080,099 A	1/1992	Way et al.	5,862,802 A	1/1999	Bird
5,083,563 A	1/1992	Collins	5,862,803 A	1/1999	Besson et al.
5,086,781 A	2/1992	Bookspan	5,865,733 A	2/1999	Malinouskas et al.
5,113,869 A	5/1992	Nappholz et al.	5,876,353 A	3/1999	Riff
5,125,412 A	6/1992	Thornton	5,904,708 A	5/1999	Goedeke
5,133,355 A	7/1992	Strand et al.	5,935,079 A	8/1999	Swanson et al.
5,140,985 A	8/1992	Schroeder et al.	5,941,831 A	8/1999	Turcott
5,150,708 A	9/1992	Brooks	5,944,659 A	8/1999	Flach et al.
5,168,874 A	12/1992	Segalowitz	5,949,636 A	9/1999	Johnson et al.
5,226,417 A	7/1993	Swedlow et al.	5,957,854 A	9/1999	Besson et al.
5,241,300 A	8/1993	Buschmann	5,957,861 A	9/1999	Combs et al.
5,257,627 A	11/1993	Rapoport	5,964,703 A	10/1999	Goodman et al.
5,271,411 A	12/1993	Ripley et al.	5,970,986 A	10/1999	Bolz et al.
5,273,532 A	12/1993	Niezink et al.	5,984,102 A	11/1999	Tay
5,282,840 A	2/1994	Hudrlik	5,987,352 A	11/1999	Klein et al.
5,291,013 A	3/1994	Nafarrate et al.	6,007,532 A	12/1999	Netherly
5,297,556 A	3/1994	Shankar	6,027,523 A	2/2000	Schmieding
5,301,677 A	4/1994	Hsung	6,045,513 A	4/2000	Stone et al.
5,319,363 A	6/1994	Welch et al.	6,047,203 A	4/2000	Sackner et al.
5,331,966 A	7/1994	Bennett et al.	6,047,259 A	4/2000	Campbell et al.
5,335,664 A	8/1994	Nagashima	6,049,730 A	4/2000	Kristbjarnarson
5,343,869 A	9/1994	Pross et al.	6,050,267 A	4/2000	Nardella et al.
5,353,793 A	10/1994	Bornn	6,050,951 A	4/2000	Friedman et al.
			6,052,615 A	4/2000	Feild et al.
			6,067,467 A	5/2000	John
			6,080,106 A	6/2000	Lloyd et al.
			6,081,735 A	6/2000	Diab et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,095,991 A	8/2000	Krausman et al.	6,577,139 B2	6/2003	Cooper
6,102,856 A	8/2000	Groff et al.	6,577,893 B1	6/2003	Besson et al.
6,104,949 A	8/2000	Pitts Crick et al.	6,577,897 B1	6/2003	Shurubura et al.
6,112,224 A	8/2000	Peifer et al.	6,579,231 B1	6/2003	Phipps
6,117,077 A	9/2000	Del Mar et al.	6,580,942 B1	6/2003	Willshire
6,125,297 A	9/2000	Siconolfi	6,584,343 B1	6/2003	Ransbury et al.
6,129,744 A	10/2000	Boute	6,587,715 B2	7/2003	Singer
6,141,575 A	10/2000	Price	6,589,170 B1	7/2003	Flach et al.
6,144,878 A	11/2000	Schroeppe et al.	6,595,927 B2	7/2003	Pitts-Crick et al.
6,164,284 A	12/2000	Schulman et al.	6,595,929 B2	7/2003	Stivorice et al.
6,181,963 B1	1/2001	Chin et al.	6,600,949 B1	7/2003	Turcott
6,185,452 B1	2/2001	Schulman et al.	6,602,201 B1	8/2003	Malecha et al.
6,190,313 B1	2/2001	Hinkle	6,605,038 B1	8/2003	Teller et al.
6,190,324 B1	2/2001	Kieval et al.	6,611,705 B2	8/2003	Hopman et al.
6,198,394 B1	3/2001	Jacobsen et al.	6,611,783 B2	8/2003	Kelly et al.
6,198,955 B1	3/2001	Axelgaard et al.	6,616,606 B1	9/2003	Petersen et al.
6,208,894 B1	3/2001	Schulman et al.	6,622,042 B1	9/2003	Thacker
6,212,427 B1	4/2001	Hoover	6,636,754 B1	10/2003	Baura et al.
6,213,942 B1	4/2001	Flach et al.	6,641,542 B2	11/2003	Cho et al.
6,225,901 B1	5/2001	Kail, IV	6,645,153 B2	11/2003	Kroll et al.
6,245,021 B1	6/2001	Stampfer	6,649,829 B2	11/2003	Garber et al.
6,259,939 B1	7/2001	Rogel	6,650,917 B2	11/2003	Diab et al.
6,267,730 B1	7/2001	Pacunas	6,658,300 B2	12/2003	Govari et al.
6,272,377 B1	8/2001	Sweeney et al.	6,659,947 B1	12/2003	Carter et al.
6,277,078 B1	8/2001	Porat et al.	6,659,949 B1	12/2003	Lang et al.
6,287,252 B1	9/2001	Lugo	6,687,540 B2	2/2004	Marcovecchio
6,289,238 B1	9/2001	Besson et al.	6,697,658 B2	2/2004	Al-Ali
6,290,646 B1	9/2001	Cosentino et al.	RE38,476 E	3/2004	Diab et al.
6,295,466 B1	9/2001	Ishikawa et al.	6,699,200 B2	3/2004	Cao et al.
6,305,943 B1	10/2001	Pougatchev et al.	6,701,271 B2	3/2004	Willner et al.
6,306,088 B1	10/2001	Krausman et al.	6,714,813 B2	3/2004	Ishigooka et al.
6,308,094 B1	10/2001	Shusterman et al.	RE38,492 E	4/2004	Diab et al.
6,312,378 B1	11/2001	Bardy	6,721,594 B2	4/2004	Conley et al.
6,315,721 B2	11/2001	Schulman et al.	6,728,572 B2	4/2004	Hsu et al.
6,327,487 B1	12/2001	Stratbucker	6,748,269 B2	6/2004	Thompson et al.
6,330,464 B1	12/2001	Colvin et al.	6,749,566 B2	6/2004	Russ
6,336,903 B1	1/2002	Bardy	6,751,498 B1	6/2004	Greenberg et al.
6,339,722 B1	1/2002	Heethaar et al.	6,760,617 B2	7/2004	Ward et al.
6,343,140 B1	1/2002	Brooks	6,773,396 B2	8/2004	Flach et al.
6,347,245 B1	2/2002	Lee et al.	6,775,566 B2	8/2004	Nissila
6,358,208 B1	3/2002	Lang et al.	6,790,178 B1	9/2004	Mault et al.
6,385,473 B1	5/2002	Haines et al.	6,795,722 B2	9/2004	Sheraton et al.
6,398,727 B1	6/2002	Bui et al.	6,814,706 B2	11/2004	Barton et al.
6,400,982 B2	6/2002	Sweeney et al.	6,816,744 B2	11/2004	Garfield et al.
6,409,674 B1	6/2002	Brockway et al.	6,821,249 B2	11/2004	Casscells, III et al.
6,411,853 B1	6/2002	Millot et al.	6,824,515 B2	11/2004	Suorsa et al.
6,416,471 B1	7/2002	Kumar et al.	6,827,690 B2	12/2004	Bardy
6,440,069 B1	8/2002	Raymond et al.	6,829,503 B2	12/2004	Alt
6,442,422 B1	8/2002	Duckert	6,858,006 B2	2/2005	MacCarter et al.
6,450,820 B1	9/2002	Palsson et al.	6,871,211 B2	3/2005	Labounty et al.
6,450,953 B1	9/2002	Place et al.	6,878,121 B2	4/2005	Krausman et al.
6,453,186 B1	9/2002	Lovejoy et al.	6,879,850 B2	4/2005	Kimball
6,454,707 B1	9/2002	Casscells, III et al.	6,881,191 B2	4/2005	Oakley et al.
6,454,708 B1	9/2002	Ferguson et al.	6,887,201 B2	5/2005	Bardy
6,463,328 B1	10/2002	John	6,890,096 B2	5/2005	Tokita et al.
6,473,640 B1	10/2002	Erlebacher	6,893,396 B2	5/2005	Schulze et al.
6,480,733 B1	11/2002	Turcott	6,894,204 B2	5/2005	Dunshee
6,480,734 B1	11/2002	Zhang et al.	6,906,530 B2	6/2005	Geisel
6,485,461 B1	11/2002	Mason et al.	6,912,414 B2	6/2005	Tong
6,490,478 B1	12/2002	Zhang et al.	6,936,006 B2	8/2005	Sabra
6,491,647 B1	12/2002	Bridger et al.	6,940,403 B2	9/2005	Kail, IV
6,494,829 B1	12/2002	New, Jr. et al.	6,942,622 B1	9/2005	Turcott
6,496,715 B1	12/2002	Lee et al.	6,952,695 B1	10/2005	Trinks et al.
6,512,949 B1	1/2003	Combs et al.	6,970,742 B2	11/2005	Mann et al.
6,520,967 B1	2/2003	Cauthen	6,972,683 B2	12/2005	Lestienne et al.
6,527,711 B1	3/2003	Stivorice et al.	6,978,177 B1	12/2005	Chen et al.
6,527,729 B1	3/2003	Turcott	6,980,851 B2	12/2005	Zhu et al.
6,528,960 B1	3/2003	Roden et al.	6,980,852 B2	12/2005	Jersey-Willuhn et al.
6,544,173 B2	4/2003	West et al.	6,985,078 B2	1/2006	Suzuki et al.
6,544,174 B2	4/2003	West et al.	6,987,965 B2	1/2006	Ng et al.
6,551,251 B2	4/2003	Zuckerwar et al.	6,988,989 B2	1/2006	Weiner et al.
6,551,252 B2	4/2003	Sackner et al.	6,993,378 B2	1/2006	Wiederhold et al.
6,569,160 B1	5/2003	Goldin et al.	6,997,879 B1	2/2006	Turcott
6,572,557 B2	6/2003	Tchou et al.	7,003,346 B2	2/2006	Singer
6,572,636 B1	6/2003	Hagen et al.	7,009,362 B2	3/2006	Tsukamoto et al.
			7,010,340 B2	3/2006	Scarantino et al.
			7,018,338 B2	3/2006	Vetter et al.
			7,020,508 B2	3/2006	Stivorice et al.
			7,027,862 B2	4/2006	Dahl et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

7,041,062	B2	5/2006	Friedrichs et al.	2002/0116009	A1	8/2002	Fraser et al.
7,044,911	B2	5/2006	Drinan et al.	2002/0123672	A1	9/2002	Christophersom et al.
7,047,067	B2	5/2006	Gray et al.	2002/0123674	A1	9/2002	Plicchi et al.
7,050,846	B2	5/2006	Sweeney et al.	2002/0138017	A1	9/2002	Bui et al.
7,054,679	B2	5/2006	Hirsh	2002/0167389	A1	11/2002	Uchikoba et al.
7,059,767	B2	6/2006	Tokita et al.	2002/0182485	A1	12/2002	Anderson et al.
7,088,242	B2	8/2006	Aupperle et al.	2003/0009092	A1	1/2003	Parker
7,113,826	B2	9/2006	Henry et al.	2003/0023184	A1	1/2003	Pitts-Crick et al.
7,118,531	B2	10/2006	Krill	2003/0028221	A1	2/2003	Zhu et al.
7,127,370	B2	10/2006	Kelly, Jr. et al.	2003/0028327	A1	2/2003	Brunner et al.
7,129,836	B2	10/2006	Lawson et al.	2003/0045922	A1	3/2003	Northrop
7,130,396	B2	10/2006	Rogers et al.	2003/0051144	A1	3/2003	Williams
7,130,679	B2	10/2006	Parsonnet et al.	2003/0055460	A1	3/2003	Owen et al.
7,133,716	B2	11/2006	Kraemer et al.	2003/0069510	A1	4/2003	Semler
7,136,697	B2	11/2006	Singer	2003/0083581	A1	5/2003	Taha et al.
7,136,703	B1	11/2006	Cappa et al.	2003/0085717	A1	5/2003	Cooper
7,142,907	B2	11/2006	Xue et al.	2003/0087244	A1	5/2003	McCarthy
7,149,574	B2	12/2006	Yun et al.	2003/0092975	A1	5/2003	Casscells, III et al.
7,149,773	B2	12/2006	Haller et al.	2003/0093125	A1	5/2003	Zhu et al.
7,153,262	B2	12/2006	Stivoric et al.	2003/0093298	A1	5/2003	Hernandez et al.
7,156,807	B2	1/2007	Carter et al.	2003/0100367	A1	5/2003	Cooke
7,156,808	B2	1/2007	Quy	2003/0105411	A1	6/2003	Smallwood et al.
7,160,252	B2	1/2007	Cho et al.	2003/0135127	A1	7/2003	Sackner et al.
7,160,253	B2	1/2007	Nissila	2003/0143544	A1	7/2003	McCarthy
7,166,063	B2	1/2007	Rahman et al.	2003/0149349	A1	8/2003	Jensen
7,167,743	B2	1/2007	Heruth et al.	2003/0181815	A1	9/2003	Ebner et al.
7,184,821	B2	2/2007	Belalcazar et al.	2003/0187370	A1	10/2003	Kodama
7,191,000	B2	3/2007	Zhu et al.	2003/0191503	A1	10/2003	Zhu et al.
7,194,306	B1	3/2007	Turcott	2003/0212319	A1	11/2003	Magill
7,206,630	B1	4/2007	Tarler	2003/0221687	A1	12/2003	Kaigler
7,212,849	B2	5/2007	Zhang et a	2003/0233129	A1	12/2003	Matos
7,215,984	B2	5/2007	Diab et al.	2004/0006279	A1	1/2004	Arad (Abboud)
7,215,991	B2	5/2007	Besson et al.	2004/0010303	A1	1/2004	Bolea et al.
7,238,159	B2	7/2007	Banet et al.	2004/0014422	A1	1/2004	Kallio
7,248,916	B2	7/2007	Bardy	2004/0015058	A1	1/2004	Besson et al.
7,251,524	B1	7/2007	Hepp et al.	2004/0019292	A1	1/2004	Drinan et al.
7,257,438	B2	8/2007	Kinast	2004/0044293	A1	3/2004	Burton
7,261,690	B2	8/2007	Teller et al.	2004/0049132	A1	3/2004	Barron et al.
7,277,741	B2	10/2007	Debreczeny et al.	2004/0064133	A1	4/2004	Miller et al.
7,284,904	B2	10/2007	Tokita et al.	2004/0073094	A1	4/2004	Baker
7,285,090	B2	10/2007	Stivoric et al.	2004/0073126	A1	4/2004	Rowlandson
7,294,105	B1	11/2007	Islam	2004/0077954	A1	4/2004	Oakley et al.
7,295,879	B2	11/2007	Denker et al.	2004/0100376	A1	5/2004	Lye et al.
7,297,119	B2	11/2007	Westbrook et al.	2004/0102683	A1	5/2004	Khanuja et al.
7,318,808	B2	1/2008	Tarassenko et al.	2004/0106951	A1	6/2004	Edman et al.
7,319,386	B2	1/2008	Collins, Jr. et al.	2004/0122489	A1	6/2004	Mazar et al.
7,336,187	B2	2/2008	Hubbard, Jr. et al.	2004/0127790	A1	7/2004	Lang et al.
7,346,380	B2	3/2008	Axelgaard et al.	2004/0133079	A1	7/2004	Mazar et al.
7,382,247	B2	6/2008	Welch et al.	2004/0133081	A1	7/2004	Teller et al.
7,384,398	B2	6/2008	Gagnadre et al.	2004/0134496	A1	7/2004	Cho et al.
7,390,299	B2	6/2008	Weiner et al.	2004/0143170	A1	7/2004	DuRousseau
7,395,106	B2	7/2008	Ryu et al.	2004/0147969	A1	7/2004	Mann et al.
7,423,526	B2	9/2008	Despotis	2004/0152956	A1	8/2004	Korman
7,423,537	B2	9/2008	Bonnet et al.	2004/0158132	A1	8/2004	Zaleski
7,443,302	B2	10/2008	Reeder et al.	2004/0167389	A1	8/2004	Brabrand
7,450,024	B2	11/2008	Wildman et al.	2004/0172080	A1	9/2004	Stadler et al.
7,468,032	B2	12/2008	Stahmann et al.	2004/0199056	A1	10/2004	Husemann et al.
7,510,699	B2	3/2009	Black et al.	2004/0215240	A1	10/2004	Lovett et al.
7,660,632	B2	2/2010	Kirby et al.	2004/0215247	A1	10/2004	Bolz
7,701,227	B2	4/2010	Saulnier et al.	2004/0220639	A1	11/2004	Mulligan et al.
7,813,778	B2	10/2010	Benaron et al.	2004/0225199	A1	11/2004	Evanyk et al.
7,881,763	B2	2/2011	Brauker et al.	2004/0225203	A1	11/2004	Jemison et al.
7,942,824	B1	5/2011	Kayyali et al.	2004/0243018	A1	12/2004	Organ et al.
8,248,686	B2	8/2012	Kwon et al.	2004/0267142	A1	12/2004	Paul
8,285,356	B2	10/2012	Bly et al.	2005/0004506	A1	1/2005	Gyory
2001/0047127	A1	11/2001	New, Jr. et al.	2005/0015094	A1	1/2005	Keller
2002/0004640	A1	1/2002	Conn et al.	2005/0015095	A1	1/2005	Keller
2002/0019586	A1	2/2002	Teller et al.	2005/0020935	A1	1/2005	Helzel et al.
2002/0019588	A1	2/2002	Marro et al.	2005/0027175	A1	2/2005	Yang
2002/0022786	A1 *	2/2002	Takehara et al. 600/547	2005/0027204	A1	2/2005	Kligfield et al.
2002/0028989	A1	3/2002	Pelletier et al.	2005/0027207	A1	2/2005	Westbrook et al.
2002/0032581	A1	3/2002	Reitberg	2005/0027918	A1	2/2005	Govindarajulu et al.
2002/0045836	A1	4/2002	Alkawwas	2005/0043675	A1	2/2005	Pastore et al.
2002/0088465	A1	7/2002	Hill	2005/0054944	A1	3/2005	Nakada et al.
2002/0099277	A1	7/2002	Harry et al.	2005/0059867	A1	3/2005	Chung
				2005/0065445	A1	3/2005	Arzbaeher et al.
				2005/0065571	A1	3/2005	Imran
				2005/0070768	A1	3/2005	Zhu et al.
				2005/0070778	A1	3/2005	Lackey et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2005/0080346 A1	4/2005	Gianchandani et al.	2006/0135858 A1	6/2006	Nidd et al.
2005/0080460 A1	4/2005	Wang et al.	2006/0142654 A1	6/2006	Rytky
2005/0080463 A1	4/2005	Stahmann et al.	2006/0142820 A1	6/2006	Von Arx et al.
2005/0085734 A1	4/2005	Tehrani	2006/0149168 A1	7/2006	Czarnek
2005/0091338 A1	4/2005	de la Hueraga	2006/0155174 A1	7/2006	Glukhovskiy et al.
2005/0096513 A1	5/2005	Ozguz et al.	2006/0155183 A1	7/2006	Kroecker et al.
2005/0113703 A1	5/2005	Farrington et al.	2006/0155200 A1	7/2006	Ng
2005/0124878 A1	6/2005	Sharony	2006/0157893 A1	7/2006	Patel
2005/0124901 A1	6/2005	Misczynski et al.	2006/0161073 A1	7/2006	Singer
2005/0124908 A1	6/2005	Belalcazar et al.	2006/0161205 A1	7/2006	Mitrani et al.
2005/0131288 A1	6/2005	Turner et al.	2006/0161459 A9	7/2006	Rosenfeld et al.
2005/0137464 A1	6/2005	Bomba	2006/0167374 A1	7/2006	Takehara et al.
2005/0137626 A1	6/2005	Pastore et al.	2006/0173257 A1	8/2006	Nagai et al.
2005/0148895 A1	7/2005	Misczynski et al.	2006/0173269 A1	8/2006	Glossop
2005/0158539 A1	7/2005	Murphy et al.	2006/0195020 A1	8/2006	Martin et al.
2005/0177038 A1	8/2005	Kolpin et al.	2006/0195039 A1	8/2006	Drew et al.
2005/0187482 A1	8/2005	O'Brien et al.	2006/0195097 A1	8/2006	Evans et al.
2005/0187796 A1	8/2005	Rosenfeld et al.	2006/0195144 A1	8/2006	Giftakis et al.
2005/0192488 A1	9/2005	Brynton et al.	2006/0202816 A1	9/2006	Crump et al.
2005/0197654 A1	9/2005	Edman et al.	2006/0212097 A1	9/2006	Varadan et al.
2005/0203433 A1	9/2005	Singer	2006/0224051 A1	10/2006	Teller et al.
2005/0203435 A1	9/2005	Nakada	2006/0224072 A1	10/2006	Shennib
2005/0203436 A1	9/2005	Davies	2006/0224079 A1	10/2006	Washchuk
2005/0203637 A1	9/2005	Edman et al.	2006/0235281 A1	10/2006	Tuccillo
2005/0206518 A1	9/2005	Welch et al.	2006/0235316 A1	10/2006	Ungless et al.
2005/0215914 A1	9/2005	Bornzin et al.	2006/0235489 A1	10/2006	Drew et al.
2005/0215918 A1	9/2005	Frantz et al.	2006/0241641 A1	10/2006	Albans et al.
2005/0228234 A1	10/2005	Yang	2006/0241701 A1	10/2006	Markowitz et al.
2005/0228238 A1	10/2005	Monitzer	2006/0241722 A1	10/2006	Thacker et al.
2005/0228244 A1	10/2005	Banet	2006/0247545 A1	11/2006	St. Martin
2005/0239493 A1	10/2005	Batkin et al.	2006/0252999 A1	11/2006	Devaal et al.
2005/0240087 A1	10/2005	Keenan et al.	2006/0253005 A1	11/2006	Drinan et al.
2005/0251044 A1	11/2005	Hocor et al.	2006/0253044 A1	11/2006	Zhang et al.
2005/0256418 A1	11/2005	Mietus et al.	2006/0258952 A1	11/2006	Stahmann et al.
2005/0261598 A1	11/2005	Banet et al.	2006/0264730 A1	11/2006	Stivoric et al.
2005/0261743 A1 *	11/2005	Kroll 607/8	2006/0264767 A1	11/2006	Shennib
2005/0267376 A1	12/2005	Marossero et al.	2006/0264776 A1	11/2006	Stahmann et al.
2005/0267377 A1	12/2005	Marossero et al.	2006/0271116 A1	11/2006	Stahmann et al.
2005/0267381 A1	12/2005	Benditt et al.	2006/0276714 A1	12/2006	Holt et al.
2005/0273023 A1	12/2005	Bystrom et al.	2006/0281981 A1	12/2006	Jang et al.
2005/0277841 A1	12/2005	Shennib	2006/0281996 A1	12/2006	Kuo et al.
2005/0277842 A1	12/2005	Silva	2006/0293571 A1	12/2006	Bao et al.
2005/0277992 A1	12/2005	Koh et al.	2006/0293609 A1	12/2006	Stahmann et al.
2005/0280531 A1	12/2005	Fadem et al.	2007/0010721 A1	1/2007	Chen et al.
2005/0283197 A1	12/2005	Daum et al.	2007/0010750 A1	1/2007	Ueno et al.
2005/0288601 A1	12/2005	Wood et al.	2007/0015973 A1	1/2007	Nanikashvili
2006/0004300 A1	1/2006	Kennedy	2007/0015976 A1	1/2007	Miesel et al.
2006/0004377 A1	1/2006	Keller	2007/0016089 A1	1/2007	Fischell et al.
2006/0009697 A1	1/2006	Banet et al.	2007/0021678 A1	1/2007	Beck et al.
2006/0009701 A1	1/2006	Nissila et al.	2007/0021790 A1	1/2007	Kieval et al.
2006/0010090 A1	1/2006	Brockway et al.	2007/0021792 A1	1/2007	Kieval et al.
2006/0020218 A1	1/2006	Freeman et al.	2007/0021794 A1	1/2007	Kieval et al.
2006/0025661 A1	2/2006	Sweeney et al.	2007/0021796 A1	1/2007	Kieval et al.
2006/0030781 A1	2/2006	Shennib	2007/0021797 A1	1/2007	Kieval et al.
2006/0030782 A1	2/2006	Shennib	2007/0021798 A1	1/2007	Kieval et al.
2006/0031102 A1	2/2006	Teller et al.	2007/0021799 A1	1/2007	Kieval et al.
2006/0041280 A1	2/2006	Stahmann et al.	2007/0027388 A1	2/2007	Chou
2006/0047215 A1	3/2006	Newman et al.	2007/0027497 A1	2/2007	Parnis
2006/0052678 A1	3/2006	Drinan et al.	2007/0032749 A1	2/2007	Overall et al.
2006/0058543 A1	3/2006	Walter et al.	2007/0038038 A1	2/2007	Stivoric et al.
2006/0058593 A1	3/2006	Drinan et al.	2007/0038078 A1	2/2007	Osadchy
2006/0064030 A1 *	3/2006	Cosentino et al. 600/547	2007/0038255 A1	2/2007	Kieval et al.
2006/0064040 A1	3/2006	Berger et al.	2007/0038262 A1	2/2007	Kieval et al.
2006/0064142 A1	3/2006	Chavan et al.	2007/0043301 A1	2/2007	Martinsen et al.
2006/0066449 A1	3/2006	Johnson	2007/0043303 A1	2/2007	Osyypka et al.
2006/0074283 A1	4/2006	Henderson et al.	2007/0043394 A1 *	2/2007	Zhang et al. 607/8
2006/0074462 A1	4/2006	Verhoef	2007/0048224 A1	3/2007	Howell et al.
2006/0075257 A1	4/2006	Martis et al.	2007/0060800 A1	3/2007	Drinan et al.
2006/0084881 A1	4/2006	Korzinov et al.	2007/0060802 A1	3/2007	Ghevondian et al.
2006/0085049 A1	4/2006	Cory et al.	2007/0073132 A1	3/2007	Vosch
2006/0089679 A1	4/2006	Zhu et al.	2007/0073168 A1	3/2007	Zhang et al.
2006/0094948 A1	5/2006	Gough et al.	2007/0073169 A1 *	3/2007	Averina et al. 600/483
2006/0102476 A1	5/2006	Niwa et al.	2007/0073181 A1	3/2007	Pu et al.
2006/0116592 A1	6/2006	Zhou et al.	2007/0073361 A1	3/2007	Goren et al.
2006/0122474 A1	6/2006	Teller et al.	2007/0082189 A1	4/2007	Gillette
			2007/0083092 A1	4/2007	Rippo et al.
			2007/0092862 A1	4/2007	Gerber
			2007/0104840 A1	5/2007	Singer
			2007/0106132 A1	5/2007	Elhag et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2007/0106137	A1	5/2007	Baker, Jr. et al.	
2007/0106167	A1	5/2007	Kinast	
2007/0118039	A1	5/2007	Bodecker et al.	
2007/0123756	A1	5/2007	Kitajima et al.	
2007/0123903	A1	5/2007	Raymond et al.	
2007/0123904	A1	5/2007	Stad et al.	
2007/0129622	A1	6/2007	Bourget et al.	
2007/0129643	A1	6/2007	Kwok et al.	
2007/0129769	A1	6/2007	Bourget et al.	
2007/0142715	A1	6/2007	Banet et al.	
2007/0142732	A1	6/2007	Brockway et al.	
2007/0149282	A1	6/2007	Lu et al.	
2007/0150008	A1	6/2007	Jones et al.	
2007/0150009	A1	6/2007	Kveen et al.	
2007/0150029	A1	6/2007	Bourget et al.	
2007/0162089	A1	7/2007	Mosesov	
2007/0167753	A1	7/2007	Van Wyk et al.	
2007/0167848	A1	7/2007	Kuo et al.	
2007/0167849	A1	7/2007	Zhang et al.	
2007/0167850	A1	7/2007	Russell et al.	
2007/0172424	A1	7/2007	Roser	
2007/0173705	A1	7/2007	Teller et al.	
2007/0180047	A1	8/2007	Dong et al.	
2007/0180140	A1	8/2007	Welch et al.	
2007/0191723	A1	8/2007	Prystowsky et al.	
2007/0207858	A1	9/2007	Breving	
2007/0208233	A1	9/2007	Kovacs	
2007/0208235	A1	9/2007	Besson et al.	
2007/0208262	A1	9/2007	Kovacs	
2007/0232867	A1	10/2007	Hansmann	
2007/0244403	A1	10/2007	Natarajan et al.	
2007/0249946	A1	10/2007	Kumar et al.	
2007/0250121	A1	10/2007	Miesel et al.	
2007/0255120	A1	11/2007	Rosnov	
2007/0255153	A1	11/2007	Kumar et al.	
2007/0255184	A1	11/2007	Shennib	
2007/0255531	A1	11/2007	Drew	
2007/0260133	A1	11/2007	Meyer	
2007/0260155	A1	11/2007	Rapoport et al.	
2007/0260289	A1	11/2007	Giftakis et al.	
2007/0270678	A1	11/2007	Fadem et al.	
2007/0273504	A1	11/2007	Tran	
2007/0276273	A1	11/2007	Watson, Jr	
2007/0282173	A1	12/2007	Wang et al.	
2007/0293738	A1 *	12/2007	Bardy	600/300
2007/0299325	A1	12/2007	Farrell et al.	
2008/0004499	A1	1/2008	Davis	
2008/0004547	A1	1/2008	Dinsmoor et al.	
2008/0004904	A1 *	1/2008	Tran	705/2
2008/0021336	A1	1/2008	Dobak	
2008/0024293	A1	1/2008	Stylos	
2008/0024294	A1	1/2008	Mazar	
2008/0033260	A1	2/2008	Sheppard et al.	
2008/0039700	A1 *	2/2008	Drinan et al.	600/301
2008/0058614	A1	3/2008	Banet et al.	
2008/0058656	A1	3/2008	Costello et al.	
2008/0059239	A1	3/2008	Gerst et al.	
2008/0091089	A1	4/2008	Guillory et al.	
2008/0103399	A1 *	5/2008	Patangay et al.	600/508
2008/0114220	A1	5/2008	Banet et al.	
2008/0120784	A1	5/2008	Warner et al.	
2008/0139934	A1	6/2008	McMorrow et al.	
2008/0146892	A1	6/2008	LeBoeuf et al.	
2008/0167538	A1	7/2008	Teller et al.	
2008/0171918	A1	7/2008	Teller et al.	
2008/0171922	A1	7/2008	Teller et al.	
2008/0171929	A1	7/2008	Katims	
2008/0183052	A1	7/2008	Teller et al.	
2008/0200774	A1	8/2008	Luo	
2008/0214903	A1	9/2008	Orbach	
2008/0220865	A1	9/2008	Hsu	
2008/0221399	A1	9/2008	Zhou et al.	
2008/0221402	A1	9/2008	Despotis	
2008/0224852	A1	9/2008	Dicks et al.	
2008/0228084	A1	9/2008	Bedard et al.	

2008/0275465	A1	11/2008	Paul et al.
2008/0287751	A1	11/2008	Stivoric et al.
2008/0287752	A1	11/2008	Stroetz et al.
2008/0293491	A1	11/2008	Wu et al.
2008/0294019	A1	11/2008	Tran
2008/0294020	A1	11/2008	Sapounas
2008/0318681	A1	12/2008	Rofougaran et al.
2008/0319279	A1	12/2008	Ramsay et al.
2008/0319282	A1	12/2008	Tran
2008/0319290	A1	12/2008	Mao et al.
2009/0005016	A1	1/2009	Eng et al.
2009/0018410	A1	1/2009	Coene et al.
2009/0018456	A1	1/2009	Hung
2009/0048526	A1	2/2009	Aarts
2009/0054737	A1	2/2009	Magar et al.
2009/0062670	A1	3/2009	Sterling et al.
2009/0073991	A1	3/2009	Landrum et al.
2009/0076336	A1	3/2009	Mazar et al.
2009/0076340	A1	3/2009	Libbus et al.
2009/0076341	A1	3/2009	James et al.
2009/0076342	A1	3/2009	Amurthur et al.
2009/0076343	A1	3/2009	James et al.
2009/0076345	A1	3/2009	Manicka et al.
2009/0076346	A1	3/2009	James et al.
2009/0076348	A1	3/2009	Manicka et al.
2009/0076349	A1	3/2009	Libbus et al.
2009/0076350	A1	3/2009	Bly et al.
2009/0076363	A1	3/2009	Bly et al.
2009/0076364	A1	3/2009	Libbus et al.
2009/0076397	A1	3/2009	Libbus et al.
2009/0076401	A1	3/2009	Mazar et al.
2009/0076405	A1	3/2009	Amurthur et al.
2009/0076410	A1	3/2009	Libbus et al.
2009/0076559	A1	3/2009	Libbus et al.
2009/0177145	A1	7/2009	Ohlander et al.
2009/0182204	A1	7/2009	Semler et al.
2009/0234410	A1	9/2009	Libbus et al.
2009/0264792	A1	10/2009	Mazar
2009/0292194	A1	11/2009	Libbus et al.
2010/0056881	A1	3/2010	Libbus et al.
2010/0191310	A1	7/2010	Bly
2011/0144470	A1	6/2011	Mazar et al.
2011/0245711	A1	10/2011	Katra et al.
2011/0270049	A1	11/2011	Katra et al.

FOREIGN PATENT DOCUMENTS

EP	1579801	A1	9/2005
JP	2005-521448		7/2005
WO	WO 00/79255		12/2000
WO	WO 01/89362	A2	11/2001
WO	WO 02/092101		11/2002
WO	WO 03/082080		10/2003
WO	WO 2005/051164		6/2005
WO	WO 2005/104930		11/2005
WO	WO 2006/008745		1/2006
WO	WO 2006/102476		9/2006
WO	WO 2006/111878	A1	11/2006
WO	WO 2007/041783		4/2007
WO	WO 2007/106455	A2	9/2007
WO	2009/116906	A1	9/2009

OTHER PUBLICATIONS

AD5934: 250 kSPS 12-Bit Impedance Converter Network Analyzer, Analog Devices, retrieved from the Internet: <<http://www.analog.com/static/imported-files/data_sheets/AD5934.pdf>>, 40 pages.

Something in the way he moves, The Economist, 2007, retrieved from the Internet: <<http://www.economist.com/science/printerFriendly.cfm?story_id=9861412>>.

Abraham, "New approaches to monitoring heart failure before symptoms appear," Rev Cardiovasc Med. 2006 ;7 Suppl 1 :33-41.

Adams, Jr. "Guiding heart failure care by invasive hemodynamic measurements: possible or useful?," Journal of Cardiac Failure 2002; 8(2):71-73.

Adamson et al., "Continuous autonomic assessment in patients with symptomatic heart failure: prognostic value of heart rate variability

(56)

References Cited

OTHER PUBLICATIONS

- measured by an implanted cardiac resynchronization device," *Circulation*. 2004;110:2389-2394.
- Adamson et al., "Ongoing right ventricular hemodynamics in heart failure," *J Am Coll Cardiol*, 2003; 41:565-57.
- Adamson, "Integrating device monitoring into the infrastructure and workflow of routine practice," *Rev Cardiovasc Med*. 2006 ;7 Suppl 1:42-6.
- Adhere [presentation], "Insights from the adhere Registry: Data from over 100,000 patient cases," 70 pages total.
- Advamed White Sheet, "Health Information Technology: Improving Patient Safety and Quality of Care," Jun. 2005, 23 pages.
- Aghababian, "Acutely decompensated heart failure: opportunities to improve care and outcomes in the emergency department," *Rev Cardiovasc Med*. 2002;3 Suppl 4:S3-9.
- Albert, "Bioimpedance to prevent heart failure hospitalization," *Curr Heart Fail Rep*. Sep. 2006;3(3):136-42.
- American Heart Association, "Heart Disease and Stroke Statistics—2006 Update," 2006, 43 pages.
- American Heart Association, "Heart Disease and Stroke Statistics—2007 Update. A Report From the American Heart Association Statistics Committee and Stroke Statistics Subcommittee," *Circulation* 2007; 115:e69-e171.
- Belalcazar et al., "Monitoring lung edema using the pacemaker pulse and skin electrodes," *Physiol. Meas.* 2005; 26:S153-S163.
- Bennet, "Development of implantable devices for continuous ambulatory monitoring of central hemodynamic values in heart failure patients," *PACE Jun*. 2005; 28:573-584.
- Bourge, "Case studies in advanced monitoring with the chronicle device," *Rev Cardiovasc Med*. 2006 ;7 Suppl 1:S56-61.
- Braunschweig, "Continuous haemodynamic monitoring during withdrawal of diuretics in patients with congestive heart failure," *European Heart Journal* 2002 23(1):59-69.
- Braunschweig, "Dynamic changes in right ventricular pressures during haemodialysis recorded with an implantable haemodynamic monitor," *Nephrol Dial Transplant* 2006; 21:176-183.
- Brennan, "Measuring a Grounded Impedance Profile Using the AD5933," Analog Devices, retrieved from the internet <<http://www.analog.com/static/imported-files/application_notes/427095282381510189AN847_0.pdf>>, 12 pages total.
- Buono et al., "The effect of ambient air temperature on whole-body bioelectrical impedance," *Physiol. Meas.* 2004;25:119-123.
- Burkhoff et al., "Heart failure with a normal ejection fraction: Is it really a disorder of diastolic function?" *Circulation* 2003; 107:656-658.
- Burr et al., "Heart rate variability and 24-hour minimum heart rate," *Biological Research for Nursing*, 2006; 7(4):256-267.
- Cardionet, "CardioNet Mobile Cardiac Outpatient Telemetry: Addendum to Patient Education Guide", CardioNet, Inc., 2007, 2 pages.
- Cardionet, "Patient Education Guide", CardioNet, Inc., 2007, 7 pages Undated.
- Charach et al., "Transthoracic monitoring of the impedance of the right lung in patients with cardiogenic pulmonary edema," *Crit Care Med Jun*. 2001;29(6):1137-1144.
- Charlson et al., "Can disease management target patients most likely to generate high costs? The Impact of Comorbidity," *Journal of General Internal Medicine*, Apr. 2007, 22(4):464-469.
- Chaudhry et al., "Telemonitoring for patients with chronic heart failure: a systematic review," *J Card Fail*. Feb. 2007; 13(1): 56-62.
- Chung et al., "White coat hypertension: Not so benign after all?," *Journal of Human Hypertension* (2003) 17, 807-809.
- Cleland et al., "The EuroHeart Failure survey programme—a survey on the quality of care among patients with heart failure in Europe—Part 1: patient characteristics and diagnosis," *European Heart Journal* 2003 24(5):442-463.
- Cowie et al., "Hospitalization of patients with heart failure. A population-based study," *European Heart Journal* 2002 23(11):877-885.
- Dimri, Chapter 1: Fractals in geophysics and seismology: an introduction, *Fractal Behaviour of the Earth System*, Springer Berlin Heidelberg 2005, pp. 1-22. [Summary and 1st page Only].
- EL-Dawlatly et al., "Impedance cardiography: noninvasive assessment of hemodynamics and thoracic fluid content during bariatric surgery," *Obesity Surgery*, May 2005, 15(5):655-658.
- Erdmann, "Editorials: The value of diuretics in chronic heart failure demonstrated by an implanted haemodynamic monitor," *European Heart Journal* 2002 23(1):7-9.
- FDA—Medtronic Inc., Chronicle 9520B Implantable Hemodynamic Monitor Reference Manual, 2007, 112 pages.
- FDA Executive Summary Memorandum, prepared for Mar. 1, 2007, meeting of the Circulatory Systems Devices Advisory Panel, P050032 Medtronic, Inc. Chronicle Implantable Hemodynamic Monitor (IHM) System, 23 pages. Retrieved from the Internet: <<http://www.fda.gov/ohrms/dockets/ac/07/briefing/2007-4284b1_02.pdf>>.
- FDA Executive Summary, Medtronic Chronicle Implantable Hemodynamic Monitoring System P050032: Panel Package Sponsor Executive Summary; vol. 1, section 4: Executive Summary. 12 pages total. Retrieved from the Internet: <<http://www.fda.gov/OHRMS/DOCKETS/AC/07/briefing/2007-4284b1_03.pdf>>.
- FDA—Medtronic Chronicle Implantable Hemodynamic Monitoring System P050032: Panel Package Section 11: Chronicle IHM Summary of Safety and Effectiveness, 77 pages.
- FDA, Draft questions for Chronicle Advisory Panel Meeting, 3 pages. Retrieved from the Internet: <<http://www.fda.gov/ohrms/dockets/ac/07/questions/2007-4284q1_draft.pdf>>.
- FDA, References for Mar. 1 Circulatory System Devices Panel, 1 page total. 2007. Retrieved from the Internet: <<http://www.fda.gov/OHRMS/DOCKETS/AC/07/briefing/2007-4284bib1_01.pdf>>.
- FDA, Circulatory System Devices Advisory Panel Meeting Roster, Mar. 1, 2007. Retrieved from the Internet: <<http://www.fda.gov/ohrms/dockets/AC/07/roster/2007-4284r1_draft.pdf>>.
- Fonarow et al., "Risk stratification for in-hospital mortality in acutely decompensated heart failure: classification and regression tree analysis," *JAMA*. Feb. 2, 2005;293(5):572-580.
- Fonarow, "How well are chronic heart failure patients being managed?," *Rev Cardiovasc Med*. 2006;7 Suppl 1:S3-11.
- Fonarow, "Maximizing Heart Failure Care" [Powerpoint Presentation], downloaded from the Internet <<<http://www.medreviews.com/media/MaxHFCare.ppt>>>, 130 pages total.
- Fonarow, "Proactive monitoring and management of the chronic heart failure patient," *Rev Cardiovasc Med*. 2006; 7 Suppl 1:S1-2.
- Fonarow, "The Acute Decompensated Heart Failure National Registry (ADHERE): opportunities to improve care of patients hospitalized with acute decompensated heart failure," *Rev Cardiovasc Med*. 2003;4 Suppl 7:S21-S30.
- Ganion et al., "Intrathoracic impedance to monitor heart failure status: a comparison of two methods in a chronic heart failure dog model," *Congest Heart Fail*. Jul.-Aug. 2005;11(4):177-81, 211.
- Gass et al., "Critical pathways in the management of acute decompensated heart failure: A CME-Accredited monograph," Mount Sinai School of Medicine, 2004, 32 pages total.
- Gheorghade et al., "Congestion is an important diagnostic and therapeutic target in heart failure," *Rev Cardiovasc Med*. 2006 ;7 Suppl 1 :12-24.
- Gilliam, III et al., "Changes in heart rate variability, quality of life, and activity in cardiac resynchronization therapy patients: results of the HF-HRV registry," *Pacing and Clinical Electrophysiology*, Jan. 18, 2007; 30(1): 56-64.
- Gilliam, III et al., "Prognostic value of heart rate variability footprint and standard deviation of average 5-minute intrinsic R-R intervals for mortality in cardiac resynchronization therapy patients," *J Electrocardiol*. Oct. 2007;40(4):336-42.
- Gniadecka, "Localization of dermal edema in lipodermatosclerosis, lymphedema, and cardiac insufficiency high-frequency ultrasound examination of intradermal echogenicity," *J Am Acad oDermatol*, Jul. 1996; 35(1):37-41.
- Goldberg et al., "Randomized trial of a daily electronic home monitoring system in patients with advanced heart failure: The Weight Monitoring in Heart Failure (WHARF) Trial," *American Heart Journal*, Oct. 2003; 416(4):705-712.

(56)

References Cited

OTHER PUBLICATIONS

- Grap et al., "Actigraphy in the Critically III: Correlation With Activity, Agitation, and Sedation," *American Journal of Critical Care* 2005;14: 52-60.
- Gudivaka et al., "Single- and multifrequency models for bioelectrical impedance analysis of body water compartments," *J Appl Physiol*, 1999;87(3):1087-1096.
- Guyton et al., Unit V: The Body Fluids and Kidneys, Chapter 25: The Body Fluid Compartments: Extracellular and Intracellular Fluids; Interstitial Fluid and Edema, *Guyton & Hall Textbook of Medical Physiology* 11th Edition, Saunders 2005; pp. 291-306.
- Hadase et al., "Very low frequency power of heart rate variability is a powerful predictor of clinical prognosis in patients with congestive heart failure," *Circ J* 2004; 68(4):343-347.
- Hallstrom et al., "Structural relationships between measures based on heart beat intervals: potential for improved risk assessment," *IEEE Biomedical Engineering* 2004, 51(8):1414-1420.
- HFSA 2006 Comprehensive Heart Failure Practice Guideline—Executive Summary: HFSA 2006 Comprehensive Heart Failure Practice Guideline, *Journal of Cardiac Failure* 2006;12(1):10-e38.
- HFSA 2006 Comprehensive Heart Failure Practice Guideline—Section 12: Evaluation and Management of Patients With Acute Decompensated Heart Failure, *Journal of Cardiac Failure* 2006;12(1):e86-e103.
- HFSA 2006 Comprehensive Heart Failure Practice Guideline—Section 2: Conceptualization and Working Definition of Heart Failure, *Journal of Cardiac Failure* 2006;12(1):e10-e11.
- HFSA 2006 Comprehensive Heart Failure Practice Guideline—Section 3: Prevention of Ventricular Remodeling Cardiac Dysfunction, and Heart Failure Overview, *Journal of Cardiac Failure* 2006;12(1):e12-e15.
- HFSA 2006 Comprehensive Heart Failure Practice Guideline—Section 4: Evaluation of Patients for Ventricular Dysfunction and Heart Failure, *Journal of Cardiac Failure* 2006;12(1):e16-e25.
- HFSA 2006 Comprehensive Heart Failure Practice Guideline—Section 8: Disease Management in Heart Failure Education and Counseling, *Journal of Cardiac Failure* 2006;12(1):e58-e68.
- Hunt et al., "ACC/AHA 2005 Guideline Update for the Diagnosis and Management of Chronic Heart Failure in the Adult: A Report of the American College of Cardiology/American Heart Association Task Force on Practice Guidelines (Writing Committee to Update the 2001 Guidelines for the Evaluation and Management of Heart Failure): Developed in Collaboration With the American College of Chest Physicians and the International Society for Heart and Lung Transplantation: Endorsed by the Heart Rhythm Society," *Circulation* 2005;112:e154-e235.
- Hunt et al., ACC/AHA Guidelines for the Evaluation and Management of Chronic Heart Failure in the Adult: Executive Summary A Report of the American College of Cardiology/American Heart Association Task Force on Practice Guidelines (Committee to Revise the 1995 Guidelines for the Evaluation and Management of Heart Failure), *Circulation* 2001;104:2996-3007.
- Imhoff et al., "Noninvasive whole-body electrical bioimpedance cardiac output and invasive thermodilution cardiac output in high-risk surgical patients," *Critical Care Medicine* 2000; 28(8):2812-2818.
- Jaeger et al., "Evidence for Increased Intrathoracic Fluid Volume in Man at High Altitude," *J Appl Physiol* 1979; 47(6): 670-676.
- Jerant et al., "Reducing the cost of frequent hospital admissions for congestive heart failure: a randomized trial of a home telecare intervention," *Medical Care* 2001, 39(11):1234-1245.
- Jaio et al., "Variance fractal dimension analysis of seismic refraction signals," *WESCANEX 97: Communications, Power and Computing*. IEEE Conference Proceedings., May 22-23, 1997, pp. 163-167 [Abstract Only].
- Kasper et al., "A randomized trial of the efficacy of multidisciplinary care in heart failure outpatients at high risk of hospital readmission," *J Am Coll Cardiol*, 2002; 39:471-480.
- Kaukinen, "Cardiac output measurement after coronary artery bypass grafting using bolus thermodilution, continuous thermodilution, and whole-body impedance cardiography," *Journal of Cardiothoracic and Vascular Anesthesia* 2003; 17(2):199-203.
- Kawaguchi et al., "Combined ventricular systolic and arterial stiffening in patients with heart failure and preserved ejection fraction: implications for systolic and diastolic reserve limitations," *Circulation*. 2003;107:714-720.
- Kawasaki et al., "Heart rate turbulence and clinical prognosis in hypertrophic cardiomyopathy and myocardial infarction," *Circ J*. Jul. 2003;67(7):601-604.
- Kearney et al., "Predicting death due to progressive heart failure in patients with mild-to-moderate chronic heart failure," *J Am Coll Cardiol*, 2002; 40(10):1801-1808.
- Kitzman et al., "Pathophysiological characterization of isolated diastolic heart failure in comparison to systolic heart failure," *JAMA* Nov. 2002; 288(17):2144-2150.
- Köobi et al., "Non-invasive measurement of cardiac output : whole-body impedance cardiography in simultaneous comparison with thermodilution and direct oxygen Fick methods," *Intensive Care Medicine* 1997; 23(11):1132-1137.
- Koyama et al., "Evaluation of heart-rate turbulence as a new prognostic marker in patients with chronic heart failure," *Circ J* 2002; 66(10):902-907.
- Krumholz et al., "Predictors of readmission among elderly survivors of admission with heart failure," *American Heart Journal* 2000; 139(1):72-77.
- Kyle et al., "Bioelectrical Impedance Analysis—part I: review of principles and methods," *Clin Nutr*. Oct. 2004;23(5):1226-1243.
- Kyle et al., "Bioelectrical Impedance Analysis—part II: utilization in clinical practice," *Clin Nutr*. Oct. 2004;23(5):1430-1453.
- Lee et al., "Predicting mortality among patients hospitalized for heart failure: derivation and validation of a clinical model," *JAMA* 2003;290(19):2581-2587.
- Leier "The Physical Examination in Heart Failure—Part I," *Congest Heart Fail*. Jan.-Feb. 2007;13(1):41-47.
- Libbus, "BioZ Analysis," Corventis, Inc., 7 pages (date unknown).
- LifeShirt® Model 200 Directions for Use*, "Introduction", VivoMetrics, Inc. 9 page total.
- Liu et al., "Fractal analysis with applications to seismological pattern recognition of underground nuclear explosions," *Signal Processing*, Sep. 2000, 80(9):1849-1861. [Abstract Only].
- Lozano-Nieto, "Impedance ratio in bioelectrical impedance measurements for body fluid shift determination," *Proceedings of the IEEE 24th Annual Northeast Bioengineering Conference*, Apr. 9-10, 1998, pp. 24-25.
- Lucreziotti et al., "Five-minute recording of heart rate variability in severe chronic heart failure : Correlates with right ventricular function and prognostic implications," *American Heart Journal* 2000; 139(6):1088-1095.
- Lüthje et al., "Detection of heart failure decompensation using intrathoracic impedance monitoring by a triple-chamber implantable defibrillator," *Heart Rhythm* Sep. 2005;2(9):997-999.
- Magalski et al., "Continuous ambulatory right heart pressure measurements with an implantable hemodynamic monitor: a multicenter, 12-Month Follow-up Study of Patients With Chronic Heart Failure," *J Card Fail* 2002, 8(2):63-70.
- Mahlberg et al., "Actigraphy in agitated patients with dementia: Monitoring treatment outcomes," *Zeitschrift für Gerontologie und Geriatrie*, Jun. 2007; 40(3):178-184. [Abstract Only].
- Matthie et al., "Analytic assessment of the various bioimpedance methods used to estimate body water," *Appl Physiol* 1998; 84(5):1801-1816.
- Matthie, "Second generation mixture theory equation for estimating intracellular water using bioimpedance spectroscopy," *J Appl Physiol* 2005; 99:780-781.
- McMurray et al., "Heart Failure: Epidemiology, Aetiology, and Prognosis of Heart Failure," *Heart* 2000;83:596-602.
- Miller, "Home monitoring for congestive heart failure patients," *Caring Magazine*, Aug. 1995: 53-54.
- Moser et al., "Improving outcomes in heart failure: it's not unusual beyond usual care," *Circulation*. 2002;105:2810-2812.
- Nagels et al., "Actigraphic measurement of agitated behaviour in dementia," *International journal of geriatric psychiatry* , 2009; 21(4):388-393. [Abstract Only].

(56)

References Cited

OTHER PUBLICATIONS

- Nakamura et al., "Universal scaling law in human behavioral organization," *Physical Review Letters*, Sep. 28, 2007; 99(13):138103 (4 pages).
- Nakaya, "Fractal properties of seismicity in regions affected by large, shallow earthquakes in western Japan: Implications for fault formation processes based on a binary fractal fracture network model," *Journal of geophysical research*, Jan. 2005; 11(B1):B01310.1-B01310.15. [Abstract Only].
- Naylor et al., "Comprehensive discharge planning for the hospitalized elderly: a randomized clinical trial," *Amer. College Physicians* 1994; 120(12):999-1006.
- Nesiritide (NATRECOR) [Presentation] Acutely Decompensated Congestive Heart Failure: Burden of Disease, downloaded from the Internet: <<<http://www.huntsvillehospital.org/foundation/events/cardiologypupdate/CHF.ppt>>>, 39 pages.
- Nieminen et al., "EuroHeart Failure Survey II (EHFS II): a survey on hospitalized acute heart failure patients: description of population," *European Heart Journal* 2006; 27(22):2725-2736.
- Nijssen et al., "The potential value of three-dimensional accelerometry for detection of motor seizures in severe epilepsy," *Epilepsy Behav.* Aug. 2005; 7(1):74-84.
- Noble et al., "Diuretic induced change in lung water assessed by electrical impedance tomography," *Physiol. Meas.* 2000; 21(1):155-163.
- Noble et al., "Monitoring patients with left ventricular failure by electrical impedance tomography," *Eur J Heart Fail.* Dec. 1999; 1(4):379-84.
- O'Connell et al., "Economic impact of heart failure in the United States: time for a different approach," *J Heart Lung Transplant.*, Jul.-Aug. 1994; 13(4):5107-5112.
- Ohlsson et al., "Central hemodynamic responses during serial exercise tests in heart failure patients using implantable hemodynamic monitors," *Eur J Heart Fail.* Jun. 2003; 5(3):253-259.
- Ohlsson et al., "Continuous ambulatory monitoring of absolute right ventricular pressure and mixed venous oxygen saturation in patients with heart failure using an implantable haemodynamic monitor," *European Heart Journal* 2001 22(11):942-954.
- Packet et al., "Utility of impedance cardiography for the identification of short-term risk of clinical decompensation in stable patients with chronic heart failure," *J Am Coll Cardiol*, 2006; 47(11):2245-2252.
- Palatini et al., "Predictive value of clinic and ambulatory heart rate for mortality in elderly subjects with systolic hypertension" *Arch Intern Med.* 2002; 162:2313-2321.
- Piirila et al., "Crackles in patients with fibrosing alveolitis bronchiectasis, COPD, and Heart Failure," *Chest* May 1991; 99(5):1076-1083.
- Pocock et al., "Predictors of mortality in patients with chronic heart failure," *Eur Heart J* 2006; (27): 65-75.
- Poole-Wilson, "Importance of control of fluid volumes in heart failure," *European Heart Journal* 2000; 22(11):893-894.
- Raj et al., "Letter Regarding Article by Adamson et al., "Continuous Autonomic Assessment in Patients With Symptomatic Heart Failure: Prognostic Value of Heart Rate Variability Measured by an Implanted Cardiac Resynchronization Device," *Circulation* 2005; 112:e37-e38.
- Raj, Correspondence—Letter Regarding Article by Adamson et al., "Continuous Autonomic Assessment in Patients With Symptomatic Heart Failure: Prognostic Value of Heart Rate Variability Measured by an Implanted Cardiac Resynchronization Device," *Circulation* 2005; 112:e37-e38.
- Ramirez et al., "Prognostic value of hemodynamic findings from impedance cardiography in hypertensive stroke," *AJH* 2005; 18(20):65-72.
- Rich et al., "A multidisciplinary intervention to prevent the readmission of elderly patients with congestive heart failure," *New Engl. J. Med.* 1995; 333:1190-1195.
- Rodgers, [presentation] "Update on the Management of Heart Failure," Southern Regional Area Health Education Centers at Sampson Regional Medical Center, Clinton, NC Apr. 2004, 76 pages total.
- Roglieri et al., "Disease management interventions to improve outcomes in congestive heart failure," *Am J Manag Care.* Dec. 1997; 3(12):1831-1839.
- Sahalos et al., "The Electrical impedance of the human thorax as a guide in evaluation of intrathoracic fluid volume," *Phys. Med. Biol.* 1986; 31:425-439.
- Saxon et al., "Remote active monitoring in patients with heart failure (rapid-rf): design and rationale," *Journal of Cardiac Failure* 2007; 13(4):241-246.
- Scharf et al., "Direct digital capture of pulse oximetry waveforms," *Proceedings of the Twelfth Southern Biomedical Engineering Conference*, 1993., pp. 230-232.
- Shabetai, "Monitoring heart failure hemodynamics with an implanted device: its potential to improve outcome," *J Am Coll Cardiol*, 2003; 41:572-573.
- Small, "Integrating monitoring into the Infrastructure and Workflow of Routine Practice: OptiVol," *Rev Cardiovasc Med.* 2006 ; 7 Suppl 1: S47-S55.
- Smith et al., "Outcomes in heart failure patients with preserved ejection fraction: mortality, readmission, and functional decline," *J Am Coll Cardiol*, 2003; 41:1510-1518.
- Someren, "Actigraphic monitoring of movement and rest-activity rhythms in aging, Alzheimer's disease, and Parkinson's disease," *IEEE Transactions on Rehabilitation Engineering*, Dec. 1997; 5(4):394-398. [Abstract Only].
- Starling, "Improving care of chronic heart failure: advances from drugs to devices," *Cleveland Clinic Journal of Medicine* Feb. 2003; 70(2):141-146.
- Steijaert et al., "The use of multi-frequency impedance to determine total body water and extracellular water in obese and lean female individuals," *International Journal of Obesity* Oct. 1997; 21(10):930-934.
- Stewart et al., "Effects of a home-based intervention among patients with congestive heart failure discharged from acute hospital care," *Arch Intern Med.* 1998; 158:1067-1072.
- Stewart et al., "Effects of a multidisciplinary, home-based intervention on planned readmissions and survival among patients with chronic congestive heart failure: a randomised controlled study," *The Lancet* Sep. 1999, 354(9184):1077-1083.
- Stewart et al., "Home-based intervention in congestive heart failure: long-term implications on readmission and survival," *Circulation.* 2002; 105:2861-2866.
- Stewart et al., "Prolonged beneficial effects of a home-based intervention on unplanned readmissions and mortality among patients with congestive heart failure," *Arch Intern Med.* 1999; 159:257-261.
- Stewart et al., "Trends in Hospitalization for Heart Failure in Scotland, 1990-1996. An Epidemic that has Reached Its Peak?," *European Heart Journal* 2001 22(3):209-217.
- Swedberg et al., "Guidelines for the diagnosis and treatment of chronic heart failure: executive summary (update 2005): The Task Force for the Diagnosis and Treatment of Chronic Heart Failure of the European Society of Cardiology," *Eur Heart J.* Jun. 2005; 26(11):1115-1140.
- Tang, "Case studies in advanced monitoring: OptiVol," *Rev Cardiovasc Med.* 2006; 7 Suppl 1:S62-S66.
- The ESCAPE Investigators and ESCAPE Study Coordinators, "Evaluation Study of Congestive Heart Failure and Pulmonary Artery Catheterization Effectiveness," *JAMA* 2005; 294:1625-1633.
- Tosi et al., "Seismic signal detection by fractal dimension analysis," *Bulletin of the Seismological Society of America*; Aug. 1999; 89(4):970-977. [Abstract Only].
- Van De Water et al., "Monitoring the chest with impedance," *Chest.* 1973; 64:597-603.
- Vasan et al., "Congestive heart failure in subjects with normal versus reduced left ventricular ejection fraction," *J Am Coll Cardiol*, 1999; 33:1948-1955.
- Verdecchia et al., "Adverse prognostic value of a blunted circadian rhythm of heart rate in essential hypertension," *Journal of Hypertension* 1998; 16(9):1335-1343.

(56)

References Cited

OTHER PUBLICATIONS

Verdecchia et al., "Ambulatory pulse pressure: a potent predictor of total cardiovascular risk in hypertension," *Hypertension*. 1998;32:983-988.

Vollmann et al., "Clinical utility of intrathoracic impedance monitoring to alert patients with an implanted device of deteriorating chronic heart failure," *European Heart Journal Advance Access published on Feb. 19, 2007*, downloaded from the Internet: <<<http://eurheartj.oxfordjournals.org/cgi/content/full/ehl506v1>>>, 6 pages total.

Vuksanovic et al., "Effect of posture on heart rate variability spectral measures in children and young adults with heart disease," *International Journal of Cardiology* 2005;101(2): 273-278.

Wang et al., "Feasibility of using an implantable system to measure thoracic congestion in an ambulatory chronic heart failure canine model," *PACE* 2005;28(5):404-411.

Wickemeyer et al., #197—"Association between atrial and ventricular tachyarrhythmias, intrathoracic impedance and heart failure decompensation in CRT-D Patients," *Journal of Cardiac Failure* 2007; 13 (6) Suppl.; S131-132.

Williams et al., "How do different indicators of cardiac pump function impact upon the long-term prognosis of patients with chronic heart failure," *American Heart Journal*, 150(5):983.e1-983.e6.

Wonisch et al., "Continuous haemodynamic monitoring during exercise in patients with pulmonary hypertension," *Int J Cardiol*. Jun. 8, 2005;101(3):415-420.

Wynne et al., "Impedance cardiography: a potential monitor for hemodialysis," *Journal of Surgical Research* 2006, 133(1):55-60.

Yancy "Current approaches to monitoring and management of heart failure," *Rev Cardiovasc Med* 2006; 7 Suppl 1:S25-32.

Ypenburg et al., "Intrathoracic Impedance Monitoring to Predict Decompensated Heart Failure," *Am J Cardiol* 2007, 99(4):554-557.

Yu et al., "Intrathoracic Impedance Monitoring in Patients With Heart Failure: Correlation With Fluid Status and Feasibility of Early Warning Preceding Hospitalization," *Circulation*. 2005;112:841-848.

Zannad et al., "Incidence, clinical and etiologic features, and outcomes of advanced chronic heart failure: The EPICAL Study," *J Am Coll Cardiol*, 1999; 33(3):734-742.

Zile, "Heart failure with preserved ejection fraction: is this diastolic heart failure?" *J Am Coll Cardiol*, 2003; 41(9):1519-1522.

U.S. Appl. No. 60/006,600, filed Nov. 13, 1995; inventor: Terry E. Flach.

U.S. Appl. No. 60/972,316, filed Sep. 12, 2008; inventor: Imad Libbus et al.

U.S. Appl. No. 60/972,329, filed Sep. 14, 2007; inventor: Yatheendhar Manicka et al.

U.S. Appl. No. 60/972,333, filed Sep. 14, 2007; inventor: Mark Bly et al.

U.S. Appl. No. 60/972,336, filed Sep. 14, 2007; inventor: James Kristofer et al.

U.S. Appl. No. 60/972,340, filed Sep. 14, 2007; inventor: James Kristofer et al.

U.S. Appl. No. 60/972,343, filed Sep. 14, 2007; inventor: James Kristofer et al.

U.S. Appl. No. 60/972,354, filed Sep. 14, 2007; inventor: Scott Thomas Mazar et al.

U.S. Appl. No. 60/972,359, filed Sep. 14, 2007; inventor: Badri Amurthur et al.

U.S. Appl. No. 60/972,363, filed Sep. 14, 2007; inventor: Badri Amurthur et al.

U.S. Appl. No. 60/972,512, filed Sep. 14, 2007; inventor: Imad Libbus et al.

U.S. Appl. No. 60/972,537, filed Sep. 14, 2007; inventor: Yatheendhar Manicka et al.

U.S. Appl. No. 60/972,581, filed Sep. 14, 2007; inventor: Imad Libbus et al.

U.S. Appl. No. 60/972,616, filed Sep. 14, 2007; inventor: Imad Libbus et al.

U.S. Appl. No. 60/972,629, filed Sep. 14, 2007; inventor: Mark Bly et al.

U.S. Appl. No. 61/035,970, filed Mar. 12, 2008; inventor: Imad Libbus et al.

U.S. Appl. No. 61/046,196, filed Apr. 18, 2008; inventor: Scott T. Mazar.

U.S. Appl. No. 61/047,875, filed Apr. 25, 2008; inventor: Imad Libbus et al.

U.S. Appl. No. 61/055,645, filed May 23, 2008; inventor: Mark Bly et al.

U.S. Appl. No. 61/055,656, filed May 23, 2008; inventor: Imad Libbus et al.

U.S. Appl. No. 61/055,662, filed May 23, 2008; inventor: Imad Libbus et al.

U.S. Appl. No. 61/055,666, filed May 23, 2008; inventor: Yatheendhar Manicka et al.

U.S. Appl. No. 61/079,746, filed Jul. 10, 2008; inventor: Brett Landrum.

U.S. Appl. No. 61/084,567, filed Jul. 29, 2008; inventor: Mark Bly.

Packer et al., "Utility of impedance cardiography for the identification of short-term risk of clinical decompensation in stable patients with chronic heart failure," *J Am Coll Cardiol*, 2006; 47(11):2245-2252.

EM Microelectronic—Marin SA, "Plastic Flexible LCD," [product brochure]; retrieved from the Internet: <<<http://www.em-microelectronic.com/Line.asp?IdLine=48>>>, copyright 2009, 2 pages total.

HRV Enterprises, LLC, "Heart Rate Variability Seminars," downloaded from the Internet: <<<http://hrventerprise.com/>>> on Apr. 24, 2008, 3 pages total.

HRV Enterprises, LLC, "LoggerPro HRV Biosignal Analysis," downloaded from the Internet: <<<http://hrventerprise.com/products.html>>> on Apr. 24, 2008, 3 pages total.


3M Corporation, "3M Surgical Tapes—Choose the Correct Tape" quicksheet (2004).

Cooley, "The Parameters of Transthoracic Electrical Conduction," *Annals of the New York Academy of Sciences*, 1970, 170(2):702-713.

The Criteria Committee of the New York Heart Association, *Nomenclature and Criteria for Diagnosis of Diseases of the Heart and Great Vessels*, 9th Edition, Eds. Dolgin et al., Little, Brown and Company, Boston, 1994, pp. 253-255.

Varughese, Sheeba, "Management of Acute Decompensated Heart Failure," *Crit Care Nurs Q*, vol. 30, No. 2, Mar. 7, 2007, pp. 94-103.

* cited by examiner






FIG. 1B




FIG. 1C




FIG. 1D




FIG. 1D-1




FIG. 1E




FIG. 1F




FIG. 1H




FIG. 1G




FIG. 2A




FIG. 3A




FIG. 3B

1

MULTI-SENSOR PATIENT MONITOR TO DETECT IMPENDING CARDIAC DECOMPENSATION

CROSS-REFERENCES TO RELATED APPLICATIONS

The present application claims the benefit under 35 USC 119(e) of U.S. Provisional Application Nos. 60/972,512 and 60/972,537 both filed Sep. 14, 2007, and 61/055,666 filed May 23, 2008; the full disclosures of which are incorporated herein by reference in their entirety.

The subject matter of the present application is related to the following applications: 60/972,329; 60/972,354; 60/972,616; 60/972,363; 60/972,343; 60/972,581; 60/972,629; 60/972,316; 60/972,333; 60/972,359; 60/972,336; 60/972,340 all of which were filed on Sep. 14, 2007; 61/046,196 filed Apr. 18, 2008; 61/047,875 filed Apr. 25, 2008; 61/055,645, 61/055,656, 61/055,662 all filed May 23, 2008; and 61/079,746 filed Jul. 10, 2008.

The following applications are being filed concurrently with the present application, on Sep. 12, 2008: application Ser. No. 12/209,288 entitled "Adherent Device with Multiple Physiological Sensors"; application Ser. No. 12/209,430 entitled "Injectable Device for Physiological Monitoring"; application Ser. No. 12/209,479 entitled "Delivery System for Injectable Physiological Monitoring System"; application Ser. No. 12/209,262 entitled "Adherent Device for Cardiac Rhythm Management"; application Ser. No. 12/209,268 entitled "Adherent Device for Respiratory Monitoring"; application Ser. No. 12/209,269 entitled "Adherent Athletic Monitor"; application Ser. No. 12/209,259 entitled "Adherent Emergency Monitor"; application Ser. No. 12/209,273 entitled "Adherent Device with Physiological Sensors"; application Ser. No. 12/209,276 entitled "Medical Device Automatic Start-up upon Contact to Patient Tissue"; application Ser. No. 12/210,078 entitled "System and Methods for Wireless Body Fluid Monitoring"; application Ser. No. 12/209,265 entitled "Adherent Cardiac Monitor with Advanced Sensing Capabilities"; application Ser. No. 12/209,292 entitled "Adherent Device for Sleep Disordered Breathing"; application Ser. No. 12/209,278 entitled "Dynamic Pairing of Patients to Data Collection Gateways"; application Ser. No. 12/209,508 entitled "Adherent Multi-Sensor Device with Implantable Device Communications Capabilities"; application Ser. No. 12/209,528 entitled "Data Collection in a Multi-Sensor Patient Monitor"; application Ser. No. 12/209,271 entitled "Adherent Multi-Sensor Device with Empathic Monitoring"; application Ser. No. 12/209,274 entitled "Energy Management for Adherent Patient Monitor"; and application Ser. No. 12/209,294 "Tracking and Security for Adherent Patient Monitor."

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to patient monitoring, and more specifically to patient monitoring to detect and/or avoid impending cardiac decompensation. Although embodiments make specific reference to monitoring impedance and electrocardiogram signals with an adherent patch, the system methods and device described herein may be applicable to many applications in which physiological monitoring is used, for example wireless physiological monitoring with implantable devices for extended periods.

Patients are often treated for diseases and/or conditions associated with a compromised status of the patient, for

2

example a compromised physiologic status such as heart disease. In some instances a patient may have suffered a heart attack and require care and/or monitoring after release from the hospital. While such long term care may be at least partially effective, many patients are not sufficiently monitored and eventually succumb to cardiac decompensation, or heart failure. One example of a device that may be used to monitor a patient is the Holter monitor, or ambulatory electrocardiography device. Although such a device may be effective in measuring electrocardiography, such measurements alone may not be sufficient to reliably detect and/or avoid an impending cardiac decompensation.

In addition to measuring heart signals with electrocardiograms, known physiologic measurements include impedance measurements. For example, transthoracic impedance measurements can be used to measure hydration and respiration. Although transthoracic measurements can be useful, such measurements may use electrodes that are positioned across the midline of the patient, and may be somewhat uncomfortable and/or cumbersome for the patient to wear.

Work in relation to embodiments of the present invention suggests that known methods and apparatus for long term monitoring of patients may be less than ideal to detect and/or avoid an impending cardiac decompensation. In at least some instances, cardiac decompensation can be difficult to detect, for example in the early stages. At least some of the known devices may not collect the right kinds of data to treat patients optimally. For example, although successful at detecting and storing electrocardiogram signals, devices such as the Holter monitor can be somewhat bulky and may not collect all of the kinds of data that would be ideal to diagnose and/or treat a patient, for example to detect decompensation. In at least some instances, devices that are worn by the patient may be somewhat uncomfortable, which may lead to patients not wearing the devices and not complying with direction from the health care provider, such that data collected may be less than ideal. Although implantable devices may be used in some instances, many of these devices can be invasive and/or costly, and may suffer at least some of the shortcomings of known wearable devices. As a result, at least some patient are not adequately monitored, and may go into cardiac decompensation, or even die. Work in relation to embodiments of the present invention suggests that improved monitoring may avoid patient trauma, save lives, and decrease health care costs.

Therefore, a need exists for improved patient monitoring. Ideally, such improved patient monitoring would avoid at least some of the short-comings of the present methods and devices.

2. Description of the Background Art

The following U.S. Patents and Publications may describe relevant background art: U.S. Pat. Nos. 4,121,573; 4,955,381; 4,981,139; 5,080,099; 5,353,793; 5,469,859; 5,511,553; 5,544,661; 5,558,638; 5,724,025; 5,772,586; 5,862,802; 6,047,203; 6,117,077; 6,129,744; 6,225,901; 6,308,094; 6,385,473; 6,416,471; 6,454,707; 6,454,708; 6,527,711; 6,527,729; 6,551,252; 6,595,927; 6,595,929; 6,605,038; 6,645,153; 6,821,249; 6,980,851; 7,020,508; 7,054,679; 7,153,262; 7,160,252; 2004/133079; 2004/152956; 2005/0113703; 2005/0131288; 2006/0010090; 2006/0031102; 2006/0089679; 2006/122474; 2006/0155183; 2006/0224051; 2006/0264730; 2007/0021678; 2007/0038038; 2005/256418; 2005/137626; and 2006/161459. The following PCT Publication(s) may also describe relevant background art: WO2006/111878.

BRIEF SUMMARY OF THE INVENTION

Embodiments of the present invention provide systems and methods for the detection of an impending cardiac decompensation.

pensation. In many embodiments, the impending decompensation can be detected early enough to avoid, or at least delay, the impending decompensation, such that patient trauma and/or expensive ICU care can be avoided. Although embodiments make specific reference to monitoring impedance and electrocardiogram signals with an adherent patch, the system methods and device described herein may be applicable to many applications in which physiological monitoring is used, for example wireless physiological monitoring with implanted sensors for extended periods.

In a first aspect, embodiments of the present invention provide a method of detecting an impending cardiac decompensation of a patient. At least two of an electrocardiogram signal of the patient, a hydration signal of the patient, a respiration signal of the patient or an activity signal of the patient are measured. The at least two of the electrocardiogram signal, the hydration signal, the respiration signal or the activity signal are combined to detect the impending cardiac decompensation. In many embodiments, the impending decompensation can be detected at least 24 hours before the decompensation occurs, for example 72 hours, and in many embodiments with a confidence level of at least 80%, for example 90%.

In many embodiments, the at least two comprise at least three of the electrocardiogram signal, the hydration signal, the respiration signal or the activity signal, and the at least three are measured and combined to detect the impending cardiac decompensation. In specific embodiments, the at least three comprise at least four of the electrocardiogram signal, the hydration signal, the respiration signal or the activity signal, and the at least four are measured and combined to detect the impending cardiac decompensation.

In specific embodiments, the electrocardiogram signal, the hydration signal, the respiration signal and the activity signal are measured combined to detect the impending cardiac decompensation.

In many embodiments, the at least two of the electrocardiogram signal, the hydration signal, the respiration signal or the activity signal can be used simultaneously to determine impending cardiac decompensation. The at least two signals can be used simultaneously in many ways.

In many embodiments, combining comprises using the at least two of the electrocardiogram signal, the hydration signal, the respiration signal or the activity signal to look up a value in a previously existing array. In some embodiments, combining may comprise at least one of adding, subtracting, multiplying, scaling or dividing the at least two of the electrocardiogram signal, the hydration signal, the respiration signal or the activity signal. In some embodiments, the at least two of the electrocardiogram signal, the hydration signal, the respiration signal or the activity signal can be combined with at least one of a weighted combination, a tiered combination or a logic gated combination, a time weighted combination or a rate of change.

In many embodiments, a flag status is determined in response to the at least two of the electrocardiogram signal, the hydration signal, the respiration signal or the activity signal. The flag status can be determined in response to a change in the at least two of the electrocardiogram signal, the hydration signal, the respiration signal or the activity signal. In some embodiments, additional signal measurements of the patient can be made in response to the flag status.

In many embodiments, the at least two of the electrocardiogram signal, the hydration signal, the respiration signal or the activity signal are combined in response to a time of day.

In many embodiments, the at least two of the electrocardiogram signal, the hydration signal, the respiration signal or

the activity signal may comprise at least one of a derived signal, a time averaged signal, a filtered signal or a raw signal.

In many embodiments, baseline values of the patient for the at least two of the electrocardiogram signal, the hydration signal, the respiration signal or the activity signal are determined, and the at least two of the electrocardiogram signal, the hydration signal, the respiration signal or the activity signal signals comprise changes from the baseline values.

In many embodiments, the at least two of the electrocardiogram signal, the hydration signal, the respiration signal or the activity signal comprise differences from population baseline values, and the impending decompensation is detected in response to the differences from the baseline values of the patient population.

In many embodiments, the hydration signal comprises an impedance signal and the activity signal comprise an accelerometer signal.

In many embodiments, the activity signal may comprise an accelerometer signal to indicate a posture of the patient. In specific embodiments, the accelerometer signal may comprise a three dimensional inclination signal to determine a three dimensional orientation of the patient.

In many embodiments, a temperature signal is combined with the at least two of the electrocardiogram signal, the hydration signal, the respiration signal or the activity signal to detect the impending cardiac decompensation.

In many embodiments, the at least two of the electrocardiogram signal, the hydration signal, the respiration signal or the activity signal are transmitted to a remote site where the at least two of the electrocardiogram signal, the hydration signal, the respiration signal or the activity signal are combined to detect the impending cardiac decompensation.

In many embodiments, instructions are transmitted from a remote site to a processor supported with the patient, and the at least two of the electrocardiogram signal, the hydration signal, the respiration signal or the activity signal are combined with the processor in response to the instructions to detect the impending cardiac decompensation.

In another aspect, embodiments of the present invention provide a system to detect impending cardiac decompensation of a patient. The system comprises circuitry to measure at least two of an electrocardiogram signal of the patient, a hydration signal of the patient, or an activity signal of the patient. A processor system comprising a tangible medium in communication with the circuitry is configured to combine the at least two of the electrocardiogram signal, the hydration signal, the respiration signal or the activity signal to detect the impending cardiac decompensation.

In some embodiments, the processor system comprises a least one processor remote from the patient configured to combine the at least two to detect the decompensation.

In some embodiments, the processor system comprises a processor supported with the patient configured to receive instructions transmitted from a remote site and combine the at least two in response to the instructions to detect the impending cardiac decompensation.

In many embodiments, the at least two comprise at least three of the electrocardiogram signal, the hydration signal, the respiration signal or the activity signal and the at least three are measured and combined to detect the impending cardiac decompensation. In specific embodiments, the at least three comprise at least four of the electrocardiogram signal, the hydration signal, the respiration signal or the activity signal and the at least four are measured and combined to detect the impending cardiac decompensation.

In specific embodiments, the processor system simultaneously uses the at least two of the electrocardiogram signal,

5

the hydration signal, the respiration signal or the activity signal to determine impending cardiac decompensation. The at least two signals can be used simultaneously in many ways,

In many embodiments, combining comprises the processor system using the at least two of the electrocardiogram signal, the hydration signal, the respiration signal or the activity signal to look up a value in a previously existing array. In some embodiments, combining comprises at least one of adding, subtracting, multiplying, scaling or dividing the at least two of the electrocardiogram signal, the hydration signal, the respiration signal or the activity signal. In some embodiments, the at least two of the electrocardiogram signal, the hydration signal, the respiration signal, or the activity signal can be combined with at least one of a weighted combination, a tiered combination or a logic gated combination, a time weighted combination or a rate of change.

In many embodiments, the processor system determines a flag status in response to the at least two of the electrocardiogram signal, the hydration signal, the respiration signal or the activity signal. The processor system determines the flag status in response to a change in the at least two of the electrocardiogram signal, the hydration signal, the respiration signal or the activity signal. In some embodiments, the processor system affects the circuitry to make additional signal measurements of the patient in response to the flag status.

In many embodiments, the processor system combines the at least two of the electrocardiogram signal, the hydration signal, the respiration signal or the activity signal in response to a time of day.

In many embodiments, the at least two of the electrocardiogram signal, the hydration signal, the respiration signal or the activity signal comprise at least one of a derived signal, a time averaged signal, a filtered signal or a raw signal.

In many embodiments, the processor determines baseline values of the patient for the at least two of the electrocardiogram signal, the hydration signal, the respiration signal or the activity signal. The at least two of the electrocardiogram signal, the hydration signal, the respiration signal or the activity signal signals may comprise changes from the baseline values.

In many embodiments, the at least two of the electrocardiogram signal, the hydration signal, the respiration signal or the activity signal comprise differences from baseline values of a patient population. The impending decompensation is detected in response to the differences from the baseline value of the patient population.

In many embodiments, the hydration signal comprises an impedance signal and the activity signal comprise an accelerometer signal.

In many embodiments, the activity signal may comprise an accelerometer signal to determine a posture of the patient. In specific embodiments, the accelerometer signal may comprise a three dimensional inclination signal to determine a three dimensional orientation of the patient.

In many embodiments, the processor system combines a temperature signal with the at least two of the electrocardiogram signal, the hydration signal, the respiration signal or the activity signal to detect the impending cardiac decompensation.

In many embodiments, the processor transmits the at least two of the electrocardiogram signal, the hydration signal, the respiration signal or the activity signal to a remote site where the at least two of the electrocardiogram signal, the hydration signal, the respiration signal or the activity signal are combined to detect the impending cardiac decompensation.

In many embodiments, instructions are transmitted from a remote site to a processor supported with the patient. The

6

processor combines at least two of the electrocardiogram signal, the hydration signal, the respiration signal or the activity signal in response to the instructions to detect the impending cardiac decompensation

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A shows a patient and a monitoring system comprising an adherent device, according to embodiments of the present invention;

FIG. 1B shows a bottom view of the adherent device as in FIG. 1A comprising an adherent patch;

FIG. 1C shows a top view of the adherent patch, as in FIG. 1B;

FIG. 1D shows a printed circuit boards and electronic components over the adherent patch, as in FIG. 1C;

FIG. 1D-1 shows an equivalent circuit that can be used to determine optimal frequencies for determining patient hydration, according to embodiments of the present invention;

FIG. 1E shows batteries positioned over the printed circuit board and electronic components as in FIG. 1D;

FIG. 1F shows a top view of an electronics housing and a breathable cover over the batteries, electronic components and printed circuit board as in FIG. 1E;

FIG. 1G shows a side view of the adherent device as in FIGS. 1A to 1F;

FIG. 1H shown a bottom isometric view of the adherent device as in FIGS. 1A to 1G;

FIG. 2A shows a method of predicting an impending cardiac decompensation, according to embodiments of the present invention; and

FIGS. 3A and 3B show clinical data measured with an adherent patch device.

DETAILED DESCRIPTION OF THE INVENTION

Embodiments of the present invention provide systems and methods for the detection of an impending cardiac decompensation. In many embodiments, the impending decompensation can be detected early enough to avoid, or at least delay, the impending decompensation, such that patient trauma and/or expensive ICU care can be avoided. Although embodiments make specific reference to monitoring impedance and electrocardiogram signals with an adherent patch, the system methods and device described herein may be applicable to many applications in which physiological monitoring is used, for example wireless physiological monitoring with implanted sensors for extended periods. In some embodiments, implanted sensors may be used, for example as described in U.S. Pat. Nos. 6,208,894; 6,315,721; 6,185,452; and U.S. Application No. 60/972,329, entitled "Injectable Device for Physiological Monitoring" filed on Sep. 14, 2007, the same day as the present application with the same assignee, the full disclosures of which are incorporated by reference.

Decompensation is failure of the heart to maintain adequate blood circulation. Although the heart can maintain at least some pumping of blood, the quantity is inadequate to maintain healthy tissues. Several symptoms can result from decompensation including pulmonary congestion, breathlessness, faintness, cardiac palpitation, edema of the extremities, and enlargement of the liver. Cardiac decompensation can result in slow or sudden death. Sudden Cardiac Arrest (hereinafter "SCA"), also referred to as sudden cardiac death, is an abrupt loss of cardiac pumping function that can be caused by a ventricular arrhythmia, for example ventricular tachycardia and/or ventricular fibrillation. Although decom-

pensation and SCA can be related in that patients with decompensation are also at an increased risk for SCA, decompensation is primarily a mechanical dysfunction caused by inadequate blood flow, and SCA is primarily an electrical dysfunction caused by inadequate and/or inappropriate electrical signals of the heart.

FIG. 1A shows a patient P and a monitoring system 10. Patient P comprises a midline M, a first side S1, for example a right side, and a second side S2, for example a left side. Monitoring system 10 comprises an adherent device 100. Adherent device 100 can be adhered to a patient P at many locations, for example thorax T of patient P. In many embodiments, the adherent device may adhere to one side of the patient, from which data from the one side can be collected. Work in relation with embodiments of the present invention suggests that location on a side of the patient can provide comfort for the patient while the device is adhered to the patient.

Monitoring system 10 includes components to transmit data to a remote center 106. Adherent device 100 can communicate wirelessly to an intermediate device 102, for example with a single wireless hop from the adherent device on the patient to the intermediate device. Intermediate device 102 can communicate with remote center 106 in many ways, for example with an internet connection. In many embodiments, monitoring system 10 comprises a distributed processing system with at least one processor on device 100, at least one processor on intermediate device 102, and at least one process at remote center 106, each of which processors is in electronic communication with the other processors. Remote center 106 can be in communication with a health care provider 108A with a communication system 107A, such as the Internet, an intranet, phone lines, wireless and/or satellite phone. Health care provider 108A, for example a family member, can be in communication with patient P with a communication, for example with a two way communication system, as indicated by arrow 109A, for example by cell phone, email, landline. Remote center 106 can be in communication with a health care professional, for example a physician 108B, with a communication system 107B, such as the Internet, an intranet, phone lines, wireless and/or satellite phone. Physician 108B can be in communication with patient P with a communication, for example with a two way communication system, as indicated by arrow 109B, for example by cell phone, email, landline. Remote center 106 can be in communication with an emergency responder 108C, for example a 911 operator and/or paramedic, with a communication system 107C, such as the Internet, an intranet, phone lines, wireless and/or satellite phone. Emergency responder 108C can travel to the patient as indicated by arrow 109C. Thus, in many embodiments, monitoring system 10 comprises a closed loop system in which patient care can be monitored and implemented from the remote center in response to signals from the adherent device.

In many embodiments, the adherent device may continuously monitor physiological parameters, communicate wirelessly with a remote center, and provide alerts when necessary. The system may comprise an adherent patch, which attaches to the patient's thorax and contains sensing electrodes, battery, memory, logic, and wireless communication capabilities. In some embodiments, the patch can communicate with the remote center, via the intermediate device in the patient's home. In the many embodiments, the remote center receives the data and applies the prediction algorithm. When a flag is raised, the center may communicate with the patient, hospital, nurse, and/or physician to allow for therapeutic intervention to prevent decompensation.

The adherent device may be affixed and/or adhered to the body in many ways. For example, with at least one of the following an adhesive tape, a constant-force spring, suspenders around shoulders, a screw-in microneedle electrode, a pre-shaped electronics module to shape fabric to a thorax, a pinch onto roll of skin, or transcutaneous anchoring. Patch and/or device replacement may occur with a keyed patch (e.g. two-part patch), an outline or anatomical mark, a low-adhesive guide (place guide/remove old patch/place new patch/remove guide), or a keyed attachment for chatter reduction. The patch and/or device may comprise an adhesiveless embodiment (e.g. chest strap), and/or a low-irritation adhesive model for sensitive skin. The adherent patch and/or device can comprise many shapes, for example at least one of a dogbone, an hourglass, an oblong, a circular or an oval shape.

In many embodiments, the adherent device may comprise a reusable electronics module with replaceable patches (the module collects cumulative data for approximately 90 days) and/or the entire adherent component (electronics+patch) may be disposable. In a completely disposable embodiment, a "baton" mechanism may be used for data transfer and retention, for example baton transfer may include baseline information. In some embodiments, the device may have a rechargeable module, and may use dual battery and/or electronics modules, wherein one module 101A can be recharged using a charging station 103 while the other module 101B is placed on the adherent device. In some embodiments, the intermediate device 102 may comprise the charging module, data transfer, storage and/or transmission, such that one of the electronics modules can be placed in the intermediate device for charging and/or data transfer while the other electronics module is worn by the patient.

In many embodiments, the system can perform the following functions: initiation, programming, measuring, storing, analyzing, communicating, predicting, and displaying. The adherent device may contain a subset of the following physiological sensors: bioimpedance, respiration, respiration rate variability, heart rate (average, minimum, maximum), heart rhythm, HRV, HRT, heart sounds (e.g. S3), respiratory sounds, blood pressure, activity, posture, wake/sleep, orthopnea, temperature/heat flux, and weight. The activity sensor may be one of the following: ball switch, accelerometer, minute ventilation, HR, bioimpedance noise, skin temperature/heat flux, BP, muscle noise, posture.

In many embodiments, the patch wirelessly communicates with a remote center. In some embodiments, the communication may occur directly (via a cellular or Wi-Fi network), or indirectly through intermediate device 102. Intermediate device 102 may consist of multiple devices which communicate wired or wirelessly to relay data to remote center 106.

FIG. 1B shows a bottom view of adherent device 100 as in FIG. 1A comprising an adherent patch 110. Adherent patch 110 comprises a first side, or a lower side 110A, that is oriented toward the skin of the patient when placed on the patient. In many embodiments, adherent patch 110 comprises a tape 110T which is a material, preferably breathable, with an adhesive 116A. Patient side 110A comprises adhesive 116A to adhere the patch 110 and adherent device 100 to patient P. Electrodes 112A, 112B, 112C and 112D are affixed to adherent patch 110. In many embodiments, at least four electrodes are attached to the patch, for example six electrodes. In some embodiments the patch comprises at least two electrodes, for example two electrodes to measure an electrocardiogram (ECG) of the patient. Gel 114A, gel 114B, gel 114C and gel 114D can each be positioned over electrodes 112A, 112B, 112C and 112D, respectively, to provide elec-

trical conductivity between the electrodes and the skin of the patient. In many embodiments, the electrodes can be affixed to the patch 110, for example with known methods and structures such as rivets, adhesive, stitches, etc. In many embodiments, patch 110 comprises a breathable material to permit air and/or vapor to flow to and from the surface of the skin.

FIG. 1C shows a top view of the adherent patch 100, as in FIG. 1B. Adherent patch 100 comprises a second side, or upper side 110B. In many embodiments, electrodes 110A, 110B, 110C and 110D extend from lower side 110A through the adherent patch to upper side 110B. In some embodiments, an adhesive 116B can be applied to upper side 110B to adhere structures, for example, a cover, to the patch such that the patch can support the electronics and other structures when the patch is adhered to the patient. The printed circuit board (PCB) comprise completely flex PCB, rigid PCB combined flex PCB and/or rigid PCB boards connected by cable.

FIG. 1D shows a printed circuit boards and electronic components over adherent patch 110, as in FIG. 1C. A printed circuit board (PCB), for example flex PCB 120, can be positioned above 110B of patch 110. Flex PCB 120 can include traces that extends to connectors 122A, 122B, 122C and 122D on the flex PCB. Connectors 122A, 122B, 122C and 122D can be positioned on flex PCB 120 in alignment with electrodes 112A, 112B, 112C and 112D so as to electrically couple the flex PCB with the electrodes. In some embodiments, connectors 122A, 122B, 122C and 122D may comprise insulated wires or a flex circuit that provide strain relief between the PCB and the electrodes. In some embodiments, additional PCB's for example PCB 120A, 120B, 120C and 120D be connected to flex PCB 120. Electronic components 130 can be connected to flex PCB 120 and/or mounted thereon. In some embodiments, electronic components 130 can be mounted on the additional PCB's.

Electronic components 130 comprise components to take physiologic measurements, transmit data to remote center 106 and receive commands from remote center 106. In many embodiments, electronics components 130 may comprise known low power circuitry, for example complementary metal oxide semiconductor (CMOS) circuitry components. Electronics components 130 comprise an activity sensor and activity circuitry 134, impedance circuitry 136 and electrocardiogram circuitry, for example ECG circuitry 136. In some embodiments, electronics circuitry 130 may comprise a microphone and microphone circuitry 142 to detect an audio signal from within the patient, and the audio signal may comprise a heart sound and/or a respiratory sound, for example an S3 heart sound and a respiratory sound with rales and/or crackles. Electronics circuitry 130 may comprise a temperature sensor, for example a thermistor, and temperature sensor circuitry 144 to measure a temperature of the patient, for example a temperature of a skin of the patient. Electronics circuitry may comprise a heat flux sensor and heat flux sensor circuitry to measure a skin heat flow of a patient.

Work in relation to embodiments of the present invention suggests that skin temperature may effect impedance and/or hydration measurements, and that skin temperature measurements may be used to correct impedance and/or hydration measurements. In some embodiments, increase in skin temperature can be associated with increased vaso-dilation near the skin surface, such that measured impedance measurement decreased, even through the hydration of the patient in deeper tissues under the skin remains substantially unchanged. Thus, use of the temperature sensor can allow for correction of the hydration signals to more accurately assess the hydration, for example extra cellular hydration, of deeper tissues of the patient, for example deeper tissues in the thorax.

Electronics circuitry 130 may comprise a processor 146. Processor 146 comprises a tangible medium, for example read only memory (ROM), electrically erasable programmable read only memory (EEPROM) and/or random access memory (RAM). Electronic circuitry 130 may comprise real time clock and frequency generator circuitry 148. In some embodiments, processor 136 may comprise the frequency generator and real time clock. The processor can be configured to control a collection and transmission of data from the impedance circuitry electrocardiogram circuitry and the accelerometer. In many embodiments, device 100 comprise a distributed processor system, for example with multiple processors on device 100.

In many embodiments, electronics components 130 comprise wireless communications circuitry 132 to communicate with remote center 106. The wireless communication circuitry can be coupled to the impedance circuitry, the electrocardiogram circuitry and the accelerometer to transmit to a remote center with a communication protocol at least one of the hydration signal, the electrocardiogram signal or the accelerometer signal. In specific embodiments, wireless communication circuitry is configured to transmit the hydration signal, the electrocardiogram signal and the accelerometer signal to the remote center with a single wireless hop, for example from wireless communication circuitry 132 to intermediate device 102. The communication protocol comprises at least one of Bluetooth, Zigbee, WiFi, WiMax, IR, amplitude modulation or frequency modulation. In many embodiments, the communications protocol comprises a two way protocol such that the remote center is capable of issuing commands to control data collection.

In some embodiments, intermediate device 102 comprises a data collection system to collect and store data from the wireless transmitter. The data collection system can be configured to communicate periodically with the remote center. In many embodiments, the data collection system can transmit data in response to commands from remote center 106 and/or in response to commands from the adherent device.

Activity sensor and activity circuitry 134 can comprise many known activity sensors and circuitry. In many embodiments, the accelerometer comprises at least one of a piezoelectric accelerometer, capacitive accelerometer or electro-mechanical accelerometer. The accelerometer may comprise a 3-axis accelerometer to measure at least one of an inclination, a position, an orientation or acceleration of the patient in three dimensions. Work in relation to embodiments of the present invention suggests that three dimensional orientation of the patient and associated positions, for example sitting, standing, lying down, can be very useful when combined with data from other sensors, for example ECG data and/or hydration data.

Impedance circuitry 136 can generate both hydration data and respiration data. In many embodiments, impedance circuitry 136 is electrically connected to electrodes 112A, 112B, 112C and 112D such that electrodes 112A and 112D comprise outer electrodes that are driven with a current, or force electrodes. The current delivered between electrodes 112A and 112D generates a measurable voltage between electrodes 112B and 112C, such that electrodes 112B and 112C comprise inner electrodes, or sense electrodes that measure the voltage in response to the current from the force electrodes. The voltage measured by the sense electrodes can be used to determine the hydration of the patient.

FIG. 1D-1 shows an equivalent circuit 152 that can be used to determine optimal frequencies for measuring patient hydration. Work in relation to embodiments of the present invention indicates that the frequency of the current and/or

voltage at the force electrodes can be selected so as to provide impedance signals related to the extracellular and/or intracellular hydration of the patient tissue. Equivalent circuit **152** comprises an intracellular resistance **156**, or $R(ICW)$ in series with a capacitor **154**, and an extracellular resistance **158**, or $R(ECW)$. Extracellular resistance **158** is in parallel with intracellular resistance **156** and capacitor **154** related to capacitance of cell membranes. In many embodiments, impedances can be measured and provide useful information over a wide range of frequencies, for example from about 0.5 kHz to about 200 KHz. Work in relation to embodiments of the present invention suggests that extracellular resistance **158** can be significantly related extracellular fluid and to cardiac decompensation, and that extracellular resistance **158** and extracellular fluid can be effectively measured with frequencies in a range from about 0.5 kHz to about 20 kHz, for example from about 1 kHz to about 10 kHz. In some embodiments, a single frequency can be used to determine the extracellular resistance and/or fluid. As sample frequencies increase from about 10 kHz to about 20 kHz, capacitance related to cell membranes decrease the impedance, such that the intracellular fluid contributes to the impedance and/or hydration measurements. Thus, many embodiments of the present invention employ measure hydration with frequencies from about 0.5 kHz to about 20 kHz to determine patient hydration.

In many embodiments, impedance circuitry **136** can be configured to determine respiration of the patient. In specific embodiments, the impedance circuitry can measure the hydration at 25 Hz intervals, for example at 25 Hz intervals using impedance measurements with a frequency from about 0.5 kHz to about 20 kHz.

ECG circuitry **138** can generate electrocardiogram signals and data from electrodes **112A**, **112B**, **112C** and **112D**. In some embodiments, ECG circuitry **138** is connected to inner electrodes **12B** and **122C**, which may comprise sense electrodes of the impedance circuitry as described above. In some embodiments, the inner electrodes may be positioned near the outer electrodes to increase the voltage of the ECG signal measured by ECG circuitry **138**. In some embodiments, the ECG circuitry can share components with the impedance circuitry.

FIG. 1E shows batteries **150** positioned over the flex printed circuit board and electronic components as in FIG. 1D. Batteries **150** may comprise rechargeable batteries that can be removed and/or recharged. In some embodiments, batteries **150** can be removed from the adherent patch and recharged and/or replaced.

FIG. 1F shows a top view of a cover **162** over the batteries, electronic components and flex printed circuit board as in FIG. 1E. In many embodiments, an electronics housing **160** may be disposed under cover **162** to protect the electronic components, and in some embodiments electronics housing **160** may comprise an encapsulant over the electronic components and PCB. In many embodiments, electronics housing **160** may comprise a water proof material, for example a sealant adhesive such as epoxy or silicone coated over the electronics components and/or PCB. In some embodiments, electronics housing **160** may comprise metal and/or plastic, which may be potted with silicone, epoxy, etc.

Cover **162** may comprise many known biocompatible cover, casing and/or housing materials, such as elastomers, for example silicone. The elastomer may be fenestrated to improve breathability. In some embodiments, cover **162** may comprise many known breathable materials, for example polyester or polyamide fabric. The breathable fabric may be coated to make it water resistant, waterproof, and/or to aid in

wicking moisture away from the patch. The breathable fabric may be coated in order to make the outside hydrophobic and the inside hydrophilic.

FIG. 1G shows a side view of adherent device **100** as in FIGS. 1A to 1F. Adherent device **100** comprises a maximum dimension, for example a length **170** from about 4 to 10 inches (from about 100 mm to about 250 mm), for example from about 6 to 8 inches (from about 150 mm to about 200 mm). In some embodiments, length **170** may be no more than about 6 inches (no more than about 150 mm). Adherent device **100** comprises a thickness **172**. Thickness **172** may comprise a maximum thickness along a profile of the device. Thickness **172** can be from about 0.2 inches to about 0.4 inches (from about 5 mm to about 10 mm), for example about 0.3 inches (about 7.5 mm).

FIG. 1H shown a bottom isometric view of adherent device **100** as in FIGS. 1A to 1G. Adherent device **100** comprises a width **174**, for example a maximum width along a width profile of adherent device **100**. Width **174** can be from about 2 to about 4 inches (from about 50 mm to 100 mm), for example about 3 inches (about 75 mm).

FIG. 2A shows a method **200** of predicting an impending cardiac decompensation. A step **205** measures an ECG signal. The ECG signal may comprise a differential signal measured with at least two electrodes and may be measured in many known ways. A step **210** measures an hydration signal. The hydration signal may comprise an impedance signal, for example a four pole impedance signal, and may be measured in many known ways. A step **215** measures a respiration signal. The respiration signal may comprise an impedance signal, and may be measured in many known ways. A step **220** measures an activity signal. The activity signal may be measured in many known ways and may comprise a three dimensional accelerometer signal to determine a position of the patient, for example from a three dimensional accelerometer signal. A step **225** measures a temperature signal. The temperature signal may be measured in many ways, for example with a thermistor, a thermocouple, and known temperature measurement devices. A step **230** records a time of day of the signals, for example a local time of day such as morning, afternoon, evening, and/or nighttime.

A step **235** processes the signals. The signals may be processed in many known ways, for example to generate at least one of a derived signal, a time averaged signal, a filtered signal. In some embodiments, the signals may comprise raw signals. The ECG signal may comprise at least one of a heart rate signal, a heart rate variability signal, an average heart rate signal, a maximum heart rate signal or a minimum heart rate signal. The hydration signal may comprise an impedance measurement signal. The activity signal may comprise at least one of an accelerometer signal, a position signal indicating the orientation of the patient, such as standing, lying, or sitting. The respiration signal may comprise a least one of a respiration rate, a maximum respiration rate, a minimum respiration rate, an average respiration rate or respiration rate variability. The temperature may comprise an average temperature or a peak temperature.

A step **240** compares the signals with baseline values. In many embodiments, the baseline values may comprise measurements from the same patient at an earlier time. In some embodiments, the baseline values comprise values for a patient population. In some embodiments, the baseline values for a patient population may comprise empirical data from a suitable patient population size, for example at least about 144 patients, depending on the number of variables measured,

statistical confidence and power used. The measured signals may comprise changes and/or deviations from the baseline values.

A step 245 transmits the signals. In many embodiments, the measurement signals, which may comprise derived and/or processed measurement signals, are transmitted to the remote site for comparison. In some embodiments, the signals may be transmitted to a processor supported with the patient for comparison.

A step 250 combines at least two of the ECG signal, the hydration signal, the respiration signal, the activity signal and the temperature signal to detect the impending decompensation. In many embodiments, at least three of the signals are combined. In some embodiments, at least four signals comprising ECG signal, the hydration signal, the respiration signal and the activity signal are combined to detect the impending decompensation. In specific embodiments, at least four signals comprising the ECG signal, the hydration signal, the respiration signal, the activity signal and the temperature signal are combined to detect the impending decompensation.

The signals can be combined in many ways. In some embodiments, the signals can be used simultaneously to determine the impending cardiac decompensation.

In some embodiments, the signals can be combined by using the at least two of the electrocardiogram signal, the hydration signal, the respiration signal or the activity signal to look up a value in a previously existing array.

TABLE 1

Lookup Table for ECG and Hydration Signals			
Heart Rate/Hydration	0-49 bpm	50-69 bpm	70-90 bpm
>60 Ohms	N	N	Y
41-59 Ohms	N	Y	Y
0-40 Ohms	Y	Y	Y

Table 1 shows combination of the electrocardiogram signal with the hydration signal to look up a value in a pre-existing array. For example at a heart rate of 89 bpm and a hydration of 35 Ohms, the value in the table may comprise Y. In specific embodiments, the values of the look up table can be determined in response to empirical data measured for a patient population of at least about 100 patients, for example measurements on about 1000 to 10,000 patients.

In some embodiments, the table may comprise a three or more dimensional look up table.

In some embodiments, the signals may be combined with at least one of adding, subtracting, multiplying, scaling or dividing the at least two of the electrocardiogram signal, the hydration signal, the respiration signal or the activity signal. In specific embodiments, the measurement signals can be combined with positive and or negative coefficients determined in response to empirical data measured for a patient population of at least about 100 patients, for example data on about 1000 to 10,000 patients.

In some embodiments, a weighted combination may combine at least 3 measurement signals to generate an output value according to a formula of the general form

$$\text{OUTPUT} = aX + bY + cZ$$

where a, b and c comprise positive or negative coefficients determined from empirical data and X, Y and Z comprise measured signals for the patient, for example at least three of the electrocardiogram signal, the hydration signal, the respiration signal or the activity signal. While three coefficients

and three variables are shown, the data may be combined with multiplication and/or division. One or more of the variables may be the inverse of a measured variable.

In some embodiments, the ECG signal comprises a heart rate signal that can be divided by the activity signal. Work in relation to embodiments of the present invention suggest that an increase in heart rate with a decrease in activity can indicate an impending decompensation. The signals can be combined to generate an output value with an equation of the general form

$$\text{OUTPUT} = aX/Y + bZ$$

where X comprise a heart rate signal, Y comprises a hydration rate signal and Z comprises a respiration signal, with each of the coefficients determined in response to empirical data as described above.

In some embodiments, the data may be combined with a tiered combination. While many tiered combinations can be used a tiered combination with three measurement signals can be expressed as

$$\text{OUTPUT} = (\Delta X) + (\Delta Y) + (\Delta Z)$$

where (ΔX) , (ΔY) , (ΔZ) may comprise change in heart rate signal from baseline, change in hydration signal from baseline and change in respiration signal from baseline, and each may have a value of zero or one, based on the values of the signals. For example if the heart rate increase by 10%, (ΔX) can be assigned a value of 1. If hydration increases by 5%, (ΔY) can be assigned a value of 1. If activity decreases below 10% of a baseline value (ΔZ) can be assigned a value of 1. When the output signal is three, a flag may be set to trigger an alarm.

In some embodiments, the data may be combined with a logic gated combination. While many logic gated combinations can be used a logic gated combination with three measurement signals can be expressed as

$$\text{OUTPUT} = (\Delta X) \text{AND} (\Delta Y) \text{AND} (\Delta Z)$$

where (ΔX) , (ΔY) , (ΔZ) may comprise change in heart rate signal from baseline, change in hydration signal from baseline and change in respiration signal from baseline, and each may have a value of zero or one, based on the values of the signals. For example if the heart rate increase by 10%, (ΔX) can be assigned a value of 1. If hydration increases by 5%, (ΔY) can be assigned a value of 1. If activity decreases below 10% of a baseline value (ΔZ) can be assigned a value of 1. When each of (ΔX) , (ΔY) , (ΔZ) is one, the output signal is one, and a flag may be set to trigger an alarm. If any one of (ΔX) , (ΔY) or (ΔZ) is zero, the output signal is zero and a flag may be set so as not to trigger an alarm. While a specific example with AND gates has been shown the data can be combined in many ways with known gates for example NAND, NOR, OR, NOT, XOR, XNOR gates. In some embodiments, the gated logic may be embodied in a truth table.

A step 255 sets a flag. The flag can be set in response to the output of the combined signals. In some embodiments, the flag may comprise a binary parameter in which a value of zero does not triggers an alarm and a value of one triggers an alarm.

A step 260 communicates with the patient and/or a health care provider. In some embodiments, the remote site may contact the patient to determine if he or she is okay and communicate the impending decompensation such that the patient can receive needed medical care. In some embodiments, the remote site contacts the health care provider to

warn the provider of the impending decompensation and the need for the patient to receive medical care.

A step 265 collects additional measurements. Additional measurements may comprise additional measurements with the at least two signals, for example with greater sampling rates and or frequency of the measurements. Additional measurements may comprise measurements with a additional sensors, for example an onboard microphone to detect at least one of rales, S1 heart sounds, S2 heart sounds, S3 heart sounds, or arrhythmias. In some embodiments, the additional measurements, for example sounds, can be transmitted to the health care provider to diagnose the patient in real time.

The processor system, as described above, can be configured to perform the method 200, including many of the steps described above. It should be appreciated that the specific steps illustrated in FIG. 2A provide a particular method of predicting an impending cardiac decompensation, according to an embodiment of the present invention. Other sequences of steps may also be performed according to alternative embodiments. For example, alternative embodiments of the present invention may perform the steps outlined above in a different order. Moreover, the individual steps illustrated in FIG. 2A may include multiple sub-steps that may be performed in various sequences as appropriate to the individual step. Furthermore, additional steps may be added or removed depending on the particular applications. One of ordinary skill in the art would recognize many variations, modifications, and alternatives.

Experimental Clinical Study

The protocol below has been used to measure signals from actual patients with an adherent device. These data show that an adherent patch as described above can be continuously adhered for at least one week. These data also show that 90 day continuous in home monitoring can be achieved with a set of 13 patches in which one of the patches is replaced each week. The clinical testing device used an adherent device with modifications, as described more fully below and referred to as the MS system (multi-sensor). Although the clinical device did not include wireless circuitry and processor circuitry supported with the patch adhered to the skin of the patient, these data do show that such a device, as described above, can be made by one of ordinary skill in the art based on the teachings described herein. Additional empirical studies can be conducted on a suitable number of patients.

MS Clinical System Description

The MS clinical system includes many of the structure components described above. There is a flexible connection between the electrodes and the flex PCB, for example wires or polyurethane with silver ink. The cover can stretch with the breathable tape on both the clinical device and the above described wireless device. There is generally a gap between the flex PCB and breathable tape in both clinical and above described wireless devices. The tested device used weights to at least partially simulate the weight of wireless and processor circuitry. The adherent device of the MS clinical system comprises four electrodes to measure bioimpedance and ECG signals and a 3-axis accelerometer, as described above. Bioimpedance signals were used to determine patient respiration and patient hydration, and accelerometer signals were used to determine patient activity and posture. The MS clinical adherent patch device comprising the sensors and at least some sensor circuitry were connected to a processor to record data. The processor was connected to the tested adherent device with wires and supported away from the tested adherent patch device, for example around the patient's waist. Data were collected at regular intervals and uploaded to a remote site, as described above.

Clinical testing of the MS clinical system shows the effectiveness of the structures for continuous adherence of at least one week and data collection, and that patches can be successfully removed and replaced by the patient for in-home monitoring. This effectiveness has been shown without requiring fully functional electronics circuitry such as a battery, wireless circuitry and process circuitry on the adherent device. For example, the MS system includes an insert with about 20 g of additional weight. Although an insert with a 20 gram weight was used for the MS clinical device, greater amounts of weight and circuitry can be used, for example about 30-50 g. The patch device may be modified to accommodate additional weight, for example by increasing the size of the adherent surface. The shape of the MS clinical patch is generally elongate, similar to the elongate shape shown above.

Study Design and Rationale

The MS System is used in a clinical study of heart failure patients to gather data that can be used to develop an algorithm for diagnosing and predicting impending heart failure decompensation events. Events typically manifest as heart failure-related hospitalization, emergency room or urgent care visits leading to a change in oral or IV diuretic treatment.

The purpose of the clinical study is to correlate physiological signals recorded by the system to clinical events of acute heart failure decompensation (AHFD). Signals from the patch can be weighted and combined to determine an index that associates physiologic parameters to impending events of decompensation. Patients who have been classified as New York Heart Association class III and IV within the last 12 months and have had a recent AHFD event can be enrolled into the study and are monitored with the MS system for approximately 90 days.

AHFD events are defined as any of the following:

1) Any heart failure related ER, Urgent Care, in-office visit or hospitalization requiring administration of IV diuretics, administration of IV inotropes, or ultrafiltration for fluid removal.

2) A change in diuretic, defined as a change in diuretic directed by the health care provider occurring inside a hospital, emergency room, or urgent care setting (i.e. no patient self-directed changes to medications not approved by a health care provider would be included), that satisfies one or more of the following: a) a change in the type of diuretic the patient is taking, b) a dose increase of an existing diuretic, or c) the addition of another diuretic.

3) A heart failure decompensation event for which death is the outcome.

Patients enrolled in the study were asked to replace the patch weekly. The study can enroll at least about 550 patients. The patient was provided with a kit comprising 13 patches for replacement. The patches were placed on alternating left and right sides of the patient's thorax, as described above, to minimize progressive irritation.

The data collected in the study can be used to develop an algorithm to at least one of detect, diagnose or predict an impending cardiac decompensation. The algorithm can be implemented on a processor system as described above. Known methods can be used to analyze the data, for example splitting the patients into two groups, one to develop parameters for the algorithm and a second group to test the algorithm developed with the first group. In many embodiments, the signal of the algorithm may comprise a simple binary output for impending cardiac decompensation of the patient. The logic output, yes or no, can be determined in response to patient data combined as described above. The logic output may comprise a signal, such as a binary Y or N signal.

The developed algorithm can be evaluated with composite sensitivity and false positive patient signal status rates. The sensitivity may be defined as the percent of true positive events out of all condition present events, and the false positive patient status signal status rate can be defined as the number of false positive patient status signals per patient-years of follow up. For example, the sensitivity can be at least 50%, for example at least 60%, at least 70%, or even at least 80%. The false positive patient signal status rate may be limited to no more than about 1.1 false positive patient status signals per patient year, for example no more than about 1.0 false positive patient status signals per patient year, no more than about 0.9 false positive patient status signals per patient year, and even no more than about 0.8 false positive patient status signals per patient year.

Clinical Results

Clinical data are available for the first 180 patients enrolled in the study.

FIGS. 3A and 3B show clinical data measured with an adherent patch device, in accordance with the above protocol. FIG. 3A shows data from a patient with the MS patch adhered to a first patient, and the data was acquired over the 90 day period with the series of 13 patches. The signals measured included Heart Rate (beats per minute), Heart Rate Variability (ms), Respiratory Rate (breaths per minute), Activity (m-G's) and Body Fluid (Ohms). FIG. 3B shows data from a second patient similar to FIG. 3A.

Of the 180 patients who have completed the study with the MS adherent patch, as described above, all patches in all patients adhered continuously without patch failure. In all patients, the first patch adhered continuously for the first week. With the exception of a handful of patient deaths and early withdrawals that were unrelated to device failure, all patients reached the end of 90-day follow-up period having used 13 weekly patches without incident. None of the 180 patients showed skin irritation or damage that required withdrawal from the study.

The above data show that the wireless adherent patch device can be constructed for in home wireless patient monitoring for an extended period of at least 90 day, in which each patch of a set is continuously adhered to a patient for at least one week and each patch is configured to support the measurement circuitry, the processor, the wireless communication circuitry and the battery with the skin of the patient.

While the exemplary embodiments have been described in some detail, by way of example and for clarity of understanding, those of skill in the art will recognize that a variety of modifications, adaptations, and changes may be employed. Hence, the scope of the present invention should be limited solely by the appended claims.

What is claimed is:

1. A system to detect impending acute cardiac decompensation of a patient, the patient having a skin and an extracellular fluid, the system comprising:

impedance circuitry to measure, a hydration signal of the patient and a respiration signal of the patient, wherein the hydration signal corresponds to a tissue hydration of the patient; and

a processor system comprising a computer readable memory in communication with the impedance circuitry, wherein the computer readable memory of the processor system embodies instructions to combine the hydration signal and the respiration signal to detect the impending acute cardiac decompensation.

2. The system of claim 1 wherein the processor system comprises at least one processor at a location remote from the patient configured to detect impending acute cardiac decompensation.

3. The system of claim 1 wherein the processor system, supported with the patient, receives instructions transmitted from a remote site and combines the hydration signal and the respiration signal in response to the instructions to detect the impending acute cardiac decompensation.

4. The system of claim 1, further comprising circuitry to measure an electrocardiogram signal of the patient, wherein the computer readable memory of the processor system embodies instructions to combine the electrocardiogram signal, the hydration signal, and the respiration signal to detect the impending acute cardiac decompensation.

5. The system of claim 4, further comprising circuitry to measure an activity signal of the patient, wherein the computer readable memory of the processor system embodies instructions to combine the electrocardiogram signal, the hydration signal, the respiration signal and the activity signal to detect the impending acute cardiac decompensation.

6. The system of claim 1 wherein the processor system simultaneously uses the hydration signal and the respiration signal to detect the impending acute cardiac decompensation.

7. The system of claim 1 wherein combining comprises the processor system using the hydration signal and the respiration signal to look up a value in a previously existing array.

8. The system of claim 1 wherein combining comprises at least one of adding, subtracting, multiplying, scaling or dividing the hydration signal and the respiration signal.

9. The system of claim 1 wherein the processor system combines the hydration signal and the respiration signal with at least one of a weighted combination, a tiered combination or a logic gated combination, a time weighted combination or a rate of change.

10. The system of claim 1 wherein the processor system determines a flag status in response to the hydration signal and the respiration signal.

11. The system of claim 8 wherein the processor system determines the flag status in response to a change in the hydration signal and the respiration signal.

12. The system of claim 8 wherein the processor system affects the circuitry to make additional signal measurements of the patient in response to the flag status.

13. The system of claim 1 wherein the processor system combines the hydration signal and the respiration signal in response to a time of day.

14. The system of claim 1 wherein the hydration signal and the respiration signal comprise at least one of a derived signal, a time averaged signal, a filtered signal or a raw signal.

15. The system of claim 1, further comprising an accelerometer to measure an activity signal of the patient, wherein the activity signal is combined with the hydration signal and the respiration signal.

16. The system of claim 1, further comprising circuitry to measure an activity signal of the patient, wherein the activity signal comprises an accelerometer signal to determine a posture of the patient.

17. The system of claim 16 wherein the accelerometer signal comprises a three dimensional inclination signal to determine a three dimensional orientation of the patient.

18. The system of claim 1 wherein the processor transmits the hydration signal and the respiration signal to a remote site where the hydration signal and the respiration signal are combined to detect the impending acute cardiac decompensation.

19

19. The system of claim 1 wherein the processor system comprises a remote processor located at a site remote from the patient and a processor coupled to a support configured to adhere to the skin of the patient and wherein the remote processor is configured to transmit instructions from the site remote from the patient to the processor coupled to the support, and wherein the processor coupled to the support is configured to combine the hydration signal and the respiration signal in response to the instructions to detect the impending acute cardiac decompensation.

20. The system of claim 1 wherein the circuitry comprises circuitry to measure a skin temperature signal of the patient and wherein the computer readable memory of the processor system embodies instructions to correct the hydration signal such that the hydration signal remains substantially unchanged when the measured impedance decreases and the skin temperature increases.

21. The system of claim 1 wherein the patient exhibits heart failure corresponding to a New York Heart Association classification of class III and wherein the computer readable memory embodies instructions to detect the impending acute cardiac decompensation with a sensitivity of at least about 50% and a false positive patient status signal rate of no more than about 1.1 false positive patient status signals per patient year.

22. The system of claim 1 wherein the hydration signal of the patient and the respiration signal of the patient are based on impedance measurements made at a single frequency within a range from about 0.5 kHz to about 20 kHz to determine a tissue impedance.

23. The system of claim 1 wherein the hydration signal of the patient and the respiration signal of the patient are based on impedance measurements made at a single frequency within a range from about 0.5 kHz to about 10 kHz to determine a tissue impedance.

24. The system of claim 1 wherein the computer readable memory embodies instructions to determine the change of the hydration signal based on a baseline hydration value of the patient measured at least one week before the hydration signal and instructions to determine the change of the respiration signal based on a baseline respiration value of the patient measured at least one week before the respiration signal.

25. The system of claim 1 wherein the computer readable memory embodies instructions to determine the change of the hydration signal based on a baseline hydration value of the patient measured with a first adherent device at least one week before the hydration signal measured with a second adherent device and instructions to determine the change of the respiration signal based on a baseline respiration value of the patient measured with the first adherent device at least one week before the respiration signal measured with the second adherent device.

26. A system to predict an impending acute cardiac decompensation of a patient having heart failure, the patient having a skin and extracellular fluid, the system comprising: circuitry to measure an activity signal of the patient, a hydration signal of the patient and a respiration signal of the patient, the circuitry comprising an accelerometer to measure the activity signal of the patient, the circuitry comprising impedance circuitry to measure the hydration signal of the patient and the respiration signal of the patient based on impedance measurements, the imped-

20

ance measurements having a single frequency within a range from about 1 kHz to about 10 kHz such that the hydration signal corresponds to a tissue hydration of the patient; and

a processor system comprising a computer readable memory in communication with the circuitry, wherein the computer readable memory of the processor system embodies instructions to combine the hydration signal and the respiration signal to predict the impending acute cardiac decompensation, wherein the computer readable memory embodies instructions to determine a baseline hydration value of the patient and compare the baseline hydration value to the hydration signal to determine a change of the hydration signal from the baseline hydration value over a 90 day period and instructions to determine a baseline respiration value of the patient and compare the baseline respiration value to the respiration signal over the 90 day period to determine a change of the respiration signal from the baseline respiration value and wherein the processor system embodies instructions to predict the impending acute cardiac decompensation based on the change of the hydration signal and the change of the respiration signal.

27. The system of claim 1, wherein the computer readable memory embodies instructions to determine a baseline hydration value of the patient and compare the baseline hydration value to the hydration signal to determine a change of the hydration signal from the baseline hydration value and instructions to detect the impending acute cardiac decompensation based in part on the change of the hydration signal.

28. A system to detect impending acute cardiac decompensation of a patient, the system comprising:

impedance circuitry to measure a hydration signal of the patient such that the hydration signal corresponds to a tissue hydration of the patient, wherein a respiration signal of the patient is derived from the impedance circuitry; and

a processor system in communication with the impedance circuitry, the processor system comprising a computer readable memory storing instructions to detect the impending acute cardiac decompensation based at least in part on the hydration signal of the patient and the respiration signal of the patient.

29. The system of claim 28, wherein the computer readable memory stores instructions to determine a baseline hydration value of the patient and compare the baseline hydration value to the hydration signal to determine a change of the hydration signal from the baseline hydration value and instructions to detect the impending acute cardiac decompensation based at least in part on the change of the hydration signal.

30. The system of claim 29, wherein the hydration signal is based on impedance measurements having a frequency within a range from about 0.5 kHz to about 20 kHz.

31. The system of claim 28, wherein the computer readable memory stores instructions to determine a baseline respiration value of the patient and compare the baseline respiration value to the respiration signal to determine a change of the respiration signal from the baseline respiration value and instructions to detect the impending acute cardiac decompensation based in part on the change of the respiration signal.

* * * * *

专利名称(译)	多传感器患者监护仪，用于检测即将发生的心脏代偿失调		
公开(公告)号	US8790257	公开(公告)日	2014-07-29
申请号	US12/209279	申请日	2008-09-12
[标]申请(专利权)人(译)	科文迪斯有限公司		
申请(专利权)人(译)	CORVENTIS INC.		
当前申请(专利权)人(译)	CORVENTIS INC.		
[标]发明人	LIBBUS IMAD BLY MARK J JAMES KRISTOFER J MAZAR SCOTT T WANG JERRY S		
发明人	LIBBUS, IMAD BLY, MARK J. JAMES, KRISTOFER J. MAZAR, SCOTT T. WANG, JERRY S.		
IPC分类号	A61B5/053 A61B5/00		
CPC分类号	A61B5/6801 A61B5/6885 G06F19/3431 A61B5/02055 A61B2562/0209 A61B5/0535 A61B2562/164 A61B5/6833 A61B5/4875 A61B5/7275 A61B2560/0412 A61B2562/043 A61B5/02405 A61B5/0816 A61B5/04085 A61B5/0537 A61B5/0404 A61B5/04087 A61B5/0002 A61B5/0452 A61B5/044 G01N2800 /50 A61B5/04012 A61B5/02028 A61B5/1118 A61B5/1116 A61B5/08 A61B5/0006 A61B5/1114 A61B5 /746 A61B5/7264 G06F19/3418 A61B5/0245 A61B5/0008 A61B5/01 A61B5/443 A61B5/6843 A61B2562/0215 G16H40/67 G16H50/30		
代理机构(译)	KILPATRICK TOWNSEND & STOCKTON LLP		
审查员(译)	JACKSON , GARY		
优先权	60/972512 2007-09-14 US 60/972537 2007-09-14 US 61/055666 2008-05-23 US		
其他公开文献	US20090076344A1		
外部链接	Espacenet USPTO		

摘要(译)

检测患者即将发生的心脏代偿失调的系统和方法测量患者的心电图信号，患者的水合信号，患者的呼吸信号或患者的活动信号中的至少两个。将心电图信号，水合信号，呼吸信号或活动信号中的至少两个与算法组合以检测即将发生的心脏代偿失调。

