



US008649839B2

(12) **United States Patent**  
**Chin et al.**

(10) **Patent No.:** **US 8,649,839 B2**  
(45) **Date of Patent:** **Feb. 11, 2014**

(54) **MOTION COMPATIBLE SENSOR FOR  
NON-INVASIVE OPTICAL BLOOD ANALYSIS**

(75) Inventors: **Rodney Chin**, Oakland, CA (US); **Paul  
D Mannheimer**, Danville, CA (US);  
**Ross Flewelling**, Oakland, CA (US)

(73) Assignee: **Covidien LP**, Mansfield, MA (US)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **12/822,898**

(22) Filed: **Jun. 24, 2010**

(65) **Prior Publication Data**

US 2010/0261986 A1 Oct. 14, 2010

**Related U.S. Application Data**

(60) Continuation of application No. 11/827,858, filed on  
Jul. 13, 2007, now abandoned, which is a continuation  
of application No. 10/991,111, filed on Nov. 16, 2004,  
now Pat. No. 7,260,425, which is a continuation of  
application No. 10/080,433, filed on Feb. 21, 2002,  
now Pat. No. 6,845,256, which is a division of  
application No. 09/348,437, filed on Jul. 7, 1999, now  
Pat. No. 6,374,129, which is a division of application  
No. 08/722,443, filed on Oct. 10, 1996, now Pat. No.  
6,018,673.

(51) **Int. Cl.**  
**A61B 5/1455** (2006.01)

(52) **U.S. Cl.**  
USPC ..... **600/324**

(58) **Field of Classification Search**  
USPC ..... 600/310, 323, 336, 340, 476  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

3,403,555 A	10/1968	Versaci et al.
3,536,545 A	10/1970	Traynor et al.
D222,454 S	10/1971	Beeber
3,721,813 A	3/1973	Condon et al.
4,098,772 A	7/1978	Bonk et al.

(Continued)

**FOREIGN PATENT DOCUMENTS**

DE	3405444	8/1985
DE	3516338	11/1986

(Continued)

**OTHER PUBLICATIONS**

Azhar, N., et al.; "Automatic Feedback Control of Oxygen Therapy  
Using Pulse Oximetry," *Annual International Conference of the  
IEEE Engineering in Medicine and Biology Society*, vol. 13, No. 4,  
pp. 1614-1615 (1991).

(Continued)

*Primary Examiner* — Tse Chen


*Assistant Examiner* — Rochelle Reardon

(74) *Attorney, Agent, or Firm* — Fletcher Yoder

(57) **ABSTRACT**

A non-invasive optical sensor which uses the motion signal to  
calculate the physiological characteristic being measured.  
For pulse oximetry, a least squares or a ratio-of-ratios tech-  
nique can be applied to the motion signal itself. This is made  
possible by selecting a site on the patient where variations in  
motion produce signals of two wavelengths which are suffi-  
ciently correlated. In particular, it has been determined that a  
sensor placed on a nail, in particular a thumbnail, exhibits the  
characteristics of having the red and infrared signals corre-  
lated when used for pulse oximetry, and the resulting signals  
correlate to arterial oxygen saturation.

**13 Claims, 10 Drawing Sheets**



(56)

## References Cited

## U.S. PATENT DOCUMENTS

4,120,296 A *	10/1978	Prinz .....	600/503	5,025,791 A	6/1991	Niwa
D250,275 S	11/1978	Bond		RE33,643 E	7/1991	Isaacson et al.
D251,387 S	3/1979	Ramsey et al.		5,028,787 A	7/1991	Rosenthal et al.
D262,488 S	12/1981	Rossmann et al.		5,035,243 A	7/1991	Muz
4,334,544 A	6/1982	Hill et al.		5,040,539 A	8/1991	Schmitt et al.
4,350,165 A	9/1982	Striese		5,041,187 A	8/1991	Hink et al.
4,353,372 A	10/1982	Ayer		5,054,488 A	10/1991	Muz
4,380,240 A	4/1983	Jobsis et al.		5,055,671 A	10/1991	Jones
4,406,289 A	9/1983	Wesseling et al.		5,058,588 A	10/1991	Kaestle
4,510,551 A	4/1985	Brainard, II		5,065,749 A	11/1991	Hasebe et al.
4,586,513 A	5/1986	Hamaguri		5,066,859 A	11/1991	Karkar et al.
4,603,700 A	8/1986	Nichols et al.		5,069,213 A	12/1991	Polczynski
4,621,643 A	11/1986	New, Jr. et al.		5,078,136 A	1/1992	Stone et al.
4,653,498 A	3/1987	New, Jr. et al.		5,086,229 A	2/1992	Rosenthal et al.
4,677,528 A	6/1987	Miniet		5,088,493 A	2/1992	Giannini et al.
4,685,464 A	8/1987	Goldberger et al.		5,090,410 A	2/1992	Saper et al.
4,694,833 A	9/1987	Hamaguri		5,094,239 A	3/1992	Jaeb et al.
4,697,593 A	10/1987	Evans et al.		5,094,240 A	3/1992	Muz
4,700,708 A	10/1987	New, Jr. et al.		5,099,841 A	3/1992	Heinonen et al.
4,714,080 A	12/1987	Edgar, Jr. et al.		5,099,842 A	3/1992	Mannheimer et al.
4,714,341 A	12/1987	Hamaguri et al.		H1039 H	4/1992	Tripp et al.
4,722,120 A	2/1988	Lu		5,101,825 A	4/1992	Gravenstein et al.
4,726,382 A	2/1988	Boehmer et al.		5,104,623 A	4/1992	Miller
4,759,369 A	7/1988	Taylor		5,109,849 A	5/1992	Goodman et al.
4,770,179 A	9/1988	New, Jr. et al.		5,111,817 A	5/1992	Clark et al.
4,773,422 A	9/1988	Isaacson et al.		5,113,861 A	5/1992	Rother
4,776,339 A	10/1988	Schreiber		D326,715 S	6/1992	Schmidt
4,781,195 A	11/1988	Martin		5,125,403 A	6/1992	Culp
4,783,815 A	11/1988	Buttner		5,127,068 A	6/1992	Baer et al.
4,796,636 A	1/1989	Branstetter et al.		5,127,406 A	7/1992	Yamaguchi
4,800,495 A	1/1989	Smith		5,131,391 A	7/1992	Sakai et al.
4,800,885 A	1/1989	Johnson		5,140,989 A	8/1992	Lewis et al.
4,802,486 A	2/1989	Goodman et al.		5,152,296 A	10/1992	Simons
4,805,623 A	2/1989	Jöbsis		5,154,175 A	10/1992	Gunther
4,807,630 A	2/1989	Malinouskas		5,158,082 A	10/1992	Jones
4,807,631 A	2/1989	Hersh et al.		5,170,786 A	12/1992	Thomas et al.
4,819,646 A	4/1989	Cheung et al.		5,188,108 A	2/1993	Secker et al.
4,819,752 A	4/1989	Zelin		5,190,038 A	3/1993	Polson et al.
4,824,242 A	4/1989	Frick et al.		5,193,542 A	3/1993	Missanelli et al.
4,825,872 A	5/1989	Tan et al.		5,193,543 A	3/1993	Yelderman
4,825,879 A	5/1989	Tan et al.		5,203,329 A	4/1993	Takatani et al.
4,830,014 A	5/1989	Goodman et al.		5,209,230 A	5/1993	Swedlow et al.
4,832,484 A	5/1989	Aoyagi et al.		5,213,099 A	5/1993	Tripp et al.
4,846,183 A	7/1989	Martin		5,216,598 A	6/1993	Branstetter et al.
4,848,901 A	7/1989	Hood, Jr.		5,217,012 A	6/1993	Young et al.
4,854,699 A	8/1989	Edgar, Jr.		5,217,013 A	6/1993	Lewis et al.
4,859,056 A	8/1989	Prosser et al.		5,218,207 A	6/1993	Rosenthal
4,859,057 A	8/1989	Taylor et al.		5,218,962 A	6/1993	Mannheimer et al.
4,863,265 A	9/1989	Flower et al.		5,224,478 A	7/1993	Sakai et al.
4,865,038 A	9/1989	Rich et al.		5,226,417 A	7/1993	Swedlow et al.
4,867,557 A	9/1989	Takatani et al.		5,228,440 A	7/1993	Chung et al.
4,869,253 A	9/1989	Craig, Jr. et al.		5,237,994 A	8/1993	Goldberger
4,869,254 A	9/1989	Stone et al.		5,239,185 A	8/1993	Ito et al.
4,880,304 A	11/1989	Jaeb et al.		5,246,002 A	9/1993	Prosser
4,883,055 A	11/1989	Merrick		5,246,003 A	9/1993	DeLonzor
4,883,353 A	11/1989	Hausman et al.		5,247,931 A	9/1993	Norwood
4,890,619 A	1/1990	Hatschek		5,247,932 A	9/1993	Chung et al.
4,892,101 A	1/1990	Cheung et al.		5,249,576 A	10/1993	Goldberger et al.
4,901,238 A	2/1990	Suzuki et al.		5,253,645 A	10/1993	Friedman et al.
4,908,762 A	3/1990	Suzuki et al.		5,253,646 A	10/1993	Delpy et al.
4,911,167 A	3/1990	Corenman et al.		5,259,381 A	11/1993	Cheung et al.
4,913,150 A	4/1990	Cheung et al.		5,259,761 A	11/1993	Schnettler et al.
4,926,867 A	5/1990	Kanda et al.		5,263,244 A	11/1993	Centa et al.
4,927,264 A	5/1990	Shiga et al.		5,266,803 A *	11/1993	Heffelfinger ..... 250/582
4,928,692 A	5/1990	Goodman et al.		5,267,562 A	12/1993	Ukawa et al.
4,934,372 A	6/1990	Corenman et al.		5,267,563 A	12/1993	Swedlow et al.
4,938,218 A	7/1990	Goodman et al.		5,267,566 A	12/1993	Choucair et al.
4,942,877 A	7/1990	Sakai et al.		5,273,036 A	12/1993	Kronberg et al.
4,948,248 A	8/1990	Lehman		5,275,159 A	1/1994	Griebel
4,955,379 A	9/1990	Hall		5,278,627 A	1/1994	Aoyagi et al.
4,960,126 A	10/1990	Conlon et al.		5,279,295 A	1/1994	Martens et al.
4,964,408 A	10/1990	Hink et al.		5,285,783 A	2/1994	Secker
4,971,062 A	11/1990	Hasebe et al.		5,285,784 A	2/1994	Seeker
4,974,591 A	12/1990	Awazu et al.		5,287,853 A	2/1994	Vester et al.
5,007,423 A	4/1991	Branstetter et al.		5,291,884 A	3/1994	Heinemann et al.
				5,297,548 A	3/1994	Pologe
				5,299,120 A	3/1994	Kaestle
				5,299,570 A	4/1994	Hatschek
				5,309,908 A	5/1994	Friedman et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

5,311,865 A	5/1994	Mayeux	5,551,423 A	9/1996	Sugiura
5,313,940 A	5/1994	Fuse et al.	5,551,424 A	9/1996	Morrison et al.
5,323,776 A	6/1994	Blakely et al.	5,553,613 A	9/1996	Parker
5,329,922 A	7/1994	Atlee, III	5,553,614 A	9/1996	Chance
5,337,744 A	8/1994	Branigan	5,553,615 A	9/1996	Carim et al.
5,339,810 A	8/1994	Ivers et al.	5,555,882 A	9/1996	Richardson et al.
5,343,818 A	9/1994	McCarthy et al.	5,558,096 A	9/1996	Palatnik
5,343,869 A	9/1994	Pross et al.	5,560,355 A	10/1996	Merchant et al.
5,348,003 A	9/1994	Caro	5,564,417 A	10/1996	Chance
5,348,004 A	9/1994	Hollub et al.	5,575,284 A	11/1996	Athan et al.
5,348,005 A	9/1994	Merrick et al.	5,575,285 A	11/1996	Takanashi et al.
5,349,519 A	9/1994	Kaestle	5,577,500 A	11/1996	Potratz
5,349,952 A	9/1994	McCarthy et al.	5,582,169 A	12/1996	Oda et al.
5,349,953 A	9/1994	McCarthy et al.	5,584,296 A	12/1996	Cui et al.
5,351,685 A	10/1994	Potratz	5,588,425 A	12/1996	Sackner et al.
5,353,799 A	10/1994	Chance	5,588,427 A	12/1996	Tien
5,355,880 A	10/1994	Thomas et al.	5,590,652 A	1/1997	Inai
5,355,882 A	10/1994	Ukawa et al.	5,595,176 A	1/1997	Yamaura
5,361,758 A	11/1994	Hall et al.	5,596,986 A	1/1997	Goldfarb
5,365,066 A	11/1994	Krueger, Jr. et al.	5,611,337 A	3/1997	Bukta
5,368,025 A	11/1994	Young et al.	5,617,852 A	4/1997	MacGregor
5,368,026 A	11/1994	Swedlow et al.	5,619,992 A	4/1997	Guthrie et al.
5,368,224 A	11/1994	Richardson et al.	5,626,140 A	5/1997	Feldman et al.
5,372,136 A	12/1994	Steuer et al.	5,630,413 A	5/1997	Thomas et al.
5,377,675 A	1/1995	Ruskewicz et al.	5,632,272 A	5/1997	Diab et al.
5,385,143 A	1/1995	Aoyagi	5,632,273 A	5/1997	Suzuki
5,387,122 A	2/1995	Goldberger et al.	5,634,459 A	6/1997	Gardosi
5,390,670 A	2/1995	Centa et al.	5,638,593 A	6/1997	Gerhardt et al.
5,392,777 A	2/1995	Swedlow et al.	5,638,816 A	6/1997	Kiani-Azarbayjany et al.
5,398,680 A	3/1995	Polson et al.	5,638,818 A	6/1997	Diab et al.
5,402,777 A	4/1995	Warring et al.	5,645,060 A	7/1997	Yorkey et al.
5,402,779 A	4/1995	Chen et al.	5,645,440 A	7/1997	Tobler et al.
5,411,023 A	5/1995	Morris, Sr. et al.	5,660,567 A	8/1997	Nierlich et al.
5,411,024 A	5/1995	Thomas et al.	5,662,105 A	9/1997	Tien
5,413,099 A	5/1995	Schmidt et al.	5,662,106 A	9/1997	Swedlow et al.
5,413,100 A	5/1995	Barthelemy et al.	5,664,270 A	9/1997	Bell et al.
5,413,101 A	5/1995	Sugiura	5,666,952 A	9/1997	Fuse et al.
5,413,102 A	5/1995	Schmidt et al.	5,671,529 A	9/1997	Nelson
5,417,207 A	5/1995	Young et al.	5,673,692 A	10/1997	Schulze et al.
5,421,329 A	6/1995	Casciani et al.	5,673,693 A	10/1997	Solenberger
5,425,360 A	6/1995	Nelson	5,676,139 A	10/1997	Goldberger et al.
5,425,362 A	6/1995	Siker et al.	5,676,141 A	10/1997	Hollub
5,427,093 A	6/1995	Ogawa et al.	5,678,544 A	10/1997	DeLonzor et al.
5,429,128 A	7/1995	Cadell et al.	5,680,857 A	10/1997	Pelikan et al.
5,429,129 A	7/1995	Lovejoy et al.	5,685,299 A	11/1997	Diab et al.
5,431,159 A	7/1995	Baker et al.	5,685,301 A	11/1997	Klomhaus
5,431,170 A	7/1995	Mathews	5,687,719 A	11/1997	Sato et al.
5,437,275 A	8/1995	Amundsen et al.	5,687,722 A	11/1997	Tien et al.
5,438,986 A	8/1995	Disch et al.	5,692,503 A	12/1997	Kuenstner
5,448,991 A	9/1995	Polson et al.	5,692,505 A	12/1997	Fouts
5,452,717 A	9/1995	Branigan et al.	5,709,205 A	1/1998	Bukta
5,465,714 A	11/1995	Scheuing	5,713,355 A	2/1998	Richardson et al.
5,469,845 A	11/1995	DeLonzor et al.	5,724,967 A	3/1998	Venkatachalam
RE35,122 E	12/1995	Corenman et al.	5,727,547 A	3/1998	Levinson et al.
5,482,034 A	1/1996	Lewis et al.	5,730,124 A	3/1998	Yamauchi
5,482,036 A	1/1996	Diab et al.	5,731,582 A	3/1998	West
5,485,847 A	1/1996	Baker, Jr.	D393,830 S	4/1998	Tobler et al.
5,490,505 A	2/1996	Diab et al.	5,743,260 A	4/1998	Chung et al.
5,490,523 A	2/1996	Isaacson et al.	5,743,262 A	4/1998	Lepper, Jr. et al.
5,491,299 A	2/1996	Naylor et al.	5,743,263 A	4/1998	Baker, Jr.
5,494,032 A	2/1996	Robinson et al.	5,746,206 A	5/1998	Mannheimer
5,494,043 A	2/1996	O'Sullivan et al.	5,746,697 A	5/1998	Swedlow et al.
5,497,771 A	3/1996	Rosenheimer	5,752,914 A	5/1998	DeLonzor et al.
5,499,627 A	3/1996	Steuer et al.	5,755,226 A	5/1998	Carim et al.
5,503,148 A	4/1996	Pologe et al.	5,758,644 A	6/1998	Diab et al.
5,505,199 A	4/1996	Kim	5,760,910 A	6/1998	Lepper, Jr. et al.
5,507,286 A	4/1996	Solenberger	5,766,125 A	6/1998	Aoyagi et al.
5,511,546 A	4/1996	Hon	5,766,127 A	6/1998	Pologe et al.
5,517,988 A	5/1996	Gerhard	5,769,785 A	6/1998	Diab et al.
5,520,177 A	5/1996	Ogawa et al.	5,772,587 A	6/1998	Gratton et al.
5,521,851 A	5/1996	Wei et al.	5,774,213 A	6/1998	Trebino et al.
5,522,388 A	6/1996	Ishikawa et al.	5,776,058 A	7/1998	Levinson et al.
5,524,617 A	6/1996	Mannheimer	5,776,059 A	7/1998	Kaestle
5,529,064 A	6/1996	Rall et al.	5,779,630 A	7/1998	Fein et al.
5,533,507 A	7/1996	Potratz et al.	5,779,631 A	7/1998	Chance
			5,782,237 A	7/1998	Casciani et al.
			5,782,756 A	7/1998	Mannheimer
			5,782,757 A *	7/1998	Diab et al. .... 600/323
			5,782,758 A	7/1998	Ausec et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

5,786,592 A	7/1998	Hök	6,041,247 A	3/2000	Weckstrom et al.
5,788,634 A	8/1998	Suda et al.	6,044,283 A	3/2000	Fein et al.
5,790,729 A	8/1998	Pologe et al.	6,047,201 A	4/2000	Jackson, III
5,792,052 A	8/1998	Isaacson et al.	6,055,447 A	4/2000	Well
5,795,292 A	8/1998	Lewis et al.	6,061,584 A	5/2000	Lovejoy et al.
5,797,841 A	8/1998	DeLonzor et al.	6,064,898 A	5/2000	Aldrich
5,800,348 A	9/1998	Kaestle	6,064,899 A	5/2000	Fein et al.
5,800,349 A	9/1998	Isaacson et al.	6,067,462 A	5/2000	Diab et al.
5,803,910 A	9/1998	Potratz	6,073,038 A	6/2000	Wang et al.
5,807,246 A	9/1998	Sakaguchi et al.	6,078,829 A	6/2000	Uchida
5,807,247 A	9/1998	Merchant et al.	6,078,833 A	6/2000	Hueber
5,807,248 A	9/1998	Mills	6,081,735 A	6/2000	Diab et al.
5,807,266 A *	9/1998	Itonaga et al. .... 600/499	6,083,157 A	7/2000	Noller
5,810,724 A	9/1998	Gronvall	6,083,172 A	7/2000	Baker, Jr. et al.
5,813,980 A	9/1998	Levinson et al.	6,088,607 A	7/2000	Diab et al.
5,817,008 A	10/1998	Rafert et al.	6,094,592 A	7/2000	Yorkey et al.
5,817,009 A	10/1998	Rosenheimer et al.	6,095,974 A	8/2000	Shemwell et al.
5,818,985 A	10/1998	Merchant et al.	6,104,938 A	8/2000	Huiku et al.
5,820,550 A	10/1998	Polson et al.	6,104,939 A	8/2000	Groner
5,823,950 A	10/1998	Diab et al.	6,112,107 A	8/2000	Hannula
5,823,952 A	10/1998	Levinson et al.	6,113,541 A	9/2000	Dias et al.
5,827,179 A	10/1998	Lichter et al.	6,115,621 A	9/2000	Chin
5,829,439 A	11/1998	Yokosawa et al.	6,122,535 A	9/2000	Kaestle et al.
5,830,135 A	11/1998	Bosque et al.	6,133,994 A	10/2000	Mathews et al.
5,830,136 A	11/1998	DeLonzor et al.	6,135,952 A	10/2000	Coetzee
5,839,439 A	11/1998	Nierlich et al.	6,144,444 A	11/2000	Haworth et al.
5,842,981 A	12/1998	Larsen et al.	6,144,867 A	11/2000	Walker et al.
5,842,982 A	12/1998	Mannheimer	6,144,868 A	11/2000	Parker
5,846,190 A	12/1998	Woehrle	6,149,481 A	11/2000	Wang et al.
5,851,178 A	12/1998	Aronow	6,151,107 A	11/2000	Schöllermann et al.
5,851,179 A	12/1998	Ritson et al.	6,151,516 A	11/2000	Kiani-Azarbayjani et al.
5,853,364 A	12/1998	Baker, Jr. et al.	6,151,518 A	11/2000	Hayashi
5,860,919 A	1/1999	Kiani-Azarbayjany et al.	6,152,754 A	11/2000	Gerhardt et al.
5,879,294 A	3/1999	Anderson et al.	6,154,667 A	11/2000	Miura et al.
5,885,213 A	3/1999	Richardson et al.	6,157,850 A	12/2000	Diab et al.
5,891,022 A	4/1999	Pologe	6,159,147 A	12/2000	Lichter
5,891,025 A	4/1999	Buschmann et al.	6,163,715 A	12/2000	Larsen et al.
5,891,026 A	4/1999	Wang et al.	6,165,005 A	12/2000	Mills et al.
5,902,235 A	5/1999	Lewis et al.	6,173,196 B1	1/2001	Delonzor et al.
5,910,108 A	6/1999	Solenberger	6,178,343 B1	1/2001	Bindzus et al.
5,911,690 A	6/1999	Rall	6,179,159 B1	1/2001	Gurley
5,912,656 A	6/1999	Tham et al.	6,181,958 B1	1/2001	Steuer et al.
5,913,819 A	6/1999	Taylor et al.	6,181,959 B1	1/2001	Schöllermann et al.
5,916,155 A	6/1999	Levinson et al.	6,184,521 B1	2/2001	Coffin, IV et al.
5,919,133 A	7/1999	Tyalar et al.	6,188,470 B1	2/2001	Grace
5,924,979 A	7/1999	Swedlow et al.	6,192,260 B1	2/2001	Chance
5,934,277 A	8/1999	Mortz	6,195,575 B1	2/2001	Levinson
5,934,925 A	8/1999	Tobler et al.	6,198,951 B1	3/2001	Kosuda et al.
5,940,182 A	8/1999	Lepper, Jr. et al.	6,206,830 B1	3/2001	Diab et al.
5,957,840 A	9/1999	Terasawa et al.	6,213,952 B1	4/2001	Finarov et al.
5,961,450 A	10/1999	Merchant et al.	6,217,523 B1	4/2001	Amano et al.
5,961,452 A	10/1999	Chung et al.	6,222,189 B1	4/2001	Misner et al.
5,964,701 A	10/1999	Asada et al.	6,223,064 B1	4/2001	Lynn
5,978,691 A	11/1999	Mills	6,226,539 B1	5/2001	Potratz
5,983,120 A	11/1999	Groner et al.	6,226,540 B1	5/2001	Bernreuter et al.
5,995,855 A	11/1999	Kiani et al.	6,229,856 B1	5/2001	Diab et al.
5,995,856 A	11/1999	Mannheimer et al.	6,230,035 B1	5/2001	Aoyagi et al.
5,995,859 A	11/1999	Takahashi	6,233,470 B1	5/2001	Tsuchiya
5,997,343 A	12/1999	Mills et al.	6,236,871 B1	5/2001	Tsuchiya
5,999,834 A	12/1999	Wang et al.	6,236,872 B1	5/2001	Diab et al.
6,002,952 A	12/1999	Diab et al.	6,240,305 B1	5/2001	Tsuchiya
6,005,658 A	12/1999	Kaluza et al.	6,253,097 B1	6/2001	Aronow et al.
6,006,120 A	12/1999	Levin	6,253,098 B1	6/2001	Walker et al.
6,011,985 A	1/2000	Athan et al.	6,256,523 B1	7/2001	Diab et al.
6,011,986 A	1/2000	Diab et al.	6,256,524 B1	7/2001	Walker et al.
6,014,576 A	1/2000	Raley et al.	6,261,236 B1	7/2001	Grinblatov
6,018,673 A	1/2000	Chin et al.	6,263,221 B1	7/2001	Chance et al.
6,018,674 A	1/2000	Aronow	6,263,222 B1	7/2001	Diab et al.
6,022,321 A	2/2000	Amano et al.	6,263,223 B1	7/2001	Shepherd et al.
6,023,541 A	2/2000	Merchant et al.	6,266,546 B1	7/2001	Steuer et al.
6,026,312 A	2/2000	Shemwell et al.	6,266,547 B1	7/2001	Walker et al.
6,026,314 A	2/2000	Amerov et al.	6,272,363 B1	8/2001	Casciani et al.
6,031,603 A	2/2000	Fine et al.	6,278,522 B1	8/2001	Lepper, Jr. et al.
6,035,223 A	3/2000	Baker, Jr.	6,280,213 B1	8/2001	Tobler et al.
6,036,642 A	3/2000	Diab et al.	6,280,381 B1	8/2001	Malin et al.
			6,285,894 B1	9/2001	Oppelt et al.
			6,285,895 B1	9/2001	Ristolainen et al.
			6,285,896 B1	9/2001	Tobler et al.
			6,298,252 B1	10/2001	Kovach et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

6,308,089	B1	10/2001	Von der Ruhr et al.	6,526,301	B2	2/2003	Larsen et al.
6,321,100	B1	11/2001	Parker	6,541,756	B2	4/2003	Schulz et al.
6,330,468	B1	12/2001	Scharf	6,542,764	B1	4/2003	Al-Ali et al.
6,334,065	B1	12/2001	Al-Ali et al.	6,546,267	B1	4/2003	Sugiura et al.
6,339,715	B1	1/2002	Bahr et al.	6,553,241	B2	4/2003	Mannheimer et al.
6,342,039	B1	1/2002	Lynn	6,553,242	B1	4/2003	Sarussi
6,343,223	B1	1/2002	Chin et al.	6,553,243	B2	4/2003	Gurley
6,343,224	B1	1/2002	Parker	6,554,788	B1	4/2003	Hunley
6,349,228	B1	2/2002	Kiani et al.	6,556,852	B1	4/2003	Schulze et al.
6,351,658	B1	2/2002	Middleman et al.	6,560,470	B1	5/2003	Pologe
6,353,750	B1	3/2002	Kimura	6,564,077	B2	5/2003	Mortara
6,356,774	B1	3/2002	Bernstein et al.	6,564,088	B1	5/2003	Soller et al.
6,360,113	B1	3/2002	Dettling	6,571,113	B1	5/2003	Fein et al.
6,360,114	B1	3/2002	Diab et al.	6,571,114	B1	5/2003	Koike et al.
6,361,501	B1	3/2002	Amano et al.	6,574,491	B2	6/2003	Elghazzawi
6,363,269	B1	3/2002	Hanna et al.	6,580,086	B1	6/2003	Schulz et al.
D455,834	S	4/2002	Donars et al.	6,584,336	B1	6/2003	Ali et al.
6,370,409	B1	4/2002	Chung et al.	6,587,703	B2	7/2003	Cheng et al.
6,371,921	B1	4/2002	Caro	6,587,704	B1	7/2003	Fine et al.
6,374,129	B1	4/2002	Chin et al.	6,589,172	B2	7/2003	Williams et al.
6,377,829	B1	4/2002	Al-Ali et al.	6,591,122	B2	7/2003	Schmitt
6,381,479	B1	4/2002	Norris	6,591,123	B2	7/2003	Fein et al.
6,381,480	B1	4/2002	Stoddard et al.	6,594,511	B2	7/2003	Stone et al.
6,385,471	B1	5/2002	Mortz	6,594,512	B2	7/2003	Huang
6,385,821	B1	5/2002	Modgil et al.	6,594,513	B1	7/2003	Jobsis et al.
6,388,240	B2	5/2002	Schulz et al.	6,597,931	B1	7/2003	Cheng et al.
6,393,310	B1	5/2002	Kuenstner	6,597,933	B2	7/2003	Kiani et al.
6,393,311	B1	5/2002	Edgar, Jr. et al.	6,600,940	B1	7/2003	Fein et al.
6,397,091	B2	5/2002	Diab et al.	6,606,510	B2	8/2003	Swedlow et al.
6,397,092	B1	5/2002	Norris et al.	6,606,511	B1	8/2003	Ali et al.
6,397,093	B1	5/2002	Aldrich	6,606,512	B2	8/2003	Muz et al.
6,400,971	B1	6/2002	Finarov et al.	6,608,562	B1	8/2003	Kimura et al.
6,400,972	B1	6/2002	Fine	6,609,016	B1	8/2003	Lynn
6,400,973	B1	6/2002	Winter	6,615,064	B1	9/2003	Aldrich
6,402,690	B1	6/2002	Rhee et al.	6,615,065	B1	9/2003	Barrett et al.
6,408,198	B1	6/2002	Hanna et al.	6,618,602	B2	9/2003	Levin et al.
6,411,832	B1	6/2002	Guthermann	6,618,614	B1	9/2003	Chance
6,411,833	B1	6/2002	Baker, Jr. et al.	6,622,034	B1	9/2003	Gorski et al.
6,421,549	B1	7/2002	Jacques	6,628,975	B1	9/2003	Fein et al.
6,430,423	B2	8/2002	DeLonzor et al.	6,631,281	B1	10/2003	Kästle
6,430,513	B1	8/2002	Wang et al.	6,632,181	B2	10/2003	Flaherty
6,430,525	B1	8/2002	Weber et al.	6,640,116	B2	10/2003	Diab
6,434,408	B1	8/2002	Heckel et al.	6,643,530	B2	11/2003	Diab et al.
6,438,396	B1	8/2002	Cook	6,643,531	B1	11/2003	Katarow
6,438,399	B1	8/2002	Kurth	6,647,279	B2	11/2003	Pologe
6,449,501	B1	9/2002	Reuss	6,647,280	B2	11/2003	Bahr et al.
6,453,183	B1	9/2002	Walker	6,650,916	B2	11/2003	Cook
6,453,184	B1	9/2002	Hyogo et al.	6,650,917	B2	11/2003	Diab et al.
6,456,862	B2	9/2002	Benni	6,650,918	B2	11/2003	Terry
6,461,305	B1	10/2002	Schnall	6,654,621	B2	11/2003	Palatnik et al.
6,463,310	B1	10/2002	Swedlow et al.	6,654,622	B1	11/2003	Eberhard et al.
6,463,311	B1	10/2002	Diab	6,654,623	B1	11/2003	Kästle
6,466,808	B1	10/2002	Chin et al.	6,654,624	B2	11/2003	Diab et al.
6,466,809	B1	10/2002	Riley	6,658,276	B2	12/2003	Kianl et al.
6,470,199	B1	10/2002	Kopotic et al.	6,658,277	B2	12/2003	Wassermann
6,470,200	B2	10/2002	Walker et al.	6,662,033	B2	12/2003	Casciani et al.
6,480,729	B2	11/2002	Stone	6,665,551	B1	12/2003	Suzuki
6,490,466	B1	12/2002	Fein et al.	6,668,182	B2	12/2003	Hubelbank
6,493,568	B1	12/2002	Bell	6,668,183	B2	12/2003	Hicks et al.
6,496,711	B1	12/2002	Athan et al.	6,671,526	B1	12/2003	Aoyagi et al.
6,498,942	B1	12/2002	Esenaliev et al.	6,671,528	B2	12/2003	Steuer et al.
6,501,974	B2	12/2002	Huiku	6,671,530	B2	12/2003	Chung et al.
6,501,975	B2	12/2002	Diab et al.	6,671,531	B2	12/2003	Al-Ali et al.
6,505,060	B1	1/2003	Norris	6,671,532	B1	12/2003	Fudge et al.
6,505,061	B2	1/2003	Larson	6,675,031	B1	1/2004	Porges et al.
6,505,133	B1	1/2003	Hanna et al.	6,678,543	B2	1/2004	Diab et al.
6,510,329	B2	1/2003	Heckel	6,681,126	B2	1/2004	Solenberger
6,510,331	B1	1/2003	Williams et al.	6,681,128	B2	1/2004	Steuer et al.
6,512,937	B2	1/2003	Blank et al.	6,681,454	B2	1/2004	Modgil et al.
6,515,273	B2	2/2003	Al-Ali	6,684,090	B2	1/2004	Ali et al.
6,519,484	B1	2/2003	Lovejoy et al.	6,684,091	B2	1/2004	Parker
6,519,486	B1	2/2003	Edgar, Jr. et al.	6,694,160	B2	2/2004	Chin
6,519,487	B1	2/2003	Parker	6,697,653	B2	2/2004	Hanna
6,525,386	B1	2/2003	Mills et al.	6,697,655	B2	2/2004	Sueppel et al.
6,526,300	B1	2/2003	Kiani et al.	6,697,656	B1	2/2004	Al-Ali
				6,697,658	B2	2/2004	Al-Ali
				RE38,476	E	3/2004	Diab et al.
				6,699,194	B1	3/2004	Diab et al.
				6,699,199	B2	3/2004	Asada et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

6,701,170 B2 3/2004 Stetson  
 6,702,752 B2 3/2004 Dekker  
 6,707,257 B2 3/2004 Norris  
 6,708,049 B1 3/2004 Berson et al.  
 6,709,402 B2 3/2004 Dekker  
 6,711,424 B1 3/2004 Fine et al.  
 6,711,425 B1 3/2004 Reuss  
 6,712,762 B1 3/2004 Lichter  
 6,714,803 B1 3/2004 Mortz  
 6,714,804 B2 3/2004 Al-Ali et al.  
 6,714,805 B2 3/2004 Jeon et al.  
 RE38,492 E 4/2004 Diab et al.  
 6,719,686 B2 4/2004 Coakley et al.  
 6,719,705 B2 4/2004 Mills  
 6,720,734 B2 4/2004 Norris  
 6,721,584 B2 4/2004 Baker, Jr. et al.  
 6,721,585 B1 4/2004 Parker  
 6,725,074 B1 4/2004 Kästle  
 6,725,075 B2 4/2004 Al-Ali  
 6,731,962 B1 5/2004 Katarow  
 6,731,963 B2 5/2004 Finarov et al.  
 6,731,967 B1 5/2004 Turcott  
 6,735,459 B2 5/2004 Parker  
 6,745,060 B2 6/2004 Diab et al.  
 6,745,061 B1 6/2004 Hicks et al.  
 6,748,253 B2 6/2004 Norris et al.  
 6,748,254 B2 6/2004 O'Neil et al.  
 6,754,515 B1 6/2004 Pologe  
 6,754,516 B2 6/2004 Mannheimer  
 6,760,607 B2 7/2004 Al-Ali  
 6,760,609 B2 7/2004 Jacques  
 6,763,255 B2 7/2004 DeLonzor et al.  
 6,773,397 B2 8/2004 Kelly  
 6,778,923 B2 8/2004 Norris et al.  
 6,780,158 B2 8/2004 Yarita  
 6,791,689 B1 9/2004 Weckstrom  
 6,792,300 B1 9/2004 Diab et al.  
 6,801,797 B2 10/2004 Mannheimer et al.  
 6,801,798 B2 10/2004 Geddes et al.  
 6,801,799 B2 10/2004 Mendelson  
 6,801,802 B2 10/2004 Sitzman et al.  
 6,802,812 B1 10/2004 Walker et al.  
 6,805,673 B2 10/2004 Dekker  
 6,810,277 B2 10/2004 Edgar, Jr. et al.  
 6,813,511 B2 11/2004 Diab et al.  
 6,816,741 B2 11/2004 Diab  
 6,819,950 B2 11/2004 Mills  
 6,822,564 B2 11/2004 Al-Ali  
 6,825,619 B2 11/2004 Norris  
 6,826,419 B2 11/2004 Diab et al.  
 6,829,496 B2 12/2004 Nagai et al.  
 6,830,711 B2 12/2004 Mills et al.  
 6,836,679 B2 12/2004 Baker, Jr. et al.  
 6,839,579 B1 1/2005 Chin  
 6,839,580 B2 1/2005 Zonios et al.  
 6,839,582 B2 1/2005 Heckel  
 6,839,659 B2 1/2005 Tarassenko et al.  
 6,842,635 B1 1/2005 Parker  
 6,845,256 B2 1/2005 Chin et al.  
 6,850,787 B2 2/2005 Weber et al.  
 6,954,664 B2 10/2005 Sweitzer  
 6,968,221 B2 11/2005 Rosenthal  
 6,979,812 B2 12/2005 Al-Ali  
 7,003,339 B2 2/2006 Diab et al.  
 7,020,507 B2 3/2006 Scharf et al.  
 7,024,233 B2 4/2006 Ali et al.  
 7,024,235 B2 4/2006 Melker et al.  
 7,128,622 B2 10/2006 Tsai  
 7,130,671 B2 10/2006 Baker, Jr. et al.  
 7,132,641 B2 11/2006 Schulz et al.  
 7,215,984 B2 5/2007 Diab et al.  
 7,228,161 B2 6/2007 Chin  
 7,254,433 B2 8/2007 Diab et al.  
 7,315,753 B2 1/2008 Baker, Jr. et al.  
 7,397,172 B2 7/2008 Kikushima

2002/0016537 A1 2/2002 Muz et al.  
 2002/0026109 A1 2/2002 Diab et al.  
 2002/0072681 A1 6/2002 Schnall  
 2002/0116797 A1 8/2002 Modgil et al.  
 2002/0128544 A1 9/2002 Diab et al.  
 2003/0045785 A1 3/2003 Diab et al.  
 2004/0068164 A1 4/2004 Diab et al.  
 2004/0117891 A1 6/2004 Hannula et al.  
 2004/0147824 A1 7/2004 Diab et al.  
 2004/0158134 A1 8/2004 Diab et al.  
 2004/0167381 A1 8/2004 Lichter  
 2004/0204637 A1 10/2004 Diab et al.  
 2004/0204638 A1 10/2004 Diab et al.  
 2004/0204639 A1 10/2004 Casciani et al.  
 2004/0210146 A1 10/2004 Diab et al.  
 2004/0215085 A1 10/2004 Schnall  
 2004/0236196 A1 11/2004 Diab et al.  
 2005/0014999 A1 1/2005 Rahe-Meyer  
 2005/0033131 A1 2/2005 Chen  
 2005/0043600 A1 2/2005 Diab et al.  
 2005/0049468 A1 3/2005 Carlson  
 2005/0070773 A1 3/2005 Chin  
 2005/0075546 A1 4/2005 Samssoondar  
 2005/0085704 A1 4/2005 Schulz  
 2005/0090720 A1 4/2005 Wu  
 2005/0228248 A1 10/2005 Dietiker  
 2005/0256386 A1 11/2005 Chan  
 2005/0272986 A1 12/2005 Smith  
 2006/0020179 A1 1/2006 Anderson  
 2006/0030764 A1 2/2006 Porges  
 2006/0074280 A1 4/2006 Martis  
 2006/0084166 A1 4/2006 Appel  
 2006/0084878 A1 4/2006 Banet  
 2006/0086678 A1 4/2006 Mattesky  
 2006/0122517 A1 6/2006 Banet  
 2006/0129039 A1 6/2006 Lindner  
 2006/0155198 A1 7/2006 Schmid  
 2006/0173257 A1 8/2006 Nagai  
 2007/0032710 A1 2/2007 Raridan et al.  
 2007/0032712 A1 2/2007 Raridan et al.  
 2007/0032715 A1 2/2007 Eghbal et al.  
 2007/0060808 A1 3/2007 Hoarau  
 2007/0073117 A1 3/2007 Raridan  
 2007/0073121 A1 3/2007 Hoarau et al.  
 2007/0073122 A1 3/2007 Hoarau  
 2007/0073123 A1 3/2007 Raridan  
 2007/0073125 A1 3/2007 Hoarau et al.  
 2007/0073126 A1 3/2007 Raridan  
 2007/0073128 A1 3/2007 Hoarau  
 2007/0078315 A1 4/2007 Kling et al.  
 2007/0078316 A1 4/2007 Hoarau  
 2007/0084793 A1 4/2007 Wenden  
 2007/0260129 A1 11/2007 Chin  
 2007/0260130 A1 11/2007 Chin  
 2007/0260131 A1 11/2007 Chin  
 2008/0058622 A1 3/2008 Baker et al.  
 2008/0076982 A1 3/2008 Ollerlessen  
 2009/0163783 A1 6/2009 Bowman et al.  
 2009/0163787 A1 6/2009 Bowman et al.

## FOREIGN PATENT DOCUMENTS

DE 3703458 8/1988  
 DE 3938759 5/1991  
 DE 4210102 9/1993  
 DE 4423597 8/1995  
 DE 19632361 2/1997  
 DE 69123448 5/1997  
 DE 19703220 7/1997  
 EP 0127947 5/1984  
 EP 0194105 9/1986  
 EP 0204459 12/1986  
 EP 0262779 4/1988  
 EP 0315040 10/1988  
 EP 0314331 5/1989  
 EP 0352923 1/1990  
 EP 0360977 4/1990  
 EP 0430340 6/1991  
 EP 0435500 7/1991

(56)

**References Cited**

## FOREIGN PATENT DOCUMENTS

EP	0572684	5/1992
EP	0497021	8/1992
EP	0529412	8/1992
EP	0531631	9/1992
EP	0566354	4/1993
EP	0587009	8/1993
EP	0630203	9/1993
EP	0572684	12/1993
EP	0615723	9/1994
EP	0702931	3/1996
EP	0724860	8/1996
EP	0864293	9/1998
EP	0898933	3/1999
FR	2685865	1/1992
GB	2259545	3/1993
JP	63275325	11/1988
JP	2191434	7/1990
JP	3170866	7/1991
JP	3173536	7/1991
JP	3245042	10/1991
JP	4174648	6/1992
JP	4191642	7/1992
JP	4332536	11/1992
JP	5049624	3/1993
JP	5049625	3/1993
JP	3115374	4/1993
JP	5200031	8/1993
JP	5212016	8/1993
JP	06014906	1/1994
JP	6016774	3/1994
JP	3116255	4/1994
JP	6029504	4/1994
JP	6098881	4/1994
JP	6154177	6/1994
JP	6269430	9/1994
JP	6285048	10/1994
JP	7001273	1/1995
JP	7124138	5/1995
JP	7136150	5/1995
JP	3116259	6/1995
JP	3116260	6/1995
JP	7155311	6/1995
JP	7155313	6/1995
JP	3238813	7/1995
JP	7171139	7/1995
JP	3134144	9/1995
JP	7236625	9/1995

JP	7246191	9/1995
JP	8256996	10/1996
JP	11188019	7/1999
JP	3124073	1/2001
WO	WO8909566	10/1989
WO	WO9001293	2/1990
WO	WO9004352	5/1990
WO	WO9101678	2/1991
WO	WO9111137	8/1991
WO	WO9200513	1/1992
WO	WO9221281	12/1992
WO	WO9309711	5/1993
WO	WO9313706	7/1993
WO	WO9316629	9/1993
WO	WO9403102	2/1994
WO	WO9423643	10/1994
WO	WO9502358	1/1995
WO	WO9512349	5/1995
WO	WO9516970	6/1995
WO	WO9613208	5/1996
WO	WO9639927	12/1996
WO	WO9736536	10/1997
WO	WO9736538	10/1997
WO	WO9900053	1/1999
WO	WO9963884	12/1999
WO	WO0167946	9/2001
WO	WO02085202	10/2002
WO	WO03020129	3/2003
WO	WO03063697	8/2003
WO	WO2004069046	8/2004
WO	WO2005065540	7/2005

## OTHER PUBLICATIONS



Aoyagi, T., et al.; "Analysis of Motion Artifacts in Pulse Oximetry," *Japanese Society ME*, vol. 42, p. 20 (1993) (Article in Japanese—contains English summary of article).

Barreto, A.B., et al.; "Adaptive Cancellation of Motion artifact in Photoplethysmographic Blood Volume Pulse Measurements for Exercise Evaluation," *IEEE—EMBC and CMBEC—Theme 4: Signal Processing*, pp. 983-984 (1995).



Vincente, L.M., et al.; "Adaptive Pre-Processing of Photoplethysmographic Blood Volume Pulse Measurements," pp. 114-117 (1996).

Rheineck-Leyssius, Aart t., et al.; "Advanced Pulse Oximeter Signal Processing Technology Compared to Simple Averaging: I. Effect on Frequency of Alarms in the Operating Room," *Journal of clinical Anesthesia*, vol. 11, pp:192-195 (1999).

\* cited by examiner

*FIG. 1**FIG. 2*



*FIG. 3**FIG. 4*




FIG. 5




FIG. 6




FIG. 7

FIG. 8A		FIG. 8B	
*Lissajous-Bandpass <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>		*Lissajous-Bandpass <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	
10X	Red	IR	
	NO MOTION HIGH SATURATION(100%)		MOTION HIGH SATURATION(100%)
*Lissajous-Bandpass <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>		*Lissajous-Bandpass <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	
10X	NO MOTION LOW SATURATION(70%)		MOTION LOW SATURATION(70%)

FIG. 8C

FIG. 8D




FIG. 9A

FIG. 9B






FIG. 10



*FIG. 11A*  
(PRIOR ART)

*FIG. 11B*




FIG. 12




FIG. 13




FIG. 14




FIG. 15

FIG. 16




FIG. 17




FIG. 18






FIG. 19

# **MOTION COMPATIBLE SENSOR FOR NON-INVASIVE OPTICAL BLOOD ANALYSIS**

## **CROSS-REFERENCES TO RELATED APPLICATIONS**

This application is a continuation of U.S. application Ser. No. 11/827,858, filed on Jul. 11, 2007, which is a continuation of U.S. application Ser. No. 10/991,111 filed Nov. 16, 2004, now U.S. Pat. No. 7,260,425, which is a continuation of U.S. application Ser. No. 10/080,433, filed Feb. 21, 2002, now U.S. Pat. No. 6,845,256, which is a division of U.S. application Ser. No. 09/348,437, filed Jul. 7, 1999, now U.S. Pat. No. 6,374,129, which is a division of U.S. application Ser. No. 08/722,443, filed Oct. 10, 1996, now U.S. Pat. No. 6,018,673, which disclosures are incorporated by reference for all purposes.

## **BACKGROUND OF THE INVENTION**

The present invention relates to optical sensors for non-invasive determination of physiological characteristics, and in particular to sensors for making such determinations in the presence of motion.

Many types of optical sensors are used to measure physiological characteristics of a patient. Typically, an optical sensor provides emitted light which is then scattered through tissue and detected. Various characteristics of a patient can be determined from analyzing such light, such as oxygen saturation, pulse rate, pH, etc.

Pulse oximetry is typically used to measure various blood characteristics including, but not limited to, the blood-oxygen saturation of hemoglobin in arterial blood, the volume of individual blood pulsations supplying the tissue, and the rate of blood pulsations corresponding to each heartbeat of a patient. Measurement of these characteristics has been accomplished by use of a non-invasive sensor which scatters light through a portion of the patient's tissue where blood perfuses the tissue, and photoelectrically senses the absorption of light in such tissue. The amount of light absorbed is then used to calculate the amount of blood constituent being measured.

The light scattered through the tissue is selected to be of one or more wavelengths that are absorbed by the blood in an amount representative of the amount of the blood constituent present in the blood. The amount of transmitted light scattered through the tissue will vary in accordance with the changing amount of blood constituent in the tissue and the related light absorption. For measuring blood oxygen level, such sensors have typically been provided with a light source that is adapted to generate light of at least two different wavelengths, and with photodetectors sensitive to both of those wavelengths, in accordance with known techniques for measuring blood oxygen saturation.

Known non-invasive sensors include devices that are secured to a portion of the body, such as a finger, an ear or the scalp. In animals and humans, the tissue of these body portions is perfused with blood and the tissue surface is readily accessible to the sensor. A photoelectric pulse transducer from World Precision Instruments is described as even recording signals through the fingernail.

Optical sensors are typically either reflective or transmissive. Transmissive sensors have the emitter and detector on opposite sides of a finger, toe, nose or other tissue. They measure light transmitted through the tissue from one side to the other. Reflectance sensors, on the other hand, have the emitter and detector side-by-side, such as placement on the

forehead, or on a fetus where it is difficult to position a sensor over a finger, etc. Reflectance sensors detect light which is scattered back to the same surface.

In pulse oximetry, the goal is to determine the amount of oxygen in arterial blood, as distinguished from venous blood or the tissue itself. The light emitted can be absorbed by all three, however, and they need to be distinguished among. FIG. 1 illustrates a plot of the logarithm of the detected intensity signal versus time. Solid line 10 is the detected infrared signal in a pulse oximeter, shown varying with time. Dotted line 12 is the detected red wavelength signal. As can be seen, the value moves up and down with the heartbeat frequency, due to the pulsing of the blood through the arteries. The portion of the signal below line 14 is representative of light absorbed by the tissue, venous blood, and a baseline component of the arterial blood.

Using appropriate signal analysis, the DC portion can be eliminated, leaving an extracted AC portion which is due to absorption by arterial blood. As can be seen in FIG. 1, and more clearly in FIG. 2, the red and infrared signals, although varying by different amounts, are in phase. FIG. 2 illustrates a plot over an epoch of time of the red logarithmic signal versus the infrared logarithmic signal, and is commonly referred to as a Lissajous plot. As can be seen, a line is formed, indicating they are in phase.

This characteristic of the red and infrared signals allows the determination of oxygen saturation through two methods. In a first method, the "ratio of ratios" is calculated, which is the ratio, between red and infrared, of the logarithms of the quotients obtained by dividing the maximum signal intensity and the subsequent minimum signal intensity. This ratio-of-ratios is then used in a predetermined formula to calculate arterial oxygen saturation. This is described more fully in U.S. Pat. No. 4,653,498.

In a second method, referred to here as "least squares," a least squares regression analysis is performed on the above-mentioned Lissajous plot to determine the slope of the ensemble of data points taken during an epoch of time. This slope is then used in a predetermined formula to determine arterial oxygen saturation. Other techniques are set forth in a co-pending application entitled "Method and Apparatus for Estimating Physiological Parameters Using Model-Based Adaptive filtering," filed Jun. 7, 1996, Ser. No. 08/660,510, the disclosure of which is hereby incorporated by reference.

In some cases, it is desirable to measure the oxygen saturation of the venous blood in order to get an indication of how much oxygen is being used by the body. The arterial blood, on the other hand, gives an indication of how much oxygen is being delivered to the body. In Shiga U.S. Pat. No. 4,927,264, the oxygen saturation in venous blood is determined by inducing a venous pressure with a pressure cuff. This effectively varies line 14 of FIG. 1 at a frequency different from the heart rate, so that it can be separately filtered and isolated and compared to the arterial pulse. The non-varying portion is then assumed to be the tissue absorption and can be distinguished from the slowly varying pressure induced venous blood absorption. An alternate approach can be used in extracorporeal monitoring where the blood is actually pumped out of the body and then back in. Such a technique is set forth in an article by Odell et al., entitled "Use of Pulse Oximetry to Monitor Venous Saturation During Extracorporeal Life Support" Critical Care Medicine, vol. 22, no. 4 (Apr. 4, 1994). In Odell, the venous blood being pumped out of the body passes the sensor, and the pumping mechanism provides an artificial pulse allowing the use of pulse oximetry techniques.

Motion artifact can degrade a pulse oximetry signal relied upon by a physician, without the physician's awareness. This

is especially true if the monitoring of the patient is remote, the motion is too small to be observed, or the doctor is watching the instrument or other parts of the patient, and not the sensor site. Thus, typically techniques are employed to reduce the effects of motion or compensate for motion.

In one oximeter system described in U.S. Pat. No. 5,025, 791, an accelerometer is used to detect motion. When motion is detected, readings influenced by motion are either eliminated or indicated as being corrupted. In a typical oximeter, measurements taken at the peaks and valleys of the blood pulse signal are used to calculate the desired characteristic. Motion can cause a false signal peak and valley, resulting in a measurement having an inaccurate value and one which is recorded at the wrong time. In U.S. Pat. No. 4,802,486, assigned to Nellcor Puritan Bennett, the assignee of the present invention, an EKG signal is monitored and correlated to the oximeter reading to provide synchronization to limit the effect of noise and motion artifact pulses on the oximeter readings. This reduces the chances of the oximeter locking onto a periodic motion signal. Still other systems, such as the one described in U.S. Pat. No. 5,078,136, assigned to Nellcor Puritan Bennett, use signal processing in an attempt to limit the effect of noise and motion artifact. The '136 patent, for instance, uses linear interpolation and rate of change techniques to analyze the oximeter signal. U.S. Pat. No. 5,337,744 sets forth sensor modifications used to improve the immunity of the signal from motion artifacts.

The motion signal impedes the measurement because it obscures the cardiac signal. The motion signal can have many components, such as, for example, the emitter or detector physically moving away from the body, or a volume of venous and arterial blood sloshing around in response to the motion, or the signal path being shortened or lengthened by expansion or compression of the tissue due to motion.

Contrary to conventional practice, signal analysis might be able to directly use the time-varying motion signal to calculate oxygen saturation. Under some conditions, the ratio-of-ratios (or least squares) resulting from a motion-induced signal has the same value as the ratio-of-ratios (or least squares) for the cardiac induced signal. The red and infrared intensity signals are often not in phase, and can limit the use of the motion signal for calculating oxygen saturation. One of the factors that may cause this is illustrated in FIG. 3. As FIG. 3 illustrates, light from emitter 28 can pass through skin 13, fat 15, muscle 16, and bone 18, on its way to a detector 30. Light of one wavelength may, on average, take path 32, while light of another wavelength may penetrate deeper and take path 34. Motion will cause disproportionate variances in the path lengths of the two wavelengths of light, resulting in out-of-phase signals of the detector.

#### BRIEF SUMMARY OF THE INVENTION

The present invention provides a non-invasive optical sensor which uses the motion signal to calculate the physiological characteristic being measured. For pulse oximetry, a least squares or a ratio-of-ratios technique can be applied to the slope of the motion signal itself. This is made possible by selecting a site on the patient where motion produces signals at two wavelengths which are adequately correlated with each other. Adequately correlated signals have a "closed" or "nearly closed" Lissajous. In particular, it has been determined that a sensor placed on a nail, in particular a thumbnail, exhibits the characteristics of having the red and infrared signals in phase when used for pulse oximetry.

The present invention also provides an optical sensor which fits entirely on a nail. No adhesive or other securing

mechanism around the rest of the finger is necessary, resulting in the entire sensor moving with the nail. The use of the nail site reduces the likelihood of out-of-phase motion signals for red and infrared wavelengths, and takes advantage of the predominantly arterial blood saturation characteristic of the blood present beneath the nail. In addition, the nail is an advantageous surface for adhering the sensor to, and at this location the method of attachment allows a low profile, low mass sensor to be used which further limits differential phase errors due to motion.

Preferably, the sensor on a nail of the present invention is a reflectance-type sensor. In one embodiment, a closer spacing is used than in typical prior art sensors, preferably less than 5 mm, more preferably approximately 4 mm. It has been empirically determined that the physiological characteristics at a nail site produce an improved signal with closer spacing. In addition, the sensor preferably has a curvature which conforms to the shape of the nail, and is attached with an adhesive.

In alternate embodiments of the invention, artificial motion may be induced with an air bag or otherwise to produce a motion signal which can be used with the sensor of the invention. In particular, this could be used for patients with low perfusion, a weak heartbeat or no heartbeat such as is the case during heart bypass surgery.

For a further understanding of the nature and advantages of the invention, reference should be made to the following description taken in conjunction with the accompanying drawings.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a graph of the log of the infrared and red intensity signals for pulse oximeters.

FIG. 2 is a graph of the red and IR signals showing correlation.

FIG. 3 is a diagram of the different average paths of different wavelength light through a patient.

FIG. 4 is a perspective view of a nail sensor according to the present invention on a thumb.

FIG. 5 is a cross-sectional, cutaway view of a thumb showing its components.

FIG. 6 is a end, cutaway view of one embodiment of a conformable nail sensor according to the present invention.

FIG. 7 is a diagram of a sensor according to the present invention placed longitudinally to span the lunula of the nail.

FIGS. 8A-8D are Lissajous plots of the output of a sensor according to the invention with and without motion, and at low and high saturation.

FIG. 9A is a plot of the red and infrared frequency distribution (FFT of time signals) showing experimental results from a thumbnail sensor according to the invention.

FIG. 9B is a plot of the Lissajous for the results of FIG. 9A.

FIG. 10 is a graph showing a plot of oxygen saturation readings of a sensor according to the present invention compared to a standard prior art sensor.

FIGS. 11A and 11B compare the prior art sensor and the present invention. The output waveforms and Lissajous plot are shown for each.

FIG. 12 is a diagram of an alternate embodiment of the invention showing a combination reflective and transmissive sensor.

FIG. 13 is a diagram of an alternate embodiment of the invention showing a self-contained nail sensor with its own display.

FIG. 14 is a diagram of a nail sensor with a motion inducing mechanism according to the present invention.

FIGS. 15 and 16 are top and side views of the motion stimulating mechanism of FIG. 14.

FIG. 17 is a flowchart of one embodiment of a program for responding to whether motion or a cardiac pulse is used for calculating saturation.

FIG. 18 is a block diagram of one embodiment of portions of an oximeter using controlled generation of motion.

FIG. 19 is a diagram of an embodiment of the sensor using a cylindrical lens and a tinted adhesive.

#### DETAILED DESCRIPTION OF THE INVENTION

FIG. 4 illustrates a sensor 40 according to the present invention preferably mounted on a nail 42 (a thumbnail or any other digit may be used). The sensor is held on with adhesive, and has an emitter 44 and a detector 46. A flexible circuit 48 provides the electrical connections to the emitter and detector, and may be accordion-shaped between the sensor and a securing band 50 to provide additional strain relief. This isolates the sensor from tugging or pulling on the electrical connection cord from either the sensor side or the other direction. Band 50 may be, for instance, an elastic band, cloth wrap secured with Velcro™, or another device. Flexible circuit 48 could be electrical wires or fiber optic cables. The different 25 wavelength light could be premixed using the fiber optic cable.

The placement on the top of the nail allows the cable to extend along the top of the finger or other digit, without the sensor or the cable being on the palmar side of the digit where it would interfere with grasping or other functionality of the hand.

As can be seen, the emitter 44 and detector 46 are arranged laterally across the width of the nail. However, a longitudinal arrangement (discussed more fully below) or any other arrangement on a nail is possible. The spacing of the emitter and detector may be varied, but an optimum spacing was experimentally found to be less than 10 mm, preferably less than 5 mm, more preferably approximately 4 mm.

The nailbed makes a good site for the sensor because it has been observed that motion generates artifact signals for the red and infrared wavelengths that are largely correlated to one another. The inventors have observed that this results in a ratio-of-ratios (or least squares) which correlates well with the arterial oxygen saturation.

Referring to FIG. 5, a cross-sectional view of the thumb is shown. As can be seen, the thumb includes a bone 52 with a thin layer of connective tissue 54 between the bone and thumbnail 56. A number of characteristics may contribute to the improved signal and the motion induced artifact being in phase. The different wavelength paths illustrated in FIG. 3 may be limited by the presence of bone 52, preventing one of the wavelengths from going deeper into tissue and having a different distance to travel. This effect is provided by the selection of the thumbnail as a site, and the use of reflectance oximeter sensor as opposed to a transmissive sensor. In a transmissive sensor, light would have to travel around the bone deep through the tissue, and the red and infrared may travel different lengths and be affected differently by motion.

Connective tissue layer 54 is thin and apparently strongly connective. Thus, the expansion and compression of tissues, particularly fatty tissues, which may cause out of phase motion artifacts for other sites and types of sensors, is apparently greatly reduced here. Because the thumbnail 56 itself provides a strong mounting platform, the sensor can be securely attached to it with adhesive, avoiding the emitter and detector from separating from the patient and causing gaps that may cause corrupt ratio-of-ratio values.

The region beneath nail 56 also provides a region which appears to be concentrated with oxygen saturated blood similar to the saturation of arterial blood. Oxygen consumption beneath the nail appears to be small relative to the circulation there, or the relative volume of venous blood may be negligibly small.

The presence of many small capillaries, rather than large vessels, makes the region more homogeneous, and thus lessens the likelihood that two different light wavelengths would be affected differently by passing through differing regions. In the absence of motion, the high perfusion allows a normal pulse oximetry reading to be made. During the occurrence of motion, the large amount of blood present allows a strong motion signal to be obtained, since a lot of blood is moved around by the motion. In experiments conducted by the inventors, motion artifact signals greater than 50 times that of a normal pulsatile plethysmogram signal have been observed. The nail site also appears to have a nailbed-tissue boundary that is optically phase-matched for the wavelengths of the sensor.

In addition to measuring oxygen saturation, the nailbed is a good site for other optical sensors. For example, glucose detection which requires the use of a near infrared wavelength could be used. Among the blood properties or constituents that can be measured are blood gases (CO<sub>2</sub>, O<sub>2</sub>), pH, glucose, drug concentrations, or other analytes (THb, Hct, lactate, K<sup>+</sup>, Na<sup>+</sup>, Ca<sup>2+</sup>, etc.).

FIG. 6 is an end, cutaway view of one embodiment of a sensor 40 according to the present invention. Emitter 44 and detector 46 are shown mounted on a flexible circuit board 60. An electrical cord 62 provides the connection to the electrical components of circuit board 60. The body of the sensor is preferably a semi-rigid piece of black poron foam. A metal strip could be imbedded to give extra rigidity. An adhesive is attached to underside 64 of the sensor to attach it securely to the nail. The underside is also curved to conform to the shape of the nail, but is slightly flexible to allow adaptation to differing nail shapes. Different curvature sensors could be provided for different sizes and shapes of nails to provide optimum fit, or the bottom surface could be fabricated from a softer, more conforming material.

One characteristic of the nail as a site is that the nail itself could act as a light pipe, shunting light between the emitter and the detector. Preferably, the light travels through the tissue beneath the nail along a path 66. However, some light could bounce back and forth through the nail itself on a path 68 between the emitter and detector in a manner not unlike a waveguide. To limit this shunting, the sensor body is made to absorb light, or at least the region between the emitter and detector is made at least partially absorbing to the wavelengths of interest. In this way, each time light strikes the side of the nail adjacent the absorbing layer, it will be absorbed, rather than propagating along the nail.

Shunting can also be limited by recessing the emitter and detector and providing a narrow numerical aperture. Because of the rigidity of the sensor body, recessing will not produce variations in distance during motion. By limiting the numerical aperture of the emitter and detector to values less than 0.9, preferably to values less than 0.5, the emitter will not directly launch light into the nail "waveguide," and light which does potentially travel path 68 will be outside the acceptance angle of the detector.

The nail also provides advantages for adhering the sensor to the patient since the nail does not have the quantity of oils or sweat as present on the skin.

FIG. 7 is a diagram of a sensor 700 arranged longitudinally along a nail 706. The sensor has an emitter 702 and a detector

704 which are not both on the lunula of the nail. The lunula is the light colored area of the nail below line 708 in FIG. 7. It is believed that if both the emitter and detector are located on the lunula, more undesirable shunting of light will occur.

FIG. 8 has FIGS. 8A-8D which show the Lissajous plots and calculated saturations for a sensor according to the present invention during four conditions: motion and no motion at high and low saturation. As can be seen in FIGS. 8A and 8B at high saturation, the calculated saturation 100% is equivalent with or without motion. In FIG. 8B, the motion signal is seen to be more than 10 times larger than the cardiac signal of FIG. 8A (FIGS. 8A and 8C are magnified by 10). Similar results occur at low saturation as seen in FIGS. 8C and 8D where the saturation values are calculated to be 70% under both conditions.

FIG. 9A is a graph of the frequency distribution of the detected red and infrared signals for a sensor of the present invention in an experiment with an 8 Hz artificial motion pulse applied. The cardiac signature can be seen at the lower frequencies below 5 Hz, while the 8 Hz driven motion signal is also visible. FIG. 9B is a graph of the red versus infrared intensity signals for the experiment illustrating that both signals are correlated and representative of the same saturation.

FIG. 10 illustrates the oxygen saturation readings of a sensor according to the present invention in experimental tests without motion comparing it with a standard prior art transmissive sensor at another site. A close agreement was noted, indicating the calibration of this sensor on the nailbed site is similar to a conventional transmission sensor.

FIGS. 11A and 11B show a comparison of the output waveform and Lissajous, in the presence of motion, of a sensor according to the present invention (FIG. 11B) with a standard prior art transmissive sensor at another site (FIG. 11A).

FIG. 12 illustrates an alternate embodiment of the present invention in which a nail sensor 70 according to the present invention is attached via a flexible circuit 72 to a transmissive sensor 74 which wraps around the finger and has an emitter 76 and detector 78 positioned on top and on the bottom of the finger. Such a combination sensor could allow the oximeter monitor with its program to choose between the sensors depending upon motion conditions. When motion is present, nail sensor 70 could be used, and when motion is not present, sensor 74, which may be more sensitive to the cardiac pulse signal, could be used. Alternately, a single pair of red and infrared emitters could be used, with a reflectance detector on the nail, and a transmissive detector off the nail. Depending on the mode, a switch in the sensor, or in an intermediate amplifier module, or in the oximeter monitor could select between the detectors. In another embodiment, a single detector is used, with one pair of emitters on the nail, and another pair of emitters off the nail. Alternately, a completely separate transmissive sensor could be used.

In some patients, in particular those with low blood perfusion, it may be difficult to lock onto a pulse waveform. The additional transmissive sensor could be used to enable locking on for such patients. In addition, a transmissive sensor could be used to calibrate the nail sensor "on-the-fly." Because of shunting and other unique aspects of the nail site, a predetermined calibration may be off. A measurement of saturation using the transmissive and the nail reflectance sensors could be done in the absence of motion, with a correction factor applied to the reflectance sensor. The correction could be a constant which is added or a multiplicative factor, or both. If measurements are done at different saturations, a calibration line or curve could be determined by the oximeter to allow adjustments anywhere along the calculated curve.

Subsequently, in the presence of motion, the nail sensor will be more accurately calibrated.

FIG. 13 illustrates an alternate embodiment of the invention in which a self-contained sensor 80 according to the present invention includes the processing circuitry on one or more semiconductor chips inside, and has its own display 82, which may be a liquid crystal display, for instance. In one embodiment, a button 84 allows switching between modes, such as between displaying a pulse and oxygen saturation. In an alternate embodiment, a flex connection 86 to a module 88 attached on a band 90 may be used. Module 88 might contain the battery, or alternately the processing circuitry, or the display. Additionally, either embodiment could be used for a wireless transmission to an oximeter, with the transmitting circuit either being in module 88 or sensor body 80.

FIG. 14 illustrates another embodiment of the present invention in which a stimulator is used to generate an artificial pulse. A stimulator could electrically stimulate the nerves to cause motion of an appendage, or could use a pneumatic pressure cuff to stimulate an artificial pulse; or use electro-mechanical stimulation or any other mechanism which generates a pulse characteristically different (e.g., amplitude, frequency, shape, etc.) than the cardiac pulse so that the cardiac pulse need not be used. Such an apparatus would be particularly advantageous for patients with low blood perfusion or a weak heartbeat. FIG. 14 is one embodiment showing a sensor 92 mounted on a thumbnail, with an airbag 94 mounted to the bottom of the thumb and held in place with a band 96. A hose 98 to the airbag periodically inflates and deflates it, causing a pressure wave through the thumb, giving artificially induced motion. This pressure induced motion provides the variation needed for sensor 92 to measure the oxygen saturation using either the ratio-of-ratios or a least squares technique. If the motion is in the frequency range of a heartbeat, the sensor can be backward compatible with existing oximeter monitors, even those that look for a cardiac signal.

FIG. 15 illustrates airbag 94 in a top view, showing hose 98 connected to a diaphragm pump 100. FIG. 16 shows a side view of the airbag 94 of FIG. 15, showing that it is wide but flat.

FIG. 17 is a flowchart of one embodiment of a portion of a program for operating an oximeter so that either cardiac pulses or motion pulses can be used to calculate oxygen saturation. The oxygen saturation is calculated in a known manner (step A). In a first alternative, the signal is analyzed to determine if it is a cardiac pulse or a motion pulse (step B). This can be done using any of the pulse qualification or motion detection techniques known to those of skill in the art. If a motion signal is present and used for the oxygen saturation calculation, then in step C only the oxygen saturation signal is displayed, and not a pulse rate (which would be a motion pulse rate, and not the patient's heart rate). If a cardiac pulse is used, the pulse rate is also displayed (step D).

Alternately, a pulse determination step E could be used where the sensor includes both a reflectance sensor and a transmittance sensor. If motion is present above a predetermined threshold (such as at least twice the arterial pulse signal), the reflectance sensor is used, which uses the motion signal, and alters any motion filtering or motion reduction techniques (step F). If the motion signal is below the threshold, the transmittance sensor is used (step G), with standard motion reduction techniques being employed (either hardware or software or both).

Both sensors could be energized in an ongoing manner, and the saturation and rate could be chosen to come from the sensor considered most reliable, depending on the instru-

ment's assessment of motion. Simultaneous computation may further allow improved processed signal estimates of cardiac rate in the presence of motion given knowledge of estimated saturation.

FIG. 18 is a block diagram of a portion of a pulse oximeter monitor used in conjunction with an artificial pulse generator, such as shown in FIGS. 14-16. A frequency generator 110 produces a desired frequency for the motion pulse. This could be varied to give a frequency which is not interfered with by other noise, or frequency hopping could be used to isolate the signal from other sources of motion or noise. A pump controller 112 activates a pump or motor 100 (FIG. 12) at the generated frequency. Since the driven frequency is known, optionally other frequencies could be filtered out to reduce noise. After a signal is captured and converted to digital form by a circuit 114, a bandpass filter 116 is used to reduce other frequency signals. A control signal from frequency generator 110 could vary the bandpass frequency. A circuit or processor 118 then calculates the oxygen saturation. A central controller 120 controls the rest of the circuitry, including a sensor driver circuit 122, which could selectively activate different reflectance and transmittance emitters in one embodiment. Controller 120 could also analyze the signals for the presence of motion to alternate between motion and cardiac pulse modes in one embodiment. Alternately, a separate motion sensor could provide an input to controller 120. Note that other physical implementations are possible, such as using a single processor to do the filtering, the frequency generation and the oxygen saturation calculation.

A calibration resistor (or other active or passive element) 115 encodes the mean wavelength of at least one LED, and provides it to a calibration reader circuit or CPU 120. The wavelength indicated is used to select coefficients stored in the monitor. Such a calibration technique is described in more detail in U.S. Pat. No. 4,621,643, the disclosure of which is incorporated herein by reference.

FIG. 19 is a cut-away view of an embodiment of a sensor 130 according to the invention. An emitter 132 is mounted on a circuit 134 inside the sensor housing. A cylindrical lens 136 is mounted in an aperture 138. The lens directs the light down through the nail, minimizing the light which hits the nail at an angle and can be shunted to the detector. An aperture itself can perform the same function, but the lens insures that more of the light is used, maintaining a higher intensity at a given power, or allowing less power to be used. Detector 140 is recessed in an aperture 142 to avoid shunted light on the receiving end.

The sensor is secured to a nail 144 using an adhesive layer 146. The adhesive layer can act as a shunt path itself. Accordingly, the adhesive layer may be tinted to be opaque to the wavelengths used, with preferably transparent windows 148 and 150 for the detector and emitter apertures.

As will be understood by those of skill in the art, the present invention could be embodied in other specific forms without departing from the spirit or essential characteristics thereof. For example, a sensor could be placed on a fingernail other than the thumb nail, and could be placed on toenails. Alternately, a sensor could be placed on the cuticle or the live nail fold skin extending over the beginning of the nail. The sensor could be attached with a clip-type sensor, or an elastic wrap, bandage or adhesive which encircles the appendage could be used. The sensor could be placed at locations other than the nailbed where signals at the multiple wavelengths in the presence of motion are still adequately correlated. The emitter in the sensor could be fabricated using an optical fiber to carry the light from a source remotely located, and equivalently the detector could be an optical light guide to pipe the light to a

remote detector. Accordingly, reference should be made to the following claims which set forth the scope of the invention.

The invention claimed is:

1. An optical sensor comprising:
  - a sensor body configured to attach to a distal end portion of a patient's digit, the sensor body housing a light emitter and a light detector; and
  - a flexible circuit having a first portion operatively connected to the light emitter and to the light detector, having a second portion that is accordion-shaped and that extends over at least one joint of the patient's digit, and having a third portion configured to be secured to a proximal end portion of the patient's digit, wherein the accordion-shaped second portion is configured to move independently of the sensor body.
2. The optical sensor of claim 1, wherein the sensor comprises a pulse oximetry sensor.
3. The optical sensor of claim 1, wherein the light emitter is recessed in a first cavity of the sensor body, the light detector is recessed in a second cavity of the sensor body, and wherein the first cavity includes a lens between the light emitter and an edge of the sensor body, and the second cavity includes an empty space between the light detector and the edge of the sensor body.
4. The optical sensor of claim 1, comprising a securing band for attaching the sensor body to the patient's digit.
5. The optical sensor of claim 4, wherein the securing band comprises an elastic band and a hook and loop fastener.
6. The optical sensor of claim 1, wherein the sensor body is configured to be attached to the patient's nail such that the light emitter and the light detector are positioned on the patient's nail.
7. The optical sensor defined in claim 1, comprising a display disposed on the sensor for displaying at least one of a blood oxygen saturation value or a pulse rate.
8. The optical sensor defined in claim 7, wherein the light emitter, the light detector, and the display are located in one housing of the sensor body.
9. The optical sensor defined in claim 7, comprising a button or switch for alternating between displaying the pulse rate and the oxygen saturation value.
10. A method of reducing light shunting in an optical sensor, comprising:
  - emitting light into a tissue with a light emitter disposed in a sensor body, the sensor body configured to attach to a distal end portion of a patient's digit;
  - detecting the light from the tissue with the light detector disposed in the sensor body;
  - generating a signal based on the detected light; and
  - transmitting the signal to a monitor via a first portion of a flexible circuit operatively connected to the light emitter and to the light detector via a second portion of the flexible circuit that is accordion-shaped and that extends over at least one joint of the patient's digit and via a third portion of the flexible circuit configured to be secured to a proximal end portion of the patient's finger wherein the accordion-shaped second portion is configured to move independently of the sensor body.
11. The method of claim 10, comprising determining a blood oxygen saturation value from the signal.
12. The method of claim 10, comprising displaying the blood oxygen saturation value on a display located on the sensor body.
13. The method of claim 10, wherein the light emitter is recessed in a first cavity of the sensor body having a lens, the light detector is recessed in a second cavity of the sensor body,

**11**

and wherein the second cavity includes an empty space between the light detector and a patient contacting surface of sensor body.

\* \* \* \* \*

**12**

专利名称(译)	运动兼容传感器，用于非侵入式光学血液分析		
公开(公告)号	<a href="#">US8649839</a>	公开(公告)日	2014-02-11
申请号	US12/822898	申请日	2010-06-24
[标]申请(专利权)人(译)	内尔科尔普里坦贝内特公司		
申请(专利权)人(译)	NELLCOR PURITAN BENNETT LLC		
当前申请(专利权)人(译)	COVIDIEN LP		
[标]发明人	CHIN RODNEY MANNHEIMER PAUL D FLEWELLING ROSS		
发明人	CHIN, RODNEY MANNHEIMER, PAUL D FLEWELLING, ROSS		
IPC分类号	A61B5/1455 A61B5/1464 A61B5/00 A61B5/145 A61B5/1495		
CPC分类号	A61B5/6833 A61B5/14552 A61B5/7207 A61B5/6826 A61B5/6838		
其他公开文献	US20100261986A1		
外部链接	<a href="#">Espacenet</a> <a href="#">USPTO</a>		

#### 摘要(译)

一种非侵入式光学传感器，其使用运动信号来计算被测量的生理特征。对于脉搏血氧测定法，可以将最小二乘法或比率比技术应用于运动信号本身。这可以通过选择患者的位置来实现，其中运动的变化产生两个充分相关的波长的信号。特别地，已经确定放置在指甲上的传感器，特别是缩略图，表现出当用于脉搏血氧测定时具有相关的红色和红外信号的特性，并且所得到的信号与动脉血氧饱和度相关。

