




US 20120310061A1

(19) **United States**(12) **Patent Application Publication**  
**Al-Ali et al.**(10) **Pub. No.: US 2012/0310061 A1**(43) **Pub. Date: Dec. 6, 2012**(54) **NONINVASIVE OXIMETRY OPTICAL  
SENSOR INCLUDING DISPOSABLE AND  
REUSABLE ELEMENTS**continuation of application No. 10/351,645, filed on  
Jan. 24, 2003, now Pat. No. 6,920,345.**Publication Classification**(76) Inventors: **Ammar Al-Ali**, San Juan  
Capistrano, CA (US); **Yassir  
Abdul-Hafiz**, Irvine, CA (US)(51) **Int. Cl.**  
**A61B 5/1455** (2006.01)  
**B23P 11/00** (2006.01)  
**A61B 5/0205** (2006.01)(21) Appl. No.: **13/585,669**(52) **U.S. Cl. .... 600/324; 600/323; 29/428**(22) Filed: **Aug. 14, 2012****Related U.S. Application Data**(63) Continuation of application No. 11/754,972, filed on  
May 29, 2007, now Pat. No. 8,244,325, which is a  
continuation of application No. 11/172,587, filed on  
Jun. 30, 2005, now Pat. No. 7,225,007, which is a(57) **ABSTRACT**

A pulse oximetry sensor includes reusable and disposable elements. To assemble the sensor, members of the reusable element are mated with assembly mechanisms of the disposable element. The assembled sensor provides independent movement between the reusable and disposable elements.













FIG. 1










FIG. 7A








FIG. 7B














## NONINVASIVE OXIMETRY OPTICAL SENSOR INCLUDING DISPOSABLE AND REUSABLE ELEMENTS

### RELATED APPLICATIONS

[0001] The present application is a continuation of U.S. patent application Ser. No. 11/754,972, filed May 29, 2007, entitled “*Noninvasive Oximetry Optical Sensor Including Disposable and Reusable Elements*,” now U.S. Pat. No. 8,244,325, which is a continuation of U.S. patent application Ser. No. 11/172,587, filed Jun. 30, 2005, entitled “*Optical Sensor Including Disposable and Reusable Elements*,” now U.S. Pat. No. 7,225,007, which is a continuation of U.S. patent application Ser. No. 10/351,645, filed Jan. 24, 2003, entitled “*Optical Sensor Including Disposable and Reusable Elements*,” now U.S. Pat. No. 6,920,345, and claims priority benefit under 35 U.S.C. §120 to the same. The present application incorporates the foregoing disclosures herein by reference.

### FIELD OF THE INVENTION

[0002] The present invention relates to the field of sensors that measure oxygen content in a patient's blood. More specifically, the invention relates to a sensor that assembles reusable and disposable elements and/or allows longitudinal displacement between the reusable and disposable elements.

### BACKGROUND OF THE INVENTION

[0003] Early detection of low blood oxygen is important in a wide variety of medical applications, and oximetry was developed to study and to measure, among other things, the oxygen status of blood. One type of oximetry, pulse oximetry, employs a sensor attached to a patient in order to output a signal indicative of a physiological parameter of the patient, such as, for example, the patient's blood oxygen saturation.

[0004] A pulse oximeter sensor generally uses a number of sensor components, such as one or more energy emission devices like red and infrared LED emitters, and an energy detection device like a photodiode detector. The sensor is generally attached to a measurement site such as a patient's finger, toe, ear, forehead, foot, hand, heel or the like, using an attachment mechanism such as a disposable tape, reusable housing, Velcro strap, or the like. The attachment mechanism positions the emitter and detector in proximity to the measurement site, such that the emitter projects energy into the blood vessels and capillaries of the measurement site, and the photodiode detector then detects the attenuated energy. The emitted energy can be light or other forms of energy. The detector communicates a signal indicative of the detected attenuated energy to a signal processing device such as an oximeter. The oximeter generally calculates, among other things, one or more physiological parameters of the measurement site.

[0005] In sensors where the detector detects emissions through the measurement site, it is generally desirable to position the detector opposite the emitter around the measurement site, such as, for example, above and below a finger. However, sensors are produced in a limited number of sizes and shape configurations, while patients have, for example, fingers and toes of many different sizes and shapes.

[0006] In addition, the attachment mechanism and the electronic components of a sensor are generally curved around a measurement site in a manner detrimental to one or more

elements of the sensor. For example, the attachment mechanism generally wraps around the measurement site at an approximate “inner circle” having a first radius, while the electronic components such as the flexible circuits are generally fixedly attached to the attachment mechanism. Accordingly, the electronic components can form an approximate “outer circle” having a second radius unequal to the first radius. However, because the attachment mechanism generally does not move independently with respect to the electrical components, attachment of the sensor to the measurement site can exert forces on the electrical components, such as, for example, exerting forces which try to lengthen, or longitudinally stretch the electrical components to account for an increased radius thereof. The forced stretching can damage the electrical components of a flexible circuit, such as the conductive traces.

### SUMMARY OF THE INVENTION

[0007] Based on the foregoing, embodiments of the present invention include a sensor comprising reusable and disposable sensor elements that permit longitudinal displacement with respect to one another when the sensor is attached to a measurement site. For example, in one embodiment the sensor includes a reusable element and a disposable element configured to receive the reusable element in a releasable attachment assembly providing longitudinal displacement between the disposable and reusable elements. The longitudinal displacement advantageously allows the sensor elements to self-adjust with respect to one another during attachment to the measurement site. The self-adjustment or independent movement advantageously reduces the forces caused by longitudinal stretching, thereby reducing damage to the reusable element.

[0008] One aspect of the invention relates to an optical probe including a reusable element and a disposable element that can be attached together by placing or snapping protrusions on one element into apertures and receiving slots on the other element. For example, the reusable element can be fitted with protrusions made of plastic, and the disposable element can be fitted with detents or tabs, which include apertures or receiving slots. The reusable element attaches to the disposable element by inserting, or snapping, the protrusions into the apertures and the receiving slots of the tabs. When assembled, at least some of the protrusions are slidable within the receiving slots to independently move along a longitudinal axis of the sensor, thereby providing some longitudinal decoupling between the reusable element and the disposable element.

[0009] Another aspect of the invention relates to a sensor with a reusable element and a disposable element where the reusable element is made of a flexible or pliable material and includes one or more neck sections. The disposable element includes two straps, each of which is configured to receive a neck section. The reusable element and the disposable element are attached together by placing the neck sections within the straps. In one embodiment, the neck sections include a long neck section and a short neck section. The long neck section has a sufficient length to allow longitudinal movement of the reusable element within the strap, thus permitting movement of the reusable element with respect to the disposable element.

[0010] Another aspect of the invention relates to a sensor with a reusable element and a disposable element where the reusable element is secured by guides or tabs affixed to the

disposable element. The guides allow limited longitudinal motion of the reusable element and thereby allow the reusable element to flex independently of the disposable element as the device is positioned on a patient.

[0011] Another aspect of the invention relates to a sensor with a reusable element and a disposable element where the reusable element is encased in a protective cover. In one embodiment, the protective cover is made of a pliable material and prevents any sharp edges from scratching or poking a patient or caregiver. The protective cover also advantageously prevents damage to the reusable element that could occur from dirt, dust, liquids, or other elements of the environment.

[0012] Yet another aspect of the invention relates to a sensor with a reusable element and a disposable element where the disposable element includes a breakable element. After an approximate predetermined number of safe uses, the breakable element breaks and the disposable element is rendered inoperable or otherwise indicates its over use.

[0013] For purposes of summarizing the invention, certain aspects, advantages and novel features of the invention have been described herein. Of course, it is to be understood that not necessarily all such aspects, advantages or features will be embodied in any particular embodiment of the invention.

#### BRIEF DESCRIPTION OF THE DRAWINGS

[0014] A general architecture that implements the various features of the invention will now be described with reference to the drawings. The drawings and the associated descriptions are provided to illustrate embodiments of the invention and not to limit the scope of the invention. The drawings are not necessarily drawn to scale. Throughout the drawings, reference numbers are re-used to indicate correspondence between referenced elements. In addition, the first digit of each reference number indicates the figure in which the element first appears.

[0015] FIG. 1 illustrates a perspective view of an embodiment of an unassembled sensor that includes reusable and disposable elements.

[0016] FIG. 2 illustrates a perspective view of tabs of the disposable element of FIG. 1.

[0017] FIG. 3A illustrates a cross-sectional view of another embodiment of tabs of a disposable element.

[0018] FIG. 3B illustrates a cross-sectional view of yet another embodiment of tabs of a disposable element.

[0019] FIG. 4A illustrates a cross-sectional view of the two tabs of FIG. 2, adhesively attached to the disposable element.

[0020] FIG. 4B illustrates a cross-sectional view of the two tabs of FIG. 2, attached between layers of the disposable element.

[0021] FIG. 5 illustrates a top view of the disposable element of FIG. 1, including an information element and breakable conductor.

[0022] FIG. 6 illustrates a top view of another embodiment of an assembled sensor that includes reusable and disposable elements.

[0023] FIGS. 7A and 7B illustrate simplified cross-sectional views of an embodiment of a strap of the disposable element of FIG. 6.

[0024] FIG. 8 illustrates an exploded view of a disposable element according to another embodiment of an optical sensor.

[0025] FIG. 9 illustrates a perspective view of the disposable element of FIG. 8.

[0026] FIG. 10 illustrates a perspective view of an embodiment of a reusable element according to an embodiment of the optical sensor of FIG. 8.

[0027] FIG. 11 illustrates a perspective view of a flex circuit of the reusable element of FIG. 10.

[0028] FIG. 12 illustrates a perspective view of the assembled optical sensor including the disposable element of FIG. 8 and the reusable element of FIG. 10.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

[0029] FIG. 1 illustrates an embodiment of a sensor 100. The sensor 100 includes a reusable element 110 and a disposable element 120. According to one embodiment, the reusable element 110 generally includes those components of the sensor 100 that are more expensive, such as, for example, one or more energy emitters, one or more energy detectors, one or more breakable conductors, one or more information elements, some or all of the same, or the like. In addition, the reusable element 110 includes an assembly mechanism generally shaped to mate with a corresponding component of the disposable element 120, as will be disclosed in greater detail below.

[0030] The disposable element 120 generally includes those components of the sensor 100 that are less expensive, such as, for example, face tape, bandages, or other mechanisms for removably attaching the reusable element 110 to a measurement site. Moreover, the disposable element 120 includes a mating assembly mechanism generally shaped to mate with assembly mechanism of the reusable element 110, thereby attaching the reusable element 110 to the disposable element 120 in a manner that provides for at least some self adjustment or displacement between the elements.

[0031] When the disposable element 120 attaches the reusable element 110 to tissue of a measurement site, a signal processing device, such as an oximeter, activates the energy emitters to transmit light energy into the tissue. The tissue attenuates the light energy, which is then detected by the detector. A signal indicative of the detected light energy is then generally forwarded back to the signal processing device for determination of one or more physiological parameters of the tissue, such as, for example, oxygen saturation, pulse rate, or the like.

[0032] A skilled artisan will recognize from the disclosure herein that there are many combinations of differing shapes and circuit configurations for the reusable and disposable elements, 110 and 120, respectively, such as, for example, those disclosed in U.S. Pat. No. 6,377,829, and U.S. patent application Ser. No. 10/020,664, filed on Dec. 11, 2001, both of which are hereby incorporated by reference.

[0033] As shown in the exemplary embodiment of FIG. 1, the reusable element 110 can include one or more energy emitters 112, an energy detector 114, and an electrical connector 116 electrically communicating with the emitters 112 and the detector 114 through a flexible circuit. According to one embodiment, the flexible circuit comprises material of a generally flexible or pliable construction.

[0034] The reusable element 110 also includes the foregoing assembly mechanism, such as, for example, the one or more protrusions 118. According to one embodiment, the protrusions 118 comprise approximately cylindrical-shaped or tab-shaped extensions made of plastic or other durable materials. FIG. 1, shows the reusable element 110 including four protrusions 118, two opposing protrusions proximate a

front portion and extending in opposite generally horizontal directions, and two opposing protrusions proximate a back portion and extending in opposite generally horizontal directions. According to one embodiment, the protrusions 118 roughly align with one or more of the electronic components of the sensor 100. As described below, the protrusions 118 each advantageously mate with the mating assembly mechanism of the disposable element 120 in a manner providing for at least some displacement of the reusable element 110 with respect to the disposable element 120, thereby avoiding damage or harmful wear of the reusable element 110.

[0035] FIG. 1 also shows the flexible circuit including an optical barrier, such as, for example, an aperture or gap 119 to reduce light energy from traveling from the emitter 112 to the detector 114 without first passing through tissue at the measurement site (i.e., light piping). A skilled artisan will recognize from the disclosure herein that the gap 119 could be replaced with opaque materials, protrusions, pads, tabs, or other light blocking mechanisms.

[0036] Although disclosed with reference to preferred embodiments, a skilled artisan will recognize from the disclosure herein, a number of other embodiments of the reusable element 110. For example, one or more of the emitters 112 or the detector 114 can be located on the disposable element 120. Moreover, the flexible circuit may comprise plastic, electric wires, polyester substrates, or the like.

[0037] FIG. 1 also shows the disposable element 120. According to an embodiment, the disposable element 120 generally comprises a base 130 comprising a face tapestock material similar to that of an adhesive bandage shaped to position the reusable element proximate the measurement site. The face tape can include an adhesive covered base protected by one or more conveniently shaped release liners or layers. Although illustrated in a conventional elongated surface with opposing wings style shape, an artisan will recognize from the disclosure herein that the tape may comprise virtually any shape, including those disclosed in U.S. patent application Ser. No. 10/020,664, referenced above. Moreover, the disposable element 120 may comprise a Velcro strap, a foam wrap, a reusable plastic housing or the like.

[0038] The disposable element 120 also includes the assembly mechanism, illustrated as tabs 122 and 124. Each of the tabs 122 include an aperture 132, while each of the tabs 124 include a receiving slot 134. In one embodiment, the apertures 132 and the receiving slots 134 have sufficient depth to receive the protrusions 118. In other embodiments, the apertures 132 and receiving slots 134 extend through the tabs 122 and 124. As shown in FIG. 1, the tabs 122 and 124 are shaped to removably receive the reusable element 110. For example, the tabs 122 and 124 can include sloped surfaces that cause the tabs 122 and 124 to displace outwardly during assembly of the sensor 100. For example, when the reusable element 110 is properly positioned within the tabs 122 and 124, the tabs 122 and 124 snap inwardly over the reusable element 110 such that the protrusions 118 are within the apertures 132 and the receiving slots 134. When assembled, vertical and horizontal movement between the reusable and disposable elements, 110 and 120 respectively, is substantially prevented by the relationship between the tabs 122 and 124, the apertures 132, the slots 134 and the protrusions 118. However, the slots 134 provide for displacement between elements along longitudinal axis A when the disposable portion 120 is wrapped around a measurement site by allowing the protrusions 118 to slide back and forth within the slots

134. Thus, the assembly mechanisms of the reusable and disposable elements, 110 and 120, provide independent movement between the elements, thereby allowing self-adjustment of the sensor 100 to the differing radiuses of each element. Such construction advantageously reduces the harmful stressing effects applied to components of the reusable element 110.

[0039] FIG. 1 also shows that a gap 142, slot or aperture, or otherwise transparent area can be included on the disposable element 120 to permit light from the emitter 112 to travel through the disposable element 120 to the tissue of the measurement site. Moreover, another gap 144 can be included on the disposable element 120 to permit attenuated light from the measurement site tissue to travel through the disposable element 120 to the detector 114. In another embodiment, some or all of the base 130 of the disposable element 120 is made of a transparent material, and the gaps 142 and 144 can be omitted.

[0040] A skilled artisan will recognize from the disclosure herein that the tabs 122 and 124 of the disposable element 120 can be implemented in a wide variety of embodiments. For example, an embodiment can include each of the tabs 122 and 124 having a receiving slot 134 while another embodiment can include each of the tabs 122 and 124 having an aperture 132.

[0041] FIG. 2 illustrates a perspective view of the tabs 124 including the receiving slots 134. As disclosed, the tabs 124 can be shaped to include a sloped surface 220 configured to displace a ledge or catch 230 during sensor assembly. For example, the sloped surface 220 displaces outwardly when protrusions 118 are pressed in the direction of the arrow C. Then when the reusable element 110 is properly positioned, the protrusions 118 snap into the receiving slots 134 and the catch 230 snaps over a top surface of the reusable element 110.

[0042] The receiving slots 134 are longer than the cross sectional width of the protrusions 118 so that the protrusions 118 can move within the receiving slots 134 to different positions along the longitudinal axis A of the disposable element 120. The apertures 132, on the other hand, are sized to allow protrusions 118 to be located within the apertures 132 but to prevent substantial movement along the longitudinal axis A of the disposable element 120, thus ensuring proper positioning of the sensor elements, with respect to the tissue and one another.

[0043] In an embodiment, the reusable element 110 and the disposable element 120 are assembled into the sensor 100 when the protrusions 118 are snapped into the apertures 132 and the receiving slots 134 of the tabs 122 and 124. The assembled sensor 100 is then attached to a measurement site, through, for example, application of the adhesive covered side of the face tape to tissue at the measurement site. During application, the protrusions 118 within the receiving slots 134 move along the receiving slot 134, while the protrusions 118 remain positioned within the aperture 132. This type of flexibility advantageously reduces the stretching force placed on conventional reusable elements.

[0044] FIG. 2 also shows receiving slots 134 as grooves in the walls 240 of the tabs 124, where the grooves do not extend all the way through the walls 240. In other embodiments, the receiving slots 134 can be open slots that extend through the walls 240. Likewise, the aperture 132 can be straightforward depressions, or punch through holes.

[0045] FIG. 3A illustrates a cross-sectional view of tabs 300 of another embodiment of a disposable element, such as disposable element 120 of FIG. 1. The tabs 300 include the receiving slot 134 for receiving the protrusions 118, but does not include the sloped surface 220 or the catch 230 of FIG. 2. Thus, the reusable element 110 is assembled relying on the interaction described in the foregoing between the protrusions 118 and the apertures 132 and the slots 134.

[0046] FIG. 3B illustrates a cross-sectional view of tabs 310 of another embodiment of a disposable element, such as the disposable element of FIG. 1. The tabs 310 include the sloped surface 220 and the catch 230, but do not include the receiving slot 134 or aperture 132. Thus, the sensor 100 is assembled relying on the interaction between the catch 230 and the surface of the reusable element 110.

[0047] FIG. 4A illustrates a cross-sectional view of the tabs 124 of FIG. 1 adhesively attached to the disposable element 120, according to an embodiment. In FIG. 4A, the tabs 124 are attached to the base 130 by adhesive. In a preferred arrangement, the tabs 124 share a common substrate 310, and an adhesive is applied between the substrate 310 and the base 130 to attach the tabs 124 to the disposable element 120.

[0048] FIG. 4B illustrates a cross-sectional view of the tabs 124 of FIG. 1 attached between layers of the disposable element 120 of FIG. 1, according to another embodiment. In FIG. 4B, the tabs 124 are attached between two layers 410 and 420 of the base 130. In a preferred arrangement, the two tabs 124 share a common substrate 310, and the substrate 310 is sandwiched between the layers 410 and 420.

[0049] A skilled artisan will recognize from the disclosure herein that the embodiments disclosed with reference to FIGS. 3 and 4 can be applied to one or both sets of the tabs 122 and 124. Moreover, a skilled artisan will recognize from the disclosure herein that the protrusions 118 can be attached to the reusable element 110 in a number of ways, such as, for example, attached by adhesive to the reusable element 110, manufactured as integral parts of the reusable element 110, sandwiched between a top layer and a bottom layer of the reusable element 110, or the like.

[0050] FIG. 5 illustrates a top view of the disposable element of FIG. 1, including an information element 510, contacts 520, and a breakable conductor 530, according to yet another embodiment. The contacts 520 can electrically connect with contacts on the flexible circuit of the reusable element 120, thereby adding the information element 510 and/or the breakable conductor 530 into the electric circuit of the sensor 100. As is understood in the art, the information element 510 can provide an indication of the sensor or patient type, operating characteristics or the like, or that the sensor 100 is from an authorized supplier. In an embodiment, the information element 510 is a resistive element made by depositing a conductive ink trace having a predetermined length and width. The information element 510 is disposed between contacts 520, which can also be implemented with conductive ink. As an artisan will recognize from the disclosure herein, many type of information elements can be included, such as, for example, passive or active elements, accessible memory elements, or the like.

[0051] The breakable conductor 530 is configured to break after a predetermined number of safe uses, thus providing quality control to ensure that the disposable element 120 is not over used. Various embodiments of information element 510, contacts 520, and breakable conductor 530 can be found in U.S. Pat. No. 6,377,829.

[0052] FIG. 6 illustrates a top view of an assembled sensor 600 that includes reusable and disposable elements, according to another embodiment. As shown in FIG. 6, the sensor 600 includes a reusable element 610 and a disposable element 620. The disposable element 620 includes straps 630 which position the reusable element 610 as described below. As shown in FIG. 6, the reusable element 610 can be similar to the reusable element 110 of the foregoing embodiments, generally including, for example, the more expensive components of the sensor 600. Moreover, disposable element 620 can be similar to the disposable element 120 of the foregoing embodiments, generally including for example, a disposable tape. The disposable tape can be virtually any suitable shape, and is shown in FIG. 6 in a generally "L" shaped configuration.

[0053] FIG. 6 also shows the reusable portion 610 including an extended narrow neck or notch 635 and a neck or notch 640, each narrower in width than the general width of the reusable element 610. The straps 630 attached to the disposable element 620 extend over the necks 635 and 640 to position the reusable element 610 with respect to and proximate the disposable element 620. The straps 630 provide for longitudinal movement between the elements of the sensor 600 similar to that disclosed in the foregoing.

[0054] FIG. 7A illustrates a simplified cross-sectional view of one of the straps 630 of the disposable element 620 of FIG. 6, according to an embodiment. The strap 630 may comprise a hook-and-loop device such as Velcro. The strap 630 may alternatively be an integral part of the structure of the disposable element 620. According to an embodiment, the strap 630 includes blocks 720 forming a gap 710 therebetween. As shown in FIG. 7A, an embodiment of the strap 620 can be removed from the disposable element 620 to permit the neck 630 of the reusable element 610 to be placed within the gap 710, as show in FIG. 7B an artisan will also recognize from the disclosure herein that the pliable material of the reusable portion 610 can alternatively or concurrently be compressed together and guided through attached straps 630.

[0055] According to one embodiment, the gap 710 is as wide or slightly wider than the necks 635 and 640, but narrower than other adjacent portions of the reusable element 610. Therefore, once placed in the gaps 710 and attached to the disposable element 620, the reusable element 610 can be moved along its longitudinal axis along the arrows A and B (FIG. 7B), but only to the extent that the necks 635 and 640 remain in the gaps 710.

[0056] In one embodiment shown in FIG. 6, the reusable element 610 includes the relatively "long" neck 635 shown near the top of the figure and a relatively "short" neck 640 shown near the bottom of the figure. Once the two necks 635 and 640 are placed within the straps 650, the long neck 635 allows the reusable element 610 to be moved along a longitudinal axis of the disposable element 120. In contrast, the short neck 640 prevents substantial movement along the longitudinal axis. Thus, similar to embodiments disclosed in the foregoing, the sensor 600 allows the neck 630 to self adjust during application to a measurement site, thereby avoiding damaging the reusable element 610.

[0057] FIG. 8 illustrates an exploded view of a disposable element 810 according to another embodiment of an optical sensor. The disposable element 810 includes a top layer 812, at least one attachment mechanism, tab, or positioning guide 814, and an adhesive, preferably transparent, tape layer 816.

FIG. 8 shows tabs **814** positioned in a back-to-back or opposing manner, as will be described in greater detail below.

[0058] FIG. 8 shows the top layer **812** as a generally L shaped tape or other pliable substrate including a first side **822** and a second side **824**, although an artisan will recognize from the disclosure herein that the virtually any shape can be used which provides attachment to tissue of a patient. According to an embodiment, the first side **822** includes a breakable element **826**, such as the conductive trace disclosed in U.S. Pat. No. 6,377,829, discussed in the foregoing. The breakable element **826** is included into the electrical circuit of the optical sensor through electrical leads or contacts **830** configured to electrically communicate with contacts of a reusable element of the optical sensor. Moreover, the first side **822** of the top layer **812** can optionally include an optical barrier layer **831**, such as a layer of material opaque or substantially opaque to light. The optical barrier layer **831** is generally designed to help prevent ambient light or light piping from interfering with the optical signals before or after they are passed through the tissue of the patient. In one embodiment, the barrier layer **831** comprises conductive trace material similar to that of the breakable element **826**.

[0059] According to an embodiment, the top layer **812** also includes a plurality of apertures **832**, which when the optical sensor is assembled, accept portions of the tabs **814** in a manner designed to provide proper placement, positioning, and support of the tabs **814**. However, an artisan will recognize from the disclosure herein that top layer **812** may use ink outlines combined with adhesive, or the like to help an assembler properly place and support the tabs **814** on the first side **822** of the top layer **812**.

[0060] Each tab **814** includes a base **836**, a signal aperture **838**, and grooves or slots **840**. The base **836** connects and supports each of two raised side members forming a generally U shaped structure. The signal apertures **838** comprise holes through which a properly positioned sensor element can emit or detect optical signals, and the raised side members each include the slot **840**, similar to the grooves **134** of the tabs **124** of FIG. 1. However, unlike FIG. 1, an embodiment of each of the slots **840** opens from one side of the raised side member, extends along the side member, and ends before the other side of the raised side member. Thus, the slot **840** accepts a protrusion or the like from an insertion side, and allows the protrusion to slide within the slot **840** to the end thereof, proximate a blocked side. Moreover, according to one embodiment, the blocked sides of the tabs **814** approximately adjacently oppose one another, such that protrusions inserted into the insertion sides, are at one point blocked from sliding closer than a predetermined distance from one another by the blocked sides.

[0061] According to one embodiment, the tape layer **816** comprises a transparent tape or other substrate layer. The tape layer **816** has a first side **846** and a second side **848**. When assembled, the first side **846** adheres to the top layer **812** and sandwiches the tabs **814** therebetween. The second side **848** includes an adhesive, hook-and-loop, similar or combination structure configured to secure the disposable element **810** to tissue of a patient.

[0062] FIG. 8 also shows the disposable element **810** including a cable connector **850**. The cable connector **850** generally provides for connection of the disposable element **810** to the remainder of a sensor, such as, for example, the reusable elements. According to the exemplary embodiment, the cable connector **850** comprises a plastic plate **852** includ-

ing mating portions **854**, such as, for example, raised pliable detents that each including a catch. However, an artisan will recognize from the disclosure herein any suitable mating mechanism can be used to connect the disposable element **810**, including virtually any mechanical-type mating mechanism, adhesives, hook-and-loop materials, combinations, or the like.

[0063] When the disposable element **810** is assembled as shown in FIG. 9, the bases **836** of the tabs **814** and the plate **852** communicate with the second side **824** of the top layer **812** and first side **846** of the tape layer **816** such that the bases **836** of the tabs **814** and the plate **852** are secured in position between the top layer **812** and the tape layer **816**. The raised side members of the tabs **814** extend through the plurality of apertures **832** in the top layer **812**, thereby aligning the signal apertures **838** with apertures in the top layer **812**. Moreover, as shown in the illustrated embodiment, the mating portions **854** of the cable connector **850** extend above the top layer **812**.

[0064] FIG. 10 shows a perspective view of an embodiment of a reusable element **1000**. The reusable element **1000** preferably includes a protective cover or coating **1004** covering a plurality of electronic sensor elements **1005** and a plurality of protrusions **1006**. The reusable element **1000** also includes a cable connection housing **1008**, and cord or cable **1010**. According to one embodiment, the protective cover **1004** comprises a soft material, such as a pliable rubber, plastic or the like, which preferably encapsulates and protects the electronic sensor elements **1005** from damage and advantageously protects caregivers and patients from sharp corners often associated with the reusable element **1000**, such as, for example, the protrusions **1006** or the sensor elements **1005**.

[0065] The protrusions **1006** extend from opposing sides of the reusable element **1000** in generally horizontal and opposing directions. To assemble the optical sensor, the protrusions are aligned with the outside-facing insertion side of each of the slots **840** of the disposable element **810**, shown in FIG. 8, and are slid toward one another on each side. As can be seen in FIG. 12, an embodiment of the assembled sensor includes one or more of the protrusions **1006** abutting the blocked side of one pair of the slots **810**, while the other protrusions **1006** are proximate the blocked side of the other pair of slots **810**, thereby allowing the reusable element **1000** to self adjust and avoid the detrimental stretching forces caused from application to a measurement site.

[0066] FIG. 10 also shows the cable connection housing **1008** including insertion slots **1012** configured to receive and mate with the mating portions **854** of the cable connector **850** shown in FIG. 8. When mated, the cable connection housing **1008** provides electrical contact between the electrical leads **830** of the disposable element **810** and the sensor circuitry.

[0067] FIG. 11 illustrates a perspective view of portions of the electronic sensor elements **1005** of the reusable element **1100** without the protective cover or coating **1004**. The elements **1005** include one or more energy emitters **1102**, such as one or more LEDs, an energy detector **1104**, such as a photodetector, electrically connected to a connector **1106** through a flexible circuit **1108**. The connector **1106** is configured to electrically communicate with the leads **830** of the disposable element **810** when the sensor is assembled. Moreover, the connector **1106** is configured to electrically attach the conductive traces of the flexible circuit **1108** to the conductors of the cable **1010**.



[0068] FIG. 12 shows a perspective view of an assembled sensor 1200. The sensor 1200 includes the reusable element 1000, including the disposable element 810 connected to the connection housing 1008 through the mating portions 854 of the cable connector 850, such that the breakable element 826 is part of the electrical circuitry of the sensor. In one embodiment, the sensor is inoperative or otherwise provides an indication of overuse or misuse when the breakable element 826 is broken or otherwise becomes an open circuit.

[0069] As disclosed, when connected to the disposable element 810, the protrusions 1006 have a limited range of motion within the tabs 814, thereby giving the reusable element 1000 a limited range of longitudinal motion independent of the disposable element 810. As described with other embodiments, this longitudinal motion allows the disposable element 810 and the reusable element 1000 to flex independently as the sensor 1200 is attached to tissue of a user, such as a finger, toe, ear, or the like, thereby avoiding damage or unnecessarily harmful wear of the reusable element 1000. Also, this limited range of motion ensures at least approximate proper alignment of various sensor components.

[0070] After use, as with embodiments described above, the disposable element 810 is removed and discarded, while the reusable element 812 can be sterilized and reused.

[0071] Although the foregoing invention has been described in terms of certain preferred embodiments, other embodiments will be apparent to those of ordinary skill in the art from the disclosure herein. For example, although the above sections describe a reusable element fitted with protrusions or necks and a disposable element fitted with apertures and receiving slots or straps, the embodiments can be reversed having, for example, the reusable element fitted with the apertures, receiving slots, or straps, and with the disposable element fitted with the protrusions or necks.

[0072] Additionally, other combinations, omissions, substitutions and modifications will be apparent to the skilled artisan in view of the disclosure herein. Accordingly, the present invention is not intended to be limited by the reaction of the preferred embodiments, but is to be defined by reference to the appended claims.

What is claimed is:

1. A reusable portion of a noninvasive optical oximetry sensor, the sensor when assembled with a disposable portion being configured to attach to a measurement site of a monitored patient and to output signals responsive to light absorption by tissue at said measurement site, said signals including sufficient information for an oximeter to determine one or more physiological parameters of the patient including at least one of oxygen saturation or pulse rate, the reusable portion comprising:

- a flex circuit;
- a light source;
- one or more detectors configured to detect light from said light source after attenuation by said tissue and output said signals responsive to said detected light;
- a plurality of conductors proximate said flex circuit, some of said conductors communicating with said light source and others of said conductors communicating with said one or more detectors;
- a protective coating encasing at least said light source, said one or more detectors and at least some of said conductors and some of said flex circuit; and
- tabs proximate at least said light source and said one or more detectors, said tabs configured to mate with slots of

said disposable portion where at least some of said tabs can move with respect to a corresponding mated slot to self-adjust the disposable portion and the reusable portion with respect to one another when the disposable portion is applied to said patient after sensor assembly.

2. The reusable portion of claim 1 wherein said protective coating comprises a flexible protective coating.

3. The reusable portion of claim 2 wherein the flexible protective coating comprise a rubber or plastic material.

4. The reusable portion of claim 1, wherein said protective coating includes apertures providing a light path from said light source or said detector to said measurement site.

5. The reusable portion of claim 1, wherein at least some of said tabs slide laterally along corresponding ones of said slots until vertical movement of said tab is reduced when said sensor is applied to said patient.

6. The reusable portion of claim 1, wherein said tabs mate with said slots comprising a rigid material.

7. A method of assembling a noninvasive optical oximetry sensor, the method comprising:

providing a disposable element of a sensor including an attachment mechanism configured to removably attach to a patient at a measurement site;

providing a reusable element of said sensor, the reusable element including a flex circuit, a light source, one or more detectors configured to detect light from said light source after attenuation by said tissue and output said signals responsive to said detected light, a plurality of conductors proximate said flex circuit, some of said conductors communicating with said light source and others of said conductors communicating with said one or more detectors, a protective coating encasing at least said light source, said one or more detectors and at least some of said conductors and some of said flex circuit, and tabs proximate at least said light source and said one or more detectors, said tabs configured to mate with slots of said disposable element where at least some of said tabs can move with respect to a corresponding mated slot to self-adjust the disposable element and the reusable element with respect to one another when the disposable element is applied to said patient after sensor assembly; and

positioning the tabs within the slots.

8. The method of claim 7, wherein said providing said reusable element including said protective coating comprises providing said reusable element including a flexible protective coating.

9. The method of claim 8, wherein said providing said reusable element including said flexible protective coating comprises providing said reusable element including a flexible protective coating comprising rubber.

10. The method of claim 8, wherein said providing said reusable element including said flexible protective coating comprises providing said reusable element including a flexible protective coating comprising plastic.

11. The method of claim 7, wherein said providing said reusable element, including said protective coating comprises providing said reusable element including said protective coating having apertures providing a light path from said light source or said detector to said measurement site.

12. The method of claim 7, wherein said providing said reusable element, including said tabs comprises providing said reusable element including at least some of said tabs configured to slide laterally along corresponding ones of said slots until vertical movement of said tab is reduced when said sensor is applied to said patient.

\* \* \* \* \*

专利名称(译)	无创血氧测定光学传感器，包括一次性和可重复使用的元件		
公开(公告)号	<a href="#">US20120310061A1</a>	公开(公告)日	2012-12-06
申请号	US13/585669	申请日	2012-08-14
[标]申请(专利权)人(译)	AL ALI AMMAR ABDUL HAFIZ亚瑟尔		
申请(专利权)人(译)	AL-ALI AMMAR 阿卜杜勒·哈菲兹亚瑟尔		
当前申请(专利权)人(译)	AL-ALI AMMAR 阿卜杜勒·哈菲兹亚瑟尔		
[标]发明人	AL ALI AMMAR ABDUL HAFIZ YASSIR		
发明人	AL-ALI, AMMAR ABDUL-HAFIZ, YASSIR		
IPC分类号	A61B5/1455 B23P11/00 A61B5/0205 A61B5/00		
CPC分类号	A61B5/14552 A61B5/6826 Y10T29/49826 A61B5/6838 A61B5/6833		
其他公开文献	US8781549		
外部链接	<a href="#">Espacenet</a> <a href="#">USPTO</a>		

#### 摘要(译)

脉搏血氧饱和度传感器包括可重复使用和一次性元件。为了组装传感器，可重复使用元件的构件与一次性元件的组装机构配合。组装好的传感器在可重复使用和一次性元件之间提供独立的运动。

