



US 2004/0116992A1

(19) **United States**(12) **Patent Application Publication****Wardle et al.**(10) **Pub. No.: US 2004/0116992 A1**(43) **Pub. Date: Jun. 17, 2004**(54) **CARDIOVASCULAR ANCHORING DEVICE
AND METHOD OF DEPLOYING SAME****Publication Classification**(76) Inventors: **John L. Wardle**, San Clemente, CA
(US); **Neal L. Eigler**, Pacific Palisades,
CA (US)(51) **Int. Cl.⁷** **A61B 5/00**; A61N 1/05;
A61K 9/22; A61B 5/04(52) **U.S. Cl.** **607/116**; 600/373; 600/323;
604/891.1; 600/311

Correspondence Address:

KNOBBE MARTENS OLSON & BEAR LLP
2040 MAIN STREET
FOURTEENTH FLOOR
IRVINE, CA 92614 (US)(57) **ABSTRACT**

An anchoring device and a delivery method thereof can effectively provide a means for securing an implant to a wall of an internal organ within a patient in a variety of clinical applications. In one embodiment, an anchoring device used to retain a cardiac pressure measurement device is provided. The device is implanted in the body by deforming it to a small cross section profile, sliding it through a low profile delivery device and ejecting from the delivery device at a targeted site. The anchoring mechanism, when ejected from the delivery device, reverts back to pre-formed configuration and engages opposite sides of an organ wall, thereby anchoring the implant in the organ wall.


(21) Appl. No.: **10/672,443**(22) Filed: **Sep. 26, 2003****Related U.S. Application Data**(60) Provisional application No. 60/413,758, filed on Sep.
26, 2002.

FIG. 1





FIG. 2









FIG. 7





FIG. 8

FIG. 9




FIG. 11




FIG. 10





FIG. 12






FIG. 13















FIG. 14

























CARDIOVASCULAR ANCHORING DEVICE AND METHOD OF DEPLOYING SAME

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This application claims the benefit of U.S. Provisional Patent Application Serial No. 60/413,758, which was filed on Sep. 26, 2002 and which is incorporated herein by reference.

BACKGROUND

[0002] 1. Field of the Invention

[0003] This invention relates generally to cardiovascular anchoring devices and methods of deploying the same.

[0004] 2. Description of the Related Art

[0005] Heart failure is a cardiovascular condition in which the heart fails to sufficiently supply the body with the oxygen rich blood the body requires, either at exercise or at rest. Congestive heart failure (CHF) is heart failure accompanied by a build-up of fluid pressure in the pulmonary blood vessels that drain the lungs. Transudation of fluid from the pulmonary veins into the pulmonary interstitial spaces, and eventually into the alveolar air spaces, is called pulmonary edema, and can cause shortness of breath, hypoxemia, acidosis, respiratory arrest, and death.

[0006] It is estimated that about four million people in the United States suffer from various degrees of heart failure. Although CHF is a chronic condition, the disease often requires acute hospital care. Patients are commonly admitted for acute pulmonary congestion accompanied by serious or severe shortness of breath. Acute care for CHF accounts for the use of more hospital days than any other cardiac diagnosis, and consumes in excess of seven and one-half billion dollars in the United States annually.

[0007] It is far more cost effective, and much better for the patient's health, if chronic CHF can be managed and controlled by the routine administration of appropriate drug therapy rather than by hospital treatment upon the manifestation of acute symptoms. Patients with chronic CHF are typically placed on triple or quadruple drug therapy to manage the disease. The drug regimen commonly includes diuretics, vasodilators such as ACE inhibitors or A2 receptor inhibitors, and inotropic agents usually in the form of cardiac glycosides such as Digoxin. Patients may also be placed on beta blockers such as Carvedilol.

[0008] As with all drugs, these agents must be taken in doses sufficient to ensure their effectiveness. Problematically, however, over-treatment can lead to hypotension, renal impairment, hyponatremia, hypokalemia, worsening CHF, impaired mental functioning, and other adverse conditions. Adding to the challenge of maintaining proper drug dosage is the fact that the optimal dosage will depend on diet, particularly salt and fluid intake, level of exertion, and other variable factors. Adding further to the problem of managing this condition is the fact that patients frequently miss scheduled doses by forgetting to take pills on time, running out of medications, or deciding to stop medications without consulting their physician. It is important, therefore, that the patient's condition be monitored regularly and thoroughly, so that optimal or near optimal drug therapy can

be maintained. This monitoring is itself problematic, however, in that it requires frequent visits with a caregiver, resulting in considerable inconvenience and expense.

SUMMARY OF THE INVENTION

[0009] In view of the above discussion, it is desirable to provide a system by which a patient's congestive heart failure can be monitored routinely or continuously with minimal attendance by a caregiver, and then only when actually required. It is also desirable that such a system include a means for communicating diagnostic information not only to the physician but to the patient as well, so that the patient can continue or modify his own drug therapy appropriately and generally without the direct intervention of a physician. One example of such a system is described in U.S. Pat. No. 6,328,699 to Eigler et al., herein incorporated by reference (referred to herein as "the Eigler patent"). The systems and methods described in several embodiments of the Eigler patent generally involve implantation of a pressure sensor within a portion of the patient's heart (such as the left atrium) in order to continuously monitor a fluid pressure in the portion of the heart.

[0010] Notwithstanding the particular advantages of the systems and methods described in the Eigler patent, there remains room for improvement to the systems and methods used for anchoring a sensor to a wall of the patient's heart (such as the atrial septum).

[0011] Preferred embodiments of the present invention provide an anchoring device and a method of delivery which can effectively be used to deploy an anchoring mechanism for a variety of clinical applications. In one embodiment, an anchoring device is configured to cross the septum between the right and left atrium and trap itself between the two chambers such that a pressure sensing member is exposed to the left atrium. The device is configured in a manner that will allow it to position the pressure sensing member at a desired location relative to the septal wall while conforming to anatomical variations.

[0012] According to one embodiment, radiopaque markers can be provided on the anchor and/or the delivery and retrieval apparatus. One advantage of such markers is to enable fluoroscopic guidance of the devices during delivery and retrieval procedures.

[0013] According to one embodiment, an implantable device is provided. The device of this embodiment comprises a proximal anchor having one or more helical legs extending between a proximal ring and a distal ring. The device also comprises a distal anchor having one or more legs. The proximal and distal anchors of this embodiment are preferably configured to be movable between a collapsed delivery position and an expanded position in which the proximal and distal anchors secure the implant to a wall of an organ within a patient. The device further includes a diagnostic and/or therapeutic implant configured to be supported by the proximal and distal anchors. In one embodiment, the diagnostic tool includes apparatus operable to measure one or more physiological parameters. In one embodiment, the diagnostic tool includes apparatus operable to measure pressure, oxygen levels, or electrical activity, or some combination thereof. In one embodiment, the therapeutic tool comprises apparatus operable to deliver one or more pharmaceutical agents to the patient. In another

embodiment, the therapeutic tool includes apparatus operable to deliver one or more electrical signals or pulses to the patient. In one embodiment, the implant comprises a pressure sensor (or pressure transducer). In other embodiments, the implant includes, but is not limited to, sensors, sensing and stimulating electrodes, ultrasound transducers, drug delivery systems, pacing leads, electrocardiogram leads, oxygen partial pressure sensors, oxygen saturation sensors, and any other device that one desires to securely anchor to a wall of an internal organ.

[0014] Another embodiment provides a system for diagnosing and/or treating a condition in a patient. The system of this embodiment comprises an implant configured to be implanted within a patient, a proximal anchor comprising at least one helical leg configured to expand from a compressed state to a relaxed state, and a distal anchor comprising at least one leg configured to expand from a compressed state to an expanded state. The proximal anchor and the distal anchor of this embodiment are preferably configured to sandwich an atrial septum wall (or the left atrial free wall, the pulmonary vein wall, or any other suitable wall of a heart) between the proximal anchor leg and the distal anchor leg and to support the implant in the septum wall. The system of this embodiment also preferably comprises a delivery catheter configured to deploy the sensor, the proximal anchor, and the distal anchor in the septum wall. In one embodiment, the system is particularly suited to monitoring congestive heart failure in the patient.

[0015] Another embodiment provides a system for monitoring a patient for congestive heart failure comprising an implantable pressure sensor and a means for contacting a proximal wall and a distal wall of an organ to anchor said pressure sensor to the organ wall. The system can further comprise a means for delivering said implantable sensor and said means for contacting to said organ wall. In another embodiment, the system further comprises a means for retrieving said implantable pressure sensor from the organ wall.

[0016] In another embodiment, a method of monitoring congestive heart failure in a patient is provided. The method of this embodiment comprises providing a pressure sensor secured to a proximal anchor and a distal anchor, and delivering the pressure sensor to a hole in an atrial septum of the patient's heart. The method further comprises deploying the pressure sensor with the proximal anchor on a proximal side of the septum, and the distal anchor on a distal side of the septum; monitoring a fluid pressure in the left atrium of the patient's heart.

[0017] Another embodiment provides a method of monitoring congestive heart failure within a patient. The method of this embodiment comprises providing an implantable pressure sensor and coupling said implantable pressure sensor to a means for anchoring said pressure sensor in an organ wall. The method further comprises delivering said pressure sensor and said means for anchoring to said organ wall, and causing said means for anchoring said pressure sensor in said organ wall to expand, thereby capturing said organ wall and anchoring said pressure sensor thereto. In another embodiment, the method can further comprise removing said pressure sensor and said means for anchoring from said organ wall. In one embodiment, said removing is performed by introducing a means for retrieving said means for anchoring.

[0018] According to still another embodiment, a method of anchoring a device in the heart of a patient is provided. The method includes providing an implantable cardiac anchoring device comprising a proximal anchor having at least one helical leg and a distal anchor having at least one linear leg. The method comprises attaching an implantable tool, (referred to herein as an "implant"), to the implantable cardiac anchoring device, positioning a tubular delivery catheter in a wall of a patient's heart, and inserting the implant and the implantable cardiac anchoring device into the tubular delivery catheter. The method further includes deploying the sensor and the implantable cardiac anchoring device such that the sensor is retained in a transverse orientation relative to the wall.

[0019] According to further embodiments, methods and apparatus are also provided for engaging and removing the anchoring mechanism from its deployed position. According to one embodiment, a retrieval device is configured to retrieve a cardiac anchoring device from a position deployed in a wall of an organ within a patient. The retrieval device of this embodiment comprises a retrieval head having a plurality of grasping hooks extending from a distal end thereof, a ribbon of sufficient length to extend from a retrieval location within a patient to a location outside of a patient. The grasping hooks of this embodiment are preferably configured to engage a proximal ring of a proximal anchor.

[0020] According to another embodiment, a method is provided for retrieving a cardiac anchoring device from a heart of a patient using a retrieval device. The method of this embodiment comprises placing a retrieval device in a delivery catheter. The retrieval device placed in the catheter comprises a retrieval head with a plurality of distally-extending grasping hooks and a control ribbon attached to the retrieval device. The method further comprises guiding said delivery catheter into a position adjacent a sensor device anchored to a wall of the patient's heart. The retrieval device is then engaged on a proximal ring of a proximal anchor secured to the sensor device, and the proximal ring of the proximal anchor is pulled into the delivery catheter. The method is continued by holding the sensor device stationary while pulling the retrieval device, the proximal ring of the proximal anchor and the delivery catheter proximally, thereby returning an anchor leg of said proximal anchor to a compressed position. The delivery catheter is advanced distally while holding the proximal anchor and the sensor device stationary in order to compress at least one expanded leg of the distal anchor attached to the sensor device. Once the anchors are compressed, the sensor device, the proximal anchor and the distal anchor are all pulled completely into the lumen of the delivery catheter, the delivery catheter is removed from the patient.

BRIEF DESCRIPTION OF THE DRAWINGS

[0021] FIG. 1 is a perspective view of one embodiment of a distal anchor in a compressed state for deployment in a patient.

[0022] FIG. 2 is a perspective view of the distal anchor of FIG. 1 in an expanded state.

[0023] FIG. 3 is a perspective view of one embodiment of a proximal anchor in a compressed state.

[0024] FIG. 4 is a perspective view of the proximal anchor of FIG. 3 in an expanded state.

[0025] FIG. 5 is a side view of the proximal anchor of FIG. 4.

[0026] FIG. 6 is a front view, looking proximally at the proximal anchor of FIG. 5.

[0027] FIG. 7 is a front view, looking proximally at a distal anchor and a sensor mounted to the distal anchor.

[0028] FIG. 8 is a cross-sectional view of the distal anchor and sensor of FIG. 7 taken through line 8-8.

[0029] FIG. 9 is a detail view of a portion of the distal anchor and sensor of FIG. 8, taken at line 9-9.

[0030] FIG. 10 is a perspective view of one embodiment of an assembly of a proximal anchor, a distal anchor, and a sensor.

[0031] FIG. 11 is a detail view of a portion of the assembly of FIG. 10, taken through line 11-11.

[0032] FIG. 12 is an exploded view of the proximal anchor, distal anchor and sensor of FIG. 10.

[0033] FIG. 13 is a perspective view of an alternative embodiment of a distal anchor in an expanded state.

[0034] FIG. 14 is a perspective view of an alternative embodiment of the proximal anchor.

[0035] FIG. 15 is a perspective view of a delivery catheter with a portion of a distal anchor visible at the distal end of the delivery catheter.

[0036] FIG. 16 is a perspective view of the assembly of FIG. 15 shown with the delivery catheter removed to show detail.

[0037] FIG. 17 is a perspective view of a distal anchor and a sensor deployed on a distal side of an atrial septum wall.

[0038] FIG. 18 is a perspective view of the distal anchor and sensor of FIG. 17 with the delivery catheter further retracted.

[0039] FIG. 19 is a perspective view illustrating a delivery catheter deploying an anchor and sensor assembly as viewed from a proximal side of an atrial septum wall.

[0040] FIG. 20 is a side view of an anchor and sensor assembly deployed and anchored to a thin atrial septum wall (shown in cross-section).

[0041] FIG. 21 is a side view of an anchor and sensor assembly deployed and anchored to a thicker atrial septum wall (shown in cross-section).

[0042] FIG. 22 is a perspective view of one embodiment of a retrieval device for retrieving the anchor and sensor assembly.

[0043] FIG. 23 is a detail view of a portion of the retrieval device of FIG. 22, taken through line 23-23.

[0044] FIG. 24 is a side view of one embodiment of a retrieval device.

[0045] FIG. 25 is a detail view of the retrieval head of the retrieval device of FIG. 24.

[0046] FIG. 26 is a side view of one embodiment of a retrieval device.

[0047] FIG. 27 is a detail view of the retrieval head of the retrieval device of FIG. 26.

[0048] FIG. 28 is a perspective view of an alternative embodiment of a retrieval device.

[0049] FIG. 29 is a detail view of a distal portion of the retrieval device of FIG. 28, taken through line 29-29.

[0050] FIG. 30 is a detail view of a proximal portion of the retrieval device of FIG. 28, taken through line 30-30.

[0051] FIG. 31 is a side perspective view illustrating a retrieval device positioned for retrieving the anchor and sensor assembly.

[0052] FIG. 32 is a detail view of the retrieval device and the anchor and sensor assembly of FIG. 31 taken through line 32-32.

[0053] FIG. 33 is a side perspective view of the retrieval device and the anchor and sensor assembly of FIG. 31, shown with the proximal anchor partially withdrawn into the retrieval catheter.

[0054] FIG. 34 is the side perspective view of FIG. 33 shown with the catheter removed to show detail.

[0055] FIG. 35 is a detail view of a portion of the retrieval device of FIG. 34, taken through line 35-35.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0056] The following embodiments are described in relation to the placement of an anchoring and pressure measurement device within an atrial septum wall. The skilled artisan will recognize that certain aspects of the present invention can be applied to other applications as well. For example, the anchor devices described herein can be configured to anchor any suitable diagnostic and/or therapeutic implant to a wall of an organ within a patient. Therefore, it is intended that the scope of the present invention not be limited by the particular embodiments described below, but should be determined only by a fair reading of the claims.

[0057] Throughout the following description, the terms "proximal" and "distal" are used to describe relative positions, locations and/or orientations of various components. As used herein, the term "distal" is used in its ordinary sense, and generally refers to objects and locations that are further along a trans-vascular path. Similarly, the term "proximal" is used in its ordinary sense, and refers without limitation, to objects and locations that are closer along a trans-vascular path to an operator of a trans-vascular device. For example, in some embodiments the most proximal end of a catheter is the end that is operated by a clinician performing a procedure within a patient with the catheter. Similarly, in such embodiments the distal-most end of a catheter is the end placed furthest into the body of the patient and furthest from the clinician performing the procedure. The terms "proximal" and "distal" are used herein with reference to certain preferred embodiments of the orientation of certain components during a procedure. The skilled artisan will recognize however, that in alternative embodi-

ments the directions of “proximal” and “distal” as used herein may be reversed with respect to a single component used in a similar procedure.

[0058] Turning now to the figures, embodiments of cardiovascular anchoring devices for use in anchoring an implantable diagnostic or therapeutic implant to an organ wall (such as an atrial septum wall) will now be described. In one embodiment, the diagnostic tool comprises apparatus operable to measure one or more physiological parameters. In one embodiment, the diagnostic tool comprises apparatus operable to measure pressure, oxygen levels, and/or electrical activity. In one embodiment, the therapeutic tool comprises apparatus operable to deliver one or more pharmaceutical agents to the patient. In another embodiment, the therapeutic tool includes apparatus operable to deliver one or more electrical signals or pulses to the patient. Implants also include, but are not limited to, sensors, sensing and stimulating electrodes, ultrasound transducers, drug delivery systems, pacing leads, electrocardiogram leads, oxygen partial pressure sensors, oxygen saturation sensors, and any other device that one desires to securely anchor to a wall of an internal organ. In some embodiments, the implant comprises a sensor, and in one particular embodiment, the implant is a pressure sensor or transducer. The figures included herein illustrate a straight device and deployment apparatus for the purpose of demonstration. However, one skilled in the art will understand that, in use, the delivery catheter and contained components will typically be substantially flexible or may assume other non-straight shapes. For example, a delivery catheter can be configured to include a pre-shaped curve or a pre-shaped stylet in order to facilitate navigation of a patient's tortuous vasculature. As will also be clear to the skilled artisan, the flexibility of certain components will be particularly advantageous for navigation through tortuous anatomy.

[0059] FIGS. 1-14 illustrate embodiments of an anchor and sensor assembly 100 comprising a distal anchor 110 and a proximal anchor 112 configured to secure a sensor 120 to a wall of an internal organ (such as a left atrium of a heart) within a patient. The proximal and distal anchor components 110 and 112 are configured to be compressed to a delivery state such that they can be placed within a tubular delivery catheter. The anchors 110 and 112 are further configured such that when they are released from their compressed state, they will relax to assume a preformed, expanded configuration in which they engage opposite sides of a septum wall 210 (e.g. see FIGS. 20 and 21) in order to support the sensor 120 in an operative position.

[0060] Many of the embodiments of implantable devices shown and described herein are preferably configured to be deployed via a tubular, flexible delivery catheter that can be guided either alone or over a guidewire to a delivery location within a patient. A delivery catheter for use in delivering and deploying an implantable device preferably comprises an internal diameter that is at least as large as the outer diameter of the distal and proximal anchors in their compressed states. In some embodiments, a delivery catheter can be configured to be sufficiently large in diameter to allow the catheter to be filled with a continuous column of fluid. This advantageously allows for simultaneous monitoring of a fluid pressure at the distal end of the catheter through the continuous fluid column surrounding the anchoring system in the catheter. Such an arrangement would also advantageously allow

for the injection of a radiographic contrast medium through the delivery catheter in order to determine the precise location of the catheter tip in the cardiovascular system. The skilled artisan will recognize that other embodiments of delivery catheters incorporating additional fluid-carrying lumens can also be used to deliver an implantable anchoring device.

[0061] In order to allow the proximal and distal anchors 110 and 112 to self-expand from a compressed state to an expanded state, they are preferably made from materials that exhibit superelastic and/or shape memory characteristics. Alternatively, the anchors could be made from other non-superelastic or non-shape memory materials as desired. For example, suitable materials for fabrication of the proximal and distal anchors include, but are not limited to, nickel titanium alloys (NiTi or NITINOL), cobalt-chromium alloys, stainless steel, ELGILOY, MP35N or other biocompatible, superelastic, and/or shape memory materials that are well known to those skilled in the art of clinical medical devices. The anchors can be made by any suitable process appropriate for a particular material. For example, the anchors could be molded, machined, laser cut, etc as desired.

[0062] FIGS. 1 and 2 illustrate one embodiment of a distal anchor 110 in a compressed state and an expanded state respectively. The distal anchor 110 generally comprises a circular base portion 122 with a plurality of legs 124 extending distally therefrom. In the illustrated embodiment, the legs 124 include slots 126 to advantageously promote tissue overgrowth in a deployed position, which will advantageously aid in securement of the device to the septum wall. In alternative embodiments, the legs 124 can be solid. As shown, the distal anchor 112 also comprises struts or locking tabs 130 configured to engage a portion of the sensor 120 as will be further described below. In its compressed state, as shown in FIG. 1, the distal anchor 124 occupies a substantially cylindrical shape, thereby allowing it to be placed within a cylindrical, tubular delivery catheter or delivery sheath.

[0063] In an expanded shape, as shown in FIG. 2, the legs 124 of the distal anchor 110 bend outwards and proximally. In one embodiment, the legs 124 bend outwards until they are substantially perpendicular to the longitudinal axis of the cylindrical base portion 122. In alternative embodiments, the legs bend proximally until they are oriented at more than 90° to the longitudinal axis of the cylindrical base 122 as shown for example in FIG. 8. In such embodiments, the angle θ (which represents the amount beyond perpendicular to the longitudinal axis that the legs 124 can bend) can be between about 0° and about 20°. In some preferred embodiments, the angle θ can be between about 5° and about 15°, and in one specific preferred embodiment, the angle θ can be about 10°. In one preferred embodiment, the angle θ will preferably be reduced to zero degrees when the distal anchor 110 is deployed on a distal side of a septum wall 210 (see FIG. 20) with a proximal anchor 112 on the proximal side of the wall 210 due to the opposing force of the proximal anchor 112. Thus, in a preferred embodiment, the angle θ is selected along with a spring constant of the distal anchor legs 124 such that an opposing force applied by the proximal anchor 112 through a septum wall of a particular thickness (as will be further described below) will cause the angle θ to be

substantially reduced to zero or to deflect a small amount in the distal direction so as to conform with a substantially concave left atrial surface.

[0064] FIGS. 3-6 illustrate one embodiment of a proximal anchor 112 in compressed (FIG. 3) and expanded (FIGS. 4-6) states. In its compressed state, the proximal anchor 112 occupies a substantially cylindrical space such that it can be placed in a cylindrically tubular delivery catheter. The proximal anchor 112 generally includes a proximal ring 140 and a distal ring 142 with a plurality of legs 144 extending therebetween. The proximal anchor 112 can include any number of anchor legs 144 as desired. For example, in the embodiment illustrated in FIG. 3, the proximal anchor comprises six anchor legs 144. Alternatively, the proximal anchor 112 can include a greater or lesser number of anchor legs 144. The proximal anchor 112 can also include struts or locking tabs 150 which can be used to secure the sensor 120 to the proximal anchor as will be further described below.

[0065] In the embodiment of FIG. 3, the anchor legs 144 are configured to follow a helical path between the proximal ring 140 and the distal ring 142. In one preferred embodiment, the helical path of the anchor legs 144 passes through 360 degrees between the proximal ring 140 and the distal ring 142. In alternative embodiments, the proximal anchor 112 can be longer and/or the legs 144 can pass through 720 degrees. In general, it is desirable that the legs pass through a substantially whole number of complete circles between the proximal and distal rings 140, 142. This configuration allows the proximal anchor 112 to negotiate the tortuous path that is typically encountered during delivery of the device to a desired location within a patient. The spiral or helical shape of the proximal anchor is particularly advantageous because this configuration equalizes bending stresses experienced by the anchor legs 144 in order to maintain an internal lumen (typically with a circular cross-section) of the proximal anchor 112 as the device is navigated through a tortuous path. Additionally, the illustrated configuration advantageously increases flexibility of the proximal anchor 112 and reduces its diameter to allow the anchor to be more effectively negotiated through a tortuous anatomy without damaging the device or injuring the patient.

[0066] FIGS. 4-6 illustrate the proximal anchor 112 in its expanded state. As shown, proximal anchor 112 preferably assumes a substantially "mushroomed" shape in its expanded state. In moving between the compressed and expanded states (assuming the distal ring 142 is held substantially stationary), the anchor legs 144 preferably unwind and buckle outwards and distally relative to the proximal ring 142. As shown, the proximal anchor 112 preferably "unwinds" such that the proximal ring 140 rotates relative to the distal ring 142 as the anchor 112 moves between its compressed and expanded states. The amount of rotation of the proximal ring relative to the distal ring will typically be a function of the final resting distance between the proximal ring and the distal ring.

[0067] In their fully expanded state, the anchor legs 144 preferably bend outwards and distally until each leg 144 forms a loop 152 with a distal most edge 154 that is positioned substantially distally from the distal edge of the distal ring 142. In some preferred embodiments, the anchor assembly can be configured such that, in free space (i.e. with

no tissue or material between the proximal and distal anchors), the distal edge 154 of the proximal anchor leg loops 152 and the proximal tissue-contacting surface of the distal anchor 110 can actually overlap by up to about 0.06". In some preferred embodiments the overlap can be between about 0.03" and about 0.05", and in one specifically preferred embodiment, the distance is about 0.04". In some embodiments (as shown in FIG. 5), the distance 156 between the distal edge 154 of the proximal anchor leg loops 152 and the distal edge of the distal ring 142 of the proximal anchor can be between about 0.040" and about 0.070". In some preferred embodiments, the distance 156 is between about 0.050" and about 0.060", and in one particular preferred embodiment, the distance 156 is about 0.054". By providing the proximal and distal anchor legs 144 and 124 with sufficient resilience that they relax to overlapping positions, it can be assured that the assembly will be able to securely anchor to even the thinnest of septum walls.

[0068] FIGS. 7-9 illustrate the distal anchor 110 mounted to a sensor 120. In the illustrated embodiment, the sensor 120 is a pressure sensor having a substantially cylindrical body 160 with a pressure sensing face 162 at its distal end, and a lead-attachment interface 164 at its proximal end. In one preferred embodiment, as shown, the lead-attachment interface comprises a series of annular notches which can be engaged by a tightly-wound coil to secure the electrical lead. In some embodiments, a lead-attachment mechanism can be welded in place (such as by laser welding) on the sensor 120 in order to provide a more secure connection. In another embodiment, the lead-attachment interface 164 can comprise screw threads. Alternatively, the skilled artisan will recognize that any number of suitable alternative interfaces could also be used. Additional details of a suitable pressure sensor are provided, for example, in U.S. Pat. No. 6,328,699 to Eigler et al. ("the Eigler patent"), which is incorporated herein by reference and made part of the present disclosure. In alternative embodiments, the sensor 120 can be configured to sense and/or monitor any desired parameter within a patient.

[0069] In the embodiment of FIGS. 7-9, the distal anchor 110 is secured to the sensor 120 by struts or locking tabs 130 on the anchor, which engage an angled annular groove 170 which circumscribes a distal portion of the sensor 120. The locking tabs 130 extending distally from the distal anchor 110 (as shown in FIGS. 1 and 2) are preferably bent slightly radially inwards such that they will engage the distal annular groove 170 in the sensor as shown in the detail view of FIG. 9. Similarly, a proximal annular groove 172 is provided to be engaged by the locking tabs 150 of the proximal anchor 112 (shown in FIG. 3). The anchor-to-sensor attachment system illustrated in FIGS. 7-9 allows the anchors 110 and 112 to rotate about the sensor 120. In some situations it is desirable to prevent rotation of the anchors relative to the sensor 120 by spot-welding the proximal and/or distal anchors to an annular flange 174 provided on the sensor 120. Alternatively, in place of an annular groove, the sensor could comprise angled notches for receiving the locking tabs in a single rotational orientation on the sensor 120. Alternatively still, other attachment systems can also be used, such as welds, adhesives, and other mechanical fasteners.

[0070] FIG. 8 illustrates a cross-sectional view of the sensor 120 attached to a distal anchor. In some embodiments, it may be desirable to vary the distance 166 between

a distal most edge of a distal anchor leg **124** (in an expanded state as shown) and the pressure sensing face **162** of the sensor **120**. In one preferred embodiment, the distance **166** is preferably zero, i.e. the pressure sensing face **162** is preferably substantially co-planar with the distal most point of a deployed distal anchor leg **124**. Such a configuration will preferably advantageously place the pressure sensing face **162** substantially flush with the atrium wall, thereby reducing the hemodynamic effect experienced by the sensor **120**. In alternative embodiments, it may be desirable that the sensor **120** be moved distally such that the pressure sensing face extends distally outwards from the distal anchor. Alternatively still, it may be desirable to support the sensor **120** within the distal anchor **110** such that the sensor face **162** is recessed within the distal anchor **110**. The location of the sensor face relative to the distal anchor can be varied by changing a location of the distal annular groove **170** and/or by varying a size of the locking tabs **130**.

[0071] FIGS. **10-14** illustrate an alternative embodiment of an anchor and sensor assembly **100** wherein the components are attached to one another with interlocking mechanical fasteners. As shown, the proximal anchor **112**, the distal anchor **110**, and the sensor **120** include interlocking structures configured to mechanically interconnect the assembly components in such a way as to limit both axial and rotational movement of the components relative to one another.

[0072] The distal anchor of FIGS. **10-12** comprises a plurality of fingers **180** which extend proximally from the cylindrical base portion **122**. As shown, each finger **180** can include a narrow neck section **182** and a wider proximal tab section **184**. The proximal anchors **112** can include correspondingly shaped slots **186** in the distal ring **142** to receive the fingers **180**. The sensor **120** can also include corresponding interlocking structures configured to engage structures on the distal and/or proximal anchors **110, 112**. As shown the sensor **120** can include raised sections **188** around the circumference of the cylindrical body **160**. The raised sections **188** can be positioned so as to leave gaps **190** for receiving the neck sections **182** of the fingers **180**. The raised sections **188** can be machined into the cylindrical body **160** of the sensor, or they can comprise independent segments welded, adhered, or otherwise secured to the cylindrical body **160** of the sensor **120**. The components can be assembled as shown in FIG. **10** to provide a secure and substantially immobile connection between the proximal anchor **112**, the sensor **120** and the distal anchor **110**. The specific geometry of the interlocking structures of FIGS. **10-12** are intended to be merely exemplary, and the specific shapes of the fingers **180**, slots **186**, and spaces **190** can alternatively include a variety of different geometric shapes in order to provide a secure connection between the components. If desired, the interlocking structures can also be welded together once they are assembled, thereby further securing the connection.

[0073] FIGS. **13 and 14** illustrate the proximal and distal anchors of FIGS. **10-12** with the addition of a plurality of radiopaque markers **200** for facilitating visualization of the assembly under fluoroscopy during deployment. As shown, radiopaque markers **200** can be applied to the legs **124** of the distal anchor **110** and/or to the proximal ring **140** of the proximal anchor **112**. Radiopaque markers can also be provided on other portions of the proximal anchor **112**, the

distal anchor **110** and/or the sensor **120**. The radiopaque markers are preferably placed in "low flex zones," such as the tips of the distal anchor legs **124** and the proximal ring **140** of the proximal anchor. Generally, "low flex zones" are portions of the anchor that experience substantially minimal flexing or bending. This insures that the materials used in the radiopaque markers do not negatively affect the elasticity of the flexing anchor sections, and also insures that the radiopaque materials to not separate from the anchor within a patient.

[0074] Radiopaque markers are typically made of noble metals, such as gold, platinum/ iridium, tantalum, etc, and are typically attached to the anchor by selective plating or ion beam deposition. Alternatively, the markers could be micro rivets and/or rings that are mechanically attached to portions of the system components. In order to reduce the risk of galvanic corrosion which can be experienced by dissimilar metals exposed to blood, the radiopaque material can be selected to have a galvanic corrosion potential that is substantially similar to a galvanic corrosion potential of the material from which the anchors and/or sensor are made. For example, if the anchors **110, 112** are to be made of NITINOL, the radiopaque markers **200** can be made of tantalum. Alternatively, an electrically insulating coating (conformal coatings) such as parylene or other biocompatible synthetic material can be used to cover the radiopaque markers in order to isolate the marker and anchor section from exposure to the blood or other bodily fluid.

[0075] FIGS. **15-21** illustrate embodiments of systems and methods for delivering and deploying the anchor assembly **100** to secure a sensor **120** in a septum wall **210**. According to one embodiment, a guidewire is placed through the septum wall **210** at the target site. A dilator sheath can then be fed over the guide wire and into the left atrium. The guidewire and dilator sheath can then be removed. A delivery catheter can then be fed over the dilator sheath until it crosses the septum and enters the left atrium.

[0076] As shown in FIGS. **15 and 16**, an assembly **100** of a proximal anchor **112**, a distal anchor **110** and a sensor **120** is provided within an introducer sheath configured to introduce the anchor assembly into the proximal end of the delivery catheter **220**. A stylet **224** is advanced through a central lumen of the electrical lead **226** to provide column strength and guidance to the device.

[0077] The introducer sheath containing the anchor and sensor assembly is then inserted into the proximal end of the delivery catheter, and the sheath is retracted and withdrawn. The anchor assembly is then guided through the delivery catheter **220** (which was previously positioned through the septum wall) until the legs of the distal anchor **110** are positioned at the distal end of the delivery catheter **220**, which can be visually verified under fluoroscopy by noting the position of the distal radiopaque marker **225** on the distal edge of the delivery catheter **220**. The delivery catheter **220** can be withdrawn while holding the anchor and sensor assembly **100** in place with the stylet **224** extending through the center of the sensor lead **226**. The stylet **224** is preferably configured to provide sufficient column strength to allow the anchor and sensor assembly **100** to be held in place relative to the septum **210** while the catheter **220** is retracted to expose and deploy the anchors.

[0078] As the catheter **220** is retracted to expose the distal anchor **110**, the distal anchor legs **124** will expand to assume

their expanded state on a distal side of the septum wall **210**. Continued retraction of the catheter **220** will expose the proximal anchor **112**, allowing it to relax to its expanded state on a proximal side of the septum wall **210** as shown in **FIG. 19**. The fully deployed proximal **112** and distal **110** anchors preferably resiliently engage the septum wall **210** in order to firmly secure the sensor **120** to the septum wall **210**.

[0079] In one embodiment, the legs **144** of the proximal anchor **112** apply a lower spring force to the septum wall **210** than the legs **124** of the distal anchor **110** so that variations in septum wall thickness are accommodated by variations in the position of the proximal anchor legs **144** as shown in **FIGS. 20 and 21**. **FIG. 20** shows a relatively thin septum wall **210** with a thickness **230**. In order to securely anchor the sensor, the legs **144** of the proximal anchor **112** will extend distally until their distal motion is stopped by the pressure of the septum wall **210**. In the embodiment of **FIG. 21**, the septum wall **210** is substantially thicker **231**, thereby causing the legs **144** of the proximal anchor **112** to extend a shorter distance distally than in the embodiment of **FIG. 20**. This difference in anchored position of the proximal anchor legs **144** can also be seen in the difference in the dimensions **232** and **234**. As shown in **FIGS. 20 and 21**, the distance **232** in **FIG. 20** between the proximal edge of the proximal ring **140** and the proximal surface of the septum wall **210** is greater than a corresponding distance **234** for the thicker septum wall of **FIG. 21**.

[0080] In one embodiment, the lead **226** shown in **FIGS. 16, 19 and 20** is part of a pressure monitoring apparatus and is used to relay electrical signals to a signaling device as described, for example, in the Eigler patent mentioned above.

[0081] **FIGS. 22-35** illustrate systems and methods for retrieving an anchor and sensor assembly **100** from its position anchored to a septum wall **210**. Retrieval devices having preferred features and advantages are generally configured to be placed within a catheter and guided to the location of the anchor and sensor assembly **100** within a patient. A retrieval device can then be operated to grasp the anchor assembly **100** and draw it into a lumen of the catheter for removal from the patient's body.

[0082] In one embodiment, a retrieval apparatus **250** such as that shown in **FIGS. 22-27** generally comprises a retrieval head **252** with a plurality of grasping hooks **254** extending distally from a cylindrical body **256**. The cylindrical body **256** of the retrieval head **252** comprises as small an axial length as possible in order to allow the retrieval device to be easily guided through the tortuous anatomy of a patient's vasculature.

[0083] With reference to **FIG. 23**, the grasping hooks **254** can be configured to comprise return legs **258** which are substantially parallel to the attachment portion of the legs **259**. In their relaxed position, the legs **259** are bent radially outwards as shown in **FIGS. 24 and 25** in order to allow the hooks **254** to be advanced distally past the proximal ring **140**. When the retrieval device **250** is drawn into the catheter, the legs **254** assume a compressed state as shown in **FIGS. 26 and 27**. In their compressed state, the legs **259** are substantially parallel to the longitudinal axis of the cylindrical body **256** of the retrieval device **250**.

[0084] As shown in **FIGS. 22-27**, the cylindrical body **256** can include a slot **260** configured to allow the retrieval head

to allow the retrieval device **250** to be assembled onto the lead by "side loading," e.g., by placing the cylindrical body **256** beside the lead and pressing the lead **226** sideways through the slot **260** of the cylindrical body **256**. This is particularly advantageous in embodiments in which the lead **226** comprises an enlarged proximal end (such as an electrical connector), since side-loading the retrieval head onto the lead **226** allows the retrieval head to have an internal diameter only slightly larger than the diameter of the lead.

[0085] In an alternative embodiment, the retrieval head **252** can be configured to be moved from an open position to a closed position by compressing the cylindrical body **256** to a smaller diameter. According to this embodiment, the slot **260** in the cylindrical body **256** is provided to allow the retrieval head to expand to assume an internal diameter that is sufficiently large that the cylindrical body **256** can be fed over a sensor lead **226** (e.g. see **FIG. 34**). The retrieval head of this embodiment can be constricted to assume a smaller diameter, and to cause the grasping hooks to engage the proximal anchor.

[0086] **FIGS. 28-30** illustrate an alternative embodiment of a retrieval device **280** that comprises a retrieval head **252** with a plurality of helical legs **282** extending between and attached to proximal **284** and distal **286** rings. The construction of the retrieval device **280** advantageously allows the device to be more easily guided through a patient's tortuous vasculature. The proximal ring **284** of the retrieval device **280** can be configured to receive an attachment loop **278** of a push/pull ribbon **262**. The retrieval device **280** also includes a plurality of grasping hooks **292** for engaging and removing the anchor and sensor assembly **100**. This embodiment is also advantageously longer than the previous retriever embodiment in order to allow it to be extended further out of the delivery catheter. With reference to the detail view of **FIG. 29**, the grasping hooks **292** generally include attachment legs **294** and return legs **296**. The return legs **296** as shown, are oriented to be substantially perpendicular to a longitudinal axis of the retrieval device **282**. The return legs **296** also preferably include radiopaque markers **300** to facilitate visualization of the distal end of the retrieval device **280** under fluoroscopy.

[0087] The retrieval devices **250, 280** are generally configured such that the grasping hooks **254, 292** can be moved between an "open" or expanded position and a "closed" position. In the open position, the hooks **254, 292** are spaced sufficiently to be placed distally of the proximal ring **140** of the proximal anchor **112**. The grasping hooks **254, 292** can be moved to their closed position for example by advancing the catheter **220** distally relative to the retrieval device **250, 280**. The distal edge of the catheter **220** will compress the hooks **254, 292** to their closed position. In the alternative embodiment of **FIGS. 26 and 27**, the device can be moved to a closed position by radially compressing the cylindrical body **256** of the retrieval device. In order to fully engage the hooks on the proximal ring, the ribbon **262** can be pulled proximally slightly.

[0088] Methods of retrieving the anchor and sensor assembly will now be described with reference to **FIGS. 31-35**. Once a retrieval device **250, 280** is in position with the grasping hooks **254, 292** engaged on a proximal ring **140** of the proximal anchor **112**, the retrieval device **250, 280** is pulled proximally until the proximal ring **140** of the proxi-

mal anchor **112** enters the distal end of the delivery catheter **220**. At this point, the radiopaque markers of the retrieval device (**300**), the proximal ring **140** and the delivery catheter (**225**) are all aligned with one another. The stylet **224** is then held fixed to maintain the position of the sensor while the proximal anchor **112** is stretched, causing it to compress, by drawing back both the catheter and the retrieval implant. Once the proximal anchor **112** is stretched to its compressed state, it can be introduced into the catheter **220** by holding the ribbon **262** stationary and advancing the delivery catheter **220** over the proximal anchor **112**, while holding the sensor **120**, the proximal anchor **112** and distal anchor **110** substantially stationary with the stylet **224**.

[0089] Once the proximal anchor **112** has been is fully compressed and is contained within the catheter **220**, the catheter **220** can be advanced distally while holding the retrieval device stationary. The catheter is advanced until the distal edge of the catheter extends through the septum wall **210** and is positioned adjacent the legs **124** of the distal anchor **110**. The legs **124** of the distal anchor **110** can be compressed by further advancing the catheter **220** distally while pulling the ribbon **262** proximally, and allowing the stylet to move proximally. Once the legs **124** of the distal anchor **110** have been fully compressed, the distal anchor can be pulled back into the lumen of the catheter **220**. The catheter **220** containing the anchors **110**, **112** and the sensor **120** can then be removed from the patient's vasculature.

[0090] Additionally, removal of a chronically implanted device can also involve the adjunctive use of a commercial cardiac lead removal system including a lead grasping stylet, such as a SPECTRANETICS LEAD LOCKING DEVICE (LLD™ model 518-018, 518-019, or 518-021) and/or a suitable lead removal sheath or excimer laser lead removal catheter, such as a SPECTRANETICS LASER SHEATH (SLSII™ model 500-001, 500-012, or 500-013). The skilled artisan will recognize that additional equipment can also be used in order to effectively remove an implanted anchor device from within a patient.

[0091] In most situations, it is not necessary to remove the sensor from an implant site, however in some situations removal may be necessary. In general, the reasons for removing the anchor and sensor assembly from its position anchored to a septum wall might include: incorrect placement of the device, device failure, infections, etc. As mentioned above, the hole through which the sensor and anchor assembly **100** extends is preferably formed by stretching a very small guidewire access hole. Thus, upon removal of the sensor and anchor assembly from the septum wall, the hole will typically substantially collapse to a small size. In time, the hole will typically heal on its own. If necessary, however any one of a number of devices and systems for closing septal defects can be used to substantially close a hole in the septum wall.

[0092] In some embodiments, it is desirable to provide one or more radiopaque markers on one or more of the system components in order to facilitate visualization of the various system components under fluoroscopy during deployment or retrieval procedures and/or to verify correct placement of the anchor and sensor assembly **100** after deployment. Radiopaque markers can advantageously allow a physician to visually confirm a location of the device within a patient during placement and retrieval of the sensor assembly **100**.

As shown throughout the Figures, in several embodiments, radiopaque markers can be applied to portions of one or more of the proximal and distal anchors **110** and **112** (e.g. see markers **200** in FIGS. **10-14**), the delivery and/or retrieval catheters **220** (e.g. see markers **225** in FIGS. **15-21**, **32** and **33**), the retrieval heads **252** (e.g. see markers **300** in FIGS. **23** and **29**), and the sensor itself. In some embodiments, the sensor can comprise components made of a sufficiently dense material, including but not limited to zirconia ceramic materials, such that portions of the sensor itself are radiopaque.

[0093] Radiopaque markers can be formed on the various system components by any suitable process or method. For example, in some embodiments, the markers are plated or ion deposited onto portions of the system components. The radiopaque markers are preferably placed in "low flex zones" of the system components such as the tips of the distal anchor legs **124**, the proximal ring **140** of the proximal anchor **112**, and the return legs **258**, **296** of the grasping hooks **254**, **292**. Generally, "low flex zones" are portions of a device that experience substantially minimal flexing or bending. This insures that the materials used in the radiopaque markers do not negatively affect the elasticity of the flexing sections, (e.g. the flexing anchor legs) and also insures that the radiopaque materials do not undesirably delaminate from the devices within a patient due to differences in ultimate strain values of the materials of the anchor and the markers.

[0094] Radiopaque markers are typically made of noble metals, such as gold, platinum/ iridium, tantalum, etc. In order to reduce the risk of galvanic corrosion which can be experienced by dissimilar metals exposed to blood, the radiopaque material can be selected to have a galvanic corrosion potential that is substantially similar to a galvanic corrosion potential of the material from which the anchors, retrieval device(s) and/or the sensor are made. For example, if the anchors **110**, **112** are to be made of NITINOL, the radiopaque markers **200** can be made of tantalum to reduce the possibility of galvanic corrosion. Alternatively, an electrically insulating or conformal coatings such as parylene or other biocompatible synthetic material can be used to cover the radiopaque markers in order to isolate the marker and/or other metallic sections from exposure to the blood.

[0095] The apparatus and methods of the present invention may be embodied in other specific forms and for other applications without departing from its spirit or essential characteristics. The described embodiments are to be considered in all respects only as illustrative and not restrictive.

[0096] Although certain embodiments and examples have been described herein, it will be understood by those skilled in the art that many aspects of the methods and devices shown and described in the present disclosure may be differently combined and/or modified to form still further embodiments. Additionally, it will be recognized that the methods described herein may be practiced using any device suitable for performing the recited steps. Such alternative embodiments and/or uses of the methods and devices described above and obvious modifications and equivalents thereof are intended to be within the scope of the present disclosure. Thus, it is intended that the scope of the present invention should not be limited by the particular embodiments described above, but should be determined only by a fair reading of the claims that follow.

[0097] Additionally, the skilled artisan will recognize that the embodiments of anchoring devices and methods described herein may be advantageously applied for anchoring any other diagnostic and/or therapeutic implant to a wall of any organ within a patient. In addition to sensors, such implants include, but are not limited to, sensing and stimulating electrodes, ultrasound transducers, drug delivery systems, pacing leads, electrocardiogram leads, oxygen partial pressure sensors, oxygen saturation sensors, or any other device that one desires to securely anchor to a wall of an internal organ. It will also be apparent to one skilled in the art that the field of use of the embodiments of devices and methods described herein extends beyond the specific condition of heart failure to any cardiovascular condition or other condition in a medical patient where a device is implanted through a wall of a chamber or vessel is affixed to a wall of that chamber or vessel.

What is claimed is:

1. An implantable device, comprising:
 - a proximal anchor having at least one helical leg extending between a proximal ring and a distal ring;
 - a distal anchor having at least one leg; and
 - an implant configured to be supported by the proximal and distal anchors,
 wherein the proximal and distal anchors are configured to be movable between a collapsed delivery position and an expanded position in which the proximal and distal anchors secure the implant to a wall of an organ within a patient.
2. The device of claim 1, wherein the implant is a diagnostic tool.
3. The device of claim 1, wherein the implant is a therapeutic tool.
4. The device of claim 2, wherein the diagnostic tool comprises apparatus operable to measure one or more physiological parameters.
5. The device of claim 2, wherein the diagnostic tool comprises apparatus operable to measure pressure.
6. The device of claim 2, wherein the diagnostic tool comprises apparatus operable to measure oxygen levels.
7. The device of claim 2, wherein the diagnostic tool comprises apparatus operable to measure electrical activity.
8. The device of claim 3, wherein the therapeutic tool comprises apparatus operable to deliver one or more pharmaceutical agents to the patient.
9. The device of claim 3, wherein the therapeutic tool comprises apparatus operable to deliver one or more electrical signals to the patient.
10. The device of claim 1, wherein the implant is selected from the group consisting of one or more of the following: stimulating electrodes, ultrasound transducers, drug delivery systems, pacing leads, and electrocardiogram leads.
11. The device of claim 1, wherein the implant is a sensor.
12. The device of claim 11, wherein the sensor is a sensing electrode, oxygen partial pressure sensor or an oxygen saturation sensor.
13. The device of claim 11, wherein the sensor is a pressure sensor.
14. The device of claim 1, wherein said proximal anchor comprises at least three legs.
15. The device of claim 1, wherein the at least one proximal anchor leg passes through substantially a whole

number of complete circles between the proximal ring and the distal ring of the proximal anchor.

16. The device of claim 1, wherein said at least one proximal anchor leg has a lower spring force than said at least one distal anchor leg.

17. The device of claim 16, wherein the proximal anchor leg and the distal anchor leg are configured to secure the implant to organ walls with varying thicknesses.

18. The device of claim 1, wherein said anchoring device is made from a biocompatible material selected from the group consisting of: nickel titanium alloys, stainless steel, ELGILOY, and MP35N.

19. The device of claim 11, wherein the sensor comprises a pressure sensing face configured to measure a fluid pressure in a left atrium of a patient's heart.

20. The device of claim 19, wherein the proximal and distal anchors are configured to support the sensor such that the pressure sensing face is substantially coplanar with a distal side of an atrial septum wall.

21. The device of claim 19, wherein the proximal and distal anchors are configured to support the sensor such that the pressure sensing face is spaced distally from a plane of a distal side of an atrial septum wall.

22. The device of claim 19, wherein the proximal and distal anchors are configured to support the sensor such that the pressure sensing face is spaced proximally from a plane of an atrial septum wall.

23. The device of claim 1, wherein the proximal anchor, the distal anchor and the implant comprise interlocking structures configured to rigidly secure the proximal anchor, the distal anchor and the implant to one another.

24. The device of claim 11, wherein the sensor is configured to attach to an electrical lead.

25. The device of claim 1, wherein at least one member of the group consisting of the proximal anchor, the distal anchor and the implant comprises one or more radiopaque markers configured to facilitate visualization under fluoroscopy.

26. The device of claim 25, wherein a portion of an element comprising said one or more radiopaque markers is coated with a polymeric material adapted to prevent galvanic corrosion.

27. The device of claim 25, wherein said one or more radiopaque markers are placed in low flex zones.

28. The device of claim 27, wherein tips of the at least one distal anchor leg comprise said one or more radiopaque markers.

29. The device of claim 27, wherein the proximal ring of the proximal anchor comprises said one or more radiopaque markers.

30. The device of claim 27, wherein the distal ring of the proximal anchor comprises said one or more radiopaque markers.

31. The device of claim 11, wherein the sensor comprises a cylindrical body with at least one annular groove configured to engage a portion of the proximal anchor or a portion of the distal anchor in order to retain the proximal or distal anchor against axial movement relative to the sensor.

32. The device of claim 1, wherein the distal anchor comprises a plurality of legs comprising slots configured to promote tissue overgrowth.

33. A system for diagnosing and/or treating a condition in a patient, the system comprising:

- an implant configured to be implanted within a patient;
- a proximal anchor comprising at least one helical leg configured to expand from a compressed state to a relaxed state;
- a distal anchor comprising at least one leg configured to expand from a compressed state to an expanded state;
- wherein the proximal anchor and the distal anchor are configured to sandwich an atrial septum wall between the at least one proximal anchor leg and the at least one distal anchor leg and to support the implant in the septum wall; and
- a delivery catheter configured to deploy the implant, the proximal anchor, and the distal anchor in the septum wall.

34. The system of claim 33, wherein the implant is a diagnostic tool.

35. The system of claim 34, wherein the diagnostic tool comprises apparatus operable to measure one or more parameters selected from the group consisting of: pressure, oxygen and electrical activity.

36. The system of claim 33, wherein the implant is a therapeutic tool.

37. The system of claim 36, wherein the therapeutic tool comprises apparatus operable to deliver one or more pharmaceutical agents to the patient.

38. The system of claim 36, wherein the therapeutic tool comprises apparatus operable to deliver one or more electrical pulses to the patient.

39. The system of claim 33, wherein the proximal anchor further comprises a proximal ring and a distal ring attached to opposite ends of the at least one helical leg.

40. The system of claim 34, further comprising a retrieval device configured to grasp the proximal ring of the proximal anchor in the relaxed state, and to retract the proximal ring of the proximal anchor proximally relative to the distal ring, thereby returning the proximal anchor to the compressed state.

41. The system of claim 40, wherein the retrieval device comprises a cylindrical body with a plurality of distally-extending grasping hooks.

42. The system of claim 40, wherein the retrieval device comprises a distal ring with at least one distally-extending grasping hook, a proximal ring, and at least one helical leg extending between the proximal ring and the distal ring.

43. The system of claim 33, wherein the retrieval device comprises a push/pull ribbon.

44. The system of claim 33, wherein the retrieval head comprises an internal diameter configured to allow the retrieval head to pass over a sensor lead.

45. The system of claim 33, wherein said proximal anchor comprises at least three legs.

46. The system of claim 33, wherein the at least one proximal anchor leg passes through substantially a whole number of complete circles between the proximal ring and the distal ring of the proximal anchor.

47. The system of claim 33, wherein said at least one proximal anchor leg has a lower spring force than said at least one distal anchor leg.

48. The system of claim 47, wherein the at least one proximal anchor leg and the at least one distal anchor leg are configured to secure the implant to organ walls with varying thicknesses.

49. The system of claim 33, wherein said anchoring device is made from a biocompatible material selected from the group consisting of: nickel titanium alloys, stainless steel, ELGILOY, and MP35N.

50. The system of claim 33, wherein the implant comprises a pressure sensor with a pressure sensing face configured to measure a fluid pressure in a left atrium of a patient's heart.

51. The system of claim 50, wherein the proximal and distal anchors are configured to support the sensor such that the pressure sensing face is substantially coplanar with a distal side of an atrial septum wall.

52. The system of claim 50, wherein the proximal and distal anchors are configured to support the sensor such that the pressure sensing face is spaced distally from a plane of a distal side of an atrial septum wall.

53. The system of claim 50, wherein the proximal and distal anchors are configured to support the sensor such that the pressure sensing face is spaced proximally from a plane of an atrial septum wall.

54. The system of claim 33, wherein the proximal anchor, the distal anchor and the implant comprise interlocking structures configured to rigidly secure the proximal anchor, the distal anchor and the implant to one another.

55. The system of claim 33, wherein the implant is configured to attach to an electrical lead.

56. The system of claim 33, wherein at least one member of the group consisting of the proximal anchor, the distal anchor and the implant comprises a radiopaque marker configured to facilitate visualization under fluoroscopy.

57. The system of claim 56, wherein a portion of an element comprising a radiopaque marker is coated with a polymeric material adapted to prevent galvanic corrosion.

58. The system of claim 56, wherein the radiopaque marker is placed in one or more low flex zones.

59. The system of claim 58, wherein the at least one distal anchor leg comprises the radiopaque marker.

60. The system of claim 56, wherein the proximal ring and/or the distal ring of the proximal anchor comprise the radiopaque marker.

61. The system of claim 33, wherein the implant comprises a sensor.

62. The system of claim 33, wherein the implant comprises a pressure sensor having a cylindrical body with at least one annular groove configured to engage a portion of the proximal anchor or a portion of the distal anchor in order to retain the proximal or distal anchor against axial movement relative to the sensor.

63. The system of claim 33, wherein the distal anchor comprises a plurality of legs having slots configured to promote tissue overgrowth.

64. A system for monitoring a patient for congestive heart failure, the system comprising:

an implantable pressure sensor;

means for contacting a proximal wall and a distal wall of an organ to anchor said pressure sensor to the organ wall.

65. The system of claim 64, further comprising a means for delivering said implantable sensor and said means for contacting to said organ wall.

66. The system of claim 65, further comprising a means for retrieving said implantable pressure sensor from the organ wall.

67. A method of monitoring congestive heart failure in a patient, the method comprising:

providing a pressure sensor secured to a proximal anchor and a distal anchor;

delivering the pressure sensor to a hole in an atrial septum of the patient's heart;

deploying the pressure sensor with the proximal anchor on a proximal side of the septum, and the distal anchor on a distal side of the septum; and

monitoring a fluid pressure in the left atrium of the patient's heart.

68. The method of claim 67, further comprising orienting a sensor face of the pressure sensor to be substantially coplanar with a left atrium side surface of the atrial septum wall.

69. The method of claim 67, further comprising orienting a sensor face of the pressure sensor to extend beyond the atrial septum into a left atrium of the heart.

70. The method of claim 67, further comprising orienting a sensor face of the pressure sensor to be proximally recessed with respect to a left atrium side surface of the atrial septum wall.

71. The method of claim 67, wherein deploying the sensor comprises expanding the proximal and distal anchors to compress the atrial septum wall between the proximal anchor and the distal anchor.

72. A method of monitoring congestive heart failure within a patient, the method comprising:

providing an implantable pressure sensor;

coupling said implantable pressure sensor to a means for anchoring said pressure sensor in an organ wall;

delivering said pressure sensor and said means for anchoring to said organ wall; and

causing said means for anchoring said pressure sensor in said organ wall to expand, thereby capturing said organ wall.

73. The method of claim 72, further comprising removing said pressure sensor and said means for anchoring from said organ wall.

74. A method of anchoring a device in the heart of a mammal using an implantable cardiac anchoring device, the method comprising:

providing an implantable cardiac anchoring device comprising a proximal anchor having at least one helical leg and a distal anchor having at least one linear leg;

attaching an implant to the implantable cardiac anchoring device;

positioning a tubular delivery catheter in a wall of a patient's heart;

inserting said implant and said implantable cardiac anchoring device into said tubular delivery catheter; and

deploying said implant and said implantable cardiac anchoring device such that said implant is retained in the wall.

75. The method of claim 74, wherein attaching an implant further comprises providing a diagnostic tool or therapeutic tool.

76. The method of claim 74, wherein attaching an implant further comprises providing apparatus selected from the group consisting of one or more of the following: sensors, stimulating electrodes, ultrasound transducers, drug delivery systems, pacing leads, and electrocardiogram leads.

77. The method of claim 74, wherein attaching an implant comprises providing a pressure sensor having a pressure sensing face.

78. The method of claim 74, wherein said providing an implantable cardiac anchoring device comprises placing said anchoring device into a lumen of a delivery catheter and advancing said cardiac anchoring device through said lumen to a distal end of the delivery catheter.

79. The method of claim 78, wherein deploying said implant comprises withdrawing said delivery catheter while holding said anchoring device in a desired location, said anchoring device being configured to relax to an expanded shape in which the anchoring device is secured in a desired location within a patient.

80. The method of claim 74, wherein providing an implantable cardiac anchoring device comprises inserting said anchoring device into said delivery catheter in a first compressed shape, and wherein said deploying comprises expanding said anchoring device to a second expanded shape.

81. The method of claim 74, wherein attaching said implant to said implantable cardiac anchoring device comprises providing at least one locking tab extending from the implantable cardiac anchoring device and configuring the tab to engage in an annular groove in the implant.

82. The method of claim 75, wherein deploying said sensor comprises orienting a sensor face to be substantially coplanar with a surface of the wall.

83. The method of claim 75, wherein deploying said sensor comprises orienting a sensor face to be located distally from a surface of the wall.

84. The method of claim 75, wherein deploying said sensor comprises orienting a sensor face to be located proximally to a surface of the wall.

85. The method of claim 75, wherein deploying the sensor comprises anchoring said pressure sensor in an atrial septum wall so as to measure a fluid pressure in the left atrium of the heart.

86. The method of claim 74, further comprising providing one or more radiopaque markers on the delivery catheter, the proximal anchor, and the distal anchor; and wherein the markers are employed during said deploying so as to facilitate visualization of the delivery catheter, the proximal anchor, and the distal anchor.

87. The method of claim 74, further comprising promoting tissue overgrowth by providing slots in the at least one leg of said distal anchor.

88. A retrieval device configured to retrieve a cardiac anchoring device from a position deployed in a wall of an organ within a patient, the retrieval device comprising:

a retrieval head comprising a plurality of grasping hooks extending from a distal end thereof;

a ribbon of sufficient length to extend from a retrieval location within a patient to a location outside of a patient; and

wherein the grasping hooks are configured to engage a proximal ring of a proximal anchor.

89. The retrieval device of claim 88 wherein the grasping hooks comprise return legs oriented so as to be substantially perpendicular to a longitudinal axis of the retrieval device.

90. The retrieval device of claim 88, wherein the grasping hooks comprise return legs oriented so as to be substantially parallel to a longitudinal axis of the retrieval device.

91. The retrieval device of claim 88, wherein the retrieval head comprises a substantially cylindrical body with an axial slot configured to permit the diameter of the cylindrical body to increase or decrease.

92. The retrieval device of claim 88, wherein the retrieval head comprises an internal diameter configured to allow the retrieval head to pass over a sensor lead.

93. The retrieval device of claim 88, wherein the retrieval head comprises a plurality of helical legs extending between a proximal ring and a distal ring, and wherein the grasping hooks extend distally from the distal ring.

94. The retrieval device of claim 93, wherein the helical legs pass through a substantially whole number of complete circles between the proximal and distal rings.

95. A method of retrieving a cardiac anchoring device from a heart of a patient using a retrieval device, the method comprising:

placing a retrieval device in a delivery catheter, the retrieval device comprising a retrieval head with a plurality of distally-extending grasping hooks and a control ribbon attached to the retrieval device;

guiding said delivery catheter into a position adjacent an sensor device anchored to a wall of the patient's heart;

engaging a proximal ring of a proximal anchor secured to said sensor device;

pulling said proximal ring of said proximal anchor into said delivery catheter;

holding the sensor device stationary while pulling the retrieval device, the proximal ring of the proximal anchor and the delivery catheter proximally, thereby returning an anchor leg of said proximal anchor to a compressed position;

advancing said delivery catheter distally while holding the proximal anchor and the sensor device stationary to compress at least one expanded leg of the distal anchor attached to the sensor device;

pulling the sensor device, the proximal anchor and the distal anchor completely into the lumen of the delivery catheter; and

removing said delivery catheter from the patient.

* * * * *

专利名称(译)	心血管锚固装置及其展开方法		
公开(公告)号	US20040116992A1	公开(公告)日	2004-06-17
申请号	US10/672443	申请日	2003-09-26
[标]申请(专利权)人(译)	沃德尔约翰·L· EIGLER NEAL 大号		
申请(专利权)人(译)	沃德尔约翰L. EIGLER NEAL L.		
当前申请(专利权)人(译)	沃德尔约翰L. EIGLER NEAL L.		
[标]发明人	WARDLE JOHN L EIGLER NEAL L		
发明人	WARDLE, JOHN L. EIGLER, NEAL L.		
IPC分类号	A61B A61B5/00 A61B5/0215 A61B5/04 A61B5/042 A61B17/00 A61B17/064 A61K9/22 A61N1/05 A61N1/37		
CPC分类号	A61B5/0215 A61B5/042 A61B5/145 A61N1/057 A61B17/064 A61B2017/00243 A61B5/6882		
优先权	60/413758 2002-09-26 US		
其他公开文献	US7149587		
外部链接	Espacenet USPTO		

摘要(译)

锚固装置及其输送方法可有效地提供用于在各种临床应用中將植入物固定到患者体内的器官壁上的装置。在一个实施例中，提供了一种用于保持心脏压力测量装置的锚固装置。该装置通过使其变形为小的横截面轮廓而植入体内，使其滑过低轮廓的输送装置并从目标部位的输送装置中弹出。当从输送装置中弹出时，锚定机构恢复到预先形成的构型并与器官壁的相对侧接合，从而將植入物锚固在器官壁中。

