





US 20050234431A1



(19) **United States**(12) **Patent Application Publication** (10) **Pub. No.: US 2005/0234431 A1**  
(43) **Pub. Date: Oct. 20, 2005**  
**Williams et al.**(54) **INTRAVASCULAR DELIVERY SYSTEM FOR  
THERAPEUTIC AGENTS****Related U.S. Application Data**(60) Provisional application No. 60/543,260, filed on Feb.  
10, 2004. Provisional application No. 60/634,585,  
filed on Dec. 9, 2004.(76) Inventors: **Michael S. Williams**, Santa Rosa, CA  
(US); **Kevin Holbrook**, Chapel Hill,  
NC (US); **Terrance Ransbury**, Chapel  
Hill, NC (US)**Publication Classification**(51) **Int. Cl.<sup>7</sup>** ..... **A61K 9/24; A61K 9/22**  
(52) **U.S. Cl.** ..... **604/890.1**Correspondence Address:  
**STALLMAN & POLLOCK LLP**  
**SUITE 2200**  
**353 SACRAMENTO STREET**  
**SAN FRANCISCO, CA 94111 (US)****ABSTRACT**




Described herein is a system for intravascular drug delivery system, which includes a reservoir implantable a blood vessel, an intravascular pump fluidly coupled to the reservoir and an anchor expandable into contact with a wall of the blood vessel to retain the system within the vasculature. Delivery conduits may be extend from the reservoir and are positionable at select locations within the vasculature for target drug delivery to select organs or tissues.


(21) Appl. No.: **11/055,540**(22) Filed: **Feb. 10, 2005**




**FIG. 1**









**FIG. 6A**



**FIG. 6B**



**FIG. 7**



**FIG. 8A**




FIG. 8B







FIG. 8C









**FIG. 9A**




**FIG. 9B**




**FIG. 9C**








**FIG. 9D**




**FIG. 9E**





**FIG. 12**



**FIG. 13**

## INTRAVASCULAR DELIVERY SYSTEM FOR THERAPEUTIC AGENTS

### PRIORITY CLAIM

[0001] The present application claims benefit from U.S. Provisional Patent Application Ser. No. 60/543,260, filed Feb. 10, 2004, which is incorporated herein by reference. The present application also claims benefit from U.S. Provisional Patent Application Ser. No. 60/634,585, filed Dec. 9, 2004, which is incorporated herein by reference.

### FIELD OF THE INVENTION

[0002] The present invention relates generally to the field of delivery systems for drugs, and more particularly to intravascular systems for delivering such agents with the body.

### BACKGROUND OF THE INVENTION

[0003] This application describes an implantable intravascular drug delivery system, which allows administration of therapeutic agents ("or drugs") directly into the vasculature.

[0004] Numerous drugs cannot be taken orally for various reasons. For example, oral ingestion of certain agents cannot be tolerated by the GI systems of some patients, or will result in severe systemic side effects. Other agents cannot withstand a gastrointestinal route of administration without breaking down and becoming ineffective. Some agents must be targeted to specific organs or tissues and thus are not suitable for oral ingestion. It would thus be highly desirable to administer these drugs, including drugs that are conventionally delivered intravenously, using an automated implanted administration system.

[0005] An automated implantable administration system can also benefit patients taking drugs that generally can be taken orally. For example, oral administration can be impractical in patients who are unable to self-administer a required dosage when needed. Administration using an automated implantable administration system is further beneficial in that it can administer a drug when a physical or chemical condition is detected by the system's sensors (e.g., reduced blood sugar), but before the patient suffers from the imminent symptoms. An automated system can also accelerate the desired systemic or local response to the drug administration by eliminating the time necessary for an orally ingested drug to be absorbed from the stomach into the bloodstream. Also, a lower dosage of a drug may be used (e.g., in some cases as little as 1% of the dosage needed for oral ingestion) when the drug is administered directly into the bloodstream. Finally, an automated system also allows for automatic dosage modification based on detected patient conditions.

[0006] In view of the forgoing need, a system has been developed which is fully or partially positionable within the vascular system of a body, and which can deliver pharmacological agents to induce a therapeutic effect.

### BRIEF DESCRIPTION OF THE DRAWINGS

[0007] FIG. 1 is a front perspective view showing a first embodiment of an intravascular drug delivery system.

[0008] FIG. 2 is a perspective view of a housing segment of the first embodiment, illustrating features of a gear pump housed within the segment.

[0009] FIG. 3A is a perspective view similar to FIG. 2 showing a peristaltic pump which may be used as an alternative to the pump of FIG. 2. FIG. 3B is a cross-sectional end-view of the housing segment further illustrating features of the FIG. 3A pump.

[0010] FIGS. 4 through 6A are side elevation views of other alternative pump designs. In these views, the pump chamber is shown in cross-section to allow the interior components to be seen. FIG. 6B is a perspective view of a device incorporating the pump of FIG. 6A.

[0011] FIG. 7 is a side elevation view of a second embodiment of an intravascular drug delivery system.

[0012] FIG. 8A is a perspective view of an anchor suitable for use with implantable drug delivery systems.

[0013] FIG. 8B is a perspective view showing the anchor of FIG. 8A attached to an implantable electrophysiological device and in the expanded position.

[0014] FIG. 8C is a cross-sectional end view of the device shown in FIG. 8B.

[0015] FIG. 8D is a side elevation view of a device showing the anchor of FIG. 8B positioned on a device and compressed by a sheath.

[0016] FIG. 8E is similar to FIG. 8D but shows retraction of the sheath to permit expansion of the anchor within a blood vessel.

[0017] FIGS. 9A through 9C are a sequence of drawings schematically illustrating implantation of the device of FIG. 1 within the vasculature.

[0018] FIG. 9D illustrates a third embodiment of an intravascular drug delivery device positioned within the vasculature.

[0019] FIG. 9E illustrates a fourth embodiment of an intravascular drug delivery device positioned within the vasculature, and with the fill tube of the device withdrawn from the body for use in refilling the device reservoir.

[0020] FIG. 10 is a front elevation view showing a fourth embodiment of an intravascular drug delivery device having delivery conduits for localized drug delivery.

[0021] FIG. 11 schematically illustrates an intravascular drug delivery device anchored within a blood vessel and having a delivery conduit positioned in the hepatic artery.

[0022] FIG. 12 is similar to FIG. 11 but shows the device positioned in the descending aorta and delivery conduits positioned in the renal arteries.

[0023] FIG. 13 schematically illustrates positioning of an intravascular drug delivery device which includes a refill port disposed in the right axillary vein.

### DETAILED DESCRIPTION

[0024] This application describes fully or partially intravascular systems for administering drugs including hormones, chemotherapeutic agents, antibiotics pharmaceuticals, synthetic, recombinant or natural biologics, and other agents within the body. Generally speaking, the systems include drug reservoirs and associated components that are anchored in the vasculature and that administer drugs into the bloodstream or into certain organs or tissues. Throughout



this disclosure, the terms “drugs” and “agent” will be used to refer to substances to be delivered into the body using systems of the type described herein.

[0025] In some embodiments, the systems may be programmed to deliver agents into the body according to a particular delivery schedule. For example, the device may be programmed to deliver 10 cc of agent over a 24-hour period every two weeks. According to this example, the device's control system may be programmed to activate the pump continuously at a specified rate during the 24-hour period. Alternatively, the control system may be programmed to cause the pump to deliver a single bolus of the agent every minute over the 24-hour period. This latter algorithm can extend battery life by avoiding continuous draw on the battery (e.g., by the pump or associated motor) for an extended duration. Delivery schedules may be set and/or adjusted using an external programming device (e.g., a handheld device, PC, or other microprocessor device) that communicates with the implantable device using radio frequency encoded signals or other telemetric methods.

[0026] In other embodiments, the systems may be controlled via internal intelligence that is responsive to in-situ diagnostic analysis of liquid, chemical or physical changes in the patient. Such systems can utilize feedback from sensors on the implantable device to initiate release of the agent. The internal intelligence may be provided with various levels of sophistication. For example, the device may be programmed to simply deliver a pre-specified volume of agent when a detected parameter exceeds a specified level; or it may be equipped to select the volume of the agent to be delivered depending on the severity of the change in detected parameters and/or the amount of time elapsed since the last administration of the agent.

[0027] Alternatively, the systems may be configured to deliver agents “on-demand” when prompted by a patient to do so. In this type of system, patient communication may be carried out using an external programming device, or using remote activators that use magnetic, radio frequency, infrared, acoustic, or other triggers to initiate drug delivery.

[0028] Applications

[0029] Systems of the type described herein find use in many areas of medicine. Applications for the present technology include, but are not limited, to the following:

[0030] Cardiovascular Applications:

[0031] An intravascular drug delivery system may be used to treat cardiovascular conditions and/or their symptoms by delivering suitable agents into the blood within the vasculature and/or the heart. For example, the system may be used to deliver agents used to treat symptoms of congestive heart failure (CHF). Such agents may include agents within the classes of positive inotropes, diuretics, vasodilators, and cytokine effectors. Specific agents include: Dobutamine, Atrial Natriuretic Peptide, Digoxin, Enoximone, Nesiritide, Tezosentan, Bumetanide, Hydralazine, Alprostadil, Carvedilol, Enalaprilat, Ambrisentan, and Levosimendan (sold by Abbott Laboratories under the trade name Simdax)

[0032] As discussed, the drug may be administered according to a pre-programmed delivery protocol (for example X volume every Y seconds for a period of Z days), or in response to telemetric instructions provided by a

physician or patient, or in response to closed-loop feedback from a sensor forming part of the system. Such sensors might be positioned on or coupled to the implantable system, or they may communicate with the system from a remote location elsewhere in the body.

[0033] Thus a system for treating CHF symptoms might include a sensor for detecting conditions indicative of CHF. The sensor may be of a type to detect any of a number of criteria including but not limited to: arterial pressure, such as in the right atrium, right ventricle, and/or pulmonary artery; cardiac output; heart rate; Q-T interval; AVO<sub>2</sub> difference; blood pH (including as an indicator of lactic acid levels in the blood); blood gas levels (including blood O<sub>2</sub> and/or blood CO<sub>2</sub> levels).

[0034] The system might also include a sensor for detecting biochemical markers which might include:

[0035] (1) Triage Cardiac—a unique set of three biochemical indicators of cardiac muscle necrosis: Mioglobine; CK-MB and Cardiac Troponine I.

[0036] Alternatively, the system may rely on one or two of these markers alone or in combination with other markers.

[0037] (2) Brain Natriuretic Peptide—a non-invasive, objective marker of Congestive Heart Failure. Research indicates that

[0038] The concentration of BNP increases with the severity of CHF (precise correlation with NYHA classification).

[0039] BNP concentration has the positive correlation with end-diastolic pressure in left ventricle.

[0040] There is a reverse ratio between BNP level and the function of left ventricle after heart infarction.

[0041] The increase of BNP level is associated with increasing of Pulmonary Artery Wedge Pressure (precise correlation), deterioration of LV diastolic and systolic functions, LV Hypertrophy and Heart Infarction.

[0042] (3) Tumor Necrosis Factor. Elevated levels of the immune factor tumor necrosis factor (TNF $\alpha$ ) may be very strong and accurate predictors of a poor outlook in CHF patients. This immune factor is known to be a potent agent in the inflammatory process.

[0043] In one example of a closed-loop type system, the sensor might be a pH sensor for detecting blood acid levels, since a patient suffering from congestive heart failure (CHF) typically possesses elevated levels of lactic acid in his/her bloodstream. According to this embodiment, a delivery system might be programmed to deliver Dobutamine or another agent in response to detection of elevated lactate levels.

[0044] Diabetes

[0045] An intravascular drug delivery system may also be configured to deliver insulin to diabetic patients. According to one embodiment, an intravascular insulin-delivery system may be a closed-loop system including a glucose sensor for measuring blood sugar levels and an insulin reservoir. This

embodiment of the system may be programmed to administer appropriate doses of insulin as needed by the patient.

**[0046]** Emphysema and Asthma

**[0047]** An intravascular system may include an O<sub>2</sub> or CO<sub>2</sub> sensor equipped to detect hypoxia or hypercarbia in the patient's blood. In response, the system may administer a bronchodilator and/or other medications such as NO (nitric oxide) at the earliest onset of hypoxemia or hypercarbia, even before the patient becomes aware of the onset of the condition.

**[0048]** Organ Specific Examples

**[0049]** By directing drugs to a particular aortic branch (e.g., hepatic artery, renal artery, etc), an intravascular delivery device can achieve target delivery of therapeutic drugs (including chemotherapy, gene therapy or other organ-specific therapeutics) to specific organs including the brain, liver, kidneys, pancreas, lung, etc. For example, drugs may be directed towards the brain to treat diseases such as Alzheimer's, Parkinson's, or epilepsy; towards the brain, liver, kidneys, pancreas or lungs for cancer treatment; or towards the kidneys to treat cardio-renal syndrome that can be associated with congestive heart failure. Drugs may be directed towards the lungs via the venous system for treatment of conditions such as asthma or pulmonary hypertension, or via the arterial system for treatment of lung cancer.

**[0050]** The system may also be used to deliver drugs or chemicals to a specific organ in order to enhance the sensitivity of the tissues in that organ to externally or internally delivered therapies such as radiation.

**[0051]** Cancer

**[0052]** Another embodiment of an intravascular system could administer chemotherapy according to a pre-programmed timetable, or in response to telemetric instructions received from a physician. In some embodiments, the system may be positioned for targeted delivery of agents into blood vessels that feed vascularized tumor masses. The system may also be used to deliver radioactive particles to target sites.

**[0053]** Chronic Pain Management

**[0054]** Many patients suffering from chronic pain are candidates for PCA (Patient Controlled Analgesic), which is presently administered intravenously in hospitals. An intravascular system of the type described here would allow patients to control pain using PCA while remaining ambulatory.

**[0055]** Other Examples

**[0056]** Other applications for intravascular drug delivery systems include treatment of ophthalmic conditions, blood conditions such as hemophilia, as well as diseases and conditions not specifically mentioned herein.

**[0057]** System

**[0058]** Generally speaking, an intravascular drug delivery system may include a variety of components, the selection of which will vary depending on the application for the device and its intended drug delivery protocol (i.e., closed-loop vs. programmed delivery protocol vs. on-demand or telemetric initiation of delivery).

**[0059]** A first embodiment of an intravascular drug delivery device **10** is a fully intravascular system as shown in **FIG. 1**. The device of the first embodiment is preferably programmed to deliver an agent according to a time schedule, although it may be modified to administer drugs on-demand or in response to sensor feedback as described elsewhere in this application.

**[0060]** Device **10** includes a drug reservoir **12**, a device body **14**, and a retention device or anchor **16** for retaining the device **10** within the vasculature.

**[0061]** The reservoir **12** may take the form of a flexible inflatable bladder at least partially formed of a thin membrane. The bladder may be implanted prior to inflation, and then filled the necessary agent once implanted. The bladder might be formed of polyurethane, polyethylene or similar materials capable of withstanding rupture and degradation during implantation and use, and suitable for containing the agents to be delivered. Although the bladder is shown as having a cylindrical shape, other shapes (e.g., a crescent shape) may be selected so as to reduce the overall length of the device and/or to reduce the cross-sectional profile of the device at certain points along its length. In one embodiment, the reservoir may have a volume of approximately 40 ml, although larger or smaller reservoirs will be used when warranted by the concentration of the agent and the number and size of anticipated doses.

**[0062]** An alternative reservoir embodiment might include a non-inflatable reservoir formed of titanium or suitable polymeric materials. As yet another alternative (which is described in connection with **FIG. 7**), the reservoir may take the form of one or more inflatable bladders housed within one or more protective enclosures formed of titanium, polymeric material, or other suitable materials.

**[0063]** The reservoir is proportioned to minimize obstruction of blood flow even when inflated. The cross-sectional area of the reservoir in the transverse direction (i.e., transecting the longitudinal axis) should be as small as possible while still accommodating the required volume of drug. This area is preferably in the range of approximately 79 mm<sup>2</sup> or less, and more preferably in the range of approximately 40 mm<sup>2</sup> or less, or most preferably between 12.5-40 mm<sup>2</sup>. For a cylindrical reservoir, a cross-sectional diameter in the range of approximately 3-15 mm may be suitable.

**[0064]** An elongate pickup tube **18** extends through the reservoir. The tube is preferably manufactured of a material having sufficient flexibility to permit flexing of the tube as the device passes through bends in the patient's blood vessels, but also having sufficient kink-resistance to prevent kinks from forming in the tube during bending. The material should also be one that will not corrode or degrade in the presence of the agent to be delivered. Nitinol and suitable polymeric materials are examples.

**[0065]** The walls of the tube **18** include one or more openings **20**. During use, the agent is drawn into the tube **18** via these openings. The agent flows through the tube **18** into a pump chamber from which it may then be pumped from the pump chamber into the bloodstream.

**[0066]** A reservoir fill port **22** is fluidly coupled to the reservoir **12** and is configured to receive a needle or other device that may to fill and/or re-fill the reservoir **12**. The port **22** may also be engaged by an implantation tool which can

be used to push the device **10** through the vasculature and into the desired location within the body.

[0067] Device body **14** houses various components used to carry out drug delivery. The components within the device are disposed within an enclosure that is a rigid, semi-rigid or flexible housing preferably formed of a material that is biocompatible, capable of sterilization and capable of hermetically sealing the components contained within it. Various materials may be used for the enclosure, including molded compounds, metals such as titanium or stainless steel, or other materials. The exterior of the enclosure may be anti-thrombogenic (e.g., ePTFE or perfluorocarbon coatings applied using supercritical carbon dioxide) so as to prevent thrombus formation on the device. It may also be beneficial that the coating have anti-proliferative properties so as to minimize endothelialization or cellular ingrowth, since minimizing growth into or onto the device will help minimize vascular trauma when the device is explanted. The coating may thus also be one which elutes anti-thrombogenic compositions (e.g., heparin sulfate) and/or compositions that inhibit cellular ingrowth and/or immunosuppressive agents. Coatings of a type that may be used on the device **10** include those described in U.S. application Ser. No. 11/020,779, filed Dec. 22, 2004, entitled Liquid Perfluoropolymers and Medical Applications Incorporating Same," which is incorporated herein by reference. Others include nanocoatings provided by Nanosys of Palo Alto, Calif.

[0068] Alternatively, the housing exterior may include a coating or surface that functions as a tissue ingrowth promoter, thus aiding in retention of the device within the vasculature. As yet another example, the device **10** may be insertable into a separately implantable flexible "exoskeleton" that is pre-implanted into the vasculature. The exoskeleton includes a pocket into which the device **10** is inserted. Eventually, anchoring of the exoskeleton within the vessel may become reinforced by tissue ingrowth, whereas the device **10** remains free of ingrowth. This allows the device to be withdrawn from the exoskeleton, leaving the exoskeleton in place with minimal trauma to the vessel walls. This would facilitate removal for various purposes, including refilling or replacement of fluid reservoirs, replacement of batteries, replacement of the device with a fresh device, or for other purposes. The original or replacement device might then be passed into the vasculature and inserted into the exoskeleton. Examples of exoskeleton configurations are described in U.S. application Ser. No. 11/009,649, filed Dec. 10, 2004, entitled IMPLANTABLE MEDICAL DEVICE HAVING PRE-IMPLANT EXOSKELETON, which is incorporated herein by reference.

[0069] The device is proportioned to be passed into the patient's vasculature and to be anchored within the vasculature with minimal obstruction to blood flow. Suitable sites for the device **10** may include, but are not limited to the venous system using access through the right or left femoral vein or the subclavian or brachiocephalic veins, or the arterial system using access through one of the femoral arteries. Thus, the housing **14** preferably has a streamlined maximum cross sectional diameter which may be in the range of 3-15 mm or less, with a most preferred maximum cross-sectional diameter of 3-8 mm or less. The cross-sectional area of the device in the transverse direction (i.e., transecting the longitudinal axis) should be as small as

possible while still accommodating the required components. This area is preferably in the range of approximately 79 mm<sup>2</sup> or less, and more preferably in the range of approximately 40 mm<sup>2</sup> or less, or most preferably between 12.5-40 mm<sup>2</sup>.

[0070] The cross-section of the device (transecting the longitudinal axis) may have a circular cross-section, although other cross-sections including crescent, flattened, or elliptical cross-sections may also be used. It is desirable to provide the device with a smooth continuous contour so as to avoid voids or recesses that could encourage thrombus formation on the device.

[0071] Depending on the length of the device, it may be advantageous to manufacture flexibility into the housing so that it can be easily passed through the vasculature. In the FIG. 1 embodiment, the device body is divided into housing segments **25**, each separated by flexible articulations **24** which may be formed using silicone rubber filler or other material. The articulations **24** form living hinges, which bend in response to passage of the device **10** through curved regions of the vasculature. For some embodiments, which may have device bodies of approximately 10-60 cm in length (including the length of the reservoir) with individual segments ranging from approximately 2-28 cm in length, flexibility of the device may be essential for movement and positioning of the device within the vasculature with minimal damage to the blood vessels.

[0072] Alternatively, flexibility may be achieved through the use of flexible materials for the device body.

[0073] A motor **26**, pump **28**, control circuitry and electronics **30**, and a battery **32** for powering operation of the motor and electronics are housed within the device body **14**. Although a particular arrangement of components is shown in FIG. 1, the components may be arranged in a variety of different ways, although it is desirable to arrange the components so as to make efficient use of the available space so as to minimize unnecessary bulk or length.

[0074] These components may be contained within separate housing segments **25a**, **25b**, **25c**, in which case electrical conductors may extend through the articulations **24** as needed to electrically couple the components in each of the housing segments. The mechanical elements used to connect the housing segments **25a**, **25b**, **25c** are preferably designed such that axial, flexural and torsional forces imparted to the device are transmitted by the mechanical elements rather than by the electrical conductors that extend between the segments to electrically couple the various components of the device. Suitable arrangements of mechanical and electrical elements for coupling between housing segments are described in U.S. application Ser. No. 10/862,113, filed Jun. 4, 2004, and entitled INTRAVASCULAR ELECTROPHYSIOLOGICAL SYSTEM AND METHODS, the entire disclosure of which is incorporated herein by reference.

[0075] Battery **32** may be a 3 V lithium battery although other batteries suitable for the parameters of the motor and proportioned to fit within the housing may also be used.

[0076] The electronics **30** include control circuitry for controlling operation of the motor or other pumping mechanisms. If a closed-loop system is employed, the electronics **30** will also include intelligence for receiving data concerning parameters detected by sensors and for initiating deliv-

ery of an appropriate quantity of the agent. The electronics **30** may also include telemetry circuitry allowing for on-demand control of delivery, and dosage programming and/or modification.

[0077] Various dispensing mechanisms may be used to move or pump the agent from the reservoir into the blood stream. These mechanisms include but are not limited to:

[0078] diffusion of the agent through a polymeric membrane;

[0079] osmotic pumps (e.g., pumps of the type sold by ALZA Scientific products under the trade name ALZET) which pump via osmotic pressure induced by movement of fluid into the reservoir (i.e., by osmosis) and exertion of force on a dynamic membrane which pushes the agent out of the reservoir and into blood, tissues or organs);

[0080] electromechanical micropumps. Examples include gear pumps, solenoid pumps, peristaltic pumps, vacuum pumps, venturi pumps, double-acting membrane pumps, syringe pumps and vaporization displacement pumps.

[0081] a controlled-rate compression membrane within a reservoir housing which drives the agent through an exit orifice in the reservoir at a specific rate. A variety of mechanisms may be used to cause the compression membrane to bear against the fluid in the reservoir. Such mechanisms include rechargeable osmotic pumps, compressive sleeves, or expandable springs or sleeves;

[0082] ameroid constrictor-type control, in which a ring having an adjustable orifice is disposed around a compliant reservoir and in which the inner diameter of the ring is increased/decreased to increase/reduce flow of the agent

[0083] In another embodiment of an intravascular delivery device, the device may include a plurality of tiny agent-containing reservoirs, each sealed by a barrier layer (e.g., a polymer or a low-melt metal or alloy such as gold). According to this embodiment, delivery of the agent is achieved through the application of energy (such as RF, ultrasound, or other energy forms) to the barrier layer of one or more of the reservoirs. The energy induces micro-erosion of the barrier, allowing the agent to be diffused or pumped to the bloodstream or to a target site. This may be achieved through the use of MEMS technologies, which allow mechanical elements and electronics to be formed on tiny sections of silicon substrate.

[0084] In the FIG. 1 embodiment, a pump is preferably used to pump agent into the bloodstream. One type of a pump particularly useful in the device **10** is a gear pump which propels fluid using a pair of rotating gears. Referring to FIG. 2, the pump **28** and motor **26** are disposed within one of the housing segments **25a** forming the device body. Pickup tube **18**, which extends through reservoir **12** (see FIG. 1), has an outlet **34** (FIG. 2) positioned within the housing segment **25a**. An exit tube **36** has an inlet port **38** within the segment **25a** and extends to the exterior face of the housing segment wall to form a delivery port **40** through which drug is released from the device. One or more such delivery ports may open directly into the bloodstream. The

exit tube **36** may be adjacent to the pump as shown, or it may extend to a remote portion of the device, such as the distal end of the device. Drug release may be antegrade to blood flow, or it may be retrograde so as to promote mixing of the drug with the blood. If more localized delivery of agent is desired, the device may include delivery conduits of the type described below in connection with FIGS. 10-12.

[0085] Pump **28** includes a pair of gears **42a**, **42b** disposed between the outlet **34** of the pickup tube **18** and the inlet port **38** of the exit tube **36**. The teeth of the gears are enmeshed such that rotation of one gear will compel rotation of the other gear. A fluid impermeable barrier **44** surrounds the outlet **34**, gears **42a**, **42b** and inlet port **38** to form a pump chamber **46**. The barrier **44** is spaced slightly from the outermost points of the gears so as to permit rotation of the gears.

[0086] Gear **42a** includes a socket **48** for receiving a shaft (not shown) that is driven by the motor. Thus, activation of the motor drives the gear **42a**, which in turn causes gear **42b** to rotate.

[0087] During operation, rotation of the gears in the direction of the arrows shown in FIG. 2 causes fluid to be drawn from the reservoir **12** (FIG. 1) through the pickup tube **18** and into the pump chamber **46** (FIG. 2). The fluid is propelled into and through the exit tube **36** by the teeth of the gears, thus causing the agent to pass through exit port **40** and into the bloodstream.

[0088] FIGS. 3A through 6 illustrate alternative pump configurations that may be used in an intravascular drug delivery system.

[0089] In one alternative embodiment, the pump may take the form of a peristaltic pump. Referring to FIGS. 3A and 3B, the peristaltic pump **28a** includes a plurality of rollers **50** coupled to a central hub **52** by radially-extending arms **51** (FIG. 3B). Motor **26** (FIG. 3A) is coupled to the hub such that activation of the motor rotates the hub **52**, causing the rollers **50** to revolve around the hub.

[0090] In this embodiment, pump pick-up tube **18a** extends from the reservoir **12** (FIG. 1) into the housing segment **25a**, and extends around the rollers **50** as shown in FIG. 3B. (It should be noted that the portion of the tube **18a** that extends around the bearings **50** has been omitted from FIG. 3A for clarity.) Pump pick-up tube **18a** is fluidly coupled to an exit tube **36a** that is in turn coupled to an exit port. Although not shown in FIGS. 3A and 3B, the exit port may be similar to exit port **40** of FIG. 1 or it may be positioned in a more remote location on the device body.

[0091] As best shown in FIG. 3B, a wall **54** at least partially surrounds the rollers **50**. At least a portion of the wall is positioned sufficiently close to the roller/hub assembly to cause a portion of the pick-up tube **18a** to be squeezed against the wall **54** by the rollers **50** during rotation of the hub **52**. In other words, a portion of the wall **54** is positioned such that activation of the motor **26** causes rollers **50** to roll over, and thus temporarily compress, the tube **18a** against the wall. It can be seen from FIG. 3B that the tube becomes squeezed against the upper-most portion of wall **54** by the passing roller bearing. The temporary compression of the tube **18a** drives fluid in the tube out the exit tube **36a** to the exit port. When a roller **50** separates from the delivery tube **18a**, compression is released, thereby creating suction

within the pick-up tube **18a** to draw additional fluid into it from the reservoir. Continued rotation of the hub will cause the rollers to sequentially squeeze and release the tube until the motor is turned off. Naturally, the portion of the tube **18a** that extends around the rollers is preferably formed of a flexible and compressible material such as an appropriate polymer.

[0092] Another alternative type of pump **28b** is shown in **FIG. 4**. Pump **28b** is a displacement type pump which uses a solenoid-driven plunger to drive fluid from a fluid chamber. This embodiment eliminates the need for the motor shown in prior embodiments.

[0093] For simplicity, the housing segment (such as segment **25a** in **FIG. 1**) surrounding the pump is not shown in **FIG. 4**. Referring to the figure, the pump **28b** includes a chamber **54** fluidly coupled to pickup tube **18b**. As with prior pump examples, the pickup tube **18b** is fluidly coupled to a reservoir containing the agent to be delivered to the patient. A one-way valve **55** within the pickup tube **18b** permits fluid flow into, but not out of, the chamber **54**. An exit tube **36b** extending from the chamber **54** provides a flow path for movement of agent to a delivery port **40a**. The delivery port may alternatively be formed directly into the chamber **54**. The exit tube **36b** or delivery port **40b** includes a one-way valve **57** that allows only outward flow of fluid from the chamber **54**.

[0094] A solenoid **56** is positioned adjacent to the chamber **54**. Energy for the solenoid is provided by the battery **32** (**FIG. 1**). Referring again to **FIG. 4**, a magnetic piston **58** is slidable within the solenoid **56**. Piston **58** includes a broad section that tapers at a shoulder **60** to form a plunger **62**. A portion of the plunger **62** extends through an opening in the chamber **54**. A seal **66** preferably surrounds the opening to prevent leakage of fluid from the chamber **54**. It should be noted that the solenoid might instead be sealed within the chamber **54** to prevent loss of agent from the chamber.

[0095] The plunger **62** moves between the retracted position shown in solid lines in **FIG. 4**, and the extended position shown in dashed lines. A spring **64** sits between the piston's shoulder **60** and the wall of chamber **54**, and functions to bias the plunger **62** in the retracted position.

[0096] To pre-load the pump chamber with agent, the solenoid **56** is energized to drive the piston **58** forward, causing the plunger **62** to advance within the chamber. The chamber **54** may come preloaded with a volume of saline to prevent this step from expelling air through delivery port **40** into the bloodstream. The shoulder **60** of the advancing piston compresses the spring **64** such that, upon de-energization of the solenoid, the spring expands against the shoulder **60** to return the plunger to the retracted position. Retraction of the plunger causes the chamber to fill with agent, by creating a vacuum which draws agent into the chamber via pickup tube **18b**. Naturally, the chamber **54** and the plunger **58** are proportioned such that advancement of the plunger dispenses a volume of the agent that is appropriate for the patient's condition.

[0097] To deliver the agent to the patient, the solenoid is energized, causing the plunger to drive the agent out through the delivery port **40b**. Once the agent has been delivered, the solenoid is de-activated, causing the plunger **62** to retract and to draw additional agent into the chamber **54** via pickup tube **18b**.

[0098] It should be appreciated that the **FIG. 4** embodiment may be modified to use alternative mechanisms for advancing and retracting the plunger. For example, a motor may provided with a lead screw that is coupled to the plunger. In this example, operation of the motor at a first polarity causes advancement of the plunger, whereas operation of the motor at a reverse polarity causes retraction of the plunger. As another example shown in **FIG. 5**, the plunger **62c** may be advanced by fluid (e.g., saline) introduced into a section **53** of the chamber **54c** as indicated by arrow A. The pressure of the introduced fluid advances the plunger within the chamber **54c**, thereby driving the agent out the delivery port **40c**. The fluid may be introduced directly into the chamber as shown, or in may be introduced into a bladder that expands against the plunger **62c**.

[0099] **FIG. 6A** shows yet another pump configuration using a metering screw **68** positioned within a chamber containing the agent. In this embodiment as well as the others, the chamber may be the agent reservoir **12d** itself, or it may be a separate chamber fluidly coupled to a fluid reservoir as described in previous embodiments. Rotation of the metering screw **68** causes the threads of the screw to push agent in the reservoir towards a delivery port **40d**. During use, the metering screw **68** is rotated for an appropriate number of turns to cause the necessary amount of drug to be dispensed through a delivery port **40d**. The metering screw **68** is rotated using motor **26d**, which may be a stepper motor to facilitate precise metering of the agent. **FIG. 6B** illustrates the pump configuration of **FIG. 6A** on a device **10d** having features similar to those shown in **FIG. 1**. The device **10d** additional includes an atraumatic distal end including a wire **11** to facilitate guidance of the device within a blood vessel. If the device **10d** includes telemetry circuitry, wire **11** may also be used for telemetric communication to a remote communications device.

[0100] **FIG. 7** shows an alternative embodiment of an implantable drug delivery device **10e** which differs from the **FIG. 1** embodiment largely in the construction of the reservoir. Referring to **FIG. 7**, reservoir **12e** is formed of a bladder **70** (e.g., polyurethane, polyethylene or similar material) housed within a durable housing **72**. The housing is preferably formed of titanium, molded compounds, or other durable and biocompatible materials. If the compound to be housed in the reservoir **12e** is thermally sensitive, the reservoir may include insulating materials such as to isolate the agent against the warming effects of the surrounding blood. If necessary, the housing may be equipped with a cooling system for maintaining the temperature of the agent within a desired range. Such a cooling system would be powered by the battery **32**.

[0101] To provide sufficient flexibility to allow the reservoir to move through the vasculature, the reservoir **12e** may be divided into multiple reservoir segments separated by flexible connectors **74** similar to those described above for segmenting the device housing. In this embodiment, the pickup tube **18e** preferably passes through each of the bladders **70**, and extends to the pump **28e**, which in this embodiment is positioned on an end of the device **10e**.

[0102] Although this description refers to the delivered agents as fluids, it should be mentioned that the reservoir and delivery mechanisms might be modified to allow agents in other forms such as agents in powder form (or lyophilized

agents) to be used in place of liquid agents. For example, a powder form of an agent may be stored in a titanium reservoir within the device, and a delivery mechanism (for example the screw-auger type metering pump described in connection with FIG. 6) may feed quantities of the powder into a mixing chamber. A volume of saline or other fluid may be stored in a reservoir similar to the reservoir 12 of FIG. 12. A pump, such as any of the pumps described above, would then deliver a volume of the saline into the mixing chamber to mix with a quantity of the powder to form a liquid agent, which is then pumped or released into the blood stream. This embodiment allows a larger quantity of the agent to be stored within the device, and to remain stable within the body, than could be achieved by storing a liquid form of the agent within the device. The fluid reservoir could be refilled as needed using refill techniques described below. Other mechanisms for making use of powdered forms of agents might include delivering the agents directly into the bloodstream, or mixing the agents with blood drawn into the mixing chamber.

[0103] In another example, the delivery port of the device may be positioned to inject microspheres (e.g. agents embedded in a polymer matrix) loaded with the agent upstream of a vascularized bed or upstream of a vascularized tumor. The microspheres would embolize within small vessels in the vascularized bed or tumor, and over time would elute drug from the polymer matrix into the surrounding blood. Any of the pumps described above, including an auger-type metering pump or a piston-type pump, may be used to drive the microspheres into the bloodstream. The microspheres may be provided in a liquid solution, if desired. Agent embedded in microspheres can be advantageous in that it may allow the agent to remain stable within a reservoir within the body over extended periods of time.

[0104] It should also be noted at this point that the device might be configured to deliver multiple agents. According to this type of embodiment, the agents may be simultaneously released into the blood stream, independently released, or mixed in a mixing chamber within the device prior to release into the body. For example, the device may include one reservoir that stores a pharmaceutical agent in an inactivated state, and another reservoir that stores a chemical required to activate the agent. Combining the substances in a mixing chamber or simultaneously pumping them into the bloodstream activates the agent prior to or during administration.

[0105] Referring again to FIGS. 1 and 7, the intravascular drug delivery device preferably includes a retention mechanism 16 for retaining the device in the patient's vasculature. Although various means may be used to retain the device within the vasculature, one example of a retention device is the anchor 16 of the type shown in detail in FIGS. 8A through 8E.

[0106] Referring to FIG. 8A, anchor 16 includes structural features that allow the anchor to radially engage a vessel wall. For example, a band, mesh or other framework formed of one or more shape memory (e.g., nickel titanium alloy, nitinol, thermally activated shape-memory material, or shape memory polymer) elements or stainless steel, Elgiloy, or MP35N elements may be used. The anchor may include anti-proliferative and anti-thrombogenic coatings, although in this embodiment the anchor structure 16 is preferably provided to promote tissue ingrowth to as to enhance anchor

stability within the vessel. The anchor may also have drug delivery capability via a coating matrix impregnated with one or more pharmaceutical agents.

[0107] FIG. 8B shows one anchor 16 attached to a device body 14, although two or more such anchors may alternatively be used. As shown, anchor 16 is attached to the device body 14 by a collar 76, or other suitable connection. The body 14 may include a recessed portion 78 that allows the exterior of the anchor to sit flush with the exterior of the body when the anchor is in its compressed position. The recessed portion should have smooth contours in order to discourage thrombus formation on the device.

[0108] The anchor 16 and device body 14 may be detachably connected to the recessed portion using methods that allow the anchor 16 and the device 10 to be separated in situ, for permanent or temporary removal of the device 10. A detachable connection between the anchor 16 and device 10 may utilize a snap fit between the collar 76 and device body 14. As shown in FIG. 8C, both the collar 16 and the recessed portion 78 of the implant may include an elliptical cross-section. If it becomes necessary to remove the device 10 from the patient's body, the device may be torqued about its longitudinal axis, causing the device body 14 to cam the edges of the collar 76 to a slightly opened position, thereby allowing the device body to be passed between the edges 80 of the collar 76. In an alternative embodiment, a clevis pin-type connection may be made between the anchor 16 and the device body 14. Such a connection would be provided with a remotely actuated mechanism for releasing the clevis pin connection to thus permit separation of the device and the anchor.

[0109] The anchor may be configured such that the device 10 and anchor 16 share a longitudinal axis, or such that the axes of device 10 and anchor 16 are longitudinally offset.

[0110] Referring to FIG. 8D, a retractable sheath 82 may be slidably positioned over the anchor 16 and device 10 so as to retain the anchor in its compressed position. Retraction of the sheath as indicated in FIG. 8E allows the anchor 16 to expand into contact with the surrounding walls of the vessel, thereby holding the medical implant in the desired location. Once deployed, the anchor 16 is preferably intimate to the vessel wall, which is distended slightly, allowing the vessel lumen to remain approximately continuous despite the presence of the anchor and thus minimizing turbulence or flow obstruction.

[0111] The anchor 16 is beneficial in that it is implanted integrally with the device, and thus does not require a separate implantation step. However, non-integral anchors may also be equally useful. Examples of non-integral anchors are described in U.S. application Ser. No. 10/862, 113, filed Jun. 4, 2004, and entitled INTRAVASCULAR ELECTROPHYSIOLOGICAL SYSTEM AND METHODS, the entire disclosure of which is incorporated herein by reference.

[0112] FIGS. 9A through 9C illustrate a method for implanting an intravascular drug delivery device such as device 10 of FIG. 1 in the inferior vena cava (IVC). First, a small incision is formed in the femoral vein and an introducer 84 is inserted through the incision into the vein to keep the incision open during the procedure. Next, the device 10 is passed into the introducer 84, and pushed in a

superior direction into the inferior vena cava ("IVC"). With an end of the device **10** still remaining outside the body, a mandrel **86** (**FIG. 9B**) is attached to the fill port **22** at the exposed end of the device **10**. Pressure is applied against the mandrel **86** to advance the device **10** to the target location. See **FIG. 9B**.

[0113] Once the device has been properly positioned, the anchor **16** is deployed as described in connection with **FIGS. 8E and 8F**. Although the anchor can be positioned anywhere along the length of the device, in one example the anchor position is positioned at a distance of approximately 3-5 cm inferior to the right atrium (RA).

[0114] If the device **10** is not pre-filled with agent prior to implantation, agent may be introduced into the reservoir using the mandrel **86**. Referring to **FIG. 9C**, a syringe **87** containing agent is coupled to the mandrel **86** and the agent is injected from the syringe **87** into the device reservoir **12** (**FIG. 1**) via the mandrel **86**. The mandrel **86** and introducer **84** are removed from the body, leaving the device in place. The physician may next use an external telemetry unit **89** to set the dosing schedule and any other necessary parameters. Telemetry systems permitting external devices to communicate with implanted medical devices are known in the art. See, for example, U.S. Pat. Nos. 6,824,561, 5,312,453 and 5,127,404. Alternatively, the device may be pre-programmed with a dosing schedule prior to implantation.

[0115] Referring to **FIG. 9D**, it should be noted that if mandated by the length of the device (due to, for example, a sizeable reservoir **12** and/or a string several batteries **32** as shown), the device may extend from the inferior vena cava (IVC), through the right atrium of the heart (RA), to the superior vena cava (SVC) and into the left subclavian vein (LSV) as shown. Implantation of a system of this length may be facilitated by the use of guidewires. Techniques for guidewire implantation of intravascular systems are shown and described in U.S. application Ser. No. 10/862,113, filed Jun. 4, 2004, and entitled INTRAVASCULAR ELECTRO-PHYSIOLOGICAL SYSTEM AND METHODS, the entire disclosure of which is incorporated herein by reference (the '113 application).

[0116] Referring again to **FIG. 9C**, if at a later date it becomes necessary to add additional agent to the reservoir, the mandrel **86** may be reintroduced and coupled to the device **10** to allow agent to then be directed through the mandrel to the reservoir **12** using syringe **87** or similar means. To facilitate this process, the mandrel may have a distal coupling comprising a mouth that is significantly broader than the proximal end of the device. When the mandrel is advanced towards the device **10** within the vessel, the mouth will pass over the proximal end of the device **10** and will then be clamped over the proximal end of the device to sealingly engage the device to create a fluid coupling between the mandrel's fluid lumen and the fill port **22**.

[0117] As another alternative shown in **FIG. 9E**, the device may include a permanent flexible refill tube **23** having fill port **22a** at its proximal end. Tube **23** extends through the vasculature from the device location. The proximal end of the tube is positioned in a subcutaneous pocket and can be grasped and withdrawn through an incision (e.g. in the groin region) for fluid coupling to a refill vessel (e.g. syringe **87**, **FIG. 9C**) outside the body. Once the reservoir **12** is refilled, tube **23** is tucked back into the pocket until

accessed again during future refilling. Other methods for refilling the reservoir are discussed below.

[0118] **FIG. 10** shows an alternative embodiment of an intravascular drug delivery device **10f** utilizing an alternative arrangement of elements. The device is shown implanted within a blood vessel. In this arrangement, device **10** includes diagnostic electronics **88** for monitoring a physical and/or chemical condition of the patient, a valve **90**, and valve control electronics **92** that are responsive to the diagnostic electronics to allow an appropriate dose of a drug compound to be released through the valve **90** and into the bloodstream. The drug compound is contained within a reservoir **94** which may, but need not be, similar to the reservoirs described elsewhere in this application. A refill port **96** allows the reservoir **94** to be refilled using a refill device passed through the vasculature. A mandrel connector **98** is engageable by an implantation mandrel **102** as described above. Although the refill port is shown as remote from the mandrel connection, the refill port may instead be positioned in fluid communication with the mandrel connector **98** as described in connection with the **FIG. 1** embodiment so that the device can be refilled using mandrel **102**.

[0119] The device may include a pressure generator **106** which osmotically generates sufficient pressure to drive agent from the reservoir and out of the valve **90**. Alternatively, one of a variety of mechanisms, including those described above, may be used to drive agent from the reservoir.

[0120] A battery **106** powers the system and may be detachable from the device **12** for in-situ battery replacement. Mandrel connector **98** allows the mandrel **102** to be connected to the device and used for guiding the device (e.g., by pushing, pulling and/or torquing) through the patient's vasculature and into position during implantation. The connector **98** may take the form of a threaded bore for receiving a threaded screw member at the distal end of the mandrel **102**, or it may have any other type of configuration for detachably engaging the distal end of the mandrel. As discussed, the mandrel may be used for re-filling the reservoir in the device with pharmaceutical agents, and it also be used for in-situ replacement of the battery.

[0121] In yet another embodiment, the device may be configured with a removeable drug reservoir, such that a mandrel may be used to separate the drug reservoir from the device **10** and to attach a fresh reservoir into the device.

[0122] Mandrel **102** may serve purely mechanical purposes, or it may also be a "smart mandrel" that provides electrical connections. Such connections can be used to couple the device (via an instrument cable) for direct electrical and/or electronic communication between the device and instrumentation located outside the body. This communication may be used several purposes, including device testing, initiation and/or programming during implantation, reaccess to the device for reprogramming or diagnostic testing, and/or recharging of the device battery.

[0123] The components within the device are disposed within an enclosure that may include some or all of the features of the housing described in connection with the **FIG. 1** embodiment.

[0124] Device **10f** may include delivery conduits such as elongate tubules **108** that create a fluid path from the device

10f to a target location within the body. For example, if it is desired to direct drugs to certain tissues or a particular organ, such as the brain, kidney or the heart, the distal ends of the delivery conduits 108 are passed through the appropriate vasculature to the target organ using guidewires or other implantation means.

[0125] Obviously, the positioning of the delivery conduits 108 will depend on the location to which drugs are to be delivered. For example, a delivery conduit 108 may extend into the left subclavian artery and may be positioned to administer drugs to the upper extremities, including the brain. As illustrated in FIG. 11, a device 10g may be positioned in the aorta and have a delivery conduit 108 positionable to direct agent into the hepatic artery (HA) or vessels further downstream of the hepatic artery for delivery of drugs to the liver for cancer treatment or for other purposes such as treatment of hepatitis. The vessel into which drug is delivered may be selected to be one that feeds the particular region of the organ of the liver to be treated, or one that feeds a vascularized tumor of the liver. The figure shows the delivery conduit 108 anchored in position using an (optional) anchor 16a. As yet another alternative shown in FIG. 12, the delivery conduits 108a,b may be positioned to deliver drugs into the blood flowing into the kidneys (e.g., for treatment of cardio-renal syndrome, cancer, or other conditions), with delivery conduit 108a extending into the right renal artery and delivery conduit 108b extending into the left renal artery. Agent flows into the delivery conduits 108a, 108b from the device 10h, which may be positioned in the descending aorta as shown.

[0126] Implantation of the FIGS. 11 and 12 embodiments may be carried out using methods described above. However it should be noted that guidewire techniques may be used for implantation of delivery conduits 108, 108a, 108a (FIGS. 11 and 12) in a manner similar to the lead implantation techniques described in U.S. patent application Ser. No. 10/862,113.

[0127] In the FIG. 11 and FIG. 12 embodiments it may be particularly useful to provide the agent in the form of microspheres (e.g. agent embedded in a polymer matrix), which once released onto the bloodstream would become lodged in capillaries, arterioles, or associated small blood vessels from which they would release the embedded agent over time. For example, referring again to the FIG. 11 embodiment, for cancer treatment the delivery conduit 108 may be selectively positioned to direct agent into a feeder vessel for a vascularized tumor of the liver, allowing highly selective control of microsphere delivery to a target site. One type of microsphere that may be useful for this purpose is the doxorubicin Drug Eluting Bead manufactured by Biocompatibles International PLC of Farnham, Surrey, UK.

[0128] The size of the microsphere may be selected to embolize within target feeder vessels, allowing the microsphere to limit blood flow to (and to thus starve) the tumor while simultaneously eluting agent into the tumor. The microspheres may be selected to be biologically activated, chemically activated, or activated through physical means. For example, biological activation may occur through bulk erosion of the polymer with consequent release of the drug, or through a diffusion of a more-rapidly dissolvable drug from a relatively less-rapidly degradable polymer matrix. Materials may be selected that are sensitive to particular

conditions with the body (e.g. pH levels) so as to trigger agent release. As another example, chemical agents may be injected into contact with the microspheres (using the device 10 or a separate delivery mechanism) to trigger release of agent from the microspheres, or physical activation may be achieved by exposing the microspheres to energy generated by ultrasonic, magnetic, thermal or light sources. The microspheres may also be responsive to chemical de-activation, i.e. by injecting a chemical into contact with the microspheres to "turn-off" the microspheres thereby preventing further erosion or diffusion.

[0129] In an alternative embodiment, the system may be adapted to release radioactive beads (e.g. yttrium-90 impregnated glass beads) from the device to a targeted vascularized bed such as a tumor for cancer radiation treatment. Alternatively, a modified device containing radioactive particles (e.g. beads impregnated with Thulium 170 or P-32) may be advanced through the vasculature into a vessel within a tumor mass for radiation treatment. In this type of embodiment, a radio-protective storage housing might be positioned within the vasculature such that the modified device could be withdrawn into the radio-protective housing before and after the radiation treatment.

[0130] In some instances, it may be desirable to refill the system with additional agent. Thus, the embodiment of FIG. 12 (or the prior embodiments) may include an optional conduit 108c that is positioned to extend through a small needle stick formed in the aorta or other blood vessel. Conduit 108c is coupled to a subcutaneous reservoir or pad 110 for recharging/refilling the reservoir of device 10h. The subcutaneous reservoir 110 may be an elastomeric bladder positioned in the patient's body such as beneath the skin on the patient's chest. The membrane overlaying the bladder may be identified using a physical marker (e.g., tattoo) to allow the bladder to be easily located when it is necessary to recharge the reservoir. The subcutaneous reservoir 110 is recharged by injecting the bladder using a hypodermic needle containing the pharmaceutical compound. The bladder material is preferably self-sealing so that needle punctures will reseal following recharging. If necessary, the reservoir or pad and associated tubules may be coated or loaded with silver nitrate, steroids, anti-proliferative or anti-inflammatory compounds.

[0131] FIG. 13 shows a refill port 114 and conduit 108d for use with an implantable drug delivery device 10i. In this embodiment, the refill port 114 is positionable within a vessel that is easily accessible using a needle passed through the skin. One such vessel is the right axillary vein (RAV) accessible using a needle inserted into the arm. Another example is the femoral vein which may be accessed via a needle stick to the groin. Conduit 108d fluidly couples the refill port 114 to the device's agent reservoir. Refilling of the reservoir is carried out by locating the refill port 114 by palpating the skin or by locating a tattoo marking the port's location. A syringe containing the appropriate agent is then passed through the skin and into the port, and is used to inject the compound into the port. The compound flows through the conduit 108d and into the reservoir within the device 10i. The reservoir may be maintained at a negative pressure so as to draw the agent from the syringe once fluid communication is established. This provides feedback to the user that the syringe needle has been inserted at the proper



location and can thus help to avoid injection of the agent directly into the patient in the event the refill port 114 is missed by the needle.

[0132] Various embodiments of systems, devices and methods have been described herein. These embodiments are given only by way of example and are not intended to limit the scope of the present invention. It should be appreciated, moreover, that the various features of the embodiments that have been described might be combined in various ways to produce numerous additional embodiments. Moreover, while various materials, dimensions, shapes, implantation locations, etc. have been described for use with disclosed embodiments, others besides those disclosed may be utilized without exceeding the scope of the invention.

1. A system for intravascular drug delivery, the system comprising:

- a reservoir proportioned for implantation within a blood vessel;
- a flexible elongate device body proportioned for implantation within the blood vessel;
- an anchor coupled to the device body and expandable into contact with a wall of the blood vessel;
- a pump housed within the device body and fluidly coupled to the reservoir, the pump operable to direct agent from the reservoir into the bloodstream.

2. The system according to claim 1, wherein the reservoir is housed within the device body.

3. The system according to claim 2, wherein the reservoir comprises an inflatable bladder disposed within the device body.

4. The system according to claim 1, wherein the reservoir is external to the device body.

5. The system according to claim 4, wherein the reservoir comprises an elongate inflatable bladder extending longitudinally from the device body.

6. The system according to claim 1, wherein the pump includes a motor and an energy source electrically coupled to the motor.

7. The system according to claim 5, wherein the energy source includes a battery.

8. The system according to claim 1, wherein the reservoir extends longitudinally from the device body.

9. The system according to claim 1, wherein the device body includes at least one flexible region, the region sufficiently flexible to permit bending of the device body during movement of the device through a blood vessel.

10. The system of claim 9, wherein the device body includes a plurality of housing segments, and flexible regions interconnecting adjacent housing segments.

11. The system of claim 10, wherein the pump is sealed within one of the housing segments, and wherein the system further includes a motor and a battery each sealed within housing segments.

12. The system of claim 10, wherein the reservoir is positioned within a plurality of the housing segments.

13. The system of claim 13, wherein the reservoir includes a plurality of bladders, each positioned in a corresponding one of the housing segments.

14. The system of claim 1, wherein the device body is formed of titanium.

15. The system of claim 1, wherein the device body has a length of approximately 10 cm or greater.

16. The system of claim 1, wherein the device body has a cross-sectional area of approximately 79 mm<sup>2</sup> or less.

17. The system of claim 16, wherein the pulse generator has a cross-sectional area of approximately 40 mm<sup>2</sup> or less.

18. The system of claim 1, wherein the pump is selected from the group of pumps consisting of gear pumps, peristaltic pumps, solenoid pumps, vacuum pumps, venturi pumps, double-acting membrane pumps, metering pumps, syringe pumps and vaporization displacement pumps.

19. The system according to claim 1, wherein the reservoir contains microspheres containing an agent.

20. The system of claim 1, further including telemetry circuitry within the device housing and a remote communication device operable from outside the body to communicate with the telemetry circuitry.

21. The system according to claim 1, further including at least one elongate conduit extending from the device body, wherein the pump is operable to direct agent through the conduit into the bloodstream.

22. The system according to claim 21, further including an anchor expandable to anchor the elongate conduit within a blood vessel.

23. The system according to claim 21, wherein the device body is positionable in a first blood vessel and the conduit is positionable in a second, different, blood vessel.

24. The system according to claim 1, wherein the system includes a fill conduit extending from the reservoir, a fill port coupled to the fill conduit, and an extracorporeal reservoir connectable to the fill conduit.

25. The system according to claim 24, wherein the fill port is positionable within a blood vessel.

26. The system according to claim 24, wherein the fill port is positionable within a subcutaneous pocket.

27. The system according to claim 24, wherein the extracorporeal reservoir comprises a syringe.

28. The system according to claim 24, wherein the syringe includes a needle engageable with the fill port.

29. The system according to claim 1, wherein:

the reservoir includes a mixing chamber, a first chamber containing a first substance, and a second chamber containing a second substance;

the pump is a dispensing pump positioned to pump agent from the mixing chamber into the bloodstream;

the system further includes a first pump for pumping the first substance from the first chamber into the mixing chamber;

the system further includes a second pump for pumping the second substance from the second chamber into the mixing chamber.

30. The system according to claim 29, wherein the first substance is a liquid and the second substance is a powder.

31. The system according to claim 30, wherein the second pump is a metering pump.

32. The system according to claim 30, wherein the first chamber is an inflatable bladder.

33. The system according to claim 32, wherein the inflatable bladder is positioned external to the device body, and wherein the second chamber is positioned within the device body.

34. The system according to claim 1, further including:  
a controller within the device body, wherein the pump is controlled by the controller to pump agent into the bloodstream.
35. The system according to claim 34, wherein the controller is programmed to cause agent delivery according to a predetermined dosing schedule.
36. The system according to claim 34, further including a sensor on the device body for detecting a condition within the patient's body, wherein the controller is responsive to a condition detected by the sensor to cause agent to be pumped into the bloodstream.
37. The system according to claim 36, wherein the controller is responsive to a degree of the condition detected by the sensor to determine a dosage of agent to be pumped into the bloodstream.
38. The system according to claim 34, wherein the controller includes telemetry circuitry and the system includes a remote communication device operable from outside the body to communicate with the telemetry circuitry, wherein the controller is responsive to signals received by the telemetry circuitry to cause agent to be pumped into the bloodstream according to a specified dosing schedule.
39. A method for delivering an agent into the bloodstream, comprising the steps of:
- providing an intravascular drug delivery system comprising an elongate flexible device body and a reservoir;
  - percutaneously introducing the delivery system into a blood vessel and advancing the delivery system within the blood vessel, causing the device body to flex during movement through the blood vessel;
  - anchoring the delivery system within the blood vessel;
  - delivering an agent into the reservoir; and
  - releasing agent from the reservoir into the bloodstream.
40. The method of claim 39, wherein the delivering step is carried out prior to the introducing step.
41. The method of claim 39, wherein the delivering step is carried out after the introducing step.
42. The method of claim 39, wherein the delivering step causes the reservoir to inflate.
43. The method of claim 39, wherein the device body includes a plurality of housing segments, and flexible regions interconnecting adjacent housing segments, and wherein the step of causing the device body to flex includes causing bending at the flexible regions.
44. The method of claim 39, wherein the releasing step includes driving agent into the bloodstream using a pump.
45. The method of claim 39, wherein:
- the providing step provides the system to include an elongate conduit extending from the device body; and
  - the method includes positioning the conduit within a blood vessel; and
  - the releasing step includes releasing agent through the conduit into the bloodstream.
46. The method of claim 45, wherein the anchoring step includes anchoring the delivery system with the device body in a first blood vessel and positioning at least a portion of the conduit in a second blood vessel different from the first blood vessel.
47. The method of claim 46, wherein the second blood vessel is a hepatic artery.
48. The method of claim 46, wherein the second blood vessel is a renal artery.
49. The method of claim 46, wherein the second blood vessel is a subclavian artery.
50. The method of claim 39, wherein:
- the device body and reservoir include a mixing chamber, a first chamber containing a first substance, and a second chamber containing a second substance; and
  - the method includes the steps of directing a quantity of first substance from the first chamber into the mixing chamber, and directing a quantity of second substance from the second chamber into the mixing chamber to form the agent; and
  - the releasing step includes releasing the agent from the mixing chamber.
51. The method according to claim 50, wherein the first substance is a liquid and the second substance is a powder.
52. The method according to claim 50, wherein the step of directing a quantity of second substance into the mixing chamber includes the step of activating a metering pump disposed in the second chamber.
53. The method according to claim 50, wherein the first chamber is an inflatable bladder.
54. The method according to claim 39, wherein the step of delivering the agent includes delivering microspheres containing the agent.
55. The method according to claim 54, wherein releasing step includes releasing the microspheres from the reservoir.
56. The method according to claim 55, wherein the method further includes causing the microspheres to embolize within a vessel and allowing agent to elute from the microspheres into the bloodstream.
57. The method according to claim 39, wherein the system includes a pump and a controller within the device body and wherein in the releasing step the controller causes the pump to pump agent into the bloodstream according to a dosing schedule.
58. The method according to claim 57, further including the step of programming the dosing schedule into the controller prior to the introducing step.
59. The method according to claim 57, further including the step of programming the dosing schedule into the controller after the introducing step.
60. The method according to claim 59, wherein the introducing step includes the step of attaching a delivery mandrel to the device body and pushing the mandrel the position the device body within the blood vessel, and wherein the programming step includes the step of electronically coupling the delivery mandrel to a programming device positioned outside the body and transmitting the dosing schedule to the controller using the programming device.
61. The method according to claim 59, wherein the controller includes telemetry circuitry and the system further includes a remote communication device operable from outside the body to communicate with the telemetry circuitry, and wherein the programming step includes transmitting the dosing schedule to the controller using the remote communication device.
62. The method according to claim 57, wherein the system includes a sensor on the device body, wherein the method

includes the step of detecting a parameter within the body using the sensor, and wherein in the releasing step the controller is responsive to a parameter detected by the sensor to cause agent to be pumped into the bloodstream.

**63.** The method according to claim 62, wherein the detecting step determines a degree of the detected parameter, and wherein in the releasing step the controller is responsive to the detected degree to determine a dosing schedule and to cause the agent to be pumped according to the determined dosing schedule.

**64.** The method according to claim 62, wherein the sensor detects a physical or chemical parameter.

**65.** The method according to claim 64, wherein the sensor detects a parameter from the group of parameters consisting of arterial pressure, cardiac output, heart rate, Q-T interval,

AVO<sub>2</sub> difference, blood pH, blood gas levels, blood sugar, and biochemical markers.

**66.** The method according to claim 47, wherein the step of delivering the agent includes delivering microspheres containing the agent and wherein the releasing step includes releasing the microspheres from the reservoir, and wherein the method further includes causing the microspheres to embolize within a vessel and allowing agent to elute from the microspheres into the bloodstream.

**67.** The method according to claim 66, wherein the microspheres include a chemotherapeutic agent.

**68.** The method according to claim 1, wherein the reservoir contains radioactive particles.

\* \* \* \* \*

专利名称(译)	用于治疗剂的血管内递送系统		
公开(公告)号	<a href="#">US20050234431A1</a>	公开(公告)日	2005-10-20
申请号	US11/055540	申请日	2005-02-10
[标]申请(专利权)人(译)	WILLIAMS MICHAEL小号 HOLBROOK KEVIN RANSBURY TERRANCE		
申请(专利权)人(译)	WILLIAMS MICHAEL小号 HOLBROOK KEVIN RANSBURY TERRANCE		
当前申请(专利权)人(译)	SYNECOR , LLC		
[标]发明人	WILLIAMS MICHAEL S HOLBROOK KEVIN RANSBURY TERRANCE		
发明人	WILLIAMS, MICHAEL S. HOLBROOK, KEVIN RANSBURY, TERRANCE		
IPC分类号	A61B5/00 A61B5/0215 A61F2/00 A61F2/82 A61K9/22 A61K9/24 A61M5/00 A61M5/142 A61M5/172 A61M25/04 A61M31/00		
CPC分类号	A61B5/0215 A61B5/145 A61B5/14532 A61F2/82 A61F2250/0068 A61M2205/3523 A61M5/14236 A61M5/14276 A61M5/172 A61M25/04 A61M5/14232 A61M5/14216		
优先权	60/543260 2004-02-10 US 60/634585 2004-12-09 US		
外部链接	<a href="#">Espacenet</a> <a href="#">USPTO</a>		

#### 摘要(译)

本文描述了一种用于血管内药物递送系统的系统，其包括可植入血管的储器，流体连接到储器的血管内泵和可扩张成与血管壁接触的锚，以将系统保持在脉管系统内。递送导管可以从储存器延伸并且可定位在脉管系统内的选定位位置处，用于将药物递送至选定的器官或组织。

