




US 20100146300A1

(19) **United States**(12) **Patent Application Publication**  
**Brown**(10) **Pub. No.: US 2010/0146300 A1**(43) **Pub. Date: Jun. 10, 2010**(54) **HEALTH MONITORING SYSTEM**(76) Inventor: **Stephen J. Brown**, Woodside, CA  
(US)Correspondence Address:  
**HEALTH HERO NETWORK, INC.**  
**2400 GENG ROAD, SUITE 200**  
**PALO ALTO, CA 94303 (US)**(21) Appl. No.: **12/630,792**(22) Filed: **Dec. 3, 2009****Related U.S. Application Data**

(63) Continuation of application No. 10/605,228, filed on Sep. 16, 2003, which is a continuation of application No. 09/237,194, filed on Jan. 26, 1999, which is a continuation of application No. 08/481,925, filed on Jun. 7, 1995, now Pat. No. 5,899,855, which is a continuation of application No. 08/233,397, filed on Apr. 26, 1994, now abandoned, which is a continuation-in-part of application No. 07/977,323, filed on Nov. 17, 1992, now Pat. No. 5,307,263.

**Publication Classification**(51) **Int. Cl.**  
**G06F 12/14** (2006.01)  
**G06F 17/30** (2006.01)  
**G06F 13/38** (2006.01)  
**G06F 13/36** (2006.01)**G06F 1/26** (2006.01)  
**G06F 12/16** (2006.01)  
**G06F 12/02** (2006.01)  
**G06F 3/048** (2006.01)  
**G06F 9/00** (2006.01)  
**G06F 21/00** (2006.01)  
**G06F 15/16** (2006.01)  
**G06F 9/44** (2006.01)  
**G06F 19/00** (2006.01)  
**G06F 15/00** (2006.01)  
**G06F 3/12** (2006.01)(52) **U.S. Cl. .... 713/189; 707/822; 710/301; 710/305;**  
**713/300; 711/163; 711/103; 715/771; 707/812;**  
**713/2; 726/21; 709/219; 717/168; 726/22;**  
**702/19; 702/130; 358/1.15; 707/E17.001;**  
**707/E17.009; 707/E17.044; 711/E12.008;**  
**711/E12.103**(57) **ABSTRACT**

A health monitoring system includes a plurality of remote user sites, each remote user site comprising at least one health monitoring device for collection of user health monitoring data, an interactive video device, and a user interface apparatus; at least one remote computing facility configured for signal communication with, and to receive health monitoring data-related signals from, the plurality of remote user sites; and at least one computer, configured for signal communication with the remote computing facility, wherein the interactive video device is interactively coupled with the remote computing facility. Associated methods are also described.






Fig. 1.




Fig. 2.




Fig. 3.

*Fig.4.***Attention**

Calibration was  
not successful.

Please insert  
the code strip  
again.

*Fig.5.*


June 19 12:30 pm

**Blood Glucose**

**109** mg /dl  
remove test strip

*Fig.6.*

Mon Sept. 28 1992

*Fig.7.*

Sept. 20-26 1992



*Fig. 8.*

Glucose  
Ave: 123 mg/dl  
SD: 56  
Num: 15  
No. under 50: 13  
No. hypo sym: 23

*Fig. 9.*

June 12 9:30pm  
BG 113 mg/dl  
Regin 12.5 U  
NPHin 13.2 U  
Food 1 BE  
Pre-meal HYPO



*Fig. 10.*

Fig. 11.



## HEALTH MONITORING SYSTEM

### RELATED APPLICATIONS

**[0001]** This application is a Continuation of U.S. patent application Ser. No. 10/605,228, filed Sep. 16, 2003, which is a Continuation of U.S. patent application Ser. No. 09/237,194 filed Jan. 26, 1999, which is a Continuation of U.S. patent application Ser. No. 08/481,925 filed Jun. 7, 1995, now U.S. Pat. No. 5,899,855, which is a Continuation of U.S. patent application Ser. No. 08/233,397 filed Apr. 26, 1994, now abandoned. The contents of the above-listed applications are incorporated herein by reference in their entirety.

### FIELD OF THE INVENTION

**[0002]** This invention relates to self-care health monitoring arrangements that enable a patient or other user to gather data important to a health management program and, if appropriate, provide that data to a healthcare professional.

### BACKGROUND OF THE INVENTION

**[0003]** In the following discussion certain articles and methods will be described for background and introductory purposes. Nothing contained herein is to be construed as an "admission" of prior art. Applicant expressly reserves the right to demonstrate, where appropriate, that the articles and methods referenced herein do not constitute prior art under the applicable statutory provisions. Controlling or curing conditions of ill health generally involves both establishing a therapeutic program and monitoring the progress of the afflicted person. Based on that progress, decisions can be made as to altering therapy to achieve a cure or maintain the affliction or condition at a controlled level. Successfully treating certain health conditions calls for rather frequent monitoring and a relatively high degree of patient participation. For example, in order to establish and maintain a regimen for successful diabetes care, a diabetic should monitor his or her blood glucose level and record that information along with the date and time at which the monitoring took place. Since diet, exercise, and medication all affect blood glucose levels, a diabetic often must record data relating to those items of information along with blood glucose level so that the diabetic may more closely monitor his or her condition and, in addition, can provide information of value to the healthcare provider in determining both progress of the patient and detecting any need to change the patient's therapy program.

**[0004]** Advances in the field of electronics over the past several years have brought about significant changes in medical diagnostic and monitoring equipment, including arrangements for self-care monitoring of various chronic conditions. With respect to the control and monitoring of diabetes, relatively inexpensive and relatively easy-to-use blood glucose monitoring systems have become available that provide reliable information that allows a diabetic and his or her healthcare professional to establish, monitor and adjust a treatment plan (diet, exercise, and medication). More specifically, microprocessor-based blood glucose monitoring systems are being marketed which sense the glucose level of a blood sample that is applied to a reagent-impregnated region of a test strip that is inserted in the glucose monitor. When the monitoring sequence is complete, the blood glucose level is displayed by, for example, a liquid crystal display (LCD) unit.

**[0005]** Typically, currently available self-care blood glucose monitoring units include a calendar/clock circuit and a

memory circuit that allows a number of blood glucose test results to be stored along with the date and time at which the monitoring occurred. The stored test results (blood glucose level and associated time and date) can be sequentially recalled for review by the blood glucose monitor user or a health professional by sequentially actuating a push button or other control provided on the monitor. In some commercially available devices, the average of the blood glucose results that are stored in the monitor or the average of the results for a predetermined period of time, (e.g., fourteen days) also is displayed during the recall sequence. Further, some self-care blood glucose monitors allow the user to tag the test result with an "event code" that can be used to organize the test results into categories. For example, a user might use a specific event code to identify test results obtained at particular times of the day, a different event code to identify a blood glucose reading obtained after a period of exercise, two additional event codes to identify blood glucose readings taken during hypoglycemia symptoms and hyperglycemia symptoms, etc. When event codes are provided and used, the event code typically is displayed with each recalled blood glucose test result.

**[0006]** Microprocessor-based blood glucose monitoring systems have advantages other than the capability of obtaining reliable blood glucose test results and storing a number of the results for later recall and review. By using low power microprocessor and memory circuits and powering the units with small, high capacity batteries (e.g., a single alkaline battery), extremely compact and light designs have been achieved that allow taking the blood glucose monitoring system to work, school, or anywhere else the user might go with people encountered by the user not becoming aware of the monitoring system. In addition, most microprocessor-based self-care blood glucose monitoring systems have a memory capacity that allows the system to be programmed by the manufacturer so that the monitor displays a sequence of instructions during any necessary calibration or system tests and during the blood glucose test sequence itself. In addition, the system monitors various system conditions during a blood glucose test (e.g., whether a test strip is properly inserted in the monitor and whether a sufficient amount of blood has been applied to the reagent impregnated portion of the strip) and if an error is detected generates an appropriate display (e.g., "retest"). A data port may be provided that allows test results stored in the memory of the microprocessor-based blood glucose monitoring system to be transferred to a data port (e.g., RS-232 connection) of a personal computer or other such device for subsequent analysis.

**[0007]** Microprocessor-based blood glucose monitoring systems are a significant advance over previously available self-care systems such as those requiring a diabetic to apply a blood sample to reagent activated portions of a test strip; wipe the blood sample from the test strip after a predetermined period of time; and, after a second predetermined period of time, determine blood glucose level by comparing the color of the reagent activated regions of the test strip with a color chart supplied by the test strip manufacturer. Despite what has been achieved, numerous drawbacks and disadvantages still exist. For example, establishing and maintaining diabetic healthcare often requires the diabetic to record additional data pertaining to medication, food intake, and exercise. However, the event codes of currently available microprocessor blood glucose monitoring systems provide only limited capability for tagging and tracking blood glucose test results according to



food intake and other relevant factors. For example, the event codes of currently available monitoring systems only allow the user to classify stored blood glucose readings in a manner that indicates blood glucose tests taken immediately after a heavy, light or normal meal. This method of recording information not only requires subjective judgment by the system user, but will not suffice in a situation in which successfully controlling the user's diabetes requires the recording and tracking of relatively accurate information relating to food intake, exercise, or medication (e.g., insulin dosage). An otherwise significant advantage of currently available blood glucose monitoring systems is lost when blood glucose test results must be recorded and tracked with quantitative information relating to medication, food intake, or exercise. Specifically, the system user must record the required information along with a time and date tagged blood glucose test result by, for example, writing the information in a log book.

**[0008]** The use of event codes to establish subcategories of blood glucose test results has an additional disadvantage or drawback. In particular, although alphanumeric display devices are typically used in currently available microprocessor-based blood glucose monitoring systems, the display units are limited to a single line of information having on the order of six characters. Moreover, since the systems include no provision for the user to enter alphanumeric information, any event codes that are used must be indicated on the display in a generic manner (e.g., displayed as "EVENT 1", "EVENT 2", etc.) This limitation makes the system more difficult to use because the diabetic must either memorize his or her assignment of event codes or maintain a list that defines the event codes. The limited amount of data that can be displayed at any one time presents additional drawbacks and disadvantages. First, instructions and diagnostics that are displayed to the user when calibrating the system and using the system to obtain a blood glucose reading must be displayed a line at a time and in many cases, the information must be displayed in a cryptic manner.

**[0009]** The above-discussed display limitations and other aspects of currently available blood glucose monitoring systems is disadvantageous in yet another way. Little statistical information can be made available to the user. For example, in diabetic healthcare maintenance, changes or fluctuations that occur in blood glucose levels during a day, a week, or longer period can provide valuable information to a diabetic and/or his or her healthcare professional. As previously mentioned, currently available systems do not allow associating blood glucose test results with attendant quantitative information relating to medication, food intake, or other factors such as exercise that affect a person's blood glucose level at any particular point in time. Thus, currently available blood glucose monitoring systems have little or no capability for the generating and display of trend information that may be of significant value to a diabetic or the diabetic's healthcare professional.

**[0010]** Some currently available blood glucose monitoring systems provide a data port that can be interconnected with and transfer data to a personal computer (e.g., via an RS-232 connection). With such a system and a suitable programmed computer, the user can generate and display trend information or other data that may be useful in administering his or her treatment plan. Moreover, in such systems, data also can be transferred from the blood glucose monitoring system to a healthcare professional's computer either directly or remotely by telephone if both the blood glucose monitoring

system (or computer) to which the data has been downloaded and the healthcare professional's computer are equipped with modems. Although such a data transfer provision allows a healthcare professional to analyze blood glucose data collected by a diabetic, this aspect of currently available blood glucose monitoring systems has not found widespread application. First, the downloading and subsequent analysis feature can only be used by system users that have ready access to a computer that is programmed with appropriate software and, in addition, have both the knowledge required to use the software (and the inclination to do so). This same problem exists with respect to data transfer to (and subsequent analysis by) a healthcare professional. Moreover, various manufacturers of systems that currently provide a data transfer feature do not use the same data format. Therefore, if a healthcare professional wishes to analyze data supplied by a number of different blood glucose monitoring systems, he or she must possess software for each of the systems and must learn to conduct the desired analyses with each software system.

**[0011]** The above-discussed disadvantages and drawbacks of microprocessor-based self-care health monitoring systems take on even greater significance with respect to children afflicted with diabetes, asthma and other chronic illnesses. In particular, a child's need for medication and other therapy changes as the child grows. Current microprocessor-based self-care health monitoring systems generally do not provide information that is timely and complete enough for a healthcare professional to recognize and avert problems before relatively severe symptoms develop. Too often, a need for a change in medication and/or other changes in therapeutic regimen is not detected until the child's condition worsens to the point that emergency room care is required.

**[0012]** Further, currently available microprocessor-based health monitoring systems have not been designed with children in mind. As previously mentioned, such devices are not configured for sufficient ease of use in situations in which it is desirable or necessary to record and track quantitative information that affects the physical condition of the system user (e.g., medication dosage administered by a diabetic and food intake). Children above the age at which they are generally capable of obtaining blood samples and administering insulin or other medication generally can learn to use at least the basic blood glucose monitoring features of currently available microprocessor-based blood glucose monitoring systems. However, the currently available monitoring systems provide nothing in the way of motivation for a child to use the device and, in addition, include little or nothing that educates the child about his or her condition or treatment progress.

**[0013]** The lack of provision for the entering of alphanumeric data also can be a disadvantage. For example, currently available blood glucose monitoring systems do not allow the user or the healthcare professional to enter information into the system such as medication dosage and other instructions or data that is relevant to the user's self-care health program.

**[0014]** The above-discussed disadvantages and drawbacks of currently available microprocessor-based blood glucose monitoring systems also have been impediments to adopting the basic technology of the system for other healthcare situations in which establishing and maintaining an effective regimen for cure or control is dependent upon (or at least facilitated by) periodically monitoring a condition and recording that condition along with time and date tags and

other information necessary or helpful in establishing and maintaining a healthcare program.

#### SUMMARY OF THE INVENTION

**[0015]** Certain aspects of this invention provide a new and useful system for healthcare maintenance in which the invention either serves as a peripheral device to (or incorporates) a small handheld microprocessor-based unit of the type that includes a display screen, buttons or keys that allow a user to control the operation of the device and a program cartridge or other arrangement that can be inserted in the device to adapt the device to a particular application or function. The invention in effect converts the handheld microprocessor device into a healthcare monitoring system that has significant advantages over systems such as the currently available blood glucose monitoring systems. To perform this conversion, the invention includes a microprocessor-based healthcare data management unit, a program cartridge and a monitoring unit. When inserted in the handheld microprocessor unit, the program cartridge provides the software necessary (program instructions) to program the handheld microprocessor unit for operation with the microprocessor-based data management unit. Signal communication between the data management unit and the handheld microprocessor unit is established by an interface cable. A second interface cable can be used to establish signal communication between the data management unit and the monitoring unit or, alternatively, the monitoring unit can be constructed as a plug-in unit having an electrical connector that mates with a connector mounted within a region that is configured for receiving the monitoring unit.

**[0016]** According to certain embodiments, in operation, the control buttons or keys of the handheld microprocessor-based unit are used to select the operating mode for both the data management unit and the handheld microprocessor-based unit. In response to signals generated by the control buttons or keys, the data management unit generates signals that are coupled to the handheld microprocessor unit and, under control of the program instructions contained in the program cartridge, establish an appropriate screen display on the handheld microprocessor-based unit display. In selecting system operating mode and other operations, the control buttons are used to position a cursor or other indicator in a manner that allows the system user to easily select a desired operating mode or function and provide any other required operator input. In the disclosed detailed embodiment of the invention several modes of operation are made available.

**[0017]** In certain embodiments of the invention, the handheld microprocessor unit is a compact video game system such as the system manufactured by Nintendo of America Inc. under the trademark "GAME BOY". Use of a compact video game system has several general advantages, including the widespread availability and low cost of such systems. Further, such systems include switch arrangements that are easily adapted for use in the invention and the display units of such systems are of a size and resolution that can advantageously be employed in the practice of the invention. In addition, such systems allow educational or motivational material to be displayed to the system user, with the material being included in the program cartridge that provides the monitor system software or, alternatively, in a separate program cartridge.

**[0018]** The use of a compact video game system for the handheld microprocessor-based unit of the invention can be advantageous with respect to children. Specifically, the com-

pact video game systems of the type that can be employed in the practice of the invention are well known and well accepted by children. Such devices are easily operated by a child and most children are well accustomed to using the devices in the context of playing video games. Motivational and educational material relating to the use of the invention can be presented in game-like or animated format to further enhance acceptance and use of the invention by children that require self-care health monitoring.

**[0019]** A microprocessor-based health monitoring system that is configured in accordance with some embodiments of the invention provides additional advantages for both the user and a healthcare professional. In accordance with one aspect of the invention, standardized reports are provided to a physician or other healthcare provider by means of facsimile transmission. To accomplish this, the data management unit of some embodiments of the invention include a modem which allows test results and other data stored in system memory to be transmitted to a remote clearinghouse via a telephone connection. Data processing arrangements included in the clearinghouse perform any required additional data processing; format the standardized reports; and, transmit the reports to the facsimile machine of the appropriate healthcare professional.

**[0020]** The clearinghouse also can fill an additional communication need, allowing information such as changes in medication dosage or other information such as modification in the user's monitoring schedule to be electronically sent to a system user. In arrangements that incorporate this particular aspect of the invention, information can be sent to the user via a telephone connection and the data management unit modem when a specific inquiry is initiated by the user, or when the user establishes a telephone connection with the clearinghouse for other purposes such as providing data for standardized reports.

**[0021]** The clearinghouse-facsimile aspect of the invention allows a healthcare professional to receive timely information about patient condition and progress without requiring a visit by the patient (system user) and without requiring analysis or processing of test data by the healthcare professional. In this regard, the healthcare professional need not possess or even know how to use a computer and/or the software conventionally employed for analysis of blood glucose and other health monitoring data and information.

**[0022]** The invention may also include provision for data analysis and memory storage of information provided by the user and/or the healthcare professional. In particular, the data management units of the currently preferred embodiments of the invention include a data port such as an RS-232 connection that allows the system user or healthcare professional to establish signal communication between the data management unit and a personal computer or other data processing arrangement. Blood glucose test data or other information can then be downloaded for analysis and record keeping purposes. Alternatively, information such as changes in the user's treatment and monitoring regimen can be entered into system memory. Moreover, if desired, remote communication between the data management unit and the healthcare professional's computer can be established using the clearinghouse as an element of the communications link. That is, in the currently preferred arrangements of the invention a healthcare professional has the option of using a personal computer that communicates with the clearinghouse via a modem and telephone line for purposes of transmitting instructions and

information to a selected user of the system and/or obtaining user test data and information for subsequent analysis.

**[0023]** The invention can be embodied in forms other than those described above. For example, although small handheld microprocessor-based units such as a handheld video game system or handheld microprocessor-based units of the type often referred to as "palm-top" computers provide many advantages, there are situations in which other compact microprocessor-based units can advantageously be used. Among the various types of units that can be employed are using compact video game systems of the type that employ a program cartridge, but uses a television set or video monitor instead of a display unit that is integrated into the previously described handheld microprocessor-based units.

**[0024]** Those skilled in the art also will recognize that the above-described microprocessor-implemented functions and operations can be apportioned between one or more microprocessors in a manner that differs from the above-described arrangement. For example, in some situations, the programmable microprocessor-based unit and the program cartridge used in practicing the invention may provide memory and signal processing capability that is sufficient for practicing the invention. In such situations, the microprocessor of the microprocessor-based data management unit of the above-described embodiments in effect is moved into the video game system, palm-top, computer or programmable microprocessor device. In such an arrangement, the data management unit can be realized as a relatively simple interface unit that includes little or no signal processing capability. Depending upon the situation at hand, the interface unit may or may not include a telephone modem and/or an RS-232 connection (or other data port) for interconnecting the healthcare system with a computer or other equipment. In other situations, the functions and operations associated with processing of the monitored health care data may be performed by a microprocessor that is added to or already present in the monitoring device that is used to monitor blood glucose or other condition.

**[0025]** Because the invention can be embodied to establish systems having different levels of complexity, the invention satisfies a wide range of self-care health monitoring applications. The arrangements that include a modem (or other signal transmission facility) and sufficient signal processing capability can be employed in situations in which reports are electronically transmitted to a healthcare professional either in hard copy (facsimile) form or in a signal format that can be received by and stored in the healthcare professional's computer. On the other hand, less complex (and, hence, less costly) embodiments of the invention are available for use in which transfer of system information need not be made by means of telephonic data transfer or other remote transmission methods. In these less complex embodiments, transfer of data to a healthcare professional can still be accomplished. Specifically, if the program cartridge includes a battery and suitable program instructions, monitored healthcare data can be stored in the program cartridge during use of the system as a healthcare monitor. The data cartridge can then be provided to the healthcare professional and inserted in a programmable microprocessor-based unit that is the same as or similar to that which was used in the healthcare monitoring system. The healthcare professional can then review the data, and record it for later use, and/or can use the data in performing various analyses. If desired, the microprocessor-based unit used by the healthcare professional can be programmed and arranged

to allow information to be stored in the cartridge for return to and retrieval by the user of the healthcare monitoring system. The stored information can include messages (e.g., instructions for changes in medication dosage) and/or program instructions for reconfiguring the program included in the cartridge so as to effect changes in the treatment regimen, the analyses or reports to be generated by the healthcare monitoring system, or less important aspects such as graphical presentation presented during the operation of the healthcare system.

#### BRIEF DESCRIPTION OF THE DRAWINGS

**[0026]** The foregoing aspects and many of the attendant advantages of this invention will become more readily appreciated as the same becomes better understood by reference to the following detailed description, when taken in conjunction with the accompanying drawings, wherein:

**[0027]** FIG. 1 is a block diagram that illustrates a healthcare monitoring system arranged in accordance with the invention;

**[0028]** FIG. 2 diagrammatically illustrates monitoring systems constructed in accordance with the invention connected in signal communication with a remotely located computing facility which includes provision for making the data supplied by the monitoring system of the invention available to a designated healthcare professional and/or for providing data and instructions to the system user;

**[0029]** FIG. 3 is a block diagram diagrammatically depicting the structural arrangement of the system data management unit and its interconnection with other components of the system shown in FIG. 1;

**[0030]** FIGS. 4-10 depict typical system screen displays of data and information that can be provided by the arrangements shown in FIGS. 1-3; and

**[0031]** FIG. 11 diagrammatically illustrates an alternative healthcare monitoring system that is arranged in accordance with the invention.

#### DETAILED DESCRIPTION

**[0032]** FIG. 1 depicts a self-care health monitoring system arranged in accordance with the invention. In the arrangement shown in FIG. 1, a data management unit 10 is electrically interconnected with a handheld microprocessor-based unit 12 via a cable 14. In the depicted arrangement, data management unit 10 also is electrically interconnected with a blood glucose monitor 16 of the type capable of sensing blood glucose level and producing an electrical signal representative thereof. Although FIG. 1 illustrates blood glucose monitor 16 as being connected to data management unit 10 by a cable 18, it may be preferable to construct blood glucose monitor 16 as a plug-in unit that is placed in a recess or other suitable opening or slot in data management unit 10. Regardless of the manner in which blood glucose monitor 16 is interconnected with data management unit 10, both that interconnection and cable 14 are configured for serial data communication between the interconnected devices.

**[0033]** Also shown in FIG. 1 are two additional monitoring devices and 22, which are electrically connected for serial data communication with data management unit 10 via cables 24 and 26, respectively. Monitoring units 20 and 22 of FIG. 1 represent devices other than blood glucose monitor 16 that can be used to configure the invention for self-care health monitoring applications other than (or in addition to) diabetes

care. For example, as is indicated in FIG. 1, the monitoring device 20 can be a peak-flow meter that provides a digital signal representative of the airflow that results when a person suffering from asthma or another chronic respiratory affliction expels a breath of air through the meter. As is indicated by monitor 22 of FIG. 1, various other devices can be provided for monitoring conditions such as blood pressure, pulse, and body temperature to thereby realize systems for self-care monitoring and control of conditions such as hypertension, certain heart conditions and various other afflictions and physical conditions. Upon understanding the hereinafter discussed aspects and features of the invention it will be recognized that the invention is easily implemented for these and other types of healthcare monitoring. In particular, monitors used in the practice of the invention can be arranged in a variety of ways as long as the data to be recorded or otherwise employed by handheld microprocessor unit 12 and/or data management unit 10 is provided in serial format in synchronization with clock signals provided by data management unit 10. As is the case with blood glucose monitor 16, the additional monitors can be configured as plug-in units that are directly received by data management unit 10, or can be connected to data management unit 10 with cables (as shown in FIG. 1).

**[0034]** As is shown in FIG. 1, handheld microprocessor unit 12 includes a display screen 28 and a plurality of switches or keys (30, 32, 34, 36, and 38 in FIG. 1), which are mounted on a housing 40. Located in the interior of housing 40, but not shown in FIG. 1, are a microprocessor, memory circuits, and circuitry that interfaces switches 30, 32, 34, 36 and 38 with the microprocessor.

**[0035]** Stored in the memory of program handheld microprocessor unit 12 is a set of program instructions that establishes a data protocol that allows handheld microprocessor unit 12 to perform digital data signal processing and generate desired data or graphics for display on display unit 28 when a program cartridge 42 is inserted in a slot or other receptacle in housing 40. That is, program cartridge 42 of FIG. 1 includes read-only memory units (or other memory means such as battery-powered random access memory) which store program instructions and data that adapt handheld microprocessor 12 for operation in a blood glucose monitoring system. More specifically, when the instructions and data of program cartridge 42 are combined with program instructions and data included in the internal memory circuits of handheld microprocessor unit 12, handheld microprocessor unit 12 is programmed for processing and displaying blood glucose information in the manner described below and additional monitors 22 to provide health monitoring for asthma and various other previously mentioned chronic conditions. In each case, the plurality of switches or keys (30, 32, 34, 36, and 38 in FIG. 1) are selectively operated to provide signals that result in pictorial and/or alphanumeric information being displayed by display unit 42.

**[0036]** Various devices are known that meet the above-set forth description of handheld microprocessor unit 12. For example, compact devices are available in which the plurality of keys allows alphanumeric entry and internal memory is provided for storing information such as names, addresses, phone numbers, and an appointment calendar. Small program cartridges or cards can be inserted in these devices to program the device for various purposes such as the playing of games, spreadsheet application, and foreign language translation sufficient for use in travel. More recently, less compact products

that have more extensive computational capability and are generally called "palm-top" computers have been introduced into the marketplace. These devices also can include provision for programming the device by means of an insertable program card or cartridge.

**[0037]** The currently preferred embodiments of the invention are configured and arranged to operate in conjunction with yet another type of handheld microprocessor unit. Specifically, in the currently preferred embodiments of the invention, program cartridge 42 is electrically and physically compatible with commercially available compact video game systems, such as the system manufactured by Nintendo of America Inc. under the trademark "GAME BOY". Configuring data management unit 10 and program cartridge 42 for operation with a handheld video game system has several advantages. For example, the display unit of such a device provides display resolution that allows the invention to display both multi-line alphanumeric information and graphical data. In this regard, the 160×144 pixel dot matrix-type liquid crystal display screen currently used in the above-referenced compact video game systems provides sufficient resolution for at least six lines of alphanumeric text, as well as allowing graphical representation of statistical data such as graphical representation of blood glucose test results for a day, a week, or longer.

**[0038]** Another advantage of realizing handheld microprocessor unit 12 in the form of a compact video game system is the relatively simple, yet versatile arrangement of switches that is provided by such a device. For example, as is indicated in FIG. 1, a compact video game system includes a control pad 30 that allows an object displayed on display unit 42 to be moved in a selected direction (i.e., up-down or left-right). As also is indicated in FIG. 1, compact video game systems typically provide two pair of distinctly-shaped push button switches. In the arrangement shown in FIG. 1, a pair of spaced-apart circular push button switches (36 and 38) and a pair of elongate switches (32 and 34) are provided. The functions performed by the two pairs of switches is dependent upon the program instructions contained in each program cartridge 42.

**[0039]** Yet another advantage of utilizing a compact video game system for handheld microprocessor-based unit 12 of FIG. 1 is the widespread popularity and low cost of such units. In this regard, manufacture and sale of a data management unit 10, blood glucose monitor 16 and program cartridge 42 that operate in conjunction with a compact microprocessor-based video allows the self-care health monitoring system of FIG. 1 to be manufactured and sold at a lower cost than could be realized in an arrangement in which handheld unit 12 is designed and manufactured solely for use in the system of FIG. 1.

**[0040]** An even further advantage of using a compact video game system for handheld microprocessor 12 is that such video game systems include means for easily establishing the electrical interconnection provided by cable 14 in FIG. 1. In particular, such compact video game systems include a connector mounted to the game unit housing (40 in FIG. 1) and a cable that can be connected between the connectors of two video game units to allow interactive operation of the two interconnected units (i.e., to allow contemporaneous game play by two players or competition between players as they individually play identical but separate games). In the preferred embodiments of the invention, the "two-player" cable supplied with the compact video game unit being used as

handheld microprocessor unit 12 is used as cable 14 to establish serial data communication between the handheld microprocessor unit 12 (compact video game system) and data management unit 10. In these preferred embodiments, the program instructions stored on the memory of data management unit 10 and program cartridge 42 respectively program data management unit 10 and the compact video game system (i.e., handheld microprocessor unit 12) for interactive operation in which switches 30, 32, 34, 36 and 38 are used to control the operation of data management unit 10 (e.g., to select a particular operational mode such as performance of a blood glucose test or the display of statistical test data and, in addition, to control operation such as selection of an option during operation of the system in a particular operational mode). In each operational mode, data management unit 10 processes data in accordance with program instructions stored in the memory circuits of data management unit 10. Depending upon the operational mode selected by the user, data is supplied to data management unit 10 by blood glucose monitor 16, by additional monitors (20 and 22 in FIG. 1) or any interconnected computers or data processing facility (such as the hereinafter described user's computer 48 and clearinghouse 54 of FIG. 1). During such operation, mode switches 30, 32, 34, 36 and 38 are selectively activated so that signals are selectively coupled to the video game system (handheld microprocessor unit 12) and processed in accordance with program instructions stored in program cartridge 42. The signal processing performed by handheld microprocessor unit 12 results in the display of alphanumeric, symbolic, or graphic information on the video game display screen (i.e., display unit 28 in FIG. 1), which allow the user to control system operation and obtain desired test results and other information.

[0041] Although the above-discussed advantages apply to use of the invention by all age groups, employing a compact video game system in the practice of the invention is of special significance in monitoring a child's blood glucose or other health parameters. Children and young adults are familiar with compact video game systems. Thus, children will accept a health monitoring system incorporating a compact video game system more readily than a traditional system, even an embodiment of the invention that uses a different type of handheld microprocessor unit. Moreover, an embodiment of the invention that functions in conjunction with a compact video game system can be arranged to motivate children to monitor themselves more closely than they might otherwise by incorporating game-like features and/or animation in system instruction and test result displays. Similarly, the program instructions can be included in program cartridges 41, 42 and 43 (or additional cartridges) that allow children to select game-like displays that help educate the child about his or her condition and the need for monitoring.

[0042] With continued reference to FIG. 1, data management unit 10 of the currently preferred embodiments of the invention includes a data port 44 that allows communication between data management unit 10 and a personal computer 48 (or other programmable data processor). In the currently preferred embodiments of the invention, data port 44 is an RS-232 connection that allows serial data communication between data management unit 10 and personal computer 48. In the practice of the invention, personal computer can be used to supplement data management unit 10 by, for example, performing more complex analyses of blood glucose and other data that has been supplied to and stored in the memory

circuits of data management unit 10. With respect to embodiments of the invention configured for use by a child, personal computer 48 can be used by a parent or guardian to review and analyze the child's progress and to produce printed records for subsequent review by a healthcare professional. Alternatively, personal computer 48 can be used to supply data to data management unit 10 that is not conveniently supplied by using handheld microprocessor switches 30, 32, 34, 36 and 38 as an operator interface to the system shown in FIG. 1. For example, some embodiments of the invention may employ a substantial amount of alphanumeric information that must be entered by the system user. Although it is possible to enter such data by using switches 30, 32, 34, 36 and 38 in conjunction with menus and selection screens displayed on display screen 28 of FIG. 1, it may be more advantageous to use a device such as personal computer 48 for entry of such data. However, if personal computer 48 is used in this manner, some trade-off of system features may be required because data management unit 10 must be temporarily interconnected with personal computer 48 during these operations. That is, some loss of system mobility might result because a suitably programmed personal computer would be needed at each location at which data entry or analysis is to occur.

[0043] As is indicated in FIG. 1, data management unit 10 of the currently preferred embodiments of the invention also includes a modem that allows data communication between data management unit 10 and a remote computing facility identified in FIG. 1 as clearinghouse 54 via a conventional telephone line (indicated by reference numeral 50 in FIG. 1) and a modem 52 that interconnects clearinghouse 54 and telephone line 50. As shall be described in more detail, clearinghouse computing facility 54 facilitates communication between a user of the system shown in FIG. 1 and his or her healthcare professional and can provide additional services such as updating system software. As is indicated by facsimile machine 55 of FIG. 1, a primary function of clearinghouse 54 is providing the healthcare professional with standardized reports 56, which indicate both the current condition and condition trends of the system user. Although a single facsimile machine 55 is shown in FIG. 1, it will be recognized that numerous healthcare professionals (and hence facsimile machine 55) can be connected in signal communication with a clearinghouse 54.

[0044] Regardless of whether a compact video game system, another type of commercially available handheld microprocessor-based unit, or a specially designed unit is used, the preferred embodiments of FIG. 1 provide a self-care blood glucose monitoring system in which program cartridge 42: (a) adapts handheld microprocessor unit 12 for displaying instructions for performing the blood glucose test sequence and associated calibration and test procedures; (b) adapts handheld microprocessor unit 12 for displaying (graphically or alphanumerically) statistical data such as blood glucose test results taken during a specific period of time (e.g., a day, week, etc.); (c) adapts handheld microprocessor unit 12 for supplying control signals and signals representative of food intake or other useful information to data management unit 10; (d) adapts handheld microprocessor unit 12 for simultaneous graphical display of blood glucose levels with information such as food intake; and, (e) adapts handheld microprocessor unit 12 for displaying information or instructions from a healthcare professional that are coupled to data management unit 10 from a clearinghouse 54. The manner in

which the arrangement of FIG. 1 implements the above-mentioned functions and others can be better understood with reference to FIGS. 2 and 3.

**[0045]** Referring first to FIG. 2, clearinghouse 54 receives data from a plurality of self-care microprocessor-based healthcare systems of the type shown in FIG. 1, with the individual self-care health monitoring systems being indicated in FIG. 2 by reference numeral 58. Preferably, the data supplied to clearinghouse 54 by each individual self-care health monitoring system 58 consists of "raw data" (i.e., test results and related data that was stored in memory circuits of data management unit 10, without further processing by data management unit 10). For example, with respect to the arrangement shown in FIG. 1, blood glucose test results and associated data such as food intake information, medication dosage and other such conditions are transmitted to clearinghouse 54 and stored with a digitally encoded signal that identifies both the source of the information (i.e., the system user or patient) and those having access to the stored information (i.e., the system user's doctor or other healthcare professional).

**[0046]** As shall be recognized upon understanding the manner in which it operates, clearinghouse 54 can be considered to be a central server for the various system users (58 in FIG. 2) and each healthcare professional 60. In that regard, clearinghouse 54 includes conventionally arranged and interconnected digital processing equipment (represented in FIG. 2 by digital signal processor 57) which receives digitally encoded information from a user 58 or healthcare professional 60; processes the information as required; stores the information (processed or unprocessed) in memory if necessary; and, transmits the information to an intended recipient (i.e., user 58 or healthcare professional 60).

**[0047]** In FIG. 2, rectangular outline 60 represents one of numerous remotely located healthcare professionals who can utilize clearinghouse 54 and the arrangement described relative to FIG. 1 in monitoring and controlling patient healthcare programs. Shown within outline 60 is a computer 62 (e.g., personal computer), which is coupled to clearinghouse 54 by means of a modem (not shown in FIG. 2) and a telephone line 64. Also shown in FIG. 2 is the previously mentioned facsimile machine 55, which is coupled to clearinghouse 54 by means of a second telephone line 68. Using the interface unit of computer 62 (e.g., a keyboard or pointing device such as a mouse), the healthcare professional can establish data communication between computer 62 and clearinghouse 54 via telephone line 64. Once data communication is established between computer 62 and clearinghouse 54, patient information can be obtained from clearinghouse 54 in a manner similar to the manner in which subscribers to various database services access and obtain information. In particular, the healthcare professional can transmit an authorization code to clearinghouse 54 that identifies the healthcare professional as an authorized user of the clearinghouse and, in addition, can transmit a signal representing the patient for which healthcare information is being sought. As is the case with conventional database services and other arrangements, the identifying data is keyed into computer 62 by means of a conventional keyboard (not shown in FIG. 2) in response to prompts that are generated at clearinghouse 54 for display by the display unit of computer 62 (not shown in FIG. 2).

**[0048]** Depending upon the hardware and software arrangement of clearinghouse 54 and selections made by the healthcare professional via computer 62, patient information

can be provided to the healthcare professional in different ways. For example, computer 62 can be operated to access data in the form that it is stored in the memory circuits of clearinghouse 54 (i.e., raw data that has not been processed or altered by the computational or data processing arrangements of clearinghouse 54). Such data can be processed, analyzed, printed and/or displayed by computer 62 using commercially available or custom software. On the other hand, various types of analyses may be performed by clearinghouse 54 with the results of the analyses being transmitted to the remotely located healthcare professional 60. For example, clearinghouse 54 can process and analyze data in a manner identical to the processing and analysis provided by the self-care monitoring system of FIG. 1. With respect to such processing and any other analysis and processing provided by clearinghouse 54, results expressed in alphanumeric format can be sent to computer 62 via telephone line 64 and the modem associated with computer 62, with conventional techniques being used for displaying and/or printing the alphanumeric material for subsequent reference.

**[0049]** The arrangement of FIG. 2 also allows the healthcare professional to send messages and/or instructions to each patient via computer 62, telephone line 64, and clearinghouse 54. In particular, clearinghouse 54 can be programmed to generate a menu that is displayed by computer 62 and allows the healthcare professional to select a mode of operation in which information is to be sent to clearinghouse 54 for subsequent transmission to a user of the system described relative to FIG. 1. This same menu (or related submenus) can be used by the healthcare professional to select one or more modes of operation of the above-described type in which either unmodified patient data or the results of data that has been analyzed by clearinghouse 54 is provided to the healthcare provider via computer 62 and/or facsimile machine 55.

**[0050]** In the currently contemplated arrangements, operation of the arrangement of FIG. 2 to provide the user of the invention with messages or instructions such as changes in medication or other aspects of the healthcare program is similar to the operation that allows the healthcare professional to access data sent by a patient (i.e., transmitted to clearinghouse 54 by a data management unit 10 of FIG. 1). The process differs in that the healthcare professional enters the desired message or instruction via the keyboard or other interface unit of computer 62. Once the data is entered and transmitted to clearinghouse 54, it is stored for subsequent transmission to the user for whom the information or instruction is intended.

**[0051]** With respect to transmitting stored messages or instructions to a user of the invention, at least two techniques are available. The first technique is based upon the manner in which operational modes are selected in the practice of the invention. Specifically, in the currently preferred embodiments of the invention, program instructions that are stored in data management unit 10 and program cartridge 42 cause the system of FIG. 1 to generate menu screens which are displayed by display unit 28 of handheld microprocessor unit 12. The menu screens allow the system user to select the basic mode in which the system of FIG. 1 is to operate and, in addition, allow the user to select operational subcategories within the selected mode of operation. Various techniques are known to those skilled in the art for displaying and selecting menu items. For example, in the practice of this invention, one or more main menus can be generated and displayed which allow the system user to select operational modes that may

include: (a) a monitor mode (e.g., monitoring of blood glucose level); (b) a display mode (e.g., displaying previously obtained blood glucose test results or other relevant information); (c) an input mode (e.g., a mode for entering data such as providing information that relates to the healthcare regimen, medication dosage, food intake, etc.); and, (d) a communications mode (for establishing a communication link between data management unit 10 and personal computer 48 of FIG. 1; or between data management unit 10 and a remote computing facility such as clearinghouse 54 of FIG. 2).

[0052] In embodiments of the invention that employ a compact video game system for handheld microprocessor unit 12, the selection of menu screens and the selection of menu screen items preferably is accomplished in substantially the same manner as menu screens and menu items are selected during the playing of a video game. For example, the program instructions stored in data management unit 10 and program cartridge 42 of the arrangement of FIG. 1 can be established so that a predetermined one of the compact video game switches (e.g., switch 32 in FIG. 1) allows the system user to select a desired main menu in the event that multiple main menus are employed. When the desired main menu is displayed, operation by the user of control pad 30 allows a cursor or other indicator that is displayed on the menu to be positioned adjacent to or over the menu item to be selected. Activation of a switch (e.g., switch 36 of the depicted handheld microprocessor unit 12) causes the handheld microprocessor unit 12 and/or data management unit 10 to initiate the selected operational mode or, if selection of operational sub-modes is required, causes handheld microprocessor unit 12 to display a submenu.

[0053] In view of the above-described manner in which menus and submenus are selected and displayed, it can be recognized that the arrangement of FIG. 1 can be configured and arranged to display a menu or submenu item that allows the user to obtain and display messages or instructions that have been provided by a healthcare professional and stored in clearinghouse 54. For example, a submenu that is generated upon selection of the previously mentioned communications mode can include submenu items that allow the user to select various communication modes, including a mode in which serial data communication is established between data management unit 10 and clearinghouse 54 and data management unit 10 transmits a message status request to clearinghouse 54. When this technique is used, the data processing system of clearinghouse 54 is programmed to search the clearinghouse memory to determine whether a message exists for the user making the request. Any messages stored in memory for that user are then transmitted to the user and processed for display on display unit 28 of handheld microprocessor unit 12. If no messages exist, clearinghouse 54 transmits a signal that causes display unit 28 to indicate "no messages". In this arrangement, clearinghouse 54 preferably is programmed to store a signal indicating that a stored message has been transmitted to the intended recipient (user). Storing such a signal allows the healthcare professional to determine that messages sent to clearinghouse 54 for forwarding to a patient have been transmitted to that patient. In addition, the program instructions stored in data management unit 10 of FIG. 1 preferably allow the system user to designate whether received messages and instructions are to be stored in the memory of data management unit for subsequent retrieval or review. In addition, in some instances it may be desirable to program clearinghouse 54 and data management unit 10 so that the healthcare

professional can designate (i.e., flag) information such as changes in medication that will be prominently displayed to the user (e.g., accompanied by a blinking indicator) and stored in the memory of data management unit 10 regardless of whether the system user designates the information for storage.

[0054] A second technique that can be used for forwarding messages or instructions to a user does not require the system user to select a menu item requesting transmission by clearinghouse 54 of messages that have been stored for forwarding to that user. In particular, clearinghouse 54 can be programmed to operate in a manner that either automatically transmits stored messages for that user when the user operates the system of FIG. 1 to send information to the clearinghouse or programmed to operate in a manner that informs the user that messages are available and allows the user to access the messages when he or she chooses to do so.

[0055] Practicing the invention in an environment in which the healthcare professional uses a personal computer in some or all of the above-discussed ways can be very advantageous. On the other hand, the invention also provides healthcare professionals timely information about system users without the need for a computer (62 in FIG. 2) or any equipment other than a conventional facsimile machine (55 in FIGS. 1 and 2). Specifically, information provided to clearinghouse 54 by a system user 58 can be sent to a healthcare professional 60 via telephone line 68 and facsimile machine 55, with the information being formatted as a standardized graphic or textual report (56 in FIG. 1). Formatting a standardized report 56 (i.e., analyzing and processing data supplied by blood glucose monitor 16 or other system monitor or sensor) can be effected either by data management unit 10 or within the clearinghouse facility 54. Moreover, various standardized reports can be provided (e.g., the textual and graphic displays discussed below relating to FIGS. 6-10). Preferably, the signal processing arrangement included in clearinghouse 54 allows each healthcare professional 60 to select which of several standardized reports will be routinely transmitted to the healthcare professional's facsimile machine 55, and, to do so on a patient-by-patient (user-by-user) basis.

[0056] FIG. 3 illustrates the manner in which data management unit 10 is arranged and interconnected with other system components for effecting the above-described operational aspects of the invention and additional aspects that are described relative to FIGS. 4-10. As is symbolically indicated in FIG. 3, handheld microprocessor unit 12 and blood glucose monitor 16 are connected to a dual universal asynchronous receiver transmitter 70 (e.g., by cables 14 and 18 of FIG. 1, respectively). As also is indicated in FIG. 3 when a system user connects a personal computer 48 (or other programmable digital signal processor) to data port 44, signal communication is established between personal computer 48 and a second dual universal asynchronous receiver transmitter 72 of data management unit 10. Additionally, dual universal asynchronous receiver transmitter 72 is coupled to modem 46 so that data communication can be established between data management unit 10 and a remote clearinghouse 54 of FIGS. 1 and 2.

[0057] Currently preferred embodiments of data management unit 10 include a plurality of signal sensors 74, with an individual signal sensor being associated with each device that is (or may be) interconnected with data management unit 10. As previously discussed and as is indicated in FIG. 3, these devices include handheld microprocessor unit 12, blood



glucose monitor **16**, personal computer **48**, remote computing facility **54** and, in addition, peak-flow meter **20** or other additional monitoring devices **22**. Each signal sensor **74** that is included in data management unit **10** is electrically connected for receiving a signal that will be present when the device with which that particular signal sensor is associated is connected to data management unit **10** and, in addition, is energized (e.g., turned on). For example, in previously mentioned embodiments of the invention in which data port **44** is an RS-232 connection, the signal sensor **74** that is associated with personal computer **48** can be connected to an RS-232 terminal that is supplied power when a personal computer is connected to data port **44** and the personal computer is turned on. In a similar manner, the signal sensor **74** that is associated with clearinghouse **54** can be connected to modem **46** so that the signal sensor **74** receives an electrical signal when modem **46** is interconnected to a remote computing facility (e.g., clearinghouse **54** of FIG. 2) via a telephone line **50**.

**[0058]** In the arrangement of FIG. 3, each signal sensor **74** is a low power switch circuit (e.g., a metal-oxide semiconductor field-effect transistor circuit), which automatically energizes data management unit **10** whenever any one (or more) of the devices associated with signal sensors **74** is connected to data management unit **10** and is energized. Thus, as is indicated in FIG. 3 by signal path **76**, each signal sensor **74** is interconnected with power supply **78**, which supplies operating current to the circuitry of data management unit **10** and typically consists of one or more small batteries (e.g., three AAA alkaline cells).

**[0059]** The microprocessor and other conventional circuitry that enables data management unit **10** to process system signals in accordance with stored program instructions is indicated in FIG. 3 by central processing unit (CPU) **80**. As is indicated in FIG. 3 by interconnection **82** between CPU **80** and battery **78**, CPU **80** receives operating current from power supply **78**, with power being provided only when one or more of the signal sensors **74** are activated in the previously described manner. A clock/calendar circuit **84** is connected to CPU **80** (via signal path **86** in FIG. 3) to allow time and date tagging of blood glucose tests and other information. Although not specifically shown in FIG. 3, operating power is supplied to clock/calendar **84** at all times.

**[0060]** In operation, CPU **80** receives and sends signals via a data bus (indicated by signal path **88** in FIG. 3) which interconnects CPU **80** with dual universal asynchronous receiver transmitters **70** and **72**. The data bus **88** also interconnects CPU **80** with memory circuits which, in the depicted embodiment, include a system read-only memory (ROM) **90**, a program random access memory (RAM) **92**, and an electronically erasable read-only memory (EEROM) **94**. System ROM **90** stores program instructions and any data required in order to program data management unit **10** so that data management unit **10** and a handheld microprocessor unit **12** that is programmed with a suitable program cartridge **72** provide the previously discussed system operation and, in addition, system operation of the type described relative to FIGS. 4-10. During operation of the system, program RAM **92** provides memory space that allows CPU **80** to carry out various operations that are required for sequencing and controlling the operation of the system of FIG. 1. In addition, RAM **92** can provide memory space that allows external programs (e.g., programs provided by clearinghouse **54**) to be stored and executed. EEROM **94** allows blood glucose test results and other data information to be stored and preserved until the

information is no longer needed (i.e., until purposely erased by operating the system to provide an appropriate erase signal to EEROM **94**).

**[0061]** FIGS. 4-10 illustrate typical screen displays that are generated by the arrangement of the invention described relative to FIGS. 1-3. Reference will first be made to FIGS. 4 and 5, which exemplify screen displays that are associated with operation of the invention in the blood glucose monitoring mode. Specifically, in the currently preferred embodiments of the invention, blood glucose monitor **16** operates in conjunction with data management unit **10** and handheld microprocessor unit **12** to: (a) perform a test or calibration sequence in which tests are performed to confirm that the system is operating properly; and, (b) perform the blood glucose test sequence in which blood glucose meter **16** senses the user's blood glucose level. Suitable calibration procedures for blood glucose monitors are known in the art. For example, blood glucose monitors often are supplied with a "code strip" that is inserted in the monitor and results in a predetermined value being displayed and stored in memory at the conclusion of the code strip calibration procedure. When such a code strip calibration procedure is used in the practice of the invention, the procedure is selected from one of the system menus. For example, if the system main menu includes a "monitor" menu item, a submenu displaying system calibration options and an option for initiating the blood glucose test may be displayed when the monitor menu item is selected. When a code strip option is available and selected, a sequence of instructions is generated and displayed by display screen **28** of handheld microprocessor unit **12** to prompt the user to insert the code strip and perform all other required operations. At the conclusion of the code strip calibration sequence, display unit **28** of handheld microprocessor unit **12** displays a message indicating whether or not the calibration procedure has been successfully completed. For example, FIG. 4 illustrates a screen display that informs the system user that the calibration procedure was not successful and that the code strip should be inserted again (i.e., the calibration procedure is to be repeated). As is indicated in FIG. 4, display screens that indicate a potential malfunction of the system include a prominent message such as the "Attention" notation included in the screen display of FIG. 4.

**[0062]** As previously indicated, the blood glucose test sequence that is employed in the currently preferred embodiment of the invention is of the type in which a test strip is inserted in a receptacle that is formed in the blood glucose monitor. A drop of the user's blood is then applied to the test strip and a blood glucose sensing sequence is initiated. When the blood glucose sensing sequence is complete, the user's blood glucose level is displayed.

**[0063]** In the practice of the invention, program instructions stored in data management unit **10** (e.g., system ROM **90** of FIG. 3) and program instructions stored in program cartridge **42** of handheld microprocessor unit **12** cause the system to display step-by-step monitoring instructions to the system user and, in addition, preferably result in display of diagnostic messages if the test sequence does not proceed in a normal fashion. Although currently available self-contained microprocessor-based blood glucose monitors also display test instruction and diagnostic messages, the invention provides greater message capacity and allows multi-line instructions and diagnostic messages that are displayed in easily understood language rather than cryptic error codes and abbreviated phraseology that is displayed one line or less at a



time. For example, as is shown in FIG. 5, the complete results of a blood glucose test (date, time of day, and blood glucose level in milligrams per deciliter) can be concurrently displayed by display screen 28 of handheld microprocessor unit 12 along with an instruction to remove the test strip from blood glucose monitor 16. As previously mentioned, when the blood glucose test is complete, the time and date tagged blood glucose test result is stored in the memory circuits of data management unit 10 (e.g., stored in EEPROM 94 of FIG. 3).

**[0064]** The arrangement shown and described relative to FIGS. 1-3 also is advantageous in that data relating to food intake, concurrent medication dosage and other conditions easily can be entered into the system and stored with the time and date tagged blood glucose test result for later review and analysis by the user and/or his or her healthcare professional. Specifically, a menu generated by the system at the beginning or end of the blood glucose monitoring sequence can include items such as "hypoglycemic" and "hyperglycemic", which can be selected using the switches of handheld microprocessor unit 12 (e.g., operation of control pad 30 and switch 36 in FIG. 1) to indicate the user was experiencing hypoglycemic or hyperglycemic symptoms at the time of monitoring blood glucose level. Food intake can be quantitatively entered in terms of "Bread Exchange" units or other suitable terms by, for example, selecting a food intake menu item and using a submenu display and the switches of handheld microprocessor 12 to select and enter the appropriate information. A similar menu item—submenu selection process also can be used to enter medication data such as the type of insulin used at the time of the glucose monitoring sequence and the dosage.

**[0065]** As was previously mentioned, program instructions stored in data management unit 10 and program instructions stored in program cartridge 42 of handheld microprocessor unit 12 enable the system to display statistical and trend information either in a graphic or alphanumeric format. As is the case relative to controlling other operational aspects of the system, menu screens are provided that allow the system user to select the information that is to be displayed. For example, in the previously discussed embodiments in which a system menu includes a "display" menu item, selection of the menu item results in the display of one or more submenus that list available display options. For example, in the currently preferred embodiments, the user can select graphic display of blood glucose test results over a specific period of time, such as one day, or a particular week. Such selection results in displays of the type shown in FIGS. 6 and 7, respectively. When blood glucose test results for a single day are displayed (FIG. 6), the day of the week and date can be displayed along with a graphic representation of changes in blood glucose level between the times at which test results were obtained. In the display of FIG. 6, small icons identify points on the graphic representation that correspond to the blood glucose test results (actual samples). Although not shown in FIG. 6, coordinate values for blood glucose level and time of day can be displayed if desired. When the user chooses to display a weekly trend graph (FIG. 7), the display generated by the system is similar to the display of a daily graph, having the time period displayed in conjunction with a graph that consists of lines interconnecting points that correspond to the blood glucose test results.

**[0066]** The screen display shown in FIG. 8 is representative of statistical data that can be determined by the system of FIG.

1 (using conventional computation techniques) and displayed in alphanumeric format. As previously mentioned, such statistical data and information in various other textual and graphic formats can be provided to a healthcare professional (60 in FIG. 2) in the form of a standardized report 56 (FIG. 1) that is sent by clearinghouse 54 to facsimile machine 55. In the exemplary screen display of FIG. 8, statistical data for blood glucose levels over a period of time (e.g., one week) or, alternatively, for a specified number of monitoring tests is provided. In the exemplary display of FIG. 8, the system (data management unit 10 or clearinghouse 54) also calculates and displays (or prints) the average blood glucose level and the standard deviation. Displayed also is the number of blood glucose test results that were analyzed to obtain the average and the standard deviation; the number of test results under a predetermined level (50 milligrams per deciliter in FIG. 8); and the number of blood glucose tests that were conducted while the user was experiencing hypoglycemic symptoms. As previously noted, in the preferred embodiments of the invention, a screen display that is generated during the blood glucose monitoring sequence allows the user to identify the blood sample being tested as one taken while experiencing hyperglycemic or hypoglycemic symptoms and, in addition, allows the user to specify other relevant information such as food intake and medication information.

**[0067]** The currently preferred embodiments of the invention also allow the user to select a display menu item that enables the user to sequentially address, in chronological order, the record of each blood glucose test. As is indicated in FIG. 9, each record presented to the system user includes the date and time at which the test was conducted, the blood glucose level, and any other information that the user provided. For example, the screen display of FIG. 9 indicates that the user employed handheld microprocessor unit 12 as an interface to enter data indicating use of 12.5 units of regular insulin; 13.2 units of "NPH" insulin; food intake of one bread exchange unit; and pre-meal hypoglycemic symptoms.

**[0068]** Use of data management unit 10 in conjunction with handheld microprocessor unit 12 also allows display (or subsequent generation of a standardized report 56) showing blood glucose test results along with food intake and/or medication information. For example, shown in FIG. 10 is a daily graph in which blood glucose level is displayed in the manner described relative to FIG. 6. Related food intake and medication dosage is indicated directly below contemporaneous blood glucose levels by vertical bar graphs.

**[0069]** It will be recognized by those skilled in the art that the above-described screen displays and system operation can readily be attained with conventional programming techniques of the type typically used in programming microprocessor arrangements. It also will be recognized by those skilled in the art that various other types of screen displays can be generated and, in addition, that numerous other changes can be made in the embodiments described herein without departing from the scope and the spirit of the invention.

**[0070]** It will also be recognized by those skilled in the art that the invention can be embodied in forms other than the embodiments described relative to FIGS. 1-10. For example, the invention can employ compact video game systems that are configured differently than the previously discussed handheld video game systems and palm-top computers. More specifically, as is shown in FIG. 11, a self-care health monitoring system arranged in accordance with the invention can

employ a compact video game system of the type that includes one or more controllers **100** that are interconnected to a game console **102** via cable **104**. As is indicated in FIG. **11**, game console **102** is connected to a video monitor or television **106** by means of a cable **108**. Although differing in physical configuration, controller **100**, game console **102** and the television or video monitor **106** collectively function in the same manner as the handheld microprocessor **12** of FIG. **1**. In that regard, a program cartridge **42** is inserted into a receptacle contained in game console **102**, with program cartridge **42** including stored program instructions for controlling microprocessor circuitry that is located inside game console **102**. Controller **100** includes a control pad or other device functionally equivalent to control pad **30** of FIG. **1** and switches that functionally correspond to switches **32-38** of FIG. **1**.

**[0071]** Regardless of whether the invention is embodied with a handheld microprocessor unit (FIG. **1**) or an arrangement such as the compact video game system (FIG. **11**), in some cases it is both possible and advantageous to apportion the signal processing functions and operations differently than was described relative to FIGS. **1-10**. For example, in some situations, the microprocessor-based unit that is programmed by a card or cartridge (e.g., handheld unit **12** of FIG. **1** or compact video game console **102** of FIG. **11**) includes memory and signal processing capability that allows the microprocessor to perform all or most of the functions and operations attributed to data management unit **10** of the embodiments discussed relative to FIGS. **1-10**. That is, the digitally encoded signal supplied by blood glucose monitor **16** (or one of the other monitors **20** and **22** of FIG. **1**) can be directly coupled to the microprocessor included in game console **102** of FIG. **11** or handheld microprocessor **12** of FIG. **1**. In such an arrangement, the data management unit is a relatively simple signal interface (e.g., interface unit **110** of FIG. **11**), the primary purpose of which is carrying signals between the blood glucose monitor **16** (or other monitor) and the microprocessor of game console **102** (FIG. **11**) or handheld unit **12** (FIG. **1**). In some situations, the interface unit may consist primarily or entirely of a conventional cable arrangement such as a cable for interconnection between RS-232 data ports or other conventional connection arrangements. On the other hand, as is shown in FIG. **11**, signal interface **110** can either internally include or be connected to a modem **52**, which receives and transmits signals via a telephone line **50** in the manner described relative to FIGS. **1** and **2**.

**[0072]** It also should be noted that all or a portion of the functions and operations attributed to data management unit **10** of FIG. **1** can be performed by microprocessor circuitry located in blood glucose monitor **16** (or other monitor that is used with the system). For example, a number of commercially available blood glucose monitors include a clock/calendar circuit of the type described relative to FIG. **3** and, in addition, include microprocessor circuitry for generating visual display signals and signals representative of both current and past values of monitored blood glucose level. Conventional programming and design techniques can be employed to adapt such commercially available units for the performance of the various functions and operations attributed in the above discussion of FIGS. **1-11** to data management unit **10** and/or the microprocessors of handheld unit **12** and compact video console **102**. In arrangements in which the blood glucose monitor (or other system monitor) includes a microprocessor that is programmed to provide signal pro-

cessing in the above-described manner, the invention can use a signal interface unit **110** of the above-described type. That is, depending upon the amount of signal processing effected by the monitoring unit (e.g., blood glucose monitor **16**) and the amount of signal processing performed by the microprocessor of video game console **102** (or handheld unit **12**), the signal interface required ranges from a conventional cable (e.g., interconnection of RS232 ports) to an arrangement in which signal interface **110** is arranged for signal communication with an internal or external modem (e.g., modem **52** of FIG. **11**) or an arrangement in which signal interface **110** provides only a portion of the signal processing described relative to FIGS. **1-10**.

**[0073]** The invention also is capable of transmitting information to a remote location (e.g., clearinghouse **54** and/or a remotely located healthcare professional) by means other than conventional telephone lines. For example, a modem (**52** in FIGS. **1** and **11**) that is configured for use with a cellular telephone system can be employed to transmit the signals provided by the healthcare monitoring system to a remote location via modulated RF transmission. Moreover, the invention can be employed with various digital networks such as recently developed interactive voice, video and data systems such as television systems in which a television and user interface apparatus is interactively coupled to a remote location via coaxial or fiberoptic cable and other transmission media (indicated in FIG. **11** by cable **112**, which is connected to television or video monitor **106**). In such an arrangement, compact video game controller **100** and the microprocessor of video game console **102** can be programmed to provide the user interface functions required for transmission and reception of signals via the interactive system. Alternatively, the signals provided by video game console **102** (or handheld unit **12** if FIG. **1**) can be supplied to the user interface of the interactive system (not shown in FIG. **11**) in a format that is compatible with the interactive system and allows the system user interface to be used to control signal transmission between the healthcare system and a remote facility such as clearinghouse **54**, FIGS. **1** and **2**.

**[0074]** While this invention is satisfied by embodiments in many different forms, as described in detail in connection with preferred embodiments of the invention, it is understood that the present disclosure is to be considered as exemplary of the principles of the invention and is not intended to limit the invention to the specific embodiments illustrated and described herein. Numerous variations may be made by persons skilled in the art without departure from the spirit of the invention. The abstract and the title are not to be construed as limiting the scope of the present invention, as their purpose is to enable the appropriate authorities, as well as the general public, to quickly determine the general nature of the invention. Unless the term "means" is expressly used, none of the features or elements recited herein should be construed as means-plus-function limitations pursuant to 35 U.S.C. §112, paragraph 6.

1. A system for managing healthcare data, comprising:
  - a first set of at least one module providing primary healthcare functions;
  - a first central engine controlling the first set of at least one module;
  - a second set of at least one module providing secondary healthcare functions;
  - a second central engine controlling the second set of at least one module; and

- a communication interface providing a connection between the first central engine and the second central engine.
2. The system of claim 1, wherein the first central engine is assembled with the first set of at least one module according to a first development process and the second central engine is assembled with the second set of at least one module according to a second development process.
3. The system of claim 1, wherein the communication interface is at least one of a USB interface, a radio frequency (RF) interface, a Wi-Fi interface, and an Ethernet interface.
4. The system of claim 1, wherein the first central engine is implemented on a first mother board, the second central engine is implemented on a second mother board, the first set of at least one module is separately implemented on a first set of at least one daughter board, and the second set of at least one module is separately implemented on a second set of at least one daughter board.
5. The system of claim 1, further comprising a first housing including the first central engine and a second housing including the second central engine.
6. The system of claim 1, wherein the first set of at least one module provide a diabetes-management system.
7. The system of claim 1, wherein the central engine is implemented on a mother board and the at least one module is separately implemented on a daughter board, the daughter board being standardized for connection with the mother board.
8. A method for managing healthcare data, comprising:  
developing, according to a first development process, a first assembly of a first central engine and a first set of at least one module providing primary healthcare functions, the first central engine controlling the first set of at least one module;  
developing, according to a second development process, a second assembly of a second central engine and a second set of at least one module secondary healthcare functions; and  
connecting the first assembly and the second assembly via a communication interface.
9. A device for managing health data, comprising:  
a first housing portion including a data storage system that stores health data; and  
a second housing portion including a data communications element that provides data communications between the data storage system and a processing device by connecting with the processing device, the processing device processing the health data according to a data-management software, wherein the first housing portion and the second housing portion are connected by a cable that communicates signals between the data communications element and other components in the first housing portion.
10. The device of claim 9, wherein the data communications element is a USB connector that is received by a USB port in the processing device.
11. The device of claim 9, wherein a length of the cable between the first housing portion and the second housing portion is adjustable.
12. The device of claim 11, wherein the second housing portion includes a storage chamber for storing an excess length of the cable.
13. The device of claim 12, wherein the storage chamber includes a spring device, the spring device drawing the excess length of the cable into the storage chamber.
14. The device of claim 9, wherein the first housing portion includes a storage cavity for receiving the second housing portion.
15. A device for managing health data, comprising:  
a first housing portion including a health data management system and a data communications element that provides data communications between the health data management system and an external processing device; and a second housing portion that is removably coupled to the first housing portion, the second housing portion including at least one component used by the health data management system.
16. The device of claim 15, wherein the second housing portion is a cap for the data communications element.
17. The device of claim 16, wherein the data communications element is a USB connector and the second housing portion is a cap for the USB connector.
18. The device of claim 16, wherein the at least one component is a power source that provides power, via the data communications element, to the health data management system when the cap is coupled to the first housing portion.
19. The device of claim 18, wherein the power source is a rechargeable battery.
20. The device of claim 18, wherein the rechargeable battery exchanges power with another power source in the first housing portion via the data communications element.
21. The device of claim 18, wherein the power source is a backup for another power source in the first housing portion.
22. The device of claim 18, wherein the power source provides power to the health data management system when the cap is coupled to the first housing portion according to a first orientation, and does not provide power to the health data management system when the cap is coupled to the first housing according to a second orientation.
23. The device of claim 18, further comprising a third housing portion that is removably coupled to the first housing portion, the third housing portion storing test sensors for a health data measurement system included in the health data management system in the first housing portion.
24. The device of claim 23, wherein the health data management system includes a health data measurement system and a user interface that displays results from the health data measurement system.
25. The device of claim 24, wherein the at least one component includes one or more test sensors for the health data measurement system.
26. The device of claim 24, wherein the at least one component includes a temperature sensor that provides a measurement of ambient temperature to the health data management system, the health data management system using the measurement of ambient temperature to determine results from the health data measurement system.
27. The device of claim 26, wherein the temperature sensor measures the ambient temperature at a surface of the cap.
28. The device of claim 27, wherein the temperature sensor measures the ambient temperature of a thin membrane at the surface of the cap.
29. A system for managing health data, comprising:  
a data storage system storing health data, data-management software, and an initialization program, the initialization program launching the data-management soft-

- ware on a processing device and the data-management software processing the health data on the processing device; and
- a data communications interface providing data communications between the data storage system and the processing device, wherein, upon establishment of the data communications between the data storage system and the processing device, the initialization program launches the data-management software on the processing device without requiring prior installation, on the processing device, of an additional program component associated with the data-management software.
30. The system of claim 29, wherein the data storage system includes at least one of a USB flash drive and a memory card.
31. The system of claim 29, wherein the data storage system is configured according to a memory map indicating security levels for areas of memory in the data storage system, the security levels determining access to data stored in the areas of memory.
32. The system of claim 29, wherein the data storage system includes a first memory device storing the data-management software and the initialization program, and a second memory device storing the health data.
33. The system of claim 32, wherein the first memory device is an EEPROM and the second memory device is a flash memory.
34. The system of claim 29, further comprising a data-check system validating data to be stored in the data storage system.
35. The system of claim 29, wherein the data-management software processes the health data without permanently storing the data on the processing device.
36. The system of claim 29, wherein the data-management software removes any data on the processing device associated with the data-management software before ending execution.
37. The system according to claim 29, wherein the data-management software closes when the data communications between the data portable device and the processing device is terminated.
38. The system of claim 29, wherein the processing device is compatible with an interface protocol configuration allowing data communication to be established between the data storage system and the processing device, and the initialization program reconfigures the data storage system to a software configuration specific to the data-management software allowing the data-management software to be launched on the processing device, the software configuration being different from the interface protocol configuration.
39. The system of claim 38, wherein the interface protocol configuration is a USB mass portable device (MSD) configuration.
40. The system of claim 29, wherein the data communications interface includes at least one of a universal serial bus (USB) interface, a secure digital (SD) interface, and a radio frequency (RF) link.
41. The system of claim 29, wherein the processing device is a personal computer, a personal digital assistant, or a smart cellular phone.
42. The system of claim 29, wherein the data communications interface further provides data communications between the data storage system and a blood glucose meter.
43. The system of claim 29, wherein The system of claim 1, wherein the data communications interface further provides data communications between the data storage system and a printer, and wherein (i) the data storage system provides a ready-to-print file from the health data and sends the ready to print file to the printer, or (ii) the printer receives, formats, and prints the health data from the data storage system.
44. The system of claim 29, wherein the health data includes analyte data, temperature data, blood pressure data, heart rate data, breathing data or weight data.
45. The system of claim 29, wherein the health data includes blood-glucose data.
46. The system of claim 29, wherein the processing device is one of a plurality of types of processing devices that are compatible with the data communications interface.
47. The system of claim 29, further comprising a measurement system determining health data from an individual for storage in the data storage system.
48. The system of claim 47, wherein the measurement system, the data storage device system, and the data communications interface are integrated with a housing.
49. The system of claim 48, further comprising a user interface integrated with the housing, the user interface operable to display the health data.
50. The system of claim 49, further comprising a local processor and local software integrated with the housing, the local processor processing the health data to be displayed via the user interface.
51. The system of claim 29, wherein one processing device is designated as a base station of the data storage system, wherein additional features of the data-management software are enabled when the data storage system detects it is connected to the base station.
52. The system of claim 51, wherein the additional features include a download of all health data in the storage device to the base station or a launching of a master version of the data management software.
53. The system of claim 29, wherein a security component controls access by the processing device to the health data in the data storage system.
54. The system of claim 53, wherein the security component prompts a user for authentication information and validates the authentication information when the processing device attempts to access the health data.
55. The system of claim 53, wherein the security component establishes a trusted system by requiring the processing device to be registered with the data storage system.
56. The system of claim 55, wherein the processing device requires the data storage system to be registered and a two-way authentication is established.
57. The system of claim 53, wherein the security component encrypts the health data on the data storage system during transmission to the processing device.
58. The system of claim 53, wherein the security component restricts access to the health data to the data-management software.
59. The system of claim 53, wherein the security component restricts access to the health data in the data storage system according to data type.
60. The system of claim 53, wherein the health data is encrypted and the data-management software is required to decrypt the data.
61. A system for managing health data, comprising:

- a portable device including data-management software that processes health data, the portable device having a first software configuration corresponding to an interface protocol and a second software configuration specific to the data-management software; and
  - a processing device connected to the portable device, wherein upon connection between the portable device and the processing device, the processing device communicates with the portable device according to the interface protocol, and after the portable device is reconfigured from the first configuration to the second configuration, the processing device executes the data management software.
- 62.** The system according to claim **61**, wherein the portable device includes an initialization program, and upon connection between the storage device and the processing device, the initialization program is executed and reconfigures the portable device from the first configuration to the second configuration.
- 63.** The system of claim **61**, wherein the interface protocol corresponds to a universal serial bus (USB) and the first configuration is a USB mass portable device (MSD) configuration.
- 64.** The system according to claim **61**, wherein the portable device and the processing device are connected via a universal serial bus (USB) interface, a secure digital interface, or a radio frequency (RF) link.
- 65.** The system of claim **61**, wherein the processing device is a personal computer, a personal digital assistant, or a smart cellular phone.
- 66.** The system of claim **61**, wherein the data-management software processes the health data without permanently storing the data on the processing device.
- 67.** The system of claim **61**, wherein the data-management software removes any data on the processing device associated with the data-management software before ending execution.
- 68.** The system according to claim **61**, wherein the data-management software closes when the data communications between the data portable device and the processing device is terminated.
- 69.** A method for managing health data, comprising:
- establishing, for a first time, data communications between a data storage system to a processing device via a data communications interface, the data storage system storing health data, data-management software, and an initialization program;
  - executing, on the processing device, the initialization program upon establishment of the data communications between the data storage system and the processing device, without requiring prior installation, on the processing device, of an additional program component associated with the data-management software;
  - launching, with the initialization program, the data-management software on the processing device; and
  - processing the health data on the processing device with the data-management software.
- 70.** The method of claim **69**, wherein processing the health data on the processing device comprises processing the health data without permanently storing the data on the processing device.

**71.** The method of claim **69**, further comprising removing any data on the processing device associated with the data-management software before termination of the act of processing the health data.

**72.** The method according to claim **69**, further comprising terminating the act of processing the health data when the data communications between the data portable device and the processing device is terminated.

**73.** The method of claim **69**, wherein the processing device is compatible with an interface protocol configuration allowing data communication to be established between the data storage system and the processing device, and the act of executing the initialization program comprises reconfiguring the data storage system to a software configuration specific to the data-management software, the software configuration being different from the interface protocol configuration.

**74.** The method of claim **73**, wherein the interface protocol configuration is a USB mass portable device (MSD) configuration.

**75.** The method of claim **69**, wherein the data communications interface includes at least one of a universal serial bus (USB) interface, a secure digital (SD) interface, and a radio frequency (RF) link.

**76.** The method of claim **69**, wherein the processing device is a personal computer, a personal digital assistant, or a smart cellular phone.

**77.** The method of claim **69**, further comprising controlling access by the processing device to the health data in the data storage system.

**78.** The method of claim **77**, wherein controlling access comprises prompting a user for authentication information and validating the authentication information when the processing device attempts to access the health data.

**79.** The method of claim **77**, wherein controlling access comprises establishing a trusted system by requiring the processing device to be registered with the data storage system.

**80.** The method of claim **77**, wherein controlling access comprises requiring the data storage system to be registered and a two-way authentication is established.

**81.** The method of claim **77**, wherein controlling access comprises encrypting the health data on the data storage system during transmission to the processing device.

**82.** The method of claim **77**, wherein controlling access comprises restricting access to the health data to the data-management software.

**83.** The method of claim **77**, wherein controlling access comprises restricting access to the health data in the data storage system according to data type.

**84.** The method of claim **77**, further comprising encrypting the health data is encrypted and controlling access comprises requiring the data-management software to decrypt the data.

**85.** A method for managing health data, comprising:

- detecting a connection between a portable device and a processing device, the portable device containing data-management software processing health data and having a first software configuration corresponding to an interface protocol, wherein upon connection between the portable device and the processing device, the processing device communicates with the portable device according to the interface protocol;
- reconfiguring the portable device from the first configuration to a second configuration specific to the software; and

launching the software from the reconfigured portable device.

**86.** The method of claim **85**, further comprising launching an initialization program from the portable device upon detection of the connection, wherein the portable device is reconfigured by the initialization program.

**87.** The method of claim **85**, further comprising receiving, by the portable device, the health data from a measurement system.

**88.** The method of claim **85**, wherein the interface protocol corresponds to one of a universal serial bus (USB) interface, a secure digital interface, and a radio frequency (RF) link.

**89.** A system for managing health data, comprising:

a first device that stores health data, data-management software, and an initialization program;

a second device that processes the health data with the data-management software; and

a data communications interface providing data communications between the first device and the second device, wherein upon establishment of the data communications between the data storage system and the processing device, the initialization program launches the data-management software on the processing device without requiring prior installation, on the processing device, of an additional program component associated with the data-management software.

**90.** A system for managing healthcare data, comprising:

at least one module providing a healthcare function;

a central engine controlling the at least one module;

one or more communication interfaces providing a connection to a remote server, the remote server storing one or more program components corresponding to the at least one module or the central engine; and

a download engine configured to receive the one or more program components from the remote server via the one or more communication interfaces and to deliver the one or more program components for use with the at least one module or the central engine.

**91.** The system of claim **90**, further comprising a version management component that determines whether the one or more program components is compatible with the at least one module or the central engine before the download engine receives the one or more program components.

**92.** The system of claim **90**, wherein the one or more program components replaces an older version of a software running on the at least one module or the central engine with an updated version of the software.

**93.** The system of claim **92**, further comprising a restore component that restores the older version of the software.

**94.** The system of claim **93**, wherein the updated version of the software is downloaded to a memory area that is separate from the older version of the software, and the older version of the software remains available to be restored.

**95.** The system of claim **94**, wherein the older version of the software is restored when a validation component determines that the updated version of the software operates incorrectly or has not been downloaded properly.

**96.** The system of claim **90**, wherein the one or more program components provides a patch for software running on the at least one module or the central engine.

**97.** The system of claim **90**, wherein the one or more program components provides a new function to be executed by the at least one module or the central engine.

**98.** The system of claim **90**, wherein the one or more program components includes configuration information for software running on the at least one module or the central engine.

**99.** The system of claim **90**, wherein the download engine is manually triggered by a user to receive and deliver the one or more program components.

**100.** The system of claim **90**, wherein the download engine is automatically triggered to identify the one or more program components when communication to the remote server can be established.

**101.** The system of claim **90**, wherein the one or more interfaces include at least one of a USB interface, a radio frequency (RF) interface, a Wi-Fi interface, and an Ethernet interface.

**102.** The system of claim **90**, wherein when communication to the remote server is established when the download engine is in range of a wireless network.

**103.** The system of claim **90**, further comprising a data validation component configured to validate the one or more program components before the one or more program components is deployed.

**104.** The system of claim **103**, wherein the data validation component determines whether the one or more program components are not corrupted.

**105.** The system of claim **103**, wherein the data validation component determines, with a check-sum routine, whether the one or more program components has been completely transferred from the remote server via the download engine.

**106.** The system of claim **103**, wherein the one or more program components are removed if the data validation determines that the one or more program components is corrupted.

\* \* \* \* \*

专利名称(译)	健康监测系统		
公开(公告)号	<a href="#">US20100146300A1</a>	公开(公告)日	2010-06-10
申请号	US12/630792	申请日	2009-12-03
[标]申请(专利权)人(译)	BROWN STEPHEN J		
申请(专利权)人(译)	BROWN STEPHEN J		
当前申请(专利权)人(译)	BROWN STEPHEN J		
[标]发明人	BROWN STEPHEN J		
发明人	BROWN, STEPHEN J.		
IPC分类号	G06F12/14 G06F17/30 G06F13/38 G06F13/36 G06F1/26 G06F12/16 G06F12/02 G06F3/048 G06F9/00 G06F21/00 G06F15/16 G06F9/44 G06F19/00 G06F15/00 G06F3/12 A61B5/00 A61B5/0205 A61B5/087 G01N33/487 G06F15/02 G16H10/60		
CPC分类号	A61B5/0205 A61B5/0022 A61B5/14532 A61B5/6896 A61B2560/0443 G01N33/48792 G06F15/025 G06F19/322 G06F19/3406 G06F19/3412 G06F19/3418 G06F19/345 G06F19/3456 G06F19/3475 G06F19/3481 G06F19/3487 G06Q10/10 G06Q40/08 G06Q50/22 G06Q50/24 Y10S128/903 A61B5/743 G06Q40/12 A61B5/087 G16H10/60 G16H15/00 G16H20/17 G16H40/40 G16H40/63 G16H40/67 G16H50/20		
外部链接	<a href="#">Espacenet</a> <a href="#">USPTO</a>		

# 摘要(译)

健康监测系统包括多个远程用户站点，每个远程用户站点包括至少一个用于收集用户健康监测数据的健康监测设备，交互式视频设备和用户界面设备；至少一个远程计算设备，被配置用于与多个远程用户站点进行信号通信，并从多个远程用户站点接收健康监视数据相关信号；配置用于与远程计算设备进行信号通信的至少一个计算机，其中交互式视频设备与远程计算设备交互地耦合。还描述了相关方法。

