



US007211053B2

(12) **United States Patent**
Marmaropoulos et al.

(10) **Patent No.:** **US 7,211,053 B2**
(45) **Date of Patent:** ***May 1, 2007**

(54) **SELECTIVELY APPLIED WEARABLE MEDICAL SENSORS**

(75) Inventors: **George Marmaropoulos**, Thessaloniki (GR); **Clive van Heerden**, London (GB)

(73) Assignee: **Koninklijke Philips Electronics, N.V.**, Eindhoven (NL)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **10/842,380**

(22) Filed: **May 10, 2004**

(65) **Prior Publication Data**

US 2004/0210165 A1 Oct. 21, 2004

Related U.S. Application Data

(63) Continuation of application No. 10/043,380, filed on Oct. 26, 2001, now Pat. No. 6,755,795.

(51) **Int. Cl.**

A61B 5/117 (2006.01)

A61B 5/103 (2006.01)

(52) **U.S. Cl.** **600/587**

(58) **Field of Classification Search** 600/300, 600/301, 386-390, 481, 509, 529, 534, 544, 600/546, 547, 549; 73/379.01; 2/1, 69; 128/897, 898

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,454,376 A *	10/1995	Stephens et al.	600/534
5,683,404 A *	11/1997	Johnson	606/151
5,802,611 A *	9/1998	McKenzie et al.	2/69
6,198,394 B1 *	3/2001	Jacobsen et al.	340/573.1
6,346,025 B1 *	2/2002	Tachau et al.	446/71
6,487,906 B1 *	12/2002	Hock	73/379.01
6,551,252 B2 *	4/2003	Sackner et al.	600/536
6,755,795 B2 *	6/2004	Marmaropoulos et al. ..	600/587
2002/0032386 A1 *	3/2002	Sackner et al.	600/536

* cited by examiner


Primary Examiner—Max F. Hindenburg

Assistant Examiner—Brian Szmaj

(57) **ABSTRACT**

A wearable garment includes sensor device of well-known design that are selectively pressed against the skin of the wearer when it is desired to obtain sensor readings, such as heart rate or temperature, or to apply treatment such as electrical pulses for defibrillation purposes. The garment incorporates one or more bands of flexible material that circumscribe portions of the wearer's body, with at least one sensor device positioned on the garment between the band and the wearer's body. To assure the comfort of the wearer, the circumference of the band can be shortened selectively from a first dimension, which loosely circumscribes a desired portion of the wearer's body, to a second, lesser dimension, which more tightly circumscribes the wearer's body and presses the sensor-securely into contact with the wearer's skin.

13 Claims, 2 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3

1

SELECTIVELY APPLIED WEARABLE MEDICAL SENSORS

This is a Continuation of application Ser. No. 10/043,380,
filed Oct. 26, 2001 and issued as U.S. Pat. No. 6,755,795. 5

BACKGROUND OF THE INVENTION

1. Field of the Invention

This invention relates to sensors used in the electrical
treatment and monitoring of human and animal bodies. 10
More specifically, the invention relates to wearable garments
that allow sensor devices to be pressed selectively against
the skin of the wearer when it is desired to obtain medical
information or to apply treatment by contact with the surface 15
of the skin.

2. Description of the Invention

Sensing and treatment devices for contacting the surface
of the skin are well-known in the art. It is also well-known 20
that such devices require tight-fitting, e.g. elevated unit
pressure, contact with the skin. However, the incorporation
of such sensors into wearable garments that provide for
applying sensors to the skin of a wearer with selective and/or
variable pressure, is not well-known.

In the prior art, sensors are either adhered directly to the
skin of the wearer using well-known types of adhesive 25
materials or, they are tightly strapped to the user's body
using suitable straps or bands having buckles or other
clasping mechanisms adapted to the purpose. Such prior art
apparatus for affixing sensors to the skin of a user do not take 30
the user's comfort into consideration by allowing the pres-
sure of the sensor against the skin to be increased easily only
when the sensor is in use.

The present invention overcomes these problems and
limitations of the prior art by allowing sensors to be pressed 35
against the skin of a wearer selectively, only when needed or
desired. The sensors are mounted on the inside of a wearable
garment, and the garment incorporates circumscribing bands
that can be reduced in diameter, selectively, to press the
sensors against the skin of one wearing the garment. 40

SUMMARY OF THE INVENTION

The present invention discloses a wearable garment that
incorporates one or more skin-contacting sensor devices 45
positioned to contact the skin surface of a user wearing the
garment. The wearable garment of this invention incorpo-
rates one or more bands of flexible material that circum-
scribe portions of the wearer's body with at least one sensor
device positioned between the band and the wearer. 50
The circumference of the band can be shortened from a first
dimension, which loosely circumscribes the desired portion
of the wearer's body, to a second, lesser dimension, which
securely presses the sensor into contact with the wearer's
skin.

In accordance with this invention, the band may be
tightened about the wearer's body either by drawing the
ends of a loop about the body in the nature of a drawstring
or by shrinking the overall length of the material of a
continuous loop as by passing an electrical current through 60
a continuous loop made of shape Memory Alloy Wire. In
this regard, the band may be loosely incorporated into the
body of the garment in the well-known manner of a draw-
string or, the band may be integrated into the body of the
garment as by forming a desired portion of the fabric 65
material from different fibers such as fibers comprising
Shape Memory alloy. To utilize the electrically responsive

2

shrinkage characteristics of shape-memory alloy material in
a convenient manner, the garment may be provided with
means for supporting or otherwise carrying with it, a por-
table electrical power supply such as a battery.

Further in accordance with this invention, it may be noted
that any treatment or monitoring equipment that relies upon
the sensors carried by the wearable garment, may incorpo-
rate internal features such as a programmable microproces-
sor to activate a band formed of shape memory alloy, at a
predetermined rate or in accordance with a predetermined
schedule.

These and other and further features and advantages of
this invention will be made more apparent to those having
skill in this art, by reference to the following specification
considered in conjunction with the accompanying drawings,
in which:

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a front plan view of a wearable garment in
accordance with this invention, incorporating two separate
drawstrings positioned to apply two separate sensors to the
skin of a wearer;

FIG. 2 is a pictorial representation of an alternative
embodiment of an electrically activatable band usable in
accordance with this invention in lieu of the drawstring of
FIG. 1; and,

FIG. 3 is a front plan view of an alternative embodiment
of a wearable garment in accordance with this invention,
incorporating constriction bands formed of a shape-memory
material that is constrictable in response to the flow of
electricity therethrough.

DETAILED DESCRIPTION OF THE DISCLOSED EMBODIMENT

In the following description, for purposes of explanation
rather than limitation, specific details are set forth such as
the particular architecture, interfaces, techniques, etc., in
order to provide a thorough understanding of the present
invention. For purposes of simplicity and clarity, detailed
descriptions of well-known devices, circuits, and methods
are omitted so as not to obscure the description of the present
invention with unnecessary detail.

Referring now to FIG. 1 of the drawings, a wearable shirt
garment 10 in accordance with this invention may be seen to
comprise a wearable body structure 12 having a first con-
striction band 14 coupled to the body 12 in the form of a
drawstring circumscribing the chest area of a wearer, and a
second constricting drawstring 16 circumscribing a wrist
area. Shown in dotted lines representing a position on the
interior (invisible) surface of garment 10, a first sensor
device 18 is positioned so that it will lie between the band
14 and the chest skin of one wearing the garment 10. A
second sensor 20 is similarly positioned to lie between band
16 and the wrist skin of a wearer. 55

It should be understood readily by those having skill in
this art, that the number and positioning of the bands 14, 16
and the sensors 18, 20 is illustrative only, and other or
different sensors, or different number of sensors, in other or
different locations may be incorporated into this or any
differently shaped garment without departing from the spirit
and scope of this invention. For example, in the absence of
any desire for a sensor in a wrist area, the garment may be
made essentially sleeveless in form, if desired. Similarly, the
garment may assume other forms, such as, for example,
trousers rather than a shirt or vest, or even, perhaps, a simple
wrist or arm band.

Bands **14**, **16** define loops positioned so as to substantially circumscribe desired portions of the anatomy of the wearer of the garment **10** in a loose-fitting loop, and they are configured to have a first circumferential loop dimension that circumscribes the wearer's body in a loose, non-confining fit. In the embodiment illustrated in FIG. 1, bands **14**, **16** are coupled to the body structure **12** in the manner of a drawstring that is looped around the anatomy of a wearer when the body structure is being worn. Further, the bands are provided with free ends **22**, **24**, that can be drawn in opposite directions to reduce the circumferential dimension of the loop from a first value to a second value that is less than the first. When the circumferential dimension of the loop is reduced in this way, the corresponding band constricts the body of the wearer of garment **10**, and presses the corresponding sensor device **18**, **20** against the wearer's skin.

As mentioned earlier herein, FIG. 2 illustrates an alternative form of constriction band **26**, having the form of a continuous, or closed, loop formed of shape memory alloy fibers having a first loose-fitting circumferential dimension. In the well-known manner of shape memory alloy materials, the first circumferential dimension of loop **26** may be reduced to a lesser second dimension so as to constrict an interposed sensor device **18'** into contact with a wearer's body in accordance with this invention, by passing an electrical current, from a battery **28'** for example, through the material of the loop. If desired, this embodiment of the invention may incorporate a suitable microprocessor **30'** coupled with a source of electrical power such as battery **28'**, to control the application of electrical current to the band. In this manner, constriction of the band **26** may be made to take place periodically or in association with any desired external activity, such as the activation of an apparatus associated with use of sensors such as sensor **18'**, shown in FIG. 3.

Referring to FIG. 3, bands **14'**, **16'** can be integrated with the fabric of a wearable structure using conventional methods and can be of any natural or man made material sufficient to accomplish operations consistent with the requirements of the embodiments of the present disclosure, including, for example, Nitinol. Bands **14'**, **16'** can also have different arrangements suitable to operatively interact with different sensors **18'**, **20'** associated with the wearable structure in different ways, and so as to accommodate different applications.

The fabric of the garment body structure **12** may be any suitable material usable for garments, consistent with the requirements of the embodiments of the invention described herein. Similarly, the material of the bands **14**, **16** may be any suitable flexible material consistent with this disclosure.

While the preferred embodiments of the present invention have been illustrated and described, it will be understood by those skilled in the art that various changes and modifications may be made, and equivalents may be substituted for elements thereof without departing from the true scope of the present invention. In addition, many modifications may be made to adapt to a particular situation and the teaching of the present invention without departing from the central scope. Therefore, it is intended that the present invention not be limited to the particular embodiment disclosed as the best mode contemplated for carrying out the present invention, but that the present invention include all embodiments falling within the scope of the appended claims.

Referring to FIG. 3, bands **14'**, **16'** can be integrated with the fabric of a wearable structure using any of a variety of conventional methods for weaving, sewing or knitting and can be of any natural or man made material sufficient to

accomplish operations consistent with the requirements of the embodiments of the present disclosure, including, for example, Nitinol. Bands **14'**, **16'** can also have different configurations suitable to operatively interact with different sensors **18'**, **20'** associated with the wearable structure so as to accommodate different applications.

The invention claimed is:

1. A garment for applying at least one sensor against the skin of a wearer, said garment comprising:

a sensor mounted to said garment in position to contact a desired portion of the anatomy of a wearer of said garment;

a band of flexible material incorporated into said garment in position to circumscribe a desired portion of the wearer's anatomy with said sensor being positioned to lie between said band and the wearer's anatomy;

said band of flexible material defining a loop having a first circumferential dimension, and including both manual and automatic adjusting means for selectively reducing, at a predetermined or variable pressure rate, said first circumferential dimension to a second circumferential dimension less than said first circumferential dimension so as to constrict the anatomy of a wearer of said garment and press said sensor against said anatomy.

2. The garment of claim 1, wherein said flexible material of said band is axially elastic.

3. The garment of claim 1, wherein said adjusting means includes a shape memory alloy that reduces in axial length in response to the passage of electrical current therethrough.

4. The garment of claim 1, wherein said garment has the shape of a shirt.

5. The garment of claim 1, wherein said sensor is positioned to contact the chest of a wearer.

6. The garment of claim 1, wherein said adjusting means includes one or more drawstrings.

7. A method of selectively applying at least one sensor against the anatomy of a subject, said method comprising the steps of:

positioning said sensor adjacent a desired portion of the anatomy of said subject;

surrounding said sensor and said subject with a constrictable band of flexible material incorporated into a wearable structure; and

constricting said constrictable band in association with an external activity at a predetermined or variable pressure rate to press said sensor into contact with the anatomy of said subject by adjusting means forming a component of said constrictable band and being capable of both manual and automatic operation.

8. The method of claim 7, wherein said adjusting means includes a shape memory alloy that reduces in axial length in response to the passage of electrical current therethrough.

9. The method of claim 7, wherein said adjusting means includes one or more drawstrings.

10. The garment of claim 3, wherein said shape memory alloy is Nitinol.

11. The garment of claim 3, further comprising a microprocessor suitable to activate said shape memory alloy according to a predetermined schedule.

12. A garment for applying a sensor to the skin of a wearer, said garment comprising:

a sensor operatively associated with said garment so as to contact a desired portion of the wearer's anatomy;

a flexible band incorporated into said garment in position to circumscribe a desired portion of the wearer's

5

anatomy with said sensor being positioned to lie between said flexible band and the wearer's anatomy, wherein said flexible band is adjustable between at least two dimensions, a first dimension and a second dimension that differs from said first dimension, and includes both manual and automatic adjusting means for periodically, at a predetermined or variable pressure rate, adjusting the dimension thereof.

6

13. The garment of claim **12**, further comprising a shape memory alloy that reduces in axial length in response to the passage of electrical current therethrough, and a microprocessor suitable to activate said shape memory alloy according to said predetermined or variable pressure rate.

* * * * *

专利名称(译)	有选择地应用可穿戴医疗传感器		
公开(公告)号	US7211053	公开(公告)日	2007-05-01
申请号	US10/842380	申请日	2004-05-10
[标]申请(专利权)人(译)	MARMAROPOULOS GEORGE •范•希尔顿克莱夫.		
申请(专利权)人(译)	MARMAROPOULOS GEORGE •范•希尔顿克莱夫.		
当前申请(专利权)人(译)	皇家飞利浦电子N.V.		
[标]发明人	MARMAROPOULOS GEORGE VAN HEERDEN CLIVE		
发明人	MARMAROPOULOS, GEORGE VAN HEERDEN, CLIVE		
IPC分类号	A61B5/117 A61B5/103 A41D13/00 A41D1/00 A61B A61B5/00 A61B5/0205 A61B5/024 A61B5/04 A61B5/0408 A61N1/04		
CPC分类号	A61B5/02055 A61B5/02438 A61B5/6804		
其他公开文献	US20040210165A1		
外部链接	Espacenet USPTO		

摘要(译)

可穿戴服装包括众所周知的设计的传感器装置，当希望获得传感器读数（例如心率或温度）时，该传感器装置选择性地压在佩戴者的皮肤上，或者为了除颤目的而施加诸如电脉冲的治疗。该服装包括一个或多个柔性材料带，其围绕穿着者身体的一部分，至少一个传感器装置位于该带和穿着者身体之间的衣服上。为了确保穿着者的舒适性，可以从第一尺寸选择性地缩短带的周长，第一尺寸松散地围绕穿着者身体的期望部分，到第二较小尺寸，其更紧密地围绕穿着者的身体并且按压传感器 - 牢固地与佩戴者的皮肤接触。

