



US008821397B2

(12) **United States Patent**  
**Al-Ali et al.**

(10) **Patent No.:** **US 8,821,397 B2**  
(45) **Date of Patent:** **Sep. 2, 2014**

(54) **DEPTH OF CONSCIOUSNESS MONITOR INCLUDING OXIMETER**

(75) Inventors: **Ammar Al-Ali**, San Juan Capistrano, CA (US); **Yassir Abdul-Hafiz**, Irvine, CA (US)

(73) Assignee: **Masimo Corporation**, Irvine, CA (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 139 days.

(21) Appl. No.: **13/246,725**

(22) Filed: **Sep. 27, 2011**

(65) **Prior Publication Data**

US 2012/0083673 A1 Apr. 5, 2012

**Related U.S. Application Data**

(60) Provisional application No. 61/387,457, filed on Sep. 28, 2010.

(51) **Int. Cl.**

**A61B 5/00** (2006.01)  
**A61B 5/04** (2006.01)  
**A61B 5/0476** (2006.01)  
**A61B 5/0478** (2006.01)  
**A61B 5/048** (2006.01)  
**A61B 5/1455** (2006.01)

(52) **U.S. Cl.**

CPC ..... **A61B 5/0476** (2013.01); **A61B 5/0478** (2013.01); **A61B 5/048** (2013.01); **A61B 5/14553** (2013.01); **A61B 5/1455** (2013.01); **A61B 5/6803** (2013.01); **A61B 5/6814** (2013.01)  
USPC ..... **600/301**; **600/323**; **600/324**; **600/340**; **600/372**; **600/383**; **600/544**

(58) **Field of Classification Search**

CPC ..... **A61B 5/083-5/0836**; **A61B 5/6814**;

A61B 5/14551-5/14553; A61B 5/4058-5/4064; A61B 5/6867-5/6868; A61B 5/00434-5/00446; A61B 5/0476-5/0478; A61B 5/4818; A61B 5/4094; A61B 5/6803; A61B 5/02438; A61B 5/00412; A61B 5/1117; A61B 5/0002; A61B 5/0006; A61B 5/16; A61B 5/18; A61B 5/145; G06F 19/3418  
USPC ..... **600/300-301, 323, 372-386, 544**  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,638,640 A \* 2/1972 Shaw ..... 600/323  
4,223,680 A 9/1980 Jobsis

(Continued)

FOREIGN PATENT DOCUMENTS

EP 505491 9/1992  
EP 0 541 393 11/1992

(Continued)

OTHER PUBLICATIONS

Partial International Search Report for International Application No. PCT/US2011/053540, date of mailing: Jan. 30, 2012, in 4 pages.

(Continued)


*Primary Examiner* — Bill Thomson  
*Assistant Examiner* — Shirley Jian

(74) *Attorney, Agent, or Firm* — Knobbe Martens Olson & Bear LLP

(57) **ABSTRACT**

The present disclosure relates to a sensor for monitoring the depth of consciousness of a patient. The sensor includes a plurality of light sources, light detectors, and in some embodiments, electrodes. In an embodiment, the sensor includes reusable and disposable portions.

**18 Claims, 41 Drawing Sheets**



(56)

## References Cited

## U.S. PATENT DOCUMENTS

4,281,645 A	8/1981	Jobsis	D362,063 S	9/1995	Savage et al.
4,321,930 A	3/1982	Jobsis et al.	5,450,855 A	9/1995	Rosenfeld et al.
4,380,240 A	4/1983	Jobsis et al.	5,452,717 A	9/1995	Branigan et al.
4,510,938 A	4/1985	Jobsis et al.	5,452,718 A	9/1995	Clare et al.
4,796,184 A	1/1989	Bahr et al.	D363,120 S	10/1995	Savage et al.
4,803,997 A	2/1989	Bowman	5,456,252 A	10/1995	Vari et al.
4,805,623 A	2/1989	Jobsis	5,458,117 A	10/1995	Chamoun et al.
4,901,238 A	2/1990	Suzuki et al.	5,477,051 A	12/1995	Tsuchiya
4,907,876 A	3/1990	Suzuki et al.	5,479,934 A	1/1996	Imran
4,908,762 A	3/1990	Suzuki et al.	5,482,034 A *	1/1996	Lewis et al. .... 600/323
4,917,116 A	4/1990	LaViola et al.	5,482,036 A	1/1996	Diab et al.
4,928,696 A	5/1990	Henderson et al.	5,490,505 A	2/1996	Diab et al.
4,938,218 A	7/1990	Goodman et al.	5,492,118 A	2/1996	Gratton et al.
4,957,000 A	9/1990	Delpy et al.	5,494,043 A	2/1996	O'Sullivan et al.
4,960,128 A	10/1990	Gordon et al.	5,497,769 A	3/1996	Gratton et al.
4,964,408 A	10/1990	Hink et al.	5,511,552 A	4/1996	Johnson
4,967,038 A	10/1990	Gevins et al.	5,517,987 A	5/1996	Tsuchiya
4,972,331 A	11/1990	Chance	5,520,176 A	5/1996	Cohen
4,996,992 A	3/1991	LaViola et al.	5,520,683 A	5/1996	Subramaniam et al.
5,022,403 A	6/1991	LaViola	5,529,065 A	6/1996	Tsuchiya
5,032,024 A	7/1991	Cope	5,533,511 A	7/1996	Kaspari et al.
5,038,782 A	8/1991	Gevins et al.	5,534,851 A	7/1996	Russek
5,041,187 A	8/1991	Hink et al.	5,540,722 A	7/1996	Clare et al.
5,069,213 A	12/1991	Polczynski	5,553,614 A	9/1996	Chance
5,090,415 A	2/1992	Yamashita et al.	5,561,275 A	10/1996	Savage et al.
5,099,842 A	3/1992	Mannheimer et al.	5,562,002 A	10/1996	Lalin
5,101,830 A	4/1992	Duffy et al.	5,564,417 A	10/1996	Chance
5,103,829 A	4/1992	Suzuki et al.	5,564,418 A	10/1996	Ozaki et al.
5,109,849 A	5/1992	Goodman et al.	5,582,169 A	12/1996	Oda et al.
5,119,815 A *	6/1992	Chance ..... 600/433	5,590,649 A	1/1997	Caro et al.
5,122,974 A	6/1992	Chance	5,596,038 A	1/1997	Subramaniam
5,154,180 A	10/1992	Blanchet et al.	5,596,987 A	1/1997	Chance
5,163,438 A	11/1992	Gordon et al.	5,602,924 A	2/1997	Durand et al.
5,179,570 A	1/1993	Imran	5,605,157 A	2/1997	Panescu et al.
5,179,957 A	1/1993	Williams	5,626,145 A	5/1997	Clapp et al.
5,181,520 A	1/1993	Wertheim et al.	5,632,272 A	5/1997	Diab et al.
5,187,672 A	2/1993	Chance et al.	5,638,816 A	6/1997	Kiani-Azarbayjany et al.
5,195,531 A	3/1993	Bennett	5,638,818 A	6/1997	Diab et al.
5,211,174 A	5/1993	Imran	5,640,247 A	6/1997	Tsuchiya et al.
5,213,105 A	5/1993	Gratton et al.	5,645,440 A	7/1997	Tobler et al.
5,218,962 A	6/1993	Mannheimer et al.	5,664,574 A	9/1997	Chance
5,220,502 A	6/1993	Qian et al.	5,673,701 A	10/1997	Chance
5,226,417 A	7/1993	Swedlow et al.	5,676,142 A	10/1997	Miwa et al.
5,228,440 A	7/1993	Chung et al.	5,678,558 A	10/1997	Johnson
5,247,932 A	9/1993	Chung et al.	5,678,560 A	10/1997	Sakamoto et al.
5,253,646 A	10/1993	Delpy et al.	5,685,299 A	11/1997	Diab et al.
5,280,793 A	1/1994	Rosenfeld et al.	5,686,516 A	11/1997	Tzur
5,289,822 A	3/1994	Highe et al.	5,694,931 A	12/1997	Tsuchiya
5,295,482 A	3/1994	Clare et al.	5,697,367 A *	12/1997	Lewis et al. .... 600/310
5,299,118 A	3/1994	Martens et al.	5,706,821 A	1/1998	Matcher et al.
5,299,822 A	4/1994	Mayr et al.	5,727,547 A	3/1998	Levinson et al.
5,319,355 A	6/1994	Russek	D393,830 S	4/1998	Tobler et al.
5,327,888 A	7/1994	Imran	5,743,260 A	4/1998	Chung et al.
5,331,959 A	7/1994	Imran	5,743,262 A	4/1998	Lepper, Jr. et al.
5,337,744 A	8/1994	Branigan	5,746,210 A	5/1998	Benaron et al.
5,337,745 A	8/1994	Benaron	5,752,519 A	5/1998	Benaron et al.
5,341,805 A	8/1994	Stavridi et al.	5,752,914 A	5/1998	Delonzor et al.
5,345,934 A	9/1994	Highe et al.	5,758,644 A	6/1998	Diab et al.
5,353,799 A	10/1994	Chance	5,760,910 A	6/1998	Lepper, Jr. et al.
5,361,773 A	11/1994	Ives	5,769,785 A	6/1998	Diab et al.
D353,195 S	12/1994	Savage et al.	5,772,587 A	6/1998	Gratton et al.
D353,196 S	12/1994	Savage et al.	5,772,588 A	6/1998	Miwa et al.
5,377,674 A	1/1995	Kuestner	5,775,330 A	7/1998	Kangas et al.
5,377,675 A	1/1995	Ruskewicz et al.	5,776,058 A	7/1998	Levinson et al.
5,377,676 A	1/1995	Vari et al.	5,779,631 A	7/1998	Chance
5,386,827 A	2/1995	Chance et al.	5,782,237 A	7/1998	Casciani et al.
5,402,778 A	4/1995	Chance	5,782,756 A	7/1998	Mannheimer
5,406,957 A	4/1995	Tansey	5,782,757 A	7/1998	Diab et al.
5,413,098 A	5/1995	Benaron	5,785,658 A	7/1998	Benaron et al.
D359,546 S	6/1995	Savage et al.	5,785,659 A	7/1998	Caro et al.
5,421,329 A	6/1995	Casciani et al.	5,791,347 A	8/1998	Flaherty et al.
5,424,843 A	6/1995	Tromberg et al.	5,807,261 A	9/1998	Benaron et al.
5,431,170 A	7/1995	Mathews	5,807,263 A	9/1998	Chance
D361,840 S	8/1995	Savage et al.	5,810,734 A	9/1998	Caro et al.
5,441,054 A	8/1995	Tsuchiya	5,813,980 A	9/1998	Levinson et al.
			5,813,993 A	9/1998	Kaplan et al.
			5,816,247 A	10/1998	Maynard
			5,820,558 A	10/1998	Chance
			5,823,950 A	10/1998	Diab et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

5,823,952	A	10/1998	Levinson et al.	6,272,363	B1	8/2001	Casciani et al.
5,830,131	A	11/1998	Caro et al.	6,272,367	B1	8/2001	Chance
5,833,618	A	11/1998	Caro et al.	6,272,378	B1	8/2001	Baumgart-Schmitt
5,846,208	A	12/1998	Pichlmayr et al.	6,278,522	B1	8/2001	Lepper, Jr. et al.
5,851,179	A	12/1998	Ritson et al.	6,280,213	B1	8/2001	Tobler et al.
5,853,370	A *	12/1998	Chance et al. .... 600/473	6,285,896	B1	9/2001	Tobler et al.
RE36,044	E	1/1999	Benaron	6,298,252	B1	10/2001	Kovach et al.
5,857,979	A	1/1999	Ryu et al.	6,301,493	B1	10/2001	Marro et al.
5,860,919	A	1/1999	Kiani-Azarbayjany et al.	6,317,627	B1 *	11/2001	Ennen et al. .... 600/544
5,865,736	A	2/1999	Baker, Jr. et al.	6,321,100	B1	11/2001	Parker
5,873,821	A	2/1999	Chance et al.	6,325,761	B1	12/2001	Jay
5,879,294	A	3/1999	Anderson et al.	6,334,065	B1	12/2001	Al-Ali et al.
5,890,929	A	4/1999	Mills et al.	6,335,792	B1	1/2002	Tsuchiya
5,902,235	A *	5/1999	Lewis et al. .... 600/323	6,343,224	B1	1/2002	Parker
5,904,654	A	5/1999	Wohltmann et al.	6,343,229	B1	1/2002	Siebler et al.
5,917,190	A	6/1999	Yodh et al.	6,349,228	B1	2/2002	Kiani et al.
5,919,134	A	7/1999	Diab	6,360,114	B1	3/2002	Diab et al.
5,934,925	A	8/1999	Tobler et al.	6,368,283	B1	4/2002	Xu et al.
5,940,182	A	8/1999	Lepper, Jr. et al.	6,368,287	B1 *	4/2002	Hadas .... 600/529
5,954,053	A	9/1999	Chance et al.	6,371,921	B1	4/2002	Caro et al.
5,983,121	A	11/1999	Tsuchiya	6,377,829	B1	4/2002	Al-Ali
5,987,346	A	11/1999	Benaron et al.	6,377,840	B1	4/2002	Gritsenko et al.
5,987,351	A	11/1999	Chance	6,385,486	B1 *	5/2002	John et al. .... 600/544
5,995,855	A	11/1999	Kiani et al.	6,388,240	B2	5/2002	Schulz et al.
5,997,343	A	12/1999	Mills et al.	6,397,091	B2	5/2002	Diab et al.
5,999,846	A	12/1999	Pardey et al.	6,397,099	B1	5/2002	Chance
6,002,952	A	12/1999	Diab et al.	6,397,845	B1	6/2002	Burton
6,011,986	A	1/2000	Diab et al.	6,416,480	B1	7/2002	Nenov
6,011,990	A	1/2000	Schultz et al.	6,430,437	B1	8/2002	Marro
6,027,452	A	2/2000	Flaherty et al.	6,430,525	B1	8/2002	Weber et al.
6,032,064	A *	2/2000	Devlin et al. .... 600/383	6,456,862	B2	9/2002	Benni
6,032,065	A	2/2000	Brown et al.	6,463,310	B1	10/2002	Swedlow et al.
6,035,223	A	3/2000	Baker, Jr.	6,463,311	B1	10/2002	Diab
6,036,642	A	3/2000	Diab et al.	6,470,199	B1	10/2002	Kopotic et al.
6,045,509	A	4/2000	Caro et al.	6,473,632	B1	10/2002	Myers
6,052,619	A *	4/2000	John .... 600/544	6,481,899	B1	11/2002	Quast et al.
6,058,324	A	5/2000	Chance	6,487,343	B1	11/2002	Lewandowski et al.
6,067,462	A	5/2000	Diab et al.	6,496,724	B1	12/2002	Levendowski et al.
6,067,467	A	5/2000	John	6,497,658	B2	12/2002	Roizen et al.
6,069,975	A	5/2000	Lehmann et al.	6,501,975	B2	12/2002	Diab et al.
6,070,098	A	5/2000	Moore-Ede et al.	6,505,059	B1	1/2003	Kollias et al.
6,075,610	A	6/2000	Ueda et al.	6,511,424	B1	1/2003	Moore-Ede et al.
6,076,010	A	6/2000	Boas et al.	6,515,273	B2	2/2003	Al-Ali
6,078,833	A	6/2000	Hueber	6,516,209	B2	2/2003	Cheng et al.
6,081,735	A	6/2000	Diab et al.	6,516,214	B1	2/2003	Boas
6,088,607	A	7/2000	Diab et al.	6,519,487	B1	2/2003	Parker
6,110,522	A	8/2000	Lepper, Jr. et al.	6,525,386	B1	2/2003	Mills et al.
6,124,597	A	9/2000	Shehada	6,526,300	B1	2/2003	Kiani et al.
6,128,521	A	10/2000	Marro et al.	6,526,309	B1	2/2003	Chance
6,129,675	A	10/2000	Jay	6,537,228	B1	3/2003	Lambert
6,144,868	A	11/2000	Parker	6,541,756	B2	4/2003	Schulz et al.
6,151,516	A	11/2000	Kiani-Azarbayjany et al.	6,542,764	B1	4/2003	Al-Ali et al.
6,152,754	A	11/2000	Gerhardt et al.	6,542,772	B1	4/2003	Chance
6,154,669	A	11/2000	Hunter et al.	6,549,284	B1	4/2003	Boas et al.
6,157,850	A	12/2000	Diab et al.	6,564,076	B1	5/2003	Chance
6,157,857	A	12/2000	Dimpfel	6,567,165	B1	5/2003	Tsuchiya et al.
6,165,005	A	12/2000	Mills et al.	6,575,902	B1	6/2003	Burton
6,184,521	B1	2/2001	Coffin, IV et al.	6,577,884	B1	6/2003	Boas
6,192,260	B1	2/2001	Chance	6,580,086	B1	6/2003	Schulz et al.
6,192,261	B1	2/2001	Gratton et al.	6,584,336	B1	6/2003	Ali et al.
6,206,830	B1	3/2001	Diab et al.	6,587,703	B2	7/2003	Cheng et al.
6,216,021	B1	4/2001	Franceschini et al.	6,591,123	B2	7/2003	Fein et al.
6,229,856	B1	5/2001	Diab et al.	6,594,513	B1	7/2003	Jobsis et al.
6,232,609	B1	5/2001	Snyder et al.	6,594,518	B1	7/2003	Benaron et al.
6,233,470	B1	5/2001	Tsuchiya	6,595,316	B2	7/2003	Cybulski et al.
6,236,871	B1	5/2001	Tsuchiya	6,597,931	B1	7/2003	Cheng et al.
6,236,872	B1	5/2001	Diab et al.	6,597,932	B2	7/2003	Tian et al.
6,236,885	B1	5/2001	Hunter et al.	6,597,933	B2	7/2003	Kiani et al.
6,240,305	B1	5/2001	Tsuchiya	6,597,944	B1 *	7/2003	Hadas .... 600/546
6,241,683	B1	6/2001	Macklem et al.	6,599,281	B1	7/2003	Struys et al.
6,246,892	B1	6/2001	Chance	6,606,511	B1	8/2003	Ali et al.
6,253,097	B1	6/2001	Aronow et al.	6,609,024	B1	8/2003	Ryu et al.
6,256,523	B1 *	7/2001	Diab et al. .... 600/323	6,615,065	B1 *	9/2003	Barrett et al. .... 600/340
6,263,221	B1	7/2001	Chance et al.	6,618,614	B1	9/2003	Chance
6,263,222	B1	7/2001	Diab et al.	6,631,291	B2	10/2003	Viertio-Oja et al.
				6,632,181	B2	10/2003	Flaherty et al.
				6,639,668	B1	10/2003	Trepagnier
				6,640,116	B2	10/2003	Diab
				6,643,530	B2	11/2003	Diab et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

6,650,917	B2	11/2003	Diab et al.	6,975,901	B2	12/2005	Philip
6,654,624	B2	11/2003	Diab et al.	6,979,812	B2	12/2005	Al-Ali
6,654,632	B2	11/2003	Lange et al.	6,985,763	B2	1/2006	Boas et al.
6,658,276	B2	12/2003	Kianl et al.	6,985,764	B2	1/2006	Mason et al.
6,661,161	B1	12/2003	Lanzo et al.	6,993,371	B2	1/2006	Kiani et al.
6,662,033	B2	12/2003	Casciani et al.	6,993,380	B1	1/2006	Modarres
6,665,560	B2	12/2003	Becker et al.	6,996,427	B2	2/2006	Ali et al.
6,667,803	B1	12/2003	Flessland et al.	6,999,904	B2	2/2006	Weber et al.
6,671,530	B2	12/2003	Chung et al.	7,003,338	B2	2/2006	Weber et al.
6,671,531	B2	12/2003	Al-Ali et al.	7,003,339	B2	2/2006	Diab et al.
6,675,031	B1	1/2004	Porges et al.	7,010,341	B2	3/2006	Chance
6,678,543	B2	1/2004	Diab et al.	7,015,451	B2	3/2006	Dalke et al.
6,684,090	B2	1/2004	Ali et al.	7,024,233	B2	4/2006	Ali et al.
6,684,091	B2	1/2004	Parker	7,027,849	B2	4/2006	Al-Ali
6,687,524	B1	2/2004	Svejk	7,030,749	B2	4/2006	Al-Ali
6,697,656	B1	2/2004	Al-Ali	7,035,744	B2	4/2006	Cheriet et al.
6,697,657	B1	2/2004	Shehada et al.	7,039,449	B2	5/2006	Al-Ali
6,697,658	B2	2/2004	Al-Ali	7,041,060	B2	5/2006	Flaherty et al.
RE38,476	E	3/2004	Diab et al.	7,044,918	B2	5/2006	Diab
6,699,194	B1	3/2004	Diab et al.	7,047,054	B2	5/2006	Benni
6,701,170	B2	3/2004	Stetson	7,047,055	B2	5/2006	Boas et al.
6,708,048	B1	3/2004	Chance	7,047,056	B2	5/2006	Hannula et al.
6,708,049	B1	3/2004	Berson et al.	7,054,680	B1	5/2006	Genger et al.
6,711,426	B2	3/2004	Benaron et al.	7,067,893	B2	6/2006	Mills et al.
6,714,804	B2	3/2004	Al-Ali et al.	7,072,701	B2*	7/2006	Chen et al. .... 600/331
RE38,492	E	4/2004	Diab et al.	7,085,597	B2	8/2006	Fein et al.
6,721,582	B2	4/2004	Trepagnier et al.	7,092,748	B2	8/2006	Valdes et al.
6,721,585	B1	4/2004	Parker	7,096,052	B2	8/2006	Mason et al.
6,725,075	B2	4/2004	Al-Ali	7,096,054	B2	8/2006	Abdul-Hafiz et al.
6,728,560	B2	4/2004	Kollias et al.	7,132,641	B2	11/2006	Schulz et al.
6,728,564	B2	4/2004	Lahteenmaki	7,139,603	B2	11/2006	Chance
6,731,975	B1	5/2004	Viertio-Oja	7,142,901	B2	11/2006	Kiani et al.
6,735,458	B2	5/2004	Cheng et al.	7,149,561	B2	12/2006	Diab
6,735,459	B2	5/2004	Parker	7,186,966	B2	3/2007	Al-Ali
6,745,060	B2	6/2004	Diab et al.	7,190,261	B2	3/2007	Al-Ali
6,748,259	B1	6/2004	Benaron et al.	7,209,861	B2	4/2007	Hively
6,748,263	B2	6/2004	Griffiths et al.	7,215,984	B2	5/2007	Diab
6,751,499	B2	6/2004	Lange et al.	7,215,986	B2	5/2007	Diab
6,757,558	B2	6/2004	Lange et al.	7,220,240	B2	5/2007	Struys et al.
6,760,607	B2	7/2004	Al-Ali	7,221,971	B2	5/2007	Diab
6,768,920	B2	7/2004	Lange et al.	7,221,975	B2	5/2007	Lindstrom
6,770,028	B1	8/2004	Ali et al.	7,225,006	B2	5/2007	Al-Ali et al.
6,771,994	B2	8/2004	Kiani et al.	7,225,007	B2	5/2007	Al-Ali
6,792,300	B1	9/2004	Diab et al.	7,225,013	B2	5/2007	Geva et al.
6,795,724	B2	9/2004	Hogan	RE39,672	E	6/2007	Shehada et al.
6,801,648	B2	10/2004	Cheng	7,228,169	B2	6/2007	Viertio-Oja
6,801,797	B2	10/2004	Mannheimer et al.	7,229,430	B2	6/2007	Hickle et al.
6,801,803	B2	10/2004	Viertio-Oja	7,231,246	B2	6/2007	Rautee et al.
6,813,511	B2	11/2004	Diab et al.	7,239,385	B2	7/2007	Schmitz et al.
6,816,741	B2	11/2004	Diab	7,239,901	B2	7/2007	Gritsenko
6,822,564	B2	11/2004	Al-Ali	7,239,905	B2	7/2007	Kiani-Azarbayjany et al.
6,826,419	B2	11/2004	Diab et al.	7,239,988	B2	7/2007	Hasson et al.
6,830,047	B2	12/2004	Heitmeier et al.	7,245,953	B1	7/2007	Parker
6,830,711	B2	12/2004	Mills et al.	7,248,909	B2	7/2007	Lee et al.
6,836,502	B2	12/2004	Canady et al.	7,254,429	B2	8/2007	Schurman et al.
6,839,583	B1	1/2005	Lewandowski et al.	7,254,431	B2	8/2007	Al-Ali
6,850,787	B2	2/2005	Weber et al.	7,254,433	B2	8/2007	Diab et al.
6,850,788	B2	2/2005	Al-Ali	7,254,434	B2	8/2007	Schulz et al.
6,852,083	B2	2/2005	Caro et al.	7,254,500	B2	8/2007	Makeig et al.
6,861,639	B2	3/2005	Al-Ali	7,272,425	B2	9/2007	Al-Ali
6,892,006	B2	5/2005	Lewandowski et al.	7,274,955	B2	9/2007	Kiani et al.
6,898,452	B2	5/2005	Al-Ali et al.	D554,263	S	10/2007	Al-Ali
6,907,280	B2	6/2005	Becerra et al.	7,277,741	B2	10/2007	Debreczeny et al.
6,920,345	B2	7/2005	Al-Ali et al.	7,277,831	B1	10/2007	Pawelzik et al.
6,931,268	B1	8/2005	Kiani-Azarbayjany et al.	7,280,858	B2	10/2007	Al-Ali et al.
6,934,570	B2*	8/2005	Kiani et al. .... 600/324	7,288,066	B2	10/2007	Drew
6,934,579	B2	8/2005	Mantzaxaridis et al.	7,289,835	B2	10/2007	Mansfield et al.
6,939,305	B2	9/2005	Flaherty et al.	7,289,837	B2	10/2007	Mannheimer et al.
6,943,348	B1	9/2005	Coffin, IV	7,292,883	B2	11/2007	De Felice et al.
6,950,687	B2	9/2005	Al-Ali	7,295,866	B2	11/2007	Al-Ali
6,950,698	B2	9/2005	Sarkela et al.	7,313,427	B2	12/2007	Benni
6,956,650	B2	10/2005	Boas et al.	7,328,053	B1	2/2008	Diab et al.
6,958,815	B2	10/2005	Bevilacqua et al.	7,332,784	B2	2/2008	Mills et al.
6,961,598	B2	11/2005	Diab	7,333,647	B2	2/2008	Boas et al.
6,970,792	B1	11/2005	Diab	7,340,287	B2	3/2008	Mason et al.
				7,341,559	B2	3/2008	Schulz et al.
				7,343,186	B2	3/2008	Lamego et al.
				7,343,187	B2	3/2008	Stetson
				7,349,726	B2	3/2008	Casciani et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

D566,282	S	4/2008	Al-Ali et al.	7,873,497	B2	1/2011	Weber et al.
7,355,512	B1	4/2008	Al-Ali	7,880,606	B2	2/2011	Al-Ali
7,355,688	B2	4/2008	Lash et al.	7,880,626	B2	2/2011	Al-Ali et al.
7,356,365	B2	4/2008	Schurman	7,891,355	B2	2/2011	Al-Ali et al.
D568,479	S	5/2008	Mao et al.	7,894,868	B2	2/2011	Al-Ali et al.
7,371,981	B2	5/2008	Abdul-Hafiz	7,899,507	B2	3/2011	Al-Ali et al.
7,373,193	B2	5/2008	Al-Ali et al.	7,899,518	B2	3/2011	Trepagnier et al.
7,373,194	B2	5/2008	Weber et al.	7,904,132	B2	3/2011	Weber et al.
7,373,198	B2	5/2008	Bibian et al.	7,909,772	B2	3/2011	Popov et al.
7,376,453	B1	5/2008	Diab et al.	7,910,875	B2	3/2011	Al-Ali
7,376,454	B2	5/2008	Casciani et al.	7,919,713	B2	4/2011	Al-Ali et al.
7,377,794	B2	5/2008	Al-Ali et al.	7,937,128	B2	5/2011	Al-Ali
7,377,899	B2	5/2008	Weber et al.	7,937,129	B2	5/2011	Mason et al.
7,383,070	B2	6/2008	Diab et al.	7,937,130	B2	5/2011	Diab et al.
7,392,074	B2	6/2008	Isaacson et al.	7,941,199	B2	5/2011	Kiani
7,415,297	B2	8/2008	Al-Ali et al.	7,951,086	B2	5/2011	Flaherty et al.
7,415,298	B2	8/2008	Casciani et al.	7,957,780	B2	6/2011	Lamego et al.
7,427,165	B2	9/2008	Benaron et al.	7,962,188	B2	6/2011	Kiani et al.
7,428,432	B2	9/2008	Ali et al.	7,962,190	B1	6/2011	Diab et al.
7,428,434	B2	9/2008	Tromberg et al.	7,976,472	B2	7/2011	Kiani
7,438,683	B2	10/2008	Al-Ali et al.	7,988,637	B2	8/2011	Diab
7,440,787	B2	10/2008	Diab	7,990,382	B2	8/2011	Kiani
7,454,240	B2	11/2008	Diab et al.	7,991,446	B2	8/2011	Ali et al.
7,457,652	B2	11/2008	Porges et al.	8,000,761	B2	8/2011	Al-Ali
7,467,002	B2	12/2008	Weber et al.	8,008,088	B2	8/2011	Bellott et al.
7,469,157	B2	12/2008	Diab et al.	RE42,753	E	9/2011	Kiani-Azarbayjany et al.
7,471,969	B2	12/2008	Diab et al.	8,019,400	B2	9/2011	Diab et al.
7,471,971	B2	12/2008	Diab et al.	8,028,701	B2	10/2011	Al-Ali et al.
7,474,245	B1	1/2009	Wang et al.	8,029,765	B2	10/2011	Bellott et al.
7,478,108	B2	1/2009	Townsend et al.	8,036,728	B2	10/2011	Diab et al.
7,483,729	B2	1/2009	Al-Ali et al.	8,046,040	B2	10/2011	Ali et al.
7,483,730	B2	1/2009	Diab et al.	8,046,041	B2	10/2011	Diab et al.
7,483,731	B2	1/2009	Hoarau et al.	8,046,042	B2	10/2011	Diab et al.
7,486,977	B2*	2/2009	Sweitzer et al. .... 600/323	8,048,040	B2	11/2011	Kiani
7,489,958	B2	2/2009	Diab et al.	8,050,728	B2	11/2011	Al-Ali et al.
7,496,391	B2	2/2009	Diab et al.	8,103,328	B2*	1/2012	Turner et al. .... 600/383
7,496,393	B2	2/2009	Diab et al.	RE43,169	E	2/2012	Parker
7,496,400	B2	2/2009	Hoskonen et al.	8,118,620	B2	2/2012	Al-Ali et al.
D587,657	S	3/2009	Al-Ali et al.	8,126,528	B2	2/2012	Diab et al.
7,499,740	B2	3/2009	Nordstrom et al.	8,128,572	B2	3/2012	Diab et al.
7,499,741	B2	3/2009	Diab et al.	8,130,105	B2	3/2012	Al-Ali et al.
7,499,835	B2	3/2009	Weber et al.	8,145,287	B2	3/2012	Diab et al.
7,500,950	B2	3/2009	Al-Ali et al.	8,150,487	B2	4/2012	Diab et al.
7,509,154	B2	3/2009	Diab et al.	8,175,672	B2	5/2012	Parker
7,509,494	B2	3/2009	Al-Ali	8,180,420	B2	5/2012	Diab et al.
7,510,849	B2	3/2009	Schurman et al.	8,182,443	B1	5/2012	Kiani
7,515,948	B1	4/2009	Balberg et al.	8,185,180	B2	5/2012	Diab et al.
7,522,949	B2	4/2009	Berson et al.	8,190,223	B2	5/2012	Al-Ali et al.
7,526,328	B2	4/2009	Diab et al.	8,190,227	B2	5/2012	Diab et al.
7,530,942	B1	5/2009	Diab	8,203,438	B2	6/2012	Kiani et al.
7,530,949	B2	5/2009	Al Ali et al.	8,203,704	B2	6/2012	Merritt et al.
7,530,955	B2	5/2009	Diab et al.	8,224,411	B2	7/2012	Al-Ali et al.
7,563,110	B2	7/2009	Al-Ali et al.	8,228,181	B2	7/2012	Al-Ali
7,596,398	B2	9/2009	Al-Ali et al.	8,229,533	B2	7/2012	Diab et al.
7,610,082	B2	10/2009	Chance	8,233,955	B2	7/2012	Al-Ali et al.
7,618,375	B2	11/2009	Flaherty	8,244,325	B2	8/2012	Al-Ali et al.
D606,659	S	12/2009	Kiani et al.	8,255,026	B1	8/2012	Al-Ali
7,647,083	B2	1/2010	Al-Ali et al.	8,255,027	B2	8/2012	Al-Ali et al.
D609,193	S	2/2010	Al-Ali et al.	8,255,028	B2	8/2012	Al-Ali et al.
D614,305	S	4/2010	Al-Ali et al.	8,260,577	B2	9/2012	Weber et al.
RE41,317	E	5/2010	Parker	8,265,723	B1	9/2012	McHale et al.
7,729,733	B2	6/2010	Al-Ali et al.	8,274,360	B2	9/2012	Sampath et al.
7,734,320	B2	6/2010	Al-Ali	8,301,217	B2	10/2012	Al-Ali et al.
7,761,127	B2	7/2010	Al-Ali et al.	8,310,336	B2	11/2012	Muhsin et al.
7,761,128	B2	7/2010	Al-Ali et al.	8,315,683	B2	11/2012	Al-Ali et al.
7,764,982	B2	7/2010	Dalke et al.	RE43,860	E	12/2012	Parker
D621,516	S	8/2010	Kiani et al.	8,337,403	B2	12/2012	Al-Ali et al.
7,791,155	B2	9/2010	Diab	8,346,330	B2	1/2013	Lamego
7,801,581	B2	9/2010	Diab	8,353,842	B2	1/2013	Al-Ali et al.
7,822,452	B2	10/2010	Schurman et al.	8,355,766	B2	1/2013	MacNeish, III et al.
RE41,912	E	11/2010	Parker	8,359,080	B2	1/2013	Diab et al.
7,844,313	B2	11/2010	Kiani et al.	8,364,223	B2	1/2013	Al-Ali et al.
7,844,314	B2	11/2010	Al-Ali	8,364,226	B2	1/2013	Diab et al.
7,844,315	B2	11/2010	Al-Ali	8,374,665	B2	2/2013	Lamego
7,865,222	B2	1/2011	Weber et al.	8,385,995	B2	2/2013	Al-Ali et al.
				8,385,996	B2	2/2013	Smith et al.
				8,388,353	B2	3/2013	Kiani et al.
				8,396,526	B2*	3/2013	Benni ..... 600/323
				8,399,822	B2	3/2013	Al-Ali

(56)

## References Cited

## U.S. PATENT DOCUMENTS

8,401,602	B2	3/2013	Kiani	
8,405,608	B2	3/2013	Al-Ali et al.	
8,414,499	B2	4/2013	Al-Ali et al.	
8,418,524	B2	4/2013	Al-Ali	
8,423,106	B2	4/2013	Lamego et al.	
8,428,674	B2*	4/2013	Duffy et al.	600/323
8,428,967	B2	4/2013	Olsen et al.	
8,430,817	B1	4/2013	Al-Ali et al.	
8,437,825	B2	5/2013	Dalvi et al.	
8,452,364	B2*	5/2013	Hannula et al.	600/322
8,455,290	B2	6/2013	Siskavich	
8,457,703	B2	6/2013	Al-Ali	
8,457,707	B2	6/2013	Kiani	
8,463,349	B2	6/2013	Diab et al.	
8,466,286	B2	6/2013	Bellott et al.	
8,471,713	B2	6/2013	Poeze et al.	
8,473,020	B2	6/2013	Kiani et al.	
8,483,787	B2	7/2013	Al-Ali et al.	
8,489,364	B2	7/2013	Weber et al.	
8,498,684	B2	7/2013	Weber et al.	
8,509,867	B2	8/2013	Workman et al.	
8,515,509	B2	8/2013	Bruinsma et al.	
8,523,781	B2	9/2013	Al-Ali	
8,529,301	B2	9/2013	Al-Ali et al.	
8,532,727	B2	9/2013	Ali et al.	
8,532,728	B2	9/2013	Diab et al.	
8,547,209	B2	10/2013	Kiani et al.	
8,548,548	B2	10/2013	Al-Ali	
8,548,550	B2	10/2013	Al-Ali et al.	
2002/0019588	A1	2/2002	Marro et al.	
2002/0029005	A1	3/2002	Levendowski et al.	
2002/0082513	A1	6/2002	Ennen et al.	
2002/0085174	A1	7/2002	Bolger et al.	
2002/0091335	A1*	7/2002	John et al.	600/544
2002/0123693	A1	9/2002	Lange et al.	
2002/0183634	A1	12/2002	Rantala et al.	
2002/0188216	A1	12/2002	Kayyali et al.	
2003/0069516	A1	4/2003	Becker et al.	
2003/0145854	A1	8/2003	Hickle	
2003/0158587	A1	8/2003	Esteller et al.	
2003/0204148	A1	10/2003	Lange et al.	
2003/0225323	A1*	12/2003	Kiani et al.	600/323
2004/0030258	A1*	2/2004	Williams et al.	600/544
2004/0073098	A1	4/2004	Geva et al.	
2004/0073129	A1	4/2004	Caldwell et al.	
2004/0082876	A1	4/2004	Viertio-Oja et al.	
2004/0167418	A1	8/2004	Nguyen et al.	
2004/0193068	A1	9/2004	Burton et al.	
2004/0243017	A1	12/2004	Causevic	
2004/0267153	A1	12/2004	Bergethon	
2005/0010116	A1	1/2005	Korhonen et al.	
2005/0059899	A1	3/2005	Merilainen et al.	
2005/0081847	A1	4/2005	Lee et al.	
2005/0090754	A1	4/2005	Wolff et al.	
2005/0113704	A1	5/2005	Lawson et al.	
2005/0119547	A1	6/2005	Shastri et al.	
2005/0217674	A1	10/2005	Burton et al.	
2005/0277819	A1*	12/2005	Kiani et al.	600/324
2006/0084852	A1*	4/2006	Mason et al.	600/344
2006/0100538	A1	5/2006	Genger et al.	
2006/0116556	A1	6/2006	Duhamel	
2006/0167368	A1	7/2006	Sarkela	
2006/0189861	A1	8/2006	Chen et al.	
2006/0217628	A1	9/2006	Huiku	
2006/0235315	A1	10/2006	Akselrod	
2006/0241356	A1	10/2006	Flaherty	
2006/0241562	A1	10/2006	John et al.	

2006/0293608	A1	12/2006	Rothman et al.	
2007/0010755	A1	1/2007	Sarkela et al.	
2007/0010756	A1	1/2007	Viertio-Oja	
2007/0010795	A1	1/2007	Sarkela et al.	
2007/0185407	A1	8/2007	Xu et al.	
2007/0208269	A1*	9/2007	Mumford et al.	600/546
2007/0244721	A1	10/2007	Sackner-Bernstein et al.	
2007/0249952	A1	10/2007	Rubin et al.	
2008/0017800	A1	1/2008	Benni	
2008/0221461	A1*	9/2008	Zhou et al.	600/485
2008/0234597	A1	9/2008	Becker et al.	
2008/0255469	A1	10/2008	Shieh et al.	
2008/0285029	A1	11/2008	Benni et al.	
2008/0294063	A1	11/2008	Bibian et al.	
2008/0300469	A1	12/2008	Kuo et al.	
2008/0300473	A1	12/2008	Benni	
2008/0300474	A1	12/2008	Benni et al.	
2009/0018427	A1	1/2009	Causevic et al.	
2009/0018429	A1	1/2009	Saliga et al.	
2009/0036799	A1	2/2009	Sandhu et al.	
2009/0088619	A1*	4/2009	Turner et al.	600/383
2009/0108205	A1	4/2009	Duffy et al.	
2009/0182209	A1	7/2009	Benni	
2009/0281403	A1	11/2009	Benni	
2010/0049018	A1*	2/2010	Duffy et al.	600/323
2010/0063438	A1*	3/2010	Bengtsson	604/66
2010/0130840	A1*	5/2010	Isaacson	600/323
2012/0088984	A1*	4/2012	Al-Ali et al.	600/301

## FOREIGN PATENT DOCUMENTS

EP	638193	2/1995
EP	1250886	10/2002
EP	1624798	11/2004
EP	1779257	5/2007
WO	WO 91/09372	6/1991
WO	WO 91/19453	12/1991
WO	WO 92/02176	2/1992
WO	WO 93/21615	10/1993
WO	WO 99/08589	2/1999
WO	WO 00/21432	4/2000
WO	WO 00/21435	4/2000
WO	WO 00/56211	9/2000
WO	WO 00/56212	9/2000
WO	WO 01/30414	5/2001
WO	WO 2004/028362	4/2004
WO	WO 2004/054441	7/2004
WO	WO 2007/059248	5/2007
WO	WO 2007/140535	12/2007
WO	WO 2007/140536	12/2007
WO	WO 2007/149553	12/2007
WO	WO 2008/015449	2/2008
WO	WO 2008/040846	4/2008
WO	WO 2008/043365	4/2008
WO	WO 2008/109694	9/2008
WO	WO 2008/109699	9/2008
WO	WO 2008/119029	10/2008
WO	WO 2008/119031	10/2008
WO	WO 2008/122082	10/2008
WO	WO 2008/138340	11/2008

## OTHER PUBLICATIONS

International Search Report for International Application No. PCT/US2011/053540, date of mailing: May 3, 2012, in 14 pages.  
International Preliminary Report on Patentability for International Application No. PCT/US2011/053540, date of mailing: Apr. 2, 2013, in 9 pages.

\* cited by examiner

FIG. 1A






FIG. 1B








FIG. 2B




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 3D




FIG. 3E




FIG. 3F




FIG. 3G




FIG. 3H




FIG. 31




FIG. 3J




FIG. 3K





FIG. 3L



**FIG. 3M**




FIG. 3N




FIG. 30




FIG. 4A






FIG. 4D





FIG. 4E



**FIG. 4F**




FIG. 4G




FIG. 4H




FIG. 41




FIG. 4J




FIG. 4K




FIG. 4L




FIG. 4M




FIG. 4N




FIG. 4O











FIG. 4P



**FIG. 5**

FIG. 6








FIG. 8B




FIG. 8C




FIG. 8D




FIG. 8A




FIG. 9B



FIG. 9A




FIG. 9D




FIG. 9E




FIG. 10D




FIG. 10A



FIG. 10B





FIG. 10C






FIG. 12B



FIG. 12C




FIG. 12D






FIG. 12A




**FIG. 13B**



**FIG. 13C**



**FIG. 13D**



**FIG. 13A**

920




FIG. 14

## DEPTH OF CONSCIOUSNESS MONITOR INCLUDING OXIMETER

### PRIORITY CLAIM

This application claims the benefit of priority under 35 U.S.C. §119(e) of the following U.S. Provisional Patent Application No. 61/387,457, titled "Depth of Consciousness Monitor Including Oximeter," filed on Sep. 28, 2010, and incorporates that application by reference herein in its entirety.

### REFERENCE TO RELATED APPLICATIONS

This application is related to U.S. Provisional Patent Application No. 61/387,426, titled "Magnetic Electrical Connector For Patient Monitors," filed on Sep. 28, 2010, and incorporates that application by reference herein in its entirety.

### FIELD OF THE DISCLOSURE

The present disclosure relates to the field of oximetry. More specifically, the disclosure relates to oximetry technologies for depth of consciousness monitoring.

### BACKGROUND OF THE DISCLOSURE

General anesthesia is often used to put patients to sleep and block pain and memory during medical or diagnostic procedures. While extremely useful to caregivers, general anesthesia is not risk free, and thus, caregivers seek to maintain a depth of consciousness consistent with the needs of a particular medical procedure. In short, there is a desire to avoid over and under dosing. However, as a patient's depth of consciousness may change from minute to minute, caregivers often employ a host of monitoring technologies to attempt to periodically, sporadically, or continually ascertain the wellness and consciousness of a patient. For example, caregivers may desire to monitor one or more of a patient's temperature, electroencephalogram or EEG, brain oxygen saturation, stimulus response, electromyography or EMG, respiration, body oxygen saturation or other blood analytes, pulse, hydration, blood pressure, perfusion, or other parameters or combinations of parameters. For many of the foregoing, monitoring technologies are individually readily available and widely used, such as, for example, pulse oximeters, vital signs monitors, and the like.

In their depth of consciousness monitoring, caregivers may also use recording devices to acquire EEG signals. For example, caregivers place electrodes on the skin of the forehead to detect electrical activity produced by the firing of neurons within the brain. From patterns in the electrical activity, caregivers attempt to determine, among other things, the state of consciousness of the brain. Caregivers may also use cerebral oximeters to determine the percentage of oxygenation of the hemoglobin in the cerebral cavity inside the skull. Cerebral oximetry is different from conventional pulse oximetry, which detects the oxygenation of blood in the body arteries. However, like pulse oximetry, caregivers place sensors on the body, in this case on the forehead, that emit radiation and detect the radiation after attenuation by body tissue. This attenuated signal includes information relating to the blood oxygenation of the brain. Directly measuring the blood oxygenation of the brain, or at least measuring physiological parameters indicative of the blood oxygenation of the brain, provides information about the state of brain function, such as, for example, brain oxygen consumption, not

available by measurement parameters that determine only the oxygenation of the blood feeding the brain or by monitoring the brain's electrical activity.

Today, there are several approaches to implementing a cerebral oximeter. One approach includes placing emitters on the forehead and spacing detectors on the forehead at different distances from the emitters. The emitters emit radiation at two or four different wavelengths and the detectors output signals representing the detected attenuated radiation. An instrument compares a DC signal from the different detectors and uses the difference as a basis for measurement. The underlying assumption appears to be that the closer detector provides an indication of oxygen saturation of the tissue outside the cerebral cavity, while the further detector provides an indication of the oxygen saturation of the tissue outside and inside the cerebral cavity. Subtraction of the two is hoped to provide an indication of just cerebral oxygenation. In any event, caregivers use a rising or falling trend in this difference to make deductions about the cerebral oxygen status in the patient. In some cases, instruments employing four wavelength systems also seek an output value of oxygenation, as opposed to just a trend of the difference signal. The foregoing approaches appear to be consistent with commercially available instruments from Somanetics Corporation of Troy, Mich. and CAS Medical Systems, Inc. of Branford Conn. A significant drawback to each of these approaches includes the cost of the instrumentation and sensors is often prohibitively high.

Another approach to a cerebral oximeter includes deep tissue imaging. For example, this type of research exposes high frequency light to the forehead and attempts to measure time of arrival and scattering/absorption coefficients. While primarily still in a research phase, it appears that the instrumentation could be less expensive than that disclosed above, perhaps even half the cost. However, even at that savings, this type of cerebral oximeter is still primarily in the research and development phase and still relatively costly. For example, the multiple optical benches provided in a single instrument generally associated with this type of design could cost more than three thousand dollars each.

Complicating the foregoing discussion is the realization that there is limited space on a patient's head for each of the different sensors. Particularly, where the forehead is the optimal measurement site in which to position EEG and brain oximetry sensors, drawbacks occur. For example, given the forehead's relatively small size, the forehead provides space for placement of a few sensors at the same time.

### SUMMARY OF THE DISCLOSURE

Based on at least the foregoing, the present disclosure seeks to overcome some or all of the drawbacks discussed above and provide additional advantages over any prior technologies. The present disclosure describes embodiments of noninvasive methods, devices, and systems for monitoring depth of consciousness through brain electrical activity and the oxygenation of the brain. Additional embodiments include monitoring of heartbeat, arterial oxygenation, venous oxygenation, temperature, and other physiological patient characteristics. For example, the present disclosure includes a combination forehead sensor having EEG and brain oximetry components. In an embodiment, the EEG components include electrical leads and the brain oximetry components include a plurality of light sources and detectors. Moreover, in an embodiment the forehead sensor includes a multisite forehead sensor configured to be positioned above the eyebrows of a patient with connecting devices and cables traveling over

the head and conveniently away from the body. Such positioning provides an ergonomic sensor along with increased safety from potential inadvertent interference by the patient or caregiver.

In an embodiment, a light source system of the sensor includes low cost optical benches having self contained internal emission detectors, light integrators or prisms, mirrors and the like. For example, in an embodiment, a light source includes a cap configured to reflect light toward a splitting mirror focusing light to both an internal emission detector for evaluation of the intensity of the emitted light and an aperture for directing the light into the patient's tissue. The light source may also include opaque or other surfaces or walls configured to appropriately direct emitted light.

Further embodiments may transform a commercially available pulse oximeter into a brain oximetry unit. For example, a processing device may advantageously connect to a sensor or other data input connection of a pulse oximeter to, for example, acquire power and open communication between the devices. In an embodiment, the sensor would include components for measuring the attenuation thereof. In an embodiment, the sensor would output a signal that represents the attenuated light. This signal would be similar to the output of a conventional pulse oximeter sensor in that both attempt to be indicative of light attenuation.

The signal could then be transmitted to the pulse oximeter for processing, conditioning and displaying of the brain oxygenation on a monitor of the pulse oximeter. A conventional pulse oximeter would be readily adaptable to process and display information from a brain oximeter sensor because the signals output by sensors of both devices are similar in nature (as both are output from photodiode light detectors detecting light attenuated by tissue). Modifications to the oximeter may advantageously include the algorithms used to analyze the signal from the sensors as cerebral oximeters may advantageously use different wavelengths, frequencies, and different comparing and analysis techniques to determine oxygenation. However, one of ordinary skill will recognize from the disclosure herein that algorithm changes often are much more straightforward and price competitive than significant hardware changes. This is especially the case when updating an already-installed base of monitors.

In another embodiment, a forehead sensor for monitoring the depth of consciousness of a patient is disclosed comprising a brain oxygenation sensor that includes at least one light source and two detectors, an eeg sensor that includes electrical leads that make contact with the skin of the patient's forehead, a reusable portion that houses the light source and detectors of the brain oxygenation sensor and a disposable portion that houses a plurality of EEG electrodes and is removably connectable to the reusable portion. The connector of the forehead sensor may also connect to the disposable portion and the reusable portion and house the majority of the circuitry and processing components for the EEG sensor and the brain oxygenation sensor. In embodiment, an interface between the connector and the disposable portion may allow the disposable portion to be removably attached to the connector. The light source or detector may also have a lip around their edge. In an embodiment, the reusable portion is directly connected to the disposable portion.

In an embodiment, a system for monitoring the depth of consciousness of a patient is disclosed comprising a forehead sensor that includes a brain oxygenation sensor and a conventional pulse oximeter loaded with software for displaying data related to the blood oxygenation level of the brain cavity data processed by the forehead sensor. In an embodiment, the conventional pulse oximeter may provide power to the sensor

and be capable of communicating data with the sensor or provide the drive signal and process the signal from the detector of the brain oxygenation sensor. The forehead sensor may also contain all of the components for processing the sign from detectors of the brain oxygenation sensor.

In another embodiment, a light source for a brain oxygenation sensor is disclosed comprising a substrate, emitters attached to the substrate for emitting light with at least two different wavelengths, a detector for detecting emitted light before it is attenuated by tissue, a cap connected to the substrate, and an aperture for the emitted light to exit the light source and enter the tissue site. The emitters may be LED's. In an embodiment a light diffusing material may be placed between the emitters and tissue site to scatter light. The light diffusing material may also be between the emitters and the detector and be made from a glass or epoxy that fills in around the emitters and detector. In an embodiment, the cap may be reflective or non-reflective. In another embodiment, a splitting mirror may direct light either to the detector or the aperture. In a further embodiment, a temperature sensor may be connected to the substrate.

For purposes of summarizing the disclosure, certain aspects, advantages and novel features of the disclosure have been described herein. Of course, it is to be understood that not necessarily all such aspects, advantages or features will be embodied in any particular embodiment of the disclosure.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The following drawings and the associated descriptions are provided to illustrate embodiments of the present disclosure and do not limit the scope of the claims.

FIG. 1A illustrates an embodiment of a forehead sensor communicating with a brain oximetry unit, which in turn communicates with a pulse oximeter now configured to monitor a state of consciousness through brain oxygenation.

FIG. 1B illustrates an embodiment of the forehead sensor of FIG. 1A including an ear pulse oximetry sensor.

FIG. 2A-2B illustrate block diagrams of embodiments of the brain oximetry unit of FIG. 1A.

FIGS. 3A-3O illustrate various embodiments of the forehead sensor of FIG. 1A.

FIGS. 3A, 3N, and 3O illustrate embodiments of the forehead a sensor including reusable and disposable portions mated together.

FIGS. 3B-3C illustrate embodiments of the reusable portion including various cerebral oximetry sensor components.

FIGS. 3D-3M illustrate embodiments of the disposable portion including EEG, temperature and other parameter measuring components.

FIGS. 4A-4O illustrate various embodiments and views of light sources of the forehead sensor of FIG. 1A.

FIG. 4A-D illustrate perspective and side views of a light source of the cerebral oximeter according to embodiments of the present disclosure.

FIG. 4E illustrates a perspective view of the light source including light paths of a multi-faceted directing mirror according to an embodiment of the present disclosure.

FIG. 4F-G illustrate more perspective views of the light source.

FIG. 4H illustrates a further perspective view of the light source without a cap according to an embodiment of the present disclosure.

FIG. 4I illustrates a bottom view of the light source towards the top reflective covering according to an embodiment of the present disclosure.

FIG. 4J illustrates a perspective view of the light source with the reflective cover being composed of many portions according to an embodiment of the present disclosure.

FIGS. 4K-4M illustrate side views of the light source including a semi-reflectant mirror according to an embodiment of the present disclosure.

FIG. 4N illustrates a side view of the light source including a light diffusing material filling inside a cap according to an embodiment of the present disclosure.

FIG. 4O illustrates a side view of the light source with an angled substrate according to an embodiment of the present disclosure.

FIG. 4P illustrates a side view of the light source with a relatively flat cap.

FIG. 5 illustrates an exemplary graph showing the calibrated relationship of the emission detector output to the calibrated intensity of the emitter output according to an embodiment of the present disclosure.

FIG. 6 illustrates an embodiment of a forehead sensor communicating with a brain oximetry unit contained inside a connector, which in turn communicates with a pulse oximeter configured to monitor and/or display a state of consciousness through brain oxygenation.

FIGS. 7A-7E illustrate various embodiments and views of the forehead sensor of FIG. 6.

FIG. 7A illustrates a perspective view of the sensor and connector with the disposable portion of the forehead sensor detached from the connector.

FIG. 7B illustrates a top view of the forehead sensor with the disposable and reusable portion of the sensor connected.

FIG. 7C illustrates a side view of the forehead sensor with both the disposable and reusable portion of the sensor connected.

FIG. 7D illustrates a front view of the forehead sensor with both the disposable and reusable portion of the sensor connected.

FIG. 7E illustrates a bottom view of the forehead sensor with the disposable and reusable portion connected.

FIGS. 8A-8D illustrate various embodiments and views of the forehead sensor that include an EEG sensor.

FIG. 8A illustrates a perspective view of the sensor and connector with the disposable portion of the forehead sensor detached from the connector.

FIG. 8B illustrates a top view of the forehead sensor with the disposable and reusable portion of the sensor connected.

FIG. 8C illustrates a side view of the forehead sensor with both the disposable and reusable portion of the sensor connected.

FIG. 8D illustrates a bottom view of the forehead sensor with the disposable and reusable portion connected.

FIGS. 9A-9E illustrate various embodiments and views of the reusable portion of the forehead sensor.

FIG. 9A illustrates a perspective view of the reusable portion and connector of the forehead sensor with the reusable portion detached from the connector.

FIG. 9B illustrates a top view of the reusable portion of the forehead sensor.

FIG. 9C illustrates a side view reusable portion of the forehead sensor.

FIG. 9D illustrates a front view of the reusable portion of the forehead sensor.

FIG. 9E illustrates a bottom view of the reusable portion of the forehead sensor.

FIGS. 10A-10D illustrate various embodiments and views of the reusable portion of the forehead sensor.

FIG. 10A illustrates a top view of the reusable portion of the forehead sensor.

FIG. 10B illustrates a side view reusable portion of the forehead sensor.

FIG. 10C illustrates a bottom view of the reusable portion of the forehead sensor.

FIG. 10D illustrates an exploded perspective view showing an embodiment of the various layers of the reusable portion of the forehead sensor.

FIGS. 11A-11E illustrate various embodiments and views of the connector of the forehead sensor.

FIG. 11A illustrates an exploded perspective view of the various components of the connector.

FIG. 11B illustrates a top view of the connector.

FIG. 11C illustrates a front view of the connector.

FIG. 11D illustrates a side view of the connector.

FIG. 11E illustrates a bottom view of the connector.

FIGS. 12A-12D illustrate various embodiments and views of the disposable portion of the forehead sensor.

FIG. 12A illustrates a perspective view of the disposable portion of the forehead sensor with a detached adhesive layer.

FIG. 12B illustrates a top view of the disposable portion of the forehead sensor.

FIG. 12C illustrates a side view of the disposable portion of the forehead sensor.

FIG. 12D illustrates a bottom view of the disposable portion of the forehead sensor that includes an attached adhesive layer.

FIGS. 13A-13D illustrate various embodiments and views of the disposable portion of the forehead sensor that include an EEG sensor.

FIG. 13A illustrates an exploded perspective view of the disposable portion of the forehead sensor with a detached adhesive layer.

FIG. 13B illustrates a top view of the disposable portion of the forehead sensor.

FIG. 13C illustrates a side view of the disposable portion of the forehead sensor.

FIG. 13D illustrates a bottom view of the disposable portion of the forehead sensor that includes an attached adhesive layer.

FIG. 14 illustrates an embodiment of an exemplary display showing potential brain oximetry parameters that could be displayed in an embodiment of the brain oximetry sensor.

#### DETAILED DESCRIPTION

The present disclosure generally relates to patient monitoring devices. In order to provide a complete and accurate assessment of the state of a patient's various physiological systems, in an embodiment, a sensor may advantageously monitor one, multiple or combinations of EEG, cerebral oximetry, temperature, pulse oximetry, and other physiological parameters. In various embodiments, the sensor includes a disposable portion and reusable portion. For example, the disposable portion may advantageously include components near a measurement site surface (the patient's skin), including, for example, an EEG, a temperature sensor, tape, adhesive elements, positioning elements, or the like. On the other hand, the reusable portion may advantageously include more expensive or other components, circuitry or electronics, which, in some embodiments include for example time-of-use restrictions for quality control or the like. The reusable portion, can be used multiple times for a single patient, across different patients, or the like, often depending upon the effectiveness of sterilization procedures. The reusable components may include, for example, cerebral oximetry components, pulse oximetry components and other components to measure other various parameters.

In an embodiment, the disposable portion of the sensor may include an inductance connection or other electrical connection to the reusable portion of the sensor, and the signal from both sensors could thereby be transmitted through a common cable to a brain oximetry unit. In an embodiment, the brain oximetry unit may include an analog to digital converter, various electrical filters, and a microcontroller for processing and controlling the various sensor components.

In an embodiment, a brain oximetry unit or additional signal processing unit could communicate with the forehead sensor disclosed herein and one or more host display and patient monitoring stations. In an embodiment, the patient monitoring station may be a pulse oximeter. In an embodiment, the pulse oximeter may perform integrated display, data monitoring and processing of patient parameters including a connection for power and data communication. In an embodiment, some or all communication may be through wired, wireless, or other electrical connections. In an embodiment, the brain oximetry unit may advantageously be housed in a portable housing. In such embodiments, the unit may advantageously be physically associated with a monitored patient, such as, for example, attached in an arm band, a patient bed pouch, a hood or hat, a pocket of a shirt, gown, or other clothing, or the like. In other embodiments, the unit may be entirely or partially housed in a cable connector. In an embodiment, the signal processing and condition unit could also monitor patient parameters through other sensors including, for example, ECG, SpO<sub>2</sub> from the earlobe, finger, forehead or other locations, blood pressure, respiration through acoustic or other monitoring technologies, or other clinically relevant physiological parameters.

In an embodiment, the pulse oximeter communicates with a sensor, such as a forehead sensor including one or more light sources configured to emit light at a patient's forehead. In an embodiment, the light source may include one or more emitters or emitter systems, such emitters or emitter systems may be embedded into a substrate. In various embodiments, the emitters could be either light emitting diodes ("LEDs"), lasers, superluminescent LEDs or some other light emitting components. These components could be arranged in any pattern on the substrate and could be either a single light emitting source or several light emitting sources. In an embodiment, the emitting components could emit light that reflects off of reflective surfaces associated with a cap of the substrate. The reflective cover could be any number of shapes or sizes and could be constructed to direct light to specific points or a point on the cap or substrate.

In an embodiment, a multi-faceted splitting mirror could reflect light to an opening in the substrate that would allow the light to escape and be emitted to an emission detector in an embodiment also housed in the light source substrate. The emission detector may advantageously sample the light providing feedback usable to create an optical bench or at least optical bench properties of the light source, including, for example, determinations of intensity, wavelength, or the like. In an embodiment, the light source may include a polarized filter for adjusting the emitter light, in some embodiments before exiting an opening in the emitter or being detected by the emission detector.

In an embodiment, a caregiver could analyze physiological information collected from the various sensors including a patient's temperature, EEG, brain oxygen saturation, stimulus response, electromyography or EMG, respiration monitor using acoustic sensor applied to the through, body oxygen saturation, glucose concentration, or other blood analytes, pulse, hydration, blood pressure, perfusion, or other parameters or combinations of parameters to determine relevant

information about the state of a patient's well being. In another embodiment, a caregiver may advantageously analyze information collected from the various sensors to more completely assess the overall depth of a patient's sedation and obtain an assessment superior to an assessment derived from monitoring a single or a few of the parameters mentioned above.

Reference will now be made to the Figures to discuss embodiments of the present disclosure.

FIG. 1A and 1B illustrate examples of a patient monitoring system **100**. In certain embodiments, the patient monitoring system **100** measures several physiological parameters including cerebral electrical activity, temperature, cerebral oxygenation, including venous and arterial oxygenation, arterial oxygenation at various other points on the body, various other blood analytes including total hemoglobin, glucose, lipids, stimulus response, electromyography or EMG, respiration, pulse, hydration, blood pressure, perfusion, or other parameters or combination of other physiologically relevant patient characteristics. The information from these physiological parameters can be evaluated using trend analysis, absolute and relative measures of certain parameters, combined or alone to evaluate the total wellness and current state of a patient at any point in time.

The patient monitoring system can include multiple or a single sensor **120**, a brain oximetry unit **140**, and a pulse oximeter **150**. The sensor **120** can be any variety of shapes and sizes, and could be applied to a variety of measurement sites on a patient's skin including any location on the forehead and temples or other location of the head. Also, electrodes designed to be placed at a measurement site covered with a patient's hair may advantageously be implemented in order to apply the sensor to any part of a patient's head that is covered with hair. A caregiver or patient may fasten the sensor to the patient's head with a variety of mechanism including adhesive, straps, caps, combinations of the same, or other devices for fastening sensors to a patient's body or skin known in the art.

In an embodiment, the patient monitoring system **100** advantageously utilizes wireless communication to provide a portable unit to accommodate an ambulatory patient, or other patient in transit. For example, in one embodiment, the brain oximetry unit **140** may be attached to an arm band or included in an arm band or other device that is wearable by the patient, including in a cap, a hood, a sling or a pocket of a garment. In an embodiment, the sensor would communicate with the arm band brain oximetry unit **140** with a hard wired connection or a wireless connection for convenience and flexibility of the patient obtained by eliminating excess wires.

In an embodiment, the portable brain oximetry unit **140**, such as an armband brain oximetry unit **140**, could also communicate wirelessly with the pulse oximeter **150**. This would allow the brain oximetry unit **140** to be transported between various caregiving facilities, each with their own stationary pulse oximeters **150** without unhooking and reinserting hard-wired electrical connections. Instead, a brain oximetry unit **140** could establish a wireless communication link with a stationary pulse oximeter **150** as the brain oximetry unit **140** is brought into proximity of the pulse oximeter **150**. In an embodiment, the devices could establish the connection automatically and patient data may be automatically sent from the brain oximetry unit **140** to the pulse oximeter **150** or the connection may require input from a caregiver in the user interface of either of the devices. This will advantageously facilitate portability and seamless monitoring of a patient while being transported, for example, from an ambulance to a hospital room or from room to room in a hospital.

In an embodiment, the pulse oximeter **150** may be a multi-parameter patient monitoring station or other host device capable of monitoring a wide variety of vital signs and blood constituents and other parameters or combinations of parameters such as those monitors commercially available from Masimo Corporation of Irvine, Calif., and disclosed herein with reference to U.S. Pat. Nos. 6,584,336, 6,661,161, 6,850,788, and 7,415,297, among others assigned to Masimo Corporation, and U.S. Patent Publication No. 2006/0211924, 2010/0030040, among others assigned to Masimo Corporation or Masimo Laboratories, Inc. of Irvine Calif.

FIG. 1B illustrates an embodiment of the patient monitoring system **100** with a pulse oximeter **150** attached to a sensor **120** or through some physical electrical conduction connection, wireless, or other suitable electrical connection to the pulse oximeter **150**. This will advantageously provide additional information about the state of the arterial oxygenation of the blood being transported to the head. In an embodiment, the pulse oximeter **150** branches off the wiring from the sensor **120**.

In an embodiment, a caregiver or the patient may attach the brain oximetry unit **140** directly to the patient's arm or other part or clothing of the patient through an armband with straps or some other means known in the art to connect a portable monitoring unit to a patient. In an embodiment, a brain oximetry unit **140** may be integrated into a hat or other headgear wearable by the patient or some other structure near the patient. In an embodiment, brain oximetry unit **140** can rest on a table or other surface near the patient.

In some embodiments, a brain oximetry unit **140** can be integrated with the pulse oximeter **150**. Alternatively, the brain oximetry unit **140** could be a module that is docked or somehow associated with a multi-parameter patient monitoring station.

FIG. 2A and 2B show block diagrams of various embodiments of the brain oximetry unit **140**, sensors **120**, and pulse oximeter **150**. In an embodiment, the brain oximetry unit **140** may utilize a processor **220** which may be a micro-controller or other processor, which may control or coordinate some or all of the functions of the various emitters **230** and detectors **260** and other sensors **120** and in an embodiment, may coordinate, process or condition, or manipulate the electronic data in some other manner, before communicating the data to the pulse oximeter **150**. Also, the processor **220** may receive instructions or data control messages from the pulse oximeter **150** to provide the appropriate conditioning and controlling of the various front end components of the various sensors **120** associated the pulse oximeter **150**. In an embodiment, data transmitted between the brain oximetry unit **140**, the pulse oximeter **150**, the sensors **120** and any other associated components of a patient monitoring system **100** may be communicated by the devices using electrical wires, wireless communication, optical communication, RFID, LAN networks, or other electronic devices for communicating data known in the art.

The brain oximetry unit **140** may also include various front end components for the various sensors **120** that may be associated with the brain oximetry unit **140**. In an embodiment, front end components may translate and transmit instructions and control signals for driving the various sensors. In an embodiment, the front end components may translate, process, or transmit instructions and control signals to the emitting or light producing components of the sensor. The front end components may also receive and transmit data acquired by the detectors of the sensors to the microcontroller **220** or other processor **220**.

These front end components could include front end components for a variety of sensors **120** including for sensors that detect blood oxygenation, EEG, ECG, temperature, acoustic respiration monitoring ("ARM") sensors, such as those available from Masimo Corporation of Irvine, Calif., acoustic throat respiratory sensor, and brain oxygenation. In an embodiment, a caregiver could advantageously utilize a device with the ability to monitor the plurality of above mentioned parameters to more accurately determine a depth of a patient's sedation. In an embodiment, a front end component that would be associated with a sensor **120** that detects brain oxygenation may have a sub component dedicated to driving emitters **230** associated with a light source of the brain oxygenation sensor and a sub-component associated with the detector **230** or detectors **230** of the brain oxygenation sensor **300** for receiving and transmitting the detected signals that pass through various body tissues.

In an embodiment, one of the various sensors associated with the front end components of the brain oximetry unit could be, for example, a blood oxygenation sensor **310** which may be placed at various measurement sites on a patient's skin, including the earlobe, finger, forehead or other places known in the art suitable for detecting blood oxygenation. Many suitable pulse oximeter sensors **310** are known in the art such as those blood oxygenation sensors **310** commercially available from Masimo Corporation of Irvine, Calif., and disclosed herein with reference to U.S. Pat. Nos. 5,638,818, 6,285,896, 6,377,829, 6,580,086, 6,985,764, 7,341,559, or others.

In an embodiment, another sensor **120** that may be associated with a front end component of the brain oximetry unit **140** could be a temperature sensor **320**. The temperature sensor **320** could detect the temperature of the skin, the temperature inside the ear, the temperature under the tongue, or any other temperature measurement method known in the art. In an embodiment, the temperature sensor **320** could be any suitable thermistor, or any other temperature sensor **320** known in the art capable of detecting a surface temperature of a patient's skin. Additional temperature sensor may advantageously provide feedback to the unit **140** regarding the performance or temperature of one, combinations of, or all of the emitters **230**.

An EEG sensor **330** may also be associated with the front end components of the cerebral oximeter **140**. In an embodiment, the EEG sensor **330** may be any of a variety of EEG sensors **330** known in the art. An EEG sensor **330** could be applied to a patient at any of a multitude of locations and measurement sites on the skin of the head of a patient. In an embodiment, the EEG sensor **330** may include electrode leads that may be placed on a measurement site in contact with the skin of the patient. In an embodiment, the EEG **330** may monitor the electrical activity of a patient's brain through any number of electrodes, electrode leads, and channels or other systems known in the art.

In an embodiment, the EEG sensor **330** may monitor and collect data from a patient's brain using 4 channels and 6 electrodes. In another embodiment, the EEG **330** may use 3 channels and 5 electrodes. In another embodiment, any variety or combination of sensors may be used that are suitable for obtaining an EEG signal, for example, such a system is disclosed in U.S. Pat. Nos. 6,016,4444, 6,654,626, 6,128,521, or the like.

A brain oxygenation sensor **300** may also be associated with the front end components of the brain oximetry unit **140**. In an embodiment, the brain oxygenation sensor **300** includes a light source **230**, and a detector **260**. The light source **230** of the brain oxygenation sensor **300** includes emitter(s) that

would emit light, sonic or other radiation into the forehead at one, two or other plurality of measurement sites located on the skin of the patient at a plurality of predetermined wavelengths. In an embodiment, the brain oxygenation sensor **300** would include a detector **260** with photodiodes or other radiation detection devices to detect the radiation emitting from the patient at a one or two or a plurality of measurement sites on the skin of the head of a patient. Many suitable brain oxygenation sensors **300** and cerebral oximeters are known in the art including those disclosed in U.S. Pat. Nos. 7,072,701, 7,047,054, or similar sensors.

In an embodiment, the light source **230** of the brain oxygenation sensor **300** may include an emission detector **260**. In an embodiment, the emission detector **260** would detect the light emitted from the light source **230** before passing through or contacting the measurement site of the patient. In an embodiment, an output from the emission detector **230** would be communicated to the micro-controller **220** in the brain oximetry unit **140**, the processing unit in the cerebral oximeter **140** or, some other processing component associated with the patient monitoring system **100** in order to calculate an approximate output intensity of the light emitted by the emitter(s) **230**. The micro-controller **220** or other processor **220** could calculate the output intensity based on the output of the emission detector **260** by comparing the data to calibration data. In an embodiment, the calibration data could include measurement of intensity of light emitted from the emitter(s) **230** and corresponding measurements of output from the emission detector **260**. This data could then be correlated to real time output from the emission detector **260** while the oxygenation sensor **230** is in use to determine an actual or approximate intensity of light or radiation being emitted by the emitter(s) **230** utilizing a calibration curve or other suitable calculation or processing method. In an embodiment, the calibration data may be stored in an EPROM or other memory module in the brain oximetry unit **140**, the pulse oximeter **150**, or other patient processing module associated with the patient monitoring system **100**.

In an embodiment, the detector **260** will detect light or other radiation emitted from the light source **230** after, in an embodiment, some of the light has entered the measurement site on the patient and has been attenuated by a patient's tissue. In an embodiment, the detector **260** could be any number of detectors known in the art for detecting light or other radiation including photodiodes or other types of light or radiation detectors. In one embodiment, the detector **260** may convert detected light or other radiation into a signal, for example, an electrical output signal, which may represent the intensity or other attributes of the radiation. In an embodiment, the signal from the detector **260** may be sent to a brain oxygenation detector **260** front end located in the brain oximetry unit **140** for processing, conditioning or transmitting to the pulse oximeter **150** or other patient monitoring processor. In one embodiment, the signal may be converted into a digital format by an analog to digital converted located in either the brain oximetry unit **140** or the pulse oximeter **150**. In an embodiment, the data from the detector **260** of the brain oxygenation sensor **300** may be processed to determine the cerebral oxygenation of a patient's brain tissue. In an embodiment, the processing of the data may include determining the changes of intensity between various wavelengths of emitted and detected light of the cerebral oxygenation sensor **300**.

In an embodiment, the cerebral oximeter **150** or multi-parameter patient monitor acquires data from the brain oximetry unit **140** or sensor **120** derived from physiologically relevant parameters. In an embodiment, the pulse oximeter **150** could give visual quantitative or qualitative assessments

of the patient's well being based on one or more of the various parameters or physiological attributes measured.

In an embodiment, a caregiver may utilize various physiological parameters to make a quantitative assessment of the patient's depth of sedation as indicated by an index based on for example, a patient's temperature, electroencephalogram or EEG, brain oxygen saturation, stimulus response, electromyography or EMG, respiration based on acoustic through sensors, body oxygen saturation or other blood analytes, pulse, hydration, blood pressure, perfusion, or other parameters or combinations of parameters. In another embodiment, various aspects of sedation could be assessed quantitatively or qualitatively based on a visual representation of the patient's sedation in the aspects including hypnosis, responsiveness, muscle relaxation or other clinically relevant facets of depth of anesthesia.

In an embodiment, the pulse oximeter **150** may supply power to brain oximetry unit **140** over a single line and data would be transferred back and forth between the brain oximetry unit **140** and pulse oximeter **150** over a separate line or lines. In another embodiment, both power and data could be transmitted over the same line or the same wire with multiple lines in the wire. In another embodiment, data and power could be transmitted wirelessly or through an inductance connection between the patient monitoring station and the signal processing unit or any other suitable connections or transmission techniques known in the art. Induction or magnetic connections are also disclosed in U.S. patent application Ser. No. 13/246,768, titled "Magnetic Electrical Connector for Patient Monitors," filed herewith on Sep. 27, 2011.

In an embodiment, the functionality of the brain oximetry unit **140** could be optionally controlled by the pulse oximeter **150**. In an embodiment, the data and qualitative and quantitative assessments of a patient's wellness being could be displayed on either or both the brain oximetry unit **140** and pulse oximeter **150**. Also, audible alarms and other indicators could be displayed on either or both the brain oximetry unit **140** and pulse oximeter **150** in response to various threshold breaches based on the assessment of the patient's wellness determined from the various monitored parameters.

FIGS. 3A-3F illustrate several embodiments of the sensor **120**. FIG. 3A shows an embodiment of the sensor **120** wherein disposable **410** and reusable portions **420** of the sensor **120** are connected and overlaid on top of one another. FIG. 3A shows six EEG electrodes **440** with two reference electrodes and four active channel electrodes. FIG. 3A also shows the light source **230** and detector **260** components of the brain oxygenation sensor **300**. Any number of suitable light sources **230** and detectors **260** may be incorporated into the forehead sensor **120**. All or some of the above mentioned sensor components including the EEG leads **440** and the brain oxygenation emitter **230** and detector **260** components may be linked to a single chip for transmission of acquired signals and drive signals or each component may be linked to its own individual chip through wires, or printed circuits, or other suitable electrical connections.

In one embodiment, the light source **230** may include one or more emitters. In one embodiment, the emitter could be a laser, or any suitable apparatus for emitting near-infrared or other spectrum of light including LEDS, super luminescent LEDs, or some other light emitting components. In one embodiment, the light source **230** may be incorporated with the brain oximetry unit **140** and the light or other radiation could be emitted from the light source **230** onto a fiber optic cable which would transmit the light from the light source **230** to the measurement site. In another embodiment, the emitter (s), including, for example, a laser or LED emitter(s), is

embedded in the emitter **230** directly in the forehead sensor. Other fiber optics may be used after emission of the light from the light source to equalize the intensity and distribution of the radiation over a cross sectional area of a beam of emitted light after it exits the emitter and before it enters the measurement site of the patient.

The detector **260** of the brain oxygenation sensor **300** may be any suitable device for detecting radiation including any combination of various photodiodes including InGas and Si photodiodes. In an embodiment, the detector **260** is a photodiode connected directly to the forehead sensor **120**. In another embodiment, the forehead sensor **120** collects light that has passed through patient tissue with a fiber optic cable or other similar apparatus that is positioned at an appropriate measurement site, for example on the patient's forehead. In an embodiment, the fiber optic cable could then transmit the collected light to the detector **260** of the brain oxygenation sensor **300**.

The EEG electrodes **440** may be any suitable electrodes for detecting the electro-potentials on the surface of the skin of a patient's head. In one embodiment, EEG electrodes **440** comprise a metal or other suitable conductor and utilize leads contacting the surface of the skin. In another embodiment, the electrodes **440** are gelled electrodes that make contact through the skin via gel and have metal leads that come into contact with the gel. In still yet another embodiment, the EEG electrodes **440** may be glued to the forehead with any suitable patient dermal adhesive for connecting the EEG electrodes **440** and may have electrical conductivity. In an embodiment, potentials from the EEG electrodes **440** are transmitted to the brain oximetry unit **140** for further conditioning, transmitting or processing.

FIGS. 3B and 3C show embodiments of a reusable portion **420** of the sensor **120**. In an embodiment, the reusable portion **420** includes the potentially more expensive components, including, for example, the sensor light source(s) **230** and detector(s) **260**. The reusable portion **420** may also include the temperature sensor **320**. The temperature sensor **320** may be any suitable sensor that can detect the temperature of the surface of the skin or other patient temperatures. In an embodiment, the temperature sensor **320** may include a thermistor associated with the reusable portion **420** of the sensor **120**.

In an embodiment, the reusable portion **420** includes an interface **510** that couples the reusable portion **420** of the sensor to the brain oximetry unit **140**. The interface **510** may be any suitable electrical or data connection or communication port or device including, for example, a pin connector and receiver. Various other communication or electrical connections known in the art may be utilized. In an embodiment, the interface **510** is an inductance connection utilizing transformers to couple a data and electrical connection across an insulator. In another embodiment, the interface **510** provides a data or electronic coupling between the reusable portion **420** and the disposable portion **410** of the sensor.

FIGS. 3D-3O illustrate various embodiments of a disposable portion **410** of a forehead sensor **120** that, in an embodiment, attaches to a measurement site of a patient's head and provides a base **520** to which the reusable portion **420** may be docked, mated or connected. FIGS. 3D-3E illustrate an embodiment of a single chip disposable portion **410** of the sensor **120**. The disposable portion **410** houses the components of the sensor **120** that may be less expensive than at least some of the components contained in the reusable portion **420** of the sensor **120** and therefore may be disposed after a single or multiple uses, either on the same patient or different patients. The disposable portion **410** of the sensor **120**

includes a tape substrate **530** that provides a base or substrate to which at least some of the components of the disposable portion **410** may adhere or be integrated. In an embodiment, the tape **530** can be constructed from any suitable disposable material that will effectively hold the components included in the disposable portion **410** to a patient's forehead or other measurement site. In an embodiment, the tape **530** includes a suitable dermal adhesive on a patient side of the disposable portion **410** for temporary adhesion of the sensor **120** to a patient's skin.

In an embodiment, the disposable portion **410** of the sensor **120** may incorporate various disposable components which may include, EEG electrodes **440**. In one embodiment, the EEG electrodes **440** may be fastened to the tape **530** of the disposable portion **410**. In an embodiment, the EEG electrodes **440** could be embedded in the tape **530** by any known adhesive in the sensor arts or any other suitable means for connecting the EEG electrodes **440** that would allow the EEG electrode **440** leads to be exposed on a patient side of tape **530** in an appropriate position to come in close proximity to a measurement site of a patient's skin. In an embodiment, EEG electrodes **440** may be gelled so that the gel contacts the electrodes and a measurement site of a patient's skin to provide an electrical path between the measurement site of the patient's skin and the EEG electrodes **440**. In an embodiment, the leads of the EEG electrodes **440** are connected to a single chip by wires or other suitable electrical connections, such as a printed circuit.

FIGS. 3H, 3I, and 3M, illustrate a temperature sensor **320** associated with the tape of the disposable portion **410** of the sensor **120**. In an embodiment, the temperature sensor **320** is a thermistor with the thermistor leads exposed on a patient contacting side of the tape **530**, in order to facilitate the contacting of the leads of temperature sensor **320** to a measurement site of a patient's skin. In an embodiment, the temperature sensor **320** is connected to single chip through wires or other suitable electrical connections such as a flexible printed circuit. In an embodiment, the temperature sensor **320** may be located anywhere on the tape **530**, the disposable portion **410**, or the reusable portion **420** of the sensor. In an embodiment, the leads for the temperature sensor **320** may be near the center of tape **530** or anywhere on the periphery of tape **530**.

In an embodiment, the disposable portion **410** of sensor **120** may mate and connect to or overlay the reusable portion **420** of the sensor **120**. In an embodiment, the non-patient side of the tape **530** could mate or connect to the reusable portion **420** of the sensor **120** through some suitable adhesive on the tape **530** or some physical connection or mating means. In an embodiment, the disposable portion **410** of the sensor **120** may also contain one or several sensory compartments **540**. The sensory compartments **540** may contain a transparent window or a space for the light source **230** or the detectors **260** of the reusable portion **420** of the sensor **120** to emit and detect emitted light through the space or transparent window.

In one embodiment, the light source(s) **230** and detector(s) **260** of the reusable portion **420** may align with the sensory compartments **540** while the reusable **420** and disposable **410** portions physically connect at places other than the sensory compartments **540** and light sources **230** and detectors **260**. In an embodiment, the light sources **230** and detectors **260** of the reusable portion **420** of the sensor **120** may physically snap into or somehow removably mate with the sensory compartments **540** of the disposable portion **410** of the sensor **120**. In one embodiment, the windows of the sensory compartments **540** may contain certain filters to optimize the wavelengths

intensity, or other characteristics of the light that passes through the windows in the sensory compartments 540.

In still other embodiments, care may be taken to ensure sterilization of the reusable components is more straightforward, such as, for example, implementing suitable electrical connections through magnetic, optical or other coupling mechanisms that can be mostly or entirely housed in separate housings that are easily sterilized and mostly void of cavities or the like that can trap contamination.

FIGS. 3A, and 3N show an embodiment with the disposable portion 410 of the sensor electrically connected directly to the reusable portion 420 of the sensor 120 through an interface 510. In an embodiment, the interface 510 may be any suitable electrical connection such as a pin connector, a snap in lead connector, an optical connection or an inductance connection.

FIGS. 3H and 3N show an embodiment of the sensor 120 with a pulse oximeter sensor 310 associated with the sensor 120. The pulse oximeter sensor 310 shown in FIGS. 3H and 3N is an ear pulse oximeter sensor 310 that emits and detects radiation to determine the oxygenation of the blood travelling through the arteries of the ear. Many suitable ear pulse oximeter sensors 310 are known in the art such as those sensors commercially available from Masimo Corporation and disclosed herein with reference to U.S. Pat. No. 7,341,599. In another embodiment, the pulse oximeter sensor 310 may be a forehead pulse oximeter sensor 310 or any other suitable pulse oximeter known in the art or disclosed herein. The pulse oximeter sensor 310 may be connected to the sensor through electrical wires, wirelessly or other suitable electrical or data connection. Data collected from the pulse oximeter sensor 310 may be transmitted to the brain oximetry unit 140 or pulse oximeter 150 or both for conditioning, or processing.

FIG. 3G illustrates a multi chip embodiment of the disposable portion 410 of the sensor. In an embodiment, the various EEG electrodes 440 each connect to a separate chip that transmits the detected signal to the interface 510. In an embodiment, the chip transmits the signal to various inductors integrated into interface 510 which transmit the signal to inductors integrated into the reusable portion of the interface 510.

FIGS. 3A, and 3N-3O show the reusable portion 420 of the sensor 120 associated with or physically mated with the disposable portion 410 of the sensor 120. In an embodiment, the reusable 420 and disposable portions 410 of the sensor 120 physically mate at mating sections on the disposable 410 and reusable 420 portions. In one embodiment, the mating sections are located near the light source 230 and detectors 260 on the reusable portion 420 and the sensory compartments 540 on the disposable portion 410. In an embodiment, the mating sections have rims 550 into which cerebral oximeter 300 emitters 230 and detectors 260 may be placed, snapped into or mated. Rims 550 may be any suitable plastic or other flexible material, including metal that would allow the emitter 230 and detector 260 to press or squeeze fit into place. This would allow the rims to physically hold the emitters 230 and detectors 260 in the proper orientation.

FIGS. 4A-4O illustrate various embodiments of a light source 230 that may be utilized in a cerebral oximeter sensor 300. FIG. 4A shows an embodiment of the light source 230 which includes a substrate 610, guide walls 620, a dividing wall(s) 630, a cap 640, reflective portions 650 on the cap, a splitting mirror 660, and an aperture 670. In an embodiment, the light source 230 includes a substrate 610 to provide a base to associate or attach the remaining components. In an embodiment, the light source 230 includes at least one or a

plurality of emitters 680, guide walls 620 attached to the substrate 610, and a dividing wall 630 rising from the substrate 610.

FIG. 4B shows a perspective view of the light source 230 substrate 610 without the cap 640 and one of the guide walls 620, a dividing wall 630, four emitters 680, an emission detector 260 and an aperture 670. In an embodiment, the dividing wall 630 prevents light emitted from the emitters 680 from directly contacting the emission detector 260 or directly exiting through the aperture 670. In an embodiment, the aperture 670 and emission detector 260 may be located anywhere on the side of the dividing wall 630 opposite the side associated with the emitters 680. In one embodiment, the detector 260 is close to the dividing wall 630 and the aperture 670 is spaced further from the dividing wall 630 than emission detector 260. The aperture 670 can be any suitable opening, slot, space, or gap in the substrate 610 of the light source 230, in order to allow at least some of the light reflected from the cap 640 or guide walls 620 to pass through the substrate 610 and exit the light source 230. In an embodiment, the aperture 670 may be a transparent section filled with material that may have optical properties, including a filter or the like.

FIGS. 4C and 4E illustrate an embodiment of the light source 230 with the substrate 610, emitters 680, cap 640, the splitting mirror 660, the dividing wall 630, the emission detector 260, the aperture 670 and the polarizer 690 in light path of the light exiting aperture 670. FIGS. 4C and 4E illustrate an example of one possible embodiment of the variety of potential light paths taken by light emitted from the emitters 680. First, the light is emitted from the emitters 680 and subsequently may be reflected or deflected by the cap 640 towards the splitting mirror 660. Next, as the splitting mirror 660 includes many smaller reflective components that are angled in different directions, a light beam hitting the splitting mirror 660, depending on its cross sectional area, may be broken into multiple beams. The reflective components will be angled either to direct some of the light taking a certain path toward the emission detector 260 and some of the light taking a path leading to the aperture 670 and out of the light source 230. In an embodiment, these smaller reflective components of the splitting mirror 660 may be randomly spaced on the angled mirror to provide an even distribution or sampling of emitted light from the various emitters 680 to both the emission detector 260 and the aperture 670. The cap 640 may have a reflective coating or be made of a reflective material in order to reflect light the emitters toward the splitting mirror 660.

In an embodiment, the cap 640 may have a curvature similar to the curvature illustrated in FIGS. 4A, 4C, 4E-4G, and 4M and also a similar substrate 610, guide walls 620, splitting mirror 660, aperture 670, and emission detector 260 geometry to direct light emitted from the emitters 680 to the emission detector 260 and the aperture 670. This is accomplished by calculating the various angles and light paths of the curvature of the cap, the various angles of the splitting mirror 660, and the reflective components and the various distances between the various components to maintain optimal light paths as described herein.

FIG. 4D shows an embodiment of the substrate 620 without the cap 640. In an embodiment, the substrate 610 can be manufactured by etching out depressions in a block of material to create the guide walls 620, the dividing wall 630, and the depressions for the emitter(s) 230, emission detector 260, and aperture 670. The substrate 610 may be made of any suitable material. In one embodiment, the substrate 610 is made from a material that provides an even distribution of temperature such as a ceramic material. FIG. 4F shows an outside view of the light source 230 with dotted lines repre-

senting the splitting mirror 660 and the aperture 670 associated with the substrate 610 of the light source 230. In an embodiment, the cap 640 includes back guide wall 625 attached to the cap 640, the substrate 610, and the splitting mirror 660.

FIGS. 4G and 4H, and 4I show embodiments of the light source 230 from different perspectives. In an embodiment, the cap 640 is supported at least in part by the guide walls 620 that extend down from the cap 640 to the substrate 610. In an embodiment, the cap 640 is dome shaped. FIG. 4I illustrates a light source 260 with eight emitters 680. Also shown is an embodiment of the splitting mirror 660 with several different directing reflecting surfaces positioned in different orientations to angle the light rays either toward the aperture 670 or the emission detector 260. FIG. 4H shows the splitting mirror 660 as viewed from below the substrate 610. The dotted lines represent the outline of the cap 640, the aperture 670, and the emission detector 260.

FIGS. 4J and 4K illustrate an embodiment of the cap 640 that is divided into different sections, with each section tilted at a predetermined angle to facilitate directing of the light paths from light emitted from the emitter(s) 680 to be directed toward the splitting mirror 660 which would then direct the light to the emission detector 260 or the aperture 670. In an embodiment, the sections of the cap 640 may be arced to form the guide walls 620. Also, the cap 640 may include straight segments that are attached to the guide walls 620. In an embodiment, the splitting mirror 660 may be formed in the cap 640, be the material of the cap 640, be fastened to the cap 640, partially to the cap 640, to the guide walls 620 or to the substrate 610 or any combination thereof.

FIG. 4K illustrates the aperture 670 in the form of a semi-reflectant splitting mirror 660 that allows some of the light to pass through the mirror 660 and reflects the rest of the light to emission detector 260. In this embodiment, the aperture is behind the splitting mirror 660.

FIG. 4L illustrates an embodiment of the light source 230 with a splitting mirror 660 that includes both a semi-reflectant component and a completely or more strongly reflective component. In one embodiment, the splitting mirror 660 includes a first semi-reflectant mirror positioned at a first angle that reflects a portion of the emitted light to the emission detector 260 or the aperture 670. The second reflective surface reflects the remaining light toward the aperture 670 or the emission detector 260, and in an embodiment, to the opposite of the two components that the first reflective surface direct the light.

FIGS. 4K-4M also illustrate electrical connections 710 that power the emitters 680 and receive data from the emission detector 260 and are associated with or printed on the side of the substrate 610 or other components of the light source 260. These electrical connections 710 can be any suitable electrical connection and may be printed on any component of the light source 230 including the inside or outside of the cap 640.

FIG. 4M illustrates an embodiment with light source 230 that includes a semi-reflectant mirror 660 with the emission detector 260 located behind the semi-reflectant mirror 660. In this embodiment, the emission detector 260 samples light that passes through the semi-reflectant mirror 660 and the aperture 670 emits light that is reflected from the semi-reflectant mirror 660.

FIG. 4N illustrates an embodiment of the light source 230 where at least a part of the space defined by the cap 640, the substrate 610 and the guide walls 620 are filled with light diffusing material 720. The light diffusing material 720 could be any suitable light diffusing material 720 known in the art including an epoxy or other plastic material, fiber optics, any epoxy mixed with beads or other materials. In an embodi-

ment, the light diffusing material 720 may cause the light emitted from the emitters 680 to become increasingly evenly distributed in the domains of at least range and intensity, as the path length of the light emitted from the emitter(s) 680 increases. In an embodiment, the light diffusing material 720 will more evenly distribute the intensity and range of the light that is incident on the emission detector 260 and the light exiting the light source through the aperture 670.

FIG. 4O illustrates another embodiment of the light source 230 with emitters 680 on far sides of the substrate 610 and angled towards a semi reflectant mirror 660 attached to the cap 640 or guide walls 620. In this embodiment, when the light is emitted onto the semi-reflectant mirror 660, some of the rays will pass directly through the semi-reflectant mirror 660 and be detected by the emission detector 260. The other rays that do not pass directly through semi-reflectant mirror 660 will be reflected. A portion of the reflected rays that have the appropriate incident angle on the semi-reflectant mirror 660 will exit the light source 230 through the aperture 670 after reflecting off the semi-reflectant mirror 660.

FIG. 4P illustrates another embodiment of the light source 230 that may not require splitting mirror 660. In this embodiment, light rays are instead directed to the detector 260 and the apertures 670 by the diffusion and scattering of the light through light diffusing material 720. The light diffusing material 720 may be any suitable diffuser for dispersing light throughout the inside of the light source 230 including glass, epoxy fill, glass beads, plastic, and any other diffuser, scatterer, mixer or combination known in the art. The light diffusing material 720 may be filled in around emitters 680 or may be a component in front of or around the emitters 680.

Additionally the cap 640 may reflect light diffused throughout the cavity back towards detector 260. The cap 640 may be reflective or non-reflective. In an embodiment, the cap 640 absorbs light so that the detector 260 senses light that has passed through the diffuser and has not reflected off the cap 260, so that it will be similar in quality, for example, intensity, to the light emitted through the apertures 670. The cap 640 may be made of a suitable metal including, for example, copper and/or gold. In an embodiment, the cap 640 is relatively straight and does not have a rounded profile in order to reduce the cost and complexity of manufacturing and reduce the bulkiness of the light source 230. This is advantageous as a bulkier, larger sensor will add weight and make the sensor 120 more cumbersome on a patient's forehead.

In this embodiment, the apertures 670 may be directly above the emitters 680 or to the left and right of the emitters 680 so that the emitters will emit light directly outside the aperture 670 and most of the light will not have been reflected off of the cap 640 or other inside surfaces of the light source 230 before exiting the light source 230. This will provide for simpler construction of the light source 230 and other advantages.

The emitters 680 in an embodiment, may be LEDs, or any other suitable light emitting device known in the art. Also, in an embodiment, the temperature sensor 320 will provide feedback for regulating the intensity of the emitters 680 in addition to the information obtained from the detector 260 inside light source 230. The operator, therefore, will be able to maintain and determine an accurate intensity for the emitters 680, leading to more accurate results when processing the signals detected by the detectors 260 of the brain oxygenation sensor 300. In an embodiment, the embodiments disclosed with reference to FIG. 4 comprise an optical bench whose manufacturing costs are significantly lower than those available to design manufacturers today. Diffusing, scattering, reflecting or mixing material, or combinations thereof, may

advantageously be used to integrate emitted light, thereby providing an optical bench from comparatively low cost manufacturing materials.

FIG. 5 illustrates an embodiment of the calibration curve 730 used to determine the intensity of the light emitted from the light source 230 through the aperture 670. In one embodiment, the intensity 740 of the emitted light is mapped with respect to the output 750 of the emission detector 260 of the light source 230. Measuring the output of emission detector 260 will allow the patient monitoring system 100 to calculate a close approximation of the intensity 740 of light being simultaneously emitted from the light source 230 through the aperture 670.

FIG. 6 illustrates another embodiment of the patient monitoring system that incorporates that brain oximetry unit 140 into a connector 760 for the sensor 120. This advantageously allows for a streamlined profile and reduced manufacturing costs of the brain oximetry unit 140 and associated wires. In this embodiment, the circuitry for driving the front end and controlling the drive signal of the brain oxygenation sensor 300 may be in the brain oximetry unit 140 which may advantageously be partially or entirely housed by the connector 760, or may advantageously be partially or entirely housed by the pulse oximeter 150 or other multi-parameter patient monitor. Additionally, the circuitry for processing the signals detected by the detectors 260 of brain oxygenation sensor 300 may also be partially or entirely housed by the connector 760.

In an embodiment, the connector 760 may also house various other components that control and process the signals from various sensors associated with a patient monitoring system 100. For example, the connector 760 may house the circuitry for a blood oxygenation sensor 310 in, for example, an embodiment where the sensor 120 incorporates an ear blood oxygenation sensor or other blood oxygenation sensor 310. In another embodiment, the circuitry for processing, detecting and/or driving the signals for the temperature sensor 320, or EEG sensor 330 may advantageously be incorporated into the sensor connector 760.

Also, the signal processing and conditioning circuitry processor for a patient sedation monitor capable of monitoring the EEG signals of a patient and providing feedback on the depth of sedation or awareness of a patient undergoing anesthesia may be partially or entirely incorporated into the connector. Sedation brain function monitors, including those similar to the SEDLine sedation monitor commercially available from Masimo Corporation of Irvine, Calif., and disclosed herein with reference to U.S. Pat. Nos. 6,128,521, 6,301,493, 6,317,627, 6,430,437, among others assigned to Masimo Corporation. The connector 760 may house the circuit board, with six channels for six detectors and the SEDLine algorithm. In this embodiment, a conventional pulse oximeter may include upgraded programming to recognize the connection of a brain oximetry unit 140, whether separate or housed inside connector 760, and provide communication and power to the unit 140. The unit 140 performs the processing and other functionality for the sensor 120, including storing various algorithms for the associated sensors 120.

Integration of all or the majority of the associated circuitry and processing components of several different patient monitoring sensors 120 in a single connector 760 advantageously provides a caregiver a simple device that can be attached to the patient's forehead or other areas on the patient, to provide minimal discomfort to the patient and minimal amount of wires and connections to cause electrical interference with instruments in the hospital environment. Additionally, the caregiver will need to spend less time hooking various sensors to a patient where each would otherwise require its own

associated monitoring station. Furthermore, this integration of sensor 120 processing components allows some of the processing components to have shared functionality and therefore saves considerably on manufacturing costs. For example, memory chips, processors, or other electrical components may be shared by the various sensors in the connector 760.

FIGS. 7-13 illustrate various embodiments of the construction of the sensor 120. FIGS. 7A-7E illustrate an embodiment of the sensor without the EEG sensor 330 incorporated and includes the disposable portion 410, reusable portion 420, interface 510, connector 760, sensor compartments 540, light sources 230 and detectors 260. The part of the interface 510 on the disposable portion 410 slides into the interface 510 on the reusable portion 420. The interface 510 on the reusable portion 420 may be integrated into the connector 760 or may be separate and located elsewhere on the body of the sensor. In an embodiment, the interface 510 on the disposable portion 410 may slide into the interface 510 on the reusable portion 420 and lock or be somehow be held into place until it needs to be removed.

The interface 510 may include an EEPROM or other memory device from an authorized manufacturer in order to provide quality control. Also, the interface 510 may also include software programming or functionality for determining how many uses it has gone through, how many times it has been used or applied to a patient, or the date of manufacture to determine if it has expired. Also, the interface 510 may include an EEPROM for storing information unique to the electrodes that can be read by the patient monitoring system 100 or pulse oximeter 150. The pulse oximeter 150 or patient monitoring system 100 can then determine how many electrodes are contained on the disposable portion 410, for example, and other information.

FIG. 7E illustrates the placement of the light sources 230 and the detectors 260 for the brain oxygenation sensor 300. The light source 230 may be at the outer end of the sensor 120 and emits light into the cerebral cavity of a patient. The two detectors 260 closest to each light source 230 detect light emitted from the light source 230. For example, the right side light source 230 emits light into the head of a patient and some of the light is returned to the detector 260 closest to the light source 230 and some returns to the detector that is just to the right of the center of the sensor 120. The path that the light travels through the head of a patient to the closer detector generally does not enter the cerebral cavity and travels as deep as the skull. The light path taken by light detected by the further detector 260 generally enters the cerebral cavity. In an embodiment, the signal from the first detector 260 can be subtracted from the second detector 260 in order to provide the information necessary to calculate the cerebral oxygenation as disclosed herein.

FIGS. 8A-8D illustrate an embodiment of the sensor 120 with the EEG sensor 330 integrated into the sensor 120. In this embodiment, the disposable portion includes the EEG electrodes 440, which are electrically connected to the connector 760 through wires integrated into the body of the disposable portion 410. In another embodiment, the disposable portion 410 includes the EEG electrodes 440 for electrical contact with a patient's skin. In this embodiment, the disposable portion may not include any wiring except for electrically connecting the EEG electrodes 440 to the reusable portion 420.

FIGS. 9A-9E illustrate an embodiment of the reusable portion 420 that allows the reusable portion to be disconnected from connector 760. In other embodiments, the reusable portion 430 may be permanently connected to the con-

necter 760. In an embodiment, the reusable portion 420 may be more difficult to disconnect from connector 760 than the disposable portion 410, and may require the operator to open or disassemble at least a part of connector 760.

FIG. 9E illustrates an embodiment of the reusable portion 420 with light sources 230 and detectors 260 some or all of which may take advantage of several features to allow light piping. In an embodiment, the detectors 260 and light sources 230 may have a raised lip 800 that contacts the skin to create a barrier that prevents light from escaping from the light source 230 or detector 260 to the ambient. In an embodiment, the raised lip 800 may be black and absorbent, or reflective. The light sources 230 and detectors 260 may also have a valley or depression on the glass or other transparent or near transparent parts that increases in depth towards the middle of the component. This valley or depression will also advantageously assist with light piping as greater and firmer contact will be made around the edge of the light source 230 or detector 260 allowing less light to escape to the ambient from the light source 230 or emanating from the skin to the detector 230.

FIGS. 10A-10D illustrate various embodiments of the reusable portion 420 of the sensor 120. In an embodiment, the reusable portion 420 has multiple layers that are overlaid and connected together. In an embodiment, the layers include a top flexible sleeve 810, a flex circuit support 820, a flex circuit 830 and a bottom flexible sleeve 840. In an embodiment, the top and bottom flex circuit sleeves 810, 840, may be bonded together or connected together either at the edges or through other means known in the art with the flex circuit support 820 and flex circuit 830 inside and in-between. The top flexible sleeve 810 may be made of silicone or another suitable material and may be white or another color. The bottom flexible sleeve 840 may be made from silicon or other material and may be black. The flex circuit support 820 may be made from cyrlex, polyester or another suitable material and provides support for flex circuit 830. Flex circuit 830 may include EEPROM(s), the flexible circuit, the light sources 230 and detectors 260 for the brain oxygenation sensor 300 and the interface 510. The bottom sleeve includes recesses 850 for the light sources 230, detectors 260 and temperature sensor 320.

FIGS. 11A-11E illustrate an embodiment of the connector 760. The connector 760, in this embodiment, includes a housing 860 that houses the components of the connector 760, including for example, printed circuit boards 870 for various functions, such as, for example, SEDLine monitoring, brain oximetry, pulse oximetry, other blood parameter or physiological parameter calculators, combinations of the same or the like. The connector 760 also includes the interface 510 for the disposable portion 410 and reusable portion 420. The interface 510 in the connector 760 includes a slot 880 for interface 510 on the disposable portion 410.

FIGS. 12A-12D illustrate an embodiment of the disposable portion 410 that does not include the components for the EEG sensor 330 but includes the components for the brain oxygenation sensor 300. In this embodiment, the sensor 120 includes the sensory compartments 540 and the interface 510 which may include an EEPROM for security. In an embodiment, the disposable portion 410 includes an adhesive layer 890 that includes a layer of adhesive and a base material to attach the adhesive layer to the main body of the disposable portion 410. The adhesive layer 890 includes the adhesive for attaching the sensor 120 to the patient's skin. In an embodiment, where the disposable portion 410 does not have the EEG sensor 330 components, the disposable portion 410 will not contain any wires or any other electrical components allowing it to be inexpensively manufactured.

FIGS. 13A-13D illustrate an embodiment of the disposable portion 410 that includes the EEG sensor 330 components. In this embodiment, the disposable portion has the EEG electrodes 440 and wiring for the EEG electrodes 440. The EEG electrodes 440 may include pads 900 for contact with the patient's skin. The pads 900 fit into openings 910 in the adhesive layer 890 in order to make direct contact with the skin.

FIG. 14 illustrates an example of a display 920 that may be utilized for the sensor 120. Shown is the brain oxygenation level (bO<sub>2</sub>), the heart rate, blood oxygenation, and the sedation level from the SEDLine brain function monitor. As other sensors have been described or could be integrated into the sensor 120 additional parameters may be shown on the display 920.

Although the foregoing disclosure has been described in terms of certain preferred embodiments, other embodiments will be apparent to those of ordinary skill in the art from the disclosure herein. Additionally, other combinations, omissions, substitutions and modifications will be apparent to the skilled artisan in view of the disclosure herein. Accordingly, the present disclosure is not intended to be limited by the reaction of the preferred embodiments, but is to be defined by reference to the appended claims.

Additionally, all publications, patents, and patent applications mentioned in this specification are herein incorporated by reference to the same extent as if each individual publication, patent, or patent application was specifically and individually indicated to be incorporated by reference.

What is claimed is:

1. A forehead sensor for monitoring the depth of consciousness of a patient comprising:

a first brain oxygenation sensor including:

- a first light source package configured to transmit optical radiation towards a cerebral cavity of a patient,
- a first detector located on the forehead sensor at a first distance from the first light source package, and
- a second detector located on the forehead sensor at a second distance from the first light source package, wherein the first distance is closer to the first light source package than the second distance;

an EEG sensor including electrodes configured to detect electrical signals proximate skin of the forehead of the patient;

a reusable portion configured to house the first brain oxygenation sensor; and

a disposable portion configured to house the EEG sensor and is configured to be removably connectable to the reusable portion.

2. The forehead sensor of claim 1 comprising: circuitry and processing components for the EEG sensor and the first brain oxygenation sensor; and

a connector configured to connect the disposable portion and the reusable portion, the connector also configured to house a larger portion of the circuitry and processing components.

3. The forehead sensor of claim 2 comprising an interface between the connector and the disposable portion, the interface configured to removably attach the disposable portion to the connector.

4. The forehead sensor of claim 1 wherein the first light source package includes a barrier configured to retain light.

5. The forehead sensor of claim 1 wherein at least one of the first detector or the second detector includes a barrier configured to retain light.

6. The forehead sensor of claim 1 wherein the reusable portion is directly connected to the disposable portion.

23

- 7. The forehead sensor of claim 1, comprising a second brain oxygenation sensor including:
  - a second light source package configured to transmit optical radiation towards the cerebral cavity of the patient;
  - a third detector located on the forehead sensor at a third distance from the second light source package; and
  - a fourth detector located on forehead sensor at a fourth distance from the second light source package, wherein the third distance is closer to the second light source package than the fourth distance.
- 8. The forehead sensor of claim 7, wherein the first brain oxygenation sensor is located at a first end of the forehead sensor and the second brain oxygenation sensor is located at a second end of the forehead sensor.
- 9. A light source for a brain oxygenation sensor, the brain oxygenation sensor comprising:
  - a substrate;
  - a plurality of emitters, attached to the substrate, configured to emit light with at least two different wavelengths towards a tissue site of a patient;
  - a first detector configured to detect emitted light before it is attenuated by the tissue site of the patient to monitor the intensity of the emitted light;
  - a cap configured to integrate the emitted light within the light source;
  - an aperture for at least some of the emitted light to exit the light source towards the tissue site of the patient;
  - a second detector configured to detect light attenuated by the tissue site of the patient; and

24

- a positioning element configured to position the light source proximate to the tissue site of the patient.
- 10. The light source of claim 9 wherein the emitters comprise LEDs.
- 11. The light source of claim 9 wherein the emitters comprise incandescent lights.
- 12. The light source of claim 9 comprising a light diffusing material positioned within an optical path between the emitters and the tissue site, the light diffusing material configured to scatters light.
- 13. The light source of claim 12 wherein the light diffusing material comprises a glass or an epoxy, said material positioned proximate the emitters and the first detector.
- 14. The light source of claim 9 comprising a light diffusing material positioned within an optical path between the emitters and the first detector, the light diffusing material configured to scatter light.
- 15. The light source of claim 9 wherein the cap comprises a reflective material.
- 16. The light source of claim 9 wherein the cap comprises a non-reflective material.
- 17. The light source of claim 9 comprising a splitting mirror configured to directs light to the first detector and the aperture.
- 18. The light source of claim 9 comprising a temperature sensor operably connected to the substrate.

\* \* \* \* \*

UNITED STATES PATENT AND TRADEMARK OFFICE  
**CERTIFICATE OF CORRECTION**

PATENT NO. : 8,821,397 B2  
APPLICATION NO. : 13/246725  
DATED : September 2, 2014  
INVENTOR(S) : Ammar Al-Ali et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In the Claims

In column 24 at line 11 (approx.), In Claim 12, change “scatters” to --scatter--.

In column 24 at line 24, In Claim 17, change “directs” to --direct--.

Signed and Sealed this  
Twenty-fifth Day of August, 2015



Michelle K. Lee  
*Director of the United States Patent and Trademark Office*

专利名称(译)	意识深度监测包括血氧计		
公开(公告)号	<a href="#">US8821397</a>	公开(公告)日	2014-09-02
申请号	US13/246725	申请日	2011-09-27
[标]申请(专利权)人(译)	AL ALI AMMAR ABDUL HAFIZ亚瑟尔		
申请(专利权)人(译)	AL-ALI AMMAR 阿卜杜勒·哈菲兹亚瑟尔		
当前申请(专利权)人(译)	Masimo公司		
[标]发明人	AL ALI AMMAR ABDUL HAFIZ YASSIR		
发明人	AL-ALI, AMMAR ABDUL-HAFIZ, YASSIR		
IPC分类号	A61B5/00 A61B5/04 A61B5/0476 A61B5/0478 A61B5/048 A61B5/1455		
CPC分类号	A61B5/0476 A61B5/0478 A61B5/048 A61B5/14553 A61B5/1455 A61B5/6803 A61B5/6814 A61B5/14552 A61B5/4821 A61B5/742 A61B5/0006 A61B5/165 A61B5/14551 A61B5/6833 A61B2562/164		
优先权	61/387457 2010-09-28 US		
其他公开文献	US20120083673A1		
外部链接	<a href="#">Espacenet</a> <a href="#">USPTO</a>		

摘要(译)

本公开涉及一种用于监测患者意识深度的传感器。传感器包括多个光源，光检测器，并且在一些实施例中，包括电极。在一个实施例中，传感器包括可重复使用和一次性部分。

