



US007225007B2

(12) **United States Patent**
Al-Ali et al.

(10) **Patent No.:** **US 7,225,007 B2**
(45) **Date of Patent:** ***May 29, 2007**

(54) **OPTICAL SENSOR INCLUDING
DISPOSABLE AND REUSABLE ELEMENTS**

(75) Inventors: **Ammar Al-Ali**, Tustin, CA (US);
Yassir Abdul-Hafiz, Irvine, CA (US)

(73) Assignee: **Masimo Corporation**, Irvine, CA (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 6 days.

This patent is subject to a terminal dis-
claimer.

(21) Appl. No.: **11/172,587**

(22) Filed: **Jun. 30, 2005**

(65) **Prior Publication Data**

US 2005/0245797 A1 Nov. 3, 2005

Related U.S. Application Data

(63) Continuation of application No. 10/351,645, filed on
Jan. 24, 2003, now Pat. No. 6,920,345.

(51) **Int. Cl.**
A61B 5/00 (2006.01)

(52) **U.S. Cl.** **600/344; 600/323**

(58) **Field of Classification Search** **600/310,**
600/322, 323, 340, 344

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,621,643 A 11/1986 New, Jr. et al.
4,685,464 A 8/1987 Goldberger et al.
4,700,708 A 10/1987 New, Jr. et al.
4,830,014 A 5/1989 Goodman et al.
4,865,038 A 9/1989 Rich et al.
4,960,128 A 10/1990 Gordon et al.
5,090,410 A 2/1992 Saper et al.
5,094,240 A 3/1992 Muz

5,158,323 A 10/1992 Yamamoto et al.
5,163,438 A 11/1992 Gordon et al.
5,170,786 A 12/1992 Thomas et al.
5,209,230 A 5/1993 Swedlow et al.
5,249,576 A 10/1993 Goldberger et al.
5,337,744 A 8/1994 Branigan
5,387,122 A 2/1995 Goldberger et al.
5,431,170 A 7/1995 Mathews
5,437,275 A 8/1995 Amundsen et al.
5,452,717 A 9/1995 Branigan et al.
5,482,036 A 1/1996 Diab et al.
5,490,505 A 2/1996 Diab et al.
5,494,043 A 2/1996 O'Sullivan et al.
5,507,286 A 4/1996 Solenberger

(Continued)

FOREIGN PATENT DOCUMENTS

AU 200010929 B2 5/2000

(Continued)


Primary Examiner—Eric F. Winakur

(74) *Attorney, Agent, or Firm*—Knobbe, Martens, Olson &
Bear, LLP

(57) **ABSTRACT**

A pulse oximetry sensor includes reusable and disposable elements. To assemble the sensor, the reusable element is snapped or slid within assembly mechanisms of the disposable element. In one embodiment, the reusable element includes protrusions while the disposable element includes tabs which receive the protrusions. In another embodiment, the reusable element includes neck portions and the disposable element includes straps which receive the neck portions. In any event, the assembly provides longitudinal movement between elements.

9 Claims, 10 Drawing Sheets



U.S. PATENT DOCUMENTS

5,533,511 A	7/1996	Kaspari et al.	6,321,000 B1	11/2001	King
5,590,649 A	1/1997	Caro et al.	6,321,100 B1	11/2001	Parker
5,619,992 A	4/1997	Guthrie et al.	6,334,065 B1	12/2001	Al-Ali et al.
5,632,272 A	5/1997	Diab et al.	6,343,224 B1	1/2002	Parker
5,638,816 A	6/1997	Kiani-Azarbayjany et al.	6,349,228 B1	2/2002	Kiani et al.
5,638,818 A	6/1997	Diab et al.	6,360,114 B1	3/2002	Diab et al.
5,645,440 A	7/1997	Tobler et al.	6,371,921 B1	4/2002	Caro et al.
5,660,567 A	8/1997	Nierlich et al.	6,377,829 B1	4/2002	Al-Ali
5,664,270 A	9/1997	Bell et al.	6,388,240 B2	5/2002	Schulz et al.
5,673,693 A	10/1997	Solenberger	6,397,091 B2	5/2002	Diab et al.
5,678,544 A	10/1997	DeLonzor et al.	6,430,525 B1	8/2002	Weber et al.
5,685,299 A	11/1997	Diab et al.	6,463,311 B1	10/2002	Diab
D393,830 S	4/1998	Tobler et al.	6,470,199 B1	10/2002	Kopotic et al.
5,743,262 A	4/1998	Lepper, Jr. et al.	6,501,975 B2	12/2002	Diab et al.
5,758,644 A	6/1998	Diab et al.	6,515,273 B2	2/2003	Al-Ali
5,760,910 A	6/1998	Lepper, Jr. et al.	6,519,487 B1	2/2003	Parker
5,769,785 A	6/1998	Diab et al.	6,525,386 B1	2/2003	Mills et al.
5,782,727 A	7/1998	Pierce	6,526,300 B1	2/2003	Kiani et al.
5,785,659 A	7/1998	Caro et al.	6,541,756 B2	4/2003	Schulz et al.
5,791,347 A	8/1998	Flaherty et al.	6,542,764 B1	4/2003	Al-Ali et al.
5,810,734 A	9/1998	Caro et al.	6,580,086 B1	6/2003	Schulz et al.
5,817,008 A	10/1998	Rafert et al.	6,584,336 B1	6/2003	Ali et al.
5,817,010 A	10/1998	Hibl	6,597,933 B2	7/2003	Kiani et al.
5,823,950 A	10/1998	Diab et al.	6,606,511 B1	8/2003	Ali et al.
5,830,131 A	11/1998	Caro et al.	6,632,181 B2	10/2003	Flaherty et al.
5,833,618 A	11/1998	Caro et al.	6,640,116 B2	10/2003	Diab
RE36,000 E	12/1998	Swedlow et al.	6,643,530 B2	11/2003	Diab et al.
5,860,919 A	1/1999	Kiani-Azarbayjany et al.	6,650,917 B2	11/2003	Diab et al.
5,879,373 A	3/1999	Roper et al.	6,654,624 B2	11/2003	Diab et al.
5,890,929 A	4/1999	Mills et al.	6,658,276 B2	12/2003	Pishney et al.
5,904,654 A	5/1999	Wohltmann et al.	6,671,531 B2	12/2003	Al-Ali et al.
5,910,108 A	6/1999	Solenberger	6,678,543 B2	1/2004	Diab et al.
5,919,133 A	7/1999	Taylor et al.	6,684,090 B2	1/2004	Ali et al.
5,919,134 A	7/1999	Diab	6,684,091 B2	1/2004	Parker
5,934,925 A	8/1999	Tobler et al.	6,697,656 B1	2/2004	Al-Ali
5,940,182 A	8/1999	Lepper, Jr. et al.	6,697,658 B2	2/2004	Al-Ali
5,991,648 A	11/1999	Levin	RE38,476 E	3/2004	Diab et al.
5,995,855 A	11/1999	Kiani et al.	6,699,194 B1	3/2004	Diab et al.
5,997,343 A	12/1999	Mills et al.	6,714,804 B2	3/2004	Al-Ali et al.
5,999,834 A	12/1999	Wang et al.	RE38,492 E	4/2004	Diab et al.
6,002,952 A	12/1999	Diab et al.	6,721,585 B1	4/2004	Parker
6,011,986 A	1/2000	Diab et al.	6,725,075 B2	4/2004	Al-Ali
6,014,576 A	1/2000	Raley	6,735,459 B2	5/2004	Parker
6,027,452 A	2/2000	Flaherty et al.	6,745,060 B2	6/2004	Diab et al.
6,039,642 A	3/2000	Collins	6,760,607 B2	7/2004	Al-Ali
6,045,509 A	4/2000	Caro et al.	6,770,028 B1	8/2004	Ali et al.
6,061,584 A	5/2000	Lovejoy et al.	6,771,994 B2	8/2004	Kiani et al.
6,067,462 A	5/2000	Diab et al.	6,792,300 B1	9/2004	Diab et al.
6,081,735 A	6/2000	Diab et al.	6,813,511 B2	11/2004	Diab et al.
6,088,607 A	7/2000	Diab et al.	6,816,741 B2	11/2004	Diab
6,110,522 A	8/2000	Lepper, Jr. et al.	6,822,564 B2	11/2004	Al-Ali
6,144,868 A	11/2000	Parker	6,826,419 B2	11/2004	Diab et al.
6,151,516 A	11/2000	Kiani-Azarbayjany et al.	6,830,711 B2	12/2004	Mills et al.
6,152,754 A	11/2000	Gerhardt et al.	6,850,787 B2	2/2005	Weber et al.
6,157,850 A	12/2000	Diab et al.	6,850,788 B2	2/2005	Al-Ali
6,165,005 A	12/2000	Mills et al.	6,920,345 B2 *	7/2005	Al-Ali et al. 600/344
6,184,521 B1	2/2001	Coffin, IV et al.	2001/0029325 A1	10/2001	Parker
6,206,830 B1	3/2001	Diab et al.	2003/0009092 A1	1/2003	Parker
6,229,856 B1	5/2001	Diab et al.	FOREIGN PATENT DOCUMENTS		
6,236,872 B1	5/2001	Diab et al.	CA	2 346 639	4/2000
6,256,523 B1	7/2001	Diab et al.	CA	2 366 493 A1	11/2002
6,263,222 B1	7/2001	Diab et al.	EP	1 222 894 A2	7/2002
6,278,522 B1	8/2001	Lepper, Jr. et al.	EP	1 222 894 A3	7/2002
6,280,213 B1	8/2001	Tobler et al.	WO	WO 00/21433	4/2000
6,285,896 B1	9/2001	Tobler et al.	WO	WO 01/03574 A1	1/2001
6,308,089 B1	10/2001	von der Ruhr et al.	* cited by examiner		











FIG. 1










FIG. 7A








FIG. 7B












FIG. 12

OPTICAL SENSOR INCLUDING DISPOSABLE AND REUSABLE ELEMENTS

RELATED APPLICATIONS

The present application is a continuation of U.S. patent application Ser. No. 10/351,645, filed Jan. 24, 2003, entitled "Optical Sensor Including Disposable and Reusable Elements," now U.S. Pat. No. 6,920,345, and claims priority benefit under 35 U.S.C. § 120 to the same. The present application incorporates the foregoing disclosures herein by reference.

FIELD OF THE INVENTION

The present invention relates to the field of sensors that measure oxygen content in a patient's blood. More specifically, the invention relates to a sensor that assembles reusable and disposable elements and/or allows longitudinal displacement between the reusable and disposable elements.

BACKGROUND OF THE INVENTION

Early detection of low blood oxygen is important in a wide variety of medical applications, and oximetry was developed to study and to measure, among other things, the oxygen status of blood. One type of oximetry, pulse oximetry, employs a sensor attached to a patient in order to output a signal indicative of a physiological parameter of the patient, such as, for example, the patient's blood oxygen saturation.

A pulse oximeter sensor generally uses a number of sensor components, such as one or more energy emission devices like red and infrared LED emitters, and an energy detection device like a photodiode detector. The sensor is generally attached to a measurement site such as a patient's finger, toe, ear, forehead, foot, hand, heel or the like, using an attachment mechanism such as a disposable tape, reusable housing, Velcro strap, or the like. The attachment mechanism positions the emitter and detector in proximity to the measurement site, such that the emitter projects energy into the blood vessels and capillaries of the measurement site, and the photodiode detector then detects the attenuated energy. The emitted energy can be light or other forms of energy. The detector communicates a signal indicative of the detected attenuated energy to a signal processing device such as an oximeter. The oximeter generally calculates, among other things, one or more physiological parameters of the measurement site.

In sensors where the detector detects emissions through the measurement site, it is generally desirable to position the detector opposite the emitter around the measurement site, such as, for example, above and below a finger. However, sensors are produced in a limited number of sizes and shape configurations, while patients have, for example, fingers and toes of many different sizes and shapes.

In addition, the attachment mechanism and the electronic components of a sensor are generally curved around a measurement site in a manner detrimental to one or more elements of the sensor. For example, the attachment mechanism generally wraps around the measurement site at an approximate "inner circle" having a first radius, while the electronic components such as the flexible circuits are generally fixedly attached to the attachment mechanism. Accordingly, the electronic components can form an approximate "outer circle" having a second radius unequal to the first radius. However, because the attachment mechanism

generally does not move independently with respect to the electrical components, attachment of the sensor to the measurement site can exert forces on the electrical components, such as, for example, exerting forces which try to lengthen, or longitudinally stretch the electrical components to account for an increased radius thereof. The forced stretching can damage the electrical components of a flexible circuit, such as the conductive traces.

SUMMARY OF THE INVENTION

Based on the foregoing, embodiments of the present invention include a sensor comprising reusable and disposable sensor elements that permit longitudinal displacement with respect to one another when the sensor is attached to a measurement site. For example, in one embodiment the sensor includes a reusable element and a disposable element configured to receive the reusable element in a releasable attachment assembly providing longitudinal displacement between the disposable and reusable elements. The longitudinal displacement advantageously allows the sensor elements to self-adjust with respect to one another during attachment to the measurement site. The self-adjustment or independent movement advantageously reduces the forces caused by longitudinal stretching, thereby reducing damage to the reusable element.

One aspect of the invention relates to an optical probe including a reusable element and a disposable element that can be attached together by placing or snapping protrusions on one element into apertures and receiving slots on the other element. For example, the reusable element can be fitted with protrusions made of plastic, and the disposable element can be fitted with detents or tabs, which include apertures or receiving slots. The reusable element attaches to the disposable element by inserting, or snapping, the protrusions into the apertures and the receiving slots of the tabs. When assembled, at least some of the protrusions are slidable within the receiving slots to independently move along a longitudinal axis of the sensor, thereby providing some longitudinal decoupling between the reusable element and the disposable element.

Another aspect of the invention relates to a sensor with a reusable element and a disposable element where the reusable element is made of a flexible or pliable material and includes one or more neck sections. The disposable element includes two straps, each of which is configured to receive a neck section. The reusable element and the disposable element are attached together by placing the neck sections within the straps. In one embodiment, the neck sections include a long neck section and a short neck section. The long neck section has a sufficient length to allow longitudinal movement of the reusable element within the strap, thus permitting movement of the reusable element with respect to the disposable element.

Another aspect of the invention relates to a sensor with a reusable element and a disposable element where the reusable element is secured by guides or tabs affixed to the disposable element. The guides allow limited longitudinal motion of the reusable element and thereby allow the reusable element to flex independently of the disposable element as the device is positioned on a patient.

Another aspect of the invention relates to a sensor with a reusable element and a disposable element where the reusable element is encased in a protective cover. In one embodiment, the protective cover is made of a pliable material and prevents any sharp edges from scratching or poking a patient or caregiver. The protective cover also advantageously pre-

vents damage to the reusable element that could occur from dirt, dust, liquids, or other elements of the environment.

Yet another aspect of the invention relates to a sensor with a reusable element and a disposable element where the disposable element includes a breakable element. After an approximate predetermined number of safe uses, the breakable element breaks and the disposable element is rendered inoperable or otherwise indicates its over use.

For purposes of summarizing the invention, certain aspects, advantages and novel features of the invention have been described herein. Of course, it is to be understood that not necessarily all such aspects, advantages or features will be embodied in any particular embodiment of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

A general architecture that implements the various features of the invention will now be described with reference to the drawings. The drawings and the associated descriptions are provided to illustrate embodiments of the invention and not to limit the scope of the invention. The drawings are not necessarily drawn to scale. Throughout the drawings, reference numbers are re-used to indicate correspondence between referenced elements. In addition, the first digit of each reference number indicates the figure in which the element first appears.

FIG. 1 illustrates a perspective view of an embodiment of an unassembled sensor that includes reusable and disposable elements.

FIG. 2 illustrates a perspective view of tabs of the disposable element of FIG. 1.

FIG. 3A illustrates a cross-sectional view of another embodiment of tabs of a disposable element.

FIG. 3B illustrates a cross-sectional view of yet another embodiment of tabs of a disposable element.

FIG. 4A illustrates a cross-sectional view of the two tabs of FIG. 2, adhesively attached to the disposable element.

FIG. 4B illustrates a cross-sectional view of the two tabs of FIG. 2, attached between layers of the disposable element.

FIG. 5 illustrates a top view of the disposable element of FIG. 1, including an information element and breakable conductor.

FIG. 6 illustrates a top view of another embodiment of an assembled sensor that includes reusable and disposable elements.

FIGS. 7A and 7B illustrate simplified cross-sectional views of an embodiment of a strap of the disposable element of FIG. 6.

FIG. 8 illustrates an exploded view of a disposable element according to another embodiment of an optical sensor.

FIG. 9 illustrates a perspective view of the disposable element of FIG. 8.

FIG. 10 illustrates a perspective view of an embodiment of a reusable element according to an embodiment of the optical sensor of FIG. 8.

FIG. 11 illustrates a perspective view of a flex circuit of the reusable element of FIG. 10.

FIG. 12 illustrates a perspective view of the assembled optical sensor including the disposable element of FIG. 8 and the reusable element of FIG. 10.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

FIG. 1 illustrates an embodiment of a sensor 100. The sensor 100 includes a reusable element 110 and a disposable

element 120. According to one embodiment, the reusable element 110 generally includes those components of the sensor 100 that are more expensive, such as, for example, one or more energy emitters, one or more energy detectors, one or more breakable conductors, one or more information elements, some or all of the same, or the like. In addition, the reusable element 110 includes an assembly mechanism generally shaped to mate with a corresponding component of the disposable element 120, as will be disclosed in greater detail below.

The disposable element 120 generally includes those components of the sensor 100 that are less expensive, such as, for example, face tape, bandages, or other mechanisms for removably attaching the reusable element 110 to a measurement site. Moreover, the disposable element 120 includes a mating assembly mechanism generally shaped to mate with assembly mechanism of the reusable element 110, thereby attaching the reusable element 110 to the disposable element 120 in a manner that provides for at least some self adjustment or displacement between the elements.

When the disposable element 120 attaches the reusable element 110 to tissue of a measurement site, a signal processing device, such as an oximeter, activates the energy emitters to transmit light energy into the tissue. The tissue attenuates the light energy, which is then detected by the detector. A signal indicative of the detected light energy is then generally forwarded back to the signal processing device for determination of one or more physiological parameters of the tissue, such as, for example, oxygen saturation, pulse rate, or the like.

A skilled artisan will recognize from the disclosure herein that there are many combinations of differing shapes and circuit configurations for the reusable and disposable elements, 110 and 120, respectively, such as, for example, those disclosed in U.S. Pat. No. 6,377,829, and U.S. patent application Ser. No. 10/020,664, filed on Dec. 11, 2001, both of which are hereby incorporated by reference.

As shown in the exemplary embodiment of FIG. 1, the reusable element 110 can include one or more energy emitters 112, an energy detector 114, and an electrical connector 116 electrically communicating with the emitters 112 and the detector 114 through a flexible circuit. According to one embodiment, the flexible circuit comprises material of a generally flexible or pliable construction.

The reusable element 110 also includes the foregoing assembly mechanism, such as, for example, the one or more protrusions 118. According to one embodiment, the protrusions 118 comprise approximately cylindrical-shaped or tab-shaped extensions made of plastic or other durable materials. FIG. 1, shows the reusable element 110 including four protrusions 118, two opposing protrusions proximate a front portion and extending in opposite generally horizontal directions, and two opposing protrusions proximate a back portion and extending in opposite generally horizontal directions. According to one embodiment, the protrusions 118 roughly align with one or more of the electronic components of the sensor 100. As described below, the protrusions 118 each advantageously mate with the mating assembly mechanism of the disposable element 120 in a manner providing for at least some displacement of the reusable element 110 with respect to the disposable element 120, thereby avoiding damage or harmful wear of the reusable element 110.

FIG. 1 also shows the flexible circuit including an optical barrier, such as, for example, an aperture or gap 119 to reduce light energy from travelling from the emitter 112 to the detector 114 without first passing through tissue at the measurement site (i.e., light piping). A skilled artisan will

recognize from the disclosure herein that the gap 119 could be replaced with opaque materials, protrusions, pads, tabs, or other light blocking mechanisms.

Although disclosed with reference to preferred embodiments, a skilled artisan will recognize from the disclosure herein, a number of other embodiments of the reusable element 110. For example, one or more of the emitters 112 or the detector 114 can be located on the disposable element 120. Moreover, the flexible circuit may comprise plastic, electric wires, polyester substrates, or the like.

FIG. 1 also shows the disposable element 120. According to an embodiment, the disposable element 120 generally comprises a base 130 comprising a face tapestock material similar to that of an adhesive bandage shaped to position the reusable element proximate the measurement site. The face tape can include an adhesive covered base protected by one or more conveniently shaped release liners or layers. Although illustrated in a conventional elongated surface with opposing wings style shape, an artisan will recognize from the disclosure herein that the tape may comprise virtually any shape, including those disclosed in U.S. patent application Ser. No. 10/020,664, referenced above. Moreover, the disposable element 120 may comprise a Velcro strap, a foam wrap, a reusable plastic housing or the like.

The disposable element 120 also includes the assembly mechanism, illustrated as tabs 122 and 124. Each of the tabs 122 include an aperture 132, while each of the tabs 124 include a receiving slot 134. In one embodiment, the apertures 132 and the receiving slots 134 have sufficient depth to receive the protrusions 118. In other embodiments, the apertures 132 and receiving slots 134 extend through the tabs 122 and 124. As shown in FIG. 1, the tabs 122 and 124 are shaped to removably receive the reusable element 110. For example, the tabs 122 and 124 can include sloped surfaces that cause the tabs 122 and 124 to displace outwardly during assembly of the sensor 100. For example, when the reusable element 110 is properly positioned within the tabs 122 and 124, the tabs 122 and 124 snap inwardly over the reusable element 110 such that the protrusions 118 are within the apertures 132 and the receiving slots 134. When assembled, vertical and horizontal movement between the reusable and disposable elements, 110 and 120 respectively, is substantially prevented by the relationship between the tabs 122 and 124, the apertures 132, the slots 134 and the protrusions 118. However, the slots 134 provide for displacement between elements along longitudinal axis A when the disposable portion 120 is wrapped around a measurement site by allowing the protrusions 118 to slide back and forth within the slots 134. Thus, the assembly mechanisms of the reusable and disposable elements, 110 and 120, provide independent movement between the elements, thereby allowing self-adjustment of the sensor 100 to the differing radiuses of each element. Such construction advantageously reduces the harmful stressing effects applied to components of the reusable element 110.

FIG. 1 also shows that a gap 142, slot or aperture, or otherwise transparent area can be included on the disposable element 120 to permit light from the emitter 112 to travel through the disposable element 120 to the tissue of the measurement site. Moreover, another gap 144 can be included on the disposable element 120 to permit attenuated light from the measurement site tissue to travel through the disposable element 120 to the detector 114. In another embodiment, some or all of the base 130 of the disposable element 120 is made of a transparent material, and the gaps 142 and 144 can be omitted.

A skilled artisan will recognize from the disclosure herein that the tabs 122 and 124 of the disposable element 120 can be implemented in a wide variety of embodiments. For example, an embodiment can include each of the tabs 122 and 124 having a receiving slot 134 while another embodiment can include each of the tabs 122 and 124 having an aperture 132.

FIG. 2 illustrates a perspective view of the tabs 124 including the receiving slots 134. As disclosed, the tabs 124 can be shaped to include a sloped surface 220 configured to displace a ledge or catch 230 during sensor assembly. For example, the sloped surface 220 displaces outwardly when protrusions 118 are pressed in the direction of the arrow C. Then when the reusable element 110 is properly positioned, the protrusions 118 snap into the receiving slots 134 and the catch 230 snaps over a top surface of the reusable element 110.

The receiving slots 134 are longer than the cross sectional width of the protrusions 118 so that the protrusions 118 can move within the receiving slots 134 to different positions along the longitudinal axis A of the disposable element 120. The apertures 132, on the other hand, are sized to allow protrusions 118 to be located within the apertures 132 but to prevent substantial movement along the longitudinal axis A of the disposable element 120, thus ensuring proper positioning of the sensor elements, with respect to the tissue and one another.

In an embodiment, the reusable element 110 and the disposable element 120 are assembled into the sensor 100 when the protrusions 118 are snapped into the apertures 132 and the receiving slots 134 of the tabs 122 and 124. The assembled sensor 100 is then attached to a measurement site, through, for example, application of the adhesive covered side of the face tape to tissue at the measurement site. During application, the protrusions 118 within the receiving slots 134 move along the receiving slot 134, while the protrusions 118 remain positioned within the aperture 132. This type of flexibility advantageously reduces the stretching force placed on conventional reusable elements.

FIG. 2 also shows receiving slots 134 as grooves in the walls 240 of the tabs 124, where the grooves do not extend all the way through the walls 240. In other embodiments, the receiving slots 134 can be open slots that extend through the walls 240. Likewise, the aperture 132 can be straightforward depressions, or punch through holes.

FIG. 3A illustrates a cross-sectional view of tabs 300 of another embodiment of a disposable element, such as disposable element 120 of FIG. 1. The tabs 300 include the receiving slot 134 for receiving the protrusions 118, but does not include the sloped surface 220 or the catch 230 of FIG. 2. Thus, the reusable element 110 is assembled relying on the interaction described in the foregoing between the protrusions 118 and the apertures 132 and the slots 134.

FIG. 3B illustrates a cross-sectional view of tabs 310 of another embodiment of a disposable element, such as the disposable element of FIG. 1. The tabs 310 include the sloped surface 220 and the catch 230, but do not include the receiving slot 134 or aperture 132. Thus, the sensor 100 is assembled relying on the interaction between the catch 230 and the surface of the reusable element 110.

FIG. 4A illustrates a cross-sectional view of the tabs 124 of FIG. 1 adhesively attached to the disposable element 120, according to an embodiment. In FIG. 4A, the tabs 124 are attached to the base 130 by adhesive. In a preferred arrangement, the tabs 124 share a common substrate 310, and an adhesive is applied between the substrate 310 and the base 130 to attach the tabs 124 to the disposable element 120.

FIG. 4B illustrates a cross-sectional view of the tabs 124 of FIG. 1 attached between layers of the disposable element 120 of FIG. 1, according to another embodiment. In FIG. 4B, the tabs 124 are attached between two layers 410 and 420 of the base 130. In a preferred arrangement, the two tabs 124 share a common substrate 310, and the substrate 310 is sandwiched between the layers 410 and 420.

A skilled artisan will recognize from the disclosure herein that the embodiments disclosed with reference to FIGS. 3 and 4 can be applied to one or both sets of the tabs 122 and 124. Moreover, a skilled artisan will recognize from the disclosure herein that the protrusions 118 can be attached to the reusable element 110 in a number of ways, such as, for example, attached by adhesive to the reusable element 110, manufactured as integral parts of the reusable element 110, sandwiched between a top layer and a bottom layer of the reusable element 110, or the like.

FIG. 5 illustrates a top view of the disposable element of FIG. 1, including an information element 510, contacts 520, and a breakable conductor 530, according to yet another embodiment. The contacts 520 can electrically connect with contacts on the flexible circuit of the reusable element 120, thereby adding the information element 510 and/or the breakable conductor 530 into the electric circuit of the sensor 100. As is understood in the art, the information element 510 can provide an indication of the sensor or patient type, operating characteristics or the like, or that the sensor 100 is from an authorized supplier. In an embodiment, the information element 510 is a resistive element made by depositing a conductive ink trace having a predetermined length and width. The information element 510 is disposed between contacts 520, which can also be implemented with conductive ink. As an artisan will recognize from the disclosure herein, many type of information elements can be included, such as, for example, passive or active elements, accessible memory elements, or the like.

The breakable conductor 530 is configured to break after a predetermined number of safe uses, thus providing quality control to ensure that the disposable element 120 is not over used. Various embodiments of information element 510, contacts 520, and breakable conductor 530 can be found in U.S. Pat. No. 6,377,829.

FIG. 6 illustrates a top view of an assembled sensor 600 that includes reusable and disposable elements, according to another embodiment. As shown in FIG. 6, the sensor 600 includes a reusable element 610 and a disposable element 620. The disposable element 620 includes straps 630 which position the reusable element 610 as described below. As shown in FIG. 6, the reusable element 610 can be similar to the reusable element 110 of the foregoing embodiments, generally including, for example, the more expensive components of the sensor 600. Moreover, disposable element 620 can be similar to the disposable element 120 of the foregoing embodiments, generally including for example, a disposable tape. The disposable tape can be virtually any suitable shape, and is shown in FIG. 6 in a generally "L" shaped configuration.

FIG. 6 also shows the reusable portion 610 including an extended narrow neck or notch 635 and a neck or notch 640, each narrower in width than the general width of the reusable element 610. The straps 630 attached to the disposable element 620 extend over the necks 635 and 640 to position the reusable element 610 with respect to and proximate the disposable element 620. The straps 630 provide for longitudinal movement between the elements of the sensor 600 similar to that disclosed in the foregoing.

FIG. 7A illustrates a simplified cross-sectional view of one of the straps 630 of the disposable element 620 of FIG. 6, according to an embodiment. The strap 630 may comprise a hook-and-loop device such as Velcro. The strap 630 may alternatively be an integral part of the structure of the disposable element 620. According to an embodiment, the strap 630 includes blocks 720 forming a gap 710 therebetween. As shown in FIG. 7A, an embodiment of the strap 620 can be removed from the disposable element 620 to permit the neck 630 of the reusable element 610 to be placed within the gap 710, as shown in FIG. 7B an artisan will also recognize from the disclosure herein that the pliable material of the reusable portion 610 can alternatively or concurrently be compressed together and guided through attached straps 630.

According to one embodiment, the gap 710 is as wide or slightly wider than the necks 635 and 640, but narrower than other adjacent portions of the reusable element 610. Therefore, once placed in the gaps 710 and attached to the disposable element 620, the reusable element 610 can be moved along its longitudinal axis along the arrows A and B (FIG. 7B), but only to the extent that the necks 635 and 640 remain in the gaps 710.

In one embodiment shown in FIG. 6, the reusable element 610 includes the relatively "long" neck 635 shown near the top of the figure and a relatively "short" neck 640 shown near the bottom of the figure. Once the two necks 635 and 640 are placed within the straps 650, the long neck 635 allows the reusable element 610 to be moved along a longitudinal axis of the disposable element 120. In contrast, the short neck 640 prevents substantial movement along the longitudinal axis. Thus, similar to embodiments disclosed in the foregoing, the sensor 600 allows the neck 630 to self adjust during application to a measurement site, thereby avoiding damaging the reusable element 610.

FIG. 8 illustrates an exploded view of a disposable element 810 according to another embodiment of an optical sensor. The disposable element 810 includes a top layer 812, at least one attachment mechanism, tab, or positioning guide 814, and an adhesive, preferably transparent, tape layer 816. FIG. 8 shows tabs 814 positioned in a back-to-back or opposing manner, as will be described in greater detail below.

FIG. 8 shows the top layer 812 as a generally L shaped tape or other pliable substrate including a first side 822 and a second side 824, although an artisan will recognize from the disclosure herein that the virtually any shape can be used which provides attachment to tissue of a patient. According to an embodiment, the first side 822 includes a breakable element 826, such as the conductive trace disclosed in U.S. Pat. No. 6,377,829, discussed in the foregoing. The breakable element 826 is included into the electrical circuit of the optical sensor through electrical leads or contacts 830 configured to electrically communicate with contacts of a reusable element of the optical sensor. Moreover, the first side 822 of the top layer 812 can optionally include an optical barrier layer 831, such as a layer of material opaque or substantially opaque to light. The optical barrier layer 831 is generally designed to help prevent ambient light or light piping from interfering with the optical signals before or after they are passed through the tissue of the patient. In one embodiment, the barrier layer 831 comprises conductive trace material similar to that of the breakable element 826.

According to an embodiment, the top layer 812 also includes a plurality of apertures 832, which when the optical sensor is assembled, accept portions of the tabs 814 in a manner designed to provide proper placement, positioning,

and support of the tabs **814**. However, an artisan will recognize from the disclosure herein that top layer **812** may use ink outlines combined with adhesive, or the like to help an assembler properly place and support the tabs **814** on the first side **822** of the top layer **812**.

Each tab **814** includes a base **836**, a signal aperture **838**, and grooves or slots **840**. The base **836** connects and supports each of two raised side members forming a generally U shaped structure. The signal apertures **838** comprise holes through which a properly positioned sensor element can emit or detect optical signals, and the raised side members each include the slot **840**, similar to the grooves **134** of the tabs **124** of FIG. 1. However, unlike FIG. 1, an embodiment of each of the slots **840** opens from one side of the raised side member, extends along the side member, and ends before the other side of the raised side member. Thus, the slot **840** accepts a protrusion or the like from an insertion side, and allows the protrusion to slide within the slot **840** to the end thereof, proximate a blocked side. Moreover, according to one embodiment, the blocked sides of the tabs **814** approximately adjacently oppose one another, such that protrusions inserted into the insertion sides, are at one point blocked from sliding closer than a predetermined distance from one another by the blocked sides.

According to one embodiment, the tape layer **816** comprises a transparent tape or other substrate layer. The tape layer **816** has a first side **846** and a second side **848**. When assembled, the first side **846** adheres to the top layer **812** and sandwiches the tabs **814** therebetween. The second side **848** includes an adhesive, hook-and-loop, similar or combination structure configured to secure the disposable element **810** to tissue of a patient.

FIG. 8 also shows the disposable element **810** including a cable connector **850**. The cable connector **850** generally provides for connection of the disposable element **810** to the remainder of a sensor, such as, for example, the reusable elements. According to the exemplary embodiment, the cable connector **850** comprises a plastic plate **852** including mating portions **854**, such as, for example, raised pliable detents that each including a catch. However, an artisan will recognize from the disclosure herein any suitable mating mechanism can be used to connected the disposable element **810**, including virtually any mechanical-type mating mechanism, adhesives, hook-and-loop materials, combinations, or the like.

When the disposable element **810** is assembled as shown in FIG. 9, the bases **836** of the tabs **814** and the plate **852** communicate with the second side **824** of the top layer **812** and first side **846** of the tape layer **816** such that the bases **836** of the tabs **814** and the plate **852** are secured in position between the top layer **812** and the tape layer **816**. The raised side members of the tabs **814** extend through the plurality of apertures **832** in the top layer **812**, thereby aligning the signal apertures **838** with apertures in the top layer **812**. Moreover, as shown in the illustrated embodiment, the mating portions **854** of the cable connector **850** extend above the top layer **812**.

FIG. 10 shows a perspective view of an embodiment of a reusable element **1000**. The reusable element **1000** preferably includes a protective cover or coating **1004** covering a plurality of electronic sensor elements **1005** and a plurality of protrusions **1006**. The reusable element **1000** also includes a cable connection housing **1008**, and cord or cable **1010**. According to one embodiment, the protective cover **1004** comprises a soft material, such as a pliable rubber, plastic or the like, which preferably encapsulates and protects the electronic sensor elements **1005** from damage and

advantageously protects caregivers and patients from sharp corners often associated with the reusable element **1000**, such as, for example, the protrusions **1006** or the sensor elements **1005**.

The protrusions **1006** extend from opposing sides of the reusable element **1000** in generally horizontal and opposing directions. To assemble the optical sensor, the protrusions are aligned with the outside-facing insertion side of each of the slots **840** of the disposable element **810**, shown in FIG. 8, and are slid toward one another on each side. As can be seen in FIG. 12, an embodiment of the assembled sensor includes one or more of the protrusions **1006** abutting the blocked side of one pair of the slots **810**, while the other protrusions **1006** are proximate the blocked side of the other pair of slots **810**, thereby allowing the reusable element **1000** to self adjust and avoid the detrimental stretching forces caused from application to a measurement site.

FIG. 10 also shows the cable connection housing **1008** including insertion slots **1012** configured to receive and mate with the mating portions **854** of the cable connector **850** shown in FIG. 8. When mated, the cable connection housing **1008** provides electrical contact between the electrical leads **830** of the disposable element **810** and the sensor circuitry.

FIG. 11 illustrates a perspective view of portions of the electronic sensor elements **1005** of the reusable element **1100** without the protective cover or coating **1004**. The elements **1005** include one or more energy emitters **1102**, such as one or more LEDs, an energy detector **1104**, such as a photodetector, electrically connected to a connector **1106** through a flexible circuit **1108**. The connector **1106** is configured to electrically communicate with the leads **830** of the disposable element **810** when the sensor is assembled. Moreover, the connector **1106** is configured to electrically attach the conductive traces of the flexible circuit **1108** to the conductors of the cable **1010**.

FIG. 12 shows a perspective view of an assembled sensor **1200**. The sensor **1200** includes the reusable element **1000**, including the disposable element **810** connected to the connection housing **1008** through the mating portions **854** of the cable connector **850**, such that the breakable element **826** is part of the electrical circuitry of the sensor. In one embodiment, the sensor is inoperative or otherwise provides an indication of overuse or misuse when the breakable element **826** is broken or otherwise becomes an open circuit.

As disclosed, when connected to the disposable element **810**, the protrusions **1006** have a limited range of motion within the tabs **814**, thereby giving the reusable element **1000** a limited range of longitudinal motion independent of the disposable element **810**. As described with other embodiments, this longitudinal motion allows the disposable element **810** and the reusable element **1000** to flex independently as the sensor **1200** is attached to tissue of a user, such as a finger, toe, ear, or the like, thereby avoiding damage or unnecessarily harmful wear of the reusable element **1000**. Also, this limited range of motion ensures at least approximate proper alignment of various sensor components.

After use, as with embodiments described above, the disposable element **810** is removed and discarded, while the reusable element **812** can be sterilized and reused.

Although the foregoing invention has been described in terms of certain preferred embodiments, other embodiments will be apparent to those of ordinary skill in the art from the disclosure herein. For example, although the above sections describe a reusable element fitted with protrusions or necks and a disposable element fitted with apertures and receiving slots or straps, the embodiments can be reversed having, for

11

example, the reusable element fitted with the apertures, receiving slots, or straps, and with the disposable element fitted with the protrusions or necks.

Additionally, other combinations, omissions, substitutions and modifications will be apparent to the skilled artisan in view of the disclosure herein. Accordingly, the present invention is not intended to be limited by the reaction of the preferred embodiments, but is to be defined by reference to the appended claims.

What is claimed is:

1. A sensor for outputting a signal indicative of one or more physiological parameters of tissue of a patient the sensor comprising:

a reusable element comprising one or more energy emission devices, an energy detection device configured to output a signal indicative of one or more parameters of tissue of a patient, and a plurality of neck sections, each of which is narrower in cross section than adjacent sections of the reusable element; and

a disposable element comprising a bandage adapted to attach to the tissue, and a plurality of straps, each strap including a gap adapted to receive one of the plurality of neck sections, wherein the gap is narrower in cross section than the adjacent sections of the reusable element,

wherein, after assembly and during application of said sensor to said tissue, at least a portion of the reusable element is slidable within at least one of said gaps to reduce or avoid stretching forces exerted on the reusable element caused by a shape of said tissue.

2. A sensor for outputting a signal indicative of one or more physiological parameters of tissue of a patient, the sensor comprising:

a reusable element comprising one or more energy emission devices, an energy detection device configured to output a signal indicative of one or more parameters of tissue of a patient, and a plurality of neck sections, each of which is narrower in cross section than adjacent sections of the reusable element; and a disposable element comprising a bandage adapted to attach to the tissue and a plurality of straps, each strap including a gap adapted to receive one of the plurality of neck sections, wherein the gap is narrower in cross section than the adjacent sections of the reusable element,

wherein the plurality of neck sections includes a long neck section and a short neck section, wherein the long neck section is longer than a width of a corresponding strap, and wherein the short neck section is about the width of another corresponding strap.

3. A method of assembling and using a sensor, the method comprising:

snapping a reusable element into a disposable element to form a sensor, wherein, after assembly, at least a portion of the reusable element moves with respect to the disposable element opposite stretching forces exerted on the reusable element during attachment of the sensor to a measurement site; and

removably attaching the disposable element to the measurement site.

12

4. A pulse oximetry sensor for outputting a signal indicative of one or more physiological parameters of tissue of a patient, the sensor comprising:

a reusable element comprising an energy emission device adapted to transmit energy into tissue of a patient, an energy detection device adapted to detect energy from the tissue and output a signal indicative of one or more physiological parameters of the tissue, a protective cover, and a plurality of protrusions extending laterally from said protective cover and extending perpendicular to a long axis of said protective cover; and

a disposable element comprising a plurality of attachment members adapted to receive the protrusions of the reusable element and properly position the disposable element with respect to the reusable element.

5. The pulse oximetry sensor of claim 4, including an adhesive layer adapted to removably attach the disposable element to the tissue.

6. The pulse oximetry sensor of claim 4, wherein the protective cover further comprises a pliable coating.

7. The pulse oximetry sensor of claim 4, wherein the cover substantially encapsulates the reusable element.

8. A method of providing a pulse oximetry sensor, the method comprising:

providing a reusable element including an energy emission device adapted to transmit energy into tissue of a patient, an energy detection device adapted to detect energy from the tissue and output a signal indicative of one or more physiological parameters of the tissue, a protective cover, and a plurality of protrusions extending laterally from said protective cover and extending perpendicular to a long axis of said protective cover; and

providing a disposable element including a top layer with a plurality of attachment members adapted to receive the protrusions of the reusable element, and an adhesive adapted to removably attach to the tissue,

wherein the reusable element is configured to be combined with the disposable element to form a pulse oximetry sensor.

9. A method of providing a replaceable disposable element of an optical pulse oximetry sensor, the method comprising:

providing a first tape layer including a plurality of attachment members, wherein the first tape layer is configured to receive and position a reusable element of an optical sensor in a manner allowing for independent adjustment of the reusable element with respect to the first tape layer, the independent adjustment being along an axis of the first tape layer opposite stretching forces exerted on the reusable element during attachment of the sensor to a measurement site to avoid damaging portions of the reusable element; and

providing a second layer attached to the first layer and configured to removably attach the optical sensor to a measurement site.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 7,225,007 B2
APPLICATION NO. : 11/172587
DATED : May 29, 2007
INVENTOR(S) : Ammar Al-Ali et al.

Page 1 of 2

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

At page 2, column 1 (U.S. Patent Documents), line 18, please delete “5,782,727 A 7/1998 Pierce” and insert -- 5,782,757 A 7/1998 Diab et al. --, therefor.

At page 2, column 1 (U.S. Patent Documents), line 45, please delete “6,039,642 A 3/2000 Collins” and insert -- 6,036,642 A 3/2000 Diab et al. --, therefor.

At page 2, column 2 (U.S. Patent Documents), line 30 after “6,658,276 B2 12/2003”, please delete “Pishney et al.” and insert -- Kiani et al. --, therefor.

At column 8, line 11, please delete “show” and insert -- shown --, therefor.

At column 9, line 1, please delete “a” and insert -- an --, therefor.

At column 9, line 42, please delete “connected” and insert -- connect --, therefor.

At column 11, line 12, in Claim 1, please delete “patient” and insert -- patient, --, therefor.

At column 11, line 39, Claim 2, please begin a new paragraph after “and” and before “a disposable”.

At column 11, line 41, in Claim 2, please delete “tissue” and insert -- tissue, --, therefor.

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 7,225,007 B2
APPLICATION NO. : 11/172587
DATED : May 29, 2007
INVENTOR(S) : Ammar Al-Ali et al.


Page 2 of 2

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

At column 12, line 14, in Claim 4, please delete "property" and insert
-- properly, --, therefor.

Signed and Sealed this

Twenty-third Day of September, 2008

A handwritten signature in black ink, appearing to read "Jon W. Dudas". The signature is stylized with a large, looped initial "J" and a cursive "Dudas".

JON W. DUDAS
Director of the United States Patent and Trademark Office

专利名称(译)	光学传感器包括一次性和可重复使用的元件		
公开(公告)号	US7225007	公开(公告)日	2007-05-29
申请号	US11/172587	申请日	2005-06-30
[标]申请(专利权)人(译)	AL ALI AMMAR ABDUL HAFIZ亚瑟尔		
申请(专利权)人(译)	AL-ALI AMMAR 阿卜杜勒·哈菲兹亚瑟尔		
当前申请(专利权)人(译)	Masimo公司		
[标]发明人	AL ALI AMMAR ABDUL HAFIZ YASSIR		
发明人	AL-ALI, AMMAR ABDUL-HAFIZ, YASSIR		
IPC分类号	A61B5/00		
CPC分类号	A61B5/14552 A61B5/6826 A61B5/6838 A61B5/6833 Y10T29/49826		
其他公开文献	US20050245797A1		
外部链接	Espacenet USPTO		

摘要(译)

脉搏血氧饱和度传感器包括可重复使用和一次性元件。为了组装传感器，可重复使用的元件在一次性元件的组装机构内被卡扣或滑动。在一个实施例中，可重复使用元件包括突起，而一次性元件包括接收突起的突片。在另一个实施例中，可重复使用的元件包括颈部，并且一次性元件包括接收颈部的带。无论如何，组件提供元件之间的纵向移动。

