



US 20080287754A1

(19) **United States**(12) **Patent Application Publication**
Whan(10) **Pub. No.: US 2008/0287754 A1**(43) **Pub. Date: Nov. 20, 2008**(54) **SYSTEM FOR PROCESSING DECAYING PERIODIC PHYSIOLOGICAL SIGNALS****Publication Classification**(76) Inventor: **Wen Jea Whan**, El Monte, CA (US)(51) **Int. Cl.**
A61B 5/00 (2006.01)(52) **U.S. Cl.** **600/301**


Correspondence Address:

TROXELL LAW OFFICE PLLC
SUITE 1404, 5205 LEESBURG PIKE
FALLSCHURCH, VA 22041 (US)(21) Appl. No.: **12/184,744**(22) Filed: **Aug. 1, 2008****Related U.S. Application Data**

(63) Continuation-in-part of application No. 10/855,839, filed on May 28, 2004.

(57) **ABSTRACT**

A system for processing decaying periodic physiological signals comprises at least a sensor, a physiological signal-digitizing device, and a digital signal processing unit to establish a parameterized database according to P'_i , S'_i , the relationship between P'_i and S'_i , and the change with respect to time or locations of the sensors on the human body for evaluating the physiological or mental conditions. The system is applicable to processing and utilizing the decaying periodic physiological signals, such as heartbeats, respiration and ECG.






Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6

SYSTEM FOR PROCESSING DECAYING PERIODIC PHYSIOLOGICAL SIGNALS

CROSS-REFERENCE TO RELATED DOCUMENTS

[0001] The present invention is a continuation in part (CIP) to a U.S. patent application Ser. No. 10/855,839 entitled "Method and system for processing periodic physiological signals" filed on May 28, 2004.

BACKGROUND OF THE INVENTION

[0002] 1. Field of the Invention

[0003] The present invention is related to a system utilizing the decaying characteristics of periodic physiological signals for decomposing the periodic decaying physiological signals of a human body numerically into series of exponential decays represented by poles P and residuals S as signatures of the physiological and mental conditions of the human body. The present invention is applicable to processing the decaying periodic physiological signals, such as heartbeat, respiration and ECG of a human body.

[0004] 2. Description of the Prior Art

[0005] A healthy human body will naturally have some physiological phenomenon, e.g. heartbeat, respiration and pulses. Long ago, doctors have evaluated health conditions of a person by the symptoms of these physiological phenomena to prevent and cure the disease. Generally, the practitioner of Chinese medicine by feeling the pulse and the doctor practicing western medicine by stethoscopes or hemodynamometers observe the change of heartbeat, pulses and respiration. In this modern time, doctors could collect these periodic signals by electronic devices for primary evaluation.

[0006] Taking heartbeat as an example, the heartbeat of a human body has the feature of regular pattern and repeat appearing. The status of these physiological signals can be measured by sonography or electrocardiography (ECG). Referring to FIG. 1, taking a standard ECG consisted of a serial wave group as an instance. Each wave group representing a heartbeat cycle includes the P-wave, QRS complex, T-wave and U-wave, wherein (1) the P-wave is generated by depolarizing the atrium is the first wave of the periodic wave group and shows the depolarization procedure of left and right atrium. In addition, the individual periodic wave form has the characteristics of decaying.

[0007] (2) The QRS complex includes three waves connected closely, wherein the Q-wave is the first downward wave, the R-wave is an upright high-tip wave after the Q-wave, and the S-wave is downward after the R-wave. In case the three waves are connected closely, they are called as QRS complex and reflect the procedure of depolarizing of left and right ventricles.

[0008] (3) The T-wave located behind the ST segment is a low and long-duration wave and is generated by ventricular repolarization.

[0009] (4) The U-wave located after the T-wave is lower and smaller and is thought to relate to after depolarizations, which interrupt or follow repolarization. Usually the U-wave is neglected of the ECG waveforms.

[0010] Generally ECG waveforms of normal human body have clear and complete wave change. In case the body has abnormal conditions or suffers stimulations, the ECG will show a waveform different from the normal waveforms and it can be used to evaluate the health conditions of human body.

However any figures of physiological signals have to be judged by a doctor with professional training to have a result. If one can know the health conditions without evaluation by the doctor, time will be saved. Further, the physiological conditions of a person will depend on mental conditions, such as excitement, nervousness, or fear. The body will have the phenomenon of increasing heartbeat rate, sweating, and vasoconstriction. It is obvious that the mental conditions can be evaluated by observing any physiological conditions. Further more, every repeating signal decays with respect to time and could be decomposed numerically into poles and residuals. These parameters are proposed to be used as signature for the physical and mental of a human. Similar technologies had been proposed as an advanced weapon detection system which applies the decay for the stimulated eddy current as the signature for different metal weapons (U.S. Pat. No. 6,469,624 on "NON-OBTRUSIVE WEAPON DETECTION SYSTEM", Inventors: Dr. Wen J. Whan and Dr. George V. Keller; U.S. Pat. No. 5,552,705 on "NON-OBTRUSIVE WEAPON DETECTION SYSTEM AND METHOD FOR DISCRIMINATING BETWEEN A CONCEALED WEAPON AND OTHER METAL OBJECTS", Inventor: Dr. George V. Keller.)

[0011] In view of this, the inventor provides a method and a system for processing physiological signals, which take advantage of characters of time decay and periodic performance of the periodic physiological signals to obtain parameters (poles and residual) as signatures of the diseases or abnormal mental conditions.

SUMMARY OF THE INVENTION

[0012] The object of the present invention is to provide a system for processing decaying periodic physiological signals to receive series of physiological signals with respect to time or different sensor locations and to provide an evaluating result by comparing a parameterized database to evaluate the physiological and mental conditions of the human body.

[0013] To achieve the above objects, a system for processing decaying periodic physiological signals according to the present invention is provided and comprises at least a sensor for sensing the periodic physiological signals of a human body and outputting the physiological signals, a physiological signal-digitizing device for receiving and digitizing the physiological signals, and a digitized signals processing unit for digitalizing and decomposing periodic signals D of a human body into poles P and residuals S. And then establishing a parameterized database according to P'_i , S'_i , the relationship between P'_i and S'_i and the change with respect to time or space (locations), and outputting an evaluating result by the parameterized database or original data value to judge the physiological or mental conditions of the human body.

[0014] The present invention will be apparent after reading the detailed description of the preferred embodiments thereof in reference to the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0015] FIG. 1 is a schematic diagram of traditional standard decaying periodic waveforms of ECG;

[0016] FIG. 2 is a schematic view of a system for processing decaying periodic physiological signals of the present invention;

[0017] FIG. 3 is a decaying periodic signal waveform diagram recorded from an ultrasonic detector measuring the heartbeat;

[0018] FIG. 4 is a decaying periodic signals waveform diagram recorded the relative flow rate of blood vessel of thumb in different temperatures by laser Doppler flowmeter;

[0019] FIG. 5 is a three dimension waveform diagram of electromagnetic decaying signals measured by eight receiving coils on the vertical position of the main blood vessel, which is exerted by external periodic electromagnetic waves; and

[0020] FIG. 6 is a schematic view of an embodiment of the present invention of the poles P'_i , S'_i and evaluating results, which are decomposed from the signals of FIG. 5.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

[0021] Firstly, the system for processing decaying periodic physiological signals is depicted in FIG. 2. The system includes at least a sensor 21 for sensing the periodic decaying periodic physiological signals of a human body, a physiological signal-digitizing device 22 for receiving and digitizing the physiological signals, and a digital signal processing unit 23 for digitalizing and decomposing the decaying periodic physiological signals D of a human body into poles P and residuals S, wherein the P represents the decay rate of signals, the S represents the contribution value of the P. By taking j as the serial number of signals, the D^j is periodic signals with different characters, or the same periodic signals in different measuring time or locations. The D^j , P and S satisfy the following formula:

$$D^j = \sum_{i=1}^m S_i^j e^{-P_i^j}$$

Wherein m represents the maximum number of poles from the decaying signals to be decomposed and is collected from a human body. By numerical methods, P'_i , S'_i , the relationship between P'_i and S'_i and the change with respect to time or space (locations) can be established to get a parameterized database 24 for estimating the physiological or mental conditions of the human body and then output an evaluating result 25.

[0022] In addition, the system for processing decaying periodic physiological signals also includes a parameterized database 24 that is established according to P'_i , S'_i , the relationship between P'_i and S'_i and the change with respect to time or locations by the numerical method. Besides, an evaluating unit 25 is provided for outputting an evaluating result for estimating the physiological or mental conditions of said human body.

[0023] The system is also provided with an external stimulator 20 for stimulating the body to generate decaying periodic physiological signals or change the natural decaying periodic physiological signals. In other words, the decaying periodic physiological signals are obtained from said human body exerted by the external stimulator 20 and then the decaying periodic physiological signals can be collected and digitized. The external stimulation generated by said external stimulator 20 includes voltage, electromagnetic waves, ultrasonic waves, heat, or pressure.

[0024] Moreover, the value of P'_i or S'_i can be used as the signatures of the physiological or mental conditions of said human body.

[0025] Furthermore, the digital signals processing unit 23 includes a first, a second, and a third calculating unit 232, 234, 236.

[0026] The first calculating unit 232 is used for calculating ratios or statistic patterns between P'_i and S'_i as signatures of the physiological or mental conditions of said human body.

[0027] The second calculating unit 234 is used for calculating the change with respect to time or locations for P'_i or S'_i as signatures of the physiological or mental conditions of said human body.

[0028] The third calculating unit 236 is used for calculating the change with respect to time or locations for ratio and statistical patterns of P'_i and S'_i as signatures of the physiological or mental conditions of said human body.

[0029] Then take a specific physiological signal as an embodiment of the present invention. Use an ultrasonic detector as the sensor 21 to measure a subject's heartbeats to obtain a heartbeat ultrasonic waveform diagram as shown in FIG. 3. Setting the range of physiological signals from point (a) to point (b), which shows five decaying signals and transferring the signals between these two points to physiological signal-digitizing device 22 to obtain digitized decaying periodic physiological signals D. Then transferring the digitized signals to digital signal processing unit 23 to decompose D into the poles P and the residuals S by the numerical method and the D^j , P and S can satisfy the following formula:

$$D^j = \sum_{i=1}^m S_i^j e^{-P_i^j}$$

[0030] Wherein m represents the maximum number of poles from the decaying signals to be decomposed and is collected from a human body. The P value is larger; the decreasing rate is faster. Further calculating the relationship between the P'_i and S'_i or the relationship between the P'_i and S'_i and the change with respect to time/locations by a calculating unit and comparing those with a pre-determined parameterized database 24 by the evaluating unit 25 could get an evaluating result of the physiological or mental conditions of a human body to show the subject's health conditions.

[0031] If the parameterized database hasn't been established, following the above-mentioned method to measure enough healthy subjects in statistics and analyzing the physiological signals of the subjects to establish a parameterized database 24. Store the database 24 in the system of the present invention for the reference of evaluating the healthy conditions. The database 24 can be input be the parameterized data, e.g. gender, heights or weight to raise the accuracy of the database 24.

[0032] Besides, the system includes physiological signals of different measuring conditions. For example, taking laser Doppler flowmeter as a sensor 21 can measure the relative flow rate of the blood vessel of thumb in different temperatures and obtain a diagram shown in FIG. 4, wherein the control is a white object. Measuring the physiological signals in unheated conditions and in heated conditions respectively and applying the digitized signals processing unit 23 to analyze and resort the signals to further establish the physiological reference data in different measuring conditions.

[0033] The present invention is suitable for evaluating physiological signals with different characters. For example, taking the electrocardiograph as a sensor **21** of the system to detect heartbeat of a human body, and applying the system mentioned above to digitize and decompose the physiological signals to store the P_i^j , S_i^j and time/locations in the digitized signals processing unit **23** and compare those with the ultrasonic data of heartbeats mentioned above to further obtain the physiological and mental conditions of a human body.

[0034] The present invention not only measure the physiological signals from a human body under normal conditions, but also can evaluate the health conditions when a human body is exerted by an external stimulation from the external stimulator **20**. The external stimulation can generate decaying periodic physiological signals or change the natural decaying periodic physiological signals. The external stimulation can be voltage, electromagnetic waves, ultrasonic waves, heat, pressure, acupuncture, etc. For example, by stimulating external periodic stepwise electromagnetic waves, the main blood vessel is positioned with eight receiving coils. The decay signals of electromagnetic field generated by Eddy current are shown in FIG. 5. The poles P_i^j and residuals S_i^j decomposed from the signals D are shown in FIG. 6 labeled as **60**. Then comparing these values with the pre-determined parameterized database **24** could obtain an evaluating result of physiological or mental conditions of a human body. The evaluation result shown in FIG. 6 labeled as **61** can indicate the health level of the tested person.

[0035] The foregoing description of the preferred embodiments of this invention has been presented for purposes of illustration and description. It is not intended to be exhaustive or to limit the invention to the precise form disclosed, and obviously, many modifications and variations are possible. Such modifications and variations that may be apparent to a person skilled in the art are intended to be included within the scope of this invention.

[0036] Thus, the present invention has following advantages:

[0037] 1. The present invention not only can be used as analysis of single physiological signals, but also can analyze composite physiological signals to raise the accuracy of evaluation.

[0038] 2. By using the present invention to evaluate body conditions, it is controlled by electronic devices without judging by a doctor and is convenient for operating to figure out the health conditions.

[0039] 3. Because the different measuring conditions will result in different conclusions, operators can input parameters with different terms, e.g. heights, weights, external stimulations or temperatures, and then the parameterized database can make the results more accurately.

[0040] The system for processing decaying periodic physiological signals not only offer the evaluation of physiological conditions but also offer the evaluation of mental conditions. The practitioner of Chinese medicine by feeling the pulse and the doctor practicing western medicine by stethoscopes or hemodynamometers observe the change of heartbeat, pulses and respiration. In this modern time, doctors could collect these periodic signals by electronic devices for primary evaluation. By using this invention, the changes of the decaying periodic signal will be presented in a scientific and therefore more accurate way.

[0041] As stated in the above disclosed, the present invention can surely achieve its expected objects to provide a

system for processing decaying periodic physiological signals for the public or the medical personnel to evaluate the health conditions. It has its industrial practical value.

Having thus described my invention, what I claim as new and desire to be secured by Letters Patent of the United States are:

1. A system for processing decaying periodic physiological signals including:

- a at least a sensor, for sensing the decaying periodic physiological signals of a human body;
- a physiological signal-digitizing device, for receiving and digitizing the decaying periodic physiological signals; and
- a digital signals processing unit, for digitalizing and decomposing decaying periodic physiological signals D of the human body into poles P and residuals S , wherein the poles P represent the decay rate of signals, the residuals S represent the contribution value of the P , and by taking j as the serial number of signals, D^j represent periodic signals with different characters, or the same periodic signals in different measuring time or locations, and D^j , P and S satisfy the following formula:

$$D^j = \sum_{i=1}^m S_i^j e^{-P_i^j}$$

wherein m represents the maximum number of poles from the decaying periodic physiological signals to be decomposed and is collected from a human body, P_i^j represents the i^{th} pole of the j^{th} periodic human signals or j^{th} location of the sensor, and S_i^j represents the contribution value or residual value of the pole; thus, obtaining the values of the poles P_i^j and residuals S_i^j by decomposing the decaying periodic physiological signals by using a numerical method.

2. The system for processing decaying periodic physiological signals according to claim 1 further comprising a parameterized database that is established according to P_i^j , S_i^j , the relationship between P_i^j and S_i^j and the change with respect to time or locations by the numerical method.

3. The system for processing decaying periodic physiological signals according to claim 1 further comprising an evaluating unit for receiving the data from the parameterized database and for outputting an evaluating result for estimating the physiological or mental conditions of said human body.

4. The system for processing decaying periodic physiological signals according to claim 1 further comprising an external stimulator for stimulating the body to generate decaying periodic physiological signals or change the natural decaying periodic physiological signals, wherein the decaying periodic physiological signals are obtained from said human body exerted by the external stimulator and then the decaying periodic physiological signals are collected and digitized.

5. The system for processing decaying periodic physiological signals according to claim 4, wherein the external stimulation generated by said external stimulator includes voltage, electromagnetic waves, ultrasonic waves, heat, or pressure.

6. The system for processing decaying periodic physiological signals according to claim 1, wherein the value of P_i^j or S_i^j are used as the signatures of the physiological or mental conditions of said human body.

7. The system for processing decaying periodic physiological signals according to claim 1, wherein the digital signals processing unit further comprises a first calculating unit for

calculating ratios or statistic patterns between P_i^j and S_i^j as signatures of the physiological or mental conditions of said human body.

8. The system for processing decaying periodic physiological signals according to claim 1, wherein the digital signals processing unit further comprises a second calculating unit for calculating the change with respect to time or locations for P_i^j or S_i^j as signatures of the physiological or mental conditions of said human body.

9. The system for processing decaying periodic physiological signals according to claim 1, wherein the digital signals processing unit further comprises a third calculating unit for calculating the change with respect to time or locations for ratio and statistical patterns of P_i^j and S_i^j as signatures of the physiological or mental conditions of said human body.

* * * * *

专利名称(译)	处理腐朽周期生理信号的系统		
公开(公告)号	US20080287754A1	公开(公告)日	2008-11-20
申请号	US12/184744	申请日	2008-08-01
[标]申请(专利权)人(译)	WHAN文JEA		
申请(专利权)人(译)	WHAN文JEA		
当前申请(专利权)人(译)	WHAN文JEA		
[标]发明人	WHAN WEN JEA		
发明人	WHAN, WEN JEA		
IPC分类号	A61B5/00		
CPC分类号	A61B5/04017 G06K9/00523		
外部链接	Espacenet USPTO		

摘要(译)

用于处理衰减的周期性生理信号的系统至少包括传感器，生理信号数字化装置和数字信号处理单元，以根据 P_{ji} ， S_{ji} 建立参数化数据库， P_{ji} 和 S_{ji} 之间的关系以及相对于 P_{ji} 和 S_{ji} 的变化。传感器在人体上的时间或位置，用于评估生理或精神状况。该系统适用于处理和利用衰减的周期性生理信号，如心跳，呼吸和心电图。

