






US 20070179568A1

(19) **United States**(12) **Patent Application Publication** (10) **Pub. No.: US 2007/0179568 A1****Nycz et al.**(43) **Pub. Date: Aug. 2, 2007**(54) **METHODS FOR DETECTING OSTEOLYTIC CONDITIONS IN THE BODY**(22) Filed: **Jan. 31, 2006****Publication Classification**(75) Inventors: **Jeffrey H. Nycz**, Collierville, TN (US);
Susan J. Drapeau, Cordova, TN (US);
William T. Donofrio, Andover, MN (US)Correspondence Address:
HAYNES AND BOONE, LLP
901 MAIN ST
SUITE 3100
DALLAS, TX 75202 (US)(51) **Int. Cl.**
A61B 5/117 (2006.01)
A61B 5/103 (2006.01)
A61B 5/00 (2006.01)
A61N 1/00 (2006.01)
A61F 2/32 (2006.01)
A61B 5/05 (2006.01)(52) **U.S. Cl.** **607/60; 623/22.12; 600/587; 600/549; 600/348; 600/361**(73) Assignee: **SDGI Holdings, Inc.**, Wilmington, DE(21) Appl. No.: **11/344,459**(57) **ABSTRACT**

Methods and systems for detecting a biological response indicative of osteolysis or osteolytic pre-conditions in bone.








Fig. 2B




Fig. 3A











Fig. 3B





METHODS FOR DETECTING OSTEOLYTIC CONDITIONS IN THE BODY

BACKGROUND OF THE INVENTION

[0001] The present disclosure relates generally to methods and devices for detecting osteolytic conditions or pre-conditions in the body.

[0002] Human joints, such as the knee, shoulder, elbow, hip, and vertebral joints can be replaced by prostheses or implants. Such prostheses can be fixed to surrounding bone by bone ingrowth into the implant or external features that extend into the bone. Additionally, implants can be fixed in the bone with a cement agent, such as polymethylmethacrylate.

[0003] It has been determined that the debris created by the wearing of a prosthetic implant may contribute to local bone destruction and osteolysis. Unfortunately, it is difficult to detect the synthetic debris particles and/or their concentration in the body.

[0004] Loosening of the boney attachment to the implant or the cement agent and/or material debris from the wear of the prosthetic itself can cause additional problems for the patient. Thus, there remains a need for improvements in the detection of conditions that may impact bone quality.

SUMMARY OF THE INVENTION

[0005] According to certain embodiments described herein, a detection system for detecting a condition in a bone is provided.

[0006] According to one embodiment, a detection system includes an in vivo sensor, which is operable to detect a condition of a bone, and generate a signal representative of the detected condition. The sensor may detect a condition present in the bone, or adjacent to the bone.

[0007] In one embodiment, the detection system further includes a transmitter, which is operable to receive the signal from the sensor and transmit the signal. In a further embodiment, the detection system further comprises a receiver, which is operable to receive the signal from the transmitter and to enable a human intelligible display representative of the signal.

[0008] In still another embodiment, the detection system further comprises a signal processor, which is operable to receive a signal from the sensor and to transmit the signal, and a transmitter, which is operable to receive the signal from the signal processor and to transmit the signal. In a further embodiment, the detection system includes a receiver, which is operable to receive the signal from the transmitter. According to one such embodiment, the receiver includes another signal processor, which is operable to receive the signal from the receiver and to transmit the signal, and an indicator, which is operable to receive the signal from the second signal processor and enable a human intelligible display representative of the signal.

[0009] According to still other embodiments described herein, a method of detecting a condition of a bone is provided. According to one such embodiment, the method includes disposing a sensor in or adjacent to the bone, obtaining data from the sensor representative of at least one condition selected from temperature, pH, a presence of

inflammatory cytokines, a presence of matrix metalloproteinases (MMPs), a presence of calcium ions and a presence of phosphate ions, and displaying the data in a human intelligible form.

[0010] The disclosure can be more clearly understood by reference to the following drawings, which illustrate exemplary embodiments thereof, and which are not intended to limit the scope of the appended claims.

BRIEF DESCRIPTION OF DRAWINGS

[0011] FIG. 1 is a schematic of one embodiment of a detection system as described herein.

[0012] FIG. 2A is a front view of another embodiment of a detection system as described herein, which system is in use in an area where a hip prosthesis has been implanted.

[0013] FIG. 2B is a front view of another embodiment of a detection system as described herein, which system is in use in an area where a hip prosthesis has been implanted.

[0014] FIG. 3A is a front view of yet another embodiment of a detection system as described herein, which system is in use in an area where a hip prosthesis has been implanted.

[0015] FIG. 3B is a front view of still another embodiment of a detection system as described herein, which system is in use in an area where a hip prosthesis has been implanted.

[0016] FIG. 4A is an enlarged front view of one embodiment of a hip prosthesis.

[0017] FIG. 4B is an enlarged side view of one embodiment of a sensor suitable for use in a detection system, such as the detection systems illustrated in FIGS. 2 and 3.

[0018] FIG. 4C is an enlarged cross-sectional side view of the sensor illustrated in FIG. 4B, engaging the hip prosthesis illustrated in FIG. 4A and adjacent bone.

[0019] FIG. 5A is an enlarged front view of another embodiment of a hip prosthesis.

[0020] FIG. 5B is an enlarged side view of another embodiment of a sensor suitable for use in a detection system, such as the detection systems illustrated in FIGS. 2 and 3.

[0021] FIG. 5C is an enlarged cross-sectional side view of the sensor illustrated in FIG. 5B, engaging the hip prosthesis illustrated in FIG. 5A and adjacent bone.

[0022] FIG. 6 is an enlarged cross sectional view of another embodiment of a sensor suitable for use in a detection system as described herein, which sensor is disposed on an external surface of a prosthesis.

[0023] The disclosure can be more clearly understood by reference to some of its specific embodiments, described in detail below, which description is not intended to limit the scope of the claims in any way.

DETAILED DESCRIPTION

[0024] Referring now to FIG. 1, one embodiment of a system for detecting a condition in the body according to the present disclosure is illustrated.

[0025] According to the embodiment illustrated in FIG. 1, a detection system 100 comprises a sensor 105, a signal

processor 107, and a transmitter 115. The sensor 105 and the signal processor 107 are communicatively coupled by communication means 108, and the signal processor 107 and the transmitter 115 are communicatively coupled by communication means 110. Communication means 108 and 110 can be wired or wireless, as will be discussed further herein. In certain embodiments, signal processor 107 could contain a memory unit, or could be communicatively coupled to a memory unit. As will be discussed further herein, a memory unit would store data received from the signal processor.

[0026] For ease of reference, the sensor 105, signal processor 107, and transmitter 115, are illustrated separately in FIG. 1, and are discussed as separate units herein. However, it is fully contemplated that the functions of each may be combined into a single component or distributed among a plurality of components.

[0027] Sensor 105 is designed for implantation into the body of a patient. In some embodiments, sensor 105 is disposed adjacent to a prosthesis, such as a hip, knee, shoulder, wrist, jaw or vertebral implant. In some such embodiments, sensor 105 is physically associated with the prosthesis, for example, such as described in FIGS. 4-6. In other embodiments, sensor 105 is not physically associated with the prosthesis. For example, sensor 105 could be engaged in bone or embedded in soft tissue in the proximity of the prosthesis.

[0028] Sensor 105 is operable to detect conditions in bone associated with osteolysis occurring in the bone, or conditions in the bone indicative of an early onset of osteolysis ("osteolytic pre-conditions"). For example, an increase in temperature in the bone, an increase in the pH level of the bone, the presence of inflammatory cytokines (for example, TNF, IL-1, and IL-6), and the presence of certain analytes are associated with osteolysis and/or osteolytic pre-conditions. Analytes associated with osteolysis and/or osteolytic pre-conditions may include calcium ions and/or phosphate ions. Other analytes associated with osteolysis and/or osteolytic pre-conditions may include bone degradation products such as matrix metalloproteinases (MMPs), or similar bone degradation products. Still other analytes associated with osteolysis and/or osteolytic pre-conditions may include particular genes, proteins, chemicals, bacterial or similar biological substances.

[0029] Thus, a detection system as described herein could include a sensor or a plurality of sensors operable to detect one or more of a temperature increase, a pH increase, the presence of inflammatory cytokines, or the presence of a selected analyte. Accordingly, in certain embodiments, sensor 105 can be one or more of a temperature sensor (e.g., a thermocouple or a thermister), a pH sensor, a biosensor operable to detect the presence of calcium ions, a biosensor operable to detect bone degradation products or signals indicative of bone degradation, such as matrix metalloproteinases (MMPs) or similar molecules, or an in vivo assay operable to detect the presence of inflammatory cytokines. One type of pH sensor suitable for use in the detection system described herein is an iridium oxide based potentiometric electrode sold by SensiOx Inc. Fiber optic pH sensors should also be suitable. As yet another example, sensors operable to detect the presence of ions such as calcium or phosphate could have a permeable membrane selective to the ion to be detected.

[0030] Sensor 105 will detect one or more of temperature, pH, the presence of inflammatory cytokines or the presence of an analyte, and will transmit a corresponding signal to the signal processor 107. In certain embodiments, the signal processor will receive signals from the sensor for an initial period in order to generate a baseline representative of the detected condition (e.g., a baseline for temperature, pH, presence of an analyte). After a baseline has been established, then the signal processor 107 will continue to receive signals from the sensor 105. If the signal received deviates from the baseline, then the signal processor sends a deviation signal to the transmitter 115 indicating a deviation from the baseline.

[0031] In an embodiment in which the signal processor includes or is coupled to a memory unit, data representative of the baseline can be stored. In a further embodiment, the memory unit may be configured to store data it receives from the signal processor that is either outside the normal signal range or within the range of signals being detected. In yet another embodiment, a memory unit may store data such as a timestamp of the signal, the specific characteristics of the signal, or any other relevant data. It is fully contemplated that a memory unit may utilize known compression algorithms and functions to save on memory and size requirements.

[0032] In addition, it is contemplated that two or more sensors may be used to verify readings and account for potential hardware failures in the system. The plurality of sensors may generate an aggregate baseline and deviations by one or more sensors from the aggregate baseline may cause the system to generate the deviation signal.

[0033] In other embodiments, control sensors could be positioned at locations remote from the area of interest where sensor 105 would be positioned. Signals indicative of temperature, pH, presence of inflammatory cytokines, and/or presence of analytes generated by the control sensors could be wirelessly sent to the signal processor, where the signals could be compared to signals generated by sensor 105. If the signals generated by sensor 105 deviate from the signals generated by control sensors, then the signal processor would send a signal to the transmitter 115. In still other embodiments, all signals generated by the sensor 105 are processed through the transmitter 115 without screening by the signal processor.

[0034] Transmitter 115 is adapted for receiving signals from the signal processor 107 via communication means 110. Transmitter 115 is also adapted for transmitting a signal representative of the signal received from the signal processor to a receiver 125 via communication means 129. In certain embodiments as will be discussed further with respect to FIG. 2A, receiver 125 is located outside of the patient's body, while in other embodiments, as will be discussed further with respect to FIG. 2B, receiver 125 is located within the patient's body.

[0035] Referring still to FIG. 1, in certain embodiments, communication means 129 are adapted for communicating wirelessly with communication means 130 of receiver 125. There are several types of wireless telemetry circuits that may be employed for communication means 110, 129 and 130. For example, RF, such as RFID; inductive telemetry; acoustic energy; near infrared energy; "Bluetooth"; and computer networks are all possible means of wireless com-

munication. In one embodiment, communication means **129** and **130** are adapted for RFID communication such that communication means **129** is a passive RFID tag. Using a passive RFID tag helps limit the power requirements of communication means **129**, yet still allows wireless communication to receiver **125**.

[0036] In other embodiments, the transmitter comprises a modulator/transmitter that converts the voltage signal received from the sensor into a transmission signal, and transmits the converted signal to the receiver. While the specific characteristics of the internal modulator/transmitter may vary, the components will be appropriate for implantation within a patient, and will transmit a signal through the patient's body, including surrounding tissues, to the receiver.

[0037] Detection system **100** further comprises a power source **120**, which is electrically connected to one or more of the sensor **105**, the signal processor **107**, the communication means **108**, **110** or **129**, and the transmitter **115**. The sensor **105** can be directly electrically connected to the power source **120**, or can be connected through the transmitter **115**. Sensor **105** and communication means **110** may use the power source **120** to facilitate the sending of signals to the transmitter **115**. Transmitter **115** may use the power source to convert signals received from the signal processor, and/or to transmit signals received from the signal processor to the receiver.

[0038] In some embodiments, power source **120** comprises a battery, for example, a lithium iodine battery similar to those used for other medical implant devices such as pacemakers. However, any type of battery suitable for implantation can be used. It is also fully contemplated that the power source **120** may include a plurality of batteries or rechargeable batteries. In other embodiments, power source **120** may comprise a passive power supply, such as the type of power supply used in RFID tags.

[0039] In still other embodiments, the detection system may be externally powered by inductive coupling or other transmissive means from an external power supply. The detection system may also be powered by capacitor arrays, or one or more capacitors, which store the energy received from an external power supply. Additionally or alternatively, the detection system may only operate when the external power supply is energizing the system, and may be in a dormant condition when not receiving power from the external power supply.

[0040] Referring still to FIG. 1, a receiver **125** is adapted for receiving and displaying, in human intelligible form, information received from transmitter **115**. Receiver **125** comprises communication means **130**, a signal processor **135**, and an indicator **140**. In the embodiment illustrated in FIG. 1, a power supply **145** supplies power to any electrical components of the receiver **125**. Such an embodiment would be preferred if the receiver is external to the patient's body, i.e., if the receiver is "ex vivo". In an embodiment where the receiver is internal to the patient's body ("in vivo"), the receiver can be powered from the same power supply as the sensor, signal processor, etc., or can be powered from a separate power supply such as is illustrated by power supply **145**, which would also be located inside the patient's body.

[0041] The communication means **130** of the receiver **125** are adapted for wireless communication with the transmitter

115. Once a signal is received from the transmitter **115** by communication means **130**, it is processed by processor **135**, which is adapted for converting the signal into a form that may be utilized by indicator **140**.

[0042] In some embodiments, the processor **135** further comprises analysis circuitry operable to evaluate the incoming signals from the transmitter **115**, and determine a course of action based on those signals. For instance, the analysis circuitry can include a comparator circuit, in which the received signal is compared to a threshold value, for example, a predetermined temperature or pH. If the incoming signal exceeds the threshold value, the analysis circuit can send data to the indicator **140** or to any other display device.

[0043] Indicator **140** may be any type of device or interface that can output the data in human intelligible form, and may be composed of a plurality of output mechanisms or a single device. In certain embodiments, the indicator may be a visual display, such as a number representative of temperature or pH, a color based on temperature or pH (e.g., green for a "normal" temperature or pH, yellow for temperature or pH with moderate deviation from "normal", and red for temperature or pH indicative of the presence or onset of osteolysis), or any other visual display indicative of the desired data. For example, in an embodiment where the receiver is in vivo, at least the indicator portion of the receiver can be implanted close to the surface of the skin, such that a color can be visually observed through the skin. In an embodiment where the receiver is ex vivo, then the indicator could simply display a color.

[0044] As another example, the indicator may be a speaker. Where the indicator is a speaker it could do such things as beep or audibly speak a message representing "normal" conditions in the bone, or conditions indicative of the presence or onset of osteolysis. In an embodiment where the receiver is internal to the patient's body, at least the indicator portion of the receiver could be implanted close to the surface of the skin, such that sound generated by the indicator could be heard.

[0045] In certain embodiments, the receiver may also include a memory unit, which may be adapted for permanent or temporary storage of data obtained by the detection system. Thus, the memory unit may store data obtained at various times so that the data may later be reviewed, compared, or analyzed.

[0046] It is also contemplated that the processing performed by the processor **135** may only be a first step of processing. The processed data of the processor **135** may be output to a more powerful or specialized processing unit (not shown) where additional processing takes place. This second processing unit may be located either in the receiver itself or in a separate device such as a personal computer.

[0047] According to one such example, the data may be transferred from the processor **135** via a networking interface to a network or computer for permanent storage. The type of network utilized may include such communication means as telephone networks, computer networks, or any other means of communicating data electronically. The networking interface could obviate the need for the patient to even go into the doctor's office for obtaining conditional data on an implant. For example, the patient could obtain

such data on a scheduled basis (e.g. daily, weekly, monthly, etc.). Then, utilizing the networking interface the patient could send this data to the treating doctor. The networking interface may be configured to directly access a communication network such as a telephone or computer network for transferring the data. It is fully contemplated that the computer network be accessible by a treating physician for reviewing received data without requiring the patient to make an actual visit to the doctor's office. In this regard, it is also contemplated that any communication between the receiver and the computer network may be encrypted or otherwise secured so as to protect the patient's privacy.

[0048] It is also contemplated that the networking interface may be configured for communication with a separate device that is adapted for accessing the communication network. For example, the networking interface may be a USB connection. In an embodiment where the receiver is *ex vivo*, the receiver may be connected to a personal computer via the USB connection. The personal computer may then be utilized to connect to the communication network, such as the Internet, for transferring the data to a designated place where a treating doctor may receive it.

[0049] In some embodiments, receiver 125 can be secured on the patient, for example, strapped to an arm, leg, or the waist. In other embodiments, receiver 125 can merely be in the patient's vicinity, for example inches or feet away from the patient, as long as the broadcast range of the transmitter 115 is sufficient for receipt of signals by the receiver. In other embodiments, receiver 125 could be at a location remote from the patient, for example, a doctor's office. According to one such embodiment, the detection system could be activated only intermittently, for example, during a visit to the doctor's office. In this case, the power source for the detection system could be passive, such that it is activated by the receiver. The doctor can read data displayed by an indicator in the receiver in his or her office to determine whether signals indicative of osteolysis or an osteolytic pre-condition have been generated.

[0050] Referring now to FIG. 2A, a detection system that combines the functions of the sensor 105, signal processor 107 communications means 110, transmitter 115, communications means 129, and power source 120 described in FIG. 1 into a unitary sensor 305, is illustrated in use with a hip implant 200. A memory unit could also be combined into the unitary sensor 105, either as a separate component, or within the signal processor.

[0051] Hip implant 200 includes an acetabular component 205, which is configured for engagement with a prepared portion of the patient's acetabulum 206, and a femoral component 210, which comprises a head 212 and a stem 214. The femoral head 212 is configured for movable engagement with the acetabular component 205, so as to create ball-in-socket motion. The femoral stem 214 is adapted for engaging a proximal portion 215 of the patient's femur 216.

[0052] In the embodiment illustrated in FIG. 2A, a unitary sensor 305 is disposed adjacent to the acetabular component 205 of the hip implant 200. In other embodiments, unitary sensor 305 may be disposed adjacent the femoral stem 214 of the hip implant 200. In still other embodiments, unitary sensor 305 may be disposed at a plurality of locations including, but not limited to, in the bone, on the surface of

the bone, near the bone, integral to an artificial joint, adjacent to an artificial joint, or near an artificial joint. The precise locations available for placement of a sensor such as unitary sensor 305 or sensor 105 may depend at least in part on the type of sensor being utilized.

[0053] Unitary sensor 305 is configured to detect and/or keep track of indicators associated with osteolytic conditions or osteolytic pre-conditions in the bone, such as temperature increases, pH increases, presence of inflammatory cytokines, and presence of certain analytes as described above.

[0054] In the embodiment illustrated in FIG. 2A, unitary sensor 305 is in wireless communication with an external receiver 325a. External receiver 325a is configured for wireless communication with the unitary sensor 305, and is adapted for retrieving and displaying, in human intelligible form, the data gathered by the unitary sensor 305.

[0055] Referring now to FIG. 2B, another embodiment of a detection system having a unitary sensor is illustrated. The embodiment illustrated in FIG. 2B is identical to the embodiment illustrated in FIG. 2A, with the exception of the receiver. According to the embodiment illustrated in FIG. 2B, the receiver is an internal receiver 325b, which has been implanted into the patient's body at a location near the surface of the skin. Internal receiver 325b can be embedded in soft tissue, affixed to bone, or engaged in bone, at any location that allows for the data gathered by the unitary sensor 305 to be displayed in human intelligible form. In the embodiment illustrated in FIG. 2B, it is contemplated that communication from the unitary sensor 305 to the internal receiver 325b would be wireless, however, the internal receiver 325b and the unitary sensor 305 could be wired for communication.

[0056] Referring now to FIG. 3A, another embodiment of a detection system in use with a hip implant 500 is illustrated. Hip implant 500 includes an acetabular component 505, which is configured for engagement with a prepared portion of the patient's acetabulum 506, and a femoral component 510, which comprises a head 512 and a stem 514. The femoral head 512 is configured for movable engagement with the acetabular component 505, so as to create ball-in-socket motion. The femoral stem 514 is adapted for engaging a proximal portion 515 of the patient's femur 516.

[0057] A sensor 405 is disposed adjacent to the acetabular component 505, and is communicatively coupled to a transmitter 415 by internal wiring 406. The transmitter 415 is operable to receive signals from the sensor 405 indicative of osteolytic conditions or osteolytic pre-conditions in the bone, such as temperature increases, pH increases, presence of inflammatory cytokines, and presence of certain analytes, and to transmit an output signal indicative of the received signal. A power source 420 is electrically connected to the transmitter 415 to provide electrical power to the transmitter and the sensor via wiring 416. Transmitter 415 and power source 416 may be provided in a small package and positioned in soft tissue adjacent to the hip.

[0058] In the embodiment illustrated in FIG. 3A, an external receiver 425a is configured for wireless communication with the transmitter 415. In particular, external receiver 425a will receive output signals from the transmitter and display data representative of the received signals.

[0059] Referring now to FIG. 3B, another embodiment of a detection system is illustrated. The embodiment illustrated in FIG. 3B is identical to the embodiment illustrated in FIG. 3A, with the exception of the receiver. According to the embodiment illustrated in FIG. 3B, the receiver is an internal receiver 425b, which has been implanted into the patient's body at a location near the surface of the skin. Internal receiver 425b can be embedded in soft tissue, affixed to bone, or engaged in bone, at any location that allows for the data received from the transmitter 415 to be displayed in human intelligible form. In the embodiment illustrated in FIG. 3B, it is contemplated that communication from the transmitter 415 to the internal receiver 425b would be wireless, however, the internal receiver 425b and the transmitter 415 could be wired for communication.

[0060] In the embodiments illustrated in FIGS. 2A, 2B, 3A and 3B, the sensor of the detection system is located adjacent to the acetabular component of the hip implant. Alternatively, the sensor could be located adjacent the femoral component of the hip implant. In either embodiment, the sensor should be situated such that it is close enough to the bone surrounding the implant to detect a biological response (e.g., temperature, pH, presence of inflammatory cytokine, presence of an analyte) indicative of osteolysis or an osteolytic pre-condition. For example, in certain embodiments employing a pH sensor, the pH sensor could be in contact with the tissue of the bone surrounding the implant.

[0061] As described above, a sensor of a detection system as described herein may be disposed at a plurality of locations including, but not limited to, in the bone, on the surface of the bone, near the bone, integral to an artificial joint, adjacent to an artificial joint, or near an artificial joint. For example, the sensor of the detection system can be disposed on the exterior surface of the implant, either protruding therefrom, flush therewith, or embedded in a groove therein, and then engaged with or positioned adjacent the bone surrounding the implant so that the sensor can detect conditions indicative of osteolysis or an osteolytic pre-condition in the bone. In other embodiments, the sensor can be embedded in soft tissue surrounding the bone, or can be tethered so that it has some degree of movement, but will stay within proximity of the bone of interest.

[0062] In still other embodiments, the sensor can be directly engaged in bone surrounding an implant, for example, the sensor may be threaded and screwed into the bone, or may be secured to the bone by plates and/or spikes.

[0063] Referring now to FIGS. 4A-4C, one embodiment for locating a sensor in a detection system as described herein is illustrated. FIG. 4A illustrates an acetabular component 30 of a hip implant having an opening 50 adapted to engage an insertion tool for driving the component into position. Opening 50 includes an internal flange 52 of reduced diameter. The acetabular component 30 also has a substantially spherical internal surface 40 and an exterior surface 42.

[0064] FIG. 4B illustrates a sensor 308, having a main body 310, a bone engaging portion 314, a head portion 312, and an implant engaging portion 318. The bone engaging portion 314 is adapted for being disposed within bone. To facilitate bone engagement, the exterior of the sensor may include threads 316 configured such that the sensor 308 can

be screwed into engagement with bone. Implant engaging portion 318 is adapted for engaging internal flange 52 of opening 50 of the acetabular component 30. The inner surface 40 of the acetabular component 30 is adapted for movably engaging a femoral head (not illustrated) of the hip implant. Flange portion 52 is recessed with respect to inner surface 40 of the acetabular component 30 so that when implant engaging portion 318 is engaged with flange 52, the head 312 substantially aligns with inner surface 40 and does not inhibit movable engagement between the femoral head and the inner surface.

[0065] FIG. 4C illustrates sensor 308 engaged with the bone 10 and the acetabular component 205. External surface 42 of the acetabular component 30 also engages the bone 10.

[0066] Referring now to FIGS. 5A-5C, another embodiment for locating a sensor in a detection system as described herein is illustrated. The sensor 605 includes a main body 610, an implant engaging portion 612, and a bone engaging portion 614, which, in certain embodiments, may be substantially similar to a bone nail. The implant engaging portion 612 includes threads 616, which are adapted for engaging a threaded portion of an implant. For example, threads 616 may be adapted for engaging a threaded driver portion 60 of an acetabular component 205. An inner surface 44 of an acetabular component 46 is adapted for movable engagement with a femoral head (not illustrated) of a hip implant. The implant engagement portion 612 and the threaded driver portion 60 are configured such that when the two portions are threaded together the movable engagement between the femoral head and the inner surface 44 is not inhibited. FIG. 5C shows sensor 605 engaged with the bone 10 and the acetabular component 46. An external surface 48 of the acetabular component 46 also engages the bone.

[0067] Referring now to FIG. 6, yet another embodiment for locating a sensor in a detection system as described herein is illustrated. FIG. 6 illustrates a sensor 705, attached at a surface 706 to a surface 708 of an acetabular component 710 of a hip implant. The opposing surface 712 of the sensor 707 is adapted for engaging adjacent bone, or physical contact with adjacent bone. It is contemplated that the sensor 707 may be associated with surface 706 without being fixedly mounted. However, it is also contemplated that the sensor 707 may be attached to the surface 706 by any reliable means. In some embodiments, the sensor 707 can be attached to the surface 706 of the acetabular component 710 by a polymethylmethacrylate (PMMA) cement, cyanoacrylate, fibrin glue, or other biocompatible glues.

[0068] Although the figures provided illustrate a detection system in use with a hip implant, a detection system as described herein could also be used with a knee implant, vertebral implant, shoulder implant, etc. Moreover, although only a few exemplary embodiments have been described in detail above, those skilled in the art will readily appreciate that many modifications are possible in the exemplary embodiments without materially departing from the novel teachings and advantages of this disclosure. Accordingly, all such modifications and alternatives are intended to be included within the scope of the invention as defined in the following claims. Those skilled in the art should also realize that such modifications and equivalent constructions or methods do not depart from the spirit and scope of the present disclosure, and that they may make various changes,

substitutions, and alterations herein without departing from the spirit and scope of the present disclosure. It is understood that all spatial references, such as “horizontal,” “vertical,” “top,” “inner,” “outer,” “bottom,” “left,” “right,” “anterior,” “posterior,” “superior,” “inferior,” “upper,” and “lower” are for illustrative purposes only and can be varied within the scope of the disclosure. In the claims, means-plus-function clauses are intended to cover the elements described herein as performing the recited function and not only structural equivalents, but also equivalent elements.

What is claimed is:

1. A detection system for detecting a condition of a bone comprising:

a sensor capable of operating in vivo to detect a condition of a bone and generate a signal representative of the detected condition;

a transmitter operable to receive the signal from the sensor and transmit the signal; and

a receiver operable to receive the signal from the transmitter and to enable a human intelligible display representative of the signal.

2. The detection system of claim 1 wherein the condition detected is present in the bone.

3. The detection system of claim 1 wherein the condition detected is adjacent to the bone.

4. The detection system of claim 1 wherein the sensor is operable to detect at least one of temperature, pH, inflammatory cytokines, MMPs, calcium ions and phosphate ions.

5. The detection system of claim 1 further comprising:

a signal processor operable to receive signals from the sensor and to generate a baseline representative of the detected condition, and to send a signal to the transmitter when a signal received from the sensor deviates from the baseline.

6. The detection system of claim 1 further comprising:

at least one control sensor located in vivo at an area remote from the sensor, and operable to detect a condition in a bone at the remote area and to generate a signal representative of the detected condition; and

a signal processor operable to receive and compare signals generated by the sensor and signals generated by the at least one control sensor, and operable to send a signal to the transmitter when a signal received from the sensor deviates from a signal received from the at least one control sensor.

7. The detection system of claim 1 further comprising:

a wireless telemetry circuit configured for transmitting the signal from the transmitter to the receiver.

8. The detection system of claim 1 further comprising:

a power source electrically connected to at least one of the sensor, the transmitter and the receiver.

9. The detection system of claim 1 wherein the receiver comprises:

a signal processor operable to convert the signal to a displayable format and to transmit the converted signal; and

an indicator operable to receive the converted signal and provide a human intelligible display representative of the converted signal.

10. The detection system of claim 1 wherein the receiver comprises:

analysis circuitry operable to compare a signal received from the transmitter to a control, and to generate a signal when the signal received from the transmitter exceeds the control; and

an indicator operable to receive the signal generated by the analysis circuitry and to provide a human intelligible display representative of the signal.

11. The detection system of claim 1 further comprising:

an indicator operable to provide a human intelligible display representative of the signal received by the receiver.

12. The detection system of claim 1 wherein the sensor and the transmitter are combined into a unitary structure.

13. The detection system of claim 1 wherein the sensor is at least one of engaged with the bone, and adjacent the bone.

14. The detection system of claim 1 wherein the sensor comprises:

a leading end adapted for disposal in a bone; and

a flange portion adapted for engagement with an implant.

15. The detection system of claim 14, wherein the implant is for use in at least one of an ankle, a knee, a hip, a spine, a shoulder, an elbow, a wrist, and a jaw.

16. The detection system of claim 1 wherein the sensor comprises an external surface configured for bone engagement.

17. The detection system of claim 1 wherein the sensor is disposed on an external surface of an implant.

18. The detection system of claim 1 wherein the receiver is in vivo.

19. The detection system of claim 1 wherein the receiver is ex vivo.

20. A detection system for detecting a condition of a bone comprising:

a sensor located in vivo and operable to detect a condition in a bone and generate a signal representative of the detected condition;

a first signal processor operable to receive a signal from the sensor and to transmit the signal;

a transmitter operable to receive the signal from the first signal processor and to transmit the signal;

a receiver operable to receive the signal from the transmitter and to transmit the signal;

a second signal processor operable to receive the signal from the receiver and to transmit the signal; and

an indicator operable to receive the signal from the second signal processor and provide a human intelligible display representative of the signal.

21. The detection system of claim 20 wherein the sensor is operable to detect at least one of temperature, pH, inflammatory cytokines, MMPs, calcium ions and phosphate ions.

22. The detection system of claim 20 wherein the first signal processor uses the signals received from the sensor to generate a baseline representative of the detected condition, and sends a signal to the transmitter when a signal received from the sensor deviates from the baseline.

- 23.** The detection system of claim 20 further comprising:
at least one control sensor located in vivo at an area remote from the sensor, and operable to detect a condition in a bone at the remote area and to generate a signal representative of the detected condition; wherein the first signal processor is operable to receive and compare signals generated by the sensor and signals generated by the at least one control sensor, and to send a signal to the transmitter when a signal received from the sensor deviates from a signal received from the at least one control sensor.
- 24.** The detection system of claim 20 further comprising:
analysis circuitry operable to compare a signal received from the transmitter to a control, and to send a signal to the indicator when the signal received from the transmitter exceeds the control.
- 25.** The detection system of claim 20 wherein the sensor, the first signal processor and the transmitter are combined into a unitary structure.
- 26.** The detection system of claim 20 wherein the receiver, the second signal processor and the indicator are combined into a unitary structure.
- 27.** The detection system of claim 20 wherein the receiver is in vivo.
- 28.** The detection system of claim 20 wherein the receiver is ex vivo.
- 29.** A method of detecting a condition of a bone comprising:
disposing a sensor in relationship with the bone suitable for detecting at least one condition of the bone selected from temperature, pH, a presence of inflammatory cytokines, a presence of MMPs, a presence of calcium ions and a presence of phosphate ions;
obtaining data from the sensor representative of the selected condition; and
displaying the data in a human intelligible form.
- 30.** The method of claim 29 wherein the selected condition is present in the bone.
- 31.** The method of claim 29 wherein the condition detected is adjacent to the bone.
- 32.** The method of claim 29 further comprising:
obtaining a baseline representative of the selected condition;
obtaining continuing data from the sensor representative of the selected condition; and
comparing the continuing data to the baseline.
- 33.** The method of claim 29 further comprising:
disposing at least one control sensor in relationship with the bone at an area remote from the sensor;
obtaining data from the at least one control sensor representative of the selected condition at the remote area; and
comparing the data obtained from the sensor and the data obtained from the at least one control sensor.
- 34.** The method of claim 29 further comprising:
comparing the data obtained from the sensor on a selected condition with a control for the selected condition.
- 35.** The method of claim 29 wherein the sensor is disposed with the bone by engagement of a first end of the sensor in the bone.
- 36.** The method of claim 35 wherein the sensor comprises a second end, which is engaged with an implant.
- 37.** The method of claim 29 wherein the sensor is disposed on an external surface of an implant, and the external surface of the implant is disposed directly adjacent to the bone.
- 38.** The method of claim 29 wherein the displaying of the data occurs in vivo.
- 39.** The method of claim 29 wherein the displaying of the data occurs ex vivo.

* * * * *

专利名称(译)	检测体内溶骨性病症的方法		
公开(公告)号	US20070179568A1	公开(公告)日	2007-08-02
申请号	US11/344459	申请日	2006-01-31
[标]申请(专利权)人(译)	SDGI控股股份有限公司		
申请(专利权)人(译)	SDGI HOLDINGS , INC.		
当前申请(专利权)人(译)	SDGI HOLDINGS , INC.		
[标]发明人	NYCZ JEFFREY H DRAPEAU SUSAN J DONOFRIO WILLIAM T		
发明人	NYCZ, JEFFREY H. DRAPEAU, SUSAN J. DONOFRIO, WILLIAM T.		
IPC分类号	A61B5/117 A61B5/103 A61B5/00 A61N1/00 A61F2/32 A61B5/05		
CPC分类号	A61B5/0031 A61F2250/0002 A61B5/076 A61B5/14539 A61B5/4528 A61B5/6882 A61B17/68 A61B17/86 A61F2/2803 A61F2/32 A61F2/34 A61F2/36 A61F2/38 A61F2/3804 A61F2/40 A61F2/4202 A61F2/4261 A61F2/44 A61F2/4609 A61F2002/30405 A61F2002/30448 A61F2002/30449 A61F2002/3067 A61F2002/30794 A61F2002/3403 A61F2002/3404 A61F2002/3412 A61F2002/3414 A61F2002/3429 A61F2002/3611 A61F2002/3625 A61F2002/48 A61F2002/488 A61F2220/0025 A61F2220/005 A61B5/01 A61F2002/3079		
其他公开文献	US8095198		
外部链接	Espacenet USPTO		

摘要(译)

用于检测指示骨中的骨溶解或溶骨性前病症的生物反应的方法和系统。

