



US007009511B2

(12) **United States Patent**
Mazar et al.

(10) **Patent No.:** **US 7,009,511 B2**
(45) **Date of Patent:** **Mar. 7, 2006**

(54) **REPEATER DEVICE FOR
COMMUNICATIONS WITH AN
IMPLANTABLE MEDICAL DEVICE**

(75) Inventors: **Scott T. Mazar**, Inver Grove Heights,
MN (US); **Yatheendbar D. Manicka**,
Woodbury, MN (US)

(73) Assignee: **Cardiac Pacemakers, Inc.**, St. Paul,
MN (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 204 days.

4,969,464 A	11/1990	Callaghan et al.	128/419
5,058,581 A	10/1991	Silvian	128/419
5,081,987 A	1/1992	Nigam	120/419
5,113,869 A	5/1992	Nappholz et al.	607/32
5,117,825 A	6/1992	Grevious	128/419
5,137,022 A	8/1992	Henry	128/419
5,241,961 A	9/1993	Henry	607/32
5,292,343 A	3/1994	Blanchette et al.	607/32
5,331,966 A	7/1994	Bennett et al.	128/696
5,336,245 A	8/1994	Adams et al.	607/32
5,350,411 A	9/1994	Ryan et al.	607/32
5,383,915 A	1/1995	Adams	607/60
5,413,594 A	5/1995	Williams	607/32
5,415,181 A	5/1995	Hogrefe et al.	128/736
5,458,122 A	10/1995	Hethuin	128/696

(21) Appl. No.: **10/321,885**

(22) Filed: **Dec. 17, 2002**

(65) **Prior Publication Data**

US 2004/0117204 A1 Jun. 17, 2004

(51) **Int. Cl.**
G08B 1/00 (2006.01)

(52) **U.S. Cl.** **340/531**; 340/539.1; 340/539.11;
340/539.12; 705/2; 705/3

(58) **Field of Classification Search** 340/531,
340/539.1, 539.11, 539.12, 573.1, 573.4,
340/286.07, 825.19; 705/2, 3
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,658,831 A	4/1987	Reinhard et al.	128/697
4,681,111 A	7/1987	Silvian	128/419
4,705,043 A	11/1987	Imran	128/419
4,757,816 A	7/1988	Ryan et al.	128/419
4,793,353 A	12/1988	Borkan	128/421
4,809,697 A	3/1989	Causey, III et al.	128/419
4,932,408 A	6/1990	Schaldach	128/419
4,947,407 A	8/1990	Silvian	375/94
4,952,928 A *	8/1990	Carroll et al.	340/10.41

(Continued)

FOREIGN PATENT DOCUMENTS

EP 0 554 955 A1 8/1993


Primary Examiner—Daryl C Pope

(74) *Attorney, Agent, or Firm*—Patrick J. S. Inouye

(57) **ABSTRACT**

A repeater device for an advanced patient management system communicates with a medical device coupled to a patient to obtain data about the medical device and/or patient's condition. The repeater device maintains the data while if considers various factors when coordinating transfer of the data to a repository of the advanced patient management system. The repeater device may be configured to analyze the data to determine a degree of urgency, such as whether an emergency exists, and then determine when to transfer the data based on the degree of urgency. The repeater device may also be configured to test the condition of the communication medium being used to transfer the data to the repository, such as determining whether a telephone line is in use, and then determine when to transfer the data based on the condition of the of the communication medium.

22 Claims, 9 Drawing Sheets



U.S. PATENT DOCUMENTS

5,476,485 A	12/1995	Weinberg et al.	607/28	6,250,309 B1	6/2001	Krichen et al.	128/899
5,481,262 A	1/1996	Urbas et al.	340/870.17	6,261,230 B1	7/2001	Bardy	600/300
5,509,927 A	4/1996	Epstein et al.	607/32	6,263,245 B1	7/2001	Snell	607/60
5,522,865 A	6/1996	Schulman et al.	607/56	6,263,246 B1	7/2001	Goedeke et al.	607/60
5,549,654 A	8/1996	Powell	607/32	6,263,247 B1	7/2001	Mueller et al.	607/60
5,626,630 A	5/1997	Markowitz et al.	607/60	6,270,457 B1	8/2001	Bardy	600/300
5,629,678 A	5/1997	Gargano et al.	340/573	6,289,238 B1	9/2001	Besson et al.	600/509
5,630,836 A	5/1997	Prem et al.	607/61	6,292,698 B1	9/2001	Duffin et al.	607/32
5,674,249 A	10/1997	De Coriolis et al.	607/5	6,304,788 B1	10/2001	Eady et al.	700/86
5,683,432 A	11/1997	Goedeke et al.	607/32	6,319,200 B1	11/2001	Lai et al.	600/300
5,713,937 A	2/1998	Nappholz et al.	607/30	6,329,929 B1	12/2001	Weijand et al.	340/870.25
5,720,770 A	2/1998	Nappholz et al.	607/30	6,345,203 B1	2/2002	Mueller et al.	607/60
5,741,315 A	4/1998	Lee et al.	607/60	6,349,234 B1	2/2002	Pauly et al.	607/60
5,743,267 A	4/1998	Nikolic et al.	128/673	6,363,282 B1	3/2002	Nichols et al.	607/30
5,752,976 A	5/1998	Duffin et al.	607/32	6,418,346 B1	7/2002	Nelson et al.	607/59
5,752,977 A	5/1998	Grevious et al.	607/32	6,442,432 B1	8/2002	Lee	607/59
5,766,232 A	6/1998	Grevious et al.	607/60	6,442,433 B1	8/2002	Linberg	607/60
5,769,876 A	6/1998	Silvian	607/60	6,477,242 B1	11/2002	Freeny, Jr.	379/93.24
5,772,586 A	6/1998	Heinonen et al.	600/300	6,480,745 B1	11/2002	Nelson et al.	607/60
5,774,501 A	6/1998	Halpern, et al.	375/279	2001/0012955 A1	8/2001	Goedeke et al.	607/27
5,791,342 A	8/1998	Woodard	128/630	2001/0023360 A1	9/2001	Nelson et al.	607/60
5,792,207 A	8/1998	Dietrich	607/32	2001/0025137 A1	9/2001	Webb et al.	600/300
5,814,089 A	9/1998	Stokes et al.	607/32	2001/0025189 A1	9/2001	Haueter et al.	607/62
5,836,983 A	11/1998	Weijand et al.	607/9	2001/0027331 A1	10/2001	Thompson	607/60
5,843,133 A	12/1998	Routh et al.	607/14	2001/0027349 A1	10/2001	Eady et al.	700/17
5,843,139 A	12/1998	Goedeke et al.	607/32	2001/0029321 A1	10/2001	Beetz et al.	600/300
5,861,014 A	1/1999	Familoni	607/40	2001/0031998 A1	10/2001	Nelson et al.	607/60
5,861,018 A	1/1999	Feierbach	607/60	2001/0037056 A1	11/2001	Nunome	600/300
5,899,928 A	5/1999	Sholder et al.	607/27	2001/0039372 A1	11/2001	Yasushi et al.	600/300
5,899,931 A	5/1999	Deschamp et al.	607/60	2001/0044588 A1	11/2001	Mault	600/549
5,917,414 A	6/1999	Oppelt et al.	340/573.1	2001/0047125 A1	11/2001	Quy	600/300
5,919,214 A	7/1999	Ciciarelli et al.	607/32	2001/0051764 A1	12/2001	Bardy	600/300
5,935,078 A	8/1999	Feierbach	600/509	2001/0051787 A1	12/2001	Haller et al.	604/66
5,944,659 A	8/1999	Flach et al.	600/300	2002/0013517 A1	1/2002	West et al.	600/300
5,957,861 A	9/1999	Combs et al.	600/547	2002/0013518 A1	1/2002	West et al.	600/300
5,999,857 A	12/1999	Weijand et al.	607/60	2002/0013538 A1	1/2002	Teller	600/549
6,083,248 A	7/2000	Thompson	607/30	2002/0013613 A1	1/2002	Haller et al.	607/60
6,093,146 A	7/2000	Filangeri	600/300	2002/0013614 A1	1/2002	Thompson	607/60
6,141,584 A	10/2000	Rockwell et al.	607/5	2002/0019584 A1	2/2002	Schulze et al.	600/300
6,170,488 B1	1/2001	Spillman, Jr. et al.	128/899	2002/0019586 A1	2/2002	Teller et al.	600/300
6,185,452 B1	2/2001	Schulman et al.	604/20	2002/0028988 A1	3/2002	Suzuki et al.	600/300
6,200,264 B1	3/2001	Satherley et al.	600/300	2002/0033247 A1	3/2002	Linberg	607/60
6,203,495 B1	3/2001	Bardy	600/301	2002/0040234 A1	4/2002	Linberg	607/32
6,206,835 B1	3/2001	Spillman, Jr. et al.	600/485	2002/0052539 A1	5/2002	Haller et al.	600/300
6,208,894 B1	3/2001	Schulman et al.	607/2	2002/0072785 A1	6/2002	Nelson et al.	607/60
6,213,942 B1	4/2001	Flach et al.	600/300	2002/0082665 A1	6/2002	Haller et al.	607/60
6,216,038 B1	4/2001	Hartlaub et al.	607/31	2002/0095196 A1	7/2002	Linberg	607/60
6,221,011 B1	4/2001	Bardy	600/300	2002/0111542 A1	8/2002	Warkentin et al.	600/300
6,223,083 B1	4/2001	Rosar	607/60				
6,236,889 B1	5/2001	Soykan et al.	607/30				

* cited by examiner





FIG. 1

FIG. 2







FIG. 3






FIG. 5




FIG. 6




FIG. 7




FIG. 8





FIG. 9



1

REPEATER DEVICE FOR COMMUNICATIONS WITH AN IMPLANTABLE MEDICAL DEVICE

TECHNICAL FIELD

The present relay device relates generally to advanced patient management systems, and more specifically to providing information between a medical device and a repository of the advanced patient management system through a repeater device.

BACKGROUND OF THE INVENTION

In an effort to limit the number of follow-ups necessary to monitor the device and the data that it acquires, an advanced patient management system may provide a communication infrastructure. This infrastructure allows the implantable medical device to communicate over long distances at virtually any time with a backend system that monitors the implantable device and the patient. Furthermore, this backend system allows monitoring of the patient on a more frequent basis than ordinary follow-up visits can practically allow. The back end system communicates with the implantable device through a repeater that the patient keeps in close proximity. The conventional repeater device interrogates the medical device through some form of wireless communication such as inductive coupling. The repeater device retrieves data from the medical device and transmits the data through another communication medium, such as a standard telephone line, to the remote location.

Some conventional repeater devices form a direct line of communication between the medical device and the remote location and thereby act as a conduit for the data. Generally, the patient operates these conventional repeater devices and must initiate the communication of the data at appropriate times. Other conventional repeater devices may retrieve the data from the medical device at an appropriate time and maintain it until another appropriate time when it is sent to the remote location. However, the patient must also initiate the communication between these conventional repeater devices and the remote location, or the repeater device uses a preset timer to initiate communication without regard for additional considerations.

Requiring the patient to initiate communication with the remote location is overly burdensome, especially in situations where the repeater device collects data at one time and then at some later time sends the data to the remote location. Furthermore, requiring the patient to initiate communications with the remote location makes the advanced patient management system vulnerable to human error. Relying solely on a preset timer to initiate communications with the remote location is also problematic. For example, the telephone line relied upon by the repeater device may be in use or is otherwise unavailable at the preset time, or an emergency situation may be occurring that requires immediate attention rather than communication after a preset delay period.

SUMMARY OF THE INVENTION

The problems discussed above and others are addressed by various embodiments of the present invention. These embodiments allow the repeater device to automatically communicate with the remote location to transfer the patient data. The repeater device automatically communicates with the remote location by initiating communication after con-

2

sidering additional factors such as the accessibility or condition of the communications medium being used to pass the data and/or whether the condition of the patient requires immediate attention.

In one embodiment, the repeater device coordinates the transfer of data from the medical device to a data repository based upon the condition of a communications medium existing between the repeater device and the repository. The repeater device stores the data in memory after it has been retrieved from the implantable device and then begins detecting the condition of the communication medium, such as whether the telephone line is already in use or is available for placing a call. Once the communication medium has an adequate condition for transferring the data, the repeater device sends the data over the communication medium to the repository.

In another embodiment, the repeater device coordinates the transfer of data from the medical device to the data repository based upon the urgency of the data that has been retrieved from the medical device. The repeater device stores the data in memory after it has been retrieved from the implantable device and then begins to analyze the data to determine its degree of urgency, such as to determine whether the patient is about to or is already experiencing an emergency condition. The repeater then determines the time to send the data to the repository based on the degree of urgency.

These and various other features as well as advantages, which characterize the present invention, will be apparent from a reading of the following detailed description and a review of the associated drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

In the drawings, which are not necessarily drawn to scale, like numerals describe substantially similar components throughout the several views. Like numerals having different letter suffixes represent different instances of substantially similar components. The drawings illustrate generally, by way of example, but not by way of limitation, various embodiments discussed in the present document.

FIG. 1 illustrates an example advanced patient management system;

FIG. 2 illustrates an example computer system for use with the advanced patient management system;

FIG. 3 illustrates an example interrogator/transceiver unit for use with the advanced patient management system; and

FIG. 4 illustrates an example communication system for use with the advanced patient management system;

FIG. 5 illustrates communication between an implantable medical device, an external repeater device, and a repository;

FIG. 6 illustrates exemplary external repeater device of FIG. 5 in more detail;

FIG. 7 illustrates components of the exemplary repeater device;

FIG. 8 illustrates an exemplary operational flow of communication between the implantable medical device, the external repeater device, and the repository where the degree of urgency of the data is determined and considered in relation to data transfer to the repository;

FIG. 9 illustrates an exemplary operational flow of communication between the implantable medical device, the external repeater device, and the repository where the condition of the communication medium is considered in relation to data transfer to the repository;

FIG. 10 illustrates an exemplary operational flow of communication between the implantable medical device, the external repeater device, and the repository where both the degree of urgency of the data and the condition of the communication medium are considered in relation to data transfer to the repository.

DETAILED DESCRIPTION OF THE INVENTION

Prior to discussing the devices and communication protocols of the embodiments of the present invention, an example of an advanced patient management system is discussed to provide an example of an environmental context for the embodiments of the present invention. However, it is to be understood that the advanced patient management system described herein in conjunction with the embodiments of the present invention is only one example of an environmental context and that the embodiments of the present invention are applicable to other environmental contexts that may or may not include an advanced patient management system. The devices and communication protocols of the embodiments of the present invention are described below with reference to FIGS. 5–10 and section V. Repeater Communications.

An advanced patient management system is configured to collect patient-specific information, store and collate the information, and generate actionable recommendations to enable the predictive management of patients. The advanced patient management system is also configured to leverage a remote communications infrastructure to provide automatic device follow-ups to collect data, coordinate therapy, and to determine if remote devices are functioning properly. The term “patient” is used herein to mean any individual from whom information is collected. The term “caregiver” is used herein to mean any provider of services, such as health care providers including, but not limited to, nurses, doctors, and other health care provider staff.

FIG. 1 illustrates an example advanced patient management system 100. Advanced patient management system 100 generally includes the following components: one or more devices 102, 104, and 106, one or more interrogator/transceiver units 108, a communication system 110, one or more remote peripheral devices 109, and a host 112.

Each component of the advanced patient management system 100 can communicate using the communication system 110. Some components may also communicate directly with one another. For example, devices 102 and 104 may be configured to communicate directly with one another. The various components of the example advanced patient management system 100 illustrated herein are described below.

I. Devices

Devices 102, 104, and 106 can be implantable devices or external devices that may provide one or more of the following functions with respect to a patient: (1) sensing, (2) data analysis, and (3) therapy. For example, in one embodiment, devices 102, 104, and 106 are either implanted or external devices used to measure a variety of physiological, subjective, and environmental conditions of a patient using electrical, mechanical, and/or chemical means. The devices 102, 104, and 106 can be configured to automatically gather data or can require manual intervention by the patient. The devices 102, 104, and 106 can be configured to store data related to the physiological and/or subjective measurements and/or transmit the data to the communication system 110

using a variety of methods, described in detail below. Although three devices 102, 104, and 106 are illustrated in the example embodiment shown, more or fewer devices may be used for a given patient.

The devices 102, 104, and 106 can be configured to analyze the measured data and act upon the analyzed data. For example, the devices 102, 104, and 106 are configured to modify therapy or provide alarm indications based on the analysis of the data.

In one embodiment, devices 102, 104, and 106 also provide therapy. Therapy can be provided automatically or in response to an external communication. Devices 102, 104, and 106 are programmable in that the characteristics of their sensing, therapy (e.g., duration and interval), or communication can be altered by communication between the devices 102, 104, and 106 and other components of the advanced patient management system 100. Devices 102, 104, and 106 can also perform self-checks or be interrogated by the communication system 110 to verify that the devices are functioning properly. Examples of different embodiments of the devices 102, 104, and 106 are provided below.

Devices implanted within the body have the ability to sense and communicate as well as to provide therapy. Implantable devices can provide direct measurement of characteristics of the body, including, without limitation, electrical cardiac activity (e.g., a pacemaker, cardiac resynchronization management device, defibrillator, etc.), physical motion, temperature, heart rate, activity, blood pressure, breathing patterns, ejection fractions, blood viscosity, blood chemistry, blood glucose levels, and other patient-specific clinical physiological parameters, while minimizing the need for patient compliance.

A heart rhythm sensor, typically found in a pacemaker or defibrillator, is one example of an implantable device. In the heart, an electrical wave activates the heart muscle just prior to contraction. As is known in the art, electrical circuits and lead-wires transduce the heart's activation event and reject other, non-essential electrical events. By measuring the time interval between activation events, the heart rhythm can be determined. A transthoracic impedance sensor is another example of a sensor in an implantable device. During the respiratory cycle, large volumes of air pass into and out of the body. The electrical resistance of the thorax changes markedly as a result of large differences in conductivity of air and body tissues. The thoracic resistance can be measured during respiration and converted into a measurable electrical signal (i.e., impedance) so that breathing rate and profile can be approximated. Implantable devices can also sense chemical conditions, such as glucose levels, blood oxygen levels, etc. Further, the advanced patient management system 100 may utilize other implantable devices as well that provide physiological measurements of the patient, such as drug pumps, neurological devices (e.g., stimulators), oxygen sensors, etc.

Derived measurements can also be determined from the implantable device sensors. For example, a sleep sensor can rely on measurements taken by an implanted accelerometer that measures body activity levels. The sleep sensor can estimate sleeping patterns based on the measured activity levels. Other derived measurements include, but are not limited to, a functional capacity indicator, autonomic one indicator, sleep quality indicator, cough indicator, anxiety indicator, and cardiovascular wellness indicator for calculating a quality of life indicator quantifying a patient's overall health and well-being.

Devices 102, 104, and 106 can also be external devices, or devices that are not implanted in the human body, that are

used to measure physiological data. Such devices include a multitude of devices to measure data relating to the human body, such as temperature (e.g., a thermometer), blood pressure (e.g., a sphygmomanometer), blood characteristics (e.g., glucose levels), body weight, physical strength, mental acuity, diet, heart characteristics, and relative geographic position (e.g., a Global Positioning System (GPS)).

Devices **102**, **104**, and **106** can also be environmental sensors. The devices can be placed in a variety of geographic locations (in close proximity to patient or distributed throughout a population) and record non-patient specific characteristics such as, but not limited to, temperature, air quality, humidity, carbon monoxide level, oxygen level, barometric pressure, light intensity, and sound.

One or more of the devices **102**, **104**, and **106** (for example, device **106**) may be external devices that measure subjective or perceptive data from the patient. Subjective data is information related to a patient's feelings, perceptions, and/or opinions, as opposed to objective physiological data. For example, the "subjective" devices can measure patient responses to inquiries such as "How do you feel?" and "How is your pain?" The device can prompt the patient and record subjective data from the patient using visual and/or audible cues. For example, the patient can press coded response buttons or type an appropriate response on a keypad. Alternatively, subjective data may be collected by allowing the patient to speak into a microphone and using speech recognition software to process the subjective data.

In one example embodiment, the subjective device presents the patient with a relatively small number of responses to each question posed to the patient. For example, the responses available to the patient may include three faces representing feelings of happiness, nominalness, and sadness. Averaged over time, a trend of a patient's well being will emerge with a finer resolution than the quanta of the three responses.

The subjective data can be collected from the patient at set times, or, alternatively, collected whenever the patient feels like providing subjective data. The subjective data can also be collected substantially contemporaneously with physiological data to provide greater insight into overall patient wellness. The subjective device **106** can be any device that accepts input from a patient or other concerned individual and/or provides information in a format that is recognizable to the patient. Device **106** typically includes a keypad, mouse, display, handheld device, interactive TV, cellular telephone or other radio frequency ("RF") communications device, cordless phone, corded phone, speaker, microphone, email message, or physical stimulus.

In one example embodiment, the subjective device **106** includes or is part of a computer system **200**, as illustrated in FIG. 2. The example computer system **200** includes a central processor unit **212** and a system memory **214**. The computer system **200** further includes one or more drives **223** for reading data from and writing data to, as well as an input device **244**, such as a keyboard or mouse, and a monitor **252** or other type of display device. A number of program modules may be stored on the drive **223**, including an operating system **236**, one or more application programs **238**, other program modules **240**, and program data **242**. The computer system **200** can operate in a networked environment using logical connections to one or more remote computers or computer systems **256**. Computer system **200** can also include hand-held computers such as a PDA computer.

The advanced patient management system **100** may also include one or more remote peripheral devices **109**. The

remote peripheral device **109** may include, for example and without limitation, cellular telephones, pagers, PDA devices, facsimiles, remote computers, printers, video and/or audio devices, etc. The remote peripheral device **109** can communicate using wired or wireless technologies and may be used by the patient or caregiver to communicate with the communication system **10** and/or the host **112**. For example, the remote peripheral device **109** can be used by the caregiver to receive alerts from the host **112** based on data collected from the patient and to send instructions from the caregiver to either the patient or other clinical staff. In another example, the remote peripheral device **109** is used by the patient to receive periodic or real time updates and alerts regarding the patient's health and well-being.

II. Interrogator/Transceiver Unit

Referring now to FIG. 3, the example advanced patient management system **100** includes one or more interrogator/transceiver units ("ITUs"), such as ITU **108**. The ITU **108** includes an interrogator module **152** for sending and receiving data from a device, such as devices **102**, **104**, and **106**, a memory module **154** for storing data, and a transceiver module **156** for sending and receiving data to and from other components of the APM system **100**. The transceiver module may also operate as an interrogator of the devices **102**, **104** and **106**. The ITU **108** also includes a power module **158** that provides power.

The ITU **108** may perform one or more of the following functions: (1) data storage; (2) data analysis; (3) data forwarding; (4) patient interaction; (5) patient feedback; and (6) data communications. For example, the ITU **108** may facilitate communications between the devices **102**, **104**, and **106** and the communication system **110**. The ITU **108** can, periodically or in real-time, interrogate and download into memory clinically relevant patient data from the devices **102**, **104**, and/or **106**. This data includes, in the cardiac sensor context, for example, P and R-wave measurements, pacing, shocking events, lead impedances, pacing thresholds, battery voltage, capacitor charge times, ATR episodes with electrograms, tachycardia episodes with electrograms, histogram information, and any other clinical information necessary to ensure patient health and proper device function. The data is sent to the ITU **108** by the devices **102**, **104**, and **106** in real-time or periodically uploaded from buffers in the devices.

The ITU **108** may also allow patient interaction. For example, the ITU **108** may include a patient interface and allow the patient to input subjective data. In addition, the ITU **108** may provide feedback to the patient based on the data that has been analyzed or based on information communicated by the communication system **110**.

In another embodiment, the ITU **108** includes a telemetry link from the devices to a network that forms the basis of a wireless LAN in the patient's home. The ITU **108** systematically uploads information from the devices **102**, **104**, and/or **106** while the patient is sleeping, for example. The uploaded data is transmitted through the communication system **110** or directly to the host **112**. In addition, in one embodiment the ITU **108** functions in a hybrid form, utilizing wireless communication when available and defaulting to a local wireless portal or a wired connection when the wireless communication becomes unavailable.

Some devices, such as legacy implanted cardiac rhythm management ("CRM") devices, communicate via an internal telemetry transceiver that communicates with an external programmer. The communication range of such devices is

typically 1 to 4 inches. ITU 108 may include a special short-range interrogator that communicates with a legacy device.

When the interrogator 152 uses radio frequency to communicate with the devices 102, 104, 106, the ITU 108 may be in the form of a small device that is placed in an inconspicuous place within the patient's residence. Alternatively, the ITU 108 may be implemented as part of a commonly-used appliance in the patient's residence. For example, the ITU may be integrated with an alarm clock that is positioned near the patient's bed. In another embodiment, the ITU may be implemented as part of the patient's personal computer system. Other embodiments are also possible.

In another embodiment, the ITU 108 may comprise a hand-held device such as a PDA, cellular telephone, or other similar device that is in wireless communication with the devices 102, 104, and 106. The hand-held device may upload the data to the communication system 110 wirelessly. Alternatively, the hand-held device may periodically be placed in a cradle or other similar device that is configured to transmit the data to the communication system 110.

In one embodiment, the ITU 108 can perform analysis on the data and provide immediate feedback, as well as perform a variety of self-diagnostic tests to verify that it is functioning properly and that communication with the communication system 110 has not been compromised. For example, the ITU 108 can perform a diagnostic loop-back test at a time set by the host 112, which involves sending a request through the communication system 110 to the host 112. The host 112 can then reply with a response back through the communication system 110 to the ITU 108. If a specific duration elapses before the ITU 108 receives the response or the ITU 108 receives an unexpected response, or if the host 112 does not receive the diagnostic test communication, the ITU 108 can provide indications that the system is not functioning properly and the host 112 can alert an operator that there may be compromised communications with that specific ITU 108. For example, if wireless communications between the ITU 108 and the communication system 110 have been interrupted, and the ITU 108 performs a self-diagnostic test that fails, the ITU 108 may alert the patient so that corrective action may be taken. The alert can take the form of a sound or a visual and/or audible annunciator to alert the patient that communication has been interrupted. In another embodiment, the ITU 108 can automatically fail-back to a wired system to communicate with the communication system 110 and perform the same communications compromise checks.

In other embodiments of the advanced patient management system 100, the ITU 108 function can be integrated into devices 102, 104, and 106, so that the devices can communicate directly with the communication system 110 and/or host 112. The devices 102, 104 and 106 can incorporate multi-mode wireless telecommunications such as cellular, BLUETOOTH, or IEEE 802.11B to communicate with the communication system 110 directly or through a local wireless to a wired portal in the patients' home. For example, device 102 may include a miniature cellular phone capable of wirelessly uploading clinical data from the device on a periodic basis. This is particularly advantageous for devices that are mobile (e.g., an implanted device in a patient that is traveling).

To conserve the energy of the devices 102, 104, and 106, particularly when the devices (e.g., device 102) are configured to communicate directly with the communication system 110 without using an ITU 108, in one example embodiment the devices are configured to communicate during a

given duty cycle. For example, the device 102 can be configured to communicate with the communication system 110 at given intervals, such as once a week. The device 102 can record data for the time period (e.g., a week) and transmit the data to the communication system 110 during the portion of the cycle that transmission is active and then conserve energy for the rest of the cycle. In another example, the device 102 conserves energy and only communicates with the communication system 110 when an "interesting" event, such as a heart arrhythmia, has occurred. In this manner, device 102 can communicate directly with the communication system 110 and/or host 112 without requiring an ITU 108, while conserving the energy of the device by communicating only during a given duty cycle.

The interrogation rate of the ITU 108 can be varied depending on disease state and other relevant factors. In addition, the devices 102, 104, and 106 can be configured to "wake up" frequently (e.g., once every couple minutes) to provide the ITU 108 an access window for the ITU 108 to provide commands to the devices 102, 104, and 106, as well as upload data from the devices.

If multiple devices, such as devices 102, 104, and 106, are provided for a given patient, each device may include its own means for communicating with the ITU 108 or communication system 110. Alternatively, a single telemetry system may be implemented as part of one of the devices, or separate from the devices, and each device 102, 104, and 106 can use this single telemetry system to communicate with the ITU 108 or the communication system 110.

In yet another embodiment, the devices 102, 104, and 106 include wires or leads extending from devices 102, 104, and 106 to an area external of the patient to provide a direct physical connection. The external leads can be connected, for example, to the ITU 108 or a similar device to provide communications between the devices 102, 104, and 106 and the other components of the advanced patient management system 100.

The advanced patient management system 100 can also involve a hybrid use of the ITU 108. For example, the devices 102, 104, and 106 can intelligently communicate via short-range telemetry with the ITU when the patient is located within the patient's home and communicate directly with the communication system 110 or host 112 when the patient is traveling. This may be advantageous, for example, to conserve battery power when the devices are located near an ITU.

III. Communication System

Communication system 110 provides for communications between and among the various components of the advanced patient management system 100, such as the devices 102, 104, and 106, host 112, and remote peripheral device 109. FIG. 4 illustrates one embodiment for the communication system 110. The communication system 110 includes a plurality of computer systems 304, 306, 308, and 310, as well as device 102, host 112, and remote peripheral device 109, connected to one another by the communications network 300. The communications network 300 may be, for example, a local area network (LAN), wide area network (WAN), or the Internet. Communications among the various components, as described more fully below, may be implemented using wired or wireless technologies.

In the example embodiment illustrated, the host 112 includes server computers 318 and 322 that communicate with computers 304, 306, 308, and 310 using a variety of communications protocols, described more fully below. The server computers 318 and 322 store information in databases

316 and 320. This information may also be stored in a distributed manner across one or more additional servers.

A variety of communication methods and protocols may be used to facilitate communication between devices 102, 104, and 106, ITU 108, communication system 110, host 112, and remote peripheral device 109. For example, wired and wireless communications methods may be used. Wired communication methods may include, for example and without limitation, traditional copper-line communications such as DSL, broadband technologies such as ISDN and cable modems, and fiber optics, while wireless communications may include cellular, satellite, radio frequency (RF), Infrared, etc.

For any given communication method, a multitude of standard and/or proprietary communication protocols may be used. For example and without limitation, protocols such as radio frequency pulse coding, spread spectrum, direct sequence, time-hopping, frequency hopping, SMTP, FTP, and TCP/IP may be used. Other proprietary methods and protocols may also be used. Further, a combination of two or more of the communication methods and protocols may also be used.

The various communications between the components of the advanced patient management system 100 may be made secure using several different techniques. For example, encryption and/or tunneling techniques may be used to protect data transmissions. Alternatively, a priority data exchange format and interface that are kept confidential may also be used. Authentication can be implemented using, for example, digital signatures based on a known key structure (e.g., PGP or RSA). Other physical security and authentication measures may also be used, such as security cards and biometric security apparatuses (e.g., retina scans, iris scans, fingerprint scans, veinprint scans, voice, facial geometry recognition, etc.). Conventional security methods such as firewalls may be used to protect information residing on one or more of the storage media of the advanced patient management system 100. Encryption, authentication and verification techniques may also be used to detect and correct data transmission errors.

Communications among the various components of the advanced patient management system 100 may be enhanced using compression techniques to allow large amounts of data to be transmitted efficiently. For example, the devices 102, 104, and 106 or the ITU 108 may compress the recorded information prior to transmitting the information to the ITU 108 or directly to the communication system 110.

The communication methods and protocols described above can facilitate periodic and/or real-time delivery of data.

IV. Host

The example host 112 includes a database module 114, an analysis module 116, and a delivery module 118 (see FIG. 1). Host 112 preferably includes enough processing power to analyze and process large amounts of data collected from each patient, as well as to process statistics and perform analysis for large populations. For example, the host 112 may include a mainframe computer or multi-processor workstation. The host 112 may also include one or more personal computer systems containing sufficient computing power and memory. The host 112 may include storage medium (e.g., hard disks, optical data storage devices, etc.) sufficient to store the massive amount of high-resolution data that is collected from the patients and analyzed.

The host 112 may also include identification and contact information (e.g., IP addresses, telephone numbers, or a

product serial number) for the various devices communicating with it, such as ITU 108 and peripheral device 109. For example, each ITU 108 is assigned a hard-coded or static identifier (e.g., IP address, telephone number, etc.), which allows the host 112 to identify which patient's information the host 112 is receiving at a given instant. Alternatively, each device 102, 104, and 106 may be assigned a unique identification number, or a unique patient identification number may be transmitted with each transmission of patient data.

When a device is first activated, several methods may be used to associate data received by the advanced patient management system 100 with a given patient. For example, each device may include a unique identification number and a registration form that is filled out by the patient, caregiver, or field representative. The registration form can be used to collect the necessary information to associate collected data with the patient. Alternatively, the user can logon to a web site to allow for the registration information to be collected. In another embodiment, a barcode is included on each device that is scanned prior to or in conjunction deployment of the device to provide the information necessary to associate the recorded data with the given patient.

Referring again to FIG. 1, the example database module 114 includes a patient database 400, a population database 402, a medical database 404, and a general database 406, all of which are described further below.

The patient database 400 includes patient specific data, including data acquired by the devices 102, 104, and 106. The patient database 400 also includes a patient's medical records. The patient database 400 can include historical information regarding the devices 102, 104, and 106. For example, if device 102 is an implantable cardioverter defibrillator (ICD), the patient database 400 records the following device information: P and R measurements, pacing frequency, pacing thresholds, shocking events, recharge time, lead impedance, battery voltage/remaining life, ATR episode and EGMs, histogram information, and other device-specific information. The information stored in the database 400 can be recorded at various times depending on the patient requirements or device requirements. For example, the database 400 is updated at periodic intervals that coincide with the patient downloading data from the device. Alternatively, data in the database 400 can be updated in real time. Typically, the sampling frequency depends on the health condition being monitored and the co-morbidities.

The population database 402 includes non-patient specific data, such as data relating to other patients and population trends. The population database 402 also records epidemic-class device statistics and patient statistics. The population database 402 also includes data relating to staffing by health care providers, environmental data, pharmaceuticals, etc.

The example medical database 404 includes clinical data relating to the treatment of diseases. For example, the medical database 404 includes historical trend data for multiple patients in the form of a record of progression of their disease(s) along with markers of key events.

The general database 406 includes non-medical data of interest to the patient. This can include information relating to news, finances, shopping, technology, entertainment, and/or sports. The general database 406 can be customized to provide general information of specific interest to the patient. For example, stock information can be presented along with the latest health information as detected from the devices 102, 104, and 106.

In another embodiment, information is also provided from an external source, such as external database **600**. For example, the external database **600** includes external medical records maintained by a third party, such as drug prescription records maintained by a pharmacy, providing information regarding the type of drugs that have been prescribed for a patient.

The example analysis module **116** includes a patient analysis module **500**, device analysis module **502**, population analysis module **504**, and learning module **506**.

Patient analysis module **500** may utilize information collected by the advanced patient management system **100**, as well as information for other relevant sources, to analyze data related to a patient and provide timely and predictive assessments of the patient's well-being. In performing this analysis, the patient device module **500** may utilize data collected from a variety of sources, include patient specific physiological and subjective data collected by the advanced patient management system **100**, medical and historical records (e.g., lab test results, histories of illnesses, etc., drugs currently and previously administered, etc.), as well as information related to population trends provided from sources external to the advanced patient management system **100**.

For example, in one embodiment, the patient analysis module **500** makes a predictive diagnosis of an oncoming event based on information stored in the database module **114**. For example, the data continuously gathered from a device of a given patient at a heightened risk for a chronic disease event (such as de-compensations in heart failure) is analyzed. Based on this analysis, therapy, typically device based or pharmaceutical, is then be applied to the patient either through the device or through clinician intervention.

In another example embodiment, the patient analysis module **500** provides a diagnosis of patient health status and predicted trend based on present and recent historical data collected from a device as interpreted by a system of expert knowledge derived from working practices within clinics. For example, the patient analysis module **500** performs probabilistic calculations using currently-collected information combined with regularly-collected historical information to predict patient health degradation.

In another example embodiment, the patient analysis module **500** may conduct pre-evaluation of the incoming data stream combined with patient historical information and information from patients with similar disease states. The pro evaluation system is based on data derived from working clinical practices and the records of outcomes. The derived data is processed in a neural network, fuzzy logic system, or equivalent system to reflect the clinical practice. Further, the patient analysis module **500** may also provide means for periodic processing of present and historical data to yield a multidimensional health state indication along with disease trend prediction, next phase of disease progression co-morbidities, and inferences about what other possible diseases may be involved. The patient analysis module **500** may also integrate data collected from internal and external devices with subjective data to optimize management of overall patient health.

Device analysis module **502** analyzes data from the devices **102**, **104**, and **106** and ITU **108** to predict and determine device issues or failures. For example, if an implanted device **102** fails to communicate at an expected time, device analysis module **502** determines the source of the failure and takes action to restore the performance of the device **102**. The device analysis module **502** may also perform additional deterministic and probabilistic calculations.

For example, the device analysis module **502** gathers data related to charge levels within a given device, such as an ICD, and provides analysis and alerting functions based on this information if, for example, the charge level reaches a point at which replacement of the device and/or battery is necessary. Similarly, early degradation or imminent failure of implanted devices can be identified and proactively addressed, or at-risk devices can be closely monitored.

Population analysis module **504** uses the data collected in the database module **114** to manage the health of a population. For example, a clinic managing cardiac patients can access the advanced patient management system **100** and thereby obtain device-supplied advance information to predict and optimize resource allocation both as to immediate care and as a predictive metric for future need of practicing specialists. As another example, the spread of disease in remote populations can be localized and quarantined rapidly before further spread.

In one embodiment, population analysis module **504** trends the patient population therapy and management as recorded by the devices and directs health care resources to best satisfy the needs of the population. The resources can include people, facilities, supplies, and/or pharmaceuticals. In other embodiments, the population analysis module detects epidemics and other events that affect large population groups. The population analysis module **504** can issue alerts that can initiate a population quarantine, redirect resources to balance size of staffing with number of presenting population, and predict future need of qualified specialists.

The population analysis module **504** may utilize a variety of characteristics to identify like-situated patients, such as, for example, sex, age, genetic makeup, etc. The population analysis module **504** may develop large amounts of data related to a given population based on the information collected by the advanced patient management system **100**. In addition, the population analysis module **504** may integrate information from a variety of other sources. For example, the population analysis module **504** may utilize data from public domain databases (e.g., the National Institute of Health), public and governmental and health agency databases, private insurance companies, medical societies (e.g., the American Heart Association), and genomic records (e.g., DNA sequences).

In one embodiment of the invention, the host **112** may be used as a "data clearinghouse," to gather and integrate data collected from the devices **102**, **104**, and **106**, as well as data from sources outside the advanced patient management system **100**. The integrated data can be shared with other interested entities, subject to privacy restrictions, thereby increasing the quality and integration of data available.

Learning module **506** analyzes the data provided from the various information sources, including the data collected by the advanced patient system **100** and external information sources. For example, the learning module **506** analyzes historical symptoms, diagnoses, and outcomes along with time development of the diseases and co-morbidities. The learning module **506** can be implemented via a neural network (or equivalent) system.

The learning module **506** can be partially trained (i.e., the learning module **506** may be implemented with a given set of preset values and then learn as the advanced patient management system functions) or untrained (i.e., the learning module **506** is initiated with no preset values and must learn from scratch as the advanced patient management system functions). In other alternative embodiments, the learning module **506** may continue to learn and adjust as the

advanced patient management system functions (i.e., in real time), or the learning module **506** may remain at a given level of learning and only advanced to a higher level of understanding when manually allowed to do so.

In a neural network embodiment, new clinical information is presented to create new neural network coefficients that are distributed as a neural network knowledge upgrade. The learning module **506** can include a module for verifying the neural network conclusions for clinical accuracy and significance. The learning module can analyze a database of test cases, appropriate outcomes and relative occurrence of misidentification of the proper outcomes. In some embodiments, the learning module **506** can update the analysis module **116** when the analysis algorithms exceed a threshold level of acceptable misidentifications.

The example learning module **506** uses various algorithms and mathematical modeling such as, for example, trend and statistical analysis, data mining, pattern recognition, cluster analysis, neural networks and fuzzy logic. Learning module **506** may perform deterministic and probabilistic calculations. Deterministic calculations include algorithms for which a clear correlation is known between the data analyzed and a given outcome. For example, there may be a clear correlation between the energy left in a battery of an implantable device and the amount of time left before the battery must be replaced.

A probabilistic calculation involves the correlation between data and a given outcome that is less than 100 percent certain. Probabilistic determinations require an analysis of several possible outcomes and an assignment of probabilities for those outcomes (e.g., an increase in weight of a patient may, at a 25% probability, signal an impending de-compensation event and/or indicate that other tests are needed). The learning module **506** performs probabilistic calculations and selects a given response based on less than a 100% probability. Further, as the learning module **506** "learns" for previous determinations (e.g., through a neural network configuration), the learning module **506** becomes more proficient at assigning probabilities for a given data pattern, thereby being able to more confidently select a given response. As the amount of data that has been analyzed by the learning module **506** grows, the learning module **506** becomes more and more accurate at assigning probabilities based on data patterns. A bifurcated analysis may be performed for diseases exhibiting similar symptoms. As progressive quantities of data are collected and the understanding of a given disease state advances, disease analysis is refined where a former singular classification may split into two or more sub-classes.

In addition, patient-specific clinical information can be stored and tracked for hundreds of thousands of individual patients, enabling a first-level electronic clinical analysis of the patient's clinical status and an intelligent estimate of the patient's short-term clinical prognosis. The learning module **506** is capable of tracking and forecasting a patient's clinical status with increasing levels of sophistication by measuring a number of interacting co-morbidities, all of which may serve individually or collectively to degrade the patient's health. This enables learning module **506**, as well as caregivers, to formulate a predictive medical response to oncoming acute events in the treatment of patients with chronic diseases such as heart failure, diabetes, pain, cancer, and asthma/COPD, as well as possibly head-off acute catastrophic conditions such as MI and stroke.

Delivery module **118** coordinates the delivery of feedback based on the analysis performed by the host **112**. In response to the analysis module **116**, delivery module **118** can manage

the devices **102**, **104**, and **106**, perform diagnostic data recovery, program the devices, and otherwise deliver information as needed. In some embodiments, the delivery module **118** can manage a web interface that can be accessed by patients or caregivers. The information gathered by an implanted device can be periodically transmitted to a web site that is securely accessible to the caregiver and/or patient in a timely manner. In other embodiments, a patient accesses detailed health information with diagnostic recommendations based upon analysis algorithms derived from leading health care institutions.

For example, the caregiver and/or patient can access the data and analysis performed on the data by accessing one or more general content providers. In one example, the patient's health information is accessed through a general portal such as My Yahoo provided by Yahoo! Inc. of Sunnyvale, Calif. A patient can access his or her My Yahoo homepage and receive information regarding current health and trends derived from the information gathered from the devices **102**, **104**, and **106**, as well as other health information gathered from other sources. The patient may also access other information in addition to health information on the My Yahoo website, such as weather and stock market information. Other electronic delivery methods such as email, facsimile, etc. can also be used for alert distribution.

In an alternative embodiment, the data collected and integrated by the advanced patient system **100**, as well as any analysis performed by the system **100**, is delivered by delivery module **118** to a caregiver's hospital computer system for access by the caregiver. A standard or custom interface facilitates communication between the advanced patient management system **100** and a legacy hospital system used by the caregiver so that the caregiver can access all relevant information using a system familiar to the caregiver.

The advanced patient management system **100** can also be configured so that various components of the system (e.g., ITU **108**, communication system **110**, and/or host **112**) provide reporting to various individuals (e.g., patient and/or caregiver). For example, different levels of reporting can be provided by (1) the ITU **108** and (2) the host **112**. The ITU **108** may be configured to conduct rudimentary analysis of data gathered from devices **102**, **104**, and **106**, and provide reporting should an acute situation be identified. For example, if the ITU **108** detects that a significant heart arrhythmia is imminent or currently taking place, the ITU **108** provides reporting to the patient in the form of an audible or visual alarm.

The host **112** can provide a more sophisticated reporting system. For example, the host **112** can provide exception-based reporting and alerts that categorize different reporting events based on importance. Some reporting events do not require caregiver intervention and therefore can be reported automatically. In other escalating situations, caregiver and/or emergency response personnel need to become involved. For example, based on the data collected by the advanced patient management system **100**, the delivery module **118** can communicate directly with the devices **102**, **104**, and **106**, contact a pharmacy to order a specific medication for the patient, and/or contact **911** emergency response. In an alternative embodiment, the delivery module **118** and/or the patient may also establish a voice communication link between the patient and a caregiver, if warranted.

In addition to forms of reporting including visual and/or audible information, the advanced patient management system **100** can also communicate with and reconfigure one or more of the devices **102**, **104**, and **106**. For example, if

device **102** is part of a cardiac rhythm management system, the host **112** can communicate with the device **102** and reconfigure the therapy provided by the cardiac rhythm management system based on the data collected from one or more of the devices **102**, **104**, and **106**. In another embodiment, the delivery module **118** can provide to the ITU **108** recorded data, an ideal range for the data, a conclusion based on the recorded data, and a recommended course of action. This information can be displayed on the ITU **108** for the patient to review or made available on the peripheral device **109** for the patient and/or clinician to review.

One or more headings have been provided above to assist in describing the various embodiments disclosed herein. The use of headings, and the resulting division of the description by the headings, should not be construed as limiting in any way. The subject matter described under one heading can be combined with subject matter described under one or more of the other headings without limitation and as desired.

V. Repeater Communications

FIG. 5 shows a patient **602** that has a medical device **604** coupled thereto. In this example, the medical device **604** is an implantable medical device such as a pacemaker. The medical device **604** communicates bi-directionally with a repeater device **610**, such as an ITU **108** described above, by sending signals **606** to the repeater **610** and receiving signals **608** sent by the repeater **610**. Signals **606**, **608** can be achieved through inductive coupling, RF electromagnetic signaling, acoustic signaling, or other signaling methods known in the art. Furthermore, the signaling may occur wirelessly or through a wired connection, depending upon whether the device **604** is implanted or external to the patient's body **602**.

Typically, an implanted medical device **604** will communicate using on-board telemetry as is known in the art. The on-board telemetry of the implanted medical device **604** performs a handshake with an external device such as the repeater device **610** to establish communications. The repeater device **610** interrogates the medical device **604** to retrieve data that the medical device **604** has been storing in on-board memory. For example, an implantable medical device **604** may store the number of times a particular cardiac episode has occurred since the last time the repeater device **610** downloaded the data.

The repeater device **610** captures the data and stores it in on-board memory, as discussed in greater detail below. Subsequently, the repeater device **610** transmits the data through a communication medium **612** to a data repository **614**, such as an advanced patient management system maintaining a database of patient information as discussed above. The communication medium **612** and associated form of communication between the repeater device **610** and the repository **614** can take on various forms known in the art as discussed above in relation to the communication system **110** of FIGS. 1 and 4.

For example, a public switched telephone network (PSTN) may be used whereby the repeater device **610** accesses the telephone line of the patient's home and places a call to a repository telephone number to establish the connection entirely through the PSTN. As one alternative, the repeater device **610** may utilize a dial-up connection or an always-on connection to an Internet Service Provider (ISP) where the repository **614** is accessible through the Internet. Additionally, as discussed above, the repeater device **610** may incorporate wireless communication abili-

ties enabling the repeater device **610** to transmit data wirelessly to the PSTN or wireless Internet through a cellular base station.

As mentioned above, the communication between the repeater device **610** and the medical device **604** may be bi-directional so that the repeater device **610** can also send data to the medical device **604**. Furthermore, the communication between the repeater device **610** and the repository **614** may be bi-directional. This enables the repeater device **610** to forward data from the medical device **604** to the repository **614** and also forward data from the repository **614** to the medical device **604**.

For instance, the repeater device **610** may forward data from the medical device **604** to the repository **614**. After analysis of the data at the repository **614**, it may be determined that reprogramming of the medical device **604** is necessary to compensate for a change in the patient's condition. The new programming may then be transferred from the repository **614** through the repeater device **610** to the medical device **604** where it can be implemented.

FIG. 6 is a view of an exemplary repeater device **610**. The repeater device **610** may include audio and/or visual annunciation abilities to communicate progress and or alerts to the patient **602**. For example, a liquid crystal display (LCD) **704** may be included to provide a visual cue to the patient about progress of upload from the medical device **604** and the progress of download to the repository **614**. Furthermore, LCD **704** may be used to provide instructions for use of the medical device **604** and/or repeater device **610** as well as alerts. Similarly, an audio speaker **702** may provide audible cues including progress reports and warnings to the patient **602**. Various other types of annunciation may be employed as well, including light emitting diodes (LEDs), etc.

In some embodiments, the repeater device **610** may include intelligence for analyzing the data being retrieved from the medical device **604**. For example, the repeater device **610** may include programming that analyzes the data for episodes of cardiac activity that are precursors to a serious cardiac event. In this case, the repeater device **610** may annunciate to the patient **602** that a visit to a physician is necessary and immediately notify the repository **614** of the emergency situation. Likewise, the data from the medical device **604** may indicate that the medical device **604** itself has a problem, such as a broken cardiac lead. The repeater device **610** may be programmed to recognize this condition from the retrieved data and annunciate to the patient **602** that a visit to the physician is necessary.

FIG. 7 is a view of the major components of the exemplary repeater device **610** of FIG. 5. This repeater device **610** contains telemetry **802** that enables communication with a medical device **604**, such as an implantable medical device (IMD). As discussed above, such telemetry **802** may employ inductive coupling techniques to wirelessly transmit data to and from the repeater device **610**. RF communications are a wireless alternative to inductive coupling and provide better range between the medical device **604** and the repeater device **610**. Wired connections from the medical device **604** to telemetry **802** are another alternative for medical devices **604** worn externally.

The telemetry **802** demodulates or otherwise recovers data from the signal from the medical device **604** and provides the data to the processor **808**. Alternatively, the telemetry **802** provides the received signal to the processor **808** which then demodulates or otherwise recovers the data from the signal. The processor **808** stores the data in memory **812**, such as random access memory (RAM) where it can

later be accessed. In certain embodiments, the processor **808** may perform data analysis to determine the urgency of the data.

Data analysis by the repeater **610** may include analyzing raw data recorded by the medical device **604** to detect physiological conditions and specific episodes. Data analysis may also include interpreting data generated by the medical device **604** that signals such conditions and episodes, such as where the medical device **604** analyzes raw data to determine the conditions and episodes prior to sending the data to the repeater **610**. Data analysis of raw data to determine physiological condition and specific episodes is well known in the art, but examples include detecting cardiac arrhythmias, conduction disorders, pulse rate, episodes of tachycardia or bradycardia, and other physiological conditions.

The processor **808** provides the data from memory **812** to an external communications device **806**, such as a telephone line interface (modem), a wireless digital or analog RF transceiver, and/or an always-on Internet connection (i.e., cable or DSL modem). The external communications device **806** interfaces with the communication medium **612** to transfer the data to the repository **614**. Data transfer may occur through techniques well known in the art, including standard modulation techniques, circuit switched connections, and/or packet switched connections as is appropriate. The external communications device **806** is also configurable to receive data from the repository **614** through the communication medium **612**.

The processor **808** controls annunciation devices including the display circuit **804** and audio circuit **810** to provide information to the user **602**. The display circuit **804** controls the LCD display **704** to provide visual information such as instructions for use, problems with the repeater **610** or medical device **604**, or emergency alerts. Likewise, the audio circuit **810** controls the speaker **702** to provide audible information.

Logical operations of the processor **808** and its interaction with the various components shown in FIG. 7 are shown for several different embodiments in FIGS. 9–11. These logical operations of the various embodiments of the present invention are implemented (1) as a sequence of computer implemented acts or program modules and/or (2) as interconnected machine logic circuits or circuit modules. The implementation is a matter of choice dependent on the performance requirements of the repeater **610**. Accordingly, the logical operations making up embodiments of the present invention described herein are referred to variously as operations, structural devices, acts, or modules. It will be recognized by one skilled in the art that these operations, structural devices, acts and modules may be implemented in software, in firmware, in special purpose digital logic, and any combination thereof without deviating from the spirit and scope of the present invention as recited within the claims attached hereto.

FIG. 8 shows exemplary logical operations where the repeater **610** considers the urgency of the data when coordinating the transfer of data to the repository **614**. The operations begin with the processor **808** initiating communication with the medical device **604** through the telemetry **802** at communication operation **902**. At data operation **904**, the processor **808** retrieves the data through the telemetry **802** and stores the data in memory **812**. At analysis operation **906**, the processor **808** reviews the data to determine the degree of urgency. As discussed above, the processor **808** may review the data to determine whether the medical device **604** has found a specific condition or episode, or the

processor **808** may employ its own analysis logic on the raw data recorded by the medical device **604** to find a specific condition or episode. In addition to or as an alternative to determining the degree of urgency based on analysis of the data, the processor may detect the degree of urgency by receiving input provided by a user. For example, the patient may press a button of the repeater that provides a signal to the processor **808** that the patient knows the data should be treated as urgent such as if a particular episode is occurring that the patient is aware of.

At query operation **908**, the processor **808** detects from the analysis or otherwise whether the degree of urgency of the data indicates an emergency situation, such as where the data analysis shows that the user **602** needs immediate medical attention due to an imminent cardiac arrest or if the patient has indicated that the data is urgent. When the degree of urgency indicates an emergency situation, the repeater **610** proceeds to immediately initiate communication at communication operation **910**. A notice of the emergency situation is transferred to the repository **614** at notice operation **912** to trigger an alarm so that repository personnel may take emergency action including dispatching paramedics to the user's location.

The repeater **610** also warns the user **602** of the emergency through visual and/or audible warnings at notice operation **914**. The data stored in memory **812**, including at least the data signaling the emergency situation, may then be transferred to the repository **614** at transfer operation **916**. The repository personnel may then review the data to further assess the situation and assist paramedics.

If query operation **908** detects that there is no emergency, then query operation **918** tests whether the analyzed data indicates a problem. A problem may be detected from the data where the medical device **604** reports a malfunction, such as a broken cardiac lead, or reports other information that indicates the patient **602** should seek medical attention by some future point in time, although not immediately. If such a problem is detected, then the repeater **610** provides audible and/or visual notice of the problem to the user **602** at notice operation **920**.

Once notice of the problem has been given to the user **602**, or if query operation **918** detects no problem, then operational flow transitions to query operation **922** which detects whether it is an appropriate time to transfer data to the repository **614**. For example, the repeater **610** may be configured so that transfers occur over a telephone line during low-activity periods such as 3 a.m. Other factors may be considered as well in addition to or as an alternative to the time of day. If query operation **922** detects that the proper time has arrived, then the processor **808** initiates communication with the repository **614** at communication operation **926**. Data is then transferred to the repository **614** at transfer operation **928**. If the proper time for transfer has not arrived, then the processor **808** waits out a delay **924**, and then query operation **922** again detects whether the proper time has arrived.

FIG. 9 shows the logical operations where the repeater **610** considers the condition of the communication medium when coordinating transfer of data to the repository **614**. The logical operations begin at communication operation **1002** where the repeater **610** initiates communication with the medical device **604**. The repeater **610** retrieves the data from the medical device **604** and stores it in memory **812** at data operation **1004**.

After the data has been obtained from the medical device **604**, the repeater **610** checks the condition of the external communication medium **614** through interface **806** at test

operation **1006**. In this example, checking the condition of the communication medium **614** involves determining whether the telephone line is already in use. Other communication medium conditions may be determined as well. For example, if a wireless connection is being used to communicate with the repository **614**, the strength of the wireless signal may be referenced to determine whether the signal is strong enough to communicate. As another example, if the Internet is being used to transfer data to the repository **614**, the available bandwidth through the Internet connection may be determined to decide whether the data should be transferred.

The processor **808** may be configured so that test operation **1006** occurs as soon as the data has been retrieved or occurs at a later point in time, such as at a low-activity part of the day. After test operation **1006** has been performed, query operation **1008** detects whether the condition of the communication medium **614** is satisfactory. In this example, query operation **1008** detects whether the telephone line is in use. If so, the processor **808** stalls data transfer for a delay period **1010**, and operational flow returns to test operation **1006** to again check the condition of the communication medium.

Once query operation **1008** detects that the telephone line is not in use, then communication operation **1012** initiates communication through the interface **806** with the repository **614**. Once communication has been established, then data is transferred between the repeater device **610** and the repository **614** at transfer operation **1014**.

FIG. **10** shows an example of logical operations of the repeater device **610** where both the urgency of the data and the condition of the communication medium are considered when coordinating data transfer to the repository **614**. The operations begin with the processor **808** initiating communication with the medical device **604** through the telemetry **802** at communication operation **112**. At data operation **1104**, the processor **808** retrieves the data through the telemetry **802** and stores the data in memory **812**. At analysis operation **1106**, the processor **808** reviews the data to determine the degree of urgency.

At query operation **1108**, the processor **808** detects from the analysis whether the degree of urgency of the data indicates an emergency situation, such as where the data analysis shows that the user **602** needs immediate medical attention due to an imminent cardiac arrest. When the degree of urgency indicates an emergency situation, the repeater **610** proceeds to immediately detect whether the telephone line is in use at query operation **1110**. If so, then the telephone line interface **806** short circuits the telephone line to disconnect the current telephone call that is occupying the telephone line.

Once the telephone line has been freed or once query operation **1110** detects that the telephone line is not in use, the processor **808** initiates communication at communication operation **1114**. A notice of the emergency situation is transferred to the repository **614** at notice operation **1116** to trigger an alarm so that repository personnel may take emergency action including dispatching paramedics to the user's location.

The repeater **610** also warns the user **602** of the emergency through visual and/or audible warnings at notice operation **1118**. The data stored in memory **812**, including at least the data signaling the emergency situation, may then be transferred to the repository **614** at transfer operation **1120**. The repository personnel may then review the data to further assess the situation and assist paramedics.

If query operation **1108** detects that there is no emergency, then query operation **1122** tests whether the analyzed data indicates a problem. As discussed above, a problem may be detected from the data where the medical device **604** reports a malfunction, such as a broken cardiac lead, or reports other information that indicates the patient **602** should seek medical attention by some future point in time, although not immediately. If such a problem is detected, then the repeater **610** provides audible and/or visual notice of the problem to the user **602** at notice operation **1124**.

Once notice of the problem has been given to the user **602**, or if query operation **1122** detects no problem, then operational flow transitions to query operation **1126** which detects whether it is an appropriate time to transfer data to the repository **614**, such as during a low-activity period. If query operation **1126** detects that the proper time for transfer has not arrived, then the processor **808** waits out a delay **1128**, and then query operation **1126** again detects whether the proper time has arrived.

If query operation **1126** detects that the proper time has arrived, then query operation **1130** detects whether the telephone line is in use. If so, then the processor **808** stalls for a delay period **1132** and then again checks the telephone line at query operation **1130**. If the telephone line is not in use, then the processor **808** initiates communication with the repository **614** at communication operation **1134**. Data is then transferred to the repository **614** at transfer operation **1136**.

The various embodiments described above are provided by way of illustration only and should not be construed to limit the invention. Those skilled in the art will readily recognize various modifications and changes that may be made to the present invention without following the example embodiments and applications illustrated and described herein, and without departing from the true spirit and scope of the present invention, which is set forth in the following claims.

What is claimed is:

1. A repeater for relaying data to a repository from a medical device coupled to a patient, comprising:
 - a receiver configured to communicate with the medical device to obtain the data;
 - a memory to maintain the data once it has been received;
 - a transmission device configured to send the data over a wireless radio frequency connection to a data repository; and
 - a processing device configured to detect a signal strength that is available through the wireless radio frequency connection and trigger the transmission device to send the data when the signal strength is adequate for transmission.
2. A method of providing data between a medical device coupled to a patient and a repository, comprising the steps of:
 - retrieving the data from the medical device;
 - storing the data once it has been received;
 - detecting a condition of a wireless radio frequency connection to send the data over; and
 - transmitting the data over the wireless radio frequency connection when the condition of the wireless radio frequency connection is adequate for transmission.
3. A repeater for relaying data to a repository from a medical device coupled to a patient, comprising:
 - a receiver configured to communicate with the medical device to obtain the data;
 - a memory to maintain the data once it has been received;

21

a transmission device configured to send the data over a communication medium; and
 a processing device configured to detect a degree of urgency by analyzing the data to detect health conditions of the patient, and trigger the transmission device to send the data to the repository at a time based on the degree of urgency.

4. The repeater of claim 3, wherein the communication medium comprises a landline connection to a public switched telephone network.

5. The repeater of claim 3, wherein the communication medium comprises a wireless radio frequency connection.

6. The repeater of claim 3, wherein the receiver communicates with the medical device through inductive coupling.

7. The repeater of claim 3, wherein the receiver communicates with the medical device that is subcutaneously positioned.

8. The repeater of claim 3, wherein the processing device is further configured to detect the degree of urgency by receiving subjective data provided by the patient.

9. A method of providing data between a medical device coupled to a patient and a repository, comprising the steps of:

retrieving the data from the medical device;
 storing the data once it has been received;
 detecting a degree of urgency by analyzing the data to detect health conditions of the patient; and
 determining a time to transmit the data over the communications medium based on the detected degree of urgency.

10. The method of claim 9, wherein the communication medium comprises a landline connection to a public switched telephone network.

11. The method of claim 9, wherein the communications medium comprises a wireless radio frequency connection.

12. The method of claim 9, wherein the step of retrieving the data comprises inductively coupling the repeater to the medical device.

13. The method of claim 9, wherein the step of retrieving the data comprises communicating with the medical device that is subcutaneously positioned.

14. The method of claim 9, wherein the step of detecting the degree of urgency further comprises receiving subjective data provided by the patient.

22

15. A repeater for providing data between a medical device coupled to a patient and a repository, comprising the steps of:

means for retrieving the data from the medical device;
 means for storing the data once it has been received;
 means for detecting a degree of urgency of the data, wherein the means for detecting the degree of urgency analyzes the data to detect health conditions of the patient; and

means for determining a time to transmit the data over the communications medium based on the detected degree of urgency.

16. The repeater of claim 15, wherein the communication medium comprises a landline connection to a public switched telephone network.

17. The repeater of claim 15, wherein the communications medium comprises a wireless radio frequency connection.

18. The repeater of claim 15, wherein the means for retrieving the data inductively couples the repeater to the medical device.

19. The repeater of claim 15, wherein the means for retrieving the data communicates with the medical device that is subcutaneously positioned.

20. The repeater of claim 15, wherein the means for detecting the degree of urgency receives subjective data provided by the patient.

21. A system for sending data from a medical device to a data repository, the system comprising:

a medical device coupled to a patient;

a data repository; and

a repeater having:

a receiver for receiving data from the medical device,

a memory device for storing the data,

a transmission device capable of sending the data to the data repository, and

a processing device configured to detect a degree of urgency by analyzing the data to detect health conditions of the patient, and trigger the transmission device to send the data at a time based on the degree of urgency.

22. The system of claim 21, wherein the medical device comprises at least one of a pacemaker and a defibrillator.

* * * * *

专利名称(译)	用于与植入式医疗设备通信的中继器设备		
公开(公告)号	US7009511	公开(公告)日	2006-03-07
申请号	US10/321885	申请日	2002-12-17
[标]申请(专利权)人(译)	心脏起搏器股份公司		
申请(专利权)人(译)	心脏起搏器, INC.		
当前申请(专利权)人(译)	心脏起搏器, INC.		
[标]发明人	MAZAR SCOTT T MANICKA YATHEENDBAR D		
发明人	MAZAR, SCOTT T. MANICKA, YATHEENDBAR D.		
IPC分类号	G08B1/00 A61B5/00 A61B5/0205 A61B5/0215 A61B5/08 G06F19/00 G06Q50/22 G06Q50/24 G16H10/60 H04B17/40		
CPC分类号	A61B5/0031 A61B5/0022 A61B5/0809 A61B5/4839 G06F19/3406 G06F19/3418 G06F19/345 G06Q50/22 G06Q50/24 H04B17/00 A61B5/02055 A61B5/0215 A61B5/14532 A61B2560/0209 A61B2560/0271 A61B2560/045 G06F19/322 G06F19/3493 A61B5/747 G16H10/60 G16H40/63 G16H40/67 G16H50/20 G16H50/80 G16H70/20		
其他公开文献	US20040117204A1		
外部链接	Espacenet USPTO		

摘要(译)

用于高级患者管理系统的转发器设备与耦合到患者的医疗设备通信以获得关于医疗设备和/或患者状况的数据。如果在协调将数据传输到高级患者管理系统的存储库时考虑各种因素,则转发器设备维护数据。转发器设备可以被配置为分析数据以确定紧急程度,例如是否存在紧急情况,然后基于紧急程度确定何时转移数据。转发器设备还可以被配置为测试用于将数据传输到存储库的通信介质的状况,例如确定电话线是否在使用中,然后基于条件确定何时传输数据。通讯媒介。

