



US007822463B2

(12) **United States Patent**  
**Merón et al.**

(10) **Patent No.:** **US 7,822,463 B2**  
 (45) **Date of Patent:** **\*Oct. 26, 2010**

(54) **METHOD FOR DELIVERING A DEVICE TO A TARGET LOCATION**

(75) Inventors: **Gavriel Merón**, Petach Tikva (IL);  
**Gavriel J. Iddan**, Haifa (IL)

(73) Assignee: **Given Imaging Ltd.**, Yoqneam (IL)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 914 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **11/166,141**

(22) Filed: **Jun. 27, 2005**

(65) **Prior Publication Data**

US 2006/0004285 A1 Jan. 5, 2006

**Related U.S. Application Data**

(63) Continuation of application No. 09/807,892, filed as application No. PCT/IL99/00554 on Oct. 21, 1999, now Pat. No. 6,950,690.

(30) **Foreign Application Priority Data**

Oct. 22, 1998 (IL) ..... 126727

(51) **Int. Cl.**

**A61B 5/05** (2006.01)

**A61B 1/04** (2006.01)

**G06K 9/00** (2006.01)

(52) **U.S. Cl.** ..... **600/424**; 382/128; 600/117

(58) **Field of Classification Search** ..... 600/109, 600/117, 160, 424, 476; 348/65, 76; 382/128  
 See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

3,971,362 A	7/1976	Pope et al.	
4,239,040 A *	12/1980	Hosoya et al.	604/135
4,278,077 A	7/1981	Mizumoto	
4,439,197 A	3/1984	Honda et al.	
4,689,621 A	8/1987	Kleinberg	
4,803,992 A	2/1989	Lemelson	
4,844,076 A	7/1989	Lesho et al.	
5,042,486 A	8/1991	Pfeiler et al.	

(Continued)

**FOREIGN PATENT DOCUMENTS**

DE 34 40 177 5/1986

(Continued)

**OTHER PUBLICATIONS**

The Radio Pill, Rowlands, et al. British Communication and Electronics, Aug. 1960, pp. 598-601.

(Continued)

*Primary Examiner*—Long V Le


*Assistant Examiner*—Salieu M Abraham

(74) *Attorney, Agent, or Firm*—Pearl Cohen Zedek Latzer, LLP

(57) **ABSTRACT**

An autonomous device that may include for example a camera, a transmitter for transmitting a signal from the camera and a storage compartment for retaining a substance in the device. A method of delivering a medicament to a patient including imaging a gastro intestinal tract with an autonomous device, identifying a target location in such tract, and releasing a medicament from the device at the target location.

**13 Claims, 5 Drawing Sheets**



## U.S. PATENT DOCUMENTS

5,081,041 A 1/1992 Yafuso et al.  
 5,109,870 A 5/1992 Silny et al.  
 5,211,165 A 5/1993 Dumoulin et al.  
 5,279,607 A \* 1/1994 Schentag et al. .... 604/890.1  
 5,330,427 A 7/1994 Weissenburger  
 5,395,366 A 3/1995 D'Andrea et al.  
 5,429,132 A 7/1995 Guy et al.  
 5,479,935 A 1/1996 Essen-Moller  
 5,558,640 A 9/1996 Pfeiler et al.  
 5,604,531 A \* 2/1997 Iddan et al. .... 348/76  
 5,800,350 A 9/1998 Coppleson et al.  
 5,819,736 A 10/1998 Avny et al.  
 5,833,603 A 11/1998 Kovacs et al.  
 5,837,196 A 11/1998 Pinkel et al.  
 5,913,820 A 6/1999 Bladen et al.  
 5,993,378 A \* 11/1999 Lemelson ..... 600/109  
 6,099,482 A 8/2000 Brune et al.  
 6,149,581 A 11/2000 Klingenstein  
 6,285,897 B1 9/2001 Kilcoyne et al.  
 6,324,418 B1 \* 11/2001 Crowley et al. .... 600/476  
 6,369,812 B1 \* 4/2002 Iyriboz et al. .... 345/419  
 6,395,562 B1 5/2002 Hammock et al.  
 6,475,145 B1 11/2002 Baylor  
 6,488,694 B1 12/2002 Lau et al.  
 2001/0035902 A1 11/2001 Iddan et al.  
 2002/0001695 A1 1/2002 Tajima et al.  
 2002/0015952 A1 2/2002 Anderson et al.  
 2002/0103417 A1 8/2002 Gazdzinski  
 2002/0173718 A1 11/2002 Frisch et al.  
 2002/0177779 A1 11/2002 Adler et al.  
 2002/0198439 A1 12/2002 Mizuno  
 2003/0020810 A1 1/2003 Takizawa et al.

2003/0023150 A1 1/2003 Yokoi et al.

## FOREIGN PATENT DOCUMENTS

FR	2688997	10/1993
JP	4109927	4/1992
JP	5015515	1/1993
JP	6285044	4/1993
JP	7111985	5/1995
JP	2002010990	1/2002
WO	WO 99/32028	7/1999
WO	WO 00/22975	4/2000
WO	WO 01/08548	2/2001
WO	WO 02/55984	7/2002

## OTHER PUBLICATIONS

Wellesley company sends body montiors into space—Crum, Apr. 1998.  
 Wireless transmission of a color television moving images from the stomach using a mioiature CCD camera light source and microwave transmitter. Swiss CP, Gong F, Mills TN. Gastrointest Endosc 1997;45:AB40.  
 “Heidelberger Kapsel—ein Kleinstsender fur die pH-Messung im Magen”, Lange, et al Ielefunken-Zeitung. Ig 36 (1963) Heft 5, pp. 265-270.  
 “New smart plastic has good memory”—Jurke 2001.  
 Supplementary Partial European Search Report, Mar. 19, 2004.  
 Heidelberger Kapsel—ein Kleinstsender fur die pH-Messung Im Magen Lange . et al Telefunken-Zeitung Jg 38 (1983) Heft 5, pp. 265-270.  
 International Search Report for PCT/IL99/00554 dated Apr. 4, 2000.  
 Video Camera to “TAKE” - RF System Lab, Dec. 2001.  
 “New Smart Plastic Has Good Memory” - Turke, 2001.

\* cited by examiner




FIG.1




FIG. 2




FIG. 3




FIG. 4




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 6




FIG. 7

# METHOD FOR DELIVERING A DEVICE TO A TARGET LOCATION

## CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a Continuation Application of U.S. patent application Ser. No 09/807,892, filed on Jun. 6, 2001, now U.S. Pat. No. 6,950,690, which is a national phase application of International Application PCT/LL99/00554 filed Oct. 21, 1999, which in turn takes benefit from Israeli Patent Application 126727 filed on Oct. 22, 1998, all of which are incorporated by reference herein in their entirety.

## FIELD OF THE INVENTION

The present invention relates to a method for identifying a target location in the gastrointestinal tract and for direct delivery of a device to the identified location

## BACKGROUND OF THE INVENTION

In the gastrointestinal tract, the stomach is connected, through the small intestine, a long tube that folds many times to fit inside the abdomen, to the large intestine. There are numerous pathologies of the gastrointestinal tract, such as lesions causing chronic gastrointestinal tract blood loss, which occurs in about 2% of US adults, malignancies, most of which give a poor prognosis, and bowel obstructions; simple, closed-loop, strangulated and incarcerated. Some of these pathologies, such as small intestinal tumors, are difficult to diagnose. Diagnostic methods of the small intestine are usually symptom related or invasive, such as barium enemas or surgery. New methods of diagnosis can lead to an earlier diagnosis and improved prognosis.

U.S. Pat. No. 5,604,531 describes an in vivo video camera system which can image the gastrointestinal tract. Reference is now made to FIG. 1, which is a block diagram illustration of a prior art in vivo video camera system for imaging the gastrointestinal tract. The in vivo video camera system typically comprises a swallowable capsule 10 for viewing inside the digestive system and for transmitting video data, a reception system 12 typically located outside a patient and a data processor 14 for processing the video data. The data processor 14 typically operates two monitors, a position monitor 16 on which the current location of the capsule 10 within the digestive system is displayed and an image monitor 18 on which the image currently viewed by the capsule 10 is displayed.

The reception system 12 can either be portable, in which case, the data it receives is temporarily stored in a storage unit 19, prior to its processing in data processor 14, or it can be stationary and close to the data processor 14.

Reference is now made to FIGS. 2 and 3 which are a schematic illustration of calculations performed by a prior art data processor for processing the video data obtained by the above in vivo video camera system. FIG. 2 is a front view illustration of the patient 22 with an antenna array 30 wrapped around him. On it, four antennas 34a-34d are noted. Antennas 34a and 34b are located in a column at one side of the patient 22 and antennas 34c and 34d are located in a column at the other side of the patient 22.

Since the strength of a signal received by any given antenna depends on its distance from and angle to the transmitter, the ratio of the signal strengths between any two antennas, which have the transmitter between them, is constant along a curve

which intersects the location of the transmitter. Thus, antennas 34a and 34b define curve 30a and antennas 34c and 34d define curve 30b.

The intersection of curves 30a and 30b is the location of the transmitter which is the location of the capsule 10. The curves 30a and 30b are typically determined in a calibration step for a predefined number of constant values.

The designation of antennas 34a-34d depends on and is determined from the width  $L_1$  of the patient 22, which value is typically provided to data processor 14 (of FIG. 1). Alternatively, there can be a plurality of antenna arrays 30, one for each of a pre-defined number of widths  $L_1$ . The antennas 34a-34d are then constant for each antenna array 30.

The location of the capsule 10, thus generated, is typically denoted by a two-dimensional vector P, having a length P and an angle  $\square$ , from the center point O of an X-Y coordinate system.

The cross-sectional location (within an X-Z plane) of the capsule 10 can also be determined using a similar calculation to that illustrated in FIG. 2. A cross-section of the patient 22 is illustrated in FIG. 3. For this determination, four antennas 34e-34h, which are opposite in a cross-sectional manner, are utilized.

Once again, the ratio of the signal strengths between two antennas, which have the transmitter between them, is constant along a curve which intersects the location of the transmitter. Thus, antennas 34e and 34h define curve 30c and antennas 34f and 34g define curve 30d.

The location of the capsule 10 thus generated is typically denoted by a two-dimensional vector Q having a length Q and an angle  $\square$ , from the center point O).

The two vectors P and Q are combined to determine the three-dimensional location of the capsule 10. The location can be displayed two- or three-dimensionally on position monitor 16 (of FIG. 1), typically, though not necessarily, as an overlay to a drawing of the digestive tract.

There exist methods for the delivery of medicament to a selected site in the gastrointestinal tract, such as the use of time delivery capsules made of material that dissolves in a particular environment and/or within a particular time period, within the gastrointestinal tract. In these methods, the delivery of medicament is dependent on the predictability of the particular environment to which the capsule is directed.

Controllable apparatuses for delivery of medicaments are described in U.S. Pat. Nos. 5,558,640 and 4,239,040. While using these apparatuses or capsules the delivery of medicament may be obstructed, such as by folds in the intestine.

These methods can not be relied upon for localized release of a medicament.

U.S. Pat. No. 5,279,607 describes a method of obtaining directional data from the passage of an ingestible radio signal transmitting capsule. This data is subsequently compared to directional data from a capsule carrying medicament passing through the alimentary canal, for remotely triggering the release of medicament at a calculated geometric location along the gastrointestinal tract. A location selected in this method, cannot be aligned with sites of interest, such as pathologies, since no diagnostic information, such as information relating to the pathology, can be obtained in this method. Furthermore, due to the constant peristaltic movement of the alimentary canal, the geometric location of a site is not the same in a first and second pass, so that this one parameter is only partially sufficient for selection of a site.

There exist no medicament delivering systems which combine diagnostic and therapeutic processes.



## SUMMARY OF THE INVENTION

It is an object of the present invention to provide a method for delivering a utility device to a target location in the gastrointestinal tract. The method combines identification of a target in the gastrointestinal tract and delivery of a utility device to the identified target location. The method of the present invention comprises the steps of:

a) generating a map of the gastrointestinal tract, employing a sensing and utility device for a first pass, or, optionally, a plurality of passes through the gastrointestinal tract; and

b) delivering the sensing and utility device to a target location identified on the map, using the sensing and utility device in a second pass or, optionally, a plurality of passes, through the gastrointestinal tract. The sensing and utility device used in the second pass, may be the same or different than the device used in the first pass.

The term "sensing and utility device", in the present invention, refers to a device which is swallowable or placeable (such as described in IL patent application number 122716, assigned to the common assignees of the present invention and which is hereby incorporated by reference), and is capable of sensing selected parameters of the gastrointestinal tract. The device also comprises means for performing a job in the gastrointestinal tract. It is controllable and is capable of being monitored and of generating a map of the gastrointestinal tract.

The sensing and utility device may comprise, for example, any one or any combination of a video camera, which generates an image of the gastrointestinal tract, or sensing means, such as temperature, pressure or pH sensors or means for sensing the presence of blood, microorganisms, parasites or pathological indications or any objects alien to the gastrointestinal tract.

Means for performing a job may be any means suitable for researching, diagnosing or treating pathologies in the gastrointestinal tract, for example, fluid or cell sampling means, marker releasing means or medicament releasing means.

A map of the gastrointestinal tract may be generated by inserting the sensing and utility device into the gastrointestinal tract, monitoring the progress of the device through the gastrointestinal tract and optionally displaying the locations, two or three dimensionally, on a position monitor.

Monitoring the device is by periodically or repeatedly locating the device, preferably, as described in U.S. Pat. No. 5,604,531 assigned to the common assignees of the present invention. U.S. Pat. No. 5,604,531 is hereby incorporated by reference.

Delivering the sensing and utility device to a target location identified on the map comprises the steps of inserting the sensing and utility device into the gastrointestinal tract, in a second pass, receiving data from the device, either visual, from a video camera, or from the output of other sensing means, performing signal analysis of the data generated in the first pass and the data received from said sensing and utility device in the second pass; and controlling, such as by IR or telephony, the sensing and utility device according to the signal analysis.

The method of the present invention may be used for research, diagnostic or therapeutic purposes in the gastrointestinal tract.

## BRIEF DESCRIPTION OF THE FIGURES

The present invention will be understood and appreciated more fully from the following detailed description taken in conjunction with the drawings in which:

FIG. 1 is a block diagram illustration of a prior art in vivo video camera system for imaging the gastrointestinal tract;

FIGS. 2 and 3 are schematic illustrations of calculations performed by a prior art data processor for processing the video data obtained by the in vivo video camera system for imaging the gastrointestinal tract, utilizing an antenna array, wherein FIG. 3 is a top view illustration of the antenna array and FIG. 2 is a cross-sectional illustration of the antenna array.

FIG. 4 is an illustration of a sensing and utility device according to a preferred embodiment of the invention;

FIG. 5A is an illustration of a storage compartment, according to a preferred embodiment of the invention, in a recoiled position of the bi stable spring;

FIG. 5B is an illustration of a storage compartment, according to a preferred embodiment of the invention, in an extended position of the bi stable spring;

FIG. 5C is an enlargement of the storage compartment tip, according to a preferred embodiment of the invention;

FIG. 6 is an illustration of a sensing and utility device operable according to a preferred embodiment of the invention; and

FIG. 7 is an illustration of a generated and displayed map in the method according to a preferred embodiment of the invention.

## DETAILED DESCRIPTION OF THE INVENTION

The method of the present invention combines diagnostic and therapeutic processes. For example, the method combines identifying and localizing a pathology in the gastrointestinal tract with administering treatment to the location of the pathology, by non invasive means. This combination is provided by employing a sensing and utility device which is inserted into the gastrointestinal tract, either by swallowing it or by placing it in the gastrointestinal tract. The above mentioned IL patent application 122716 describes a device for the placement of an autonomous capsule in the gastrointestinal tract, which bypasses the need for swallowing the capsule by the patient.

Reference is now made to FIG. 4 which is an illustration of a sensing and utility device according to a preferred embodiment of the invention. The sensing and utility capsule shaped device, generally referenced 40, typically comprises a light source 42, a viewing window 44, through which the light illuminates the inner portions of the digestive system, a camera system 46, such as a charge-coupled device (CCD) or CMOS camera, which detects the images, an optical system 48 (typically comprising a mirror 47 and a focusing lens 47') which focuses the images onto the CCD or CMOS camera system 46, a transmitter 41, which transmits the video signal of the CCD or CMOS camera system 46, a power source 43, such as a battery, which provides power to the entirety of electrical elements of the capsule and a storage compartment 45, for the controllable discharge of medicaments or markers or for the controllable collection of fluid or cell samples from the environment, such as in a biopsy procedure.

The sensing and utility device can additionally include any known sensor element 49 such as temperature, pressure or pH sensors or means for sensing the presence of blood, microorganisms, parasites or pathological indications or any objects alien to the gastrointestinal tract.

Reference is now made to FIGS. 5A, 5B and 5C which are illustrations of a storage compartment, according to a preferred embodiment of the invention

Storage compartment 55 is located preferably at an end of the sensing and utility device, generally referenced 50. The

storage compartment is defined by an inflexible barrier **59** and the device shell. The storage compartment contains a pouch **56** made of flexible material which is encased by the device outer shell **52** and by a firm diaphragm **54** having an elasticity which will allow it to accommodate to a capsule shape. Diaphragm **54** is horizontally movable between the inflexible barrier **59** and the device tip. At the device tip there is an area **58**, in the outer shell of the device, which is permeable and which allows passage of substances from or into the pouch **56**. Permeability may be conferred, for instance by the area **58** being porous or sieve like. The pouch **56** is designed to retain substances such as releasable medicaments or markers or such as fluid or cell samples from the gastrointestinal tract environment. The pouch **56** bulk is determined by a bi stable spring **53**, preferably made of a memory shape metal such as TiNi. The spring **53** is attached, at one end to the solid barrier **59**, and at its other end, to the diaphragm **54**. The spring **53** may be made to extend (as shown in FIG. 5B) or recoil (as shown in FIG. 5A) by providing different temperatures, as known in the art (the means for providing different temperatures, such as conducting wires, are not shown). Thus, the pouch **56** bulk may be reversibly increased or decreased.

FIG. 5A illustrates a piercing pin **57** which is attached to the pouch wall and which protrudes into the pouch **56** inner space, in the direction of the opposing pouch wall **56'**. For releasing a substance from pouch **56** into the gastrointestinal tract environment, spring **53** is made to extend, causing diaphragm **54** to move towards the device end, thrusting the piercing pin **57** into the opposing pouch wall **56'**, rupturing it. A substance contained in the pouch **56** will be released into a space **51** provided between the opposing pouch wall **56'** and the outer shell permeable area **58**. The released substance may then pass through the openings in the permeable area **58** into the gastrointestinal tract.

FIG. 5B illustrates a pouch **56** meant for collecting a sample from the gastrointestinal tract. In this embodiment the bi stable spring **53** is lodged in opposing pouch wall **56'**. The spring **53** is made to recoil, pulling with it diaphragm **54** and piercing pin **57**, such that piercing pin **57** is dislodged from the opposing pouch wall **56'**, rupturing it and leaving an opening in the pouch, through which substances from the environment are drawn into the pouch **56**. The opening in the pouch is sealed after the sample is drawn in from the environment, ensuring a fixed volume and sterility of the collected sample.

Pin **57** may be a hollow cylinder through which substances may pass to or from the gastrointestinal tract.

FIG. 5C is an enlargement of the device end, through which substances are drawn into, or released from, the pouch. As can be seen in this figure, space **51** is provided, ensuring that the pin **57**, either before being dislodged from wall **56'** for collecting substances, or when piercing wall **56'** for release of substances, doesn't protrude further than the device shell **52** and injure the patient's insides.

Reference is now made to FIGS. 6 and 7. FIG. 6 is an illustration of a sensing and utility device operable according to a preferred embodiment of the invention, and FIG. 7 is an illustration of a map of the gastrointestinal tract generated in the method, according to a preferred embodiment of the invention.

Capsule **60** moves through the gastrointestinal tract **62** in a first pass to generate, by visual means, a map of the gastrointestinal tract and to identify, by visual means or other sensor means, a location of interest in the gastrointestinal tract. In its second pass, capsule **60** moves through the gastrointestinal tract and is controlled to perform a job at the identified location.

Recognition of the location, identified in the first pass, is done, in analyzing unit **65**, by analysis of the map generated in the first pass and bringing into conformity parameters, visual or others, obtained in the first pass and in the second pass. This may be achieved by any of the well known techniques of image matching by correlation, as done in image analysis, or any other suitable signal analysis techniques.

As the capsule **60** moves through the digestive system (gastrointestinal tract) **62**, in its first pass, it views the walls of the digestive system in the method described in FIGS. 2 and 3 and in U.S. Pat. No. 5,604,531, and transmits the resultant images to a reception system **64** typically located outside a patient. The reception system **64** receives a multiplicity of versions of the images, each version received by a different antenna (described in FIGS. 2 and 3) and either stores the received signals in the storage unit **68** or provides the received signals, directly, by IR or telephony, to the data processor **66**. The data processor **66** typically operates two monitors, a position monitor **63**, on which the current location of the capsule **60** within the digestive system is recorded, and, optionally, displayed and an image monitor **61**, on which the image currently viewed by the capsule **60** is displayed.

The reception system **64** can either be portable, in which case, the data it receives is temporarily stored in a storage unit **68** prior to its processing in data processor **66**, or it can be stationary and close to the data processor **66**.

The capsule **60** location can be displayed two- or three-dimensionally on position monitor **63**, typically, though not necessarily, as an overlay to a drawing of the digestive tract. The progress of capsule **60** is monitored by repeated or periodic localization of the capsule, and can be displayed on position monitor **63**.

A forward filming device can be distinguished from a backwards filming device by the flow direction of the image information relating to the direction of the device motion enables more precise localization of the storage compartment end of the device. Furthermore, analysis of the optical flow enables to calculate the device velocity in the gastrointestinal tract.

The repeated localizations generate a map of the route taken by the capsule in the gastrointestinal tract **62**. The generated map **70** is shown in FIG. 7. For maximum accuracy, images displayed on image monitor **61** are compared with the generated map **70** displayed on position monitor **63** to identify the location of a pathology **72**, though, a location may be identified by analysis of parameters other than visual (such as pH, temp, etc.), which were sensed during the first pass in the gastrointestinal tract.

Upon identifying the location of a pathology **72** on the gastrointestinal tract map **70**, either visually or by analysis of other sensor means input, capsule **60** is inserted into the gastrointestinal tract for a second pass. As capsule **60** moves through the digestive system **62**, in its second pass, it is monitored as above. When arriving at the location of the pathology **72**, or at any other point on map **70**, determined as the point for advantageously releasing medicament for the treatment of the pathology, the capsule **60** is controlled to release the medicament from the medicament storage compartment of the capsule (**45** in FIG. 4). The release of the medicament may be autonomous, automatically controlled by analyzing unit **65** or remotely controlled by an external operator.

It will be appreciated by persons skilled in the art that the present invention is not limited by what has been particularly shown and described herein above. Rather the scope of the invention is defined by the claims which follow:

The invention claimed is:

1. A method for administering a medicament to a patient, the method comprising:

imaging a first set of images from an area of the gastrointestinal tract with a first autonomous swallowable device in a first pass through the gastrointestinal tract;

accepting identification of an image of a location of interest in the gastrointestinal tract, with an analyzing unit;

imaging a second set of images from an area of the gastrointestinal tract with the first or a second autonomous swallowable device in a second pass through the gastrointestinal tract;

accepting results of image analysis performed with the analyzing unit by comparing images from the first set with images from the second set to identify in the second set an image of the location of interest corresponding to an image of the location of interest in the first set; and releasing a medicament from said first or second device at said location of interest in the gastrointestinal tract during said second pass through the gastrointestinal tract.

2. The method according to claim 1, comprising transmitting the images obtained by the swallowable device.

3. The method according to claim 1, wherein the release of the medicament from said first or second swallowable device during said second pass through the gastrointestinal tract is controlled by the analyzing unit.

4. The method according to claim 1, wherein the release of the medicament from said first or second swallowable device is controlled automatically by the device.

5. The method according to claim 1, wherein the release of the medicament from said first or second swallowable device is controlled remotely by an external operator.

6. The method according to claim 1, wherein said first or second autonomous device further comprises a sensor element selected from a group consisting of a temperature sensor, a pH sensor, a pressure sensor, and a sensor for sensing pathology.

7. The method according to claim 1, further comprising transmitting said images to an antenna array, said antenna array being outside a patient.

8. The method according to claim 1, wherein imaging the first set of images is performed by the first autonomous swallowable device in the first pass through the gastrointestinal

tract, and wherein imaging the second set of images is performed by the second autonomous swallowable device in the second pass through the gastrointestinal tract.

9. The method according to claim 1, wherein imaging the first set of images in the first pass through the gastrointestinal tract and imaging the second set of images in the second pass through the gastrointestinal tract are both performed by the first autonomous swallowable device.

10. A method for image analysis of a gastrointestinal tract using at least one autonomous device comprising a camera system, a transmitter and an analyzing unit, said method comprising:

generating a first set of images in a first pass of a first autonomous imaging device through the gastrointestinal tract and a second set of images in a second pass of a second imaging device through the gastrointestinal tract, the second imaging device further having a storage compartment for retaining a substance therein;

transmitting the first set of images in the first pass in the gastrointestinal tract;

transmitting the second set of images in the second pass in the gastrointestinal tract;

analyzing the first set of images and bringing into conformity visual parameters of the set of images obtained in the first pass and visual parameters of the set of images obtained in the second pass, thereby recognizing in the second pass a location of interest in the gastrointestinal tract which has been identified in the first pass; and releasing the substance from said storage compartment of the second imaging device at said location of interest during the second pass in the gastrointestinal tract.

11. The method according to claim 10, wherein said first or second autonomous device further comprises a sensor element selected from a group consisting of a temperature sensor, a pH sensor, a pressure sensor, and a sensor for sensing pathology.

12. The method according to claim 10, wherein the substance retained within said storage compartment is a medicament.

13. The method according to claim 10, further comprising transmitting said images to an antenna array, said antenna array being outside a patient.

\* \* \* \* \*

专利名称(译)	用于将设备递送到目标位置的方法		
公开(公告)号	<a href="#">US7822463</a>	公开(公告)日	2010-10-26
申请号	US11/166141	申请日	2005-06-27
[标]申请(专利权)人(译)	MERON GAVRIEL IDDAN GAVRIEL J		
申请(专利权)人(译)	MERON GAVRIEL IDDAN GAVRIEL J		
当前申请(专利权)人(译)	基文影像有限公司.		
[标]发明人	MERON GAVRIEL IDDAN GAVRIEL J		
发明人	MERON, GAVRIEL IDDAN, GAVRIEL J.		
IPC分类号	A61B5/05 A61B1/04 G06K9/00 A61B1/00 A61B1/05 A61B5/00 A61B5/07		
CPC分类号	A61B1/00147 A61B1/041 A61B5/0031 A61B5/06 A61B5/073 A61B1/00016 Y10S128/922 A61B5/065		
优先权	PCT/IL1999/000554 1999-10-21 WO 126727 1998-10-22 IL		
其他公开文献	US20060004285A1		
外部链接	<a href="#">Espacenet</a> <a href="#">USPTO</a>		

#### 摘要(译)

一种自主设备，其可包括例如照相机，用于从照相机发射信号的发射器和用于将物质保持在设备中的储藏室。一种向患者输送药物的方法，包括用自主装置对胃肠道成像，识别这种管道中的目标位置，以及在目标位置从装置释放药物。

