

US010194848B1

(12) **United States Patent**
Kiani et al.

(10) **Patent No.:** **US 10,194,848 B1**
(45) **Date of Patent:** ***Feb. 5, 2019**

(54) **NON-INVASIVE PHYSIOLOGICAL SENSOR COVER**

A61B 5/145 (2006.01)
A61B 5/024 (2006.01)

(71) Applicant: **MASIMO CORPORATION**, Irvine, CA (US)

(52) **U.S. Cl.**
CPC *A61B 5/14552* (2013.01); *A61B 5/02416* (2013.01); *A61B 5/02427* (2013.01); *A61B 5/14532* (2013.01); *A61B 5/14546* (2013.01); *A61B 5/6816* (2013.01); *A61B 5/6819* (2013.01); *A61B 5/6826* (2013.01); *A61B 5/6829* (2013.01); *A61B 5/6832* (2013.01); *A61B 5/6838* (2013.01)

(72) Inventors: **Abraham Mazda Kiani**, San Juan Capistrano, CA (US); **Massi Joe E. Kiani**, Laguna Niguel, CA (US)

(73) Assignee: **MASIMO CORPORATION**, Irvine, CA (US)

(58) **Field of Classification Search**
CPC A61B 2562/185
See application file for complete search history.

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(56) **References Cited**

U.S. PATENT DOCUMENTS

- 4,960,128 A 10/1990 Gordon et al.
- 4,964,408 A 10/1990 Hink et al.
- 4,972,829 A 11/1990 Knerr
- 5,041,187 A 8/1991 Hink et al.

(Continued)

Primary Examiner — Clayton E. LaBalle

Assistant Examiner — Leon W Rhodes, Jr.

(74) *Attorney, Agent, or Firm* — Knobbe Martens Olson & Bear LLP

(21) Appl. No.: **16/149,532**

(22) Filed: **Oct. 2, 2018**

Related U.S. Application Data

(63) Continuation of application No. 15/968,393, filed on May 1, 2018, which is a continuation of application No. 15/046,954, filed on Feb. 18, 2016, now Pat. No. 9,980,667, which is a continuation of application No. 14/512,945, filed on Oct. 13, 2014, now Pat. No. 9,295,421, which is a continuation of application No. 13/919,692, filed on Jun. 17, 2013, now Pat. No. 8,886,271, which is a continuation of application No. 12/844,720, filed on Jul. 27, 2010, now Pat. No. 8,473,020.


(60) Provisional application No. 61/229,682, filed on Jul. 29, 2009.

(51) **Int. Cl.**
A61B 5/1455 (2006.01)
A61B 5/00 (2006.01)

(57) **ABSTRACT**

A sensor cover according to embodiments of the disclosure is capable of being used with a non-invasive physiological sensor, such as a pulse oximetry sensor. Certain embodiments of the sensor cover reduce or eliminate false readings from the sensor when the sensor is not in use, for example, by blocking a light detecting component of a pulse oximeter sensor when the pulse oximeter sensor is active but not in use. Further, embodiments of the sensor cover can prevent damage to the sensor. Additionally, embodiments of the sensor cover prevent contamination of the sensor.

29 Claims, 11 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

5,069,213 A	12/1991	Polczynski	6,236,872 B1	5/2001	Diab et al.
5,163,438 A	11/1992	Gordon et al.	6,241,683 B1	6/2001	Macklem et al.
5,319,355 A	6/1994	Russek	6,253,097 B1	6/2001	Aronow et al.
5,337,744 A	8/1994	Branigan	6,256,523 B1	7/2001	Diab et al.
5,341,805 A	8/1994	Stavridi et al.	6,263,222 B1	7/2001	Diab et al.
D353,195 S	12/1994	Savage et al.	6,278,522 B1	8/2001	Lepper, Jr. et al.
D353,196 S	12/1994	Savage et al.	6,280,213 B1	8/2001	Tobler et al.
5,377,676 A	1/1995	Vari et al.	6,285,896 B1	9/2001	Tobler et al.
D359,546 S	6/1995	Savage et al.	6,301,493 B1	10/2001	Marro et al.
5,431,170 A	7/1995	Mathews	6,308,089 B1	10/2001	von der Ruhr et al.
D361,840 S	8/1995	Savage et al.	6,317,627 B1	11/2001	Ennen et al.
D362,063 S	9/1995	Savage et al.	6,321,100 B1	11/2001	Parker
5,452,717 A	9/1995	Branigan et al.	6,325,761 B1	12/2001	Jay
D363,120 S	10/1995	Savage et al.	6,334,065 B1	12/2001	Al-Ali et al.
5,456,252 A	10/1995	Vari et al.	6,343,224 B1	1/2002	Parker
5,479,934 A	1/1996	Imran	6,349,228 B1	2/2002	Kiani et al.
5,482,036 A	1/1996	Diab et al.	6,360,114 B1	3/2002	Diab et al.
5,490,505 A	2/1996	Diab et al.	6,368,283 B1	4/2002	Xu et al.
5,494,043 A	2/1996	O'Sullivan et al.	6,371,921 B1	4/2002	Caro et al.
5,533,511 A	7/1996	Kaspari et al.	6,377,829 B1	4/2002	Al-Ali
5,534,851 A	7/1996	Russek	6,388,240 B2	5/2002	Schulz et al.
5,561,275 A	10/1996	Savage et al.	6,397,091 B2	5/2002	Diab et al.
5,562,002 A	10/1996	Lalin	6,430,437 B1	8/2002	Marro
5,590,649 A	1/1997	Caro et al.	6,430,525 B1	8/2002	Weber et al.
5,602,924 A	2/1997	Durand et al.	6,463,311 B1	10/2002	Diab
5,619,992 A	4/1997	Guthrie et al.	6,470,199 B1	10/2002	Kopotic et al.
5,632,272 A	5/1997	Diab et al.	6,501,975 B2	12/2002	Diab et al.
5,638,816 A	6/1997	Kiani-Azarbayjany et al.	6,505,059 B1	1/2003	Kollias et al.
5,638,818 A	6/1997	Diab et al.	6,515,273 B2	2/2003	Al-Ali
5,645,440 A	7/1997	Tobler et al.	6,519,487 B1	2/2003	Parker
5,685,299 A	11/1997	Diab et al.	6,525,386 B1	2/2003	Mills et al.
D393,830 S	4/1998	Tobler et al.	6,526,300 B1	2/2003	Kiani et al.
5,743,262 A	4/1998	Lepper, Jr. et al.	6,541,756 B2	4/2003	Schulz et al.
5,758,644 A	6/1998	Diab et al.	6,542,764 B1	4/2003	Al-Ali et al.
5,760,910 A	6/1998	Lepper, Jr. et al.	6,580,086 B1	6/2003	Schulz et al.
5,769,785 A	6/1998	Diab et al.	6,584,336 B1	6/2003	Ali et al.
5,782,757 A	7/1998	Diab et al.	6,595,316 B2	7/2003	Cybulski et al.
5,785,659 A	7/1998	Caro et al.	6,597,932 B2	7/2003	Tian et al.
5,791,347 A	8/1998	Flaherty et al.	6,597,933 B2	7/2003	Kiani et al.
5,810,734 A	9/1998	Caro et al.	6,606,511 B1	8/2003	Ali et al.
5,823,950 A	10/1998	Diab et al.	6,632,181 B2	10/2003	Flaherty et al.
5,830,131 A	11/1998	Caro et al.	6,639,668 B1	10/2003	Trepagnier
5,833,618 A	11/1998	Caro et al.	6,640,116 B2	10/2003	Diab
5,860,919 A	1/1999	Kiani-Azarbayjany et al.	6,643,530 B2	11/2003	Diab et al.
5,890,929 A	4/1999	Mills et al.	6,650,917 B2	11/2003	Diab et al.
5,904,654 A	5/1999	Wohltmann et al.	6,654,624 B2	11/2003	Diab et al.
5,919,134 A	7/1999	Diab	6,658,276 B2	12/2003	Kiani et al.
5,934,925 A	8/1999	Tobler et al.	6,661,161 B1	12/2003	Lanzo et al.
5,940,182 A	8/1999	Lepper, Jr. et al.	6,671,531 B2	12/2003	Al-Ali et al.
5,987,343 A	11/1999	Kinast	6,671,532 B1	12/2003	Fudge et al.
5,995,855 A	11/1999	Kiani et al.	6,678,543 B2	1/2004	Diab et al.
5,997,343 A	12/1999	Mills et al.	6,684,090 B2	1/2004	Ali et al.
6,002,952 A	12/1999	Diab et al.	6,684,091 B2	1/2004	Parker
6,011,986 A	1/2000	Diab et al.	6,697,656 B1	2/2004	Al-Ali
6,027,452 A	2/2000	Flaherty et al.	6,697,657 B1	2/2004	Shehada et al.
6,036,642 A	3/2000	Diab et al.	6,697,658 B2	2/2004	Al-Ali
6,045,509 A	4/2000	Caro et al.	RE38,476 E	3/2004	Diab et al.
6,067,462 A	5/2000	Diab et al.	6,699,194 B1	3/2004	Diab et al.
6,081,735 A	6/2000	Diab et al.	6,714,804 B2	3/2004	Al-Ali et al.
6,088,607 A	7/2000	Diab et al.	RE38,492 E	4/2004	Diab et al.
6,110,522 A	8/2000	Lepper, Jr. et al.	6,721,582 B2	4/2004	Trepagnier et al.
6,124,597 A	9/2000	Shehada	6,721,585 B1	4/2004	Parker
6,128,521 A	10/2000	Marro et al.	6,725,075 B2	4/2004	Al-Ali
6,129,675 A	10/2000	Jay	6,728,560 B2	4/2004	Kollias et al.
6,140,549 A	10/2000	Pompei, Jr.	6,735,459 B2	5/2004	Parker
6,144,868 A	11/2000	Parker	6,745,060 B2	6/2004	Diab et al.
6,151,516 A	11/2000	Kiani-Azarbayjany et al.	6,748,254 B2	6/2004	O'Neil et al.
6,152,754 A	11/2000	Gerhardt et al.	6,760,607 B2	7/2004	Al-Ali
6,157,850 A	12/2000	Diab et al.	6,770,028 B1	8/2004	Ali et al.
6,165,005 A	12/2000	Mills et al.	6,771,994 B2	8/2004	Kiani et al.
6,179,159 B1	1/2001	Gurley	6,792,300 B1	9/2004	Diab et al.
6,184,521 B1	2/2001	Coffin, IV et al.	6,813,511 B2	11/2004	Diab et al.
6,206,830 B1	3/2001	Diab et al.	6,816,741 B2	11/2004	Diab
6,229,856 B1	5/2001	Diab et al.	6,822,564 B2	11/2004	Al-Ali
6,232,609 B1	5/2001	Snyder et al.	6,826,419 B2	11/2004	Diab et al.
			6,830,711 B2	12/2004	Mills et al.
			6,850,787 B2	2/2005	Weber et al.
			6,850,788 B2	2/2005	Al-Ali
			6,852,083 B2	2/2005	Caro et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,861,639 B2	3/2005	Al-Ali	7,440,787 B2	10/2008	Diab
6,882,873 B2	4/2005	Samuels et al.	7,454,240 B2	11/2008	Diab et al.
6,898,452 B2	5/2005	Al-Ali et al.	7,467,002 B2	12/2008	Weber et al.
6,920,345 B2	7/2005	Al-Ali et al.	7,469,157 B2	12/2008	Diab et al.
6,931,268 B1	8/2005	Kiani-Azarbayjany et al.	7,471,969 B2	12/2008	Diab et al.
6,934,570 B2	8/2005	Kiani et al.	7,471,971 B2	12/2008	Diab et al.
6,939,305 B2	9/2005	Flaherty et al.	7,483,729 B2	1/2009	Al-Ali et al.
6,943,348 B1	9/2005	Coffin, IV	7,483,730 B2	1/2009	Diab et al.
6,950,687 B2	9/2005	Al-Ali	7,486,977 B2	2/2009	Sweitzer et al.
6,961,598 B2	11/2005	Diab	7,489,958 B2	2/2009	Diab et al.
6,970,792 B1	11/2005	Diab	7,496,391 B2	2/2009	Diab et al.
6,979,812 B2	12/2005	Al-Ali	7,496,393 B2	2/2009	Diab et al.
6,985,764 B2	1/2006	Mason et al.	D587,657 S	3/2009	Al-Ali et al.
6,993,371 B2	1/2006	Kiani et al.	7,499,741 B2	3/2009	Diab et al.
6,996,427 B2	2/2006	Ali et al.	7,499,835 B2	3/2009	Weber et al.
6,999,904 B2	2/2006	Weber et al.	7,500,950 B2	3/2009	Al-Ali et al.
7,003,338 B2	2/2006	Weber et al.	7,509,154 B2	3/2009	Diab et al.
7,003,339 B2	2/2006	Diab et al.	7,509,494 B2	3/2009	Al-Ali
7,015,451 B2	3/2006	Dalke et al.	7,510,849 B2	3/2009	Schurman et al.
7,024,233 B2	4/2006	Ali et al.	7,526,328 B2	4/2009	Diab et al.
7,024,235 B2 *	4/2006	Melker A61B 5/0873 600/340	7,530,942 B1	5/2009	Diab
7,027,849 B2	4/2006	Al-Ali	7,530,949 B2	5/2009	Al Ali et al.
7,030,749 B2	4/2006	Al-Ali	7,530,955 B2	5/2009	Diab et al.
7,039,449 B2	5/2006	Al-Ali	7,563,110 B2	7/2009	Al-Ali et al.
7,041,060 B2	5/2006	Flaherty et al.	7,574,245 B2	8/2009	Arizaga Ballesteros
7,044,918 B2	5/2006	Diab	7,596,398 B2	9/2009	Al-Ali et al.
7,048,687 B1	5/2006	Reuss et al.	7,618,375 B2	11/2009	Flaherty
7,067,893 B2	6/2006	Mills et al.	D606,659 S	12/2009	Kiani et al.
7,096,052 B2	8/2006	Mason et al.	7,647,083 B2	1/2010	Al-Ali et al.
7,096,054 B2	8/2006	Abdul-Hafiz et al.	D609,193 S	2/2010	Al-Ali et al.
7,132,641 B2	11/2006	Schulz et al.	D614,305 S	4/2010	Al-Ali et al.
7,142,901 B2	11/2006	Kiani et al.	RE41,317 E	5/2010	Parker
7,149,561 B2	12/2006	Diab	7,729,733 B2	6/2010	Al-Ali et al.
7,186,966 B2	3/2007	Al-Ali	7,734,320 B2	6/2010	Al-Ali
7,190,261 B2	3/2007	Al-Ali	7,761,127 B2	7/2010	Al-Ali et al.
7,190,987 B2	3/2007	Lindekugel et al.	7,761,128 B2	7/2010	Al-Ali et al.
7,215,984 B2	5/2007	Diab	7,764,982 B2	7/2010	Dalke et al.
7,215,986 B2	5/2007	Diab	D621,516 S	8/2010	Kiani et al.
7,221,971 B2	5/2007	Diab	7,791,155 B2	9/2010	Diab
7,225,006 B2	5/2007	Al-Ali et al.	7,801,581 B2	9/2010	Diab
7,225,007 B2	5/2007	Al-Ali	7,822,452 B2	10/2010	Schurman et al.
RE39,672 E	6/2007	Shehada et al.	RE41,912 E	11/2010	Parker
7,239,905 B2	7/2007	Kiani-Azarbayjany et al.	7,844,313 B2	11/2010	Kiani et al.
7,245,953 B1	7/2007	Parker	7,844,314 B2	11/2010	Al-Ali
7,254,429 B2	8/2007	Schurman et al.	7,844,315 B2	11/2010	Al-Ali
7,254,431 B2	8/2007	Al-Ali	7,865,222 B2	1/2011	Weber et al.
7,254,433 B2	8/2007	Diab et al.	7,873,497 B2	1/2011	Weber et al.
7,254,434 B2	8/2007	Schulz et al.	7,880,606 B2	2/2011	Al-Ali
7,272,425 B2	9/2007	Al-Ali	7,880,626 B2	2/2011	Al-Ali et al.
7,274,955 B2	9/2007	Kiani et al.	7,891,355 B2	2/2011	Al-Ali et al.
D554,263 S	10/2007	Al-Ali	7,894,868 B2	2/2011	Al-Ali et al.
7,280,858 B2	10/2007	Al-Ali et al.	7,899,507 B2	3/2011	Al-Ali et al.
7,289,835 B2	10/2007	Mansfield et al.	7,899,518 B2	3/2011	Trepagnier et al.
7,292,883 B2	11/2007	De Felice et al.	7,904,132 B2	3/2011	Weber et al.
7,295,866 B2	11/2007	Al-Ali	7,909,772 B2	3/2011	Popov et al.
7,328,053 B1	2/2008	Diab et al.	7,910,875 B2	3/2011	Al-Ali
7,332,784 B2	2/2008	Mills et al.	7,919,713 B2	4/2011	Al-Ali et al.
7,340,287 B2	3/2008	Mason et al.	7,937,128 B2	5/2011	Al-Ali
7,341,559 B2	3/2008	Schulz et al.	7,937,129 B2	5/2011	Mason et al.
7,343,186 B2	3/2008	Lamego et al.	7,937,130 B2	5/2011	Diab et al.
D566,282 S	4/2008	Al-Ali et al.	7,941,199 B2	5/2011	Kiani
7,355,512 B1	4/2008	Al-Ali	7,951,086 B2	5/2011	Flaherty et al.
7,356,365 B2	4/2008	Schurman	7,957,780 B2	6/2011	Lamego et al.
7,371,981 B2	5/2008	Abdul-Hafiz	7,962,188 B2	6/2011	Kiani et al.
7,373,193 B2	5/2008	Al-Ali et al.	7,962,190 B1	6/2011	Diab et al.
7,373,194 B2	5/2008	Weber et al.	7,976,472 B2	7/2011	Kiani
7,376,453 B1	5/2008	Diab et al.	7,988,637 B2	8/2011	Diab
7,377,794 B2	5/2008	Al Ali et al.	7,990,382 B2	8/2011	Kiani
7,377,899 B2	5/2008	Weber et al.	7,991,446 B2	8/2011	Al-Ali et al.
7,383,070 B2	6/2008	Diab et al.	8,000,761 B2	8/2011	Al-Ali
7,386,334 B2	6/2008	DeLonzor et al.	8,008,088 B2	8/2011	Bellott et al.
7,415,297 B2	8/2008	Al-Ali et al.	RE42,753 E	9/2011	Kiani-Azarbayjany et al.
7,428,432 B2	9/2008	Ali et al.	8,019,400 B2	9/2011	Diab et al.
7,438,683 B2	10/2008	Al-Ali et al.	8,028,701 B2	10/2011	Al-Ali et al.
			8,029,765 B2	10/2011	Bellott et al.
			8,036,727 B2	10/2011	Schurman et al.
			8,036,728 B2	10/2011	Diab et al.
			8,046,040 B2	10/2011	Ali et al.
			8,046,041 B2	10/2011	Diab et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

8,046,042	B2	10/2011	Diab et al.	D692,145	S	10/2013	Al-Ali et al.
8,048,040	B2	11/2011	Kiani	8,547,209	B2	10/2013	Kiani et al.
8,050,728	B2	11/2011	Al-Ali et al.	8,548,548	B2	10/2013	Al-Ali
RE43,169	E	2/2012	Parker	8,548,549	B2	10/2013	Schurman et al.
8,118,620	B2	2/2012	Al-Ali et al.	8,548,550	B2	10/2013	Al-Ali et al.
8,126,528	B2	2/2012	Diab et al.	8,560,032	B2	10/2013	Al-Ali et al.
8,128,572	B2	3/2012	Diab et al.	8,560,034	B1	10/2013	Diab et al.
8,130,105	B2	3/2012	Al-Ali et al.	8,570,167	B2	10/2013	Al-Ali
8,145,287	B2	3/2012	Diab et al.	8,570,503	B2	10/2013	Vo et al.
8,150,487	B2	4/2012	Diab et al.	8,571,617	B2	10/2013	Reichgott et al.
8,175,672	B2	5/2012	Parker	8,571,618	B1	10/2013	Lamego et al.
8,180,420	B2	5/2012	Diab et al.	8,571,619	B2	10/2013	Al-Ali et al.
8,182,443	B1	5/2012	Kiani	8,577,431	B2	11/2013	Lamego et al.
8,185,180	B2	5/2012	Diab et al.	8,581,732	B2	11/2013	Al-Ali et al.
8,188,433	B2	5/2012	Gonopolskiy et al.	8,584,345	B2	11/2013	Al-Ali et al.
8,190,223	B2	5/2012	Al-Ali et al.	8,588,880	B2	11/2013	Abdul-Hafiz et al.
8,190,227	B2	5/2012	Diab et al.	8,600,467	B2	12/2013	Al-Ali et al.
8,203,438	B2	6/2012	Kiani et al.	8,606,342	B2	12/2013	Diab
8,203,704	B2	6/2012	Merritt et al.	8,626,255	B2	1/2014	Al-Ali et al.
8,204,566	B2	6/2012	Schurman et al.	8,630,691	B2	1/2014	Lamego et al.
8,219,172	B2	7/2012	Schurman et al.	8,634,889	B2	1/2014	Al-Ali et al.
8,224,411	B2	7/2012	Al-Ali et al.	8,641,631	B2	2/2014	Sierra et al.
8,228,181	B2	7/2012	Al-Ali	8,652,060	B2	2/2014	Al-Ali
8,229,533	B2	7/2012	Diab et al.	8,663,107	B2	3/2014	Kiani
8,233,955	B2	7/2012	Al-Ali et al.	8,666,468	B1	3/2014	Al-Ali
8,244,325	B2	8/2012	Al-Ali et al.	8,667,967	B2	3/2014	Al-Ali et al.
8,255,026	B1	8/2012	Al-Ali	8,670,811	B2	3/2014	O'Reilly
8,255,027	B2	8/2012	Al-Ali et al.	8,670,814	B2	3/2014	Diab et al.
8,255,028	B2	8/2012	Al-Ali et al.	8,676,286	B2	3/2014	Weber et al.
8,260,577	B2	9/2012	Weber et al.	8,682,407	B2	3/2014	Al-Ali
8,265,723	B1	9/2012	McHale et al.	RE44,823	E	4/2014	Parker
8,274,360	B2	9/2012	Sampath et al.	RE44,875	E	4/2014	Kiani et al.
8,280,473	B2	10/2012	Al-Ali	8,690,799	B2	4/2014	Telfort et al.
8,301,217	B2	10/2012	Al-Ali et al.	8,700,112	B2	4/2014	Kiani
8,306,596	B2	11/2012	Schurman et al.	8,702,627	B2	4/2014	Telfort et al.
8,310,336	B2	11/2012	Muhsin et al.	8,706,179	B2	4/2014	Parker
8,315,683	B2	11/2012	Al-Ali et al.	8,712,494	B1	4/2014	MacNeish, III et al.
RE43,860	E	12/2012	Parker	8,715,206	B2	5/2014	Telfort et al.
8,337,403	B2	12/2012	Al-Ali et al.	8,718,735	B2	5/2014	Lamego et al.
8,346,330	B2	1/2013	Lamego	8,718,737	B2	5/2014	Diab et al.
8,353,842	B2	1/2013	Al-Ali et al.	8,718,738	B2	5/2014	Blank et al.
8,355,766	B2	1/2013	Macneish, III et al.	8,720,249	B2	5/2014	Al-Ali
8,359,080	B2	1/2013	Diab et al.	8,721,541	B2	5/2014	Al-Ali et al.
8,364,223	B2	1/2013	Al-Ali et al.	8,721,542	B2	5/2014	Al-Ali et al.
8,364,226	B2	1/2013	Diab et al.	8,723,677	B1	5/2014	Kiani
8,374,665	B2	2/2013	Lamego	8,740,792	B1	6/2014	Kiani et al.
8,385,995	B2	2/2013	Al-Ali et al.	8,754,776	B2	6/2014	Poeze et al.
8,385,996	B2	2/2013	Smith et al.	8,755,535	B2	6/2014	Telfort et al.
8,388,353	B2	3/2013	Kiani et al.	8,755,856	B2	6/2014	Diab et al.
8,399,822	B2	3/2013	Al-Ali	8,755,872	B1	6/2014	Marinow
8,401,602	B2	3/2013	Kiani	8,761,850	B2	6/2014	Lamego
8,405,608	B2	3/2013	Al-Ali et al.	8,764,671	B2	7/2014	Kiani
8,414,499	B2	4/2013	Al-Ali et al.	8,768,423	B2	7/2014	Shakespeare et al.
8,418,524	B2	4/2013	Al-Ali	8,771,204	B2	7/2014	Telfort et al.
8,423,106	B2	4/2013	Lamego et al.	8,777,634	B2	7/2014	Kiani et al.
8,428,967	B2	4/2013	Olsen et al.	8,781,543	B2	7/2014	Diab et al.
8,430,817	B1	4/2013	Al-Ali et al.	8,781,544	B2	7/2014	Al-Ali et al.
8,437,825	B2	5/2013	Dalvi et al.	8,781,549	B2	7/2014	Al-Ali et al.
8,455,290	B2	6/2013	Siskavich	8,788,003	B2	7/2014	Schurman et al.
8,457,703	B2	6/2013	Al-Ali	8,790,268	B2	7/2014	Al-Ali
8,457,707	B2	6/2013	Kiani	8,801,613	B2	8/2014	Al-Ali et al.
8,463,349	B2	6/2013	Diab et al.	8,821,397	B2	9/2014	Al-Ali et al.
8,466,286	B2	6/2013	Bellot et al.	8,821,415	B2	9/2014	Al-Ali et al.
8,471,713	B2	6/2013	Poeze et al.	8,830,449	B1	9/2014	Lamego et al.
8,473,020	B2	6/2013	Kiani et al.	8,831,700	B2	9/2014	Schurman et al.
8,483,787	B2	7/2013	Al-Ali et al.	8,840,549	B2	9/2014	Al-Ali et al.
8,489,364	B2	7/2013	Weber et al.	8,847,740	B2	9/2014	Kiani et al.
8,498,684	B2	7/2013	Weber et al.	8,849,365	B2	9/2014	Smith et al.
8,504,128	B2	8/2013	Blank et al.	8,852,094	B2	10/2014	Al-Ali et al.
8,509,867	B2	8/2013	Workman et al.	8,852,994	B2	10/2014	Wojtczuk et al.
8,515,509	B2	8/2013	Bruinsma et al.	8,868,147	B2	10/2014	Stippick et al.
8,523,781	B2	9/2013	Al-Ali	8,868,150	B2	10/2014	Al-Ali et al.
8,529,301	B2	9/2013	Al-Ali et al.	8,870,792	B2	10/2014	Al-Ali et al.
8,532,727	B2	9/2013	Ali et al.	8,886,271	B2	11/2014	Kiani et al.
8,532,728	B2	9/2013	Diab et al.	8,888,539	B2	11/2014	Al-Ali et al.
				8,888,708	B2	11/2014	Diab et al.
				8,892,180	B2	11/2014	Weber et al.
				8,897,847	B2	11/2014	Al-Ali
				8,909,310	B2	12/2014	Lamego et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

8,911,377	B2	12/2014	Al-Ali	9,386,961	B2	7/2016	Al-Ali et al.
8,912,909	B2	12/2014	Al-Ali et al.	9,392,945	B2	7/2016	Al-Ali et al.
8,920,317	B2	12/2014	Al-Ali et al.	9,397,448	B2	7/2016	Al-Ali et al.
8,921,699	B2	12/2014	Al-Ali et al.	9,408,542	B1	8/2016	Kinast et al.
8,922,382	B2	12/2014	Al-Ali et al.	9,436,645	B2	9/2016	Al-Ali et al.
8,929,964	B2	1/2015	Al-Ali et al.	9,445,759	B1	9/2016	Lamego et al.
8,942,777	B2	1/2015	Diab et al.	9,466,919	B2	10/2016	Kiani et al.
8,948,834	B2	2/2015	Diab et al.	9,474,474	B2	10/2016	Lamego et al.
8,948,835	B2	2/2015	Diab	9,480,422	B2	11/2016	Al-Ali
8,965,471	B2	2/2015	Lamego	9,480,435	B2	11/2016	Olsen
8,983,564	B2	3/2015	Al-Ali	9,492,110	B2	11/2016	Al-Ali et al.
8,989,831	B2	3/2015	Al-Ali et al.	9,510,779	B2	12/2016	Poeze et al.
8,996,085	B2	3/2015	Kiani et al.	9,517,024	B2	12/2016	Kiani et al.
8,998,809	B2	4/2015	Kiani	9,532,722	B2	1/2017	Lamego et al.
9,028,429	B2	5/2015	Telfort et al.	9,538,949	B2	1/2017	Al-Ali et al.
9,037,207	B2	5/2015	Al-Ali et al.	9,538,980	B2	1/2017	Telfort et al.
9,060,721	B2	6/2015	Reichgott et al.	9,549,696	B2	1/2017	Lamego et al.
9,066,666	B2	6/2015	Kiani	9,554,737	B2	1/2017	Schurman et al.
9,066,680	B1	6/2015	Al-Ali et al.	9,560,996	B2	2/2017	Kiani
9,072,474	B2	7/2015	Al-Ali et al.	9,560,998	B2	2/2017	Al-Ali et al.
9,078,560	B2	7/2015	Schurman et al.	9,566,019	B2	2/2017	Al-Ali et al.
9,084,569	B2	7/2015	Weber et al.	9,579,039	B2	2/2017	Jansen et al.
9,095,316	B2	8/2015	Welch et al.	9,591,975	B2	3/2017	Dalvi et al.
9,106,038	B2	8/2015	Telfort et al.	9,622,692	B2	4/2017	Lamego et al.
9,107,625	B2	8/2015	Telfort et al.	9,622,693	B2	4/2017	Diab
9,107,626	B2	8/2015	Al-Ali et al.	D788,312	S	5/2017	Al-Ali et al.
9,113,831	B2	8/2015	Al-Ali	9,636,055	B2	5/2017	Al-Ali et al.
9,113,832	B2	8/2015	Al-Ali	9,636,056	B2	5/2017	Al-Ali
9,119,595	B2	9/2015	Lamego	9,649,054	B2	5/2017	Lamego et al.
9,131,881	B2	9/2015	Diab et al.	9,662,052	B2	5/2017	Al-Ali et al.
9,131,882	B2	9/2015	Al-Ali et al.	9,668,679	B2	6/2017	Schurman et al.
9,131,883	B2	9/2015	Al-Ali	9,668,680	B2	6/2017	Bruinsma et al.
9,131,917	B2	9/2015	Telfort et al.	9,668,703	B2	6/2017	Al-Ali
9,138,180	B1	9/2015	Coverston et al.	9,675,286	B2	6/2017	Diab
9,138,182	B2	9/2015	Al-Ali et al.	9,687,160	B2	6/2017	Kiani
9,138,192	B2	9/2015	Weber et al.	9,693,719	B2	7/2017	Al-Ali et al.
9,142,117	B2	9/2015	Muhsin et al.	9,693,737	B2	7/2017	Al-Ali
9,153,112	B1	10/2015	Kiani et al.	9,697,928	B2	7/2017	Al-Ali et al.
9,153,121	B2	10/2015	Kiani et al.	9,717,425	B2	8/2017	Kiani et al.
9,161,696	B2	10/2015	Al-Ali et al.	9,717,458	B2	8/2017	Lamego et al.
9,161,713	B2	10/2015	Al-Ali et al.	9,724,016	B1	8/2017	Al-Ali et al.
9,167,995	B2	10/2015	Lamego et al.	9,724,024	B2	8/2017	Al-Ali
9,176,141	B2	11/2015	Al-Ali et al.	9,724,025	B1	8/2017	Kiani et al.
9,186,102	B2	11/2015	Bruinsma et al.	9,730,640	B2	8/2017	Diab et al.
9,192,312	B2	11/2015	Al-Ali	9,743,887	B2	8/2017	Al-Ali et al.
9,192,329	B2	11/2015	Al-Ali	9,749,232	B2	8/2017	Sampath et al.
9,192,351	B1	11/2015	Telfort et al.	9,750,442	B2	9/2017	Olsen
9,195,385	B2	11/2015	Al-Ali et al.	9,750,443	B2	9/2017	Smith et al.
9,211,072	B2	12/2015	Kiani	9,750,461	B1	9/2017	Telfort
9,211,095	B1	12/2015	Al-Ali	9,775,545	B2	10/2017	Al-Ali et al.
9,218,454	B2	12/2015	Kiani et al.	9,775,546	B2	10/2017	Diab et al.
9,226,696	B2	1/2016	Kiani	9,775,570	B2	10/2017	Al-Ali
9,241,662	B2	1/2016	Al-Ali et al.	9,778,079	B1	10/2017	Al-Ali et al.
9,245,668	B1	1/2016	Vo et al.	9,782,077	B2	10/2017	Lamego et al.
9,259,185	B2	2/2016	Abdul-Hafiz et al.	9,782,110	B2	10/2017	Kiani
9,267,572	B2	2/2016	Barker et al.	9,787,568	B2	10/2017	Lamego et al.
9,277,880	B2	3/2016	Poeze et al.	9,788,735	B2	10/2017	Al-Ali
9,289,167	B2	3/2016	Diab et al.	9,788,768	B2	10/2017	Al-Ali et al.
9,295,421	B2	3/2016	Kiani et al.	9,795,300	B2	10/2017	Al-Ali
9,307,928	B1	4/2016	Al-Ali et al.	9,795,310	B2	10/2017	Al-Ali
9,323,894	B2	4/2016	Kiani	9,795,358	B2	10/2017	Telfort et al.
D755,392	S	5/2016	Hwang et al.	9,795,739	B2	10/2017	Al-Ali et al.
9,326,712	B1	5/2016	Kiani	9,801,556	B2	10/2017	Kiani
9,333,316	B2	5/2016	Kiani	9,801,588	B2	10/2017	Weber et al.
9,339,220	B2	5/2016	Lamego et al.	9,808,188	B1	11/2017	Perea et al.
9,341,565	B2	5/2016	Lamego et al.	9,814,418	B2	11/2017	Weber et al.
9,351,673	B2	5/2016	Diab et al.	9,820,691	B2	11/2017	Kiani
9,351,675	B2	5/2016	Al-Ali et al.	9,833,152	B2	12/2017	Kiani et al.
9,364,181	B2	6/2016	Kiani et al.	9,833,180	B2	12/2017	Shakespeare et al.
9,368,671	B2	6/2016	Wojtczuk et al.	9,839,379	B2	12/2017	Al-Ali et al.
9,370,325	B2	6/2016	Al-Ali et al.	9,839,381	B1	12/2017	Weber et al.
9,370,326	B2	6/2016	McHale et al.	9,847,002	B2	12/2017	Kiani et al.
9,370,335	B2	6/2016	Al-Ali et al.	9,847,749	B2	12/2017	Kiani et al.
9,375,185	B2	6/2016	Ali et al.	9,848,800	B1	12/2017	Lee et al.
9,386,953	B2	7/2016	Al-Ali	9,848,806	B2	12/2017	Al-Ali et al.
				9,848,807	B2	12/2017	Lamego
				9,861,298	B2	1/2018	Eckerbom et al.
				9,861,304	B2	1/2018	Al-Ali et al.
				9,861,305	B1	1/2018	Weber et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

9,867,578 B2	1/2018	Al-Ali et al.	2014/0316228 A1	10/2014	Blank et al.
9,872,623 B2	1/2018	Al-Ali	2014/0323825 A1	10/2014	Al-Ali et al.
9,876,320 B2	1/2018	Coverston et al.	2014/0323897 A1	10/2014	Brown et al.
9,877,650 B2	1/2018	Muhsin et al.	2014/0323898 A1	10/2014	Purdon et al.
9,877,686 B2	1/2018	Al-Ali et al.	2014/0330092 A1	11/2014	Al-Ali et al.
9,891,079 B2	2/2018	Dalvi	2014/0330098 A1	11/2014	Merritt et al.
9,895,107 B2	2/2018	Al-Ali et al.	2014/0357966 A1	12/2014	Al-Ali et al.
9,913,617 B2	3/2018	Al-Ali et al.	2015/0005600 A1	1/2015	Blank et al.
9,924,893 B2	3/2018	Schurman et al.	2015/0011907 A1	1/2015	Purdon et al.
9,924,897 B1	3/2018	Abdul-Hafiz	2015/0032029 A1	1/2015	Al-Ali et al.
9,936,917 B2	4/2018	Poeze et al.	2015/0038859 A1	2/2015	Dalvi et al.
9,943,269 B2	4/2018	Muhsin et al.	2015/0080754 A1	3/2015	Purdon et al.
9,949,676 B2	4/2018	Al-Ali	2015/0087936 A1	3/2015	Al-Ali et al.
9,955,937 B2	5/2018	Telfort	2015/0094546 A1	4/2015	Al-Ali
9,965,946 B2	5/2018	Al-Ali	2015/0099950 A1	4/2015	Al-Ali et al.
9,980,667 B2	5/2018	Kiani et al.	2015/0101844 A1	4/2015	Al-Ali et al.
D820,865 S	6/2018	Muhsin et al.	2015/0106121 A1	4/2015	Muhsin et al.
9,986,919 B2	6/2018	Lamego et al.	2015/0112151 A1	4/2015	Muhsin et al.
9,986,952 B2	6/2018	Dalvi et al.	2015/0165312 A1	6/2015	Kiani
9,989,560 B2	6/2018	Poeze et al.	2015/0196249 A1	7/2015	Brown et al.
9,993,207 B2	6/2018	Al-Ali et al.	2015/0216459 A1	8/2015	Al-Ali et al.
10,007,758 B2	6/2018	Al-Ali et al.	2015/0238722 A1	8/2015	Al-Ali
D822,215 S	7/2018	Al-Ali et al.	2015/0245773 A1	9/2015	Lamego et al.
D822,216 S	7/2018	Barker et al.	2015/0245794 A1	9/2015	Al-Ali
10,010,276 B2	7/2018	Al-Ali et al.	2015/0257689 A1	9/2015	Al-Ali et al.
10,032,002 B2	7/2018	Kiani et al.	2015/0272514 A1	10/2015	Kiani et al.
10,039,482 B2	8/2018	Al-Ali et al.	2015/0351697 A1	12/2015	Weber et al.
10,052,037 B2	8/2018	Kinast et al.	2015/0359429 A1	12/2015	Al-Ali et al.
10,058,275 B2	8/2018	Al-Ali et al.	2015/0366507 A1	12/2015	Blank
10,064,562 B2	9/2018	Al-Ali	2016/0029932 A1	2/2016	Al-Ali
2006/0161054 A1	7/2006	Reuss et al.	2016/0058347 A1	3/2016	Reichgott et al.
2007/0282478 A1	12/2007	Al-Ali et al.	2016/0066824 A1	3/2016	Al-Ali et al.
2009/0247984 A1	10/2009	Lamego et al.	2016/0081552 A1	3/2016	Wojtczuk et al.
2009/0275813 A1	11/2009	Davis	2016/0095543 A1	4/2016	Telfort et al.
2009/0275844 A1	11/2009	Al-Ali	2016/0095548 A1	4/2016	Al-Ali et al.
2010/0004518 A1	1/2010	Vo et al.	2016/0103598 A1	4/2016	Al-Ali et al.
2010/0030040 A1	2/2010	Poeze et al.	2016/0166182 A1	6/2016	Al-Ali et al.
2011/0082711 A1	4/2011	Poeze et al.	2016/0166183 A1	6/2016	Poeze et al.
2011/0125060 A1	5/2011	Telfort et al.	2016/0196388 A1	7/2016	Lamego
2011/0208015 A1	8/2011	Welch et al.	2016/0197436 A1	7/2016	Barker et al.
2011/0230733 A1	9/2011	Al-Ali	2016/0213281 A1	7/2016	Eckerbom et al.
2012/0165629 A1	6/2012	Merritt et al.	2016/0228043 A1	8/2016	O'Neil et al.
2012/0209082 A1	8/2012	Al-Ali	2016/0233632 A1	8/2016	Scruggs et al.
2012/0209084 A1	8/2012	Olsen et al.	2016/0234944 A1	8/2016	Schmidt et al.
2012/0283524 A1	11/2012	Kiani et al.	2016/0270735 A1	9/2016	Diab et al.
2013/0023775 A1	1/2013	Lamego et al.	2016/0283665 A1	9/2016	Sampath et al.
2013/0041591 A1	2/2013	Lamego	2016/0287090 A1	10/2016	Al-Ali et al.
2013/0060147 A1	3/2013	Welch et al.	2016/0287786 A1	10/2016	Kiani
2013/0096405 A1	4/2013	Garfio	2016/0296169 A1	10/2016	McHale et al.
2013/0096936 A1	4/2013	Sampath et al.	2016/0310052 A1	10/2016	Al-Ali et al.
2013/0243021 A1	9/2013	Siskavich	2016/0314260 A1	10/2016	Kiani
2013/0253334 A1	9/2013	Al-Ali et al.	2016/0324488 A1	11/2016	Olsen
2013/0296672 A1	11/2013	O'Neil et al.	2016/0327984 A1	11/2016	Al-Ali et al.
2013/0296713 A1	11/2013	Al-Ali et al.	2016/0331332 A1	11/2016	Al-Ali
2013/0324808 A1	12/2013	Al-Ali et al.	2016/0367173 A1	12/2016	Dalvi et al.
2013/0331660 A1	12/2013	Al-Ali et al.	2017/0000394 A1	1/2017	Al-Ali et al.
2014/0012100 A1	1/2014	Al-Ali et al.	2017/0007134 A1	1/2017	Al-Ali et al.
2014/0051953 A1	2/2014	Lamego et al.	2017/0007198 A1	1/2017	Al-Ali et al.
2014/0120564 A1	5/2014	Workman et al.	2017/0014083 A1	1/2017	Diab et al.
2014/0121482 A1	5/2014	Merritt et al.	2017/0014084 A1	1/2017	Al-Ali et al.
2014/0127137 A1	5/2014	Bellott et al.	2017/0042488 A1	2/2017	Muhsin
2014/0163344 A1	6/2014	Al-Ali	2017/0055851 A1	3/2017	Al-Ali
2014/0166076 A1	6/2014	Kiani et al.	2017/0055882 A1	3/2017	Al-Ali et al.
2014/0171763 A1	6/2014	Diab	2017/0055887 A1	3/2017	Al-Ali
2014/0180038 A1	6/2014	Kiani	2017/0055896 A1	3/2017	Al-Ali et al.
2014/0180154 A1	6/2014	Sierra et al.	2017/0079594 A1	3/2017	Telfort et al.
2014/0180160 A1	6/2014	Brown et al.	2017/0086723 A1	3/2017	Al-Ali et al.
2014/0187973 A1	7/2014	Brown et al.	2017/0143281 A1	5/2017	Olsen
2014/0213864 A1	7/2014	Abdul-Hafiz et al.	2017/0147774 A1	5/2017	Kiani
2014/0275835 A1	9/2014	Lamego et al.	2017/0156620 A1	6/2017	Al-Ali et al.
2014/0275871 A1	9/2014	Lamego et al.	2017/0173632 A1	6/2017	Al-Ali
2014/0275872 A1	9/2014	Merritt et al.	2017/0187146 A1	6/2017	Kiani et al.
2014/0288400 A1	9/2014	Diab et al.	2017/0188919 A1	7/2017	Al-Ali et al.
2014/0316217 A1	10/2014	Purdon et al.	2017/0196464 A1	7/2017	Jansen et al.
2014/0316218 A1	10/2014	Purdon et al.	2017/0196470 A1	7/2017	Lamego et al.
			2017/0224262 A1	8/2017	Al-Ali
			2017/0228516 A1	8/2017	Sampath et al.
			2017/0245790 A1	8/2017	Al-Ali et al.
			2017/0251974 A1	9/2017	Shreim et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2017/0251975	A1	9/2017	Shreim et al.	2018/0130325	A1	5/2018	Kiani et al.
2017/0258403	A1	9/2017	Abdul-Hafiz et al.	2018/0132769	A1	5/2018	Weber et al.
2017/0311851	A1	11/2017	Schurman et al.	2018/0132770	A1	5/2018	Lamego
2017/0311891	A1	11/2017	Kiani et al.	2018/0146901	A1	5/2018	Al-Ali et al.
2017/0325728	A1	11/2017	Al-Ali et al.	2018/0146902	A1	5/2018	Kiani et al.
2017/0332976	A1	11/2017	Al-Ali et al.	2018/0153442	A1	6/2018	Eckerbom et al.
2017/0340293	A1	11/2017	Al-Ali et al.	2018/0153446	A1	6/2018	Kiani
2017/0360310	A1	12/2017	Kiani et al.	2018/0153447	A1	6/2018	Al-Ali et al.
2017/0367632	A1	12/2017	Al-Ali et al.	2018/0153448	A1	6/2018	Weber et al.
2018/0008146	A1	1/2018	Al-Ali et al.	2018/0161499	A1	6/2018	Al-Ali et al.
2018/0014752	A1	1/2018	Al-Ali et al.	2018/0168491	A1	6/2018	Al-Ali et al.
2018/0028124	A1	2/2018	Al-Ali et al.	2018/0174679	A1	6/2018	Sampath et al.
2018/0055385	A1	3/2018	Al-Ali	2018/0174680	A1	6/2018	Sampath et al.
2018/0055390	A1	3/2018	Kiani et al.	2018/0182484	A1	6/2018	Sampath et al.
2018/0055430	A1	3/2018	Diab et al.	2018/0184917	A1	7/2018	Kiani
2018/0064381	A1	3/2018	Shakespeare et al.	2018/0192953	A1	7/2018	Shreim et al.
2018/0069776	A1	3/2018	Lamego et al.	2018/0192955	A1	7/2018	Al-Ali et al.
2018/0070867	A1	3/2018	Smith et al.	2018/0199871	A1	7/2018	Pauley et al.
2018/0082767	A1	3/2018	Al-Ali et al.	2018/0206795	A1	7/2018	Al-Ali
2018/0085068	A1	3/2018	Telfort	2018/0206815	A1	7/2018	Telfort
2018/0087937	A1	3/2018	Al-Ali et al.	2018/0213583	A1	7/2018	Al-Ali
2018/0103874	A1	4/2018	Lee et al.	2018/0214031	A1	8/2018	Kiani et al.
2018/0103905	A1	4/2018	Kiani	2018/0214090	A1	8/2018	Al-Ali et al.
2018/0110478	A1	4/2018	Al-Ali	2018/0218792	A1	8/2018	Muhsin et al.
2018/0116575	A1	5/2018	Perea et al.	2018/0225960	A1	8/2018	Al-Ali et al.
2018/0125368	A1	5/2018	Lamego et al.	2018/0238718	A1	8/2018	Dalvi
2018/0125430	A1	5/2018	Al-Ali et al.	2018/0242853	A1	8/2018	Al-Ali
2018/0125445	A1	5/2018	Telfort et al.	2018/0242921	A1	8/2018	Muhsin et al.
				2018/0242926	A1	8/2018	Muhsin et al.
				2018/0247353	A1	8/2018	Al-Ali et al.
				2018/0247712	A1	8/2018	Muhsin et al.

* cited by examiner




FIG. 1




FIG. 2B




FIG. 2A







FIG. 2C

FIG. 2D






FIG. 3D




FIG. 3E




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 5A




FIG. 5B




FIG. 6




FIG. 7




FIG. 8




FIG. 9B





FIG. 9A






FIG. 9D

NON-INVASIVE PHYSIOLOGICAL SENSOR COVER

CROSS-REFERENCE TO RELATED APPLICATIONS

The present application is a continuation of U.S. patent application Ser. No. 15/968,393, filed May 1, 2018, titled "NON-INVASIVE PHYSIOLOGICAL SENSOR COVER," which is a continuation of U.S. patent application Ser. No. 15/046,954, filed Feb. 18, 2016, titled "NON-INVASIVE PHYSIOLOGICAL SENSOR COVER," which is a continuation of U.S. patent application Ser. No. 14/512,945, filed Oct. 13, 2014, titled "NON-INVASIVE PHYSIOLOGICAL SENSOR COVER," which is a continuation of U.S. patent application Ser. No. 13/919,692, filed Jun. 17, 2013, titled "NON-INVASIVE PHYSIOLOGICAL SENSOR COVER," which is a continuation of U.S. patent application Ser. No. 12/844,720, filed Jul. 27, 2010, titled "NON-INVASIVE PHYSIOLOGICAL SENSOR COVER," which claims priority benefit under 35 U.S.C. § 119(e) from U.S. Provisional Application No. 61/229,682, filed Jul. 29, 2009, titled "Non-invasive Physiological Sensor Cover." All of the above referenced applications are hereby incorporated by reference herein in their entireties.

FIELD OF THE DISCLOSURE

The present invention relates to a sensor for measuring oxygen content in the blood, and, in particular, relates to an apparatus and method for preventing sensor activity when the sensor is not in use.

BACKGROUND OF THE DISCLOSURE

Non-invasive physiological sensors are applied to the body for monitoring or making measurements indicative of a patient's health. One application for a non-invasive physiological sensor is pulse oximetry, which provides a non-invasive procedure for measuring the oxygen status of circulating blood. Oximetry has gained rapid acceptance in a wide variety of medical applications, including surgical wards, intensive care and neonatal units, general wards, and home care and physical training. A pulse oximetry system generally includes a patient monitor, a communications medium such as a cable, and a physiological sensor having light emitters and a detector, such as one or more LEDs and a photodetector. The sensor is attached to a tissue site, such as a finger, toe, ear lobe, nose, hand, foot, or other site having pulsatile blood flow which can be penetrated by light from the emitters. The detector is responsive to the emitted light after attenuation by pulsatile blood flowing in the tissue site. The detector outputs a detector signal to the monitor over the communication medium, which processes the signal to provide a numerical readout of physiological parameters such as oxygen saturation (SpO₂) and pulse rate.

High fidelity pulse oximeters capable of reading through motion induced noise are disclosed in U.S. Pat. Nos. 6,770,028, 6,658,276, 6,157,850, 6,002,952, 5,769,785, and 5,758,644, which are assigned to Masimo Corporation ("Masimo") and are incorporated by reference herein. Advanced physiological monitoring systems may incorporate pulse oximetry in addition to advanced features for the calculation and display of other blood parameters, such as carboxyhemoglobin (HbCO), methemoglobin (HbMet) and total hemoglobin (Hbt), total Hematocrit (Hct), oxygen concentrations and glucose concentrations, as a few examples. Advanced

physiological monitors and corresponding multiple wavelength optical sensors capable of measuring parameters in addition to SpO₂, such as HbCO, HbMet and Hbt are described in at least U.S. patent application Ser. No. 11/367,013, filed Mar. 1, 2006, titled Multiple Wavelength Sensor Emitters and U.S. patent application Ser. No. 11/366,208, filed Mar. 1, 2006, titled Noninvasive Multi-Parameter Patient Monitor, assigned to Masimo Laboratories, Inc. and incorporated by reference herein. Further, noninvasive blood parameter monitors and optical sensors including Rainbow™ adhesive and reusable sensors and RAD-57™ and Radical-7™ monitors capable of measuring SpO₂, pulse rate, perfusion index (PI), signal quality (SiQ), pulse variability index (PVI), HbCO and HbMet, among other parameters, are also commercially available from Masimo.

SUMMARY OF THE DISCLOSURE

Optical sensors are widely used across clinical settings, such as operating rooms, emergency rooms, post anesthesia care units, critical care units, outpatient surgery and physiological labs, to name a few. In some situations, such as in operating rooms, emergency rooms or critical care units, sensors can be kept attached to monitors to reduce the setup time needed to begin monitoring a patient. While attached, the sensor can generate false readings by detecting ambient light even though the sensor is not in use. The sensor can also cause the monitor to emit alarms or otherwise make noise due to false readings, which can be distracting to medical personnel.

As such, a method and apparatus for preventing false readings are desirable. A sensor cover, according to embodiments of the disclosure, prevents or reduces false readings until the sensor is in use.

Further, in certain embodiments, the sensor cover can prevent damage to the sensor. For example, the sensors cover can protect the emitters and the detector during shipment or prior to use. In certain embodiments, a sensor cover decreases the likelihood of contamination by keeping covered portions of the sensor clean. Sensors in hospitals and other clinical environments are subject to exposure to infectious agents, dust or other foreign matter from depositing on the emitters or detector. The sensor cover can reduce or prevent exposure to these contaminants.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates a sensor cover attached to a sensor of a physiological measurement system according to an embodiment of the disclosure;

FIGS. 2A-2C are top cover-attached, top cover-detached, and bottom cover-attached perspective views, respectively, of the sensor cover and sensor of FIG. 1;

FIG. 2D illustrates a first and second sensor covers over the emitters and detector according to an embodiment of the disclosure;

FIG. 3A illustrates a non-protruding sensor cover according to an embodiment of the disclosure;

FIG. 3B illustrates a non-protruding sensor cover having an opaque border and a removable opaque center according to an embodiment of the disclosure;

FIG. 3C illustrates a sensor cover having a clear "window" according to an embodiment of the disclosure;

FIG. 3D illustrates a sensor cover integrated with an adhesive cover according to an embodiment of the disclosure;

FIG. 3E illustrates a sensor cover covering an adhesive sensor according to an embodiment of the disclosure;

FIGS. 4A-4B are a top view and a close up view, respectively, of an integrated sensor cover according to an embodiment of the disclosure;

FIG. 4C illustrates the sensor cover of FIGS. 4A-4B covering a sensor component;

FIG. 5A is a front view a sensor cover attachable to a reusable sensor according to an embodiment of the disclosure;

FIG. 5B illustrates the mating of the sensor cover of FIG. 5A with a sensor;

FIG. 6 illustrates a sensor cover attachable to a sensor via one or more tabs according to an embodiment of the disclosure;

FIG. 7 illustrates a sensor cover configured to block both the emitters and the detector according to an embodiment of the disclosure;

FIG. 8 illustrates a sensor cover attachable to a sensor via an attachment arm according to an embodiment of the disclosure; and

FIGS. 9A-9D illustrates embodiments of the sensor covers configured for attachment to a bioacoustic sensor, according to embodiments of the disclosure.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

A sensor cover according to embodiments of the disclosure is capable of being used with a non-invasive physiological sensor. Certain embodiments of the sensor cover reduce or eliminate false readings from the sensor when the sensor is not in use. Further, embodiments of the sensor cover can prevent damage to the sensor. Additionally, embodiments of the sensor cover prevent contamination of the sensor.

The tissue site of the illustrated embodiments is a finger and the following description therefore refers specifically to the tissue site as a finger for the purposes of clarity. This is not intended to be limiting and, as described herein, the sensor cover of certain embodiments can be used with sensors attachable to other types of tissue sites, such as a toe, ear lobe, nose, hand, foot, forehead or the like.

FIG. 1 illustrates an embodiment of a sensor cover attached to a physiological measurement system 100 having a monitor 110 and an optical sensor 120. The optical sensor 120 comprises one or more light emitters and a detector. The optical sensor 120 is configured to plug into a monitor sensor port 112 via a patient cable 130. Monitor keys 114 provide control over operating modes and alarms, to name a few. A display 116 provides readouts of measured parameters, such as oxygen saturation, pulse rate, HbCO, HbMet and Hbt to name a few. Other blood parameters that can be measured to provide important clinical information are fractional oxygen saturation, bilirubin and blood glucose, to name a few.

In the illustrated embodiment of FIG. 1, the sensor cover 140 protrudes outside the sensor. The cover can be made from an opaque material, such as, for example, plastic, polyester, polypropylene, rubber, vinyl, cling vinyl and/or the like. The sensor cover 140 can obstruct the detector and prevent the detector from detecting light, thereby reducing or eliminating false readings. For example, the sensor 120 can sometimes be left attached to a monitor 110 to facilitate quick monitoring of a patient, even when not currently in use. The opaque cover 140 can prevent or reduce false readings caused by the emitters or the ambient light, even if the sensor is active, by preventing the sensor from receiving

light. In an embodiment, the opaque material can block all wavelengths of light used by a particular sensor. Other embodiments can block different ranges of wavelengths depending on the type of sensor the cover is used for. In an embodiment, the sensor cover 140 is placed over the emitters to prevent the sensor from emitting light receivable by the detector. In an embodiment, both the detector and emitter are covered.

In some embodiments, the sensor cover 140 can be removed before placement at a measurement site. For example, once a patient arrives, medical personnel can remove the sensor cover 140 and attach the now fully operational sensor 120 to the patient. In some embodiments, the medical personnel can attach the sensor 120 with the cover 140 still in place. The opaque cover prevents measurements from being taken until the sensor 120 is generally secure and the medical personnel are ready to take measurements. For example, movement can generate artifacts for some sensors; therefore waiting until the patient is stable can reduce measurement of inaccurate data. Once the sensor 120 is generally secured to an attachment site, the cover 140 can be removed from the sensor. In some embodiments, the sensor cover 140 can be removed before and/or after placement at a measurement site. The sensor cover 140 can be removed by peeling it off from the sensor or by pulling on the protruding portion.

As will be appreciated by skilled artisans from the disclosure provided herein, various attachment mechanisms can be used. For example, the sensor cover can be attached with an adhesive. In certain embodiments, a restorable adhesive can be used to facilitate reattachments of the sensor cover. The restorable adhesive layer can be rejuvenated by application of alcohol to the adhesive. The cover can then be reattached to the sensor. This can be useful where the sensor is moved to a new location or tissue site because the cover can prevent the sensor from taking false readings while the sensor is moved. In some embodiments, no adhesive is used on the sensor cover to leave no residue. In some embodiments, the sensor cover can be made from static cling vinyl, plastic film, or other "clingy" material with no adhesive used. In some embodiments, the sensor cover can be attached through static electricity allowing the cover to cling to the sensor without any adhesive and/or allowing the sensor cover to be reapplied. In other configurations, the sensor cover can be attached with Velcro, fasteners, tabs, clips, slots, or the like.

As will also be appreciated by skilled artisans from the disclosure provided herein, the sensor cover can be detached in various ways. In some embodiments, the sensor cover can be peeled off from the sensor before the sensor is placed at a measurement site. In some embodiments, the sensor can be pulled off from the sensor after placement by pulling on a protruding portion. Depending on the attachment mechanism, the detachment of the sensor cover can expose an adhesive layer or can leave no adhesive residue on the sensor. In some embodiments, the sensor cover can be unclipped or unhooked.

In certain embodiments, the sensor covers are reusable. For example, the sensor cover can be reused if the sensor is temporarily removed for repositioning or for cleaning. The sensor cover can also be replaced on the sensor when the sensor is no longer in use. In some embodiments, the sensor covers are disposable and are disposed of once removed from the sensor.

Although disclosed with reference to the sensor of FIG. 1, an artisan will recognize from the disclosure herein a wide variety of oximeter sensors, optical sensors, noninvasive

sensors, medical sensors, or the like that may benefit from the sensor cover disclosed herein. In various embodiments, the sensor can be adapted to receive a tissue site other than a finger such as a, toe, ear lobe, nose, hand, foot, neck, or other site having pulsatile blood flow which can be penetrated by light from the emitter. In addition, the sensor cover **140** can be used with a portable monitor and associated sensor components in certain embodiments. Such monitors, including the sensor components, can be integrated into a hand-held device such as a PDA and typically do not include cables or separate monitors. Portable monitors are often used by first responders in emergency situations, in part because of their portability and ease of use. As such, sensor covers **140** which can protect the sensor components according to embodiments herein can be of particular benefit when used with spot-check monitors.

FIGS. **2A-2C** are top cover-attached, top cover-detached, and bottom cover-attached perspective views, respectively, of the sensor cover and sensor of FIG. **1**. FIG. **2D** illustrates a first **140** and second **240** sensor covers placed over the detector **210** and emitters **230**, respectively. FIG. **2A** illustrates a view of a side of the sensor placed in contact with a tissue site. In FIG. **2A**, the sensor cover **140** attaches to the sensor **120** and covers the detector **210**, with a protruding portion **220** extending past the sensor. The sensor cover **140** can be a generally elongated shape made of an opaque material. In an embodiment, one side of the sensor cover can include an adhesive layer over the portion of the cover designed to block the detector **210** while the remainder of the cover can be adhesive free. Thus, the cover **140** does not catch on other objects and cause the cover **140** to be prematurely removed. The cover **140** can be removed by pulling on the protruding portion **220** either before or after the sensor **120** has been placed onto a measurement site. FIG. **2B** illustrates the sensor **120** with the sensor cover **140** removed. FIG. **2C** illustrates a view of an opposite side of the sensor of FIG. **2A**.

FIG. **3A** illustrates a non-protruding sensor cover **310** according to an embodiment of the disclosure. The opaque sensor cover **310** fits within the sensor **120** and blocks a sensor component **210**, such as the emitters or the detector. By staying within the sensor edges, the chance of accidental removal of the cover can be reduced. When the sensor **120** is ready for use, the sensor cover **310** can be removed.

FIG. **3B** illustrates a non-protruding sensor cover having an opaque border **314** and a removable opaque center **312**. The opaque center **312** can be removed separately from the opaque border **314**, leaving an opaque material surrounding the sensor component **210**. When the sensor is attached to the patient, the opaque border **314** can minimize light piping, thereby increasing accuracy of the readings. For example, the opaque border **314** can prevent reflected or scattered light that has not passed through tissue from entering into the detector and/or prevent the detector from picking up light from the emitters that fall around instead of on the detector. In an embodiment, the sensor cover can have adhesive on one both sides. Adhesive on both sides of the sensor cover allows the cover to stick to a patient, further preventing light piping or movement of the sensor. In an embodiment the sensor cover can have a clear window section in addition to or instead of a removable center **312**.

FIG. **3C** illustrates a sensor cover **316** having a clear "window" **317** over the sensor component. In an embodiment, the sensor cover can be used to protect the sensor component, provide a new adhesive layer, and/or reduce light piping while allowing the light through the "window." By using a clear window, the sensor cover does not have to

be removed when sensor is attached to the patient. In some embodiments, a removable opaque portion can be placed over the window.

FIG. **3D** illustrates a sensor cover integrated with an opaque adhesive cover **320** for the sensor. An adhesive sensor generally has one or more adhesive covers **320** covering one or more adhesive portions **330** of the sensor. In FIG. **3D**, the opaque adhesive cover **320** is extended to cover the sensor component **210**. The adhesive cover **320** can be peeled off to reveal the adhesive layer **330** and uncover the sensor component **210**.

FIG. **3E** illustrates a sensor cover **340** covering an adhesive sensor. In FIG. **3E**, the opaque sensor cover **340** has adhesive material on both sides of the sensor cover in order to allow reattachment of a sensor where the original adhesive material **330** has lost its adhesiveness. The sensor cover **340** can be placed on the sensor using a first adhesive layer **350** while the sensor is detached from a patient. An adhesive cover (not shown) protects a second adhesive layer **360** and can be removed before the sensor is placed on the patient. The second adhesive layer allows the sensor to be reattached to the patient. The sensor cover can cover both the detector and emitters of the sensor. The sensor cover **322** can have removable or clear sections **370**, **380** over the detector and/or emitters to allow light to pass through.

FIGS. **4A-4B** are a top view and a close up view, respectively, of an integrated sensor cover according to an embodiment of the disclosure. FIG. **4A** illustrates an embodiment of the sensor cover where the sensor cover **410** is integrated with the sensor **400**. The sensor has a slot **420** positioned near an emitter or a detector. The slot allows an arm **410**, **430** to be folded over a sensor component **435**, which can be the emitters or the detector, thereby covering it. In certain embodiments, the sensor **400** is an adhesive sensor. The use of a slot allows an adhesive arm **410** to be used as a sensor cover without having to remove the arm's adhesive cover. Once a patient is available, the adhesive arm **410** can be removed from the slot, the adhesive cover can be removed, and the adhesive arms **410**, **430** used to secure the adhesive sensor to the patient. FIG. **4B** illustrates a close up view of the slot **420** and sensor cover **410** of FIG. **4A**. FIG. **4C** illustrates the sensor cover **410** folded over the sensor component **435** with the end of the sensor cover inserted into the slot. A portion of the sensor cover extends into the slot and to the back side of the sensor. The slot keeps the sensor cover **410** generally secure against the sensor component **435**.

FIG. **5A** is a front view a sensor cover **510** attachable to a reusable sensor according to an embodiment of the disclosure. The sensor cover **510** includes a recess **515** into which a sensor housing can be inserted. The sensor housing generally fits closely in the recess **515**. Friction between the inner surfaces of the sensor cover **510** and the sensor housing generally secures the housing with the sensor cover **510**. FIG. **5B** illustrates the mating of the sensor cover **510** of FIG. **5A** with a sensor **520**. In the illustrated embodiment, the sensor **520** is a reusable clip-style sensor. The sensor cover **510** fits over a lower sensor housing **525**. The sensor housings **525**, **545** can contain sensor components **530**, **540**, such as the emitters or the detector. In certain embodiments, the sensor component **530** is a detector and the sensor cover **510** prevents the detector from receiving light. The sensor cover **510** can be removed when the sensor **520** is in use and reattached once the sensor **520** is not in use.

FIG. **6** illustrates a sensor cover **610** attachable to a sensor **520** via one or more tabs or attachment arms **620** according to an embodiment of the disclosure. The tabs **620** fit over the

sides of an upper housing 545 of the sensor and generally secure the sensor cover 610 against the upper housing 545. The sensor cover 610 covers the sensor component, such as the emitters or the detector, located in the upper housing 545.

FIG. 7 illustrates an embodiment of the sensor cover 700 configured to block both the emitters and the detector. An upper arm 710 secures against an upper housing of a sensor. A lower arm 720 secures against a lower housing of a sensor. The upper 710 and lower 720 arms are connected by a hinge portion 725. The arms 710, 720 can be attached via a press fit. The lower arm 720 can also include an attachment arm 730 to better secure the sensor cover 700 against the lower housing of the sensor.

FIG. 8 illustrates an embodiment of the sensor cover 800 attachable to a sensor housing via an attachment arm 810. The attachment arm 810 is configured to secure the sensor cover 800 in place when applied to the sensor. Upon application to a sensor, the front portion of the sensor housing may occupy the space defined by the attachment arm 810 and the underside of the lower portion 805 of the sensor cover 800. The attachment arm 810 helps to releasably secure the sensor, via a friction fit, for example. One or more other features, such as the lip 815 disposed on the side of the sensor cover proximal to the sensor can be included to further secure the sensor cover 800 in the sensor. Upon insertion of the sensor cover 800 into the sensor, the sides of the sensor housing abut the lip 815. Accordingly, the lip 815 can help ensure that the sensor cover 800 is positioned appropriately deep within the sensor.

Although the above embodiments have been described with respect to an opaque material intended to optically insulate the optical sensor, as will be appreciated by skilled artisans from the disclosure provided herein, sensor covers made of different insulative materials can be used as appropriate for different types of sensors. For example, sonically insulative materials, such as foam, rubber, cotton, and/or other sound deadening materials can be used to cover sensors that employ sound, such as a bioacoustic or ultrasound sensor. In some embodiments, electrically insulative materials, such as rubber, polyethylene, silicone and/or other insulators can be used to cover sensors that employ electrical signals, such as bioimpedance sensors. In some embodiments, mechanically insulative materials, such as hard plastic, metal, rubber, silicone, and/or other rigid or dampening materials can be used to cover mechanical sensors to prevent sensor actuation. In some embodiments, chemically insulative material, such as plastic, metal, polyethylene or the like can be used to cover chemical sensors and prevent their exposure to the environment.

FIGS. 9A-9D illustrate embodiments of sensor covers for a bioacoustic sensor. FIG. 9A illustrates one embodiment of a bioacoustic sensor. The bioacoustic sensor 900 is configured for placement against a patient's skin. The contact surface 903 of the sensor 900 is placed against the skin. The bioacoustic sensor picks up sound waves from the patient's body and converts them into electrical signals for transmission to a monitoring device. In one embodiment, the bioacoustic sensor can use a piezoelectric transducer as the sensing element to detect sound waves. In FIG. 9A a sensor cover 905 made of a sound-deadening material, such as foam, rubber, and/or cotton, is attached to the contact surface to prevent sound waves from being detected by the bioacoustic sensor 900. The sound-deadening material can be attached by adhesive, tabs, clips, friction fit, and/or other connection mechanism. In FIG. 9A, the bioacoustic sensor has a bump 910 on the contact surface 903 positioned to

apply pressure to the sensing element so as to bias the sensing element in tension and improve the receptivity of the sensing element to sound waves. Where such a bump 910 exists on the contact surface 903 of the sensor, embodiments of sensor cover 905 can be provided with a corresponding recess.

FIG. 9B illustrates an embodiment of the sensor cover 920 made of shaped sound-deadening material to increase the surface area available to absorb sound. In one embodiment, a plurality of wedge shaped protrusions 925 is formed on the surface of the sensor cover 920. In other embodiments, different shaped protrusions can be used, such as waveform, pyramid, egg crate, and/or other shapes to increase the surface area.

FIG. 9C illustrates a bioacoustic sensor cover having one or more attachment arms according to an embodiment of the disclosure. An attachment arm 935 is configured to releasably secure the sensor cover 930 when applied to the sensor via a friction fit, for example. A second attachment arm 936 can be provided to further secure the sensor cover 930 to the sensor 900. A recess 940 can also be formed on the interior surface of the sensor cover 930 in order to conform to protrusions on the contact surface of the sensor 900. Where the contact surface of the sensor 900 is flat, the interior surface can also be flat.

FIG. 9D illustrates a bioacoustic sensor having conductive leads according to an embodiment of the disclosure. In FIG. 9D, the illustrated bioacoustic sensor 900 has one or more apertures 950, 955 exposing the sensing element 960 to the contact surface 903. In one embodiment, the sensor cover 962 prevents the bioacoustic sensor from taking readings by creating an electrical short in the sensor. One or more conductive leads or wires 965, 970 configured to fit into the apertures 950, 955 in the sensor housing are disposed on the sensor cover 962. The conductive leads 965, 970 abut the negative and positive electrical poles of the sensing element 960. The conductive leads can be formed of copper or other conductive material. In one embodiment, the conductive leads 965, 970 can abut internal wiring that connects to the negative and positive electrical poles, such that a direct connection is not required. The conductive leads 965, 970 are joined by a connector lead or wire 975 to generate a short circuit in the sensor 900. In an embodiment, the conductive leads 965, 970 and connector lead 975 are a single connected structure. In an embodiment, the sensor cover 962 further comprises one or more attachment arms 980, 982 for releasably securing the sensor cover 962 to the sensor 900. In an embodiment, the sensor cover 962 further comprises a recess 985 to conform against a protrusion 910 on the contact surface 903 of the sensor. In one embodiment, the sensor cover 962 is formed out of a sound deadening material, such as foam or rubber. In one embodiment, the sensor cover 962 is made of hard plastic or other types of plastic materials.

Conditional language used herein, such as, among others, "can," "could," "might," "may," "e.g.," and the like, unless specifically stated otherwise, or otherwise understood within the context as used, is generally intended to convey that certain embodiments include, while other embodiments do not include, certain features, elements and/or states. Thus, such conditional language is not generally intended to imply that features, elements and/or states are in any way required for one or more embodiments or that one or more embodiments necessarily include logic for deciding, with or without author input or prompting, whether these features, elements and/or states are included or are to be performed in any particular embodiment.

Various sensor covers have been disclosed in detail in connection with various embodiments. These embodiments are disclosed by way of examples only and are not to limit the scope of the claims that follow. One of ordinary skill in the art will appreciate the many variations, modifications and combinations. For example, in various embodiments, adhesive, snap-fit, friction-fit, clips, tabs, and other attachment mechanisms can be employed. In addition, in various embodiments the sensor covers are used with a sensor that can measure any type of physiological parameter. In various embodiments, the sensor covers can be for any type of medical device or sensor. In various embodiments, adhesive can be placed on both sides of the sensor cover to aid in the reattachment of sensors where the sensor adhesive has grown weak. In various embodiments, sensors covers can be made in whole or in part of materials such as foam, polyester, polypropylene, rubber, vinyl, cling vinyl, urethane rubber plastic or other plastic materials, cloth, metal, combinations of the same or the like.

What is claimed is:

1. A sensor covering system, the sensor covering system comprising:

a pulse oximeter sensor comprising sensing components including at least a light-emitting component and a light-detecting component; and

a sensor cover configured to be adhered to the pulse oximeter sensor and removed before use of the pulse oximeter sensor, wherein:

the sensor cover is at least partially opaque, at least a portion of the sensor cover protrudes from the pulse oximeter sensor to facilitate removal of the sensor cover, and

the sensor cover, when adhered to the pulse oximeter sensor, covers at least one of the sensing components while the pulse oximeter sensor is active and blocks at least a portion of light from the one or more emitters from being received by the detector.

2. The sensor covering system of claim 1, wherein the portion of the sensor cover that protrudes from the pulse oximeter sensor extends beyond an edge of the pulse oximeter sensor to enable removal of the sensor cover from the pulse oximeter sensor.

3. The sensor covering system of claim 2, wherein the portion of the sensor cover that protrudes from the pulse oximeter sensor comprises a rectangular planar shape.

4. The sensor covering system of claim 3, wherein the portion of the sensor cover that protrudes from the pulse oximeter sensor is not adhered to the pulse oximeter sensor when the sensor cover is adhered to the pulse oximeter sensor.

5. The sensor covering system of claim 4, wherein the sensor cover, when adhered to the pulse oximeter sensor, further blocks at least a portion of ambient light from a surrounding area from being received by the detector.

6. The sensor covering system of claim 5, wherein the sensor cover reduces false readings by the pulse oximeter sensor until the pulse oximeter sensor is in use.

7. The sensor covering system of claim 6, wherein the sensor cover is opaque.

8. The sensor covering system of claim 7, wherein: the pulse oximeter sensor further comprises a window formed on a surface of the pulse oximeter sensor that is aligned with the light-emitting component and the light-detecting component to allow light to reach the light-emitting component and the light-detecting component, and

the sensor cover, when adhered to the pulse oximeter sensor, covers the window while the pulse oximeter sensor is active and blocks at least a portion of light from the one or more emitters from being received by the detector.

9. A sensor cover for use with a pulse oximeter sensor, the sensor cover comprising:

a cover portion configured to be adhered to a pulse oximeter sensor and removed before use of the pulse oximeter sensor; and

a protruding portion that protrudes from the pulse oximeter sensor to facilitate removal of the sensor cover, wherein:

the sensor cover is removable from the pulse oximetry sensor,

the cover portion, when adhered to the pulse oximeter sensor, covers one or more sensing components of the pulse oximeter sensor while the pulse oximeter sensor is active and blocks at least a portion of light from one or more emitters of the pulse oximeter sensor from being received by a detector of the pulse oximeter sensor.

10. The sensor cover of claim 9, wherein the sensing components of the pulse oximeter sensor include at least:

the one or more emitters; and

the detector configured to receive at least a portion of the light emitted by the one or more emitters after the light has passed through a tissue site.

11. The sensor cover of claim 10, wherein the protruding portion extends beyond an edge of the pulse oximeter sensor to enable removal of the sensor cover from the pulse oximeter sensor.

12. The sensor cover of claim 11, wherein the protruding portion comprises a rectangular planar shape.

13. The sensor cover of claim 12, wherein the protruding portion is not adhered to the pulse oximeter sensor when the cover portion is adhered to the pulse oximeter sensor.

14. The sensor cover of claim 13, wherein the cover portion, when adhered to the pulse oximeter sensor, further blocks at least a portion of ambient light from a surrounding area from being received by the detector.

15. The sensor cover of claim 14, wherein the cover portion and the protruding portion together comprise a single integral component.

16. The sensor cover of claim 15, wherein the sensor cover reduces false readings by the pulse oximeter sensor until the pulse oximeter sensor is in use.

17. The sensor cover of claim 16, wherein the cover portion is partially or fully opaque.

18. A method of providing a sensor cover for a pulse oximeter sensor, the method comprising:

providing a sensor cover according to claim 9; and

adhering the sensor cover to the pulse oximeter sensor, the sensor cover covering one or more sensing components of the pulse oximeter sensor while the pulse oximeter sensor is active.

19. The method of claim 18, wherein the portion of the cover portion that protrudes from the pulse oximeter sensor extends past the sensor.

20. The method of claim 19, wherein the protruding portion extends beyond an edge of the pulse oximeter sensor to enable removal of the sensor cover from the pulse oximeter sensor.

11

21. The method of claim 20, wherein the protruding portion comprises a rectangular planar shape.

22. The method of claim 21, wherein the protruding portion is not adhered to the pulse oximeter sensor when the cover portion is adhered to the pulse oximeter sensor.

23. The method of claim 22, wherein the cover portion, when adhered to the pulse oximeter sensor, further blocks at least a portion of ambient light from a surrounding area from being received by the detector.

24. The method of claim 23, wherein cover portion and the protruding portion together comprise a single integral component.

25. The method of claim 24, wherein the pulse oximeter sensor comprises sensing components including at least: the one or more emitters; and the detector configured to receive at least a portion of the light emitted by the one or more emitters after the light has passed through a tissue site.

12

26. The method of claim 25 further comprising: activating the one or more emitters of the pulse oximeter sensor to emit light from the one or more emitters; and blocking, with the sensor cover, at least a portion of the light from the one or more emitters from being received by the detector.

27. The method of claim 26, wherein the sensor cover reduces false readings by the pulse oximeter sensor until the pulse oximeter sensor is in use.

28. The method of claim 27, wherein the cover portion is partially or fully opaque.

29. The method of claim 28 further comprising: pulling the protruding portion to remove the sensor cover from the pulse oximeter sensor to expose the one or more emitters and the detector and an adhesive surface of the pulse oximeter cover; and applying the pulse oximeter sensor to the tissue site.

* * * * *

专利名称(译)	无创生理传感器盖		
公开(公告)号	US10194848	公开(公告)日	2019-02-05
申请号	US16/149532	申请日	2018-10-02
[标]申请(专利权)人(译)	梅西莫股份有限公司		
申请(专利权)人(译)	Masimo公司		
当前申请(专利权)人(译)	Masimo公司		
[标]发明人	KIANI ABRAHAM MAZDA KIANI MASSI JOE E		
发明人	KIANI, ABRAHAM MAZDA KIANI, MASSI JOE E.		
IPC分类号	A61B5/1455 A61B5/00 A61B5/145 A61B5/024		
CPC分类号	A61B5/14552 A61B5/6826 A61B5/6838 A61B5/6819 A61B5/6816 A61B5/14546 A61B5/14532 A61B5/02416 A61B5/6829 A61B5/6832 A61B5/02427 A61B5/68335		
优先权	15/046954 2018-05-29 US 61/229682 2009-07-29 US		
其他公开文献	US20190038194A1		
外部链接	Espacenet		

摘要(译)

根据本公开的实施例的传感器盖能够与非侵入性生理传感器一起使用，例如脉搏血氧测量传感器。当传感器未使用时，传感器盖的某些实施例减少或消除来自传感器的错误读数，例如，当脉冲血氧计传感器激活但未使用时，通过阻挡脉冲血氧计传感器的光检测部件。此外，传感器盖的实施例可以防止对传感器的损坏。另外，传感器盖的实施例防止传感器的污染。

