



US009438044B2

(12) **United States Patent**  
**Proud**

(10) **Patent No.:** **US 9,438,044 B2**  
(45) **Date of Patent:** **\*Sep. 6, 2016**

(54) **METHOD USING WEARABLE DEVICE WITH UNIQUE USER ID AND TELEMETRY SYSTEM IN COMMUNICATION WITH ONE OR MORE SOCIAL NETWORKS**

USPC ..... 709/204; 379/106.01, 106.02  
See application file for complete search history.

(71) Applicant: **Hello Inc.**, San Francisco, CA (US)  
(72) Inventor: **James Proud**, San Francisco, CA (US)  
(73) Assignee: **Hello Inc.**, San Francisco, CA (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,127,363 A 3/1964 Nitzsche et al.  
3,715,334 A 2/1973 Karstedt

(Continued)

FOREIGN PATENT DOCUMENTS

DE 3839900 A1 5/1990  
EP 0183553 A2 6/1986

(Continued)

OTHER PUBLICATIONS

David, G.I., et al., "On enabling secure applications through off-line biometric identification", Proceedings of the IEEE Symposium on Security and Privacy (May 1998).

(Continued)

*Primary Examiner* — Phillip H Nguyen

(74) *Attorney, Agent, or Firm* — Paul Davis

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 406 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **13/923,750**

(22) Filed: **Jun. 21, 2013**

(65) **Prior Publication Data**

US 2014/0250181 A1 Sep. 4, 2014

**Related U.S. Application Data**

(60) Provisional application No. 61/772,265, filed on Mar. 4, 2013, provisional application No. 61/812,083, filed on Apr. 15, 2013.

(51) **Int. Cl.**  
**G06F 15/16** (2006.01)  
**H02J 5/00** (2016.01)  
(Continued)


(52) **U.S. Cl.**  
CPC ..... **H02J 5/005** (2013.01); **A61B 5/002** (2013.01); **A61B 5/002** (2013.01); **A61B 5/0015** (2013.01); **A61B 5/0022** (2013.01);  
(Continued)

(58) **Field of Classification Search**  
CPC .. G06Q 10/10; A61B 5/0002; H04M 11/002

(57) **ABSTRACT**

A method is provided for using telemetry data, and a wearable device that communicates with a social network. One or more sensors, coupled to the wearable device that has a unique user ID, are used to acquire at least one of a user's activities, behaviors and habit information. The wearable device has ID circuitry and a communication system that reads and transmits the unique ID from an ID storage. The wearable device communicates with a social network. A telemetry system communicates with the one or more sensors. The telemetry system includes a database of user ID's. Telemetry data is analyzed based on at least one of, user's activities, behaviors and habit information. Personalized information is created about the user.

**28 Claims, 23 Drawing Sheets**



(51)	<b>Int. Cl.</b>		8,126,729 B2	2/2012	Dicks et al.	
	<i>H01F 38/14</i>	(2006.01)	8,126,735 B2	2/2012	Dicks et al.	
	<i>A61B 5/00</i>	(2006.01)	8,157,731 B2	4/2012	Teller et al.	
	<i>G06F 9/445</i>	(2006.01)	8,204,786 B2	6/2012	LeBoeuf et al.	
	<i>H04L 29/06</i>	(2006.01)	8,239,784 B2	8/2012	Hotelling et al.	
	<i>H02J 7/02</i>	(2016.01)	8,251,903 B2	8/2012	LeBoeuf et al.	
	<i>H02J 17/00</i>	(2006.01)	8,279,180 B2	10/2012	Hotelling et al.	
	<i>G08C 17/02</i>	(2006.01)	8,328,718 B2	12/2012	Tran	
	<i>G06Q 20/32</i>	(2012.01)	8,352,211 B2	1/2013	Vock et al.	
	<i>H04L 29/08</i>	(2006.01)	8,369,936 B2	2/2013	Farringdon et al.	
	<i>H02J 7/00</i>	(2006.01)	8,378,811 B2	2/2013	Crump et al.	
	<i>G06F 19/00</i>	(2011.01)	8,381,135 B2	2/2013	Hotelling et al.	
(52)	<b>U.S. Cl.</b>		8,389,627 B2	3/2013	Rubinsztajn et al.	
	CPC .....	<i>A61B 5/0024</i> (2013.01); <i>G06F 8/65</i>	8,390,463 B2	3/2013	Munthe-Kaas et al.	
		(2013.01); <i>G06Q 20/322</i> (2013.01); <i>G08C</i>	8,398,546 B2	3/2013	Pacione et al.	
		<i>17/02</i> (2013.01); <i>H01F 38/14</i> (2013.01); <i>H02J</i>	8,479,122 B2	7/2013	Hotelling et al.	
		<i>7/025</i> (2013.01); <i>H02J 17/00</i> (2013.01); <i>H04L</i>	8,587,426 B2	11/2013	Bloem	
		<i>65/403</i> (2013.01); <i>H04L 67/22</i> (2013.01);	8,663,106 B2	3/2014	Stivoric et al.	
		<i>A61B 2560/0214</i> (2013.01); <i>A61B 2562/08</i>	8,929,963 B2 *	1/2015	Lisogurski .....	<i>A61B 5/0004</i>
		(2013.01); <i>G06F 19/3418</i> (2013.01); <i>H02J</i>	2002/0015024 A1	2/2002	Westerman et al.	128/903
		<i>2007/0096</i> (2013.01); <i>Y02B 60/183</i> (2013.01)	2002/0109600 A1	8/2002	Mault et al.	
			2002/0178126 A1 *	11/2002	Beck .....	<i>A61B 5/0002</i>
			2003/0023467 A1	1/2003	Moldovan	705/75
			2003/0121033 A1	6/2003	Peev et al.	
			2003/0143113 A2	7/2003	Yuzhakov et al.	
			2004/0044799 A1 *	3/2004	Sivaraman .....	<i>G06F 17/30578</i>
			2004/0172290 A1	9/2004	Leven	709/253
			2005/0113650 A1	5/2005	Pacione et al.	
			2005/0137480 A1 *	6/2005	Alt .....	<i>A61B 5/0031</i>
			2005/0190059 A1	9/2005	Wehrenberg	600/508
			2005/0245839 A1	11/2005	Stivoric et al.	
			2006/0017692 A1	1/2006	Wehrenberg et al.	
			2006/0026536 A1	2/2006	Hotelling et al.	
			2006/0030891 A1	2/2006	Saltzstein et al.	
			2006/0033724 A1	2/2006	Chaudhri et al.	
			2006/0064030 A1	3/2006	Cosentino et al.	
			2006/0066449 A1	3/2006	Johnson	
			2006/0089592 A1 *	4/2006	Kadhiresan .....	<i>A61M 5/142</i>
			2006/0098772 A1	5/2006	Reho et al.	604/65
			2006/0136270 A1	6/2006	Morgan et al.	
			2006/0159645 A1	7/2006	Miller et al.	
			2006/0197753 A1	9/2006	Hotelling	
			2006/0202816 A1 *	9/2006	Crump .....	<i>A61B 5/02055</i>
			2006/0264778 A1 *	11/2006	Lim .....	340/539.12
			2007/0149862 A1	6/2007	Pipke	<i>A61B 5/417</i>
			2007/0167753 A1	7/2007	Van Wyk et al.	600/576
			2007/0174633 A1	7/2007	Draper et al.	
			2008/0012701 A1	1/2008	Kass et al.	
			2008/0076969 A1	3/2008	Kraft et al.	
			2008/0146890 A1	6/2008	LeBoeuf et al.	
			2009/0023428 A1	1/2009	Behzad et al.	
			2009/0088820 A1	4/2009	Mao et al.	
			2009/0112247 A1	4/2009	Freeman et al.	
			2009/0119760 A1	5/2009	Hung et al.	
			2009/0182208 A1	7/2009	Cho et al.	
			2009/0192533 A1 *	7/2009	Dlugos, Jr. ....	<i>A61B 5/037</i>
			2009/0234206 A1	9/2009	Gaspard et al.	606/157
			2009/0240120 A1	9/2009	Mensingher et al.	
			2009/0255122 A1	10/2009	Azrielant	
			2009/0318773 A1	12/2009	Jung et al.	
			2010/0141042 A1	6/2010	Kesler et al.	
			2010/0153269 A1	6/2010	McCabe	
			2010/0234695 A1	9/2010	Morris	
			2010/0277003 A1	11/2010	Von Novak et al.	
			2011/0055132 A1	3/2011	Mahdian et al.	
			2011/0068935 A1	3/2011	Riley et al.	
			2011/0179450 A1	7/2011	Kim et al.	
			2012/0035487 A1	2/2012	Werner et al.	
			2012/0083705 A1 *	4/2012	Yuen .....	<i>A61B 5/0002</i>
			2012/0133079 A1	5/2012	Sykes et al.	600/508
(56)	<b>References Cited</b>					
	U.S. PATENT DOCUMENTS					
	3,775,452 A	11/1973	Karstedt			
	3,813,364 A	5/1974	Zuba et al.			
	3,814,730 A	6/1974	Karstedt			
	4,394,317 A	7/1983	McAfee et al.			
	4,603,152 A	7/1986	Laurin et al.			
	4,780,556 A	10/1988	Hata et al.			
	5,057,151 A	10/1991	Schuster et al.			
	5,187,657 A	2/1993	Forbes			
	5,319,363 A *	6/1994	Welch .....	<i>H04Q 9/00</i>		
				340/12.3		
	5,348,008 A	9/1994	Bornn et al.			
	5,564,429 A	10/1996	Bornn et al.			
	5,576,054 A	11/1996	Brown			
	5,735,887 A	4/1998	Barreras, Sr. et al.			
	5,910,544 A	6/1999	Ozawa et al.			
	5,971,941 A	10/1999	Simons et al.			
	6,038,315 A	3/2000	Strait et al.			
	6,120,467 A *	9/2000	Schallhorn .....	<i>A61N 1/36071</i>		
				600/595		
	6,200,289 B1	3/2001	Hochman et al.			
	6,221,012 B1	4/2001	Maschke et al.			
	6,323,846 B1	11/2001	Westerman et al.			
	6,416,471 B1	7/2002	Kumar et al.			
	6,440,067 B1	8/2002	DeLuca et al.			
	6,454,708 B1	9/2002	Ferguson et al.			
	6,570,557 B1	5/2003	Westerman et al.			
	6,580,356 B1	6/2003	Alt et al.			
	6,661,372 B1	12/2003	Girerd et al.			
	6,677,932 B1	1/2004	Westerman			
	6,893,396 B2	5/2005	Schulze et al.			
	7,113,932 B2	9/2006	Tayebnejad et al.			
	7,248,894 B2	7/2007	Fujieda et al.			
	7,502,643 B2	3/2009	Farringdon et al.			
	7,614,008 B2	11/2009	Ording			
	7,616,110 B2	11/2009	Crump et al.			
	7,633,076 B2	12/2009	Huppi et al.			
	7,653,883 B2	1/2010	Hotelling et al.			
	7,657,849 B2	2/2010	Chaudhri et al.			
	7,663,607 B2	2/2010	Hotelling et al.			
	7,720,855 B2	5/2010	Brown			
	7,733,224 B2	6/2010	Tran			
	7,844,914 B2	11/2010	Andre et al.			
	7,957,762 B2	6/2011	Herz et al.			
	7,959,567 B2	6/2011	Stivoric et al.			
	8,006,002 B2	8/2011	Kalayjian et al.			
	8,028,905 B2	10/2011	Holberg			
	8,033,996 B2	10/2011	Behar			
	8,044,363 B2	10/2011	Ales et al.			

(56)

References Cited

U.S. PATENT DOCUMENTS

2012/0146795 A1 6/2012 Margon et al.  
 2012/0149996 A1 6/2012 Stivoric et al.  
 2012/0170305 A1 7/2012 Rudek et al.  
 2012/0170521 A1 7/2012 Vogedes et al.  
 2012/0184876 A1 7/2012 Freeman et al.  
 2012/0194341 A1 8/2012 Peichel et al.  
 2012/0194419 A1 8/2012 Osterhout et al.  
 2012/0196832 A1 8/2012 Luria  
 2012/0205373 A1 8/2012 Caldwell  
 2012/0225719 A1 9/2012 Nowozin et al.  
 2012/0226639 A1 9/2012 Burdick et al.  
 2012/0229270 A1 9/2012 Morley et al.  
 2012/0242501 A1 9/2012 Tran et al.  
 2012/0253485 A1 10/2012 Weast et al.  
 2012/0253489 A1 10/2012 Dugan et al.  
 2012/0290327 A1 11/2012 Hanlon et al.  
 2012/0290950 A1 11/2012 Rapaport et al.  
 2012/0302920 A1\* 11/2012 Bridger ..... A61B 7/04  
 600/586  
 2012/0330109 A1 12/2012 Tran  
 2013/0022659 A1 1/2013 Roberts  
 2013/0030711 A1 1/2013 Korhonen  
 2013/0035785 A1 2/2013 MacVittie et al.  
 2013/0127980 A1 5/2013 Haddick et al.  
 2013/0154851 A1 6/2013 Gaskill et al.  
 2013/0172691 A1 7/2013 Tran  
 2013/0175732 A1 7/2013 Lust et al.  
 2013/0255681 A1 10/2013 Batch et al.  
 2013/0267794 A1 10/2013 Fernstrom et al.  
 2013/0326790 A1 12/2013 Cauwels  
 2014/0019468 A1 1/2014 Federoff et al.  
 2014/0129942 A1 5/2014 Rathod  
 2014/0266939 A1 9/2014 Baringer et al.

FOREIGN PATENT DOCUMENTS

EP 0271423 A1 6/1988  
 EP 0369255 A2 5/1990  
 EP 371004 A1 5/1990  
 EP 0477681 A2 4/1992  
 EP 0567253 A1 10/1993  
 EP 0640663 A2 3/1995

EP 0654497 A1 5/1995  
 EP 1094091 4/2001  
 EP 1094091 A1 4/2001  
 EP 1113042 A2 7/2001  
 EP 1133936 A1 9/2001  
 EP 1172414 A2 1/2002  
 EP 1217042 A1 6/2002  
 EP 1367534 A2 12/2003  
 EP 1371004 A2 12/2003  
 EP 1555297 A1 7/2005  
 EP 1595676 A1 11/2005  
 EP 1785454 A1 5/2007  
 EP 1792944 A1 6/2007  
 EP 1883798 A1 2/2008  
 EP 2052352 A1 4/2009  
 EP 2063555 A1 5/2009  
 EP 2428774 A1 3/2012  
 EP 2582116 A2 4/2013  
 EP 2614945 A2 7/2013  
 GB 1278798 A 6/1972  
 GB 1381933 A 1/1975  
 GB 2460890 A 12/2009  
 WO 8704449 A1 7/1987  
 WO 9500992 A1 1/1995  
 WO 9956922 A1 11/1999  
 WO 02063555 A2 8/2002  
 WO 2006127726 A1 11/2006  
 WO 2008050951 A1 5/2008  
 WO 2012/170305 A1 12/2012  
 WO 2013076676 A1 5/2013  
 WO 2013081447 A1 6/2013

OTHER PUBLICATIONS

Juels, A., et al., "A Fuzzy Vault Scheme", Proceedings of the 2002 IEEE Symposium on Information Theory (Jun. 2002).  
 Juels, A., et al., "A Fuzzy commitment scheme", Proc. 5th ACM Conference on Comp. and Commun. Securiry, pp. 28-36, 1999.  
 Yang, S., et al., "Secure fuzzy vault fingerprint verification system", Asilmoar Conf. on Signals, Systems and Comp., vol. 1, pp. 577-581 (Nov. 2004).  
 Uludag, U., et al., "Fuzzy fingerprint vault", Proc. Workshop: Biometrics: Challenges arising from theory to practice, pp. 13-16 (Aug. 2004).

\* cited by examiner




FIG. 1A




FIG. 1B




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16A




FIG. 16B




FIG. 16C




FIG. 16D




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23

**METHOD USING WEARABLE DEVICE  
WITH UNIQUE USER ID AND TELEMETRY  
SYSTEM IN COMMUNICATION WITH ONE  
OR MORE SOCIAL NETWORKS**

CROSS-REFERENCE TO RELATED  
APPLICATIONS

This application claims the benefit of U.S. 61/772,265 filed Mar. 4, 2013 and U.S. 61/812,083 filed Apr. 15, 2013, both of which applications are incorporated herein by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention is directed to methods using wearable device in communication with telemetry systems, and more particularly to an intelligent, wearable device with a unique ID that is in communication with one or more social networks.

2. Description of the Related Art

Telemetry systems can be implemented to acquire and transmit data from a remote source. Some telemetry systems provide information about a user's activities.

It is becoming commonplace to use wireless packet data service networks for effectuating data sessions with. In some implementations, unique identifications (ID) need to be assigned to the devices in order to facilitate certain aspects of service provisioning, e.g., security, validation and authentication, et cetera. In such scenarios, it becomes imperative that no two devices have the same indicium (i.e., collision). Further, provisioning of such indicia should be flexible so as to maintain the entire pool of indicia to a manageable level while allowing for their widespread use in multiple service environments.

The popularity and growth of social network sites and services has increased dramatically over the last few years. Present social network sites include Facebook®, Google+®, Twitter®, MySpace®, YouTube®, LinkedIn®, Flickr®, Jaiku®, MYUBO®, Bebo® and the like. Such social networking (SNET) sites are typically web-based and organized around user profiles and/or collections of content accessible by members of the network. Membership in such social networks is comprised of individuals, or groupings of individuals, who are generally represented by profile pages and permitted to interact as determined by the social networking service.

In many popular social networks, especially profile-focused social networks, activity centers on web pages or social spaces that enable members to view profiles, communicate and share activities, interests, opinions, status updates, audio/video content, etc., across networks of contacts. Social networking services might also allow members to track certain activities of other members of the social network, collaborate, locate and connect with existing friends, former acquaintances and colleagues, and establish new connections with other members.

Individual members typically connect to social networking services through existing web-based platforms via a computing device, tablet or smartphone. Members often share a common bond, social status, or geographic or cultural connection with their respective contacts. Smartphone and games-based mobile social networking services are examples of rapidly developing areas.

In so-called "cloud" computing, computing tasks are performed on remote computers/servers which are typically

accessed via Internet connections. One benefit of cloud computing is that it can reduce the relative processing and storage capabilities required by user devices (e.g., a cloud computer may load a webpage accessed by a tablet device and communicate only required information back to the tablet). Accordingly, recent years have witnessed an ever-growing amount of content and application software being migrated from local or on-site storage to cloud-based data storage and management. Such software functionality/services and content are typically available on-demand via (virtualized) network infrastructures.

There is a need for wearable telemetry devices, such as a wristband, where one size fits all. Yet there is another need for wearable telemetry devices suitable for use in social networking.

SUMMARY OF THE INVENTION

An object of the present invention is to provide a wearable device, such as a wristband, where one size fits all.

A further object of the present invention is to provide for wearable devices suitable for use in social networking.

Another object of the present invention is to provide a wearable device that gathers a user's data based on a user's habits, with a telemetry system that analyzes the data and provides the user with personalized information about their life.

Yet another object of the present invention is a wearable device or system that creates a unique portrait of its wearer that provides personalized information and mapping of a user's daily experience.

These and other objects of the present invention are achieved in a method for using telemetry data, and a wearable device that communicates with a social network. One or more sensors, coupled to the wearable device that has a unique user ID, are used to acquire at least one of a user's activities, behaviors and habit information. The wearable device has ID circuitry and a communication system that reads and transmits the unique ID from an ID storage. The wearable device communicates with a social network. A telemetry system communicates with the one or more sensors. The telemetry system includes a database of user ID's. Telemetry data is analyzed based on at least one of, user's activities, behaviors and habit information. Personalized information is created about the user.

In another embodiment of the present invention, a method is provided for using telemetry data, and a wearable device that communicates with a social network. One or more sensors are coupled to the wearable device that has a unique user ID. The wearable device acquires at least one of a user's activities, behaviors and habit information. The wearable device has ID circuitry that includes ID storage and a communication system that reads and transmits the unique ID from the ID storage. The wearable device communicates with a mobile device or computer that is in communication with a social network. A telemetry system is in communication with the one or more sensors. The telemetry system has a database of user ID's. Telemetry data is analyzed based on at least one of, user's activities, behaviors and habit information, the telemetry system creating personalized information about the user.

BRIEF DESCRIPTION OF THE DRAWINGS

FIGS. 1(a) and 1(b) illustrate one embodiment of a wearable device of the present invention, where one size fits all.

FIG. 2 illustrates one embodiment of electronics that can be included in the wearable device.

FIG. 3 illustrates one embodiment of a telemetry system of the present invention.

FIG. 4 is a diagram of the programming input schematic of the secure sensor/transmitter array of FIG. 7.

FIG. 5 is a block diagram of the system of programming the sensor/transmitter(s) comprising the secure sensor/transmitter array of FIG. 7.

FIG. 6 is a block diagram of the jam command and security/randomization bits of the secure sensor/transmitter array of FIG. 7.

FIG. 7 is a logic circuit diagram of the sensor/transmitter programming input schematic in one embodiment of the present invention.

FIG. 8 is a block diagram of an embodiment of a computer implemented system for determining the location of a remote sensor utilizing the methods of the present invention.

FIG. 9 is a block diagram illustrating one embodiment of a SNAPSHOT GPS receiver for use according to the present invention.

FIG. 10 is a block diagram of a remote sensor shown in communication with two different external communication devices.

FIG. 11 is a diagram of the active RF and RF backscatter antennas.

FIG. 12 is a diagram of the encoding scheme for the symbols in the active RF protocol.

FIG. 13 is a diagram of the packet structure in the IRDA protocol.

FIG. 14 is a diagram of the encoding scheme in the IRDA protocol.

FIG. 15 illustrates one embodiment of a wireless network that can be used with the present invention.

FIGS. 16(a)-16(d) illustrate various embodiments of the interaction of a wearable device of the present invention with an interaction engine, a transaction engine, a decoding engine, and a payment system and a third party.

FIG. 17 illustrates an embodiment of a social network circle with social devices in accordance with one embodiment of the present invention.

FIG. 18 illustrates an embodiment of a social group with a variety of members in accordance with one embodiment of the present invention.

FIG. 19 is a functional block diagram illustrating a social network infrastructure and social devices in accordance with one embodiment of the invention.

FIG. 20 illustrates a simplified block diagram of a client-server system and network in one embodiment of the present invention.

FIG. 21 illustrates a more detailed diagram of an exemplary client or server computer that can be used in one embodiment of the present invention.

FIG. 22 illustrates a system for activity collection and building a social graph including sharing activity between users in one embodiment of the present invention.

FIG. 23 illustrates a social graph with nodes representing users and edges representing sharing activity between the users in one embodiment of the present invention.

#### DETAILED DESCRIPTION

As used herein, the term engine refers to software, firmware, hardware, or other component that can be used to effectuate a purpose. The engine will typically include software instructions that are stored in non-volatile memory (also referred to as secondary memory). When the software

instructions are executed, at least a subset of the software instructions can be loaded into memory (also referred to as primary memory) by a processor. The processor then executes the software instructions in memory. The processor may be a shared processor, a dedicated processor, or a combination of shared or dedicated processors. A typical program will include calls to hardware components (such as I/O devices), which typically requires the execution of drivers. The drivers may or may not be considered part of the engine, but the distinction is not critical.

As used herein, the term database is used broadly to include any known or convenient means for storing data, whether centralized or distributed, relational or otherwise.

As used herein a mobile device includes, but is not limited to, a cell phone, such as Apple's iPhone®, other portable electronic devices, such as Apple's iPod Touches®, Apple's iPads®, and mobile devices based on Google's Android® operating system, and any other portable electronic device that includes software, firmware, hardware, or a combination thereof that is capable of at least receiving the signal, decoding if needed, exchanging information with a transaction server to verify the buyer and/or seller's account information, conducting the transaction, and generating a receipt. Typical components of mobile device may include but are not limited to persistent memories like flash ROM, random access memory like SRAM, a camera, a battery, LCD driver, a display, a cellular antenna, a speaker, a Bluetooth® circuit, and WIFI circuitry, where the persistent memory may contain programs, applications, and/or an operating system for the mobile device.

As used herein, the terms "social network" and "SNET" comprise a grouping or social structure of devices and/or individuals, as well as connections, links and interdependencies between such devices and/or individuals. Members or actors (including devices) within or affiliated with a SNET may be referred to herein as "nodes", "social devices", "SNET members", "SNET devices", "user devices" and/or "modules". In addition, the terms "SNET circle", "SNET group" and "SNET sub-circle" generally denote a social network that comprises social devices and, as contextually appropriate, human SNET members and personal area networks ("PANs").

A used herein, the term "wearable device" is anything that can be worn by an individual and that has a back side that in some embodiments contacts a user's skin and a face side. Examples of wearable device include but are not limited to a cap, arm band, wristband, garment, and the like.

As used herein, the term "computer" is a general purpose device that can be programmed to carry out a finite set of arithmetic or logical operations. Since a sequence of operations can be readily changed, the computer can solve more than one kind of problem. A computer can include of at least one processing element, typically a central processing unit (CPU) and some form of memory. The processing element carries out arithmetic and logic operations, and a sequencing and control unit that can change the order of operations based on stored information. Peripheral devices allow information to be retrieved from an external source, and the result of operations saved and retrieved.

As used herein, the term "Internet" is a global system of interconnected computer networks that use the standard Internet protocol suite (TCP/IP) to serve billions of users worldwide. It is a network of networks that consists of millions of private, public, academic, business, and government networks, of local to global scope, that are linked by a broad array of electronic, wireless and optical networking technologies. The Internet carries an extensive range of

information resources and services, such as the inter-linked hypertext documents of the World Wide Web (WWW) and the infrastructure to support email. The communications infrastructure of the Internet consists of its hardware components and a system of software layers that control various aspects of the architecture.

As used herein, the term “extranet” is a computer network that allows controlled access from the outside. An extranet can be an extension of an organization’s intranet that is extended to users outside the organization that can be partners, vendors, and suppliers, in isolation from all other Internet users. An extranet can be an intranet mapped onto the public Internet or some other transmission system not accessible to the general public, but managed by more than one company’s administrator(s). Examples of extranet-style networks include but are not limited to:

- LANs or WANs belonging to multiple organizations and interconnected and accessed using remote dial-up
- LANs or WANs belonging to multiple organizations and interconnected and accessed using dedicated lines
- Virtual private network (VPN) that is comprised of LANs or WANs belonging to multiple organizations, and that extends usage to remote users using special “tunneling” software that creates a secure, usually encrypted network connection over public lines, sometimes via an ISP

As used herein, the term “Intranet” is a network that is owned by a single organization that controls its security policies and network management. Examples of intranets include but are not limited to the following:

- A LAN
- A Wide-area network (WAN) that is comprised of a LAN that extends usage to remote employees with dial-up access
- A WAN that is comprised of interconnected LANs using dedicated communication lines
- A Virtual private network (VPN) that is comprised of a LAN or WAN that extends usage to remote employees or networks using special “tunneling” software that creates a secure, usually encrypted connection over public lines, sometimes via an Internet Service Provider (ISP)

For purposes of the present invention, the Internet, extranets and intranets collectively are referred to as (“Network Systems”).

In various embodiments, the present invention provides a wearable device **10**, such as a wearable device, where one size fits all. As illustrated in FIGS. 1(a) and 1(b), the wearable device **10** include a plurality of magnets **12**, with adjacent magnets having opposite polarity, with a length suitable to be worn by all people. In one embodiment, the length of the wearable device **10** can be 10-12 inches. The magnets **12** are positioned along an interior of the wearable device **10** to be provided for good conformation to a user’s wrist.

One or more sensors **14** are coupled to the wearable device **10**. The sensors are measuring devices. As a non-limiting example, the measuring device or sensors **14** can include RTSS devices to detect a user’s activities, motions, physical parameters, and the like, including but not limited to, a heart rate monitor, a body temperature probe, a conventional pedometer, an accelerometer and the like.

Alternatively, multifunctional sensors **14** which can perform all the aforementioned functions of RTSS may be attached or embedded in wearable device **10**. In one embodiment, each sensor can be in communication and or connect electronically and/or RF to a telemetry module **16**. A variety

of different sensors **14** can be utilized, including but not limited to, an accelerometer based sensor, and pressure based sensors, voltage resistance sensor, a radio frequency sensor, and the like, as recited above.

As a non-limiting example, an accelerometer, well known to those skilled in the art, detects acceleration and thus user activity. The accelerometer provides a voltage output that is proportional to the detected acceleration. Accordingly, the accelerometer senses vibration. This voltage output provides an acceleration spectrum over time; and information about loft time can be ascertained by performing calculations on that spectrum. A microprocessor subsystem, such as disclosed in U.S. Pat. No. 8,352,211, incorporated herein by reference, stores the spectrum into memory and processes the spectrum information to determine activity. Other examples of suitable accelerometer sensors are disclosed in EP 2428774 A1, incorporated herein by reference. Suitable pressure sensors are disclosed in EP 1883798 B1, incorporated herein by reference. A suitable voltage resistance sensor is disclosed in EP 1883798 B1, incorporated herein by reference. A suitable radio frequency sensor is disclosed in EP 2052352 B1, incorporated herein by reference.

Referring to FIG. 2, in various embodiments, the wearable device **10** includes a power source **24**, such a battery that can be rechargeable. The battery **24** can be put into a sleep state when not actively used in order to preserve power. A wake up feature allows the battery **24** and other electronics of the wearable device **10** to “sleep” during non-use or and is initiated into the “wake up” mode by certain predestinated events.

In one embodiment, as illustrated in FIG. 3, a telemetry system server **16** is coupled to a database **18**. Each wearable device **10** is assigned its own unique identification, ID.

The data transmitted by the wearable device **10** sensors **14** and its ID may be coded by appending a seed to digital data bits. As illustrated in FIG. 3 central processor unit **20** (CPU) validates or rejects received upon detection of the seed string appended to the digital data bits. In the alternative, the digital data bits may be coded and decoded by applying a scrambling algorithm utilizing the seed. A programming device **22** may be configured to transmit data to a sensor **14** utilizing a variety of alternative transmission means, including, for example, RF, IR, optical, and the like, or a magnetic loop/induction system.

In one embodiment, sensors **14** are configured to be shipped to users in a non-programmable mode with all programming already performed at the factory. A random seed may be communicated to the programming device **22** can a variety of different mechanisms, including but not limited to, via scanning a bar code, manual input, magnetic strip, random number generation, and the like.

Referring again to FIG. 2, in one embodiment, the wearable device **10** includes a control unit **26** that puts the wearable device **10** in a low power state. A monitoring system **28** can be included that remains active. The monitoring system **28** wakes up the electronics **30** in the wearable device **10** from a low power state. The control unit **26** can be notified of awaking of the other components by the monitoring system **28**. The control unit **26** can set a status bit on the monitoring system **28** only when the battery **24** needs to be in a full power state. The control unit **26** then forces a power cycle.

Referring to FIG. 3, one embodiment of a telemetry system **32** is illustrated. The telemetry system **32** is in the communication with the sensors **14** and ID of the wearable device **10** and can include one or more receivers **34**, a central server **36** with the CPU **20**. The telemetry system **32** can

optionally include a display **42** and an alarm **44**. The telemetry system **32** receives information from sensors **14** of a user's habits, activities, and the like, and then processes this information. Wearable device **10** with its unique ID and sensors **14** is assigned to a specific user in order to track and/or monitor that user. For illustrative purposes assume that three users A, B AND C are being tracked and monitored by the telemetry system **32**. It should, however, be appreciated that the telemetry system **32** may be implemented to track and/or monitor a much larger number of users.

In one embodiment of the present invention, radio frequency (RF) devices that are sensors **14** and/or chips may serve as the identifying devices. Each source, sensor **14**, ID and the like can carry a fixed radio frequency chip encoded with identifying data which may be correlated to the individual participants, parts or objects.

Telemetry system **32** of the present invention may include a Real-Time Location System (RTLS) **46** and Real-Time Sensing System (RTSS) **48** with RF technology. The RF technology may include active and/or passive RFID sensors **14** and an RF wireless array system as a receiver **34**. The RF technology in the RTLS **46** and RTSS **48** may include UWB technology (e.g., IEEE 802.15), WLAN technology (e.g., IEEE 802.11), SAW RFID positioning system technology, GPS technology, and the like.

The sensors **14** may communicate directly with each other and/or relay telemetry data directly to base receiving RF device(s) or base receivers **34**. The base receivers **34** may forward the telemetry data to a base computer either through a direct link or through a network. Alternatively the telemetry data may be forwarded to end user devices, including but not limited to, laptops, mobile devices and the like, either directly or through a network. The comprehensive telemetry system **32** using RF technologies such as UWB, ZigBee, Wi-Fi, GPS data system can be utilized as described above.

The readers/antennae may be interconnected using a LAN, such as Ethernet to provide a network communication infrastructure for the computers and servers. Active and passive RFID sensors **14** may be employed. The active sensors **14** (RFID) may have a two-way communication function, which allows the base computer system to dynamically manage the sensors **14**; vary update rates; send self-identification and telemetry data.

The active sensors **14** may employ dual-radio architecture. In one embodiment, active sensors **14** transmit radio pulses, which are used to determine precise two-dimensional or three-dimensional location and a conventional bi-directional radio, which is used as a control and telemetry channel with a sensor update rate.

The wearable device **10** gathers telemetry data, communicates that data to a base station, BLUETOOTH® enabled device, or smart phone and the like. From the base station, the wearable device **10** can receive firmware updates or via a BLUETOOTH® enabled device. The wearable device **10** can receive updates wirelessly. The base station can receive firmware updates from Network Systems, take telemetry data from the wearable device **10** and transfer it to Network Systems. Telemetry data received from the base station is analyzed by servers and presented to an end user. Any third party device can receive data from the wearable device **10** wirelessly and deliver information to the servers for processing.

In one embodiment, the wearable device **10** uses an accelerometer, gyroscope, GPS sensor, a BLUETOOTH® chip, and a heart rate monitor.

As a non-limiting example, for heart monitoring, the accelerometer, sensor **14**, determines when to sample the sensors **14** and to improve the accuracy of the heart rate monitor. The gyroscope detects movement and orientation and the GPS sensor is used to determine location of the user. A BLUETOOTH® chip allows the device to connect wirelessly to other third party devices.

As a non-limiting example, a heart rate monitor **14** detects the user's heart rate in order to accurately determine the user's activity level, behavioral patterns and the like.

An Artificial Intelligence (AI) or Machine Learning-grade algorithms is used to identify the user's activities, behaviors, behaviors and perform analysis. Examples of AI algorithms include Classifiers, Expert systems, case based reasoning, Bayesian networks, and Behavior based AI, Neural networks, Fuzzy systems, Evolutionary computation, and hybrid intelligent systems. A brief description of these algorithms is provided in Wikipedia and stated below.

Classifiers are functions that can be tuned according to examples. A wide range of classifiers are available, each with its strengths and weaknesses. The most widely used classifiers are neural networks, support vector machines, k-nearest neighbor algorithms, Gaussian mixture models, naive Bayes classifiers, and decision trees. Expert systems apply reasoning capabilities to reach a conclusion. An expert system can process large amounts of known information and provide conclusions based on them.

A case-based reasoning system stores a set of problems and answers in an organized data structure called cases. A case based reasoning system upon being presented with a problem finds a case in its knowledge base that is most closely related to the new problem and presents its solutions as an output with suitable modifications. A behavior based AI is a modular method of building AI systems by hand. Neural networks are trainable systems with very strong pattern recognition capabilities.

Fuzzy systems provide techniques for reasoning under uncertainty and have been widely used in modern industrial and consumer product control systems. An Evolutionary Computation applies biologically inspired concepts such as populations, mutation and survival of the fittest to generate increasingly better solutions to the problem. These methods most notably divide into evolutionary algorithms (e.g., genetic algorithms) and swarm intelligence (e.g., ant algorithms). Hybrid intelligent systems are any combinations of the above. It is understood that any other algorithm, AI or otherwise, may also be used. Examples of suitable algorithms that can be used with the embodiments of the present invention are disclosed in, EP 1371004 A4, EP 1367534 A2, US 20120226639 and US 20120225719, all incorporated fully herein by reference.

In various embodiments, the wearable device **10** has additional features. In one embodiment, the wearable device **10** changes color, via infrared LEDs, to accurately match the wearer's skin tone. This creates a seamless and more personal integration of technology into the user's daily life. In this embodiment, there is skin contact with the wearable device **10**.

In another embodiment, the wearable device **10** remotely reminds and can be used to administer medications. As a non-limiting example, the wearable device **10** can inject adrenalin. In one embodiment, the wearable device **10** has sleep pattern recognition based on movement and heart rate.

In various embodiments, the wearable device **10** uses algorithms to determine activity type, behavioral patterns and user habits based on collected data.

In one embodiment, the wearable device **10** uses the accelerometer information to improve the heart rate monitor. As a non-limiting example, the wearable device **10** detects movement and speed. Addition of this data improves the accuracy of the heart rate monitor and corrects for any miscalculations in vibration, noise and skin color.

In one embodiment, velocity readouts and accelerometer data are used to measure when to sample heart rate. For example, if the wearable device **10** registers zero velocity readout, the user is probably at rest or engaged in a passive activity. Thus, the wearable device **10** knows not to sample heart rate. This results in conservation of time, energy and data storage.

User activity, performance and action can be based on the acceleration and angular velocity of the wearable device **10**. In one embodiment, the wearable device **10** has a feature where the wearable device **10** authorizes third party interaction based on hand gesture, on previous interactions or patterns of behavior. As a non-limiting example, if one purchases a coke every day for the last two weeks, the wearable device **10** can "orders" the person another one based on the prior history.

In one embodiment, the wearable device **10** features near-by wearable device **10** recognition that provides for other wearable device **10** devices to be recognized within a particular vicinity and are able to share and transfer data between them. The wearable device **10**'s data analysis and feedback can be based on current or previous sensor output. The wearable device **10** can alert the user when to charge the wearable device **10** and when it is the most convenient for the user.

In one embodiment, the wearable device **10** provides feedback via color change. An outer shell of the wearable device **10** can use visual feedback, including but not limited to pigment or color changes to indicate changes in user behavior or to prompt changes in user behavior. In one embodiment, the wearable device **10** is flexible in shape. As a non-limiting example, if the user puts the wearable device **10** over their hand it can expand or contract, morphing to change size and shape.

In one embodiment, the wearable device **10** can have a sync feature for multiple bands at the same time.

In one embodiment, the wearable device **10** has data transfer to an external device that can be included or not included in system **32**. Wearable device **10** could be a data leaching device. For example, the user can relay information to someone else's device (intermediary device) to access Network Systems connected device.

In one embodiment, the wearable device **10** can disable the recording of one or more sensors **14** based on location, acceleration (or lack thereof) and the like.

In one embodiment, the wearable device **10** detects different types of transportation and activity based on sensor data. In one embodiment, wearable device **10** can unlock doors or cars. The user can turn it on and off. As a non-limiting example, it can be turned off by having a capacitor switch on top and bottom and is placed in a way that one couldn't accidentally turn it off. As a non-limiting example, turning it off can be done by rotating the wearable device **10** once.

In one embodiment, the wearable device **10** recognizes the wearer based on biometric information, previous data, movement pattern, and the like. In one embodiment, the wearable device **10** detects a new user based on an inability to match to user/usage patterns.

As non-limiting examples, a variety of different sensors **14** can be used such as, an altimeter, blood oxygen recog-

niton, heart rate from wrist via sonar, Doppler, based on sound wave and movement, based on pressure, and the like. A pressure sensor **14** can be placed on a circulatory vessel such as a vein to detect pulse.

With the wearable device **10** of the present invention, mechanical actions of the user can be triggered, recognized and evaluated.

As a non-limiting example, with multiple users and wearable devices **10**, a separate wearable device **10** ID is assigned to each of the users A, B AND C, and thereafter the assigned transmitter/monitor **14** generates user activity data and/or user tracking data. For purposes of this disclosure, monitoring data is defined to include data acquired during the process of monitoring or evaluating a predefined characteristic. The user activity data tracks data from the sensors **14** is transferred to the receivers **34** via the wireless connections **38** represented by a dashed line.

A network of receivers **34** transfers the user activity and/or tracking data to system server **16** via connection **50**. System server **16** includes a processor **52** configured to process the user data in a known manner. For example, the processor **52** may convert raw user data acquired by the sensors **14** into more conveniently readable data.

As a non-limiting example, the display **42** can be implemented to graphically convey user information from system server **16** in a conveniently readable manner. As a non-limiting example, the user may be a cardiac patient with user monitoring data graphically conveyed as a conventional ECG plot comprising a sequence of P-waves, a QRS complexes and a T-waves. As another example, user tracking data may be graphically conveyed as an icon superimposed onto a map to indicate the user's relative location. Alarm **44** may be included in this embodiment.

In some embodiments, system **32** ID circuitry delivers a unique ID to the wearable device from database **18**. Bluetooth chips can be coupled with other wearable devices **10** in the area. This data is then stored, as more fully explained in the following paragraph. The unique ID can be utilized for a variety of different applications including but not limited to payments, social networking and the like.

The ID circuitry of system **32** can include a number of system/components: unique ID storage, communication system, which reads and transmits the unique ID from the unique ID storage, battery **24** or power system that provides power to enable communication with the wearable device **10**, a pathway system to route signals to through the circuitry, a cluster that crunches information, and a control system, to orchestrate the communication between different systems. All of these systems can be implemented in hardware, software or a combination thereof. Continuing with the telemetry system **32**, sensors **14** and sensing devices are disposed on wearable devices **10** worn by users. Data, such as movement, location, speed, acceleration, and the like, can be acquired, captured and provided to system **32**.

System **32** and an associated network can include an identification reference, including user activity, performance and reference information for each individual sensor **14** and location.

The user activity, performance metrics, data and the like captured by system **32** can be recorded into standard relational databases SQL server, and/or other formats and can be exported in real-time.

In various embodiments, the wearable device **10** and/or system **32** are fully sealed and have inductively charges. All communication is done wirelessly.

In one embodiment, there are no electrical contacts, physical contacts or connections with the wearable device

10. The wearable device **10** is seamless. The telemetry system **32** can include a microprocessor with CPU **20**, memory, interface electronics and conditioning electronics **33** configured to receive a signal from the sensors **14**. In one embodiment, all or a portion of the conditioning electronics **33** are at the wearable device **10**.

In one embodiment, the CPU **20** includes a processor **52**, which can be a microprocessor, read only memory used to store instructions that the processor may fetch in executing its program, a random access memory (RAM) used by the processor **52** to store information and a master dock. The microprocessor is controlled by the master clock that provides a master timing signal used to sequence the microprocessor **52** through its internal states in its execution of each processed instruction. In one embodiment, the microprocessor **52**, and especially the CPU **20**, is a low power device, such as CMOS, as is the necessary logic used to implement the processor design. The telemetry system **32** can store information about the user's activity in memory.

This memory may be external to the CPU **20** but can reside in the RAM. The memory may be nonvolatile such as battery backed RAM or electrically erasable programmable read only memory (EEPROM). Signals from the sensors **14** can be in communication with conditioning electronics **33** that with a filter **35**, with scale and can determine the presence of certain conditions. This conditioning essentially cleans the signal up for processing by CPU **20** and in some cases preprocesses the information. These signals are then passed to interface electronics, which converts the analog voltage or currents to binary ones and zeroes understood by the CPU **20**. The telemetry system **32** can also provide for intelligence in the signal processing, such as achieved by the CPU **20** in evaluating historical data.

In one embodiment, the actions of the user wearing the wearable device **10** with the unique ID can be used for different activities and can have different classifications at system **32**.

The classification can be in response to the user's location, where the user spends it time, with which the user spends its time, determination of working relationships, family relationships, social relationships, and the like. These last few determinations can be based on the time of day, the types of interactions, comparisons of the amount of time with others, the time of day, a frequency of contact with others, the type of contact with others, the location and type of place where the user is at, and the like. These results are stored in database **18**.

In one embodiment, the user wearing the wearable device **10** can access this information from any place where data is presented to the user, including but not limited to mobile devices, the WEB, applications program identifiers, and the like.

As a non-limiting example, the wearable device **10** communicates with a base station at system **32**. The wearable device **10** can intelligently switch between data transfer and charging based on sensor readout. The wearable device **10** can represent data based on connected devices.

In one embodiment, the wearable device **10** has the capability of providing recommendations, popularity of locations or activities based on acquired data from the user.

In one embodiment, the wearable device **10** has the capability of introducing the user to other people or users based on their data and the user's data.

In one embodiment, the wearable device **10** can determine emotion of the user.

In one embodiment, the wearable device **10** uses incremental data transfer via BLUETOOTH® and the like. The

wearable device **10** can transmit data through the inductive coupling for wireless charging. The user is also able to change the frequency of data transmission.

The wearable device **10** can engage in intelligent switching between incremental and full syncing of data based on available communication routes. As a non-limiting example, this can be via cellular networks, WiFi, BLUETOOTH® and the like. In one embodiment, the wearable device **10** has data storage. As a non-limiting example, storage of telemetry data on wearable device **10** can be amounts up to about 16 mg.

In one embodiment, data transferred if it's in a selected proximity of a base station of system **32** or in proximity of an associated connected network. In one embodiment, the wearable device **10** has a dynamic change of data capture frequency. The wearable device **10** can be programmed to instantly change how often it samples any sensor **14** based upon the sensor data. Intelligent data sampling is based on sensor readout.

The wearable device **10** can receive firmware updates via a base station **110** of system **32**. In one embodiment, the wearable device **10** presents analyzed data and feedback on a website. In one embodiment, the wearable device **10**'s software is based on unique human movement. The wearable device **10** is able to identify its wearer based on the unique patterns of movement, location check-ins and daily habits of the user.

In one embodiment, the app can be used on a mobile device, including but not limited to a smart phone and the like.

In one embodiment, a breakdown of recounting data that has been collecting is presented for analysis of that data. Observation or recommendations can be presented based on historical information and live information. The importance of the data can be based on past user behavior.

In one embodiment, the wearable device **10** has artificial intelligence. A wearable device processor **54** implements logic resources that exist on wearable device **10**.

In one embodiment, wearable device **10** engages in the routing of user information to third parties based on predefined rules, based on system **32** analysis.

In one embodiment, wearable device **10** includes one or more processors **54** that implement intelligent algorithmic processing and transfer of information to third parties. Feedback can be provided to the end user that is based on visual, tactile, gesture information and the like.

The ID can be sent from the wearable device **10** in a variety of different transmit modes, which may be provided as part of the firmware or software of an ID or sensor transmitter **14**, and which may be utilized selectively during the operation of said sensor transmitter **14**, may include "burst" transmit modes, wherein a burst of data information is transmitted, or "parcel" transmit modes, wherein timed data packets of data, which may, as desired, comprise partial data strings, are transmitted, and, if desired, repeated during time intervals. Further, the sensors **14** may have programmed therein diagnostic routines or other test modes which assist during manufacture and use, providing the operator with operational status and verification information on said sensor/transmitter **14**, as needed. Referring to FIG. **4**, system **32** includes data base **18** which contains the desired transmitter, sensor, **14** personality data, as well as, the address/device ID bits for each wearable device **10**.

In one embodiment, the initial programming of the wearable device **10** for the ID, as well as optionally other personal information of the user, is done securely, as unau-

thorized future alteration of same thereafter can be utilized as a means of violating system integrity.

In one embodiment, an inductive field coil is used for programming the sensors **14** and ID of wearable device **10**.

As illustrated in FIG. 4, the wearable device **10** can include a sensor **14** with an output that be received by an amplifier **56** and decoded by an I/O decoder **58** to determine I/O logic levels, as well as, both clock and data information **60**. Many such methods are commonly available including ratio encoding, Manchester encoding, Non-Return to Zero (NRZ) encoding, or the like; alternatively, a UART type approach can be used. Once so converted, clock and data signals containing the information bits are passed to a memory **62**. Any of these connections provides a logical link from the system's database **18** to the sensor **14**, ID of the wearable device **10**, as shown in FIG. 5.

In one embodiment, illustrated in FIG. 5, the system **32** chooses the necessary programmable sensor functions and stores them into database **18**. In one embodiment, in order to insure that an unauthorized user cannot connect into and program wearable device **10** the following procedure may be used:

Both the sensor **14** and receiver **34** contain an identical, repeatable pseudo randomization algorithm in ROM or in ASIC logic.

Referring to FIG. 6, the algorithm is applied to outgoing programming data **64** from system **32** and produces a number of security/randomization bits **66** that can be appended to the outgoing programming message or message **68** and sent to a sensor **14**.

Referring to FIG. 7 the sensor **14** likewise applies this pseudo randomization algorithm as the security/randomization bits **66** to the outgoing programming data, now forming the incoming programming data **70** to sensor **14** and produces a several bit result in the shift register **71**. The scrambling algorithm is devised such that a small difference in the programming bit stream causes a great difference in the pseudo randomization result. As a non-limiting example, the present invention can use a 16 bit polynomial to produce this pseudo randomization.

Optionally, in one embodiment, before a sensor **14** accepts this programming, stored in an address and personality register **73**, both the pseudo random code, stored in data in a shift register **75** from system **32** and a sensor **14**, in a shift register **71** must match via a comparator ID, **77**, indicating unauthorized acceptance use. In addition to insuring authorized access, this process also insures that the data itself is correct. The longer the polynomial sequence used, the greater the security.

In one embodiment, spread spectrum or other RF transmission is used and can include programming to determine that the frequency or spread spectrum code is unique to the area. If a spread spectrum code, system code, or frequency channel is found to be occupied at a future time of use. Re-programming of the wearable device **10** is then done with a new, unused spread spectrum code or system code or frequency channel can be selected, or, in the alternative, CPU **20**.

As illustrated in FIG. 5, step "E" would include, for example, the step of the sensor **14**, inputting the programming message and saving a seed in memory **62**; with the sensor **14** utilizing the seed to code digital data bits transmitted.

As illustrated in FIG. 8, the location of a wearable device **10** with the ID and sensors **14** can be determined. As a non-limiting example, in one embodiment the wearable device **10** includes a sensor **14** that can provide a position

signal having positioning data (e.g., raw GPD data or pseudo ranges) and the ID is transmitted from the wearable device **10** to system server **16**. Server **16** receives the position signal and analyzes the signal to generate information representing the location of the wearable device **10**. Server **16** transmits this location information to a client computer where the location of the wearable device **10**, allowing a user to identify the location of the remote sensor **14**.

In one embodiment, the position signal transmitted by the remote sensor **14** can also include an emergency code. For example, in the event of an emergency, such as a medical emergency or otherwise, a user may press a "panic button" that can be on the wearable device **10** or by use of a user's mobile device. Pressing the panic button may cause mobile device **74** to transmit an emergency signal to a cell site **76** where the emergency signal is relayed to server **16**. In response, server **16** can transmit Doppler information regarding in-view satellites, a fix command and a time trigger signal to the wearable device **10**.

When the location of the wearable device **10** has been determined, software running on server **16** configures server **16** such that a call or other signal is sent to a local emergency operator in the vicinity of remote sensor **14**. When the call or signal is received at the emergency operator station, the location of remote sensor **14** is transmitted and displayed. In some cases, where separate panic buttons are available for identifying medical, police, fire or other types of emergencies, the nature of the emergency is also displayed for the emergency operator. Based on this information, the emergency operator can initiate an emergency response by providing the location of remote sensor **14** to the required emergency service (police, fire department, ambulance service, etc.). In other embodiments, instead of or in addition to a position report for the remote sensor **14**, the emergency operator may also be provided with information which identifies an emergency response vehicle in close proximity to remote sensor **14**.

As illustrated in FIG. 9, a sensor **14** of the wearable device **10** can include a SNAPSHOT GPS receiver **72**. As described above, sensor **14** uses information transmitted from separately located base station **110**, mobile devices, computers, and other devices, to assist in determining the position of the remote sensor **14**, as more fully disclosed in U.S. Pat. No. 6,661,372, incorporated herein by reference.

As non-limiting examples, and as illustrated in FIG. 10, the sensors **14** can be a thermal transducer **78**, an acoustic transducer **80**, and a magnetic transducer **82**. It will be appreciated that the present invention is not limited The transducers **78**, **80**, and **82** in the wearable device **10** can communicate with a microprocessor **84** also located in the wearable device **10**. The wearable device **10** can communicate with other devices via an RF transceiver **86**, an IRDA transceiver **88**, and/or an RF backscatter transceiver **90**. Each of the components in the wearable device **10** receives power as necessary from the battery **24**, which may include the rechargeable battery.

The acoustic transducer **80** may include a microphone, a low-pass filter, a gain amplifier, and a threshold comparator. The acoustic transducer **80** may include an omnidirectional microphone, although any other suitable acoustic transducer device would suffice. The microphone may be a surface mount MEMS device that has a frequency range of 100 Hz to 10 kHz. A single MCP602 operational amplifier is used on the acoustic sensor to amplify and low-pass filter the acoustic signal from the microphone. Another operational amplifier is used to generate a voltage reference used for single biasing and detection. The microphone output is biased to

the midway point between the circuit supply voltage and ground to allow for both positive and negative signal swings. The biased signal is filtered with a second order low-pass Butterworth filter to remove upper frequency noise. It is then amplified with an adjustable gain that is controlled by a digital resistor potentiometer. This digital resistor operates on an I2C bus and is controlled by the microprocessor **84**. Lastly, the amplified acoustic signal is threshold detected against a static voltage to detect sufficiently large acoustic signals. The digital output of the threshold detector is connected to the microprocessor **84** for processing.

The magnetic transducer **82** can include a magnetic sensor integrated circuit, a differential instrumentation amplifier, a low-pass filter, two gain amplifiers, and a threshold detector. The magnetic transducer **82** may include an NVE AA002-02 GMR (giant magneto resistive) field sensor, although any suitable magnetic sensor would suffice. This sensor has a saturation field of 15 Oe, a linear range of 0 to 10.5 Oe, and a sensitivity of 3 mV/V/Oe. Two MCP602 CMOS operational amplifiers are used on the magnetic sensor to amplify and low-pass filter the analog output signal. An INA122UA instrumentation amplifier is used as a difference amplifier for the differential output from the magnetic sensor. The magnetic sensor IC can be based on Spintronics technology. Its output includes a differential voltage pair proportional to the detected magnetic field. The differential voltage pair is amplified and converted to a single voltage by the instrumentation amplifier. The AC-coupled signal is then amplified and filtered with a low-pass filter to remove upper frequency noise and boost the low-voltage signal output. The signal is amplified a second time by an adjustable gain controlled by a digital resistor similar to the acoustic sensor. Lastly, the amplified magnetic signal is threshold detected against a static voltage, to detect sufficiently large changes in magnetic fields. The digital output of the threshold detector can be connected to the microprocessor **84** for processing.

A DS1803E-010 digitally controlled 10 kOhm variable resistor can be used in both the acoustic and magnetic sensor circuits. It is used to adjust the gain of one gain stage in each circuit. The digital resistor is controlled through an I2C interface. A LMV393IPWR comparator is also used in both the magnetic and acoustic sensor circuits for determining when a sufficiently strong sensor signal has been detected. It compares the analog sensor signal against the voltage reference and its output is tied to the microprocessor **84** for data collection.

The thermal transducer **78** may include a Burr Brown TMP 100NA/250 12-bit digital temperature sensor, although any suitable thermal sensor would suffice. The digital temperature sensor has an operating range of -55 to +120.degree. C., an accuracy of 0.5.degree. C. and a maximum resolution of 0.0625.degree. C.

Even though it is a 12-bit sensor, suitable results are achieved with only 9-bit conversions with only the 8 most significant bits used. The sensor has an I2C interface and is normally kept in sleep mode for low power operation. When directed by the microprocessor **84**, the thermal transducer can perform a 9-bit temperature conversion in 75 milliseconds.

The RF transceiver **86** may include an RF Monolithic DR3000 transceiver, although any suitable transceiver or separate transmitter and receiver **34** would suffice. This transceiver **86** allows for both digital transmission and reception. The transceiver **86** can have an operating frequency of 916.5 MHz and is capable of baud rates between 2.4 kbps and 19.2 kbps. It can use OOK modulation and has

an output power of 0.75 mW. It also can use digital inputs and outputs for direct connection with the microprocessor **84**. The transceiver **86** can use an antenna **92** (FIG. 11) that may include a 17 mil thick plain steel electric guitar G-string cut to a length of 8.18 cm. It is used in a monopole over ground configuration and can require a matching circuit of one inductor and one capacitor. Alternatively, Frequency Shift Keying (FSK), Quadrature Phase Shift Keying (QPSK), or any other suitable modulation scheme may be utilized.

The IRDA transceiver **88** may include a Sharp GP2W0110YPS infrared transceiver, although any suitable IRDA compliant infrared transceiver would suffice. This transceiver **88** can be IRDA v1.2 compliant and in one embodiment has an operating range of 0.7 meters. In one embodiment, it is capable of 115.2 kbps data speeds.

The RF backscatter transmission device **90** may include circuitry available from Alien Technology (of Morgan Hill, Calif.) for receiving and transmitting signals via RF backscatter. Battery **24** may be a 3.6 volt 1/2 AA lithium battery with a capacity of 1.2 amp hours. The battery **24** can be a power source **24** that can include a Texas Instruments TPS76930 DBVT voltage regulator to regulate the output signal to 3 volts and with a maximum current of 100 mA. The voltage regulator can include a LDO.

The RF backscatter transceiver **86** in the wearable device **10** communicates with an RF backscatter reader **94** such as a class 3 reader from Alien Technology. The reader **94** transmits data to the backscatter transceiver **90** of the wearable device **10** by broadcasting encoded RF pulses and receives data back from the transceiver **86** by continually broadcasting RF energy to the sensor **10** and monitoring the modulated RF reflections from the sensor **10**.

The RF backscatter transceiver **90** can include a printed circuit board (PCB) patch antenna for RF reception, and RF modulation, a Schotky diode detector circuit, a comparator circuit for signal decoding, and a logic circuit for wake-up. The logic circuit monitors the incoming data, and when an appropriate wake-up pattern is detected, it triggers the microprocessor **84** so that data reception can begin. In one embodiment, the reader **94** has an operating frequency between 2402 MHz and 2480 MHz, and uses frequency hopping in this band to reduce noise interference. A modulation method used by the reader **94** can be On-Off Keying (OOK). In one embodiment, the transmission power is 1 watt. The operation of the reader **94** may be controlled by an external computer (not shown) as directed by Labview software via a RS-232 serial link.

The RF transceiver **86** can communicate with an external RF transceiver **96** such as a DR3000 transceiver from Radio Monolithics, Inc. In one embodiment, it operates at 916.5 MHz, uses OOK modulation, has a communication range of 100 meters line of sight, and a baud rate of 19.2 kbps. The active RF antenna **92** can be a quarter-wavelength monopole made from a guitar G-string and appropriate matching circuitry. Two control lines from the microprocessor **84** can be used to select the mode of operation, choosing from transmit, receive, and sleep. The active RF receiver **34** consumes the most power in receive mode compared to the other two communication links.

FIG. 6 shows the relative positioning and shape of the active RF antenna **92** and the RF backscatter antenna **98**.

The IRDA transceiver **88** of the wearable device **10** can communicate with an external IRDA transceiver **100** that may be identical to the IRDA transceiver **88**. Alternatively, the IRDA transceiver **100** can be one such as is provided in most personal digital assistants (PDA) as well as many other

consumer devices. The IRDA communication link follows the standard IRDA signal and coding protocol and is modeled after a standard UART interface. In one embodiment, the IRDA transceiver **88** is capable of data speeds less than 115.2 kbps, and may only have a range of 0.7 meters for transmission. One advantage of the IRDA communication link is that it does not require any of the RF spectrums for operation, but it typically does require line-of-sight communication.

When any one of the transceivers **86**, **88** and **90** on the wearable device **10** detect the beginning of valid data on their respective communication link, all other transceivers are disabled, thereby preventing the corruption of incoming data with the noise or partial data packets on the other communication links. However, if the data on the active transceiver proves to be erroneous, the other transceivers will be re-enabled if appropriate to allow normal operation to continue. If the data received by the active transceiver is valid, however, the other transceivers will remain disabled for several hundred milliseconds longer in the high probability that the next data packet will be transmitted on the same communication link. If, after this extended delay, no additional packets are received, then the other transceivers will be re-enabled as appropriate.

In one embodiment, the active RF protocol has no wake-up or synchronization packets, and the packets sent to and from the sensor are identical. In one embodiment, the format of an active RF packet is shown in FIG. 2. It can include a preamble to reset and spin-up the state machine of the RF receiver **34** and to properly bias the receiver's **34** data slicer/threshold detector for optimum noise rejection and signal regeneration, two framing bits to indicate the beginning and end of the data bytes, and the data bytes themselves.

Furthermore, the encoding scheme for the three symbols is shown in FIG. 12. The entire packet is DC balanced to maintain an optimal level on the data slicer/threshold detector and the receiver **34**. Data is sent most significant bit first.

The IRDA communication link can follow the standard IRDA protocol for bit encoding and UART protocol for byte transmission. Packets transmitted on the IRDA link can contain no preamble or framing bits, but they do have a header that contains two bytes. The first byte is an ASCII "T" which denotes the beginning of a valid IRDA packet. The second byte equals the number of preceding bytes in the packet. This value is used by the receiver **34** to determine when the entire packet has been received and processing of information can begin. The packet structure is shown in FIG. 13 and the IRDA/UART encoding scheme is shown in FIG. 14.

The data bytes contained in a packet transmitted to the sensor **10** through any of the communication links conform to a packet format. The CMD section of a packet is a single byte that identifies the type of packet being sent. The CMD byte appears above the beginning and end of the packet and the two must be identical. The reason for including the redundant byte is to further eliminate the chance of a packet's CMD identifier being corrupted at the receiver **34**, even if the CHECKSUM is correct.

The PAYLOAD contains all of the data that must be sent to, or returned from, the sensor. The PAYLOAD is broken down into individual bytes with the overall number of bytes and their content dependent on the type of packet being sent.

The CHECKSUM is a 16-bit CRC that is performed on all bytes in the data packet excluding the end CMD byte in packets generated by the external device. The CHECKSUM is sent most significant byte first.

The transceivers **86**, **88** and **90** may be required to communicate over a greater distance than do the components described herein. Upgrading these components to be suitable for longer distance transmission is considered to be within the spirit of this invention. The type of transducer is not limited to the specific transducer types described herein. In addition, the logic described herein for arbitrating between which communication device to use to communicate with the outside world and which sensor data to provide at what time is but one possible approach to arbitration logic within such a remote sensor **10**.

FIG. 15 illustrates one embodiment of an exemplary network **101** that can be used with the present invention. As shown in FIG. 15 a wireless packet data service network **102** that can be utilized with the wearable device **10**. An enterprise network **104**, which may be a packet-switched network, can include one or more geographic sites and be organized as a local area network (LAN), wide area network (WAN) or metropolitan area network (MAN), and the like. One or more application servers **106-1** through **106-N** can be included and disposed as part of the enterprise network **104** are operable to provide or effectuate a host of internal and external services such as email, video mail, Network Systems access, corporate data access, messaging, calendaring and scheduling, information management, and the like using the unique IDs of the wearable devices **10**. The wearable device **10** can be in communication with a variety of personal information devices other than the wearable device **10**, including but not limited to, computers, laptop computers, mobile devices, and the like.

Additionally, system server **16** may be interfaced with the enterprise network **104** to access or effectuate any of the services from a remote location using a wearable device **10**. A secure communication link with end-to-end encryption may be established that is mediated through an external IP network, i.e., a public packet-switched network such as Network Systems **108**, as well as the wireless packet data service network **102** operable with a wearable device **10** via suitable wireless network infrastructure that includes a base station (BS) **110**. In one embodiment, a trusted relay network **112** may be disposed between Network Systems **108** and the infrastructure of wireless packet data service network **102**.

In another embodiment, the infrastructure of the trusted relay network **112** may be integrated with the wireless packet data service network **102**, and the functionality of the relay infrastructure can be consolidated as a separate layer within a "one-network" environment. Additionally, as non-limiting examples, wearable device **10** may be capable of receiving and sending messages, web browsing, interfacing with corporate application servers, and the like, regardless of the relationship between the networks **102** and **112**. Accordingly, a "network node" may include both relay functionality and wireless network infrastructure functionality in some exemplary implementations.

In one embodiment, the wireless packet data service network **102** is implemented in any known or heretofore unknown communications technologies and network protocols, as long as a packet-switched data service is available therein for transmitting packetized information. For instance, the wireless packet data service network **102** may be comprised of a General Packet Radio Service (GPRS) network that provides a packet radio access for mobile devices using the cellular infrastructure of a Global System for Mobile Communications (GSM)-based carrier network. In other implementations, the wireless packet data service network **102** may comprise an Enhanced Data Rates for

GSM Evolution (EDGE) network, an Integrated Digital Enhanced Network (IDEN), a Code Division Multiple Access (CDMA) network, a Universal Mobile Telecommunications System (UMTS) network, or any 3rd Generation (3G) network.

Referring now to FIGS. 16(a) through 16(d), in one embodiment, the wearable device 10 is in communication with an interaction engine 120 that can be at a mobile device 74 or system 32. The interface engine can be a software application running on mobile device 74 associated with another party, including but not limited to a merchant, an associate, a friend, and the like. The enables the wearable device 10 user and a merchant to interact with a transaction engine 114 to and enter into a financial transaction for the transfer of funds from a third party payment system 116 that is independent of the wearable device 10 user's financial account 118, and complete a transaction. It should be noted that the payment system 116 can be affiliated with the financial account 118 or can be a separate and non-affiliated with the financial account 118. The interaction engine 120 can take input of information related to a transfer of funds from the wearable device 10 users' financial accounts 118 as input to the transaction engine 114 to initiate and complete a financial transaction, including but not limited the purchase and payment of goods and services. In one embodiment, this input to the interaction engine 114 can include, an amount of a transaction, additional items related to the transaction, authorization and/or signature of the wearable device 10 user.

In one embodiment, the mobile device 74 receives information from the wearable device 10, e.g., the unique ID.

The interaction engine 120 can also present products or services provided by a merchant to directly to or through system 32 to the wearable device 10 user. In one embodiment, the wearable device 10 users can use the mobile device 74, the WEB, and the like, to view, text, pictures, audio, and videos, and browse through the products and services on the mobile device 74, personal computers, other communication devices, the WEB, and anything that is Bluetooth®, anything associated with Network Systems, and the like.

In one embodiment, the transaction engine 114, which can be at the mobile device 74, or external to the mobile device 74, including but not limited to wearable device 10 and the like, takes decoded financial transaction card information from a decoding engine 122, internal or external to the mobile device 74, and a transaction amount from an interaction engine 120, also internal or external to the mobile device. The transaction engine 114 then contacts the payment service 116, and or the wearable device 10 users' financial account 118, such as an acquiring bank that handles such authorization request, directly or through the payment system 116, which may then communicate with a financial transaction card issuing bank to either authorize or deny the transaction. The payment system 116 can include a user database, a transaction database, a product database, and the like. These databases can also be external to payment system 116. If the third party authorizes the transaction, then the transaction engine 114 transfers funds deducted from the account of the wearable device 10 user, or the payment system 116 can already have those funds readily available, to an account of a third party which can be another wearable device 10 user, a merchant, and the like, and provides transaction or transfer of fund results to the interaction engine 120 for presentation to a third party.

In one embodiment, the transaction engine 114 does not have the financial account or financial card information of

the wearable device 10 user that is doing the transfer. In some embodiments, the transaction engine 114 keeps only selected information of the wearable device 10 user's financial accounts 118 or financial transaction cards.

In one embodiment, the wearable device communicates directly, without mobile device 74, with the payment system 116 and/or the user's financial account 118 or associated financial institution.

In one embodiment, the transaction engine 114 communicates and interacts with the financial account 118 or associated financial institution directly or through the payment system 116, through a user database, product database, and transaction database, which databases can be separate from or included in the payment system 116, over a network. The network can be a communication network, as recited above, and can be based on well-known communication protocols, including but not limited to, a TCP/IP protocol.

With social networking applications, the wearable device 10, with its unique ID, is an ID device. Information from the wearable device 10 relating to social networking, and the like, communicates with system 32. In this manner, the wearable devices 10, with their own unique ID's, can be recognized. This can occur at different locations, close by, distanced, and notifications can be sent to the different users wearing a wearable device 10 for a variety of social networking and other communication applications. Additionally, wearable device 10, with its sensors 14 and ID can communicate directly to social networking sites, Network Systems, cloud services, and the like.

In one embodiment, with the current permissions given by the wearable device users, marketers, companies or individuals who wish can deliver advertisement wearable device 10 users. More particularly, system 32 can be configured to allow marketers, and the like, to deliver advertisements to consumers to buy products or services offered by the marketer. Advertisements can also be sent to wearable device 10 users with the appropriate permissions. In one embodiment, system 32 maintains the anonymity of the wearable device 10 users while allowing the marketers to have their advertisements delivered to those that fall within their defined market segment.

In one embodiment, the wearable device ID of a user provides a method of identifying and contacting users of a social networking service. The method may include the steps of signing up for a social networking service, displaying the wearable device ID, viewing another person's unique wearable device ID displayed by another user, and finding that user on a social networking service website by searching for the user using the wearable device ID viewed.

System 32 may serve a number of purposes without straying from the scope of the present invention. For example, the social networking service may allow wearable device 10 users to engage in non-romantic relationships, keep in touch with acquaintances, friends and family, professional business relationships, and romantic relationships, may allow communication between wearable device users on a message board or Network Systems forum, and may allow users to follow up on missed-connections that otherwise would not have been realized.

In one embodiment, the step of providing personal information to start an account with system 10 for different applications may be performed by a purchasing or acquiring a wearable device 10, with a unique assigned ID, and the user can fill in an online form. This form may require users to fill in fields on the form. These fields may include: first and last name, email address, a desired password, phone number, gender, birth date, address, geographic region,

education information, employment information, interests, relationship information and interests, family information, religious views, ethnicity, physical features including hair color, eye color, measurements, and the like, type of relationship being sought, living situation, answers to quiz questions, and a personal description about interesting personality traits, among other things. In addition, users may upload one or a plurality of photographs for other users to view, or for users to store the photo or photos on the server of system 32.

In another embodiment the step of providing personal information to start an account with system 32 by wearable device 10 users may be performed automatically. In this embodiment, system 32 can access a social networking service, access, via computer, contact lists or other sources of information that may include the type of information listed above.

In a further embodiment, the step of providing personal information to system 32 can be automated by importing data containing the personal information required from other social networking services including but not limited to Facebook®, LinkedIn®, MySpace®, Match.com®, EHarmony.com®, a user's email or contact list, v-card, and the like.

The unique wearable device ID may allow the user to be searched and identified by other users and potential users. Also, a computer generated email address may be provided to a user. In one embodiment, this email address may be the user's user ID followed by "@iseenya.com." In another embodiment, the email address may be the user's user ID directed to another domain name.

In one embodiment, a computer generated personal page may be provided to a wearable device 10 user. The personal page may utilize a computer to automatically import the information provided when signing up with system 32 or a social networking service. In another embodiment, the information and formatting of the personal page can be customizable.

When mobile device 74 is used, it communicates with one or more sensors 14 that are at the wearable device 10, as more fully herein. The mobile device can 74 pull from system 32 updates from the server 16, including but not limited to settings such as alarms, name of the wearable device wearer using the ID, a sensor 14 and the like. Sensors 14 at the wearable device 10 can send streams of information, both encrypted and non-encrypted to the mobile device and then to the server at system 32. Server 16 sends encrypted, and can also send non-encrypted information, to mobile device 74. Processing of this information can be achieved at the mobile device 74, and/or server 16. Mobile device 74 can receive raw sensor information from the wearable device 10. This information can be compressed as well as non-compressed. A compression algorithm, at the wearable device and/or mobile device 74 or system 32, can be used in order to minimize the amount of information that server 16 sends. System 32 can include additional encryption and/or decryption systems.

Referring now to FIG. 17, a social network circle/group 124 (hereinafter "SNET circle") comprising social devices 126, including wearable device 10, is shown. Beyond traditional social networking features and services, a SNET circle 124 and associated social devices 124 according to various embodiments of the invention include numerous novel features and attributes as described more fully below with general reference to the illustration. Wearable device 10

can utilize network 101 for communication with the SNET circle, as well as with other social networking sites, or through system 32.

Briefly, membership in the SNET circle 124 may comprise docked and undocked social devices 124 and human SNET circle members [104] 128, as well as proxies thereof. Further, SNET circle 124 nodes may include device services and software (e.g., applications) of various types participating as members. By way of example, SNET circle members might include artificial intelligence agents/social robots 130, SNET security device(s) 132, appliances, vehicles and service providers 134, common or authorized members/functionality of other SNET circles 124, and the like. Further, access to specific content and resources of a SNET circle 124 may be shared with members of additional SNET(s) 124, including remote or web-based applications. Such access can be conditioned on acceptable profiling and association data. Similarly, social devices or individuals may be granted temporary or ad hoc memberships, with or without restricted access.

In the illustrated embodiment, formation, maintenance and operation of SNET circle 124 is performed by stand-alone or distributed SNET processing circuitry and software 136. It is noted that the "SNET processing circuitry" may comprise hardware, software, applications, or various combinations thereof, and be configurable to support various functionalities disclosed herein. Further, the SNET processing circuitry 136 may be included in a standalone server, server farm, cloud-based resources, network 101, system 32 and/or the various types of devices described below, and incorporate authentication and security functionality 138. In addition, specialized middleware may also be utilized by SNETs according to the invention, including standardized middleware with an associated certification process. Interactions and interdependencies within the SNET circle 124 may involve one or more of a social device association/control module 140, a SNET circle member profiling module 142, and an adaptive resource allocation and arbitration module 144 as described more fully below.

Distribution of internal and external SNET content/media 146 can be accomplished in a variety of ways in accordance with various embodiments of the invention. For example, media distribution may involve an adaptive or parallel network routing infrastructure involving a wide variety of communication protocols and wired and/or wireless communications channels. SNET content/media 146 may comprise, for example, various user-driven (advertising) channels, pictures, videos, links, online text, etc. Access to such content, as well as communications with and remote access to social devices 124 of the SNET circle 124, may occur over an Network Systems backbone 148, cellular communication system, WAN, LAN, and the like.

FIG. 18 illustrates an embodiment of a social group 150 comprising a variety of members in accordance with the present invention that can communicate through their wearable devices 10 and other devices, including but not limited to mobile devices 74. In this embodiment, membership in the social group 150 may include a variety of novel social system members [204] 152 functioning in various capacities within the social group 150. As will be understood, certain of the social system members 152 may support direct or indirect associations between the social group 150 and human members/non-members and users 154.

In the illustrated embodiment, social system members (or nodes) 152 include one or more local or remote servers and server clusters that provide a support infrastructure for social group functionality and member operations (routing, data

storage, services, etc.). Communications within the social group and with non-members may occur via dedicated or multi-function communication path devices.

Social system members **152** further include devices configured to operate as nodes within the social group **150**. Social functionality in such devices and other social system members **152** can be implemented through various means. For example, a device may have integral hardware/firmware/software to support social group access and member operations. Alternatively, a general purpose device **152a** may include social code that enables participation in the social group **150**. In a further embodiment, a device **152b** designed to include social functionality may participate in the social group **150** through a combination of non-social code and a social shim layer or driver wrapper. In yet another embodiment, a member device **152c** having a social design may utilize additional social code, including code specific to a social group **150**.

Participation in the social group **150** is supported through functionality that includes automated and member-triggered membership invitations and processing (membership management) **156**. More particularly, membership management **156** may function to invite prospective members to participate in the social group **150** through automatic, automated and member-triggered processes. For example, membership management **156** might be configured by a human user **154** to establish a social group **150** by automatically inviting/accepting social system members having certain characteristics (such as devices owned or controlled by the user or acquaintances of the user).

Processing of accepted invitations and unsolicited requests to join the social group **150** may be conditioned upon input or authorization from an existing social system member(s) **152** or human user(s) **154** (e.g., through a user interface). Similarly, membership management **156** may be configured to generate automated suggestions regarding which prospective members receive an invitation. Various other approaches, such as those described herein, can be used to establish membership in accordance with the invention.

Access to and visibility of resources of a social group **150**, including services and data, may be managed through general and member class-specific access configurations **158**. For example, if membership in the social group **150** includes family members and associated devices, a uniform access configuration (or separate device and human configurations) could be applied across the class in an automatic or automated manner. In other embodiments, access control and constraints are imposed on a per-member basis.

The social group **150** may offer a wide variety of member services **162**, including both internal and external services accessible by social system members **152**. By way of example, the social group **150** may offer email or other communication services between full members and/or authorized guest members and visitors. As with other resources of the social group **150**, access control and constraints on member services **162** may be applied to individual members or classes of members.

FIG. **19** is a functional block diagram illustrating a social network (SNET) infrastructure **164**, as more fully described and disclosed in EP 2582116, fully incorporated herein by reference.

In one embodiment, illustrated in FIG. **20**, wearable devices **10** are in communication with a distributed computer network **166** that can include networks **102**, **104**, **112**, coupled to Network Systems **108** and system **32** via a plurality of communication links **168**. Communication net-

work **166** provides a mechanism for communication with system **16**, wearable device **10**, social media networks, mobile devices **74**, payment systems, **116**, the engines **114**, **120**, **122**, components of system **16**, and with all third parties, as described above.

The communication network **166** may itself be comprised of many interconnected computer systems and communication links. Communication links **168** may be hardwire links, optical links, satellite or other wireless communications links, wave propagation links, or any other mechanisms for communication of information. Various communication protocols may be used to facilitate communication between the various systems shown in FIG. **20**. These communication protocols may include TCP/IP, HTTP protocols, wireless application protocol (WAP), vendor-specific protocols, customized protocols, and others.

While in one embodiment, communication network **166** is the Network Systems, in other embodiments, communication network **166** may be any suitable communication network **166** including a local area network (LAN), a wide area network (WAN), a wireless network, an intranet, a private network, a public network, a switched network, and combinations of these, and the like.

System **32** is responsible for receiving information requests from wearable devices **10**, third parties, and the like, performing processing required satisfying the requests, and for forwarding the results corresponding to the requests backing to the requesting wearable device **10** and other systems. The processing required to satisfy the request may be performed by server **16** or may alternatively be delegated to other servers connected to communication network **166**.

FIG. **21** shows an exemplary computer system that can be utilized with the wearable devices **10**. In an embodiment, a user interfaces with system **32** using a wearable device **10** and then through a computer workstation system, such as shown in FIG. **21**, a mobile device, and the like.

The communication network **166** may be the Network systems, among other things. The network may be a wireless, a wired network (e.g., using copper), telephone network, packet network, an optical network (e.g., using optical fiber), or a wireless network, or any combination of these. For example, data and other information may be passed between the computer and components (or steps) of a system of the invention using a wireless network using a protocol such as Wi-Fi (IEEE standards 802.11, 802.11a, 802.11b, 802.11e, 802.11g, 802.11i, 802.11n, and 802.11 ac, just to name a few examples), near field communication (NFC), radio-frequency identification (RFID), mobile or cellular wireless (e.g., 2G, 3G, 4G, 3GPP LTE, WiMAX, LTE, Flash-OFDM, HIPERMAN, iBurst, EDGE Evolution, UMTS, UMTS-TDD, IxRDD, and EV-DO). For example, signals from a computer may be transferred, at least in part, wirelessly to components or other computers.

FIG. **22** shows a system for activity collection and building a social graph for network wearable device **10** users. The system monitors users as they surf the Web, their activities, locations, status, interests, and other things. This can be achieved without regard to whether the wearable device users **10** are logged into a membership site, such as a social networking site.

Resources **170** and **172** gather activity data and pass this data to an activity storage server **174**, typically via Network Systems **108**. Partner resource **172** may be processed by a partner back end, and then this data is passed to activity storage server **174**.

Wearable device **10** users can use social media sharing application or sites. Applications (e.g., a mobile device app

or sites allow sharing of information with others. These can be used to collect activity data. A wearable device **10** user (sender) can share information (e.g., video, photo, link, article, or other) by posting to a site. The wearable device **10** user can post directly on the site or use an application program, such as a mobile application on a smartphone or tablet computer. When another user (recipient) clicks or vies the link, there is connection activity between the sender and recipient. This activity data is captured by system **32**.

Messenger applications such as those on mobile device **74** or sites can allow Network Systems or Web messaging with others. Network Systems messaging is different from short messaging server (SMS) or text messaging. Messenger applications can be used to collect sharing activity data.

Users use messenger application to send links and other information to other users, and also achieve this using their wearable devices **10**. A user (sender) can copy a link (e.g., via a clipboard) and send to one or more users via the messenger application with mobile device **74** and with its wearable device **10**. When a recipient user clicks on the link, there is connection activity between the sender and recipient for that link.

Sharing activity data can be captured as described above. There can be different data collectors for different devices and platforms. The activity data is transmitted to and stored at activity storage server **174**, typically through Network Systems. Server **174** stores the data for further processing. There can be a significant amount of real-time data that is collected for processing. Distributed computing and processing can be used to process the data.

The activity data collected is stored at server **174**, usually in a database or file systems on hard drives of server **174**. There may be many terabytes of data that need are to be processed. Taking the stored activity data as input is a build-update graph component (e.g., executable code running on one or more servers or other computers). Build-update graph component **178** can run on the same server that stores the activity data, or may run on a separate server that accesses storage server **174**.

In one embodiment, a build-update graph **180** builds or updates a social graph using the collected activity data. The social graph can be stored in one or more databases or file systems. In one embodiment, build-update graph **180** can include three components: (1) identify nodes and edges for social graph that need to be updated, (2) create new nodes/edges if nodes/edges are not found, and (3) update values associated with nodes and edges.

For the incoming activity data collected, identify nodes **182** scan through and find the nodes and edges of the social graph that need to be updated.

When system **32** is processing a user activity data it has the ID of the wearable device **10** user and attributes this activity to that wearable device **10** user.

When a node or edge is found, update values update the node or an edge (e.g., associated with the node). When a node or edge is not found, a new node or edge is created in the graph. The result of build/update graph is a social graph **184** with nodes modeling user profiles and edge modeling sharing activities among users.

FIG. **23** shows a sample social graph **186** where circles **188** represent nodes and lines are edges **190** representing sharing interactions between nodes **182**. There can be one or more edges **190** between two nodes **182**. Several edges **190** between nodes **182** can indicate sharing activities along several categories: e.g., travel, computers, sports, and others.

Nodes **182** connected together directly have one degree of separation. Nodes **182** connected through one other node

have two degrees of separation. Depending on a number of intervening nodes **182** between two nodes **182**, this will be a number of degrees of separation between the two nodes **182**.

In a specific implementation, edges **190** between nodes **182** indicate sharing activities along several categories such as travel, computers, sports, and the like. For each additional new sharing category, an additional edge **190** is added. In a specific implementation, for each additional new sharing interest category, an additional edge **190** is added. Further, in an implementation, the sharing interaction or edges **190** between the nodes **182** can be weighted (e.g., weighting in a range from 0 to 1), so that certain types of sharing interactions are given different significance. Weight can be used to represent a relative strength of interaction related to a particular interest category.

Some types of sharing activities that are tracked for the social graph (or share graph) include: sending messages between users; sending files between users; sending videos between users; sending an e-mail (e.g., Web e-mail) with a link from one user to another such as sharing a link to various social media sites; and sending instant messages between users. For mobile devices **74** the sharing activities can further include: sending SMS-type messages between users. In some embodiments, messages can be sending from wearable devices **10**.

Once two users connect, such as one wearable device **10** sending another wearable device **10** user a message containing a link concerning a topic. When the recipient user clicks on the link from the sender user, system **32** will add an edge **190** to graph **186** to represent the activity. An edge **190** is added to the graph **186** to represent this sharing activity between the two users.

In a specific implementation, two wearable device **10** users are connected when one user (sender) shares information with another user or group and the other user (recipient) consumes the information that was sent (e.g., clicked-back on the shared link, opened an attachment, opened a message). For example, simply placing a link on Facebook® wall so that all Facebook® “friends” can see this link or tweeting a link to Twitter® followers will not create a connection between the sender, or sharer, and people in the graph. This would create significant noise in the system. The connections are created between the sender and only those users who clicked back on (or otherwise consumed) the message.

In one embodiment, more recently sent messages are given a greater weight than older messages.

The foregoing description of various embodiments of the claimed subject matter has been provided for the purposes of illustration and description. It is not intended to be exhaustive or to limit the claimed subject matter to the precise forms disclosed. Many modifications and variations will be apparent to the practitioner skilled in the art. Particularly, while the concept “component” is used in the embodiments of the systems and methods described above, it will be evident that such concept can be interchangeably used with equivalent concepts such as, class, method, type, interface, module, object model, and other suitable concepts. Embodiments were chosen and described in order to best describe the principles of the invention and its practical application, thereby enabling others skilled in the relevant art to understand the claimed subject matter, the various embodiments and with various modifications that are suited to the particular use contemplated.

What is claimed is:

1. A method for using telemetry data, and a monitoring device, comprising:
  - using a monitoring device with a microphone and sensors to determine air quality, sound level/quality, light quality and ambient temperature near a user;
  - detecting a user's movement or motion information using an accelerometer or other movement detection device, the microphone configured to record the user's movement sounds detected by the accelerometer or other movement detection device, the accelerometer or other movement detection device and monitoring system configured to provide information configured to assist to determine user sleep information and sleep behavior information, the accelerometer or other movement detection device configured to cause the microphone to stop recording user movement sounds when the movement sounds are not directed to a sleep related parameter;
  - communicating between a telemetry system with at least one of the monitoring device, the accelerometer or other motion detection device, the telemetry system including a database of user sleep information and sleep behavior information;
  - analyzing at the telemetry system the user sleep information and sleep behavior information received from at least one of the monitoring device, the accelerometer or other movement detection device to drive at least one of: sleep onset and wake time, sleep interruption, and the quality and depth of sleep; and
  - creating personalized information about the user in response to the sleep information and sleep behavior information received from at least one of the monitoring device, the accelerometer or other movement detection device that includes the at least one of: sleep onset and wake time, sleep interruption, and the quality and depth of sleep.
2. The method of claim 1, further comprising: routing signals through the ID circuitry using a pathway system of the ID circuitry, the ID circuitry including a power source coupled to the pathway system.
3. The method of claim 1, further comprising: using the wearable device ID of a user to identify and contact users of a social network.
4. The method of claim 1, further comprising:
  - searching by a first user with a wearable device and unique ID a second user's unique wearable device ID displayed by another user; and
  - finding the second user on a social network website or social network website by searching for the second user.
5. The method of claim 1, further comprising: enabling wearable device users to engage in at least one of, non-romantic relationships, keep in touch with acquaintances, friends and family, professional business relationships, romantic relationships, communicating between wearable device users on a message board or internet forum, and allowing users to follow up on missed-connections.
6. The method of claim 1, wherein the database includes at least one of a user, first and last name, email address, a desired password, phone number, gender, birth date, address, geographic region, education information, employment information, interests, relationship information and interests, family information, religious views, ethnicity, physical features including hair color, eye color, measurements, and the like, type of relationship being sought, living

situation, answers to quiz questions, and a personal description about interesting personality traits.

7. The method of claim 1, further comprising:
  - using the telemetry system to enable wearable device users to upload one or a plurality of photographs for other wearable device users to view, or for wearable device users to store the photo or photos on the server.
8. The method of claim 1, wherein the system is configured to access a social network.
9. The method of claim 1, further comprising: enabling a wearable device user to provide personal information to the system from social networks.
10. The method of claim 1, further comprising: using the unique wearable device ID to enable the user to be searched and identified by other wearable device users and potential wearable device users.
11. The method of claim 1, further comprising: receiving from the wearable device user an email address.
12. The method of claim 1, wherein the email address of the user's ID is directed to another domain name.
13. The method of claim 1, further comprising: using the system is to provide to a wearable device user a personal page.
14. The method of claim 13, wherein the personal page utilizes a computer to automatically import the information provided when signing up with the system or a social network.
15. A method for using telemetry data, and a monitoring device, comprising:
  - using a monitoring device with a microphone and sensors to determine air quality, sound level/quality, light quality and ambient temperature near a user;
  - detecting a user's movement or motion information using an accelerometer or other movement detection device, the microphone configured to record the user's movement sounds detected by the accelerometer or other movement detection device, the accelerometer and monitoring system configured to provide information to assist to determine user sleep information and sleep behavior information, the accelerometer or other movement detection device configured to cause the microphone to stop recording user movement sounds when the movement sounds are not directed to a sleep related parameter;
  - communicating between a telemetry system with at least one of the monitoring device, the accelerometer or the other motion detection, the telemetry system including a database of user sleep information and sleep behavior information; and
  - analyzing at the telemetry system the user sleep information and sleep behavior information received from at least one of the monitoring device, the accelerometer or the other motion detection device to drive at least one of: sleep onset and wake time, sleep interruption, and the quality and depth of sleep, the telemetry system creating personalized information about the user in response to the sleep information and sleep behavior information received from at least one of the monitoring device, the accelerometer or other movement detection device that includes the at least one of: sleep onset and wake time, sleep interruption, and the quality and depth of sleep.
16. The method of claim 15, wherein the system is configured to provide the mobile device or computer with updates from the server.

29

- 17. The method of claim 15, further comprising:  
sending streams of information from the wearable device,  
both encrypted and non-encrypted to the mobile device  
or computer and then to the server.
- 18. The method of claim 15, further comprising: 5  
sending information from the wearable device to the  
mobile device or computer.
- 19. The method of claim 18, wherein information sent  
from the telemetry system to the mobile device or computer  
is processed at the mobile device, computer or telemetry 10  
system.
- 20. The method of claim 15, further comprising:  
sending raw sensor information from the wearable device  
to the mobile device or computer.
- 21. The method of claim 20, wherein the information is 15  
compressed as well as non-compressed.
- 22. The method of claim 21, further comprising:  
using a compression algorithm to execute compression at  
the wearable device, mobile device, computer or the  
telemetry system.
- 23. The method of claim 15, further comprising: 20  
using the wearable device ID of a user to provide a  
method of identifying and contacting users of a social  
network.
- 24. The method of claim 15, further comprising: 25  
searching by a first user with a wearable device and  
unique ID a second user's unique wearable device ID  
displayed by another user; and  
finding the second user on a social network website or  
social network website by searching for the second  
user.

30

- 25. The method of claim 15, further comprising:  
using the telemetry system to enable wearable device  
users to engage in at least one of, non-romantic rela-  
tionships, keep in touch with acquaintances, friends and  
family, professional business relationships, and roman-  
tic relationships, allow communication between wear-  
able device users on a message board or network  
system forum, and allows users to follow up on missed-  
connections.
- 26. The method of claim 15, wherein the database  
includes at least one of a user, first and last name, email  
address, a desired password, phone number, gender, birth  
date, address, geographic region, education information,  
employment information, interests, relationship information  
and interests, family information, religious views, ethnicity,  
physical features including hair color, eye color, measure-  
ments, and the like, type of relationship being sought, living  
situation, answers to quiz questions, and a personal descrip-  
tion about interesting personality traits.
- 27. The method of claim 15, further comprising:  
enabling wearable device users to upload one or a plu-  
rality of photographs for other wearable device users to  
view, or for wearable device users to store the photo or  
photos on the server.
- 28. The method of claim 15, further comprising:  
communicating between the wearable device is operation  
with a social network circle/group (SNET circle).

\* \* \* \* \*

专利名称(译)	使用具有唯一用户ID的可穿戴设备的方法和与一个或多个社交网络通信的遥测系统		
公开(公告)号	<a href="#">US9438044</a>	公开(公告)日	2016-09-06
申请号	US13/923750	申请日	2013-06-21
[标]申请(专利权)人(译)	你好		
申请(专利权)人(译)	HELLO INC.		
当前申请(专利权)人(译)	HELLO INC.		
[标]发明人	PROUD JAMES		
发明人	PROUD, JAMES		
IPC分类号	G06F15/16 G06F9/445 A61B5/00 H01F38/14 H02J5/00 H04L29/06 H02J7/02 G08C17/02 H04L29/08 G06Q20/32 H02J7/00 G06F19/00		
CPC分类号	H02J5/005 A61B5/0002 A61B5/002 A61B5/0015 A61B5/0022 A61B5/0024 G06F8/65 G06Q20/322 G08C17/02 H01F38/14 H02J7/025 H02J5/80 H04L65/403 H04L67/22 A61B2560/0214 A61B2562/08 G06F19/3418 H02J2007/0096 Y02B60/183 G16H40/40 G16H40/67 H02J7/00034 H02J50/12 Y02D10/42 G16H40/63		
代理人(译)	DAVIS , PAUL		
优先权	61/772265 2013-03-04 US 61/812083 2013-04-15 US		
其他公开文献	US20140250181A1		
外部链接	<a href="#">Espacenet</a> <a href="#">USPTO</a>		

摘要(译)

提供了一种用于使用遥测数据的方法，以及一种与社交网络通信的可穿戴设备。耦合到具有唯一用户ID的可穿戴设备的一个或多个传感器用于获取用户的活动，行为和习惯信息中的至少一个。可穿戴设备具有ID电路和从ID存储器读取和发送唯一ID的通信系统。可穿戴设备与社交网络通信。遥测系统与一个或多个传感器通信。遥测系统包括用户ID的数据库。基于用户的活动，行为和习惯信息中的至少一个来分析遥测数据。创建关于用户的个性化信息。

