



US 20190099582A1

(19) **United States**

(12) **Patent Application Publication**
CROW et al.

(10) **Pub. No.: US 2019/0099582 A1**

(43) **Pub. Date: Apr. 4, 2019**

(54) **SLEEP PERFORMANCE SYSTEM AND METHOD OF USE**

(52) **U.S. Cl.**

CPC *A61M 21/02* (2013.01); *A61B 5/4815* (2013.01); *A61B 5/02405* (2013.01); *A61B 5/7278* (2013.01); *A61B 5/0482* (2013.01); *A61B 5/4812* (2013.01)

(71) Applicant: **NeuroGeneces LLC**, Santa Fe, NM (US)

(72) Inventors: **Karen CROW**, Santa Fe, NM (US); **Matt SANDERS**, Santa Fe, NM (US)

(73) Assignee: **NeuroGeneces LLC**, Santa Fe, NM (US)

(57) **ABSTRACT**

(21) Appl. No.: **16/151,715**

(22) Filed: **Oct. 4, 2018**

Related U.S. Application Data


(60) Provisional application No. 62/568,249, filed on Oct. 4, 2017, provisional application No. 62/661,932, filed on Apr. 24, 2018.

Publication Classification

(51) **Int. Cl.**

A61M 21/02 (2006.01)
A61B 5/00 (2006.01)
A61B 5/0482 (2006.01)

Sleep performance systems and methods of using the same are disclosed. The sleep performance systems can improve the quality of sleep by making one or more recommendations to the subject for increasing a sleep quality score. The sleep performance systems can have one or more electroencephalography (EEG) electrodes configured to measure a subject's brain activity during sleep. The sleep performance systems can have a processor configured to quantify the quality of the subject's slow-wave sleep by determining one or more sleep performance scores associated with the measured brain activity. The sleep performance systems can recommend and/or activate sleep improvement programs based on various threshold scores.






FIG. 1B




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 2D




FIG. 2E






FIG. 3A



- 80 yr old
- 60 yr old
- 40 yr old
- - 20 yr old

- $y = 1.25x$ 43d
- $y = 1.11x$ 43c
- $y = x$ 43b
- - $y = 0.9091x$ 43a

FIG. 3B



- 80 yr old
- 60 yr old
- 40 yr old
- - 20 yr old

- $y = 2.9165 - 130.95$ 45d
- $y = 3.6x - 198$ 45c
- $y = 4.5x - 292.5$ 45b
- - $y = 5.7x - 424$ 45a

FIG. 3C




FIG. 3D




FIG. 3E




FIG. 4A




FIG. 4B




FIG. 4C

59

		Contributors		Points
Alt. H2	Triggered Recommendation	Option 1: Performance vs Personal Baseline	Option 2: Performance vs Cohort	Points
Insufficient Deep Sleep	Deep Sleep Audio Stimulation	Deep Sleep > 10% below personal baseline	Deep Sleep < 75 points for cohort	3
		Deep Sleep > 20% below personal baseline	Deep Sleep < 65 points for cohort	3
		Deep Sleep > 30% below personal baseline	Deep Sleep < 55 points for cohort	3
Weak Deep Sleep	Deep Sleep Audio Stimulation	Amplitude during Deep Sleep is > 20% below baseline	Amplitude during Deep Sleep is 20% < Cohort	2
		Amplitude during Deep Sleep is > 40% below baseline	Amplitude during Deep Sleep is 40% < Cohort	2
		Amplitude during Deep Sleep is > 60% below baseline	Amplitude during Deep Sleep is 60% < Cohort	2
Fragmented Deep Sleep	Deep Sleep Audio Stimulation	Longest Duration of DS is 20% > baseline	Longest Duration of Deep Sleep 20% < Cohort	2
		Longest Duration of DS is 40% > baseline	Longest Duration of Deep Sleep 40% < Cohort	2
		Longest Duration of DS is 60% > baseline	Longest Duration of Deep Sleep 60% < Cohort	2
Insufficient Total Sleep: total time in bed is insufficient	Tips: Need to allocate more time to sleep. Make sure to optimize DS if getting short sleep	Total Sleep 20% below personal baseline	Total Sleep < 70 points for cohort	2
		Total Sleep 40% below personal baseline	Total Sleep < 60 points for cohort	2
		Total Sleep 60% below personal baseline	Total Sleep < 50 points for cohort	2
Insufficient Total Sleep: poor sleep efficiency	Guided Meditation for sleep relaxation	Sleep Efficiency > 5% below personal baseline	Sleep Efficiency points < 85 points for cohort	2
		Sleep Efficiency > 10% below personal baseline	Sleep Efficiency points < 75 points for cohort	2
		Sleep Efficiency > 15% below personal baseline	Sleep Efficiency points < 65 points for cohort	2
Low recovery level	Tips: take it easy, you're not at full strength today	HRV > 20% below personal baseline	HRV points < 80	4
		HRV > 30% below personal baseline	HRV points < 60	4
		HRV > 40% below personal baseline	HRV points < 40	4
Terrible Sleep Quality Score	Encouragement: Keep up the great work	Deep Sleep > 10% above personal baseline	Deep Sleep = 100 points for cohort	3
		Deep Sleep > 20% above personal baseline		3
		Deep Sleep > 30% above personal baseline		3
Great Duration of Deep Sleep	Encouragement: Congrats! You're keeping your brain nice and healthy!	Deep Sleep Duration > 20% above personal best	Deep Sleep Duration = 100 points for cohort	3
		Deep Sleep Duration > 40% above personal best		3
		Deep Sleep Duration > 60% above personal best		3

FIG. 5




FIG. 6




FIG. 7A




FIG. 7B




FIG. 7C




FIG. 7D




FIG. 7E




FIG. 8A




FIG. 8B




FIG. 8C




FIG. 8D









FIG. 8E






FIG. 11A




FIG. 11B




FIG. 11E




FIG. 11D




FIG. 11C




FIG. 11F




FIG. 11G




FIG. 11H




FIG. 11I




FIG. 11J

Table 1
Sleep structure and age

Sleep structure	Age (years)											P (one-way ANOVA)	Effect size ²	
	20-24 (n=106)	25-29 (n=130)	30-34 (n=129)	35-39 (n=119)	40-44 (n=128)	45-49 (n=126)	50-54 (n=87)	55-59 (n=79)	60-64 (n=49)	65-69 (n=40)	70-74 (n=29)			75-80 (n=24)
TST	376.3 ± 75.4	367.9 ± 78.4	364.0 ± 71.0	333.4 ± 82.9	338.0 ± 78.1	338.2 ± 74.9	316.9 ± 89.3	325.9 ± 70.9	329.1 ± 51.2	314.5 ± 80.5	282.0 ± 78.0	291.0 ± 86.0	<0.01	0.08
Eff	87.9 ± 9.5	86.1 ± 11.8	86.8 ± 8.6	81.6 ± 15.5	82.5 ± 12.2	81.3 ± 12.5	78.1 ± 13.0	77.7 ± 11.8	79.0 ± 9.6	74.9 ± 14.5	72.8 ± 17.3	65.4 ± 13.0	<0.01	0.13
Lat	13.8 ± 17.5	15.0 ± 20.1	14.5 ± 16.8	19.6 ± 32.7	13.4 ± 13.9	17.4 ± 21.0	17.8 ± 16.7	17.3 ± 16.3	17.3 ± 15.0	20.5 ± 28.7	28.7 ± 41.1	34.6 ± 45.9	0.01	0.03
REMat	106.4 ± 50.9	97.5 ± 45.5	95.6 ± 44.3	89.8 ± 37.9	97.0 ± 47.5	102.5 ± 57.0	106.1 ± 58.6	109.8 ± 64.2	109.8 ± 65.4	95.0 ± 52.0	129.1 ± 83.1	120.9 ± 3.0	0.01	0.02
WASO	38.9 ± 35.5	44.4 ± 40.5	41.0 ± 30.2	55.0 ± 47.1	58.1 ± 45.8	61.0 ± 45.3	72.3 ± 47.7	78.1 ± 44.9	72.1 ± 37.4	84.1 ± 40.4	81.1 ± 49.2	121.6 ± 49.6	<0.01	0.14
AI	8.8 ± 4.6	10.4 ± 5.8	11.4 ± 6.7	12.5 ± 7.8	15.3 ± 10.6	16.3 ± 13.3	19.6 ± 15.3	19.0 ± 11.1	22.3 ± 14.6	20.9 ± 12.4	17.5 ± 8.8	21.8 ± 13.7	<0.01	0.14
RAI	1.9 ± 2.3	2.4 ± 3.9	3.3 ± 5.1	4.1 ± 5.3	5.9 ± 10.0	7.3 ± 11.3	9.0 ± 11.7	8.8 ± 9.4	13.9 ± 13.6	10.3 ± 9.9	9.6 ± 8.7	13.3 ± 15.2	<0.01	0.13
NRAI	7.1 ± 3.4	7.9 ± 3.8	8.2 ± 4.1	8.5 ± 5.1	9.4 ± 6.4	9.1 ± 5.3	10.7 ± 7.4	10.4 ± 6.3	8.9 ± 5.4	10.8 ± 8.3	8.1 ± 4.7	8.5 ± 5.2	<0.01	0.04
S1d	13.6 ± 9.6	14.3 ± 10.0	14.5 ± 8.8	12.7 ± 8.2	14.9 ± 10.7	16.0 ± 10.3	16.2 ± 13.0	17.3 ± 13.2	15.9 ± 9.4	13.7 ± 5.3	13.3 ± 6.6	18.2 ± 10.1	0.05	0.02
S2d	204.4 ± 52.1	197.4 ± 49.1	197.0 ± 54.6	177.7 ± 53.7	184.7 ± 49.7	181.9 ± 48.4	172.6 ± 47.3	185.4 ± 51.2	184.0 ± 38.5	178.4 ± 56.1	165.7 ± 61.0	169.9 ± 58.4	<0.01	0.04
SWSD	87.4 ± 26.5	83.7 ± 25.3	77.5 ± 25.9	75.4 ± 26.3	89.9 ± 28.9	70.7 ± 30.0	70.2 ± 25.2	63.4 ± 31.5	69.3 ± 26.5	67.2 ± 37.3	63.3 ± 27.0	53.6 ± 33.2	<0.01	0.07
REMd	70.9 ± 30.5	72.6 ± 33.5	75.0 ± 27.6	67.6 ± 28.6	68.5 ± 30.7	69.5 ± 32.3	57.8 ± 26.2	59.9 ± 29.9	60.0 ± 22.2	55.1 ± 22.9	49.6 ± 26.8	49.3 ± 20.6	<0.01	0.05
S1%	3.8 ± 2.9	4.3 ± 4.2	4.1 ± 2.8	4.3 ± 4.1	4.5 ± 3.0	4.8 ± 3.1	5.2 ± 4.0	5.4 ± 4.0	4.9 ± 2.9	4.9 ± 3.3	4.8 ± 2.2	6.4 ± 3.3	<0.01	0.02
S2%	54.2 ± 7.7	53.6 ± 8.5	53.8 ± 8.0	53.0 ± 8.2	55.0 ± 9.3	54.1 ± 9.6	54.5 ± 9.3	57.4 ± 11.6	55.9 ± 8.9	56.7 ± 11.2	55.4 ± 12.4	58.2 ± 13.1	<0.01	0.02
SWS%	23.6 ± 6.7	23.2 ± 6.7	21.8 ± 7.6	23.2 ± 7.7	20.9 ± 7.9	21.3 ± 8.7	22.5 ± 7.8	19.7 ± 9.6	21.1 ± 7.4	21.3 ± 10.2	23.3 ± 11.7	18.3 ± 10.4	<0.01	0.03
REM%	18.4 ± 6.0	19.0 ± 6.9	20.3 ± 5.5	19.5 ± 6.5	19.6 ± 6.4	19.7 ± 6.8	17.8 ± 6.7	17.8 ± 7.2	18.1 ± 5.7	17.0 ± 5.8	16.5 ± 7.1	17.0 ± 6.3	<0.01	0.03

ANOVA, analysis of variance; TST, total sleep time; Eff, sleep efficiency; Lat, sleep latency; REMat, REM sleep latency (min); WASO, wake after sleep onset; AI, arousal index; RAI, respiratory arousal index; NRAI, non-respiratory arousal index; S1d, stage 1 duration (min); S2d, stage 2 duration (min); SWSD, skw wave sleep duration (min); REMd, REM sleep duration; S1% stage 1 percentage; S2%, stage 2 percentage; SWS%, skw wave sleep percentage; REM%, REM sleep percentage.

Values are mean ± SD.

a η².

FIG. 12A




FIG. 12B

Table 1
Sleep structure and age

Sleep structure	Age (years)										P (one-way ANOVA) size ²			
	20-24 (n=106)	25-29 (n=130)	30-34 (n=129)	35-39 (n=119)	40-44 (n=128)	45-49 (n=126)	50-54 (n=87)	55-59 (n=79)	60-64 (n=46)	65-69 (n=40)		70-74 (n=26)	75-80 (n=24)	
TST	376.3 ± 75.4	367.9 ± 78.4	364.0 ± 71.0	333.4 ± 82.9	338.0 ± 78.1	338.2 ± 74.9	316.9 ± 69.3	325.9 ± 70.9	329.1 ± 51.2	314.5 ± 80.5	292.0 ± 78.0	291.0 ± 66.0	<0.01	0.08
Eff	87.9 ± 9.5	86.1 ± 11.8	86.8 ± 8.6	81.6 ± 15.5	82.5 ± 12.2	81.3 ± 12.5	78.1 ± 13.0	77.7 ± 11.8	79.0 ± 9.6	74.9 ± 14.5	72.8 ± 17.3	65.4 ± 13.0	<0.01	0.13
Lat	13.8 ± 17.5	15.0 ± 20.1	14.5 ± 16.8	19.6 ± 32.7	13.4 ± 13.9	17.4 ± 21.0	17.8 ± 18.7	17.3 ± 18.3	17.3 ± 15.0	20.8 ± 28.7	28.7 ± 41.1	34.6 ± 45.9	0.01	0.03
REMIat	106.4 ± 50.9	97.5 ± 45.5	95.6 ± 44.3	89.9 ± 37.9	97.0 ± 47.5	102.5 ± 57.0	106.1 ± 58.6	109.8 ± 64.2	109.8 ± 65.4	95.0 ± 52.0	129.1 ± 83.1	120.9 ± 3.0	0.01	0.02
WASO	38.9 ± 35.5	44.4 ± 40.5	41.0 ± 30.2	55.0 ± 47.1	58.1 ± 45.8	61.0 ± 45.3	72.3 ± 47.7	78.1 ± 44.9	72.1 ± 37.4	84.1 ± 40.4	81.1 ± 49.2	121.6 ± 49.6	<0.01	0.14
AI	8.8 ± 4.6	10.4 ± 5.8	11.4 ± 6.7	12.5 ± 7.8	15.3 ± 10.6	16.5 ± 13.3	19.6 ± 15.3	19.0 ± 11.1	22.3 ± 14.6	20.9 ± 12.4	17.5 ± 8.8	21.8 ± 13.7	<0.01	0.14
RAI	1.9 ± 2.3	2.4 ± 3.9	3.3 ± 5.1	4.1 ± 5.3	5.9 ± 10.0	7.3 ± 11.3	9.0 ± 11.7	8.6 ± 9.4	13.9 ± 13.6	10.3 ± 9.9	9.6 ± 8.7	13.3 ± 15.2	<0.01	0.13
NRAI	7.1 ± 3.4	7.9 ± 3.8	8.2 ± 4.1	8.5 ± 5.1	9.4 ± 6.4	9.1 ± 5.3	10.7 ± 7.4	10.4 ± 6.3	8.9 ± 5.4	10.8 ± 8.3	8.1 ± 4.7	8.5 ± 5.2	<0.01	0.04
S1d	13.6 ± 9.6	14.3 ± 10.0	14.5 ± 8.8	12.7 ± 8.2	14.9 ± 10.7	16.0 ± 10.3	16.2 ± 13.0	17.3 ± 13.2	15.9 ± 9.4	13.7 ± 5.3	13.3 ± 6.6	18.2 ± 10.1	0.05	0.02
S2d	204.4 ± 52.1	197.4 ± 49.1	197.0 ± 54.6	177.7 ± 53.7	184.7 ± 49.7	181.9 ± 48.4	172.6 ± 47.3	185.4 ± 51.2	184.0 ± 38.5	178.4 ± 56.1	165.7 ± 61.0	169.9 ± 58.4	<0.01	0.04
SWSd	87.4 ± 26.5	83.7 ± 25.3	77.5 ± 25.9	75.4 ± 26.3	69.9 ± 28.9	70.7 ± 30.0	70.2 ± 25.2	63.4 ± 31.5	69.3 ± 28.5	67.2 ± 37.3	63.3 ± 27.0	53.6 ± 33.2	<0.01	0.07
REMId	70.9 ± 30.5	72.6 ± 33.5	75.0 ± 27.6	67.6 ± 28.6	68.5 ± 30.7	69.5 ± 32.3	57.3 ± 26.2	59.9 ± 29.9	60.0 ± 22.2	55.1 ± 22.9	49.6 ± 26.8	49.3 ± 20.6	<0.01	0.05
S1%	3.8 ± 2.9	4.3 ± 4.2	4.1 ± 2.8	4.3 ± 4.1	4.5 ± 3.0	4.8 ± 3.1	5.2 ± 4.0	5.4 ± 4.0	4.9 ± 2.9	4.9 ± 3.3	4.8 ± 2.2	6.4 ± 3.3	<0.01	0.02
S2%	54.2 ± 7.7	53.6 ± 8.5	53.8 ± 8.0	53.0 ± 8.2	55.0 ± 9.3	54.1 ± 9.6	54.5 ± 9.3	57.4 ± 11.6	55.9 ± 8.9	56.7 ± 11.2	55.4 ± 12.4	58.2 ± 13.1	<0.01	0.02
SWS%	23.6 ± 6.7	23.2 ± 6.7	21.8 ± 7.6	23.2 ± 7.7	20.9 ± 7.9	21.3 ± 8.7	22.5 ± 7.8	19.7 ± 9.6	21.1 ± 7.4	21.3 ± 10.2	23.3 ± 11.7	18.3 ± 10.4	<0.01	0.03
REM%	18.4 ± 6.0	19.0 ± 6.9	20.3 ± 5.5	19.5 ± 6.5	19.6 ± 6.4	19.7 ± 6.8	17.8 ± 6.7	17.8 ± 7.2	18.1 ± 5.7	17.0 ± 5.8	16.5 ± 7.1	17.0 ± 6.3	<0.01	0.03

ANOVA, analysis of variance; TST, total sleep time; Eff, sleep efficiency; Lat, sleep latency; REMIat, REM sleep latency (min); WASO, wake after sleep onset; AI, arousal index; RAI, respiratory arousal index; NRAI, non-respiratory arousal index; S1d, stage 1 duration (min); S2d, stage 2 duration (min); SWSd, skw wave sleep duration (min); REMd, REM sleep duration; S1% stage 1 percentage; S2% stage 2 percentage; SWS%, skw wave sleep percentage; REM%, REM sleep percentage. Values are mean ± SD.

a η².

FIG. 13A




FIG. 13B

	20 Yr old			40 y/o		
	Moraes	Ohayon	NG	Moraes	Ohayon	NG
Average	376	450	413	338	400	369
Stnd Dev	75	50	62.5	78	25	51.5
Stnd Dev%	20%	11%	15%	23%	6%	14%
Avg			413			369
Avg + 1 SD			475.5			420.5
Avg + 2 SD			538			472
Avg - 1 SD			350.5			317.5
Avg - 2 SD			288			266
						260




FIG. 14A

FIG. 14B




FIG. 14C

FIG. 14D




FIG. 15A

Total Sleep Time Scoring

Calculated	x-axis		20 y/o	40 y/o	60 y/o	80 y/o
	Hrs	minutes				
	0	0	0	0	0	0
	0.8	50	0	0	0	0
	1.7	100	0	0	0	0
	2.5	150	0	0	0	0
	3.3	200	0	0	3.48	20.63
	4.2	250	13.58	22.595	38.95	52.81
	5.0	300	42.07	52.74	65.92	75.49
	5.8	350	64.56	73.885	84.39	88.67
	6.7	400	81.05	86.03	94.36	97
	7.5	450	91.54	95	98	100
	8.3	500	96.03	99	100	100
	9.2	550	100	100	100	100

Equations

- 20 yr old $y = -0.0012x^2 + 1.2298x - 218.87$
- 40 yr old $y = -0.0018x^2 + 1.5929x - 263.13$
- 60 yr old $y = -0.0017x^2 + 1.4744x - 223.4$
- 80 yr old $y = -0.0019x^2 + 1.4986x - 203.09$

FIG. 15B




FIG. 16

Table 1
Sleep structure and age

Sleep structure	Age (years)										P (one-way ANOVA)	Effect size ²		
	20-24 (n=106)	25-29 (n=130)	30-34 (n=129)	35-39 (n=119)	40-44 (n=128)	45-49 (n=126)	50-54 (n=87)	55-59 (n=9)	60-64 (n=46)	65-69 (n=40)			70-74 (n=26)	75-80 (n=24)
TST	376.3 ± 75.4	367.9 ± 78.4	364.0 ± 71.0	333.4 ± 82.9	338.0 ± 78.1	338.2 ± 74.9	316.9 ± 68.3	325.9 ± 70.9	329.1 ± 51.2	314.5 ± 60.5	292.9 ± 78.0	291.0 ± 66.0	<0.01	0.08
Eff	87.9 ± 9.5	86.1 ± 11.8	86.8 ± 8.6	81.6 ± 15.5	82.5 ± 12.2	81.3 ± 12.5	78.1 ± 13.0	77.7 ± 11.6	79.0 ± 9.6	74.9 ± 14.5	72.8 ± 17.3	65.4 ± 13.0	<0.01	0.13
Lat	13.8 ± 17.5	15.0 ± 20.1	14.5 ± 16.8	19.6 ± 32.7	13.4 ± 13.9	17.4 ± 21.0	17.8 ± 18.7	17.3 ± 18.3	17.3 ± 15.0	20.5 ± 28.7	28.7 ± 41.1	34.6 ± 45.9	0.01	0.03
REMIat	106.4 ± 50.9	97.5 ± 45.5	95.6 ± 44.3	89.8 ± 37.9	97.0 ± 47.5	102.9 ± 57.0	106.1 ± 58.6	109.8 ± 64.2	109.8 ± 65.4	95.0 ± 52.0	129.1 ± 83.1	120.9 ± 3.0	0.01	0.02
WASO	38.9 ± 35.5	44.4 ± 40.5	41.0 ± 30.2	55.0 ± 47.1	56.1 ± 45.8	61.0 ± 46.3	72.3 ± 47.7	78.1 ± 44.9	72.1 ± 37.4	84.1 ± 40.4	81.1 ± 49.2	121.6 ± 49.6	<0.01	0.14
AI	9.8 ± 4.6	10.4 ± 5.8	11.4 ± 6.7	12.5 ± 7.8	15.3 ± 10.6	16.3 ± 13.3	19.6 ± 15.3	19.9 ± 11.1	22.3 ± 14.6	20.9 ± 12.4	17.5 ± 8.8	21.8 ± 13.7	<0.01	0.14
RAI	1.9 ± 2.3	2.4 ± 3.9	3.3 ± 5.1	4.1 ± 5.3	5.9 ± 10.0	7.3 ± 11.3	9.0 ± 11.7	8.6 ± 9.4	13.9 ± 13.6	10.3 ± 9.9	9.6 ± 8.7	13.3 ± 15.2	<0.01	0.13
NRAI	7.1 ± 3.4	7.9 ± 3.8	8.2 ± 4.1	8.5 ± 5.1	9.4 ± 6.4	9.1 ± 5.3	10.7 ± 7.4	10.4 ± 6.3	8.9 ± 5.4	10.8 ± 8.3	8.1 ± 4.7	8.5 ± 5.2	<0.01	0.04
S1d	13.6 ± 9.6	14.3 ± 10.0	14.5 ± 8.8	12.7 ± 8.2	14.9 ± 10.7	16.0 ± 10.3	16.2 ± 13.0	17.3 ± 13.2	15.9 ± 9.4	13.7 ± 5.3	13.3 ± 6.6	18.2 ± 10.1	0.05	0.02
S2d	204.4 ± 52.1	197.4 ± 49.1	197.0 ± 54.6	177.7 ± 53.7	194.7 ± 49.7	181.9 ± 48.4	172.6 ± 47.3	185.4 ± 51.2	184.0 ± 38.5	178.4 ± 56.1	165.7 ± 61.0	169.9 ± 58.4	<0.01	0.04
SWSd	87.4 ± 26.5	83.7 ± 25.3	77.5 ± 25.9	75.4 ± 26.3	69.9 ± 28.9	70.7 ± 30.0	70.2 ± 25.2	63.4 ± 31.5	69.3 ± 26.5	67.2 ± 37.3	63.3 ± 27.0	53.6 ± 33.2	<0.01	0.07
REMI	70.9 ± 30.5	72.6 ± 33.5	75.0 ± 27.6	67.6 ± 28.6	68.5 ± 30.7	69.5 ± 32.3	57.8 ± 26.2	59.9 ± 29.9	60.0 ± 22.2	55.1 ± 22.9	49.6 ± 26.8	49.3 ± 20.6	<0.01	0.05
S1%	3.9 ± 2.9	4.3 ± 4.2	4.1 ± 2.8	4.3 ± 4.1	4.5 ± 3.0	4.8 ± 3.1	5.2 ± 4.0	5.4 ± 4.0	4.9 ± 2.9	4.9 ± 3.3	4.8 ± 2.2	6.4 ± 3.3	<0.01	0.02
S2%	54.2 ± 7.7	53.6 ± 8.5	53.8 ± 8.0	53.0 ± 8.2	55.0 ± 9.3	54.1 ± 9.6	54.5 ± 9.3	57.4 ± 11.6	55.9 ± 8.9	56.7 ± 11.2	55.4 ± 12.4	58.2 ± 13.1	<0.01	0.02
SWS%	23.6 ± 6.7	23.2 ± 6.7	21.8 ± 7.6	23.2 ± 7.7	20.9 ± 7.9	21.3 ± 8.7	22.5 ± 7.8	19.7 ± 9.6	21.1 ± 7.4	21.3 ± 10.2	23.3 ± 11.7	18.3 ± 10.4	<0.01	0.03
REMI%	18.4 ± 6.0	19.0 ± 6.9	20.3 ± 5.5	19.5 ± 6.5	19.6 ± 6.4	19.7 ± 6.8	17.8 ± 6.7	17.8 ± 7.2	18.1 ± 5.7	17.0 ± 5.8	16.5 ± 7.1	17.0 ± 6.3	<0.01	0.03

ANOVA, analysis of variance; TST, total sleep time; Eff, sleep efficiency; Lat, sleep latency; REMIat, REM sleep latency (min); WASO, wake after sleep onset; AI, arousal index; RAI, respiratory arousal index; NRAI, non-respiratory arousal index; S1d, stage 1 duration (min); S2d, stage 2 duration (min); SWSd, SWS wave sleep duration (min); REMI, REM sleep duration; S1% stage 1 percentage; S2%, stage 2 percentage; SWS%, SWS wave sleep percentage; REMI%, REM sleep percentage.

Values are mean ± SD.

FIG. 17A





FIG. 17B



	60 y/o			80 y/o		
	Moraes	Ohayon	NG SCORES	Moraes	Ohayon	NG SCORES
Average TST	380	380		350	350	
SWS as % TST	10%	10%		9%	9%	
Average DSD	65	38	51.5	54	31.5	42.75
Stnd Dev	34	19	26.5	33	17.5	25.25
Stnd Dev %	52%	50%	51%	61%	56%	59%
Avg			51.5			42.75
Avg + 1SD			78			68
Avg + 2SD			104.5			93.25
Avg - 1SD			26			17.5
Avg - 2SD			-1.5			-7.75




FIG. 18C

FIG. 18D




FIG. 19A

Total Deep Sleep Scoring

Equations

20 yr old $y = -0.0063x^2 + 1.9255x - 46.537$

40 yr old $y = -0.0086x^2 + 1.9353x - 8.121$

60 yr old $y = -0.0123x^2 + 2.2326x$

80 yr old $y = -0.0144x^2 + 2.425x$

Deep Sleep minute:	20 y/o	40 y/o	60 y/o	80 y/o
0	0	0	0	0
10	0	10	21	23
20	0	27	40	43
30	6	42	56	60
40	20	56	70	74
50	34	67	81	85
60	46	77	90	94
70	57	85	96	99
80	67	92	100	100
90	76	96	100	100
100	83	99	100	100
110	89	100	100	100
120	94	100	100	100
130	97	100	100	100
140	100	100	100	100

FIG. 19B




FIG. 20

Table 1
Sleep structure and age

Sleep structure	Age (years)											P (one-way ANOVA)	Effect size ²	
	20-24 (n=106)	25-29 (n=130)	30-34 (n=129)	35-39 (n=119)	40-44 (n=128)	45-49 (n=126)	50-54 (n=87)	55-59 (n=79)	60-64 (n=48)	65-69 (n=40)	70-74 (n=26)			75-80 (n=24)
TST	376.3 ± 75.4	367.9 ± 78.4	364.0 ± 71.0	333.4 ± 82.9	338.0 ± 78.1	338.2 ± 74.9	316.9 ± 69.3	325.9 ± 70.9	329.1 ± 51.2	314.5 ± 80.5	292.0 ± 78.0	291.0 ± 66.0	<0.01	0.08
Eff	87.9 ± 9.5	86.1 ± 11.8	86.8 ± 8.6	81.6 ± 15.5	82.5 ± 12.2	81.3 ± 12.5	78.1 ± 13.0	77.7 ± 11.8	79.0 ± 9.6	74.9 ± 14.5	72.8 ± 17.3	65.4 ± 13.0	<0.01	0.13
Lat	13.8 ± 17.5	16.0 ± 20.1	14.5 ± 16.8	19.6 ± 32.7	13.4 ± 13.9	17.4 ± 21.0	17.8 ± 18.7	17.3 ± 18.3	17.3 ± 15.0	20.5 ± 28.7	28.7 ± 41.1	34.6 ± 45.9	0.01	0.03
REMIat	106.4 ± 50.9	97.5 ± 45.5	95.6 ± 44.3	89.8 ± 37.9	97.0 ± 47.5	102.5 ± 67.0	106.1 ± 58.6	109.8 ± 64.2	109.8 ± 65.4	95.0 ± 52.0	129.1 ± 83.1	120.9 ± 3.0	0.01	0.02
WASO	38.9 ± 35.5	44.4 ± 40.5	41.0 ± 30.2	55.0 ± 47.1	58.1 ± 45.8	61.0 ± 45.3	72.3 ± 47.7	78.1 ± 44.9	72.1 ± 37.4	84.1 ± 40.4	81.1 ± 49.2	121.6 ± 49.6	<0.01	0.14
AI	8.8 ± 4.6	10.4 ± 5.8	11.4 ± 6.7	12.5 ± 7.8	15.3 ± 10.6	16.3 ± 13.3	19.6 ± 15.3	19.0 ± 11.1	22.3 ± 14.6	20.9 ± 12.4	17.5 ± 8.8	21.8 ± 13.7	<0.01	0.14
RAI	1.9 ± 2.3	2.4 ± 3.9	3.3 ± 5.1	4.1 ± 5.3	5.9 ± 10.0	7.3 ± 11.3	9.0 ± 11.7	8.6 ± 9.4	13.9 ± 13.6	10.3 ± 9.9	9.6 ± 8.7	13.3 ± 15.2	<0.01	0.13
NRAI	7.1 ± 3.4	7.9 ± 3.8	8.2 ± 4.1	8.5 ± 5.1	9.4 ± 6.4	9.1 ± 5.3	10.7 ± 7.4	10.4 ± 6.3	6.9 ± 5.4	10.8 ± 8.3	8.1 ± 4.7	8.5 ± 5.2	<0.01	0.04
S1d	13.6 ± 9.6	14.3 ± 10.0	14.5 ± 8.8	12.7 ± 8.2	14.9 ± 10.7	16.0 ± 10.3	16.2 ± 13.0	17.3 ± 13.2	15.9 ± 9.4	13.7 ± 5.3	13.3 ± 6.6	18.2 ± 10.1	0.05	0.02
S2d	204.4 ± 52.1	197.4 ± 49.1	197.0 ± 54.6	177.7 ± 53.7	184.7 ± 49.7	181.9 ± 48.4	172.6 ± 47.3	185.4 ± 51.2	184.0 ± 38.5	178.4 ± 56.1	165.7 ± 61.0	169.9 ± 58.4	<0.01	0.04
SWSd	87.4 ± 26.5	83.7 ± 25.3	77.5 ± 25.9	75.4 ± 26.3	69.9 ± 28.9	70.7 ± 30.0	70.2 ± 25.2	63.4 ± 31.5	69.3 ± 26.5	67.2 ± 37.3	63.3 ± 27.0	53.6 ± 33.2	<0.01	0.07
REMI	70.9 ± 30.5	72.6 ± 33.5	75.0 ± 27.6	67.6 ± 28.6	69.5 ± 30.7	69.5 ± 32.3	57.8 ± 26.2	59.9 ± 29.9	60.0 ± 22.2	55.1 ± 22.9	49.6 ± 26.8	49.3 ± 20.6	<0.01	0.05
S1%	3.8 ± 2.9	4.3 ± 4.2	4.1 ± 2.8	4.3 ± 4.1	4.5 ± 3.0	4.8 ± 3.1	5.2 ± 4.0	5.4 ± 4.0	4.9 ± 2.9	4.9 ± 3.3	4.8 ± 2.2	6.4 ± 3.3	<0.01	0.02
S2%	54.2 ± 7.7	53.6 ± 8.5	53.8 ± 8.0	53.0 ± 8.2	56.0 ± 9.3	54.1 ± 9.6	54.5 ± 9.3	57.4 ± 11.6	55.9 ± 8.9	56.7 ± 11.2	55.4 ± 12.4	58.2 ± 13.1	<0.01	0.02
SWS%	23.6 ± 6.7	23.2 ± 6.7	21.8 ± 7.6	23.2 ± 7.7	20.9 ± 7.9	21.3 ± 8.7	22.5 ± 7.8	19.7 ± 9.6	21.1 ± 7.4	21.3 ± 10.2	23.3 ± 11.7	18.3 ± 10.4	<0.01	0.03
REM%	16.4 ± 6.0	19.0 ± 6.9	20.3 ± 5.5	19.5 ± 6.5	19.6 ± 6.4	19.7 ± 6.8	17.8 ± 6.7	17.8 ± 7.2	18.1 ± 5.7	17.0 ± 5.8	16.5 ± 7.1	17.0 ± 6.3	<0.01	0.03

ANOVA, analysis of variance; TST, total sleep time; Eff, sleep efficiency; Lat, sleep latency; REMIat, REM sleep latency (min); WASO, wake after sleep onset; AI, arousal index; RAI, respiratory arousal index; NRAI, non-respiratory arousal index; S1d, stage 1 duration (min); S2d, stage 2 duration (min); SWSd, skw wave sleep duration (min); REMI, REM sleep duration; S1% stage 1 percentage; S2% stage 2 percentage; SWS%, skw wave sleep percentage; REMI%, REM sleep percentage.

Values are mean ± SD.

FIG. 21

Averages and Standard Deviations For Sleep Efficiency				40 y/o				
20 Yr old				Moraes/Chayon NG SCORES				
Average Sleep Efficiency	88	96	92	85	82.2	92	87.1	85
Stnd Dev	9.5	4	6.75		12	4	8	
Stnd Dev %	11%	4%	7%		15%	4%	9%	
Avg								
Avg + 1 SD				92			87.1	85
Avg + 2 SD				98.75			95.1	95
Avg - 1 SD				105.5			103.1	100
Avg - 1 SD				85.25			79.1	70
Avg - 2 SD				78.5			71.1	35




FIG. 22A

FIG. 22B

	60 y/o			80 y/o		
	Moraes	Ohayon	NG SCORES	Moraes	Ohayon	NG SCORES
Average Sleep Effience	76	85.5	80.75	85	77	71
Stnd Dev	12	5	8.5	13	6	9.5
Stnd Dev %	16%	6%	11%	20%	8%	13%
Avg			80.75			71
Avg + 1 SD			89.25			80.5
Avg + 2 SD			97.75			90
Avg - 1 SD			72.25			61.5
Avg - 2 SD			63.75			52




FIG. 22D

FIG. 22C




FIG. 23A

Sleep Efficiency Scoring

Equations

- 20 yr old $y = -0.1019x^2 + 21.046x - 987.46$
- 40 yr old $y = -0.0725x^2 + 14.575x - 632.82$
- 60 yr old $y = -0.0643x^2 + 12.202x - 479.98$
- 80 yr old $y = -0.0514x^2 + 8.9367x - 288.89$

Deep Sleep r	20 y/o	40 y/o	60 y/o	80 y/o
0	0	0	0	0
10	0	0	0	0
20	0	0	0	0
30	0	0	0	0
40	0	0	0	0
50	0	0	0	29
60	0	0	21	62
70	0	32	59	85
80	44	69	85	97
90	81	92	97	99
100	98	100	100	100
110	100	100	100	100
120	100	100	100	100
130	100	100	100	100
140	100	100	100	100

FIG. 23B

Averages and Standard Deviations for Longest Deep Sleep

	NG	SCORES
Average Duration Deep Sleep	40	85
Std Dev	32	
Std Dev %	80%	
Avg	40	85
Avg + 1 SD	72	95
Avg + 2 SD	104	100
Avg - 1 SD	24	50
Avg - 2 SD	10	15

FIG. 24A




FIG. 24B

Longest Deep Sleep Scoring

$$y = -0.017x^2 + 2.7673x - 7.3885$$

0	0
10	19
20	41
30	60
40	76
50	88
60	97
70	100
80	100
90	100
100	100

FIG. 24C




FIG. 24D

Averages and Standard Deviations for Deep Sleep Strength

	NG	SCORES
Average Strength Deep Sleep	1.23	85
Stnd Dev	0.32	
Stnd Dev %	26%	
Avg power spectral density	1.23	85
Avg + 1 SD	1.55	95
Avg + 2 SD	1.87	100
Avg - 1 SD	1.07	70
Avg - 2 SD	0.91	35

FIG. 25A




FIG. 25B




FIG. 25C

Deep Sleep Strength Scoring

PSD	Score
0	0
0.2	0
0.4	0
0.6	0
0.8	20
1	54
1.2	79
1.4	95
1.6	100
1.8	100
2	100

$y = -113.59x^2 + 376.02x - 208.39$

FIG. 25D

Table 4. Gender Effects on 24-h Heart Rate Variability and Heart Rate for Four Age Groups

Age (yr) and Gender	SDNN (ms)	SDANN (ms)	SDNN Index (ms)	rMSSD (ms)	pNN50 (%)	HR (beats/min)
10-29						
M	182 ± 35	162 ± 33	88 ± 20	53 ± 18	26 ± 13	76 ± 10
F	147 ± 43	133 ± 42	66 ± 18	43 ± 18	17 ± 12	83 ± 8
30-49						
M	146 ± 30†	131 ± 31†	65 ± 14†	34 ± 13†	13 ± 10†	76 ± 7
F	129 ± 30	114 ± 31	58 ± 13	31 ± 10†	10 ± 7†	79 ± 7
50-69						
M	117 ± 30†‡	104 ± 28†‡	46 ± 18†‡	22 ± 8†‡	4 ± 5†‡	78 ± 11
F	125 ± 29	114 ± 29	49 ± 11†	25 ± 7†	5 ± 4†	74 ± 10†
70-99						
M	123 ± 24†	109 ± 28†	43 ± 12†‡	22 ± 5†‡	3 ± 2†‡	72 ± 11
F	114 ± 23†	102 ± 22†	38 ± 10†‡	22 ± 8†‡	4 ± 4†‡	73 ± 8†‡

*p < 0.05, male (M) versus female (F) in same age range. †p < 0.05, other groups versus age range 10 to 29 years for same gender. ‡p < 0.05, other groups versus age range 30 to 49 years for same gender. Data presented are mean value ± SD. Other abbreviations as in Table 2.

FIG. 26A

Age Range	Gender	rMSSD
18-25	Male	86.5
	Female	68.7
25-35	Male	66.0
	Female	55.7
35-45	Male	50.4
	Female	45.6
45-55	Male	39.6
	Female	41.7
55-65	Male	32.1
	Female	32.5
65-75	Male	30.6
	Female	24.8
75+	Male	33.1
	Female	25.5

FIG. 26B

Average rSMMD by age/gender/athletic

	Age	Athlete		Non Athlete	
		M -A	F -A	M -NA	F -NA
18-25	20	86.5	68.7	53	43
25-35	30	66	55.7	41	37
35-45	40	50.4	45.6	35	32
45-55	50	39.6	41.7	30	28
55-65	60	32	32.5	24	26
65-75	70	30.6	24.8	23	24
75-85	80	33.1	25.5	21	22

from elite

from umetani

FIG. 26C




FIG. 27B

FIG. 27A




FIG. 27D

FIG. 27C

Average rSMMD by Age/Gender/Athletic




FIG. 28

Sleep Quality Score		Weighting		Night 1				Night 2				Night 3				
Quantity of Sleep	30%	80	48					80	48.5					77	45.5	
Deep Sleep Time	40%	80	38					85	35					57	34.5	
Sleep Efficiency	30%	80	15					59	15					56.7	15.5	
			63						72						62	
Sleep Disrupt Score		Weighting		Night 1				Night 2				Night 3				
50% Deep Sleep	30%	80	48					80	38					57	35	
Longest Continuous Deep Sleep	30%	80	15					74	7					44	4	
Strength of Deep Sleep	30%	80	15					57	18					58.3	7	
			63						51						47	
				Night 1: All yr old (User) has a good quantity of sleep (8h) but not enough Deep Sleep (30 min)				Night 2: User has about sleep (8h, 45m), so is short on all stages of sleep				Night 3: User falls asleep fast, but wakes up and can't get back to sleep. Short Deep Sleep				
Sleep Totals		Actual	Target	Target	Actual	%	Actual	Target	Target	Actual	%	Actual	Target	Target	Actual	%
		H:M	H:M	H:M	H:M		H:M	H:M	H:M	H:M		H:M	H:M	H:M	H:M	
Deep Sleep		1:18	1:30	1:30	0	0%	1:46	1:30	1:30	26	20%	2:12	1:30	1:30	32	19%
Light Sleep		5:14	1:30	1:30	20	100%	1:30	1:30	1:30	20	100%	4:20	1:30	1:30	28	17%
REM Sleep		1:05	1:07	1:07	0	0%	1:40	1:07	1:07	40	38%	1:40	1:07	1:07	17	16%
WAKE		5:30	0	0	0	0%	0	0	0	0	0%	1:00	0	0	0	0%
Total Time in Bed		8:5		8:0	8:0	100%	8:34	8:0	8:0	814	100%	7:59	8:0	8:0	69	86%
Sleep Cycles		Start	End	Duration	Start	End	Duration	Start	End	Duration	Start	End	Duration	Start	End	Duration
		H:M	H:M	minutes	H:M	H:M	minutes	H:M	H:M	minutes	H:M	H:M	minutes	H:M	H:M	minutes
cycle 1	WAKE	5:30	5:30	0	0:0	0:0	0	0:0	0:0	0	0:0	0:0	0	0:0	0:0	0
cycle 1	Light	5:30	5:37	7	0:0	0:0	7	0:0	0:0	7	0:0	0:0	7	0:0	0:0	7
cycle 1	Deep	5:37	5:39	2	0:0	0:0	2	0:0	0:0	2	0:0	0:0	2	0:0	0:0	2
cycle 1	REM	5:39	5:40	1	0:0	0:0	1	0:0	0:0	1	0:0	0:0	1	0:0	0:0	1
cycle 1	Light	5:40	5:42	2	0:0	0:0	2	0:0	0:0	2	0:0	0:0	2	0:0	0:0	2
cycle 2	WAKE	5:42	5:42	0	0:0	0:0	0	0:0	0:0	0	0:0	0:0	0	0:0	0:0	0
cycle 2	Light	5:42	5:47	5	0:0	0:0	5	0:0	0:0	5	0:0	0:0	5	0:0	0:0	5
cycle 2	Deep	5:47	5:50	3	0:0	0:0	3	0:0	0:0	3	0:0	0:0	3	0:0	0:0	3
cycle 2	REM	5:50	5:51	1	0:0	0:0	1	0:0	0:0	1	0:0	0:0	1	0:0	0:0	1
cycle 2	Light	5:51	5:52	1	0:0	0:0	1	0:0	0:0	1	0:0	0:0	1	0:0	0:0	1
cycle 3	WAKE	5:52	5:52	0	0:0	0:0	0	0:0	0:0	0	0:0	0:0	0	0:0	0:0	0
cycle 3	Light	5:52	5:54	2	0:0	0:0	2	0:0	0:0	2	0:0	0:0	2	0:0	0:0	2
cycle 3	Deep	5:54	5:57	3	0:0	0:0	3	0:0	0:0	3	0:0	0:0	3	0:0	0:0	3
cycle 3	REM	5:57	5:58	1	0:0	0:0	1	0:0	0:0	1	0:0	0:0	1	0:0	0:0	1
cycle 3	Light	5:58	5:59	1	0:0	0:0	1	0:0	0:0	1	0:0	0:0	1	0:0	0:0	1
cycle 4	WAKE	5:59	5:59	0	0:0	0:0	0	0:0	0:0	0	0:0	0:0	0	0:0	0:0	0
cycle 4	Light	5:59	6:00	1	0:0	0:0	1	0:0	0:0	1	0:0	0:0	1	0:0	0:0	1
cycle 4	Deep	6:00	6:01	1	0:0	0:0	1	0:0	0:0	1	0:0	0:0	1	0:0	0:0	1
cycle 4	REM	6:01	6:02	1	0:0	0:0	1	0:0	0:0	1	0:0	0:0	1	0:0	0:0	1
cycle 4	Light	6:02	6:03	1	0:0	0:0	1	0:0	0:0	1	0:0	0:0	1	0:0	0:0	1
cycle 5	WAKE	6:03	6:03	0	0:0	0:0	0	0:0	0:0	0	0:0	0:0	0	0:0	0:0	0
cycle 5	Light	6:03	6:04	1	0:0	0:0	1	0:0	0:0	1	0:0	0:0	1	0:0	0:0	1
cycle 5	Deep	6:04	6:05	1	0:0	0:0	1	0:0	0:0	1	0:0	0:0	1	0:0	0:0	1
cycle 5	REM	6:05	6:06	1	0:0	0:0	1	0:0	0:0	1	0:0	0:0	1	0:0	0:0	1
cycle 5	Light	6:06	6:07	1	0:0	0:0	1	0:0	0:0	1	0:0	0:0	1	0:0	0:0	1
TOTAL				H:M	minutes	Summary Total		H:M	minutes	Summary Total		H:M	minutes	Summary Total		Summary Total
TOTAL	WAKE			0:0	0	0		0:0	0	0		0:0	0	0	0	0
TOTAL	Light			21	21	21		21	21	21		21	21	21	21	21
TOTAL	Deep			9	9	9		9	9	9		9	9	9	9	9
TOTAL	REM			4	4	4		4	4	4		4	4	4	4	4
TOTAL	SLEEP TIME with Wake			7:47	465	465		8:45	505	505		8:7	491	491	491	
Time in Bed				8:5	495	495		8:52	514	514		7:59	474	474	474	
TOTAL DEEP SLEEP				9:00	Target: 9:00	9:00		9:00	Target: 9:00	9:00		9:00	Target: 9:00	9:00	Target: 9:00	9:00
cycle 1				9:00	9:00	9:00		9:00	9:00	9:00		9:00	9:00	9:00	9:00	9:00
cycle 2				9:00	9:00	9:00		9:00	9:00	9:00		9:00	9:00	9:00	9:00	9:00
cycle 3				9:00	9:00	9:00		9:00	9:00	9:00		9:00	9:00	9:00	9:00	9:00
cycle 4				9:00	9:00	9:00		9:00	9:00	9:00		9:00	9:00	9:00	9:00	9:00
cycle 5				9:00	9:00	9:00		9:00	9:00	9:00		9:00	9:00	9:00	9:00	9:00
cycle 6				9:00	9:00	9:00		9:00	9:00	9:00		9:00	9:00	9:00	9:00	9:00
cycle 7				9:00	9:00	9:00		9:00	9:00	9:00		9:00	9:00	9:00	9:00	9:00
cycle 8				9:00	9:00	9:00		9:00	9:00	9:00		9:00	9:00	9:00	9:00	9:00
cycle 9				9:00	9:00	9:00		9:00	9:00	9:00		9:00	9:00	9:00	9:00	9:00
cycle 10				9:00	9:00	9:00		9:00	9:00	9:00		9:00	9:00	9:00	9:00	9:00
cycle 11				9:00	9:00	9:00		9:00	9:00	9:00		9:00	9:00	9:00	9:00	9:00
cycle 12				9:00	9:00	9:00		9:00	9:00	9:00		9:00	9:00	9:00	9:00	9:00
cycle 13				9:00	9:00	9:00		9:00	9:00	9:00		9:00	9:00	9:00	9:00	9:00
cycle 14				9:00	9:00	9:00		9:00	9:00	9:00		9:00	9:00	9:00	9:00	9:00
cycle 15				9:00	9:00	9:00		9:00	9:00	9:00		9:00	9:00	9:00	9:00	9:00
cycle 16				9:00	9:00	9:00		9:00	9:00	9:00		9:00	9:00	9:00	9:00	9:00
cycle 17				9:00	9:00	9:00		9:00	9:00	9:00		9:00	9:00	9:00	9:00	9:00
cycle 18				9:00	9:00	9:00		9:00	9:00	9:00		9:00	9:00	9:00	9:00	9:00
cycle 19				9:00	9:00	9:00		9:00	9:00	9:00		9:00	9:00	9:00	9:00	9:00
cycle 20				9:00	9:00	9:00		9:00	9:00	9:00		9:00	9:00	9:00	9:00	9:00
cycle 21				9:00	9:00	9:00		9:00	9:00	9:00		9:00	9:00	9:00	9:00	9:00
cycle 22				9:00	9:00	9:00		9:00	9:00	9:00		9:00	9:00	9:00	9:00	9:00
cycle 23				9:00	9:00	9:00		9:00	9:00	9:00		9:00	9:00	9:00	9:00	9:00
cycle 24				9:00	9:00	9:00		9:00	9:00	9:00		9:00	9:00	9:00	9:00	9:00
cycle 25				9:00	9:00	9:00		9:00	9:00	9:00		9:00	9:00	9:00	9:00	9:00
cycle 26				9:00	9:00	9:00		9:00	9:00	9:00		9:00	9:00	9:00	9:00	9:00
cycle 27				9:00	9:00	9:00		9:00	9:00	9:00		9:00	9:00	9:00	9:00	9:00
cycle 28				9:00	9:00	9:00		9:00	9:00	9:00		9:00	9:00	9:00	9:00	9:00
cycle 29				9:00	9:00	9:00		9:00	9:00	9:00		9:00	9:00	9:00	9:00	9:00
cycle 30				9:00	9:00	9:00		9:00	9:00	9:00		9:00	9:00	9:00	9:00	9:00
cycle 31				9:00	9:00	9:00		9:00	9:00	9:00		9:00	9:00	9:00	9:00	9:00
cycle 32				9:00	9:00	9:00		9:00	9:00	9:00		9:00	9:00	9:00	9:00	9:00
cycle 33				9:00	9:00	9:00		9:00	9:00	9:00		9:00	9:00	9:00	9:00	9:00
cycle 34				9:00	9:00	9:00		9:00	9:00	9:00						

Sleep Quality Score		Night 1		Night 2	
Quantity of Sleep	80%	80	80	80	80
Deep Sleep Total	40%	40	40	40	40
Deep Sleep %	50%	50	50	50	50
Stages of Sleep					
Light Sleep	30%	30	30	30	30
REM Sleep	20%	20	20	20	20
Wake	30%	30	30	30	30
Night 4: User has good night sleep - 8 hours, good across all stages					
Night 5: User has good quality sleep but not enough Deep Sleep					
Sleep Table					
	Actual	Target	Target	Actual	%
	H:M	H:M	H:M	H:M	%
Deep Sleep	1:00	1:00	1:00	1:00	100%
Light Sleep	2:00	2:00	2:00	2:00	100%
REM	1:00	1:00	1:00	1:00	100%
Wake	1:00	1:00	1:00	1:00	100%
Time in Bed	5:00	5:00	5:00	5:00	100%
Stages of Sleep					
	Start	End	Stages	Start	End
	H:M	H:M	Stages	H:M	H:M
Stage 1	0:00	0:05	Wake	0:00	0:05
Stage 2	0:05	0:15	Light	0:05	0:15
Stage 3	0:15	0:30	Light	0:15	0:30
Stage 4	0:30	0:45	REM	0:30	0:45
Stage 5	0:45	0:55	Light	0:45	0:55
Stage 6	0:55	1:00	Wake	0:55	1:00
Stage 7	1:00	1:15	Light	1:00	1:15
Stage 8	1:15	1:30	Light	1:15	1:30
Stage 9	1:30	1:45	REM	1:30	1:45
Stage 10	1:45	2:00	Light	1:45	2:00
Stage 11	2:00	2:15	Light	2:00	2:15
Stage 12	2:15	2:30	REM	2:15	2:30
Stage 13	2:30	2:45	Light	2:30	2:45
Stage 14	2:45	3:00	Light	2:45	3:00
Stage 15	3:00	3:15	REM	3:00	3:15
Stage 16	3:15	3:30	Light	3:15	3:30
Stage 17	3:30	3:45	Light	3:30	3:45
Stage 18	3:45	4:00	REM	3:45	4:00
Stage 19	4:00	4:15	Light	4:00	4:15
Stage 20	4:15	4:30	Light	4:15	4:30
Stage 21	4:30	4:45	REM	4:30	4:45
Stage 22	4:45	5:00	Light	4:45	5:00
Stage 23	5:00	5:15	Light	5:00	5:15
Stage 24	5:15	5:30	REM	5:15	5:30
Stage 25	5:30	5:45	Light	5:30	5:45
Stage 26	5:45	6:00	Light	5:45	6:00
Stage 27	6:00	6:15	REM	6:00	6:15
Stage 28	6:15	6:30	Light	6:15	6:30
Stage 29	6:30	6:45	Light	6:30	6:45
Stage 30	6:45	7:00	REM	6:45	7:00
Stage 31	7:00	7:15	Light	7:00	7:15
Stage 32	7:15	7:30	Light	7:15	7:30
Stage 33	7:30	7:45	REM	7:30	7:45
Stage 34	7:45	8:00	Light	7:45	8:00
Stage 35	8:00	8:15	Light	8:00	8:15
Stage 36	8:15	8:30	REM	8:15	8:30
Stage 37	8:30	8:45	Light	8:30	8:45
Stage 38	8:45	9:00	Light	8:45	9:00
Stage 39	9:00	9:15	REM	9:00	9:15
Stage 40	9:15	9:30	Light	9:15	9:30
Stage 41	9:30	9:45	Light	9:30	9:45
Stage 42	9:45	10:00	REM	9:45	10:00
Stage 43	10:00	10:15	Light	10:00	10:15
Stage 44	10:15	10:30	Light	10:15	10:30
Stage 45	10:30	10:45	REM	10:30	10:45
Stage 46	10:45	11:00	Light	10:45	11:00
Stage 47	11:00	11:15	Light	11:00	11:15
Stage 48	11:15	11:30	REM	11:15	11:30
Stage 49	11:30	11:45	Light	11:30	11:45
Stage 50	11:45	12:00	Light	11:45	12:00
Stage 51	12:00	12:15	REM	12:00	12:15
Stage 52	12:15	12:30	Light	12:15	12:30
Stage 53	12:30	12:45	Light	12:30	12:45
Stage 54	12:45	1:00	REM	12:45	1:00
Stage 55	1:00	1:15	Light	1:00	1:15
Stage 56	1:15	1:30	Light	1:15	1:30
Stage 57	1:30	1:45	REM	1:30	1:45
Stage 58	1:45	2:00	Light	1:45	2:00
Stage 59	2:00	2:15	Light	2:00	2:15
Stage 60	2:15	2:30	REM	2:15	2:30
Stage 61	2:30	2:45	Light	2:30	2:45
Stage 62	2:45	3:00	Light	2:45	3:00
Stage 63	3:00	3:15	REM	3:00	3:15
Stage 64	3:15	3:30	Light	3:15	3:30
Stage 65	3:30	3:45	Light	3:30	3:45
Stage 66	3:45	4:00	REM	3:45	4:00
Stage 67	4:00	4:15	Light	4:00	4:15
Stage 68	4:15	4:30	Light	4:15	4:30
Stage 69	4:30	4:45	REM	4:30	4:45
Stage 70	4:45	5:00	Light	4:45	5:00
Stage 71	5:00	5:15	Light	5:00	5:15
Stage 72	5:15	5:30	REM	5:15	5:30
Stage 73	5:30	5:45	Light	5:30	5:45
Stage 74	5:45	6:00	Light	5:45	6:00
Stage 75	6:00	6:15	REM	6:00	6:15
Stage 76	6:15	6:30	Light	6:15	6:30
Stage 77	6:30	6:45	Light	6:30	6:45
Stage 78	6:45	7:00	REM	6:45	7:00
Stage 79	7:00	7:15	Light	7:00	7:15
Stage 80	7:15	7:30	Light	7:15	7:30
Stage 81	7:30	7:45	REM	7:30	7:45
Stage 82	7:45	8:00	Light	7:45	8:00
Stage 83	8:00	8:15	Light	8:00	8:15
Stage 84	8:15	8:30	REM	8:15	8:30
Stage 85	8:30	8:45	Light	8:30	8:45
Stage 86	8:45	9:00	Light	8:45	9:00
Stage 87	9:00	9:15	REM	9:00	9:15
Stage 88	9:15	9:30	Light	9:15	9:30
Stage 89	9:30	9:45	Light	9:30	9:45
Stage 90	9:45	10:00	REM	9:45	10:00
Stage 91	10:00	10:15	Light	10:00	10:15
Stage 92	10:15	10:30	Light	10:15	10:30
Stage 93	10:30	10:45	REM	10:30	10:45
Stage 94	10:45	11:00	Light	10:45	11:00
Stage 95	11:00	11:15	Light	11:00	11:15
Stage 96	11:15	11:30	REM	11:15	11:30
Stage 97	11:30	11:45	Light	11:30	11:45
Stage 98	11:45	12:00	Light	11:45	12:00
Stage 99	12:00	12:15	REM	12:00	12:15
Stage 100	12:15	12:30	Light	12:15	12:30
Stage 101	12:30	12:45	Light	12:30	12:45
Stage 102	12:45	1:00	REM	12:45	1:00
Stage 103	1:00	1:15	Light	1:00	1:15
Stage 104	1:15	1:30	Light	1:15	1:30
Stage 105	1:30	1:45	REM	1:30	1:45
Stage 106	1:45	2:00	Light	1:45	2:00
Stage 107	2:00	2:15	Light	2:00	2:15
Stage 108	2:15	2:30	REM	2:15	2:30
Stage 109	2:30	2:45	Light	2:30	2:45
Stage 110	2:45	3:00	Light	2:45	3:00
Stage 111	3:00	3:15	REM	3:00	3:15
Stage 112	3:15	3:30	Light	3:15	3:30
Stage 113	3:30	3:45	Light	3:30	3:45
Stage 114	3:45	4:00	REM	3:45	4:00
Stage 115	4:00	4:15	Light	4:00	4:15
Stage 116	4:15	4:30	Light	4:15	4:30
Stage 117	4:30	4:45	REM	4:30	4:45
Stage 118	4:45	5:00	Light	4:45	5:00
Stage 119	5:00	5:15	Light	5:00	5:15
Stage 120	5:15	5:30	REM	5:15	5:30
Stage 121	5:30	5:45	Light	5:30	5:45
Stage 122	5:45	6:00	Light	5:45	6:00
Stage 123	6:00	6:15	REM	6:00	6:15
Stage 124	6:15	6:30	Light	6:15	6:30
Stage 125	6:30	6:45	Light	6:30	6:45
Stage 126	6:45	7:00	REM	6:45	7:00
Stage 127	7:00	7:15	Light	7:00	7:15
Stage 128	7:15	7:30	Light	7:15	7:30
Stage 129	7:30	7:45	REM	7:30	7:45
Stage 130	7:45	8:00	Light	7:45	8:00
Stage 131	8:00	8:15	Light	8:00	8:15
Stage 132	8:15	8:30	REM	8:15	8:30
Stage 133	8:30	8:45	Light	8:30	8:45
Stage 134	8:45	9:00	Light	8:45	9:00
Stage 135	9:00	9:15	REM	9:00	9:15
Stage 136	9:15	9:30	Light	9:15	9:30
Stage 137	9:30	9:45	Light	9:30	9:45
Stage 138	9:45	10:00	REM	9:45	10:00
Stage 139	10:00	10:15	Light	10:00	10:15
Stage 140	10:15	10:30	Light	10:15	10:30
Stage 141	10:30	10:45	REM	10:30	10:45
Stage 142	10:45	11:00	Light	10:45	11:00
Stage 143	11:00	11:15	Light	11:00	11:15
Stage 144	11:15	11:30	REM	11:15	11:30
Stage 145	11:30	11:45	Light	11:30	11:45
Stage 146	11:45	12:00	Light	11:45	12:00
Stage 147	12:00	12:15	REM	12:00	12:15
Stage 148	12:15	12:30	Light	12:15	12:30
Stage 149	12:30	12:45	Light	12:30	12:45
Stage 150	12:45	1:00	REM	12:45	1:00
Stage 151	1:00	1:15	Light	1:00	1:15
Stage 152	1:15	1:30	Light	1:15	1:30
Stage 153	1:30	1:45	REM	1:30	1:45
Stage 154	1:45	2:00	Light	1:45	2:00
Stage 155	2:00	2:15	Light	2:00	2:15
Stage 156	2:15	2:30	REM	2:15	2:30
Stage 157	2:30	2:45	Light	2:30	2:45
Stage 158	2:45	3:00	Light	2:45	3:00
Stage 159	3:00	3:15	REM	3:00	3:15
Stage 160	3:15	3:30	Light	3:15	3:30
Stage 161	3:30	3:45	Light	3:30	3:45
Stage 162	3:45	4:00	REM	3:45	4:00
Stage 163	4:00	4:15	Light	4:00	4:15
Stage 164	4:15	4:30	Light	4:15	4:30
Stage 165	4:30	4:45	REM	4:30	4:45
Stage 166	4:45	5:00	Light	4:45	5:00
Stage 167	5:00	5:15	Light	5:00	5:15
Stage 168	5:15	5:30	REM	5:15	5:30
Stage 169	5:30	5:45	Light	5:30	5:45
Stage 170	5:45	6:00	Light	5:45	6:00
Stage 171	6:00	6:15	REM	6:00	6:15
Stage 172	6:15	6:30	Light	6:15	6:30
Stage 173	6:30				



FIG. 30A




FIG. 30B




FIG. 30C




FIG. 30D




FIG. 30E




FIG. 30F

SLEEP PERFORMANCE SYSTEM AND METHOD OF USE

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application claims priority to U.S. Provisional Patent Application No. 62/568,249, filed on Oct. 4, 2017 and U.S. Provisional Patent Application No. 62/661,932, filed on Apr. 24, 2018, the contents of which are incorporated herein by reference in their entireties.

BACKGROUND

1. Technical Field

[0002] This disclosure relates generally to the field of sleep performance and more specifically to systems and methods that can improve the quality of sleep.

2. Background of the Art

[0003] Inadequate sleep is a public health problem. An estimated 70 million Americans suffer from chronic sleep disorders.

[0004] Insufficient sleep can impact every aspect of a person's health. For example, insufficient sleep can lead to serious health issues, including Alzheimer's, heart disease, and cancer. Insufficient sleep can also reduce cognitive and physical performance and contribute to stress.

[0005] Previous efforts to improve sleep have focused on increasing sleep quantity, but not on sleep quality. However, sleep quality—which is associated with deep sleep—is just as important as quantity, as deep sleep is critical for brain and body repair and recovery. Further, current sleep aids that focus on sleep quantity often have counterproductive side effects that actually impair sleep quality. Current sleep aids not only do not provide an objective measure of sleep improvement other than overall quantity, they also fail to positively influence deep sleep.

[0006] A need therefore exists to address this deficiency by developing a solution that can accurately monitor sleep and provide objective and trackable measures of sleep performance such as sleep quality, and more specifically, of deep sleep quality. Current sleep aids also further demonstrate that a need exists for a solution that can specifically target deep sleep quality and improve it.

BRIEF SUMMARY

[0007] This disclosure relates generally to sleep performance systems and methods of use that can improve sleep quality.

[0008] More specifically, systems and methods for increasing the quality and quantity of slow-wave sleep are disclosed.

[0009] The systems disclosed can include sleep monitoring systems. For example, systems are disclosed that can include one or more electroencephalography (EEG) electrodes configured to measure a user's brain activity during sleep. The systems can include a processor configured to quantify the quality of the user's slow-wave sleep by determining one or more sleep performance scores associated with the measured brain activity.

[0010] The methods disclosed can include methods for quantifying the quality of a user's sleep. For example, methods are disclosed that can include measuring, via one or

more electroencephalography (EEG) biosensors, a user's brain activity during sleep. The methods can include quantifying, via a computer system, a quality of the user's slow-wave sleep by determining one or more sleep performance scores associated with the measured brain activity.

[0011] The methods disclosed can include methods for quantifying the quality of a user's sleep. For example, methods are disclosed that can include measuring, via one or more electroencephalography (EEG) sensors, a user's brain activity during sleep. The methods can include determining, via a computer system, one or more parameters associated with the measured brain activity. The methods can include calculating, via the computer system, one or more sleep performance scores associated with one or more of the determined parameters, wherein at least one sleep performance score is an objective measure of sleep quality.

[0012] The methods disclosed can include methods for quantifying a sleep quality score of a subject. For example, methods are disclosed that can include measuring one or more parameters relating to a brain activity of the subject. The methods can include determining a total sleep time based upon a function of a total amount of sleep measured from the subject. The methods can include determining a deep sleep parameter based upon a function of a total amount of deep sleep time measured from the subject. The methods can include determining a sleep efficiency parameter based upon a function of sleep efficiency measured from the subject. The methods can include calculating the sleep quality score based upon a weighting of the total sleep time, deep sleep parameter, and sleep efficiency parameter.

[0013] The methods disclosed can include methods for quantifying a brain fitness score of a subject. For example, methods are disclosed that can include measuring one or more parameters relating to a brain activity of the subject. The methods can include determining a total deep sleep time based upon a function of a total amount of deep sleep measured from the subject. The methods can include determining a longest deep sleep parameter based upon a function of a total amount of longest deep sleep time measured from the subject. The methods can include determining a deep sleep strength parameter based upon a function of deep sleep strength measured from the subject. The methods can include calculating the brain fitness score based upon a weighting of the total deep sleep time, longest deep sleep parameter, and deep sleep strength parameter.

BRIEF DESCRIPTION OF THE DRAWINGS

[0014] The drawings shown and described are exemplary embodiments and non-limiting. Like reference numerals indicate identical or functionally equivalent features throughout.

[0015] FIG. 1A illustrates a variation of a sleep performance system and a method of use.

[0016] FIG. 1B illustrates a variation of a data acquisition device.

[0017] FIG. 2A illustrates a variation of total sleep reference data.

[0018] FIG. 2B illustrates a variation of total deep sleep reference data.

[0019] FIG. 2C illustrates a variation of sleep efficiency reference data.

[0020] FIG. 2D illustrates a variation of longest deep sleep reference data.

- [0021] FIG. 2E illustrates a variation of deep sleep deficit reference data.
- [0022] FIG. 3A illustrates a variation of total sleep reference data.
- [0023] FIG. 3B illustrates a variation of total deep sleep reference data.
- [0024] FIG. 3C illustrates a variation of sleep efficiency reference data.
- [0025] FIG. 3D illustrates a variation of longest deep sleep reference data.
- [0026] FIG. 3E illustrates a variation of strength of deep sleep reference data.
- [0027] FIG. 4A illustrates a variation of a data set generatable/generated by the system of FIG. 1A.
- [0028] FIG. 4B illustrates a variation of RMSSD reference data.
- [0029] FIG. 4C illustrates a variation of RMSSD reference data.
- [0030] FIG. 5 illustrates a variation of a lookup table.
- [0031] FIG. 6 illustrates a variation of a process undertaken by the system.
- [0032] FIG. 7A illustrates a variation of a method for determining total sleep points.
- [0033] FIG. 7B illustrates a variation of a method for determining total deep sleep points.
- [0034] FIG. 7C illustrates a variation of a method for determining sleep efficiency points.
- [0035] FIG. 7D illustrates a variation of a method for determining longest deep sleep points.
- [0036] FIG. 7E illustrates a variation of a method for determining deep sleep deficit points.
- [0037] FIG. 8A illustrates a variation of a method for determining total sleep points.
- [0038] FIG. 8B illustrates a variation of a method for determining total deep sleep points.
- [0039] FIG. 8C illustrates a variation of a method for determining sleep efficiency points.
- [0040] FIG. 8D illustrates a variation of a method for determining longest deep sleep points.
- [0041] FIG. 8E illustrates a variation of a method for determining strength of deep sleep points.
- [0042] FIG. 9A illustrates a variation of a method for determining a variation of a sleep quality score.
- [0043] FIG. 9B illustrates a variation of a method for determining a variation of a sleep quality score.
- [0044] FIG. 10A illustrates a variation of a method for determining a variation of a brain fitness score.
- [0045] FIG. 10B illustrates a variation of a method for determining a variation of a brain fitness score.
- [0046] FIG. 11A illustrates a variation of a graphical user interface.
- [0047] FIG. 11B illustrates a variation of a graphical user interface.
- [0048] FIG. 11C illustrates a variation of a graphical user interface.
- [0049] FIG. 11D illustrates a variation of a graphical user interface.
- [0050] FIG. 11E illustrates a variation of a graphical user interface.
- [0051] FIG. 11F illustrates a variation of a graphical user interface.
- [0052] FIG. 11G illustrates a variation of a graphical user interface.
- [0053] FIG. 11H illustrates a variation of a graphical user interface.
- [0054] FIG. 11I illustrates a variation of a graphical user interface.
- [0055] FIG. 11J illustrates a variation of a graphical user interface.
- [0056] FIGS. 12A and 12B illustrate a variation of exemplary research data.
- [0057] FIGS. 13A and 13B illustrate a variation of exemplary cohort categories selected from the research data of FIGS. 12A and 12B.
- [0058] FIGS. 14A-14D illustrate a variation of a method for deriving total sleep time cohort curves.
- [0059] FIG. 15A illustrates a variation of total sleep time cohort curves derived from the method illustrated in FIGS. 14A-14D.
- [0060] FIG. 15B illustrates a variation of a table of exemplary total sleep time scores using the cohort curves of FIG. 15A.
- [0061] FIG. 16 illustrates a variation of exemplary research data.
- [0062] FIGS. 17A and 17B illustrate a variation of exemplary cohorts selected from the research data of FIGS. 12A and 16.
- [0063] FIGS. 18A-18D illustrate a variation of a method for deriving total deep sleep cohort curves.
- [0064] FIG. 19A illustrates a variation of total deep sleep cohort curves derived from the method illustrated in FIGS. 18A-18D.
- [0065] FIG. 19B illustrates a variation of a table of exemplary total deep sleep scores using the cohort curves of FIG. 19A.
- [0066] FIG. 20 illustrates a variation of exemplary research data and a variation of exemplary cohorts selected from the illustrated research data.
- [0067] FIG. 21 illustrates a variation of exemplary cohorts selected from the research data of FIG. 12A.
- [0068] FIGS. 22A-22D illustrate a variation of a method for deriving sleep efficiency cohort curves.
- [0069] FIG. 23A illustrates a variation of sleep efficiency cohort curves derived from the method illustrated in FIGS. 22A-22D.
- [0070] FIG. 23B illustrates a variation of a table of exemplary sleep efficiency scores using the cohort curves of FIG. 23A.
- [0071] FIG. 24A illustrates a variation of a table of exemplary longest deep sleep statistics.
- [0072] FIG. 25B illustrates a variation of a longest deep sleep reference curve derived from the statistics illustrated in FIG. 24A.
- [0073] FIG. 24C illustrates a variation of a table of exemplary longest deep sleep scores using the reference curve of FIG. 24B.
- [0074] FIG. 24D illustrates another variation of a longest deep sleep reference curve.
- [0075] FIG. 25A illustrates a variation of a table of exemplary deep sleep strength statistics.
- [0076] FIG. 25B illustrates a variation of a deep sleep strength reference curve derived from the statistics illustrated in FIG. 25A.
- [0077] FIG. 25C illustrates a variation of a deep sleep strength reference curve derived from the reference curve illustrated in FIG. 25B.

[0078] FIG. 25D illustrates a variation of a table of exemplary deep sleep strength scores using the reference curve of FIG. 25C.

[0079] FIG. 26A illustrates a variation of exemplary heart rate variability (HRV) data.

[0080] FIG. 26B illustrates a variation of exemplary HRV data.

[0081] FIG. 26C illustrates a variation of exemplary HRV data.

[0082] FIGS. 27A-27D illustrate a variation of a method for deriving HRV cohort curves.

[0083] FIG. 28 illustrates a variation of HRV cohort curves.

[0084] FIGS. 29A and 29B illustrate a variation of sleep data acquired on five different nights and a variation of various analyses performed on the data.

[0085] FIG. 30A illustrates a variation of a graphical display.

[0086] FIG. 30B illustrates a variation of a graphical display.

[0087] FIG. 30C illustrates a variation of a graphical display.

[0088] FIG. 30D illustrates a variation of a graphical display.

[0089] FIG. 30E illustrates a variation of a graphical display.

[0090] FIG. 30F illustrates a variation of a graphical display.

DETAILED DESCRIPTION

[0091] Systems and methods are disclosed that can collect sleep data, analyze sleep data, determine one or more sleep performance metrics, make recommendations to improve the quality and/or quantity of a user's sleep, or any combination thereof. The systems and methods disclosed can electronically analyze sleep data and determine sleep performance metrics, for example, by executing computer algorithms. The systems and methods disclosed can recommend ways to improve sleep performance based on a value and/or property of one or more of the determined metrics. The systems and methods disclosed can determine objective and trackable measures of sleep (e.g., metrics associated with sleep quality and/or sleep quantity) that can be used as decision thresholds when making sleep improvement recommendations. The recommendations can be designed to improve sleep quality and/or sleep quantity. The recommendations can include advice, encouragement, constructive criticism, audio stimulation, visual stimulation, cranial electrical stimulation, or any combination thereof. The systems and methods disclosed can provide audio stimulation, visual stimulation, cranial electrical stimulation, or any combination thereof, for example, in response to the system recommending such stimulation and/or as a result of user input instructing the system to provide such stimulation (e.g., with or without a recommendation from the system).

System and Apparatus

[0092] FIG. 1A illustrates a variation of a sleep performance system 10. The system 10 can have a data acquisition device 12 and a data display device 20. The data acquisition device 12 can acquire or otherwise collect sleep data, for example, when a user (e.g., a person) is sleeping. The data acquisition device 12 and/or the data display device 20 can

analyze the collected sleep data to determine one or more sleep parameters, derive one or more sleep metrics, calculate one or more sleep performance scores, make sleep related observations, make sleep related recommendations, or any combination thereof. The data acquisition device 12 and/or the data display device 20 can electronically display one or more results from the data analysis to inform the user of one or more aspects of their sleep performance. The data acquisition and display devices 12, 20 can be in wired or wireless communication with one another. The data acquisition and display devices 12, 20 can be in wired or wireless communication with a remote server.

[0093] FIG. 1A illustrates that the data acquisition device 12 can have a body 14 and one or more edges 16. The body 14 can be a breathable material, for example a mesh material. The breathable material can be configured to allow air to flow across the body 14. The breathable material can advantageously make the data acquisition device 12 more comfortable by allowing the skin beneath the body 14 to breathe. The breathable material can be elastic and/or inelastic. The body 14 can have one or more body first regions 14a and/or one or more body second regions 14b. The body first regions 14a can be more elastic (e.g., can stretch more) than the body second regions 14b. For example, the body first regions 14a can be made of an elastic mesh and the body second regions 14b can be made of a less elastic mesh and/or of an inelastic mesh. The body second regions 14b can form ridges configured to lessen the downward force that the body first regions 14a can exert against the head 8. This can increase the comfort of the data acquisition device 12 during use by making it feel less tight when attached to a user's head (e.g., head 8). For example, the body second regions 14b can be configured to raise the body first regions 14a off underlying tissue or hair. The elastic properties of the body 14 can be configured to inhibit or prevent the data acquisition device 12 from slipping during use, such as when the user moves during sleep (e.g., when the user shifts position or when one of their limbs or another person contacts the device 12). The body can extend partially or completely around a perimeter of the head 8.

[0094] The edges 16 can be a slip resistance material, for example silicone. The edges 16 can be configured to inhibit or prevent the data acquisition device 12 from slipping during use, such as when the user moves during sleep (e.g., when the user shifts position or when one of their limbs or another person contacts the device 12). The edges 16 can extend partially or completely around a perimeter of the head 8. The edges 16 can form a length and/or a perimeter of the data acquisition device 12. The device 12 can have a first edge 16a (e.g., an upper edge) and/or a second edge 16b (e.g., a lower edge). The first edge 16a can form a first length of the device 12 and the second edge 16b can form a second length of the device 12. For example, the first edge 16a can form a first perimeter of the device 12 and the second edge 16b can form a second perimeter of the device 12. The first and second lengths and/or perimeters can have the same or a different size. The elastic body 14 and the slip resistant edges 16 (e.g., first and second edges 16a, 16b) can be configured to keep the data acquisition in position during use or otherwise inhibit or prevent the data acquisition device from falling off during use.

[0095] The elastic body and slip resistant edges 14, 16 can be configured to keep sensors of the data acquisition device 12 in position during use such that there is strong contact and

less resistance to movement at the point where the sensors come into contact with the skin. This can advantageously ensure that the device sensors can have reliable contact with the skin. Alternatively or additionally, the data acquisition device 12 can have one or multiple expandable mechanisms configured to keep the sensors of the data acquisition device 12 in position during use such that there is strong contact and less resistance to movement at the point where the sensors come into contact with the skin. The expandable mechanism can allow the sensors to contact the skin with precise pointed pressure (e.g., from pressure provided by the expandable mechanism). The expandable mechanism can be behind one or more sensors of the data acquisition device 12, for example, behind all of the sensors of the data acquisition device, or behind any lesser number of sensors of the device 12. The expandable mechanism can be an inflatable bladder. The expandable mechanism (e.g., the inflatable bladder) can be configured to expand to press one or more sensors into the skin. The expandable mechanism can remain expanded during use. The expandable mechanism can be expanded from an unexpanded configuration to an expanded configuration. The unexpanded configuration can have a first volume and the expanded configuration can have a second volume larger than the first volume. The first volume can be zero or greater than zero. The second volume can be, for example, about 1 mL to about 50 mL, including every 1 mL increment within this range. The expandable mechanism can be expanded until a predetermined pressure threshold is detected between the skin and one or more of the device sensors, for example, by one or more pressure sensors associated with the expandable mechanism. The expandable mechanism (e.g., inflatable bladder) can advantageously enable the device 12 to create skin-sensor contacts that have known and reproducible skin-sensor contact pressures or other measureable quantity that can characterize the contact between the sensors and the skin, or that otherwise fall within an acceptable tolerance such that the device can accurately and precisely record various physiological activity of the subject (e.g., brain activity).

[0096] The data acquisition device 12 can be a removably attachable headband, cap, hat, strip (e.g., adhesive strip), biased band, or any combination thereof. The data acquisition device 12 can have the shape of a closed or open loop (e.g., annular or semi-annular shape). The data acquisition device 12 can extend partially or completely around a perimeter of the head 8. For example, FIG. 1A illustrates that the device 12 can be a headband. FIG. 1A further illustrates that the device 12 can extend completely around the head 8, with FIG. 1A being a partial perspective view. FIG. 1A further illustrates that the device 12 can extend partially around the head 8, with FIG. 1A being a partial perspective view. The device 12 can cover one or both ears (e.g., ears 7) in either or both of the “partially around” and “completely around” configurations. Additionally or alternatively, the device 12 can be configured to not cover one or both ears or otherwise not cover a portion thereof.

[0097] The data acquisition device 12 can be positionable on a person's head 8 (e.g., during sleep and/or during naps). For example, FIG. 1A illustrates that the data acquisition device 12 can be removably positioned on the head 8. The data acquisition device 12 can be positioned on the head 8 with an elastic fit or an interference fit, and/or one or more portions of the data acquisition device can be removably adhered to the head (e.g., to skin, to the forehead), for

example, with an adhesive. The data acquisition device 12 can be configured for temporary securement to the head 8. The data acquisition device 12 can resist dislodgment from a secured position (e.g., attached position), for example, via the elasticity of the body 14 and/or the slip resistance of the edges 16.

[0098] The data acquisition device 12 can have an adjustable size to accommodate different head sizes. For example, the data acquisition device 12 can have an adjustable strap. The data acquisition device 12 can have a nonadjustable size. The system 10 can have multiple data acquisition devices 12 (e.g., 2 to 5 data acquisition devices), each having a different adjustable or nonadjustable size. For example, the system 10 can have three data acquisition devices 12, for example, first, second, and third data acquisition devices 12, each having a progressively larger size. For example, the first, second and third data acquisition devices 12 can correspond to small, medium and large sizes, respectively. As another example, the system 10 can have one or more child-sized data acquisition devices (e.g., devices 12) and one or more adult-sized data acquisition devices (e.g., devices 12).

[0099] FIG. 1A illustrates that the data display device 20 can have a display 22 (e.g., a graphics display such as a graphics user interface (GUI)). The display 22 can be a touchscreen. The display 22 can display, for example, a user interface 24. The user interface 24 can be generated via a computer algorithm, for example via software downloaded to or callable from a portable electronic device (e.g., a smartphone).

[0100] The user interface 24 can have one or multiple interactive screens. For example, FIG. 1A illustrates that the user interface 24 can have a first screen 24a and a second screen 24b. The first screen 24a can, for example, correspond to a startup screen having a “sign in” selection and a “get started” selection. The second screen 24b can, for example, correspond to a data results screen (e.g., a sleep summary screen).

[0101] The user interface 24 can display raw data, analyzed data, observations, recommendations, or any combination thereof. For example, FIG. 1A illustrates that the second screen 24b can list various observations titled “AH-HA'S” (also referred to as performance insights, things worth noting, things worth mentioning). The observations can be tied to one or more determined parameters and/or to one or more sleep performance metrics (e.g., derivations involving one or more determined parameters). The observations can provide text summaries of a user's sleep performance (e.g., “insufficient total deep sleep”), as well as insights related to the user's sleep performance (e.g., “high stress levels,” “high stress levels detected”). The recommendations can include goal suggestions related to one or more influencers of the user's sleep performance. The influencers can be variables and/or behaviors that can, may, and/or do affect sleep generally and/or the user's sleep specifically. For example, the system 10 can provide recommendations such as “smoke one less cigarette today,” “go for a 10-20 minute walk at 7 pm,” “have your Wednesday glass of wine 30 minutes earlier today,” “plan something fun for this weekend.”

[0102] FIG. 1B illustrates that the data acquisition device 12 can have a body 14 comprising multiple bands 15, for example, a first band 15a, a second band 15b, and a third band 15c. The first, second, and third bands 15a, 15b, 15c

can be separate bands and/or can be different band portions of a single unitary band. For example, the first, second, and/or third bands **15a**, **15b**, **15c** can be attached to or integrated with one another at attachment region **15d**. The data acquisition device **12** can form a headband. The first band/band portion **15a** can form a front band/strap. The second and third bands/band portions **15b**, **15c** can form back bands/straps. The device **12** can have a 'split band' in the back of the head **8** formed by the second and third straps **15b**, **15c**, where the bottom band (e.g., the third band **15c**) can be configured to cup under the curve of the back of the head to reduce any potential slippage/movement of the headband. The angle of the bands can be fixed or moveable. For example, the fixed or moveable (e.g., adjustable) angle can be from about 10 degrees to about 120 degrees, including every 1 degree increment within this range (e.g., 30 degrees, 45 degrees). A band adjuster **5a** (e.g., the 'teva-like triangle' **5a**) can enable back straps (e.g., bands **15b** and **15c**) to adjust to contour to person's head. The band adjuster **5a** can allow the second band **15b** to be adjusted independently from the third band **15c**. The band adjuster **5a** can allow the third band **15c** to be adjusted independently from the second band **15b**. The band adjuster **5a** can allow the angle between the second and third bands **15b**, **15c** to be adjusted. Alternatively or additionally, the device **12** can have another band adjuster **5b** that can have the same functionality as the band adjuster **5a**. The device **12** can have one or more length adjustment mechanisms configured to allow the length of the one or more bands to be increased, decreased, and/or locked into position. For example, FIG. 1B illustrates that the device **12** can have a first length adjustment mechanism **4a** for the first band/band portion **15a**, a second length adjustment mechanism **4b** for the second band/band portion **15b**, a third length adjustment mechanism **4c** for the third band/band portion **15c**, or any combination thereof.

Stimulation

[0103] FIG. 1A illustrates that the system **10** can provide audio stimulation (also referred to as audio entrainment) using, for example, one or more sound wave generators **17** (e.g., 1 to 4 sound wave generators). The sound wave generators can be, for example, speakers. A portion of the data acquisition device **12** can be positionable over and/or engageable with a left and/or right ear **7** of a user such that the speakers **17** can emit sound into a user's ears **7**. The data acquisition device **12** can be configured to partially or completely cover one or both ears **7**. For example, FIG. 1A illustrates that a body first region **14a** can completely cover the right ear **7**. A portion of the data acquisition device **12** can be configured for temporary securement on and/or to a user's ears. A portion of the data acquisition device **12** can be configured to fit in or extend into an ear canal. The speakers **17** can be attached to, embedded in, or integrated with the device body and/or device edges **14**, **16**. The speakers **17** can be in wired or wireless communication with the data acquisition device **12**, the data display device **20**, a remote server, or any combination thereof. The speakers **17** can be micro speakers. Alternatively or additionally, the system **10** can have one or more plastic tubes (e.g., small plastic tubes) configured to direct sound to the ears **7**. The sound wave generator/speaker **17** can be connected to the small plastic tubes. The plastic tubes can more precisely direct sound to the ears **7** and can be more comfortable over

the ear. One or more of the speakers **17** can be noise canceling speakers (e.g., to cancel environmental noise).

[0104] Additionally or alternatively, the system **10** can provide audio stimulation via bone conduction by transmitting sound signals through bone to a user's inner ear. The system **10** can have one or more actuator assemblies **13** to provide bone conduction sound transmission. The actuator assemblies **13** can have an actuator. The actuator can be vibratable (e.g., the actuator can be configured to vibrate). The actuator assemblies **13** can have a transceiver coupled to the actuator. The transceiver can cause the actuator to vibrate to generate sound, for example, when the transceiver is electronically driven with sound signals (e.g., from a driver and/or a controller, for example, from the device **12** and/or the device **20**). The actuator can be a piezoelectric actuator. The piezoelectric actuator can be configured to move a mass to provide sound through bone. The actuator assemblies **13** (e.g., the actuator) can be positioned near the ear and/or on the cheek. For example, the actuator assemblies **13** can be positioned on a user's skin proximate the zygomatic bone, the zygomatic arch, the mastoid process, or any combination thereof. The system **10** can have 1 to 6 actuator assemblies, or 1 to 6 actuators, including every 1 actuator assembly/actuator increment within these ranges. For example, FIG. 1A illustrates that the data acquisition device **12** can have one actuator assembly near the right ear **7**. As another example, FIG. 1A illustrates that the data acquisition device **12** can have two actuator assemblies **13**, one near the right ear **7** and another near the left ear (not shown).

[0105] Examples of audio stimulation that the system **10** can provide are provided in Papalambros et al. Acoustic Enhancement of Sleep Slow Oscillations and Concomitant Memory Improvement in Older Adults, *Frontiers in Human Neuroscience*, Mar. 8, 2017, Volume 11, Article 109, Pages 1-14; Ngo et al. Auditory Closed-Loop Stimulation of the Sleep Slow Oscillation Enhances Memory, *Neuron*, May 8, 2013, No. 78, Pages 545-553; and Santostasi et al. Phase-locked loop for precisely time acoustic stimulation during sleep, *Journal of Neuroscience Methods* 259 (2016) 101-114, which are each herein incorporated by reference in their entireties for all purposes.

[0106] FIG. 1A further illustrates that the system **10** can provide visual/optical stimulation (also referred to as light entrainment) using, for example, one or more light emitting sources **19** (e.g., 1 to 20 light emitting sources). A portion of the data acquisition device **12** can be positionable over and/or engageable with a left and/or right eye **6** of a user such that the light sources **19** can emit light into a user's eyes **6** (e.g., through the user's closed eyelids). The data acquisition device **12** can be configured to partially or completely cover one or both eyes **6**. The data acquisition device **12** can be configured for temporary securement above or proximate to a user's eyes/eyelids. For example, a portion of the data acquisition device **12** can be configured to rest against and/or adhere to an eyebrow, the area proximate an eyebrow, the glabella, the nose (e.g., dorsal bridge, dorsal base, tip), cheek, or any combination thereof. For example, FIG. 1A illustrates that the device **12** can have an eye cover **12e** configured to cover (e.g., partially or completely) the left and right eyes **6a**, **6b**. The eye cover **12e** can be permanently or removably attached to or integrated with the device **12** (e.g., to or with the body and/or edges **14**, **16**). The light sources **19** can be attached to, embedded in, or integrated

with the device **12** (e.g., the device eye cover **12e**). The eye cover **12e** can have one or multiple light sources **19**. For example, the eye cover **12e** can have a first light source **19a** configured to emit light into the left eye **6a** and a second light source **19b** configured to emit light into the right eye **6b**.

[0107] FIG. 1A further illustrates that the system **10** can provide cranial electrical stimulation (CES) using, for example, one or more electrodes **21** placed on an ear (e.g., earlobe), maxilla-occipital junction, mastoid process, temple, or any combination thereof.

[0108] The system **10** can provide audio entrainment, optical entrainment, CES, or any combination thereof, in addition to or in lieu of the data collection and associated analyses described below.

Data Collection & Analysis

[0109] The data acquisition device **12** can be configured to measure and collect one or more physiological parameters during sleep. For example, the data acquisition device **12** can be configured to detect, measure, monitor, and record brain activity, eye activity, muscle activity (e.g., body posture, limb movements), cardiac activity (e.g., heart rate variability (HRV)), respiration activity (e.g., respiration rate), blood oxygen saturation, or any combination thereof. For example, the data acquisition device **12** can be configured to detect, measure, monitor, and record brain activity using electroencephalography (EEG), eye activity using electrooculography (EOG), muscle activity using electromyography (EMG), cardiac activity using electrocardiography (ECG), respiration rate (e.g., using respiratory inductance plethysmography (RIP), pressure sensor, and/or a temperature sensor), oxygen saturation (e.g., using pulse oximetry), or any combination thereof. The data acquisition device **12** can be configured to detect, measure, monitor, and record pressure and temperature, for example, using one or more pressure sensors and/or one or more temperature sensors. The data acquisition device **12** can perform polysomnography (PSG) tests and can collect polysomnographic data. The data that is collected is referred to throughout as acquired data, raw data, and/or sleep data.

[0110] The data acquisition device **12** can have one or more data acquisition modules **18** (also referred to as electronics modules **18**), for example, 1 to 5 electronics modules **18**, including every 1 module increment within this range (e.g., 2 electronics modules). For example, FIG. 1A illustrates that the data acquisition device **12** can have one electronics module **18**.

[0111] The one or more electronics modules **18** can be configured to monitor and record one or more physiological activities during sleep. For example, the electronics modules **18** can be configured to detect, measure, monitor, and record brain activity, eye activity, muscle activity, cardiac activity, respiration activity, blood oxygen saturation, or any combination thereof (e.g., using EEG, EOG, EMG, ECG, RIP, pulse oximetry, or any combination thereof, respectively). The one or more electronics modules **18** can be computer interfaces, for example, brain computer interfaces (BCIs).

[0112] The data acquisition device **12** (e.g., the electronics modules **18**) can have one or more electrodes, sensors (e.g., biosensors), accelerometers, or any combination thereof. For example, the data acquisition device **12** (e.g., the electronics modules **18**) can have one or more EEG biosensors, EOG biosensors, EMG biosensors, ECG biosensors, respiration

rate biosensors, pulse oximetry biosensors, HRV biosensors, temperature sensors, pressure sensors, or any combination thereof, including one or more reference sensors and/or one or more ground electrodes.

[0113] The data acquisition device **12** (e.g., the electronics modules **18**) can have a single-channel and/or a multi-channel EEG system. The multi-channel EEG system can be operated as a single channel EEG system. The EEG system (single or multi-channel) can include one or more EEG sensors. The data acquisition device **12** (e.g., the electronics modules **18**) can have 1 to 10 EEG sensors, including every 1 EEG sensor within this range (e.g., 4 EEG electrodes). The data acquisition device **12** (e.g., the electronics modules **18**) can have more than **10** sensors (e.g., 1 to 100 EEG sensors). The electronics modules **18** can have an EEG sensor array or an EEG sensor network (e.g., of 2 to 10 or more sensors). One of the EEG sensors can be a ground electrode. The EEG system can have one or multiple reference electrodes (e.g., one or two reference electrodes). The electronics module **18** can have, for example, three channels of frontal EEG and one EEG reference sensor. The EEG electrodes can be positioned on the forehead as illustrated in FIG. 1A. The EEG electrodes can be placed according to the international 10-20 system.

[0114] The data acquisition device **12** (e.g., the electronics modules **18**) can have 2, 3, or 4 EOG sensors. Two EOG sensors can detect/measure movement of one or both eyes. For example, two EOG sensors can be positioned to detect/measure eye movement of the left and right eyes (e.g., a first EOG sensor can be positioned on the right outer edge of the right eye and a second EOG sensor can be positioned on the left outer edge of the left eye), two EOG sensors can be positioned to detect/measure eye movement of only the left eye (e.g., a first EOG sensor can be positioned on the right outer edge and a second EOG sensor can be positioned on the left outer edge of the left eye), or two EOG sensors can be positioned to detect/measure eye movement of only the right eye (e.g., a first EOG sensor can be positioned on the right outer edge and a second EOG sensor can be positioned on the left outer edge of the right eye). Three EOG sensors can be positioned to detect/measure eye movement of the left and right eyes (e.g., a first EOG sensor can be positioned on the right outer edge of the right eye, a second EOG sensor can be positioned on the left outer edge of the left eye, and a third EOG sensor can be positioned between the left and right eyes). The three EOG sensors can selectively detect/measure eye movement of the left and/or right eyes, with the first and third EOG sensors configured to detect/measure movement of the right eye, with the second and third EOG sensors configured to detect/measure movement of the left eye, and with the first and second EOG sensors configured to detect/measure movement of the left and right eyes together. Four EOG sensors can be positioned to detect/measure eye movement of the left and right eyes (e.g., first and second EOG sensors can be positioned on first and second sides of the left eye and third and fourth EOG sensors can be positioned on first and second sides of the right eye). The “outer edges” of the eyes can be in line with the eyes, above the eyes and/or below the eyes.

[0115] The system **10** can have 1 to 6 EMG sensors, including every 1 EMG electrode increment within this range (e.g., 2 EMG electrodes).

[0116] The system **10** (e.g., the data acquisition device **12** and/or the electronics modules **18**) can have 1 to 10 ECG

sensors, including every 1 ECG electrode increment within this range (e.g., 1, 2, or 3 ECG electrodes). The ECG sensors can be used to measure HRV. The ECG sensors can be used to determine HRV.

[0117] The system 10 (e.g., the data acquisition device 12 and/or the electronics modules 18) can have 1 to 10 heart rate sensors, including every 1 heart rate sensor increment within this range (e.g., 1, 2, or 3 heart rate sensors). The heart rate sensors can be used to measure HRV. The heart rate sensors can be used to determine HRV.

[0118] The system 10 can have an RIP system. The RIP system can be in electrical communication with the data acquisition device 12. The RIP system can measure movement of the chest and abdominal wall, for example, using one or more belts. Additionally or alternatively, the system 10 (e.g., the data acquisition device 12 and/or the electronics modules 18) can have one or multiple pressure sensors (e.g., pressure transducers) and/or temperature sensors (e.g., thermocouples) configured to monitor respiration. For example, the data acquisition device 12 can have 1 to 4 pressure sensors, including every 1 pressure sensor increment within this range (e.g., 1 or 2 pressure sensors). The data acquisition device 12 can have 1 to 4 temperature sensors, including every 1 temperature sensor increment within this range (e.g., 1 or 2 temperature sensors). The pressure and/or temperature sensors can be positionable near the nostrils and can be configured to detect the pressure/temperature changes that occur when a user inhales and exhales. The pressure and/or temperature sensors can be attached to or integrated with the data acquisition device 12 such that when the device 12 is removably secured to a head, the pressure and/or temperature sensors are positioned in a breathing flow path (e.g., near the nostrils and/or mouth, for example, for mouth breathers).

[0119] The data acquisition device 12 can have a pulse oximetry sensor that can be removably attachable to an ear (e.g., ear 7), for example, to an ear lobe. The system 10 can have a pulse oximetry sensor that can be removably attachable to a finger. The finger pulse oximetry sensor can be in wired or wireless communication with the data acquisition device 12 (e.g., to the electronics module 18) and/or to the data display device 20. The ear pulse oximetry sensor can be attached to or integrated with the device 12. The pulse oximetry sensor (ear and finger sensor) can be a component of a clip. The clip can attach to (e.g., clip to) an ear lobe or a finger. The clip can be attached to or integrated with the device 12, for example, to the body 14 and/or edges 16.

[0120] The data acquisition device 12 can have one or more pressure sensors (e.g., 1, 2, 3, 4, 5, 6 or more) configured to detect when the device 12 is attached to a head, for example, by measuring the amount of force exerted against each of the pressure sensors. The system 10 (e.g., the devices 12 and/or 20) can be configured to detect whether the device 12 is properly positioned on the head, for example, by detecting and/or comparing the different pressures measured by the one or more pressure sensors (e.g., by calculating one or more pressure differentials). The pressure sensors can also be used to determine whether the position can be improved or further optimized, for example, for more accurate and/or reliable data collection. The device 12 can be activated (e.g., automatically or manually) when positioned on the head 8 as a result of one or more pressure sensors exceeding a pressure threshold. The device 12 can be activated (e.g., automatically or manually) when posi-

tioned on the head 8 as a result of one or more differential pressure differentials (e.g., between two sensors) falling below a differential pressure threshold.

[0121] For example, a first pressure sensor can be on a first side of the device 12 and a second pressure sensor can be on a second side of the device 12. The pressure sensors can be separated by about 1 degree to about 180 degrees as measured from a center of the device 12 (e.g., along a longitudinal and/or transverse axis), including every 1 degree increment within this range. The center of the device 12 can fall between two inner sides of the device such that the device center is not on the body and/or edges 14, 16 of the device 12. A 180 degree separation can correspond to a configuration in which the first and second pressure sensors are diametrically opposed from one another. Angles less than 180 degrees can correspond to configurations in which the first and second pressure sensors are on opposite sides of the device, determined for example relative to a reference axis. Angles less than 180 degrees can correspond to configurations in which the first and second pressure sensors are on the same side of the device, determined for example relative to a reference axis. The first and second pressure sensors can be used to determine a side-to-side or a front-to-back pressure differential of the device 12 (i.e., the pressure levels on the left side, right side, front side, and/or back side of the device 12). Four pressure sensors can be used to determine side-to-side and/or front-to-back pressure differentials of the device when removably attached to a head. The angles between sensors can be from about 1 degree to about 180 degrees, including every 1 degree increment within this range.

[0122] The system 10 (e.g., the device 12, the device 20, and/or a remote server) can determine whether the device 12 is properly or improperly positioned by analyzing the pressure readings of the one or more pressure sensors. If properly positioned, the device 12 can automatically begin collecting data (e.g., immediately or after one or more additional conditions are satisfied). If properly positioned, the data display device 20 can prompt the user with a selectable command (e.g., via a graphic on a touch screen) to begin data collection (e.g., “start recording,” “good night,” “good night, have a good rest,” “begin data collection,” “sleep well, let’s begin data collection”). The prompt can be customizable. If improperly positioned, the data display device 20 can provide the user with suggested instructions to correct the improper placement (e.g., “please rotate the headband to the right/left,” “please pull the head band lower or higher onto your forehead,” “please adjust the headband so that the sensors are on your forehead,” “please loosen the headband,” “please tighten the headband”). The system 10 can also be configured to provide recommendations to make a proper position more comfortable. For example, the data display device 20 can be configured to display messages such as “the device is positioned properly, but it might be a little tight. Feel free to loosen it a bit! We don’t want you to wake up with a headache ☹️”). The device 12 can be activated (automatically or manually) to collect data even when not in a proper position. The device 12 can collect data when not positioned properly, however, some of the data may have accuracy, precision and/or reliability issues, or some of the data may be missing altogether (e.g., pulse oximetry data). Additionally or alternatively, the devices 12 and/or 20 can be configured to determine whether

the device **12** is properly positioned by measuring the voltage drop across one of more sensors of the electronics modules **18**).

[0123] The data acquisition device **12** can begin collecting data when one or more conditions are satisfied (e.g., 1 to 5 or more conditions). The data acquisition device **12** can begin collecting data when a proper position is detected. The data acquisition device **12** can begin collecting data when the system **10** detects that the user is in a sleeping position and/or when the user is in a sleeping location, for example, for a predetermined amount of time (e.g., immediately (no time), or after 1 min to 5 min or more have elapsed). The sleeping location can be established or otherwise settable by the user. For example, the data acquisition device **12** can begin collecting data after first, second, third, and/or fourth conditions are satisfied. The device **12** can begin collecting data immediately after any one condition or combination of conditions is satisfied. The first condition can correspond to correct device placement (e.g., of the device **12**). The second condition can correspond to user input (e.g., selection of a command prompt). The third condition can correspond to a position of the device relative to the environment, for example, whether the orientation of the device **12** is in a position indicative of a sleeping position of the user (e.g., lying down, either prone, supine, or on side). The fourth condition can correspond to a location of the user (e.g., on a bed). Sleep data collection can begin when the pressure sensors detect that the device **12** is attached to a head. Sleep data collection can begin when the pressure sensors detect that the device **12** is properly attached to a head.

[0124] The data acquisition device **12** can have one or more temperature sensors (e.g., 1, 2, 3, 4 or more temperature sensors) configured to monitor a user's body temperature. The temperature sensors can be temperature transducers (e.g., thermocouples). The temperature sensor can be attached to or integrated with the device **12**. The temperature sensors can be configured to detect when the device **12** is attached to a head, for example, by detecting a body temperature. An environment temperature sensor can be configured to measure environmental temperature. The environment temperature sensor can be one of the temperature sensors of the device **12**. The environment temperature sensor can be a temperature sensor of a sleeping location (e.g., house or apartment). The system **10** can determine a user's optimum sleeping temperature and suggest a sleeping temperature for the user, for example, from about 60 degrees Fahrenheit to about 85 degrees Fahrenheit, including every 1 degree increment within this range. For example, the system **10** (e.g., the data display device **10**) can make suggestions such as "we suggest a sleeping temperature of 71 degrees Fahrenheit" or "we suggest a sleeping temperature of 78 degrees Fahrenheit." The user can adjust the temperature of their sleeping location (e.g., house, apartment) or the system **10** can be in wired or wireless communication with a heating and/or air conditioning system of the sleeping location and control the environmental temperature automatically.

[0125] The system **10** (e.g., the data acquisition device **12** and/or the electronics modules **18**) can have one or more accelerometers (e.g., one accelerometer). The accelerometer can detect a user's positional state, for example, a user's movement. The accelerometer can be a two-axis accelerometer. The accelerometer can be a three-axis accelerometer. The accelerometer can be configured to detect head, body,

and/or limb movements, or any combination thereof. The accelerometer can be used to detect lack of movement as well, for example, the length of time in a single position without movement or with movement within a specified tolerance (e.g., voltage level or movement amount, for example, 5 cm or less).

[0126] The electronics modules (e.g., electronics modules **18**) can include, for example, three channels of frontal EEG and one EEG reference sensor to detect brain wave activity, a heart rate sensor to monitor cardiac activity (e.g., RR variability), an accelerometer (e.g., two or three axis accelerometer) to detect head, body, and/or limb movements, or any combination thereof.

[0127] FIG. 1A illustrates that the module **18** can be configured to contact a user's skin (e.g., a user's forehead) during use. The device **12** can press the EEG sensors and/or ECG sensor(s) against the user's skin (e.g., forehead) when secured to the head **8**, for example, with an elastic fit or with an interference fit. Alternatively or additionally, the sensors can be adhered to the user's skin (e.g., forehead) using an adhesive with or without the device **12**.

[0128] The electronics module **18** can be configured to measure brain activity, for example, during light sleep, during rapid eye movement (REM) sleep, during slow-wave sleep (SWS) (also referred to as deep sleep), or any combination thereof. The electronics module **18** can be configured to measure cardiac activity, for example, HRV such as RR intervals. The electronics module **18** can be configured to detect a user's motion and/or a user's lack of motion.

[0129] The electronics module components (e.g., channels, sensors, accelerometers) can be attached to or integrated with the data acquisition module **18**. The data acquisition module **18** can be permanently attached to, removably attached to, or integrated with the device **12** (e.g., to and/or with the body **14** and/or edges **16**). Additionally or alternatively, the various activity-measuring components (e.g., channels, sensors, accelerometers) can be attached to or integrated with an attachment portion of the data acquisition device **12**, for example the body **14** and/or the edges **16** separate and apart from the module **18**. The module **18** can be interchangeable with one or more other modules (not shown) having a different number of sensors, one or more different types of sensors, or otherwise having at least one different parameter-measuring capability relative to the electronics module **18**. The module **18** can be interchangeable with another module having the same exact module or otherwise with another module having the same exact parameter-measuring capabilities. Different modules **18** can have different sizes relative to one another. Different modules **18** can have different shapes relative to one another.

[0130] The data acquisition device **12** can be reusable or disposable. The electronics modules **18** can be reusable or disposable.

[0131] The data acquisition device **12**, the data display device **20**, and/or a remote server can analyze the sleep data collected. The data acquisition device **12**, the data display device **20**, and/or a remote server can determine one or more parameters from the data collected, for example, using one or more programmable processors. The parameters can include total light sleep, total SWS (also referred to as total deep sleep), total REM sleep, total non-REM sleep (total light sleep and total SWS added together), total sleep (total REM and non-REM sleep added together), longest deep sleep duration, deep sleep amplitude, heart rate, heart rate

variability, total time in bed, time to fall asleep, time awake between falling asleep and waking up, or any combination thereof. The time-based parameters (e.g., the “total,” “duration,” and “time” parameters) can be measured in the time domain, for example, using seconds, minutes, hours. Days, weeks and years can be used for accumulated and/or running totals.

[0132] The total time in bed parameter can be measured from a start point to an end point. The start point can correspond to when the user manually activates the data acquisition device 12, for example, by selecting a start instruction (e.g., “ready to sleep”) on the display 22. The start point can correspond to when the device 12 is activated (e.g., automatically or manually). The device 12 can be automatically activated, for example, when a voltage is detected across two or more sensors of the module 18 (e.g., across two or more of the EEG electrodes). The voltage can indicate contact with skin and cause the device 12 to begin measuring the total time in bed. The device 12 can have a timer. The device 12 can be automatically activated when positioned on the head 8 as a result of one or more pressure sensors exceeding a pressure threshold. The end point can correspond to when the user manually deactivates the data acquisition device 12, for example, by selecting an end instruction (e.g., “turn off alarm” or “get sleep report”) on the display 22. The end point can correspond to when the device is automatically deactivated. The device 12 can be automatically deactivated, for example, when the accelerometer indicates the user is walking around or has taken the device 12 off their head.

[0133] The data acquisition device 12, the data display device 20, and/or a remote server can calculate or otherwise derive one or more sleep performance metrics from one or more of the measured parameters, for example, using one or more programmable processors. The calculated metrics can include parameter totals (e.g., total sleep, total SWS, total REM sleep, total light sleep, total non-REM sleep). The calculated parameters can include sleep efficiency, deep sleep deficit (also referred to as deep sleep debt or accumulated deep sleep deficit), and strength of deep sleep, or any combination thereof. The sleep efficiency metric can be the ratio of the total sleep time divided by the total time in bed

$$\left(\text{i.e., } \frac{\text{total sleep time}}{\text{total time in bed}} \right).$$

The strength of deep sleep metric can be the deep sleep deficit accumulated over multiple nights, for example, 2 to 14 nights, including every 1 night increment within this range (e.g., 5 nights). The strength of deep sleep metric can be measured in millivolts (mV) or power spectral density, and can reflect the amplitude/power of the brainwaves in deep sleep, which can be determined by how much of the brain is in deep sleep, i.e., the more of the brain that is in slow-wave sleep, the higher the amplitude, and the stronger the deep sleep. If the user does not wear the device 12 for two or more consecutive nights (e.g., 5 consecutive nights), then the strength of deep sleep metric can be excluded from the sleep performance score calculations.

[0134] The data acquisition device 12, the data display device 20, and/or a remote server can identify and record a user’s sleep cycles, for example, using one or more programmable processors, and can determine the length of time

spent in each sleep cycle. A complete sleep cycle can include non-REM sleep and REM sleep. Non-REM sleep can include light sleep and deep sleep. The system 10 can identify and record light sleep, deep sleep and REM sleep, and can determine the total time spent in each, and in any combination (e.g., total light and deep sleep, total light and REM sleep, total deep and REM sleep). A complete sleep cycle can have 4 stages. Light sleep can correspond to sleep stages 1 and 2. Deep sleep can correspond to sleep stage 3. REM sleep can correspond to sleep stage 4. Sleepers complete a sleep cycle by passing through stages 1, 2, 3, and 4 in sequential order. Stages 1-4 can progress cyclically from stage 1 to stage 4 and then repeat, beginning again at stage 1. The system 10 can identify and record the total time spent in each stage, and in any combination (any combination of stages 1, 2, 3, and 4).

[0135] SWS periods in early sleep cycles can be longer relative to later sleep cycles, and REM sleep periods in early sleep cycles can be shorter relative to later sleep cycles (i.e., as a user progressively moves from one sleep cycle to the next, time spent in REM sleep can increase and time spent in SWS can sleep decrease). The system 10 (e.g., data acquisition device 12, the data display device 20, and/or a remote server) can identify the differences in time spent in each of the corresponding stages across multiple sleep cycles, including the relative increases in REM sleep and the relative decreases in SWS across sleep cycles. The system 10 can identify and record the total time spent in each sleep cycle. The system 10 can detect when a sleep cycle has been interrupted. The system 10 can detect the stage in which a sleep cycle has been interrupted. The system 10 can detect the length of the interruption and the user’s ability to recover, also referred to as a user’s recovery efficiency. The recovery efficiency can include a comparison of the sleep stage before the interruption and the sleep stage entered after the interruption, where a 100% recovery efficiency can correspond to when the pre-interruption and post-interruption sleep stages are identical to one another. A lesser percentage (e.g., 50%) can correspond to where the pre-interruption stage does not match the post-interruption stage. The recovery efficiency can include a measure of post-interruption sleep stage progression, where an accelerated progression through the sleep stages to again be at the stage at which the interruption occurred can correspond to a high efficiency.

[0136] The data acquisition device 12, the data display device 20, and/or a remote server can calculate or otherwise derive one or more sleep performance scores from one or more of the determined parameters and/or calculated parameters, for example, using one or more programmable processors. The sleep performance scores can include a sleep quality score, a brain fitness score, a recharge score (also referred to as recovery score or readiness score), an influencers score, or any combination thereof.

[0137] The system 10 can have a database of data sets. The system 10 can determine one or more sleep performance scores by referencing one or more of the data sets. For example, the system 10 can determine the sleep quality, brain fitness and recharge scores by referencing one or more stored data sets. The data sets can correspond to one or more measured parameters and/or derived sleep metrics. The data sets can correspond to calculated distributions of one or more parameters and/or derived sleep metrics. The data sets can be represented numerically and/or visually (e.g., via

tables and/or graphs). The data sets can be lookup tables. The data sets can be lookup graphs having reference curves.

[0138] The data sets can associate the measured and/or calculated parameters and/or metrics with a total number of points for any given value of the parameter and/or metric. The total points associated with a parameter/metric can correspond to a sleep performance score, and/or the total points from multiple parameters/metrics (e.g., 2 to 5 or more parameters/metrics) can be combined to determine a sleep performance score. The total points from two or more parameters/metrics can be combined via one or more mathematical operations such as addition, weighted (e.g., percentage-based) addition, subtraction, weighted (e.g., percentage-based) subtraction, multiplication, weighted (e.g., percentage-based) multiplication, division, weighted (e.g., percentage-based) division, or any combination thereof.

[0139] The data sets can be separated into cohorts, for example, based on age, gender, ethnicity, health, fitness level, or any combination thereof, and/or can be represented without breaking up the data into cohorts. For example, the data sets (e.g., cohort curves) can be gender neutral and/or gender-specific (e.g., male and/or female), such as gender neutral age cohort curves. Additionally or alternatively, a user's personal history and/or baselines (e.g., baseline scores, baseline goals) can be used in the scoring methodology when determining one or more of the sleep performance scores. The system 10 can progressively transition from the use of one or more stored data sets to the use of a user's personal history and/or baselines as acquired by the system 10 and/or set by the user. For example, the system 10 can progressively decrease the use of stored data sets from 100% to 0% by a 10% to 25% increment per time period (e.g., 1 day to 30 days, including every 1 day increment within this range) and/or per number of uses of the system 10 (e.g., 1 use to 30 uses, including every 1 use increment within this range). The percentages can correspond to weights when determining the total points for one or more of the parameters/metrics, and/or to weights when determining one or more of the sleep performance scores (e.g., sleep quality score, brain fitness score, recharge score, influencers score). The system 10 can progressively increase the use of the user's personal history and/or baselines by an equal percentage that the stored data set percentage use is decreased, for example, from 0% to 100% by a 10% to 25% increment. Alternatively or additionally, the system 10 can progressively decrease the use of stored data sets to from 1% to 80% from a 100% starting point and vice versa for the personal history and baseline database, for example, to from 1% to 80% from a 0% starting point.

[0140] The system 10 can aggregate and anonymize all the user data in the cloud, analyze the data to identify patterns in terms of what audio stimulation worked for which cohorts of people (e.g., gender, age, ethnic, fitness, health) under what situations (e.g., exercised that day, coming off of a poor/good Sleep Quality night) and then within a closed loop, update the algorithms accordingly so that the learnings are applied to the broader population.

[0141] FIGS. 2A-2E illustrate variations of reference data sets that the system 10 can have stored in memory (e.g., a database). Specifically, FIGS. 2A-2E illustrate graphs of total sleep, total deep sleep, sleep efficiency, longest deep sleep, and deep sleep deficit data, respectively. FIGS. 2A-2C further illustrate that the total sleep, total deep sleep, and sleep efficiency data can each have multiple age cohort

curves (also referred to as reference curves). For example, FIG. 2A illustrates a variation of a total sleep graph 30 having age-cohort curves 30a, 30b, 30c for ages 20 years old, 40 years old, and 65+years old (i.e., 65 years old and greater), respectively. The total sleep curves 30a, 30b, 30c can have polynomial equations, for example polynomial equations 31a, 31b, 31c, respectively. FIG. 2B illustrates a variation of a total deep sleep graph 32 having age-cohort curves 32a, 32b, 32c, 32d for ages 20 years old, 40 years old, and 60 years old, and 80 years old, respectively. The total deep sleep curves 32a, 32b, 32c, 32d can have polynomial equations, for example polynomial equations 33a, 33b, 33c, 33d, respectively. FIG. 2C illustrates a variation of a sleep efficiency graph 34 having age-cohort curves 34a, 34b, 34c, 34d for ages 20 years old, 40 years old, and 60 years old, and 80 years old, respectively. The sleep efficiency curves 34a, 34b, 34c, 34d can have polynomial equations, for example polynomial equations 35a, 35b, 35c, 35d, respectively. FIGS. 2D and 2E further illustrate that the longest deep sleep and deep sleep deficit data can be represented without cohort separation. For example, FIG. 2D illustrates a variation of a longest deep sleep graph 36 having a single longest deep sleep reference curve 36a. FIG. 2E illustrates a variation of a deep sleep deficit graph 38 having a single deep sleep deficit reference curve 38a. The longest deep sleep and deep sleep deficit curves can be polynomial curves as well. FIGS. 2A-2E each illustrate that the parameters/metrics can be indexed to a 0-100 point scale.

[0142] FIGS. 3A-3D illustrate variations of total sleep, total deep sleep, sleep efficiency, and longest deep sleep having non-polynomial equations. For example, FIGS. 3A-3D illustrate variations of linear approximations of the polynomial curves illustrated in FIGS. 2A-2D. For example, FIGS. 3A-3D illustrate variations of a series of connected line segments that approximate the polynomial curves illustrated in FIGS. 2A-2D. FIG. 3A further illustrates that the 65+total sleep curve 30c has been replaced with 60 years old and 80 years old cohort curves. FIG. 3A illustrates a variation of a total sleep graph 40 having age-cohort curves 40a, 40b, 40c, 40d for ages 20 years old, 40 years old, and 60 years old, and 80 years old, respectively. The total sleep curves 40a and 40b can be linear approximations of polynomial total sleep curves 30a and 30b, respectively. FIG. 3B illustrates a variation of a total deep sleep graph 42 having age-cohort curves 42a, 42b, 42c, 42d for ages 20 years old, 40 years old, and 60 years old, and 80 years old, respectively. The total deep sleep curves 42a, 42b, 42c, 42d can have linear equations, for example linear equations 43a, 43b, 43c, 43d, respectively. The total deep sleep curves 42a, 42b, 42c, 42d can be linear approximations of polynomial total deep sleep curves 32a, 32b, 32c, 32d, respectively. FIG. 3C illustrates a variation of a sleep efficiency graph 44 having age-cohort curves 44a, 44b, 44c, 44d for ages 20 years old, 40 years old, and 60 years old, and 80 years old, respectively. The sleep efficiency curves 44a, 44b, 44c, 44d can have linear equations, for example linear equations 45a, 45b, 45c, 45d, respectively. The sleep efficiency curves 44a, 44b, 44c, 44d can be linear approximations of polynomial total deep sleep curves 34a, 34b, 34c, 34d, respectively. FIG. 3D illustrates a variation of a longest deep sleep graph 46 having a single longest deep sleep reference curve 46a. FIG. 3E illustrates a variation of a reference data set that the system 10 can have stored in memory (e.g., a database). Specifically, FIG. 3E illustrates a graph of strength of deep

sleep data. For example, FIG. 3E illustrates a variation of a strength of deep sleep graph 49 having a single strength of deep sleep reference curve 49a. FIG. 3E illustrates that the strength of deep sleep can be a function of the root mean square (RMS) of the amplitude of SWS. The RMS of the amplitude can be a measure of the strength/deepness of deep sleep. FIGS. 3D and 3E further illustrate that the longest deep sleep and strength of deep sleep data can be represented without cohort separation. The longest deep sleep and strength of deep sleep curves can be polynomial and/or linear curves. For example, the longest deep sleep curve 46a can be a linear approximation of the polynomial longest deep sleep curve 36a. Additionally or alternatively, FIG. 3D illustrates that the longest deep sleep curve 46a can have a polynomial equation 47a. FIGS. 3A-3E each illustrate that the parameters/metrics can be indexed to a 0-100 point scale.

[0143] Extrapolation techniques such as weighted averages can be used to determine the points (i.e., the value on the y-axis) in FIGS. 2A-3E where there is one or more cohort curves (e.g., in FIGS. 2A-2C and FIGS. 3A-3C).

[0144] The system 10 can generate and/or have reference heart rate variability (HRV) data. For example, the system 10 can measure the R-R intervals of a user's heart beats. The R-R intervals can correspond to the times between heartbeats. The system 10 can calculate the root mean square of the successive differences (RMSSD) of the R-R intervals. The system 10 can measure the R-R intervals of a user's heart beats in one or more time periods. For example, the system 10 can measure RMSSD in a first RMSSD calculation period and in a second RMSSD calculation period. The first RMSSD calculation period can correspond to the RMSSD during the first 1 to 10 minutes of light sleep (e.g., the first 5 minutes of light sleep). The second RMSSD calculation period can correspond to the RMSSD during the last 1 to 15 minutes of light sleep before waking up (e.g., the last 5 minutes of light sleep before waking up). The RMSSD of the R-R can provide a beat-to-beat variability of the user's heart.

[0145] FIGS. 4A-4C illustrate variations of heart rate variability (HRV) data that the system 10 can generate and/or have stored in memory. FIG. 4A illustrates a variation of a reference data set that the system 10 can generate when determining a sleep performance score (e.g., the recharge score), and/or have stored in memory. Specifically, FIG. 4A illustrates a variation of a standard deviation graph 50 having a distribution curve 50a. As shown in FIG. 4A, the RMSSD score and percentage tile can be on the x-axis. The standard deviation curve 50a can be a user's historical ending RMSSD of the R-R intervals of the user's heart. The standard deviation curve 50a can be a cohort curve (e.g., an age, gender, ethnicity, health, and/or fitness level cohort curve). FIG. 4A illustrates that the distribution curve 50a can be an age cohort curve. The distribution curve 50a can be, for example, a curve corresponding to an age of 20 years old, 40 years old, 60 years old, 80 years old, and/or 65+ years old.

[0146] FIGS. 4B and 4C illustrate variations of reference data sets that the system 10 can have stored in memory. Specifically, FIG. 4B illustrates a variation of a percentage-tile graph 52 having a curve 52a that can be used to determine the total recovery points. The percentage tiles (e.g., 0%, 20%, 40%, 60%, 80%, 100%) can correspond to the one or more of the percentage-tiles associated with the HRV distribution curve of FIG. 4A. FIG. 4B further illustrates that the RMSSD of a user (e.g., during their last 5

minutes of light sleep before waking up) can be indexed to a 0-100 point scale. FIG. 4C illustrates a variation of an RMSSD distribution graph 54 having age-cohort curves 54a, 54b, 54c, 54d for ages 20 years old, 40 years old, 60 years old, and 80 years old, respectively. The RMSSD curves 54a, 54b, 54c, 54d can be used to determine the total recovery points. FIG. 4C further illustrates that the RMSSD data can have multiple age cohort curves. FIG. 4C further illustrates that the RMSSD of a user (e.g., during their last 5 minutes of light sleep before waking up) can be indexed to a 0-100 point scale. The system 10 can reference the non-cohort data of FIG. 4B and/or the cohort data of FIG. 4C when determining the total recovery points. The system 10 can reference the data of FIG. 4B when there is a sufficient number of data points to generate the plot of FIG. 4A, for example, when there are more than 3 to 5 nights of data. The system 10 can reference the data of FIG. 4C when there is an insufficient number of data points to generate the plot of FIG. 4A, for example, when there are less than 3 to 5 nights of data.

[0147] Extrapolation techniques such as weighted averages can be used to determine the points (i.e., the value on the y-axis) in FIGS. 2A-4C where there is one or more cohort curves (e.g., in FIGS. 2A-2C, FIGS. 3A-3C, and FIG. 4C).

Sleep Quality Score

[0148] The sleep quality score can be a function of one or multiple variables, for example, 1 to 5 or more variables, including every 1 variable increment within this range (e.g., 3 variables). For example, the sleep quality score can be a function of total sleep, total deep sleep, and sleep efficiency, or any combination thereof. The total sleep, total deep sleep, and sleep efficiency can be used to determine total sleep points, total deep sleep points, and sleep efficiency points, respectively. The system 10 can determine these points by referencing cohort and/or non-cohort data. Such data can be represented as a graph and can be stored in a memory (e.g., the data sets illustrated in FIGS. 2A-2C and/or FIGS. 3A-3C). The sleep quality score variables and/or the total points associated with each variable can be weighted. For example, the total sleep points can have a weight of about 25% to about 75%, including every 1% increment within this range (e.g., 40%, 50%). The total deep sleep points can have a weight of about 25% to about 75%, including every 1% increment within this range (e.g., 40%, 50%). The sleep efficiency points can have a weight of about 1% to about 51%, including every 1% increment within this range (e.g., 10%, 20%) For example, the sleep quality score can have a total sleep points weight—total deep sleep variable weight—sleep efficiency variable weight of about 40%-40%-20%, about 50%-40%-10%, about 50%-35%-15%. The sleep quality variables can have the same or different weights than the total sleep quality point weights.

[0149] The sleep quality score can be calculated by adding the total sleep time, deep sleep parameter, and sleep efficiency parameter. The sleep quality score can be calculated by weighing the total sleep time by 40%, deep sleep parameter by 40%, and sleep efficiency parameter by 20%. For example, the sleep quality score can be calculated with the following equation: Sleep Quality Score=50% (Total Sleep Time)+40% (Longest Deep Sleep)+10% (Sleep Efficiency).

[0150] Additionally or alternatively, the sleep quality score can be a function of sleep stage balance, number of

sleep disruptions, and magnitude of sleep disruptions. The system **10** can calculate one or more sleep quality scores (e.g., 1 to 5 or more sleep quality scores). For example, the system **10** can calculate a first sleep quality score and a second sleep quality score. The first sleep quality score can be a function of total sleep, total deep sleep, and sleep efficiency. The second sleep quality score can be a function of sleep stage balance, number of sleep disruptions, and magnitude of sleep disruptions.

[0151] The sleep quality score can be an objective and trackable measure of sleep performance. For example, the sleep quality score can be an objective and trackable measure of deep sleep quality. The system **10** can improve deep sleep quality, for example, by specifically targeting deep sleep by making one or more observations and/or recommendations to a user based on the sleep quality score and/or on one or more values of SWS-related parameters. For example, the system **10** can improve deep sleep by providing a user with one or more ways to improve their sleep quality score or one or more parameters related to SWS (e.g., audio stimulation, visual stimulation, cranial electrical stimulation, behavioral modification suggestions (e.g., “drink less coffee 4 hours before bed”), user awareness observations (e.g., “your stress level appears high”), guided relaxation/medication). The sleep performance systems **10** can recommend and/or activate sleep improvement programs based on various threshold scores related to the sleep quality score, or based entirely on the sleep quality score.

Brain Fitness Score

[0152] The brain fitness score can be a function of one or multiple variables, for example, 1 to 5 or more variables, including every 1 variable increment within this range (e.g., 3 variables). For example, the brain fitness score can be a function of total deep sleep, longest deep sleep duration, and strength of deep sleep, or any combination thereof. The total deep sleep, longest deep sleep duration, and strength of deep sleep can each be used to determine total deep sleep points, longest deep sleep duration points, and strength of deep sleep points, respectively. The system **10** can determine these points by referencing cohort and/or non-cohort data. Such data can be represented as a graph and can be stored in a memory (e.g., the data sets illustrated in FIGS. 2B, 2D and 2E and/or FIGS. 3B, 3D and 3E). The brain fitness score variables and/or the total points associated with each variable can be weighted. For example, the total deep sleep points can have a weight of about 50% to about 100%, including every 1% increment within this range (e.g., 80%). The longest deep sleep duration points can have a weight of about 1% to about 51%, including every 1% increment within this range (e.g., 10%). The strength of deep sleep points can have a weight of about 1% to about 51%, including every 1% increment within this range (e.g., 10%). For example, the brain fitness score can have a total deep sleep points weight—longest deep sleep duration points weight—strength of deep sleep points weight of about 80%-10%-10%, about 75%-15%-10%, about 70%-15%-15%, about 40%-40%-20%. The brain fitness score can also be a function of deep sleep amplitude. The system **10** can convert the deep sleep amplitude variable into an indexed point value between 0 and 100. The deep sleep amplitude points can have a weight of about 1% to about 51%, including every 1% increment within this range (e.g., 5%, 10%, 15%, 20%). For example, the brain fitness score can be

a function of total deep sleep, longest deep sleep duration, strength of deep sleep, and deep sleep amplitude, or any combination thereof.

[0153] The brain fitness score can be calculated by adding the total deep sleep time, longest deep sleep parameter, and deep sleep deficit parameter. The brain fitness score can be calculated by weighting the total deep sleep time by 80%, longest deep sleep parameter by 10%, and deep sleep deficit parameter by 10%. For example, the brain fitness score can be calculated with the following equation: Brain Fitness Score=80% (Total Deep Sleep Time)+10% (Longest Duration of Deep Sleep)+10% (Deep Sleep Deficit).

[0154] The brain fitness score can be calculated by adding the total deep sleep time, longest deep sleep parameter, and strength of deep sleep parameter. The brain fitness score can be calculated by weighting the total deep sleep time by 80%, longest deep sleep parameter by 10%, and strength of deep sleep parameter by 10%. For example, the brain fitness score can be calculated with the following equation: Brain Fitness Score=80% (Total Deep Sleep Time)+10% (Longest Duration of Deep Sleep)+10% (Strength of Deep Sleep).

[0155] The brain fitness score can be an objective and trackable measure of sleep performance. For example, the brain fitness score can be an objective and trackable measure of deep sleep quality. The system **10** can improve deep sleep quality, for example, by specifically targeting deep sleep by making one or more observations and/or recommendations to a user based on the brain fitness score and/or on one or more values of SWS-related parameters. For example, the system **10** can improve deep sleep by providing a user with one or more ways to improve their brain fitness score or one or more parameters related to SWS (e.g., audio stimulation, visual stimulation, cranial electrical stimulation, behavioral modification suggestions (e.g., “drink less coffee 4 hours before bed”), user awareness observations (e.g., “your stress level appears high”), guided relaxation/medication). The sleep performance systems **10** can recommend and/or activate sleep improvement programs based on various threshold scores related to the brain fitness score, or based entirely on the brain fitness score.

Recharge Score

[0156] The recharge score (also referred to as the recovery score) can be a function of one or multiple variables, for example, 1 to 5 or more variables, including every 1 variable increment within this range (e.g., 1 variable). The recharge score can be a function of a user’s HRV. For example, the recharge score can measure how much the HRV increases during sleep. The recharge score can be a function of a user’s RMSSD of their R-R intervals. The calculated RMSSD can be used to determine the number of recovery points associated with any given RMSSD value (e.g., the RMSSD values can correspond to a percentage-tile of the standard deviation distribution **50a** of FIG. 4A). For example, the recharge score can be the previous night RMSSD score as a percentage-tile of a user’s personal RMSSD distribution (e.g., the graph **50** of FIG. 4A). The system **10** can determine these points by referencing cohort and/or non-cohort data. Such data can be represented as a graph and can be generated and/or can be stored in a memory (e.g., the data sets illustrated in FIGS. 4A, 4B and/or 4C). The recovery points determined from the reference data in FIGS. 4B and 4C can be the recharge score. The RMSSD can be the only input into the recovery score, for example, by being translated into

a 0-100 point scale. Alternatively or additionally, the recharge points can be weighted with one or more other variables, for example, total sleep, total deep sleep, longest deep sleep duration, deep sleep amplitude, or any combination thereof. Each of these variables, including the RMSSD variable, can have a weight of about 1% to about 95%, including every 1% increment within this range (e.g., 20% each). For example, the RMSSD variable can have a weight of about 50% to about 95%, including every 1% increment within this range (e.g., 80%), with one or more other variables having a 5% to 50% weight (depending on the number of additional variables).

Influencers Score

[0157] The system 10 can monitor and keep track of factors that affect a user’s sleep. For example, the system 10 can keep track of a user’s behaviors and monitor the various effects that these behaviors have on the user’s sleep. The behaviors can include good and/or bad activities (also referred to individually and collectively as influencers/sleep factors). Positive (or good) influencers can positively affect a user’s sleep. Positive influencers can manifest in one or more of a user’s sleep performance scores, for example, by increasing the score, by increasing the score more quickly than without the positive behavior, by not decreasing the score, or by decreasing the score more slowly than without the positive behavior. Negative (or bad) influencers can negatively affect a user’s sleep. Negative influencers can manifest in one or more of a user’s sleep performance scores, for example, by decreasing the score, by decreasing the score more quickly than without the negative behavior, by not increasing the score, or by increasing the score more slowly than without the negative behavior.

[0158] The influencers can include factors such as audio stimulation, visual stimulation, cranial electrical stimulation, exercise, caffeine, alcohol, stress, quiet time, marijuana, coffee, tea, breathing exercises, meditation, listening to music, naps (e.g., time and duration of naps), diet, time of dinner (e.g., late dinner), nicotine, TV in bed, sugar, heavy/spicy foods, consistent bed time, bedtime tea, water, ear plugs/white noise, bath/shower, sleep medications, room temperature, flu/sick, jet lag, drank alcohol, complex carbohydrates before bed, melatonin, glass of water before bed, light meal, shower/bath before bed, TV before bed, computer/phone before bed, weather, or any combination thereof. A user can add their own factors/behaviors/influencers such that the influencer list can be partly or completely determined by user input. The system 10 can monitor from 0 to 100 or more positive influencers (e.g., 55 positive influencers). The system 10 can monitor from 0 to 100 or more negative influencers (e.g., 23 negative influencers).

[0159] The system 10 (e.g., the device 12, the device 20, and/or a remote server) can perform multivariate regression of the various behaviors/influencers (e.g., audio stimulation, exercise, caffeine, alcohol, stress, quiet time) on one or more of the sleep performance scores to determine the relative impact of each influencer on that performance score. An influencer can impact different sleep performance scores the same or differently (e.g., by increasing or decreasing it). For example, the system 10 can perform multivariate regression on the various behaviors/influencers (e.g., audio stimulation, exercise, caffeine, alcohol, stress, quiet time) on the sleep quality score to determine the relative impact of each on the

sleep quality score. The influencers score can be a coefficient of variables to the sleep performance scores (e.g., the sleep quality score).

Observations and Recommendations—Ah Ha’s

[0160] The system 10 can make sleep related observations and recommendations based on an analysis of one or more factors (e.g., influencers). The observations can also be referred to as performance insights, things worth noting, things worth mentioning, or “AH-HA’s.”

[0161] The observations can be tied to one or more determined parameters and/or to one or more sleep performance metrics (e.g., derivations involving one or more determined parameters). As described above, the observations can provide text summaries of a user’s sleep performance (e.g., “insufficient total deep sleep”), as well as insights related to the user’s sleep performance (e.g., “high stress levels,” “high stress levels detected”). The recommendations can include goal suggestions related to one or more influencers of the user’s sleep performance. The influencers can be variables and/or behaviors that can, may, and/or do affect sleep generally and/or the user’s sleep specifically. For example, the system 10 can provide recommendations such as “smoke one less cigarette today,” “go for a 10-20 minute walk at 7 pm,” “have your Wednesday glass of wine 30 minutes earlier today,” “plan something fun for this weekend”.

[0162] Table 1 below (next page) illustrates various factors (e.g., sleep quality factors) having various exemplary thresholds/events that trigger the listed exemplary observations and recommended programs. Table 1 further illustrates that not every observation needs to have a corresponding recommended action. Although Table 1 lists only 1 Ah-Ha with each factor, the system 10 can have 2 to 8 observations associated with each factor (e.g., 4 observations). The system 10 can then rotate the observations displayed to the user (e.g., using the device 20) on different days so that if the user has the same high-scoring or low-scoring factor repeatedly, the user will see different “ah-ha’s” for the same factor to inhibit or help prevent the user from becoming bored of the device 12 and/or to encourage the user to keep using the device 12. Although Table 1 lists only 1 recommended action associated with each factor, the system 10 can have 2 to 8 recommended actions associated with each factor (e.g., 4 recommended actions). The system 10 can then rotate the recommendations displayed to the user (e.g., using the device 20) on different days so that if the user has the same high-scoring or low-scoring factor repeatedly, the user will see different recommendations for the same factor to inhibit or help prevent the user from becoming bored of the device 12 and/or to encourage the user to keep using the device 12.

TABLE 1

Sleep Quality Ah-Ha’s and Recommendations		
Factor/Indicator	Observation (Ah-Ha)	Recommended Action
Total Sleep Points <80 points	Insufficient Total Sleep	None
Total Deep Sleep Points <80 points	Insufficient Total Deep Sleep	Audio Entrainment to Increase Sleep Quality by Increasing Deep Sleep

TABLE 1-continued

Sleep Quality Ah-Ha's and Recommendations		
Factor/Indicator	Observation (Ah-Ha)	Recommended Action
Sleep Efficiency <75%	Poor Sleep Efficiency	Guided Relaxation/Meditation
Time to Fall Asleep >20 min	Time to Fall Asleep Too Long	Guided Relaxation/Meditation
Time Awake During Night >40 min	Time Awake During Night Too Long	Guided Relaxation/Meditation
Sleep Cycle Interrupted at Stage 1, 2, 3, 4, or 5	Possible Sleep Interruption Observed	None

[0163] As Table 1 illustrates, the system 10 can determine the observations and recommendations via a lookup table. The lookup table can be stored in a memory (e.g., of the device 12, the device 20, of a remote server). One or more of the factors in the lookup table can be based on points associated with sleep parameters/metrics and/or sleep performance scores. The factors column lists the threshold values or events (e.g., sleep stage interruption) necessary to trigger the associated observation(s) and recommended action(s). The system 10 can recommend and/or activate a program based on the various threshold values and/or events in Table 1.

[0164] The system 10 can generate a lookup table over time, for example, using machine learning and artificial intelligence, with comparisons of personal results versus various cohorts, personal baselines, sleep performance scores, environmental factors, genetic factors, influencers, or any combination thereof.

[0165] FIG. 5 illustrates a variation of a lookup table 59. FIG. 5 illustrates that the "Ah Ha" points can be based on a user's performance against their goal. The user can specify the goal to be either a personal benchmark or a specified cohort. The rightmost "points" column indicates the points that the system 10 can tally whenever a contributor (e.g., factor) threshold is satisfied. The points in the rightmost column are cumulative (i.e., if a user scores <65 points for a cohort, then the system 10 will tally 6 points: 3 for <75 points+3 for <65 points). Up to 2, 3, 4, 5 or more Ah Has with the greatest number of points can be shown (e.g., displayed on the data display device 20). The system 10 can recommend and/or activate the "triggered recommendations" based on the various threshold values listed in the table 59.

Method of Use

[0166] FIG. 6 illustrates a variation of a process 60 that is implementable using and/or performable by the system 10. The method 60 can involve acquiring sleep data in operation 62. The acquiring operation 62 can include, for example, measuring, detecting, monitoring, and/or observing one or more parameters using EEG, EOG, EMG, ECG, HRV, RIP, pulse oximetry, pressure sensors, temperature sensors, or any combination thereof.

[0167] The method 60 can further involve analyzing sleep data to determine or calculate one or more sleep parameters/metrics in operation 64.

[0168] The method 60 can further involve determining sleep parameter/metric points for the sleep parameters/

metrics by determining an association between the sleep parameters/metrics and stored data (e.g., cohort data) in operation 66.

[0169] The method 60 can further involve generating one or more sleep scores based on the sleep parameter/metric points (e.g., sleep quality score, brain fitness score, recharge/recovery score, influencers score) in operation 68.

[0170] The method 60 can be an executable algorithm stored in memory that the system 10 (e.g., the device 12, the device 20, a remote server) can execute.

[0171] The system 10 can perform the method 60 every time a user uses the system 10 (e.g., at night or whenever they sleep).

[0172] FIG. 7A illustrates a variation of a method 70 for determining total sleep time points using the total sleep graph 30. The system 10 can determine the total sleep time points (y-axis) by referencing the total sleep time that the user had (x-axis), referencing the appropriate cohort curve (e.g., age cohort curve), and then determining the total sleep points associated with the total sleep time that the user had. The method 70 can involve, for example, referencing the appropriate cohort curve (e.g., age cohort curve) in operation 70a and then determining the total sleep points associated with the referenced curve in operation 70b. For example, for a 20 year old user having a total sleep time of 6 hours, the system 10 can reference the 20 years old age cohort curve 30a and determine that the total sleep points associated with 6 hours of total sleep is 74 points.

[0173] FIG. 7B illustrates a variation of a method 72 for determining total deep sleep time points using the total deep sleep graph 32. The system 10 can determine the total deep sleep time points (y-axis) by referencing the total deep sleep time that the user had (x-axis), referencing the appropriate cohort curve (e.g., age cohort curve), and then determining the total deep sleep points associated with the total deep sleep time that the user had. The method 72 can involve, for example, referencing the appropriate cohort curve (e.g., age cohort curve) in operation 72a and then determining the total deep sleep points associated with the referenced curve in operation 72b. For example, for a 20 year old user having a total deep sleep time of 34 minutes, the system 10 can reference the 20 years old age cohort curve 32a and determine that the total deep sleep points associated with 34 minutes of total deep sleep is 92 points. FIG. 7B further illustrates that the system 10 can have an audio entrainment threshold 73 associated with the total deep sleep time points. The audio entrainment threshold 73 can be from about 0 total deep sleep time points to about 90 total deep sleep time points, including every 1 point increment within this range (e.g., 70 points, 75 points, 80 points, 85 points). When the total deep sleep points fall under the audio entrainment threshold, the system 10 can be configured to recommend audio entrainment. For example, FIG. 7B illustrates that the audio entrainment threshold 73 can be about 80 points, where any score under 80 points will trigger a recommendation by the system 10 for the user to use audio entrainment.

[0174] FIG. 7C illustrates a variation of a method 74 for determining total deep sleep time points using the sleep efficiency graph 34. The system 10 can determine the sleep efficiency points (y-axis) by referencing the sleep efficiency that the user had (x-axis), referencing the appropriate cohort curve (e.g., age cohort curve), and then determining the sleep efficiency points associated with the sleep efficiency

that the user had. The method 74 can involve, for example, referencing the appropriate cohort curve (e.g., age cohort curve) in operation 74a and then determining the total deep sleep points associated with the referenced curve in operation 74b. For example, for a 20 year old user having a sleep efficiency of 72 (e.g., 72%), the system 10 can reference the 20 years old age cohort curve 34a and determine that the sleep efficiency points associated with a sleep efficiency of 72% is 33 points.

[0175] FIG. 7D illustrates a variation of a method 76 for determining longest deep sleep points using the longest deep sleep graph 36. The system 10 can determine the longest deep sleep points (y-axis) by referencing the longest deep sleep minutes that the user had (x-axis), referencing the appropriate curve (e.g., non-cohort or cohort-based curve), and then determining the longest deep sleep points associated with the longest deep sleep minutes that the user had. The method 76 can involve, for example, referencing the appropriate curve (e.g., non-cohort curve) in operation 76a and then determining the longest deep sleep points associated with the referenced curve in operation 76b. For example, for a 20 year old user having a longest deep sleep of 19 minutes, the system 10 can reference the curve 36a and determine that the longest deep sleep points associated with a longest deep sleep of 19 minutes is 72 points.

[0176] FIG. 7E illustrates a variation of a method 78 for determining deep sleep deficit points using the deep sleep deficit graph 38. The system 10 can determine the deep sleep deficit points (y-axis) by referencing the 5-day accumulated sleep deficit minutes that the user has (x-axis), referencing the appropriate curve (e.g., non-cohort or cohort-based curve), and then determining the deep sleep deficit points associated with the 5-day accumulated sleep deficit minutes that the user has. The method 78 can involve, for example, referencing the appropriate curve (e.g., non-cohort curve) in operation 78a and then determining the deep sleep deficit points associated with the referenced curve in operation 78b. For example, for a 20 year old user having a deep sleep deficit of 100 minutes, the system 10 can reference the curve 38a and determine that the deep sleep deficit points associated with a 5-day accumulated sleep deficit of 100 minutes is 57 points.

[0177] FIGS. 8A-8D illustrate variations of methods 70, 72, 74, and 76 using graphs 40, 42, 44, and 46, respectively.

[0178] For example, FIG. 8A illustrates that for a 40 year old user having a total sleep time of 405 minutes, the system 10 can reference the 40 years old age cohort curve 40a and determine that the total sleep points associated with 405 minutes of total sleep is 88 points.

[0179] For example, FIG. 8B illustrates that for a 40 year old user having a total deep sleep time of 45 minutes, the system 10 can reference the 40 years old age cohort curve 42a and determine that the total deep sleep points associated with 45 minutes of total deep sleep is 45 points.

[0180] For example, FIG. 8C illustrates that for a 40 year old user having a sleep efficiency of 98 (e.g., 98%), the system 10 can reference the 40 years old age cohort curve 44a and determine that the sleep efficiency points associated with a sleep efficiency of 98% is 100 points.

[0181] For example, FIG. 8D illustrates that for a 40 year old user having a longest deep sleep of 24 minutes, the system 10 can reference the curve 46a and determine that the longest deep sleep points associated with a longest deep sleep of 24 minutes is 74 points.

[0182] FIG. 8E illustrates a variation of a method 79 for determining strength of deep sleep points using the strength of deep sleep graph 49. The system 10 can determine the strength of deep sleep points (y-axis) by referencing the RMS of SWS that the user had (x-axis), referencing the appropriate curve (e.g., non-cohort or cohort-based curve), and then determining the strength of deep sleep points associated with the RMS of SWS that the user had. The method 79 can involve, for example, referencing the appropriate curve (e.g., non-cohort curve) in operation 79a and then determining the longest deep sleep points associated with the referenced curve in operation 79b. For example, for a 40 year old user having a RMS of the amplitude of the strength of deep sleep of 22, the system 10 can reference the curve 49a and determine that the strength of deep sleep points associated an RMS of SWS of 22 is 26 points.

[0183] FIGS. 9A and 9B illustrate a variation of a process 80 that is implementable using and/or performable by the system 10 for determining the sleep quality score. The method 80 can involve determining the total and weighted sleep time points in operation 82, determining the total and weighted deep sleep points in operation 84, and/or determining the total and weighted sleep efficiency points in operation 86.

[0184] FIG. 9A illustrates that the operations 82, 84, and 86 can involve determining the total sleep points, total deep sleep points, and sleep efficiency points according to methods 70, 72, and 74, respectively. FIG. 9A further illustrates that the operations 82, 84, and 86 can involve weighting the total sleep points, total deep sleep points, and sleep efficiency points with weights of 40%, 40%, and 20%, respectively. FIG. 9A illustrates calculated weighted points for each of the operations 82, 84, and 86 using, for example, the points determined in the methods illustrated in FIGS. 7A-7C. FIG. 9A further illustrates that the method 80 can involve calculating the weighted points for each operation 82, 84, and 86 in operation 88. FIG. 9A further illustrates that the sleep quality score 89 can be determined by adding the weighted points determined from operations 82, 84, and 86 together. For example, FIG. 9A illustrates that the sleep quality score 89 can be 73 points using the methods and weights described.

[0185] FIG. 9B illustrates that the operations 82, 84, and 86 can involve determining the total sleep points, total deep sleep points, and sleep efficiency points according to methods 70, 72, and 74, respectively. FIG. 9B further illustrates that the operations 82, 84, and 86 can involve weighting the total sleep points, total deep sleep points, and sleep efficiency points with weights of 50%, 40%, and 10%, respectively. FIG. 9B illustrates calculated weighted points for each of the operations 82, 84, and 86 using, for example, the points determined in the methods illustrated in FIGS. 8A-8C. FIG. 9B illustrates that the sleep quality score 89 can be 72 points using the methods and weights described.

[0186] FIGS. 10A and 10B illustrate a variation of a process 90 that is implementable using and/or performable by the system 10 for determining the brain fitness score. The method 90 can involve determining the total and weighted deep sleep points in operation 92, determining the total and weighted longest deep sleep points in operation 94, and/or determining the total and weighted deep sleep deficit points and/or strength of deep sleep points in operation 86.

[0187] FIG. 10A illustrates that the operations 92, 94, and 96 can involve determining the total deep sleep points, total

longest deep sleep points, and total deep sleep deficit points according to methods 72, 76, and 78, respectively. FIG. 10A further illustrates that the operations 92, 94, and 96 can involve weighting the total deep sleep points, total longest deep sleep points, and total deep sleep deficit points with weights of 80%, 10%, and 10%, respectively. FIG. 10A illustrates calculated weighted points for each of the operations 92, 94, and 96 using, for example, the points determined in the methods illustrated in FIGS. 7B, 7D, and 7E, respectively. FIG. 10A further illustrates that the method 90 can involve calculating the weighted points for each operation 92, 94, and 96 in operation 98. FIG. 10A further illustrates that brain fitness score 99 can be determined by adding the weighted points determined from operations 92, 94, and 96 together. For example, FIG. 10A illustrates that the brain fitness score 99 can be 86.5 points using the methods and weights described.

[0188] If the user does not wear the device 12 for two or more consecutive nights (e.g., 5 consecutive nights), then the deep sleep deficit metric can be excluded from the sleep performance score calculations (e.g., the brain fitness score calculation 90) and the other weightings (e.g., of the total sleep metric and the longest deep sleep metric) can be scaled up to 50% each.

[0189] FIG. 10B illustrates that the operations 92, 94, and 96 can involve determining the total deep sleep points, total longest deep sleep points, and total deep sleep strength points according to methods 72, 76, and 78, respectively. FIG. 10B further illustrates that the operations 92, 94, and 96 can involve weighting the total sleep points, total deep sleep points, and sleep efficiency points with weights of 80%, 10%, and 10%, respectively. FIG. 10B illustrates calculated weighted points for each of the operations 92, 94, and 96 using, for example, the points determined in the methods illustrated in FIGS. 8B, 8D, and 8E, respectively. FIG. 9B illustrates that the brain fitness score 99 can be 46 points using the methods and weights described.

[0190] If the user does not wear the device 12 for two or more consecutive nights (e.g., 5 consecutive nights), then the strength of deep sleep metric can be excluded from the sleep performance score calculations (e.g., the brain fitness score calculation 90) and the other weightings (e.g., of the total sleep metric and the total longest deep sleep metric) can be scaled up to 50% each.

User Interface

[0191] FIG. 11A illustrates that the data display device 20 can display a sleep summary graphical user interface (GUI) 11a having the illustrated display features.

[0192] FIG. 11B illustrates that the data display device 20 can display a sleep summary GUI 11b having the illustrated display features.

[0193] FIGS. 11C and 11D illustrate that the data display device 20 can display a sleep quality GUI 11c and 11d having the illustrated display features.

[0194] FIGS. 11E illustrates that the data display device 20 can display a brain fitness GUI 11e having the illustrated display features.

[0195] FIGS. 11F-11H illustrate that the data display device 20 can display a recovery/recharge GUI 11f, 11g, and 11h having the illustrated display features.

[0196] FIGS. 11I and 11J illustrate that the data display device 20 can display an influencers GUI 11i and 11j having the illustrated display features.

Derivation of Total Sleep Time Reference Curves

[0197] Total sleep time data can include research data, user data, or both. The total sleep time data can be separated into cohorts, for example, based on age, gender, ethnicity, health, fitness level, or any combination thereof. Total sleep time reference curves can be derived from total sleep time data. For example, cohort curves and/or non-cohort curves can be derived from total sleep time data.

[0198] A method for determining total sleep time reference curves can include using data from published research. When determining age-based cohort curves for total sleep time, for example, such research can include Walter Moraes, Ronaldo Piovezan, Dalva Poyares, Lia Rita Bittencourt, Rogerio Santos-Silva, Sergio Tufik "Effects of aging on sleep structure throughout adulthood: a population based study". *Sleep Medicine* 15 (2014) 401-409; and Ohayon M M, Carskadon M A, Guilleminault C, Vitiello M V. "Meta-analysis of quantitative sleep parameters from childhood to old age in healthy individuals: developing normative sleep values across the human lifespan". *Sleep*. Nov. 1, 2004, which are each herein incorporated by reference in their entireties for all purposes. For example, FIG. 12A illustrates that data from Table 1 of the Moraes study can be used, and FIG. 12B illustrates that data from a figure of the Ohayon study can be used.

[0199] For any given data set (e.g., data sets having age cohorts), data of one or more cohort groupings (e.g., ages and/or age groups) can be used, for example, 1 to 10 or more groupings (e.g., three ages/age groups, four ages/age groups, five ages/age groups). For example, FIG. 13A illustrates that the data for age groups 20-24, 40-44, 60-64 and 75-80 can be selected from the Moraes study, and FIG. 13B illustrates that the data for ages 20, 40, 60 and 80 can be selected from the Ohayon study.

[0200] For any given data set (e.g., Moraes and Ohayon), one or multiple total sleep time statistics can be determined for each of the selected cohorts (e.g., ages/age groups) such as the average and standard deviation. For example, the average total sleep time for the selected cohorts (e.g., ages/age groups) can be determined, and from the calculated average, one or more standard deviations above and/or below the calculated average can be determined. For example, one, two, or three standard deviations above and/or below the average can be determined. The average and standard deviations can be plot points (also referred to as key points) to which a cohort curve can be fitted. A cohort curve can be generated using 1 to 7 or more plot points. The average can but need not be used as a plot point. A standard deviation can but need not be used as a plot point. When a cohort curve is generated, the plot points can include any combination of the average, one standard deviation above the average, two standard deviations above the average, three standard deviations above the average, one standard deviation below the average, two standard deviations below the average and three standard deviations below the average. For example, when a cohort curve is generated using 3 plot points, the 3 plot points can be the average, one standard deviation above the average and one standard deviation below the average. As another example, when a cohort curve is generated using 5 plot points, the 5 plot points can be the average, one standard deviation above the average, two standard deviations above the average, one standard deviation below the average and two standard deviations below the average. As yet another example, when a cohort curve is

generated using 7 plot points, the 7 plot points can be the average, one standard deviation above the average, two standard deviations above the average, three standard deviations above the average, one standard deviation below the average, two standard deviations below the average and three standard deviations below the average.

[0201] Where multiple data sets are used (e.g., the Moraes and Ohayon data sets), the average total sleep time for the cohorts (e.g., ages/age groups) of each study can be determined, along with the standard deviations of the determined averages. A composite of the determined averages and standard deviations can then be used. The composite can include any combination of the determined plot points of each data set. For example, the composite can include an average of the determined plot points of each data set. The composite can include the plot points from each data set, an average of the corresponding plot points in each data set, or both. For example, the plot points of each data set can be plotted, an average of the like plot points in the data sets can be plotted, or both, where like plot points, using a two study example, can correspond to first study average-second study average and first study 1/2/3 standard deviation above/below-second study 1/2/3 standard deviation above/below, respectively. For example, the average and standard deviations for the 20-24 age group of the Moraes study and the average and standard deviations for the 20 year old age category of the Ohayon study can both be plotted, or the averages and corresponding standard deviations of both studies can be averaged and then plotted, or both. For example, the Moraes-average and the Ohayon average can be averaged, and each Moraes-standard deviation can be averaged with the corresponding Ohayon-standard deviation (e.g., the Moraes 1 above-Ohayon 1 above standard deviations can be averaged together, the Moraes 1 below-Ohayon 1 below standard deviations can be averaged together, the Moraes 2 above-Ohayon 2 above standard deviations can be averaged together, the Moraes 2 below-Ohayon 2 below standard deviations can be averaged together, the Moraes 3 above-Ohayon 3 above standard deviations can be averaged together, the Moraes 3 below-Ohayon 3 below standard deviations can be averaged together, or any combination thereof).

[0202] The determined averages and standard deviations can be assigned a total sleep time point value, where the total sleep time points can be on a total sleep time point scale having a minimum and maximum number of points, for example, a 0-100 point scale. The point scale can be linear or non-linear (e.g., logarithmic). A point value can be assigned to each average and standard deviation. For example, for a 100 point scale, the average for a given total sleep time cohort (e.g., age/age group) can be assigned 85 points, one standard deviation above the average can be assigned 95 points, two standard deviations above the average can be assigned 100 points, one standard deviation below the average can be assigned 70 points and two standard deviations below the average can be assigned 35 points. The maximum point value can be 100 points and the minimum point value can be 0 points. The points assigned to the total sleep time statistics can be the same or different from the points assigned to statistics of other sleep variables (e.g., total deep sleep, sleep efficiency, longest deep sleep duration, strength of deep sleep, recovery). The minimum y-intercept for the total sleep time can be zero, less than zero, or greater than zero for a total sleep time of 0 minutes.

[0203] The total sleep time averages and corresponding standard deviations for each cohort (e.g., age/age group)—also collectively referred to as data points—can be plotted, with each data point being plotted according to its age/age group (e.g., on the x-axis) and the point value assigned (e.g., on the y-axis). To determine the cohort curves (e.g., age-based cohort curves), a polynomial curve can be fitted to the plotted points. The plotted points can be composite points from multiple studies. Scores for in-between cohorts (e.g., ages/age groups) can be determined proportionately. For example, for age 25, which is one-fourth between ages 20 and 40, the resulting score can be one-fourth between the age 20 and 40 scores.

[0204] FIGS. 14A-14D illustrate how 5 key points can be determined for four different age groups: 20 year old (FIG. 14A), 40 year old (FIG. 14B), 60 year old (FIG. 14C) and 80 year old (FIG. 14D). The top halves of FIGS. 14A-14D illustrate tables for the statistics (e.g., averages and standard deviations) calculated from total sleep time data. For example, row 1 of the tables lists the average total sleep time for Moraes (20 yr: 376 minutes) and Ohayon (20 yr: 450 minutes), as well as a composite (e.g., average) of the two studies in the NG column (20 yr: $(376+450)/2=413$ minutes). Row 2 lists the standard deviation of the average and row 3 lists the standard deviation percentage relative to the average (e.g., 20 yr Moraes: $(75/376)\times 100=20\%$). The NG column lists the statistics derived from Moraes and Ohayon. For example, row 4 of the NG column relists the calculated total sleep time average (20 yr: 413 minutes) and rows 5-8 list the standard deviations shown, with the assigned total sleep time scores listed in the SCORES column. The statistics in rows 4-8 are an exemplary 5 key point set. Once the 5 key points are determined for an age group (e.g., the values shown in rows 4-8), the points can be plotted. A trend line can be determined which best fits the 5 points (e.g., see the bottom halves of FIGS. 14A-14D), where the trend line can be a polynomial or non-polynomial trend line. The five key points calculated in the top halves of FIGS. 14A-14D are denoted as the five plotted points along each of the best fit curves in the bottom halves of FIGS. 14A-14D. The trend line can be plotted and smoothed. These generated trend lines can be the derived total sleep time cohort curves. For example, FIGS. 14A-14D illustrate polynomial age-cohort curves **30a**, **30b**, **30c** and **30d** for ages 20, 40, 60 and 80, respectively. The polynomial equation for the 20 yr old curve **30a** can be $y=-0.0012x^2+1.2298x-218.87$ with $R^2=0.9906$. The polynomial equation for the 40 yr old curve **30b** can be $y=-0.0018x^2+1.5929x-263.13$ with $R^2=0.9906$. The polynomial equation for the 60 yr old curve **30c** can be $y=-0.0017x^2+1.4744x-223.4$ with $R^2=0.9906$. The polynomial equation for the 80 yr old curve **30d** can be $y=-0.0019x^2+1.4986x-203.09$ with $R^2=0.9906$. The curves **30a**, **30b**, **30c** and **30d** can alternatively be the age-cohort curves **40a**, **40b**, **40c** and **40d** for which the trend lines are non-polynomial curves.

[0205] FIG. 15A illustrates curves **30a-30d** plotted together and smoothed. For example, upon reaching max/min scores of 100/0, it can be assumed the curves will remain at 100/0 points for scores. This can correspond to the flat regions of the generated curves. However, scores outside 3 standard deviations are considered extreme and the user can get a corresponding notifying alert. The alert can include a request to the user that they recalibrate the device, can include an alert related the user's well-being, or both.

[0206] In this way, total sleep time points by age can be determined, for example, by reference to the total sleep time reference curves. For example, FIG. 15B illustrates a variation of a table of exemplary total sleep time scores using the cohort curves 30a-30d of FIG. 15A. The table of FIG. 15B is also referred to as a total sleep time scoring table.

Derivation of Total Deep Sleep Reference Curves

[0207] Total deep sleep data (also referred to as deep sleep duration data) can include research data, user data, or both. The total deep sleep data can be separated into cohorts, for example, based on age, gender, ethnicity, health, fitness level, or any combination thereof. Total deep sleep reference curves can be derived from total deep sleep data. For example, cohort curves and/or non-cohort curves can be derived from total deep sleep data.

[0208] A method for determining total deep sleep reference curves can include using data from published research. When determining age-based cohort curves for total deep sleep, for example, such research can include the Moraes and Ohayon studies incorporated above. For example, FIG. 12A illustrates that data from Table 1 of the Moraes study can be used, and FIG. 16 illustrates that data from a figure of the Ohayon study can be used.

[0209] For any given data set (e.g., data sets having age cohorts), data of one or more cohort groupings (e.g., ages and/or age groups) can be used, for example, 1 to 10 or more groupings (e.g., three ages/age groups, four ages/age groups, five ages/age groups). For example, FIG. 17A illustrates that the data for age groups 20-24, 40-44, 60-64 and 75-80 can be selected from the Moraes study, and FIG. 17B illustrates that the data for ages 20, 40, 60 and 80 can be selected from the Ohayon study.

[0210] For any given data set (e.g., Moraes and Ohayon), one or multiple total deep sleep statistics can be determined for each of the selected cohorts (e.g., ages/age groups) such as the average and standard deviation. From the calculated average, one or more standard deviations above and/or below the calculated average can be determined as described above with reference to deriving the total sleep time cohort curves.

[0211] Where multiple data sets are used (e.g., the Moraes and Ohayon data sets), the average total deep sleep for the cohorts (e.g., ages/age groups) of each study can be determined, along with the standard deviations of the determined averages. A composite of the determined averages and standard deviations can then be used or derived as described above with reference to deriving the total sleep time cohort curves.

[0212] The determined averages and standard deviations can be assigned a total deep sleep point value, where the total deep sleep points can be on a total deep sleep point scale having a minimum and maximum number of points, for example, a 0-100 point scale. The point scale can be linear or non-linear (e.g., logarithmic). A point value can be assigned to each average and standard deviation. The points assigned to the total deep sleep statistics can be the same or different from the points assigned to statistics of other sleep variables (e.g., total sleep time, sleep efficiency, longest deep sleep duration, strength of deep sleep, recovery). The total deep sleep assigned points can be modified from the total sleep time assigned points when, for example, the distribution band for total deep sleep duration is tighter than the total sleep time distribution band. For example, for a 100 point

scale, the average for a given total deep sleep cohort (e.g., age/age group) can be assigned 85 points, one standard deviation above the average can be assigned 95 points, two standard deviations above the average can be assigned 100 points, one standard deviation below the average can be assigned 50 points and two standard deviations below the average can be assigned 15 points. The maximum point value can be 100 points and the minimum point value can be 0 points. The minimum y-intercept for the total deep sleep can be zero, less than zero, or greater than zero for a total deep sleep of 0 minutes.

[0213] The total deep sleep averages and corresponding standard deviations for each cohort (e.g., age/age group)—also collectively referred to as data points—can be plotted and a curve can be fitted to the plotted points as described above with reference to deriving the total sleep time reference curves.

[0214] FIGS. 18A-18D illustrate how 5 key points can be determined for four different age groups: 20 year old (FIG. 18A), 40 year old (FIG. 18B), 60 year old (FIG. 18C) and 80 year old (FIG. 18D). The top halves of FIGS. 18A-18D illustrate tables for the statistics (e.g., averages and standard deviations) calculated from total deep sleep data. For example, for the values shown in the tables, row 1 lists the average total sleep time (TST), row 2 lists slow wave sleep (SWS) as a percentage of TST, row 3 lists the average deep sleep duration (DSD), row 4 lists the standard deviation of the average DSD and row 5 lists the standard deviation percentage relative to the average DSD (e.g., 20 yr Moraes: $(26/87) \times 100 = 30\%$). The NG column lists the statistics derived from Moraes and Ohayon. For example, row 3 lists the average DSD for Moraes (20 yr: 87 minutes) and Ohayon (20 yr: 108 minutes), as well as a composite (e.g., average) of the two studies in the NG column (20 yr: $(87+108)/2=97.5$ minutes). Row 6 of the NG column relists the calculated DSD average (20 yr: 97.5 minutes) and rows 6-10 list the standard deviations shown, with the assigned deep sleep duration scores listed in the SCORES column. The statistics in rows 6-10 are an exemplary 5 key point set. Once the 5 key points are determined for an age group (e.g., the values shown in rows 6-10), the points can be plotted. A trend line can be determined which best fits the 5 points (e.g., see the bottom halves of FIGS. 18A-18D), where the trend line can be a polynomial or non-polynomial trend line. The five key points calculated in the top halves of FIGS. 18A-18D are denoted as the five plotted points along each of the best fit curves in the bottom halves of FIGS. 18A-18D. The trend line can be plotted and smoothed. These generated trend lines can be the derived total deep sleep cohort curves. For example, FIGS. 18A-18D illustrate polynomial age-cohort curves 32a, 32b, 32c and 32d for ages 20, 40, 60 and 80, respectively. The polynomial equation for the 20 yr old curve 32a can be $y = -0.0063x^2 + 1.9255x - 46.537$ with $R^2 = 0.9939$. The polynomial equation for the 40 yr old curve 32b can be $y = -0.0086x^2 + 1.9353x - 8.121$ with $R^2 = 0.9939$. The polynomial equation for the 60 yr old curve 32c can be $y = -0.0123x^2 + 2.2326x$ with $R^2 = 0.9289$. The polynomial equation for the 80 yr old curve 32d can be $y = -0.0144x^2 + 2.425x$ with $R^2 = 0.7264$. The curves 32a, 32b, 32c and 32d can alternatively be the age-cohort curves 42a, 42b, 42c and 42d for which the trend lines are non-polynomial curves.

[0215] FIG. 19A illustrates curves 32a-32d plotted together and smoothed. For example, upon reaching max/min scores of 100/0, it can be assumed the curves will

remain at 100/0 points for scores. This can correspond to the flat regions of the generated curves. However, scores outside 3 standard deviations are considered extreme and the user can get a corresponding notifying alert. The alert can include a request to the user that they recalibrate the device, can include an alert related the user's well-being, or both.

[0216] In this way, total deep sleep points by age can be determined, for example, by reference to the total deep sleep reference curves. For example, FIG. 19B illustrates a variation of a table of exemplary total deep sleep scores using the cohort curves 32a-32d of FIG. 19A. The table of FIG. 19B is also referred to as a total deep sleep scoring table.

Derivation of Sleep Efficiency Reference Curves

[0217] Sleep efficiency data can include research data, user data, or both. Sleep efficiency data can be separated into cohorts, for example, based on age, gender, ethnicity, health, fitness level, or any combination thereof. Sleep efficiency reference curves can be derived from total sleep time data and/or from sleep efficiency data. For example, cohort curves and/or non-cohort curves can be derived from total sleep time data and/or sleep efficiency data.

[0218] A method for determining sleep efficiency reference curves can include using data from published research. When determining age-based cohort curves for sleep efficiency, for example, such research can include the Moraes and Ohayon studies incorporated above. For example, FIG. 12A illustrates that data from Table 1 of the Moraes study can be used, and FIG. 20 illustrates that data from a figure of the Ohayon study can be used.

[0219] For any given data set (e.g., data sets having age cohorts), data of one or more cohort groupings (e.g., ages and/or age groups) can be used, for example, 1 to 10 or more groupings (e.g., three ages/age groups, four ages/age groups, five ages/age groups). For example, FIG. 21 illustrates that the data for age groups 20-24, 40-44, 60-64 and 75-80 can be selected from the Moraes study, and FIG. 20 further illustrates that the data for ages 20, 40, 60 and 80 can be selected from the Ohayon study.

[0220] For any given data set (e.g., Moraes and Ohayon), one or multiple sleep efficiency statistics can be determined for each of the selected cohorts (e.g., ages/age groups) such as the average and standard deviation. From the calculated average, one or more standard deviations above and/or below the calculated average can be determined as described above with reference to deriving the total sleep time and total deep sleep cohort curves.

[0221] Where multiple data sets are used (e.g., the Moraes and Ohayon data sets), the average sleep efficiency for the cohorts (e.g., ages/age groups) of each study can be determined, along with the standard deviations of the determined averages. A composite of the determined averages and standard deviations can then be used or derived as described above with reference to deriving the total sleep time and total deep sleep cohort curves.

[0222] The determined averages and standard deviations can be assigned a sleep efficiency point value, where the sleep efficiency points can be on a sleep efficiency point scale having a minimum and maximum number of points, for example, a 0-100 point scale. The point scale can be linear or non-linear (e.g., logarithmic). A point value can be assigned to each average and standard deviation. The points assigned to the sleep efficiency statistics can be the same or different from the points assigned to statistics of other sleep

variables (e.g., total sleep time, total deep sleep, longest deep sleep duration, strength of deep sleep, recovery). For example, for a 100 point scale, the average for a given sleep efficiency cohort (e.g., age/age group) can be assigned 85 points, one standard deviation above the average can be assigned 95 points, two standard deviations above the average can be assigned 100 points, one standard deviation below the average can be assigned 70 points and two standard deviations below the average can be assigned 35 points. The maximum point value can be 100 points and the minimum point value can be 0 points. The minimum y-intercept for the sleep efficiency can be zero, less than zero, or greater than zero for a sleep efficiency of zero.

[0223] The sleep efficiency averages and corresponding standard deviations for each cohort (e.g., age/age group)—also collectively referred to as data points—can be plotted and a curve can be fitted to the plotted points as described above with reference to deriving the total sleep time reference curves.

[0224] FIGS. 22A-22D illustrate how 5 key points can be determined for four different age groups: 20 year old (FIG. 22A), 40 year old (FIG. 22B), 60 year old (FIG. 22C) and 80 year old (FIG. 22D). The top halves of FIGS. 22A-22D illustrate tables for the statistics (e.g., averages and standard deviations) calculated from sleep efficiency data. For example, row 1 of the tables lists the average sleep efficiency for Moraes (20 yr: 88) and Ohayon (20 yr: 96), as well as a composite (e.g., average) of the two studies in the NG column (20 yr: $(88 + 96)/2 = 92$). Row 2 lists the standard deviation of the average and row 3 lists the standard deviation percentage relative to the average (e.g., 20 yr Moraes: $(9.5/88) \times 100 = 11\%$). The NG column lists the statistics derived from Moraes and Ohayon. For example, row 4 of the NG column relists the calculated sleep efficiency average (20 yr: 92) and rows 5-8 list the standard deviations shown, with the assigned sleep efficiency scores listed in the SCORES column. The statistics in rows 4-8 are an exemplary 5 key point set. Once the 5 key points are determined for an age group (e.g., the values shown in rows 4-8), the points can be plotted. A trend line can be determined which best fits the 5 points (e.g., see the bottom halves of FIGS. 22A-22D), where the trend line can be a polynomial or non-polynomial trend line. The five key points calculated in the top halves of FIGS. 22A-22D are denoted as the five plotted points along each of the best fit curves in the bottom halves of FIGS. 22A-22D. The trend line can be plotted and smoothed. These generated trend lines can be the derived sleep efficiency cohort curves. For example, FIGS. 22A-22D illustrate polynomial age-cohort curves 34a, 34b, 34c and 34d for ages 20, 40, 60 and 80, respectively. The polynomial equation for the 20 yr old curve 34a can be $y = -0.1019x^2 + 21.046x - 987.46$. The polynomial equation for the 40 yr old curve 34b can be $y = -0.0725x^2 + 14.575x - 632.82$. The polynomial equation for the 60 yr old curve 34c can be $y = -0.0643x^2 + 12.202x - 479.98$. The polynomial equation for the 80 yr old curve 34d can be $y = -0.0514x^2 + 8.9367x - 288.89$. The curves 34a, 34b, 34c and 34d can alternatively be the age-cohort curves 44a, 44b, 44c and 44d for which the trend lines are non-polynomial curves.

[0225] FIG. 23A illustrates curves 34a-34d plotted together and smoothed. For example, upon reaching max/min scores of 100/0, it can be assumed the curves will remain at 100/0 points for scores. This can correspond to the flat regions of the generated curves. However, scores outside

3 standard deviations are considered extreme and the user can get a corresponding notifying alert. The alert can include a request to the user that they recalibrate the device, can include an alert related the user's well-being, or both.

[0226] In this way, sleep efficiency points by age can be determined, for example, by reference to the sleep efficiency reference curves. For example, FIG. 23B illustrates a variation of a table of exemplary sleep efficiency scores using the cohort curves 34a-34d of FIG. 23A. The table of FIG. 23B is also referred to as a sleep efficiency scoring table.

Derivation of Longest Duration of Deep Sleep Reference Curves

[0227] Longest duration of deep sleep (also referred to as longest deep sleep) can include research data, user data, or both. The longest deep sleep data can be separated into cohorts, for example, based on age, gender, ethnicity, health, fitness level, or any combination thereof. Longest deep sleep reference curves can be derived from longest deep sleep data. For example, cohort curves and/or non-cohort curves can be derived from longest deep sleep data.

[0228] A method for determining longest deep sleep reference curves can include using data from research or acquired from users during use (e.g., user data). When determining reference curves for longest deep sleep, such data can include user data (e.g., acquired via device 12) and an analysis of a polysomnogram dataset (e.g., from The Montreal Archive of Sleep Studies (MASS)) to profile overall averages and standard deviations for longest deep sleep. The averages and standard deviations can be separated in cohorts, for example, by age, gender, ethnicity, health, fitness level, or any combination thereof. The user data can be used to derive the averages and standard deviations based on age/age group and other defined cohorts for longest deep sleep. The weighting of the longest deep sleep variable can be increased to more than 10%, for example, a percentage of 11% to 80% or more, as more user data is collected.

[0229] The longest deep sleep cohort curves can be derived as described above with reference to deriving the total sleep time cohort curves, the total deep sleep cohort curves, the sleep efficiency cohort curves, or any combination thereof.

[0230] For example, for a 100 point scale, the average for a given longest deep sleep data set (e.g., cohort) can be assigned 85 points, one standard deviation above the average can be assigned 95 points, two standard deviations above the average can be assigned 100 points, one standard deviation below the average can be assigned 70 points and two standard deviations below the average can be assigned 35 points. The maximum point value can be 100 points and the minimum point value can be 0 points. The minimum y-intercept for the longest deep sleep can be zero, less than zero or greater than zero for a total deep sleep time of 0 minutes.

[0231] The longest deep sleep averages and corresponding standard deviations for the longest deep sleep data set—also collectively referred to as data points—can be plotted and a curve can be fitted to the plotted points as described above with reference to deriving any of the other reference curves.

[0232] For example, FIG. 24A illustrates how 5 key points can be determined for the longest deep sleep variable. Row 1 of the table lists the average longest deep sleep (e.g., acquired from one or multiple users using the device 12 or other sleep monitoring device), row 2 lists the standard

deviation of the average and row 3 lists the standard deviation percentage relative to the average (e.g., $32/40 \times 100=80\%$). The NG column lists the statistics derived from the analyzed data. For example, row 4 of the NG column relists the calculated longest deep sleep average (40 minutes) and rows 5-8 list the standard deviations shown, with the assigned longest deep sleep scores listed in the SCORES column. The statistics in rows 4-8 are an exemplary 5 key point set. Once the 5 key points are determined (e.g., the values shown in rows 4-8), the points can be plotted. A trend line can be determined which best fits the 5 points (e.g., see FIG. 24B), where the trend line can be a polynomial or non-polynomial trend line. The five key points calculated in FIG. 24A are denoted as the five plotted points along the best fit curve in FIG. 24B. The trend line can be plotted and smoothed. These generated trend line(s) can be the longest deep sleep reference curve(s).

[0233] For any of the sleep variables, the data can be used to derive cohort curves, non-cohort curves, or both. For example, FIG. 24B illustrates that the longest deep sleep data can be used to generate a polynomial non-cohort longest deep sleep reference curve 36a. The curve 36a in FIG. 24 can have the illustrated equation: $y=-0.017x^2+2.7673x-7.3885$, where $R^2=0.9651$. The curve 36a can alternatively be curve 46a for which the trend line is a non-polynomial curve. The curve 36a can alternatively be a non-polynomial curve, or both polynomial and non-polynomial curves can be fitted to the data.

[0234] In this way, longest deep sleep points can be determined, for example, by reference to the longest deep sleep reference curve(s). For example, FIG. 24C illustrates a variation of a table of exemplary longest deep sleep scores using the curve 36a of FIG. 24B. The left column is the longest deep sleep in minutes and the right column is the corresponding longest deep sleep score for each of the longest deep sleep values listed. The table of FIG. 24B is also referred to as a longest deep sleep scoring table.

[0235] FIG. 24D illustrates another example of a longest deep sleep curve 36a defined by the illustrated polynomial equation: $y=-0.0156x^2+2.5625x-2.4287$, where $R^2=0.9968$.

Derivation of Strength of Deep Sleep Reference Curves

[0236] Strength of deep sleep (also referred to as deep sleep strength) can include research data, user data, or both. The deep sleep strength data can be separated into cohorts, for example, based on age, gender, ethnicity, health, fitness level, or any combination thereof. Deep sleep strength reference curves can be derived from deep sleep strength data. For example, cohort curves and/or non-cohort curves can be derived from deep sleep strength data.

[0237] A method for determining deep sleep strength reference curves can include using data from research or acquired from users during use (e.g., user data). When determining reference curves for deep sleep strength, such data can include user data (e.g., acquired via device 12) and an analysis of a polysomnogram dataset. The user data can be used to derive the averages and standard deviations based on age/age group and other defined cohorts for deep sleep strength. The weighting of the deep sleep strength variable can be increased to more than 10%, for example, a percentage of 11% to 80% or more, as more user data is collected.

[0238] The deep sleep strength curves can be derived as described above with reference to deriving the total sleep

time cohort curves, the total deep sleep cohort curves, the sleep efficiency cohort curves, the longest deep sleep reference curves, or any combination thereof.

[0239] For example, for a 100 point scale, the average for a given deep sleep strength data set (e.g., cohort) can be assigned 85 points, one standard deviation above the average can be assigned 95 points, two standard deviations above the average can be assigned 100 points, one standard deviation below the average can be assigned 70 points and two standard deviations below the average can be assigned 35 points. The maximum point value can be 100 points and the minimum point value can be 0 points. The minimum y-intercept for the longest deep sleep can be zero, less than zero or greater than zero for a total deep sleep time of 0 minutes.

[0240] The deep sleep strength averages and corresponding standard deviations for the deep sleep strength data set—also collectively referred to as data points—can be plotted and a curve can be fitted to the plotted points as described above with reference to deriving any of the other reference curves.

[0241] For example, FIG. 25A illustrates how 5 key points can be determined for the deep sleep strength variable. Row 1 of the table lists the average deep sleep strength (e.g., acquired from one or multiple users using the device 12 or other sleep monitoring device), row 2 lists the standard deviation of the average and row 3 lists the standard deviation percentage relative to the average (e.g., $0.32/1.23 \times 100 = 26\%$). The NG column lists the statistics derived from the analyzed data. For example, row 4 of the NG column relists the calculated deep sleep strength (1.23)—also referred to as the average power spectral density (PSD)—and rows 5-8 list the standard deviations shown, with the assigned PSD scores listed in the SCORES column. The statistics in rows 4-8 are an exemplary 5 key point set. Once the 5 key points are determined (e.g., the values shown in rows 4-8), the points can be plotted. A trend line can be determined which best fits the 5 points (e.g., see FIG. 25B), where the trend line can be a polynomial or non-polynomial trend line. The five key points calculated in FIG. 25A are denoted as the five plotted points along the best fit curve in FIG. 25B. The trend line can be plotted (e.g., see FIG. 25B) and smoothed (e.g., see FIG. 25C). These generated trend line(s) can be the derived deep sleep curve(s).

[0242] For any of the sleep variables, the data can be used to derive cohort curves, non-cohort curves, or both. For example, FIGS. 24B and 25C illustrate that the deep sleep strength data can be used to generate a polynomial non-cohort deep sleep strength reference curve 49a. The curve 49a in FIG. 24 can have the illustrated equation: $y = -113.59x^2 + 376.02x - 208.39$, where $R^2 = 0.9576$. The curve 49a can alternatively be a non-polynomial curve, or both polynomial and non-polynomial curves can be fitted to the data.

[0243] In this way, deep sleep strength points can be determined, for example, by reference to the deep sleep strength reference curve(s). For example, FIG. 25D illustrates a variation of a table of exemplary PSD scores using the curve 49a of FIGS. 25B and 25C. The left column is the deep sleep strength and the right column is the PSD score associated with each of the PSD values listed in the left column. The table of FIG. 25D is also referred to as a deep sleep strength (or PSD) scoring table.

Calculating HRV Reference Curves

[0244] The recovery score can be derived from heart rate variability (HRV) data. The HRV data can include research data, user data, or both. The HRV data can be separated into cohorts, for example, based on age, gender, ethnicity, health, fitness level, or any combination thereof. Recovery score reference curves can be derived from HRV data. For example, cohort curves and/or non-cohort curves can be derived from HRV data.

[0245] The recovery score can be calculated, for example, using a two-step process: (1) determine the heart rate variability (HRV) during the last 5 minutes of light sleep, and (2) index this score on a scale (e.g., a 0-100 scale) using one or more reference curves (e.g., non-cohort or cohort). The HRV is the variation in intervals between heartbeats. It is measured by the intervals between successive R waves, where R is a point corresponding to the peak of the QRS complex of an ECG wave. The HRV can be determined by calculating the root mean square of successive differences (RMSSD), shown below (next page):

$$RMSSD = \sqrt{\frac{1}{N-1} \left(\sum_{i=1}^{N-1} ((R-R)_{i+1} - (R-R)_i)^2 \right)},$$

where N=number of RR interval terms.

[0246] The HRV is an accurate predictor of overall cardiovascular health and is a physiological measure of stress. HRV measurements are highly influenced by many factors, for example, by how calm/agitated a person is, the person's position (e.g., sitting, standing, laying down), breathing patterns, and their state of rest/activeness. Therefore, determining the HRV immediately upon falling asleep (e.g., during the first 5 minutes of the first light sleep cycle) is an accurate metric of the person's ability to adapt to stressors throughout the day. The degree of recovery during the night can be determined by comparing the starting HRV to the HRV during the last 5 minutes of light sleep prior to waking up. As another example, the degree of recovery during the night can be determined by comparing the starting HRV to the HRV during the last 10 minutes of light sleep prior to waking up. The HRV can but need not be measured during similar stages of sleep (e.g., the beginning and ending HRV can both be measured during light sleep, the starting HRV can be measured during light sleep and the ending HRV can be measured during the last stage of sleep the person is in prior to waking up, for example, deep sleep or light sleep). The person's recovery score can be determined by the ending HRV values and the absolute and relative increase in HRV during the night.

[0247] In addition to the situational influencers that can affect HRV (e.g., position, breathing patterns, state of calm/agitation), age, gender, and fitness level can impact overall HRV levels as well.

[0248] A user's HRV can be tracked over time so that trends and changes can be determined. Additionally or alternatively, the user's HRV data can be compared other people's HRV data. This can desirably allow the user to know how their key marker of systemic health and resilience, HRV, is changing over time and how it compares to others. Because there are many factors that the HRV is sensitive to such as age, health, gender, and fitness level to account for, in addition to small changes in physical and

mental health, when seeing how a person's HRV values compare to others, it can be advantageous to compare the user's HRV against people within a similar demographic, for example, using one or more cohort curves.

[0249] The ending HRV score can be translated to a 0-100 point scale to create the recovery score, for example, by referencing one or multiple HRV curves.

[0250] A method for determining HRV reference curves (e.g., cohort curves) can include using data from published research. For example, such research can include Nunan D, Sandercock G R, Brodie D A. "A quantitative systematic review of normal values for short-term heart rate variability in healthy adults." *Pacing Clin Electrophysiol.* 2010 November ;33(11):1407-17; Umetani K, Singer D H, McCraty R, Atkinson M. "Twenty-four hour time domain heart rate variability and heart rate: relations to age and gender over nine decades." *J Am Coll Cardiol.* 1998 Mar. 1; 31(3):593-601; and Elite HRV data, which are each herein incorporated by reference in their entireties for all purposes. For example, FIG. 26A illustrates that data from Table 4 of the Umetani and FIG. 26B illustrates that data from Elite HRV can be used. FIG. 26C illustrates an exemplary table showing the Umetani non-athlete data (FIG. 26A) and the Elite HRV athlete data (FIG. 26B) data by age, male athlete (M-A), female athlete (F-A), male non-athlete (M-NA) and female non-athlete (F-NA).

[0251] The average HRV for each cohort (e.g., age/age group, gender, fitness level) can be determined, along with the standard deviations of the determined averages.

[0252] For example, based on published studies of average HRV scores for men and women, athletes and non-athletes (e.g., Nunan, Umetani, Elite HRV), the HRV scores can be indexed to a 100 point scale by assigning a point value to the averages and standard deviations. The points assigned to the HRV statistics can be the same or different from the points assigned to statistics of other sleep variables (e.g., total sleep time, total deep sleep, longest deep sleep duration, strength of deep sleep). For example, for a 100 point scale, the average for a given HRV cohort (e.g., age/age group, fitness level and/or gender) can be assigned 85 points, one standard deviation above the average can be assigned 95 points, two standard deviations above the average can be assigned 100 points, one standard deviation below the average can be assigned 70 points and two standard deviations below the average can be assigned 35 points. This can be done for 4 cohorts within each age group: male athletes, female athletes, male non-athletes and female non-athletes. These four cohorts can be referred to as sub-cohorts such that age is the primary cohort and the categories male athlete, female athlete, male non-athlete and female non-athlete are sub-cohorts within each age category. The determined HRV statistics can be plotted and a curve can be fitted to the plotted points for each cohort/sub-cohort combination as described above with the reference curves for the other sleep variables. The curves can be polynomial or non-polynomial curves. For example, polynomial curves can be generated that best fit the HRV points, with caps at 0 and 100.

[0253] For example, FIGS. 27A-27D illustrate how 5 key points can be determined for four sub-cohorts (e.g., male athlete, female athlete, male non-athlete, female non-athlete) in four different age groups: 20 year old (FIG. 27A), 40 year old (FIG. 27B), 60 year old (FIG. 27C) and 80 year old (FIG. 27D). The top halves of FIGS. 27A-27D illustrate tables for the statistics (e.g., averages and standard deviations) calcu-

lated from HRV data. For example, row 1 of the tables lists the average HRV for the listed cohort (e.g., age) and sub-cohorts (e.g., male athlete, female athlete, male non-athlete, female non-athlete). Row 2 lists the standard deviation of the average and row 3 lists the standard deviation percentage relative to the average (e.g., 20 yr old male athlete: $(5/86.5) \times 100 = 6\%$). Row 4 relists the HRV average for each category and rows 5-8 list the standard deviations shown, with the assigned HRV scores listed in the SCORE column of each figure. The statistics in rows 4-8 are an exemplary 5 key point set. Once the 5 key points are determined for each category (e.g., the values shown in rows 4-8), the points can be plotted. A trend line can be determined for each cohort/sub-cohort combination which best fits each 5 point data set (e.g., see the bottom halves of FIGS. 27A-27D), where the trend line can be a polynomial or non-polynomial trend line. The five key points calculated in the top halves of FIGS. 27A-27D are denoted as the five plotted points along each of the best fit curves in the bottom halves of FIGS. 27A-27D. The trend line can be plotted and smoothed. These generated trend lines can be the HRV reference curves.

[0254] For example, the bottom half of FIG. 27A illustrates 20 year old cohort curves for male athlete $54a_{MA}$, female athlete $54a_{FA}$, male non-athlete $54a_{MNA}$ and female non-athlete $54a_{FNA}$, FIG. 27B illustrates 40 year old cohort curves for male athlete $54b_{MA}$, female athlete $54b_{FA}$, male non-athlete $54b_{MNA}$ and female non-athlete $54b_{FNA}$, FIG. 27C illustrates 60 year old cohort curves for male athlete $54c_{MA}$, female athlete $54c_{FA}$, male non-athlete $54c_{MNA}$ and female non-athlete $54c_{FNA}$, and FIG. 27D illustrates 80 year old cohort curves for male athlete $54d_{MA}$, female athlete $54d_{FA}$, male non-athlete $54d_{MNA}$ and female non-athlete $54d_{FNA}$. The illustrated cohort curves can be defined by the polynomial equations illustrated in FIGS. 27A-27D. The key points (e.g., 5 points) are denoted as the five plotted points along each of the derived cohort curves in FIGS. 27A-27D. The illustrated curves can alternatively be non-polynomial curves, or both polynomial and non-polynomial curves can be fitted to the data.

[0255] FIG. 28 illustrates curves illustrated in FIGS. 27A-27D plotted together, with the data from each age group being averaged together (e.g., the female non-athlete curve data points are an average of the 20 yr, 40 yr, 60 yr and 80 yr curves $54a_{FNA}$, $54b_{FNA}$, $54c_{FNA}$ and $54d_{FNA}$, respectively) to generate a linear male athlete curve $54e_{MA}$, a polynomial male athlete curve $54f_{MA}$, a linear female athlete curve $54e_{FA}$, a polynomial female athlete curve $54f_{FA}$, a linear male non-athlete curve $54e_{MNA}$, a polynomial male non-athlete curve $54f_{MNA}$, a linear female non-athlete curve $54e_{FNA}$ and a polynomial female non-athlete curve $54f_{FNA}$, where "linear" can indicate that a straight line is connecting adjacent data points. The polynomial equation for the male athlete curve $54f_{MA}$ can be $y=0.0229x^2-3.1812x+140.95$. The polynomial equation for the female athlete curve $54f_{FA}$ can be $y=0.0083x^2-1.5625x+96.064$. The polynomial equation for the male non-athlete curve $54f_{MNA}$ can be $y=0.0087x^2-1.3798x+76.214$. The polynomial equation for the female non-athlete curve $54f_{FNA}$ can be $y=0.0046x^2-0.8036x+57$.

[0256] In this way, recovery points can be determined, for example, by reference to the HRV reference curves.

[0257] For any of the sleep variables, the data can be used to derive cohort curves, non-cohort curves, or both. Polynomial curves, non-polynomial curves, or both can be fitted to the data.

[0258] Although described above under separate headings, the methods described in each section can be used to derive the reference curve or curves for any other sleep variable.

[0259] The points assigned to the sleep variable statistics can be the same or different from the points assigned to other sleep variable statistics. The assigned point value for each statistic can be a negative value, zero, or a positive value. For example, the assigned point value for each statistic can assigned a point value of -100 points to 100 points, including every 1 point increment within this range.

[0260] FIGS. 29A and 29B illustrate data acquired and analyzed on 5 nights: Night 1, Night 2, Night 3, Night 4 and Night 5.

[0261] FIG. 30A illustrates a variation of a graphical display **105a** having the illustrated display features for a sleep quality score of 82.

[0262] FIG. 30B illustrates a variation of a graphical display **105b** having the illustrated display features for a brain fitness score of 61.

[0263] FIG. 30C illustrates a variation of a graphical display **105c** having the illustrated display features for the sleep cycle durations illustrated in FIGS. 29A and 29B.

[0264] FIG. 30D illustrates a variation of a graphical display **105d** having the illustrated display features for sleep totals for a night for total sleep time (“Total”), total deep sleep (“Deep”), REM sleep (“REM”) and light sleep (“Light”).

[0265] FIG. 30E illustrates a variation of a graphical display **105e** having the illustrated display features for sleep efficiency.

[0266] FIG. 30F illustrates a variation of a graphical display **105f** having the illustrated display features for longest deep sleep and 5-night cumulative deficit.

[0267] A number of variations have been described. Nevertheless, it will be understood by one of ordinary skill in the art that various modifications may be made without departing from the spirit and scope of the variations. In addition, the flowcharts, logic flows, and algorithms depicted in the figures do not require the particular order shown, or sequential order, to achieve desirable results, and are exemplary only. In addition, other steps or operations may be provided, or steps or operations may be eliminated, from the described flows and algorithms, and other components and/or features may be added to, or removed from, the described and contemplated systems. Accordingly, other variations are within the scope of the following claims.

[0268] It will be understood by one of ordinary skill in the art that the various methods and processes disclosed herein may be embodied in a non-transitory readable medium, machine-readable medium, and/or a machine accessible medium comprising instructions compatible, readable, and/or executable by a processor or processing unit of a machine, device, or computing device. The structures and modules in the figures may be shown as distinct and communicating with only a few specific structures and not others. The structures may be merged with each other, may perform overlapping functions, and may communicate with other structures not shown to be connected in the figures. Accord-

ingly, the specification and/or drawings may be regarded in an illustrative rather than a restrictive sense.

[0269] The specific embodiments described herein are offered by way of example only. Moreover, such devices and methods may be applied to other sites within the body. Modification of the above-described assemblies and methods for carrying out the invention, combinations between different variations as practicable, and variations of aspects of the invention that are obvious to those of skill in the art are intended to be within the scope of the claims.

[0270] The claims are not limited to the exemplary variations shown in the figures, but instead may claim any feature disclosed or contemplated in the disclosure as a whole. Any elements described herein as singular can be pluralized (i.e., anything described as “one” can be more than one). Any species element of a genus element can have the characteristics or elements of any other species element of that genus. Some elements may be absent from individual figures for reasons of illustrative clarity. The above-described configurations, elements or complete assemblies and methods and their elements for carrying out the disclosure, and variations of aspects of the disclosure can be combined and modified with each other in any combination. All devices, apparatuses, systems, methods, and algorithms described herein can be used for medical (e.g., diagnostic, therapeutic or rehabilitative) or non-medical purposes.

[0271] All references including patent applications and publications cited herein are incorporated herein by reference in their entirety and for all purposes to the same extent as if each individual publication or patent or patent application was specifically and individually indicated to be incorporated by reference in its entirety for all purposes. Many modifications and variations of this invention can be made without departing from its spirit and scope, as will be apparent to those skilled in the art.

[0272] All publications mentioned herein are incorporated herein by reference to disclose and describe the methods and/or materials in connection with which the publications are cited. The publications discussed herein are provided solely for their disclosure prior to the filing date of the present application. Nothing herein is to be construed as an admission that the present invention is not entitled to antedate such publication by virtue of prior invention. Further, the dates of publication provided may be different from the actual publication dates which may need to be independently confirmed.

[0273] If there is any ambiguity above, every possible interpretation of that ambiguity is hereby disclosed for all purposes, thereby removing such ambiguity from the application.

We claim:

1. A sleep monitoring system, comprising:
 - one or more electroencephalography (EEG) electrodes configured to measure a user’s brain activity during sleep; and
 - a processor configured to quantify the quality of the user’s slow-wave sleep by determining one or more sleep performance scores associated with the measured brain activity.
2. The system of claim 1, wherein the one or more sleep performance scores comprises at least one of a sleep quality score and a brain fitness score.
3. The system of claim 2, wherein the system is configured to analyze the brain activity measured by the one or

more EEG electrodes to determine a user's total sleep time, total deep sleep, and sleep efficiency, and wherein the sleep quality score is function of total sleep time, total deep sleep, and sleep efficiency.

4. The system of claim 3, wherein the sleep quality score is based at least partly on the user's fitness level, health habits, and/or genetic characteristics.

5. The system of claim 4, wherein the genetic characteristics comprise at least one of age and gender.

6. The system of claim 3, wherein the system is configured to analyze the brain activity measured by the one or more EEG electrodes to determine a user's total deep sleep, longest deep sleep, and deep sleep strength, and wherein the brain fitness score is function of total sleep time, total deep sleep, and sleep efficiency.

7. The system of claim 6, wherein the brain fitness score is based at least partly on the user's fitness level, health habits, and/or genetic characteristics.

8. The system of claim 7, wherein the genetic characteristics comprise at least one of age and gender.

9. The system of claim 1, wherein the processor is further configured to calculate a recovery score that is a function of the user's heart rate variability during sleep.

10. The system of claim 1, wherein the processor is further configured to determine a value of one or more sleep parameters based at least partly on the measured brain activity, wherein the processor is further configured to compare the determined sleep parameter values to one or more threshold criteria, and wherein the processor is further configured to provide one or more sleep-related observations and/or recommendations upon determining that one or more of the determined sleep parameter values fall below one or more of the threshold criteria.

11. The system of claim 1, wherein the system is configured to provide at least one of audio stimulation, visual stimulation, and cranial electrical stimulation.

12. A method of quantifying the quality of a user's sleep, the method comprising:

measuring, via one or more electroencephalography (EEG) biosensors, a user's brain activity during sleep; and

quantifying, via a computer system, a quality of the user's slow-wave sleep by determining one or more sleep performance scores associated with the measured brain activity.

13. The method of claim 12, wherein the one or more sleep performance scores comprises at least one of a sleep quality score and a brain fitness score.

14. The method of claim 13, further comprising analyzing, via the computer system, the brain activity measured by the one or more EEG biosensors to determine a user's total sleep time, total deep sleep, and sleep efficiency, wherein the sleep quality score is function of total sleep time, total deep sleep, and sleep efficiency.

15. The method of claim 14, wherein the sleep quality score is based at least partly on the user's fitness level, health habits, and/or genetic characteristics.

16. The system of claim 15, wherein the genetic characteristics comprise at least one of age and gender.

17. The method of claim 12, further comprising analyzing, via the computer system, the brain activity measured by the one or more EEG biosensors to determine a user's total deep sleep, longest deep sleep, and deep sleep strength,

wherein the brain fitness score is function of total sleep time, total deep sleep, and sleep efficiency.

18. The method of claim 17, wherein the brain fitness score is based at least partly on the user's fitness level, health habits, and/or genetic characteristics.

19. The method of claim 12, further comprising calculating a recovery score that is a function of the user's heart rate variability during sleep.

20. The method of claim 12, further comprising:

determining, via the computer system, a value of one or more sleep parameters based at least partly on the measured brain activity;

comparing, via the computer system, the determined sleep parameter values to one or more threshold criteria; and providing, via the computer system, one or more sleep-related observations and/or recommendations upon determining that one or more of the determined sleep parameter values fall below one or more of the threshold criteria.

21. The method of claim 12, wherein the system is configured to provide at least one of audio stimulation, visual stimulation, and cranial electrical stimulation.

22. A method of quantifying the quality of a user's sleep, the method comprising:

measuring, via one or more electroencephalography (EEG) sensors, a user's brain activity during sleep;

determining, via a computer system, one or more parameters associated with the measured brain activity;

calculating, via the computer system, one or more sleep performance scores associated with one or more of the determined parameters, wherein at least one sleep performance score is an objective measure of sleep quality.

23. The method of claim 22, wherein the objective measure of sleep quality is associated with slow wave sleep.

24. A method of quantifying a sleep quality score of a subject, comprising:

measuring one or more parameters relating to a brain activity of the subject;

determining a total sleep time based upon a function of a total amount of sleep measured from the subject;

determining a deep sleep parameter based upon a function of a total amount of deep sleep time measured from the subject;

determining a sleep efficiency parameter based upon a function of sleep efficiency measured from the subject; and

calculating the sleep quality score based upon a weighting of the total sleep time, deep sleep parameter, and sleep efficiency parameter.

25. The method of claim 24, wherein calculating the sleep quality score comprises adding the total sleep time, deep sleep parameter, and sleep efficiency parameter.

26. The method of claim 25, wherein calculating further comprises weighting the total sleep time by 50%, deep sleep parameter by 40%, and sleep efficiency parameter by 10%.

27. The method of claim 24, further comprising providing an audio stimulation during a selected portion of a sleep cycle of the subject depending upon a value of the sleep quality score.

28. The method of claim 24, further comprising providing one or more recommendations to the subject for increasing the sleep quality score.

29. A method of quantifying a brain fitness score of a subject, comprising:

measuring one or more parameters relating to a brain activity of the subject;
determining a total deep sleep time based upon a function of a total amount of deep sleep measured from the subject;
determining a longest deep sleep parameter based upon a function of a total amount of longest deep sleep time measured from the subject;
determining a deep sleep strength parameter based upon a function of deep sleep strength measured from the subject; and
calculating the brain fitness score based upon a weighting of the total deep sleep time, longest deep sleep parameter, and deep sleep strength parameter.

30. The method of claim **29**, wherein calculating the brain fitness score comprises adding the total deep sleep time, longest deep sleep parameter, and deep sleep strength parameter.

31. The method of claim **30**, wherein calculating further comprises weighting the total deep sleep time by 80%, longest deep sleep parameter by 10%, and deep sleep strength parameter by 10%.

32. The method of claim **29**, further comprising providing an audio stimulation during a selected portion of a sleep cycle of the subject depending upon a value of the sleep quality score.

33. The method of claim **29**, further comprising providing one or more recommendations to the subject for increasing the sleep quality score.

* * * * *

专利名称(译)	睡眠性能系统和使用方法		
公开(公告)号	US20190099582A1	公开(公告)日	2019-04-04
申请号	US16/151715	申请日	2018-10-04
[标]发明人	CROW KAREN		
发明人	CROW, KAREN SANDERS, MATT		
IPC分类号	A61M21/02 A61B5/00 A61B5/0482		
CPC分类号	A61M21/02 A61B5/4815 A61B5/4812 A61B5/7278 A61B5/0482 A61B5/02405 A61M2021/0027 A61M2021/0044 A61M2021/0072 A61M2230/10		
优先权	62/568249 2017-10-04 US 62/661932 2018-04-24 US		
外部链接	Espacenet USPTO		

摘要(译)

公开了睡眠性能系统及其使用方法。睡眠表现系统可以通过向受试者提出一个或多个推荐来提高睡眠质量得分，从而改善睡眠质量。睡眠性能系统可以具有一个或多个脑电图（EEG）电极，其被配置为在睡眠期间测量受试者的大脑活动。睡眠性能系统可以具有处理器，该处理器被配置为通过确定与测量的大脑活动相关联的一个或多个睡眠性能得分来量化受试者的慢波睡眠的质量。睡眠表现系统可以基于各种阈值分数来推荐和/或激活睡眠改善程序。

