



US 20180338725A1

(19) **United States**(12) **Patent Application Publication****Shan et al.**(10) **Pub. No.: US 2018/0338725 A1**(43) **Pub. Date: Nov. 29, 2018**(54) **INTELLIGENT ELECTRIC BED SYSTEM***A61G 7/015* (2006.01)*A61B 5/0205* (2006.01)(71) Applicant: **Keeson Technology Corporation Limited**, Jiaxing (CN)(52) **U.S. Cl.**CPC *A61B 5/6892* (2013.01); *A47C 31/008* (2013.01); *A47C 20/041* (2013.01); *A61G 7/018* (2013.01); *A61B 5/024* (2013.01); *A61B 5/0022* (2013.01); *A61B 5/0205* (2013.01); *A61G 2203/42* (2013.01); *A61G 7/015* (2013.01)(72) Inventors: **Huafeng Shan**, Jiaxing (CN); **Hui Cao**, Jiaxing (CN); **Qun Yu**, Jiaxing (CN)(21) Appl. No.: **16/053,082**(22) Filed: **Aug. 2, 2018****Related U.S. Application Data**


(63) Continuation of application No. PCT/CN2017/072418, filed on Jan. 24, 2017.

(30) **Foreign Application Priority Data**

Feb. 2, 2016 (CN) 201610071895.7

Publication Classification(51) **Int. Cl.***A61B 5/00* (2006.01)*A47C 31/00* (2006.01)*A47C 20/04* (2006.01)*A61G 7/018* (2006.01)(57) **ABSTRACT**

An intelligent electric bed includes an electric bed, a terminal device, and a server. The electric bed includes: a monitoring module (1) for monitoring physical conditions of a user, and sending monitoring data to a wireless communication module (3); and a main control module (2) receiving a control signal from the wireless communication module (3) and adjusting a state of the electric bed based on the control signal. The wireless communication module (3) may transmit the received monitoring data to the server, receive the control signal from the server, and send the control signal to the main control module (2). The server may generate the control signal based on a setting signal sent by a terminal device and the monitoring data. The terminal device is adapted to adjust the state of the electric bed via the server and send the setting signal to the server.






Figure 1




Figure 2

INTELLIGENT ELECTRIC BED SYSTEM

CROSS-REFERENCE OF RELATED APPLICATIONS

[0001] The present application is a Continuation Application of PCT patent application no. PCT/CN2017/072418 filed on Jan. 24, 2017, which claims the priority of Chinese patent application no. 201610071895.7 filed on Feb. 2, 2016. All the above are hereby incorporated by reference.

FIELD OF TECHNOLOGY

[0002] The present application relates to an intelligent electric bed system.

BACKGROUND TECHNOLOGY

[0003] An electric bed includes a plurality of bed planks hinged to each other, a drive motor configured to drive the plurality of bed planks to raise or rotate, and a linkage mechanism.

[0004] An existing electric bed uses a terminal device to adjust posture of the electric bed. For this, an additional terminal device mating therewith is required for each electric bed. In mass production, remote controllers may cause additional production cost. At the same time, it is possible that a remote controller mating with the electric bed is lost and/or damaged. If such a situation occurs, a user will be temporarily unable to adjust the electric bed, thereby causing a lot of inconvenience.

[0005] In addition, the existing terminal device can only send a preset execution command to the electric bed according to the remote control of the user, but cannot make changes for different usages; the terminal device having this single function cannot meet the requirements of users. For example, when sleeping condition of a user changes, the electric bed cannot intervene the user's sleep in time, and thus fails to effectively improve the sleeping condition of the user.

SUMMARY

[0006] It is to be noted that the purpose of the present application is to overcome one or more of the disadvantages that have been found in the prior art.

[0007] For this purpose, an electric bed system controlled by an intelligent device is proposed according to the present application, which is realized by the following technical solutions:

[0008] An electric bed, adapted to monitor physical conditions of a user in real time and adjust a state of the electric bed based on monitoring data, includes:

[0009] a monitoring module, configured to monitor the physical conditions of the user, and send the monitoring data to a wireless communication module; and

[0010] a main control module, configured to receive a control signal from the wireless communication module, and adjust the state of the electric bed based on the control signal;

[0011] wherein the wireless communication module transmits the received monitoring data to a server, receives the control signal from the server, and sends the control signal to the main control module; and the server generates the control signal based on a setting signal sent by a terminal device and the monitoring data.

[0012] Further, the main control module sends information data including the state of the electric bed to the wireless communication module, and the wireless communication module sends the information data to the server.

[0013] Further, a connection mean of the wireless communication module includes at least one selected from the group consisting of Wi-Fi, Bluetooth, infrared, and ZigBee.

[0014] Further, the monitoring data includes at least one selected from the group consisting of a heart rate, a respiratory rate, an intensity of snore, an intensity of respiration, and numbers of turning and tossing in bed.

[0015] Further, the state of the electric bed includes at least one selected from the group consisting of an inclination angle of each bed plank, a state of a drive motor, and a state of an indicator light.

[0016] Further, the bed plank includes at least one selected from the group consisting of a head bed plank, a leg bed plank, a haunch bed plank, and a waist bed plank.

[0017] Further, the server is a cloud server.

[0018] A terminal device, adapted to adjust a state of an electric bed via a server, wherein the terminal device sends a setting signal to the server; the server generates, based on the setting signal, a control signal for adjusting the state of the electric bed, and further sends the control signal to the electric bed.

[0019] Further, the terminal device receives from the server and displays monitoring data indicating physical conditions of a user of the electric bed.

[0020] Further, the terminal device receives from the server and displays information data including the state of the electric bed.

[0021] Further, the terminal device communicates with the server by means of at least one connection mean selected from the group consisting of Wi-Fi, 2G, 3G, and 4G.

[0022] Further, the monitoring data includes at least one selected from the group consisting of a heart rate, a respiratory rate, an intensity of snore, an intensity of respiration, and numbers of turning and tossing in bed.

[0023] Further, the state of the electric bed includes at least one selected from the group consisting of an inclination angle of each bed plank, a state of a drive motor, and a state of an indicator light.

[0024] By performing related setting with respect to the electric bed on the terminal device provided in the present application, the user may conveniently control the electric bed. Meanwhile, the user may get to know the current state of the electric bed intuitively and in real time since the terminal displays the information data of the state of the electric bed, such that the user may make more proper adjustment.

[0025] An intelligent electric bed system includes an electric bed, a terminal device, and a server.

[0026] In the intelligent electric bed system provided in the present application, various conditions for changing the state of the electric bed may be preset in the server using the terminal device.

[0027] The electric bed may keep connected to the server in real time, and may send monitoring data in respect of physical conditions of a user to the server. When the monitoring data matches the conditions for changing the state of the electric bed, the server may send a control signal to the electric bed to change the state of the electric bed. By

using the electric bed system, changes can be made in time for usages of different users, thereby improving sleeping condition of the users.

BRIEF DESCRIPTION OF THE DRAWINGS

[0028] It should be understood that in the present application, all features, modifications, and/or specific embodiments may be combined in various combinations, except in the cases of obvious contradictions and incompatibilities.

[0029] By reading the following non-limiting illustrative embodiments, and in conjunction with the drawings, other features and advantages of the present application will become apparent. In the figures:

[0030] FIG. 1 is a schematic structural view showing an intelligent electric bed system according to the present application; and

[0031] FIG. 2 is a flow chart showing the control of an intelligent electric bed system according to the present application.

DETAILED DESCRIPTION

[0032] The present application will be described in detail below with reference to the embodiments and the accompanying drawings.

[0033] With reference to FIG. 1, an intelligent electric bed system according to an embodiment of the present application is shown.

[0034] An electric bed may include a plurality of bed planks hinged to each other, a linkage mechanism connected to the plurality of bed planks, and a drive motor for driving the linkage mechanism. The electric bed may further include a monitoring module 1, a main control module 2, and a wireless communication module 3.

[0035] The monitoring module 1 may be configured to monitor physical conditions of a user, and may include a body temperature monitoring module, a heart rate monitoring module, a respiratory rate detector, a decibel meter, and the like. The monitoring module 1 may at least acquire monitoring data of physical conditions of a user. The monitoring data may include a heart rate, a respiratory rate, an intensity of snore, an intensity of respiration, numbers of turning and tossing in bed, and the like of the user. The monitoring module 1 may be adapted to send the monitoring data to the wireless communication module 3. The wireless communication module 3 may send the received monitoring data to a server. The server may store the monitoring data. Optionally, the server may send the monitoring data to a terminal device, such that the terminal device may display the monitoring data indicating the physical conditions of the user of the electric bed.

[0036] The monitoring module 1 may be mounted on an upper part of a bed body of the electric bed that is close to a heart of the user so that accurate data may be acquired.

[0037] The monitoring module 1 can monitor the heart rate, the respiratory rate, the intensity of snore, the intensity of respiration, and numbers of turning and tossing in bed of the user.

[0038] The heart rate, the respiratory rate, and the intensity of respiration may be used to determine a basic physical condition of the user.

[0039] The numbers of turning and tossing in bed may be used to determine a basic sleeping condition of the user.

[0040] By monitoring the intensity of snore, it is possible to intervene sleeping of the user in real time so that symptoms of snoring may be effectively relieved.

[0041] To avoid electromagnetic interference to the monitoring module 1 generated by wires, in one embodiment, the monitoring module 1 may communicate with the wireless communication module 3 by means of RF (Radio Frequency) wireless communication.

[0042] The main control module 2 may be electrically connected to the monitoring module 1, the wireless communication module 3, and the drive motor. A control host may be adapted to receive and analyze a control signal received by the wireless communication module 3, and control the drive motor or other devices in the electric bed according to the control signal in order to adjust a state of the electric bed. The state of the electric bed may include an inclination angle of each bed plank, a state of the drive motor, a state of an indicator light, and the like. Wherein, the bed plank may include at least one selected from the group consisting of a head bed plank, a leg bed plank, a haunch bed plank, and a waist bed plank.

[0043] In one embodiment, the main control module 2 may adjust control (including a rotation speed and number of revolutions of a spindle of the drive motor, and the like) of the drive motor, based on the control signal from the wireless communication module 3.

[0044] The main control module 2 may make various adjustments to the state of the electric bed in real time based on the control signal so to improve the sleeping condition of the user effectively. For example, when the monitoring module 1 detects that the user is snoring, the main control module 2 may raise the waist bed plank of the electric bed to a certain angle according to a preset setting. In this way, it is possible to avoid worsening the block of an airway due to relaxation of a tongue, a soft palate and a uvula, and effectively relieve the symptoms of snoring of the user. Therefore, the sleeping condition of the user may be effectively improved.

[0045] In one embodiment, the main control module 2 may further send information data including the state of the electric bed to the wireless communication module 3.

[0046] The wireless communication module 3 may be a Wi-Fi module, and, depending on cases, may also be a Bluetooth module, an infrared module, a ZigBee module, and the like, in order to wirelessly connect with the server. The wireless communication module 3 may be adapted to send the received monitoring data to the server, receive the control signal sent by the server and forward the control signal to the main control module 2, such that the control host may determine the operation to be performed.

[0047] In one embodiment, the wireless communication module 3 may receive the information data sent by the main control module 2, and further forward the information data to the server. The state of the electric bed may include an inclination angle of each bed plank, the state of the motor, the state of an indicator light, and the like.

[0048] The server may respectively and wirelessly connected to the wireless communication module 3 of the electric bed and the terminal device by means of at least one connection mean selected from the group consisting of Wi-Fi, Bluetooth, infrared, and ZigBee. The server may generate the control signal based on a setting signal sent by the terminal device and the monitoring data.

[0049] More specifically, a processing program related to the state of the electric bed may be installed in the server. On one hand, the server may receive the monitoring data of the electric bed; on the other hand, the server may receive the setting signal sent by the terminal device. The processing program may determine whether to send the control signal to the wireless communication module 3 of the electric bed, based on the monitoring data and the setting signal. For example, a threshold range of the heart rate in the terminal device may be preset from approximately 60 times/min to approximately 140 times/min, and terminal device may send the related setting signal to the server. When the monitoring data received by the server are beyond the range, the server may send the control signal to the wireless communication module 3 to adjust the state of the electric bed, for example, by raising the head bed plank or turning on a bed lamp. On the contrary, if the monitoring data falls within the threshold range, the server will not send any control signal. For another example, a floor lamp may be preset through the terminal device to be automatically turned on when the user is out of bed after 22:00, and the terminal device may send the related setting signal to the server. When receiving the user's off-bed data, the server may send the control signal to the wireless communication module 3 to turn on the floor lamp.

[0050] Optionally, the server may further store all feature parameters (such as the heart rate, the respiratory rate, the intensity of snore, the intensity of respiration, numbers of turning and tossing in bed) of the user, in order to analyze the sleeping condition of the user, thereby making a more accurate plan to improve the sleeping quality of the user.

[0051] Optionally, the server may receive the monitoring data indicating the physical conditions of the user of the electric bed from the wireless communication module 3, and further forward the monitoring data to the terminal device.

[0052] Optionally, the server may receive the information data including the state of the electric bed from the wireless communication module 3, and further forward the information data to the terminal device.

[0053] Optionally, the server may be a cloud (computing) server.

[0054] The terminal device may include a mobile phone, a tablet computer, a notebook computer, and the like. The terminal device may be installed with an application (App) and/or software configured to control the electric bed. Using the installed application (App) and/or software, the terminal device may control a wireless module inside the terminal device to transmit the setting signal to the server. Optionally, the terminal device may communicate with the server by means of at least one connection mean selected from the group consisting of Wi-Fi, 2G, 3G, and 4G.

[0055] This type of application (App) and/or software may include a human-computer interaction interface including an option setting interface for user's selection. The user may customize various setting information of the electric bed via the interface, and further send the setting signal to the server. The setting signal may include thresholds of various monitoring data: the heart rate, the respiratory rate, the intensity of snore, the intensity of respiration, and numbers of turning and tossing in bed of the user. The user may select the information to be set by clicking, double clicking, sliding, touching, and inputting values.

[0056] Optionally, the interaction interface may include a display interface that provides the user information data

including the state of the electric bed. The state of the electric bed may include at least one selected from the group consisting of the inclination angle of each bed plank, the state of the motor, and the state of an indicator light.

[0057] Optionally, the interaction interface may include a display interface that provides the user the monitoring data indicating the physical conditions of the user. The monitoring data may include at least one selected from the group consisting of the heart rate, the respiratory rate, the intensity of snore, the intensity of respiration, and numbers of turning and tossing in bed.

[0058] The terminal device may receive the above information data and the monitoring data from the server.

[0059] As shown in FIG. 2, a flow chart showing the control of an intelligent electric bed system is shown.

[0060] On one hand, the monitoring module 1 of the electric bed may monitor various physical conditions of the user on the bed, and send the monitoring data indicating the physical conditions of the user to the wireless communication module 3 of the electric bed. The wireless communication module 3 may send the monitoring data to the server.

[0061] On the other hand, the terminal device may transmit the setting signal to the server. The setting signal may include the thresholds of various monitoring data.

[0062] The server may determine, via the processing program, whether to generate the control signal based on the monitoring data and the setting signal, and send the control signal to the wireless communication module 3. More specifically, when the monitoring data are beyond the set thresholds, the control signal will be sent; otherwise, no control signal will be sent. After that, the wireless communication module 3 may send the control signal to the main control module 2 so to adjust the state of the electric bed.

[0063] Optionally, the server may send the monitoring data to the terminal device, such that the terminal device may display the monitoring data.

[0064] Optionally, the main control module 2 may send the information data including the state of the electric bed to the wireless communication module 3, and the wireless communication module 3 may further send the information data to the server. The server may send the information data to the terminal device, such that the terminal device may display the information data.

[0065] The above embodiments are merely examples and do not limit the scope of the present application. Based on this, those skilled in the art can envision other embodiments that can achieve the same function within the scope of the claims of the present application.

[0066] Various embodiments and various modifications and improvements will be apparent to those skilled in the art. In particular, it should be understood that the above-described features, modifications, and/or embodiments of the present application may be combined with each other, except in the case of obvious contradictions or incompatibilities. All of these embodiments, as well as variations and modifications, are within the scope of the present application.

What is claimed is:

1. An electric bed, adapted to monitor physical conditions of a user in real time and adjust a state of the electric bed based on monitoring data, the electric bed comprising:

a monitoring module, configured to monitor the physical conditions of the user, and send the monitoring data to a wireless communication module; and

a main control module, configured to receive a control signal from the wireless communication module, and adjust the state of the electric bed based on the control signal;

wherein the wireless communication module transmits the received monitoring data to a server, receives the control signal from the server, and sends the control signal to the main control module; and the server generates the control signal based on a setting signal sent by a terminal device and the monitoring data.

2. The electric bed of claim 1, wherein the main control module sends information data comprising the state of the electric bed to the wireless communication module, and the wireless communication module sends the information data to the server.

3. The electric bed of claim 1, wherein a connection mean of the wireless communication module comprises at least one selected from the group consisting of Wi-Fi, Bluetooth, infrared, and ZigBee.

4. The electric bed of claim 1, wherein the monitoring data comprises at least one selected from the group consisting of a heart rate, a respiratory rate, an intensity of snore, an intensity of respiration, and numbers of turning and tossing in bed.

5. The electric bed of claim 1, wherein the state of the electric bed comprises at least one selected from the group consisting of an inclination angle of each bed plank, a state of a drive motor, and a state of an indicator light.

6. The electric bed of claim 5, wherein the bed plank comprises at least one selected from the group consisting of a head bed plank, a leg bed plank, a haunch bed plank, and a waist bed plank.

7. The electric bed of claim 1, wherein the server is a cloud server.

8. A terminal device, adapted to adjust a state of an electric bed via a server, wherein the terminal device sends a setting signal to the server; the server generates, based on the setting signal, a control signal for adjusting the state of the electric bed, and further sends the control signal to the electric bed.

9. The terminal device of claim 8, wherein the terminal device receives from the server and displays monitoring data indicating physical conditions of a user of the electric bed.

10. The terminal device of claim 8, wherein the terminal device receives from the server and displays information data comprising the state of the electric bed.

11. The terminal device of claim 8, wherein the terminal device communicates with the server by means of at least one connection mean selected from the group consisting of Wi-Fi, 2G, 3G, and 4G.

12. The terminal device of claim 9, wherein the monitoring data comprises at least one selected from the group consisting of a heart rate, a respiratory rate, an intensity of snore, an intensity of respiration, and numbers of turning and tossing in bed.

13. The terminal device of claim 10, wherein the state of the electric bed comprises at least one selected from the group consisting of an inclination angle of each bed plank, a state of a drive motor, and a state of an indicator light.

14. An intelligent electric bed system, comprising the electric bed of claim 1, a terminal device, and a server; wherein the terminal device sends a setting signal to the server; the server generates, based on the setting signal, a control signal for adjusting a state of the electric bed, and further sends the control signal to the electric bed.

* * * * *

专利名称(译)	智能电动床系统		
公开(公告)号	US20180338725A1	公开(公告)日	2018-11-29
申请号	US16/053082	申请日	2017-01-24
[标]申请(专利权)人(译)	麒盛科技股份有限公司		
[标]发明人	SHAN HUAFENG CAO HUI YU QUN		
发明人	SHAN, HUAFENG CAO, HUI YU, QUN		
IPC分类号	A61B5/00 A47C31/00 A47C20/04 A61G7/018 A61G7/015 A61B5/0205		
CPC分类号	A61B5/6892 A47C31/008 A47C20/041 A61G7/018 A61G7/015 A61B5/0022 A61B5/0205 A61G2203/42 A61B5/024 A61B5/0816 A61B5/11 A61B5/4818 A61G2203/20 A47C20/08 G05B19/4185 G08C17/02 A47C21/003 A61B5/00 A61G7/05 A47C31/123 A61B5/08 G06Q50/10 A47C17/04		
优先权	201610071895.7 2016-02-02 CN		
外部链接	Espacenet USPTO		

摘要(译)

智能电动床包括电动床，终端设备和服务器。电动床包括：监控模块（1），用于监控用户的物理状况，并将监控数据发送到无线通信模块（3）；主控制模块（2）接收来自无线通信模块的控制信号（3），并根据控制信号调整电动床的状态。无线通信模块（3）可以将接收的监控数据发送到服务器，从服务器接收控制信号，并将控制信号发送到主控制模块（2）。服务器可以基于终端设备发送的设置信号和监控数据生成控制信号。终端设备适于通过服务器调整电动床的状态，并将设置信号发送给服务器。

