

US009186061B2

(12) **United States Patent**
Bardy

(10) **Patent No.:** **US 9,186,061 B2**
(45) **Date of Patent:** ***Nov. 17, 2015**

(54) **SYSTEM AND METHOD FOR EVALUATING A PATIENT STATUS FOR USE IN HEART FAILURE ASSESSMENT**

(71) Applicant: **Cardiac Pacemakers, Inc.**, St. Paul, MN (US)

(72) Inventor: **Gust Bardy**, Carnation, WA (US)

(73) Assignee: **Cardiac Pacemakers, Inc.**, St. Paul, MN (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **14/053,375**

(22) Filed: **Oct. 14, 2013**

(65) **Prior Publication Data**

US 2014/0039327 A1 Feb. 6, 2014

Related U.S. Application Data

(60) Continuation of application No. 11/894,312, filed on Aug. 20, 2007, now Pat. No. 8,556,810, which is a

(Continued)

(51) **Int. Cl.**

A61B 5/00 (2006.01)

A61B 5/0205 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **A61B 5/0031** (2013.01); **A61B 5/0205** (2013.01); **G06F 19/322** (2013.01); **G06F 19/3418** (2013.01); **G06Q 50/24** (2013.01); **G06F 19/3406** (2013.01); **Y10S 128/92** (2013.01)

(58) **Field of Classification Search**

CPC .. A61B 5/0031; A61B 5/0205; G06F 19/322; Y10S 128/926; Y10S 128/92
USPC 600/300-301, 509, 312; 128/920, 923, 128/312

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,837,339 A 9/1974 Aisenberg et al.
4,142,533 A 3/1979 Brownlee et al.

(Continued)

FOREIGN PATENT DOCUMENTS

EP 0342859 11/1989
EP 0513457 11/1992

(Continued)

OTHER PUBLICATIONS

Schreier, et al., "A Non-Invasive Rejection Monitoring System Based on Remote Analysis of Intramyocardial Electrograms from Heart Transplants", IEEE, pp. 35-36 1997.

(Continued)


Primary Examiner — Mark W Bockelman

(74) *Attorney, Agent, or Firm* — Pauly, DeVries Smith & Deffner LLC

(57) **ABSTRACT**

A system and method for evaluating a patient status from sampled physiometry for use in heart failure assessment is presented. Physiological measures are stored, including at least one of direct measures regularly recorded on a substantially continuous basis by an implantable medical device for a patient and measures derived from the direct measures. At least one of those of the physiological measures, which each relate to a same type of physiometry, and those of the physiological measures, which each relate to a different type of physiometry are sampled. A status for the patient is determined through analysis of the sampled physiological measures assembled from a plurality of recordation points. The sampled physiological measures are evaluated. Trends that are indicated by the patient status, which might affect cardiac performance of the patient, are identified. Each trend is compared to worsening heart failure indications to generate a notification of parameter violations.

18 Claims, 12 Drawing Sheets



Related U.S. Application Data

continuation of application No. 11/540,251, filed on Sep. 29, 2006, now Pat. No. 8,277,378, which is a division of application No. 09/948,307, filed on Sep. 6, 2001, now Pat. No. 7,144,369, which is a continuation of application No. 09/324,894, filed on Jun. 3, 1999, now Pat. No. 6,312,378.

(51) Int. Cl.

G06F 19/00 (2011.01)
G06Q 50/24 (2012.01)

(56)**References Cited**

U.S. PATENT DOCUMENTS

4,197,856 A	4/1980	Northrop	5,772,585 A	6/1998	Lavin
4,531,527 A	7/1985	Reinhold, Jr. et al.	5,772,586 A	6/1998	Heinonen et al.
4,686,999 A	8/1987	Snyder et al.	5,772,599 A	6/1998	Nevo et al.
4,803,625 A	2/1989	Fu et al.	5,772,604 A	6/1998	Langberg et al.
4,809,697 A	3/1989	Casey, III et al.	5,778,882 A	7/1998	Raymond et al.
4,830,018 A	5/1989	Treatch	5,785,650 A	7/1998	Akasaka et al.
4,852,570 A	8/1989	Levine	5,785,660 A	7/1998	Van Lake et al.
4,899,758 A	2/1990	Finkelstein et al.	5,788,640 A	8/1998	Peters
4,958,645 A	9/1990	Cadell et al.	5,788,643 A	8/1998	Feldman
4,974,607 A	12/1990	Miwa	5,792,062 A	8/1998	Poon et al.
4,987,897 A	1/1991	Funke	5,819,251 A	10/1998	Kremer et al.
5,040,536 A	8/1991	Riff	5,855,593 A	1/1999	Olson et al.
5,113,859 A	5/1992	Funke	5,860,918 A	1/1999	Schradi et al.
5,113,869 A	5/1992	Nappholz et al.	5,876,353 A	3/1999	Riff
5,133,346 A	7/1992	Kulkarni	5,879,375 A	3/1999	Larson, Jr. et al.
5,199,428 A	4/1993	Obel et al.	5,891,178 A	4/1999	Mann et al.
5,301,105 A	4/1994	Cummings, Jr.	5,897,493 A	4/1999	Brown
5,307,263 A	4/1994	Brown	5,911,132 A	6/1999	Sloane
5,309,919 A	5/1994	Snell et al.	5,931,857 A	8/1999	Prieve et al.
5,313,593 A	5/1994	Barakat et al.	5,954,640 A	9/1999	Szabo
5,331,549 A	7/1994	Crawford, Jr.	5,957,861 A	9/1999	Combs et al.
5,336,245 A	8/1994	Adams et al.	5,974,124 A	10/1999	Schlueter, Jr. et al.
5,355,889 A	10/1994	Nevo et al.	5,987,352 A	11/1999	Klein et al.
5,357,427 A	10/1994	Langen et al.	5,993,386 A	11/1999	Ericsson
5,390,238 A	2/1995	Kirk et al.	6,004,276 A	12/1999	Wright et al.
5,416,695 A	5/1995	Stutman et al.	6,014,581 A	1/2000	Wayne et al.
5,421,343 A	6/1995	Feng	6,024,699 A	2/2000	Surwit et al.
5,437,278 A	8/1995	Wilk	6,038,469 A	3/2000	Karlsson et al.
5,438,983 A	8/1995	Falcone	6,047,203 A	4/2000	Sackner et al.
5,464,012 A	11/1995	Falcone	6,050,940 A	4/2000	Braun et al.
5,484,012 A	1/1996	Hiratsuka	6,058,326 A	5/2000	Hess et al.
5,544,661 A	8/1996	Davis et al.	6,063,028 A	5/2000	Luciano
5,553,609 A	9/1996	Chen et al.	6,067,466 A	5/2000	Selker et al.
5,557,514 A	9/1996	Seare et al.	6,073,046 A	6/2000	Patel et al.
5,576,952 A	11/1996	Stutman et al.	6,080,106 A	6/2000	Lloyd et al.
5,584,868 A	12/1996	Salo et al.	6,083,248 A	7/2000	Thompson
5,591,215 A	1/1997	Greenhut et al.	6,093,146 A	7/2000	Filangeri
5,603,331 A	2/1997	Heemels et al.	6,095,985 A	8/2000	Raymond et al.
5,660,183 A	8/1997	Chiang et al.	6,102,856 A	8/2000	Groff et al.
5,673,691 A	10/1997	Abrams et al.	6,122,351 A	9/2000	Schlueter, Jr. et al.
5,687,734 A	11/1997	Dempsey et al.	6,129,675 A	10/2000	Jay
5,697,959 A	12/1997	Poore	6,135,951 A	10/2000	Richardson et al.
5,704,345 A	1/1998	Berthon-Jones et al.	6,139,494 A	10/2000	Cairnes
5,704,364 A	1/1998	Saltzstein et al.	6,152,882 A	11/2000	Prutchi
5,704,365 A	1/1998	Albrecht et al.	6,155,267 A	12/2000	Nelson
5,704,366 A	1/1998	Tacklind et al.	6,166,563 A	12/2000	Volk et al.
5,711,297 A	1/1998	Iliff	6,168,563 B1	1/2001	Brown
5,713,350 A	2/1998	Yokota et al.	6,169,914 B1	1/2001	Hovland et al.
5,720,770 A	2/1998	Nappholz et al.	6,171,237 B1	1/2001	Avitall et al.
5,720,771 A	2/1998	Snell	6,171,256 B1	1/2001	Joo et al.
5,722,999 A	3/1998	Snell	6,203,495 B1	3/2001	Bardy
5,724,580 A	3/1998	Levi et al.	6,211,011 B1	4/2001	Chen
5,724,983 A	3/1998	Seiker et al.	6,221,011 B1	4/2001	Bardy
5,738,102 A	4/1998	Lemelson	6,223,078 B1	4/2001	Marcovecchio
5,743,267 A	4/1998	Nikolic et al.	6,225,901 B1	5/2001	Kail, IV
5,749,907 A	5/1998	Mann	6,234,964 B1	5/2001	Iliff
5,749,908 A	5/1998	Snell	6,246,992 B1	6/2001	Brown
5,752,976 A	5/1998	Duffin et al.	6,249,705 B1	6/2001	Snell
5,769,074 A	6/1998	Barnhill et al.	6,250,309 B1	6/2001	Krichen et al.
5,771,297 A	6/1998	Richardson	6,261,230 B1	7/2001	Bardy
			6,263,245 B1	7/2001	Snell
			6,270,457 B1	8/2001	Bardy
			6,277,072 B1	8/2001	Bardy
			6,280,380 B1	8/2001	Bardy
			6,283,923 B1	9/2001	Finkelstein et al.
			6,287,252 B1	9/2001	Lugo
			6,290,646 B1	9/2001	Cosentino et al.
			6,302,844 B1	10/2001	Walker et al.
			6,306,088 B1	10/2001	Krausman et al.
			6,312,378 B1	11/2001	Bardy
			6,331,160 B1	12/2001	Bardy
			6,336,900 B1	1/2002	Alleckson et al.
			6,336,903 B1	1/2002	Bardy
			6,363,282 B1	3/2002	Nichols et al.
			6,368,284 B1	4/2002	Bardy
			6,398,727 B1	6/2002	Bui et al.
			6,398,728 B1	6/2002	Bardy
			6,411,840 B1	6/2002	Bardy
			6,416,471 B1	7/2002	Kumar et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,428,483	B1	8/2002	Carlebach	
6,440,066	B1	8/2002	Bardy	
6,442,432	B2	8/2002	Lee	
6,442,433	B1	8/2002	Linberg	
6,454,705	B1	9/2002	Cosentino et al.	
6,454,707	B1	9/2002	Casscells, III et al.	
6,477,424	B1	11/2002	Thompson et al.	
6,478,737	B2	11/2002	Bardy	
6,480,745	B2	11/2002	Nelson et al.	
6,497,655	B1	12/2002	Linberg et al.	
6,564,104	B2	5/2003	Nelson et al.	
6,662,032	B1	12/2003	Gavish et al.	
6,811,537	B2	11/2004	Bardy	
6,827,670	B1	12/2004	Stark	
6,905,463	B2	6/2005	Bardy	
6,908,431	B2	6/2005	Bardy	
6,908,437	B2	6/2005	Bardy	
6,920,360	B2	7/2005	Lee et al.	
6,926,668	B2	8/2005	Bardy	
6,974,413	B2	12/2005	Bardy	
6,997,873	B2	2/2006	Bardy	
7,016,933	B2	3/2006	Glass et al.	
7,070,562	B2	7/2006	Bardy	
7,104,955	B2	9/2006	Bardy	
7,127,290	B2*	10/2006	Girouard et al.	607/17
7,134,996	B2	11/2006	Bardy	
7,144,369	B2	12/2006	Bardy	
7,147,600	B2	12/2006	Bardy	
7,593,952	B2	9/2009	Soll et al.	
8,277,378	B2	10/2012	Bardy	
8,556,810	B2*	10/2013	Bardy	600/301
9,149,237		10/2015	Bardy	
2005/0154267	A1	7/2005	Bardy	
2005/0182309	A1	8/2005	Bardy	
2005/0228243	A1	10/2005	Bardy	
2006/0253006	A1	11/2006	Bardy	
2007/0179357	A1	8/2007	Bardy	
2007/0203423	A1	8/2007	Bardy	
2007/0293739	A1	12/2007	Bardy	
2007/0293772	A1	12/2007	Bardy	
2010/0185063	A1	7/2010	Bardy	
2014/0121545	A1	5/2014	Bardy	
2014/0155765	A1	6/2014	Bardy	
2014/0155766	A1	6/2014	Bardy	

FOREIGN PATENT DOCUMENTS

EP	0531889	3/1993
EP	0711531	5/1996
EP	0887759	12/1998
WO	WO-9739792	10/1997
WO	WO-9801742	1/1998
WO	9807142	2/1998
WO	WO-9842103	9/1998
WO	WO-9914882	3/1999
WO	WO-9946718	9/1999
WO	WO-9955226	11/1999

OTHER PUBLICATIONS

Moody, G. B., "Integration of Real-Time and Off-Line Clinical Data in the MMIC Database", *Computers in Cardiology* 1997, vol. 24, pp. 585-588.

Long, W. J. et al., "Differential Diagnosis Generation From a Causal Network With Probabilities", *Computers in Cardiology* 1988, Proceedings, pp. 185-188.

"Pacemaker System Guide: Discovery Multiprogrammable Pacemakers", *Cardiac Rhythm Management*, Guidant Corporation (1998) (192 pages).

EP Search Report for EP Patent Application No. 00201939.6, filed May 31, 2000, which corresponds to U.S. Appl. No. 09/324,894, which is the parent application to the present U.S. Appl. No. 11/894,312 (3 pages).

Medtronic Model 9790 Programmers, Programming Guide Supplement 9891E Software (May 1996) (43 pages).

Physician's System Manual: Ventak Mini III, Automatic Implantable Cardioverter Defibrillator, Guidant Corporation (1998) (138 pages).

Physician's System Manual: Ventak Mini IV, Automatic Implantable Cardioverter Defibrillator, Guidant Corporation (1998) (136 pages).

PRM Portable Programmer Recorder Monitor, Model 2901, Operator's Manual, Guidant Corporation (1999) (22 pages).

Roberge, et al., "Basic and Applied Biomedical Engineering Building Blocks for Health Care", 1995 IEEE Engineering in Medicine and Biology 17th Annual Conference, vol. 1, Montreal, Canada (Sep. 20-23, 1995).

Hutten, et al., "Cardiac Telemonitoring by Integrating Pacemaker Telemetry within Worldwide Data Communication Systems", Proceedings of 19th International Conference, IEEE/EMBS, Chicago, IL, Oct. 30-Nov. 2, 1997, pp. 974-976.

Braunwald, "Heart Disease: A Textbook of Cardiovascular Medicine", 5th Ed., W.B. Saunders Co., vol. 1, pp. 451-455 (1997).

Vargas, Juan E., "Home-Based Monitoring of Cardiac Patients", Dept. of Electr. & Comput. Eng., South Carolina Univ., Columbia, SC, Information Technology Applications in Biomedicine, Proceedings., 1998 IEEE International Conference, pp. 133-136 (May 16-17, 1998).

Auer, et al., "Paced Epimyocardial Electrograms for Noninvasive Rejection Monitoring After Heart Transplantation", *The Journal of Heart and Lung Transplantation*, vol. 15, No. 10, Oct. 1996, pp. 993-998.

Dunn, et al., "Telemedicine Links Patients in Sioux Lookout with Doctors in Toronto", *CMA Journal*, vol. 122, Feb. 23, 1980, pp. 484-487.

Nelwan, et al., "Ubiquitous Access to Real-Time Patient Monitoring Data", *Computers in Cardiology*, vol. 24, pp. 271-274 (1997).

Magrabi, et al., "Web Based Longitudinal ECG Monitoring", Proceedings of 20th Annual International Conference of the IEEE Engineering in Medicine and Biology Society, vol. 20, No. 3, pp. 1155-1158 (1998).

"File History for co-owned, co-pending U.S. Appl. No. 11/894,281", thru Oct. 11, 2013, Entitled "System and Method for Evaluating a Patient Status for Use in Heart Failure Assessment," Filed on Aug. 20, 2007 (562 pages).

"File History for co-owned, co-pending U.S. Appl. No. 11/540,251", Issued as U.S. Pat. No. 8,277,378 on Oct. 2, 2012, entitled "System and Method for Collection and Analysis of Patient Information for Automated Remote Patient Care" (443 pages).

"File History for co-owned, co-pending U.S. Appl. No. 11/894,312", Issued as U.S. Pat. No. 8,556,810 on Oct. 15, 2013, entitled "System and Method for Evaluating a Patient Status for Use in Heart Failure Assessment" (337 pages).

"File History for co-owned, co-pending U.S. Appl. No. 12/689,706", thru Oct 11, 2013, Entitled "System and Method for Providing Feedback for Automated Remote Patient Care," Filed on Jan. 19, 2010 (296 pages).

Non-Final Office Action, for U.S. Appl. No. 14/102,229, mailed Apr. 3, 2014 (23 pages).

Notice of Allowance for U.S. Appl. No. 14/102,229 mailed Oct. 24, 2014 (5 pages).

"Final Office Action," for U.S. Appl. No. 14/139,650, mailed Mar. 12, 2015 (19 pages).

"Final Office Action," for U.S. Appl. No. 14/139,657, mailed Mar. 4, 2015 (23 pages).

"Non-Final Office Action," for U.S. Appl. No. 14/102,229, mailed Mar. 26, 2015 (17 pages).

"File History", for co-pending U.S. Appl. No. 14/102,229 as of Jan. 9, 2015, filed Dec. 10, 2013 (175 pages).

"File History" for co-owned U.S. Appl. No. 11/894,326, filed Aug. 20, 2007 (128 pages).

"File History" for co-owned U.S. Appl. No. 11/104,969, filed Apr. 12, 2005 (243 pages).

"File History" for co-owned U.S. Appl. No. 11/049,906, filed Feb. 4, 2005 (364 pages).

(56)

References Cited

OTHER PUBLICATIONS

"File History" for co-owned U.S. Appl. No. 11/894,305, filed Aug. 20, 2007 (189 pages).

"File History" for co-owned U.S. Appl. No. 11/480,634, filed Jun. 30, 2006 (211 pages).

"File History" for co-owned U.S. Appl. No. 11/146,558, filed Jun. 7, 2005 (437 pages).

"Non Final Office Action", for U.S. Appl. No. 14/139,650, mailed Nov. 10, 2014 (7 pages).

"Response to Non Final Office Action", for U.S. Appl. No. 14/139,650, filed Feb. 10, 2015 (8 pages).

"Non Final Office Action", for U.S. Appl. No. 14/139,657, mailed Nov. 7, 2014 (8 pages).

"Response to Non-Final Office Action" for U.S. Appl. No. 14/139,657, filed Feb. 9, 2015 (9 pages).

"Non-Final Office Action," for U.S. Appl. No. 14/139,657, mailed Jun. 15, 2015 (12 pages).

"Final Office Action," for U.S. Appl. No. 14/102,229 mailed Sep. 18, 2015 (13 pages).

* cited by examiner




Fig. 1.

Fig. 2.




Fig. 3.




Fig. 4.




Fig. 5.




Fig. 6.

Patient 1

Set 0				Set n-2	Set n-1	Set n
X ₀	•	•	•	X _{n-2}	X _{n-1}	X _n
Y ₀	•	•	•	Y _{n-2}	Y _{n-1}	Y _n
Z ₀	•	•	•	Z _{n-2}	Z _{n-1}	Z _n

time →

Patient 2

Set 0				Set n-2	Set n-1	Set n
X _{0'}	•	•	•	X _{n-2'}	X _{n-1'}	X _{n'}
Y _{0'}	•	•	•	Y _{n-2'}	Y _{n-1'}	Y _{n'}
Z _{0'}	•	•	•	Z _{n-2'}	Z _{n-1'}	Z _{n'}

time →

Patient 3

Set 0				Set n-2	Set n-1	Set n
X _{0''}	•	•	•	X _{n-2''}	X _{n-1''}	X _{n''}
Y _{0''}	•	•	•	Y _{n-2''}	Y _{n-1''}	Y _{n''}
Z _{0''}	•	•	•	Z _{n-2''}	Z _{n-1''}	Z _{n''}

time →

Fig. 7.




Fig. 8.




Fig. 9.




Fig. 10A.




Fig. 10B.





Fig. 11.



SYSTEM AND METHOD FOR EVALUATING A PATIENT STATUS FOR USE IN HEART FAILURE ASSESSMENT

CROSS-REFERENCE TO RELATED APPLICATION

This Patent application is a continuation of U.S. Pat. No. 8,556,810, issued Oct. 15, 2013, which is a continuation of U.S. Pat. No. 8,277,378, issued Oct. 2, 2012, which is a divisional of U.S. Pat. No. 7,144,369, issued Dec. 5, 2006, which is a continuation of U.S. Pat. No. 6,312,378, issued Nov. 6, 2001, the priority filing dates of which are claimed and the disclosures of which are incorporated by reference

FIELD

The present invention relates in general to heart failure assessment, and, in particular, to a system and method for evaluating a patient status for use in heart failure assessment.

BACKGROUND

Implantable pulse generators (IPGs) are medical devices commonly used to treat irregular heartbeats, known as arrhythmias. There are two basic types. Cardiac pacemakers are used to manage bradycardia, an abnormally slow or irregular heartbeat. Left untreated, bradycardia can cause symptoms such as fatigue, dizziness, and fainting. Implantable cardioverter defibrillators (ICDs) are used to treat tachycardia, heart rhythms that are abnormally fast and life threatening. Tachycardia can result in sudden cardiac death (SCD).

Pacemakers and ICDs are increasingly being equipped with an on-board, volatile memory in which telemetered signals can be stored for later retrieval and analysis. Typically, the telemetered signals provide patient device information regarding atrial electrical activity, ventricular electrical activity, time of day, activity level, cardiac output, oxygen level, cardiovascular pressure measures, pulmonary measures, and any interventions made on a per heartbeat or binned average basis. In addition, a growing class of cardiac medical devices, including implantable heart failure monitors, implantable event monitors, cardiovascular monitors, and therapy devices, are being used to provide similar stored device information. These devices are able to store approximately thirty minutes of per heartbeat data. Telemetered signals are also stored in a broader class of monitors and therapeutic devices for other areas of medicine, including metabolism, endocrinology, hematology, neurology, muscular, gastrointestinal, genital-urology, ocular, auditory, and the like.

Presently, stored device information is retrieved using a proprietary interrogator or programmer, often during a clinic visit or following a device event. The volume of data retrieved from a single device interrogation "snapshot" can be large and proper interpretation and analysis can require significant physician time and detailed subspecialty knowledge, particularly by cardiologists and cardiac electrophysiologists. The sequential logging and analysis of regularly scheduled interrogations can create an opportunity for recognizing subtle and incremental changes in patient condition otherwise undetectable by inspection of a single "snapshot." However, present approaches to data interpretation and understanding and practical limitations on time and physician availability make such analysis impracticable.

A prior art system for collecting and analyzing pacemaker and ICD telemetered signals in a clinical or office setting is the Model 9790 Programmer, manufactured by Medtronic,

Inc., Minneapolis, Minn. This programmer can be used to retrieve data, such as patient electrocardiogram and any measured physiological conditions, collected by the IPG for recordation, display and printing. The retrieved data is displayed in chronological order and analyzed by a physician. Comparable prior art systems are available from other IPG manufacturers, such as the Model 2901 Programmer Recorder Monitor, manufactured by Guidant Corporation, Indianapolis, Ind., which includes a removable floppy diskette mechanism for patient data storage. These prior art systems lack remote communications facilities and must be operated with the patient present. These systems present a limited analysis of the collected data based on a single device interrogation and lack the capability to recognize trends in the data spanning multiple episodes over time or relative to a disease specific peer group.

A prior art system for locating and communicating with a remote medical device implanted in an ambulatory patient is disclosed in U.S. Pat. No. 5,752,976 ('976). The implanted device includes a telemetry transceiver for communicating data and operating instructions between the implanted device and an external patient communications device. The communications device includes a communication link to a remote medical support network, a global positioning satellite receiver, and a patient activated link for permitting patient initiated communication with the medical support network.

Related prior art systems for remotely communicating with and receiving telemetered signals from a medical device are disclosed in U.S. Pat. Nos. 5,113,869 ('869) and 5,336,245 ('245). In the '869 patent, an implanted AECG monitor can be automatically interrogated at preset times of day to telemeter out accumulated data to a telephonic communicator or a full disclosure recorder. The communicator can be automatically triggered to establish a telephonic communication link and transmit the accumulated data to an office or clinic through a modem. In the '245 patent, telemetered data is downloaded to a larger capacity, external data recorder and is forwarded to a clinic using an auto-dialer and fax modem operating in a personal computer-based programmer/interrogator. However, the '976 telemetry transceiver, '869 communicator, and '245 programmer/interrogator are limited to facilitating communication and transferal of downloaded patient data and do not include an ability to automatically track, recognize, and analyze trends in the data itself.

Thus, there is a need for a system and method for providing continuous retrieval, transferal, and automated analysis of retrieved implantable medical device information, such as telemetered signals, retrieved in general from a broad class of implantable medical devices and, in particular, from IPGs and cardiovascular monitors. Preferably, the automated analysis would include recognizing a trend and determining whether medical intervention is necessary.

There is a further need for a system and method that would allow consideration of sets of collected measures, both actual and derived, from multiple device interrogations. These collected measures sets could then be compared and analyzed against short and long term periods of observation.

There is a further need for a system and method that would enable the measures sets for an individual patient to be self-referenced and cross-referenced to similar or dissimilar patients and to the general patient population. Preferably, the historical collected measures sets of an individual patient could be compared and analyzed against those of other patients in general or of a disease specific peer group in particular.

SUMMARY

The present invention provides a system and method for providing collection and analysis of patient information for

use in automated patient care. The patient device information relates to individual measures recorded by and retrieved from implantable medical devices, such as IPGs and monitors. The patient device information is received on a regular, e.g., daily, basis as sets of collected measures which are stored along with other patient records in a database. The information can be analyzed in an automated fashion and feedback provided to the patient at any time and in any location.

An embodiment provides a system and method for evaluating a patient status for use in heart failure assessment. Physiological measures are assembled, which were directly recorded as data on a substantially continuous basis by an implantable medical device for a patient or indirectly derived from the data. A status for the patient is determined through sampling and analysis of the physiological measures over a plurality of data assembly points. Trends that are indicated by the patient status are identified and each trend is compared to worsening heart failure indications.

A further embodiment provides a system and method for evaluating a patient status from sampled physiometry for use in heart failure assessment. Physiological measures are stored, including at least one of direct measures regularly recorded on a substantially continuous basis by an implantable medical device for a patient and measures derived from the direct measures. At least one of those of the physiological measures, which each relate to a same type of physiometry, and those of the physiological measures, which each relate to a different type of physiometry are sampled. A status for the patient is determined through analysis of the sampled physiological measures assembled from a plurality of recordation points. The sampled physiological measures are evaluated. Any trends that are indicated by the patient status, which might affect cardiac performance of the patient, are identified. Each trend is compared to worsening heart failure indications to generate a notification of parameter violations.

The present invention facilitates the gathering, storage, and analysis of critical patient information obtained on a routine basis and analyzed in an automated manner. Thus, the burden on physicians and trained personnel to evaluate the volumes of information is significantly minimized while the benefits to patients are greatly enhanced.

Still other embodiments of the present invention will become readily apparent to those skilled in the art from the following detailed description, wherein is described embodiments of the invention by way of illustrating the best mode contemplated for carrying out the invention. As will be realized, the invention is capable of other and different embodiments and its several details are capable of modifications in various obvious respects, all without departing from the spirit and the scope of the present invention. Accordingly, the drawings and detailed description are to be regarded as illustrative in nature and not as restrictive.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram showing a system for providing collection and analysis of patient information for use in automated patient care in accordance with the present invention;

FIG. 2 is a block diagram showing the hardware components of the server system of the system of FIG. 1;

FIG. 3 is a block diagram showing the software modules of the server system of the system of FIG. 1;

FIG. 4 is a block diagram showing the analysis module of the server system of FIG. 3;

FIG. 5 is a database schema showing, by way of example, the organization of a cardiac patient care record stored in the database of the system of FIG. 1;

FIG. 6 is a record view showing, by way of example, a set of partial cardiac patient care records stored in the database of the system of FIG. 1;

FIG. 7 is a flow diagram showing a method for providing collection and analysis of patient information for use in automated patient care in accordance with the present invention;

FIG. 8 is a flow diagram showing a routine for analyzing collected measures sets for use in the method of FIG. 7;

FIG. 9 is a flow diagram showing a routine for comparing sibling collected measures sets for use in the routine of FIG. 8;

FIGS. 10A and 10B are flow diagrams showing a routine for comparing peer collected measures sets for use in the routine of FIG. 8; and

FIG. 11 is a flow diagram showing a routine for providing feedback for use in the method of FIG. 7.

DETAILED DESCRIPTION

FIG. 1 is a block diagram showing a system 10 for providing collection and analysis of patient information for use in automated patient care in accordance with the present invention. A patient 11 is a recipient of an implantable medical device 12, such as, by way of example, an IPG or a heart failure or event monitor, with a set of leads extending into his or her heart. The implantable medical device 12 includes circuitry for recording into a short-term, volatile memory telemetered signals, which are stored as a set of collected measures for later retrieval.

For an exemplary cardiac implantable medical device, the telemetered signals non-exclusively present patient information relating to: atrial electrical activity, ventricular electrical activity, time of day, activity level, cardiac output, oxygen level, cardiovascular pressure measures, the number and types of interventions made, and the relative success of any interventions made on a per heartbeat or binned average basis, plus the status of the batteries and programmed settings. Examples of pacemakers suitable for use in the present invention include the Discovery line of pacemakers, manufactured by Guidant Corporation, Indianapolis, Ind. Examples of ICDs suitable for use in the present invention include the Ventak line of ICDs, also manufactured by Guidant Corporation, Indianapolis, Ind.

In the described embodiment, the patient 11 has a cardiac implantable medical device. However, a wide range of related implantable medical devices are used in other areas of medicine and a growing number of these devices are also capable of measuring and recording patient information for later retrieval. These implantable medical devices include monitoring and therapeutic devices for use in metabolism, endocrinology, hematology, neurology, muscularology, gastro-intestinalology, genital-urology, ocular, auditory, and similar medical subspecialties. One skilled in the art would readily recognize the applicability of the present invention to these related implantable medical devices.

On a regular basis, the telemetered signals stored in the implantable medical device 12 are retrieved. By way of example, a programmer 14 can be used to retrieve the telemetered signals. However, any form of programmer, interrogator, recorder, monitor, or telemetered signals transceiver suitable for communicating with an implantable medical device 12 could be used, as is known in the art. In addition, a personal computer or digital data processor could be interfaced to the implantable medical device 12, either directly or via a telemetered signals transceiver configured to communicate with the implantable medical device 12.

Using the programmer **14**, a magnetized reed switch (not shown) within the implantable medical device **12** closes in response to the placement of a wand **13** over the location of the implantable medical device **12**. The programmer **14** communicates with the implantable medical device **12** via RF signals exchanged through the wand **14**. Programming or interrogating instructions are sent to the implantable medical device **12** and the stored telemetered signals are downloaded into the programmer **14**. Once downloaded, the telemetered signals are sent via an internetwork **15**, such as the Internet, to a server system **16** which periodically receives and stores the telemetered signals in a database **17**, as further described below with reference to FIG. 2.

An example of a programmer **14** suitable for use in the present invention is the Model 2901 Programmer Recorder Monitor, manufactured by Guidant Corporation, Indianapolis, Ind., which includes the capability to store retrieved telemetered signals on a proprietary removable floppy diskette. The telemetered signals could later be electronically transferred using a personal computer or similar processing device to the internetwork **15**, as is known in the art.

Other alternate telemetered signals transfer means could also be employed. For instance, the stored telemetered signals could be retrieved from the implantable medical device **12** and electronically transferred to the internetwork **15** using the combination of a remote external programmer and analyzer and a remote telephonic communicator, such as described in U.S. Pat. No. 5,113,869, the disclosure of which is incorporated herein by reference. Similarly, the stored telemetered signals could be retrieved and remotely downloaded to the server system **16** using a world-wide patient location and data telemetry system, such as described in U.S. Pat. No. 5,752,976, the disclosure of which is incorporated herein by reference.

The received telemetered signals are analyzed by the server system **16**, which generates a patient status indicator. The feedback is then provided back to the patient **11** through a variety of means. By way of example, the feedback can be sent as an electronic mail message generated automatically by the server system **16** for transmission over the internetwork **15**. The electronic mail message is received by personal computer **18** (PC) situated for local access by the patient **11**. Alternatively, the feedback can be sent through a telephone interface device **19** as an automated voice mail message to a telephone **21** or as an automated facsimile message to a facsimile machine **22**, both also situated for local access by the patient **11**. In addition to a personal computer **18**, telephone **21**, and facsimile machine **22**, feedback could be sent to other related devices, including a network computer, wireless computer, personal data assistant, television, or digital data processor. Preferably, the feedback is provided in a tiered fashion, as further described below with reference to FIG. 3.

FIG. 2 is a block diagram showing the hardware components of the server system **16** of the system **10** of FIG. 1. The server system **16** consists of three individual servers: network server **31**, database server **34**, and application server **35**. These servers are interconnected via an intranetwork **33**. In the described embodiment, the functionality of the server system **16** is distributed among these three servers for efficiency and processing speed, although the functionality could also be performed by a single server or cluster of servers. The network server **31** is the primary interface of the server system **16** onto the internetwork **15**. The network server **31** periodically receives the collected telemetered signals sent by remote implantable medical devices over the internetwork **15**. The network server **31** is interfaced to the internetwork **15** through a router **32**. To ensure reliable data exchange, the

network server **31** implements a TCP/IP protocol stack, although other forms of network protocol stacks are suitable.

The database server **34** organizes the patient care records in the database **17** and provides storage of and access to information held in those records. A high volume of data in the form of collected measures sets from individual patients is received. The database server **34** frees the network server **31** from having to categorize and store the individual collected measures sets in the appropriate patient care record.

The application server **35** operates management applications and performs data analysis of the patient care records, as further described below with reference to FIG. 3. The application server **35** communicates feedback to the individual patients either through electronic mail sent back over the internetwork **15** via the network server **31** or as automated voice mail or facsimile messages through the telephone interface device **19**.

The server system **16** also includes a plurality of individual workstations **36** (WS) interconnected to the intranetwork **33**, some of which can include peripheral devices, such as a printer **37**. The workstations **36** are for use by the data management and programming staff, nursing staff, office staff, and other consultants and authorized personnel.

The database **17** consists of a high-capacity storage medium configured to store individual patient care records and related health care information. Preferably, the database **17** is configured as a set of high-speed, high capacity hard drives, such as organized into a Redundant Array of Inexpensive Disks (RAID) volume. However, any form of volatile storage, non-volatile storage, removable storage, fixed storage, random access storage, sequential access storage, permanent storage, erasable storage, and the like would be equally suitable. The organization of the database **17** is further described below with reference to FIG. 3.

The individual servers and workstations are general purpose, programmed digital computing devices consisting of a central processing unit (CPU), random access memory (RAM), non-volatile secondary storage, such as a hard drive or CD ROM drive, network interfaces, and peripheral devices, including user interfacing means, such as a keyboard and display. Program code, including software programs, and data are loaded into the RAM for execution and processing by the CPU and results are generated for display, output, transmittal, or storage. In the described embodiment, the individual servers are Intel Pentium-based server systems, such as available from Dell Computers, Austin, Tex., or Compaq Computers, Houston, Tex. Each system is preferably equipped with 128 MB RAM, 100 GB hard drive capacity, data backup facilities, and related hardware for interconnection to the intranetwork **33** and internetwork **15**. In addition, the workstations **36** are also Intel Pentium-based personal computer or workstation systems, also available from Dell Computers, Austin, Tex., or Compaq Computers, Houston, Tex. Each workstation is preferably equipped with 64 MB RAM, 10 GB hard drive capacity, and related hardware for interconnection to the intranetwork **33**. Other types of server and workstation systems, including personal computers, minicomputers, mainframe computers, supercomputers, parallel computers, workstations, digital data processors and the like would be equally suitable, as is known in the art.

The telemetered signals are communicated over an internetwork **15**, such as the Internet. However, any type of electronic communications link could be used, including an intranetwork link, serial link, data telephone link, satellite link, radio-frequency link, infrared link, fiber optic link, coaxial cable link, television link, and the like, as is known in the art. Also, the network server **31** is interfaced to the inter-

network **15** using a T-1 network router **32**, such as manufactured by Cisco Systems, Inc., San Jose, Calif. However, any type of interfacing device suitable for interconnecting a server to a network could be used, including a data modem, cable modem, network interface, serial connection, data port, hub, frame relay, digital PBX, and the like, as is known in the art.

FIG. **3** is a block diagram showing the software modules of the server system **16** of the system **10** of FIG. **1**. Each module is a computer program written as source code in a conventional programming language, such as the C or Java programming languages, and is presented for execution by the CPU as object or byte code, as is known in the arts. The various implementations of the source code and object and byte codes can be held on a computer-readable storage medium or embodied on a transmission medium in a carrier wave. There are three basic software modules, which functionally define the primary operations performed by the server system **16**: database module **51**, analysis module **53**, and feedback module **55**. In the described embodiment, these modules are executed in a distributed computing environment, although a single server or a cluster of servers could also perform the functionality of the modules. The module functions are further described below in more detail beginning with reference to FIG. **7**.

For each patient being provided remote patient care, the server system **16** periodically receives a collected measures set **50** which is forwarded to the database module **51** for processing. The database module **51** organizes the individual patient care records stored in the database **52** and provides the facilities for efficiently storing and accessing the collected measures sets **50** and patient data maintained in those records. An exemplary database schema for use in storing collected measures sets **50** in a patient care record is described below, by way of example, with reference to FIG. **5**. The database server **34** (shown in FIG. **2**) performs the functionality of the database module **51**. Any type of database organization could be utilized, including a flat file system, hierarchical database, relational database, or distributed database, such as provided by database vendors, such as Oracle Corporation, Redwood Shores, Calif.

The analysis module **53** analyzes the collected measures sets **50** stored in the patient care records in the database **52**. The analysis module **53** makes an automated determination of patient wellness in the form of a patient status indicator **54**. Collected measures sets **50** are periodically received from implantable medical devices and maintained by the database module **51** in the database **52**. Through the use of this collected information, the analysis module **53** can continuously follow the medical well being of a patient and can recognize any trends in the collected information that might warrant medical intervention. The analysis module **53** compares individual measures and derived measures obtained from both the care records for the individual patient and the care records for a disease specific group of patients or the patient population in general. The analytic operations performed by the analysis module **53** are further described below with reference to FIG. **4**. The application server **35** (shown in FIG. **2**) performs the functionality of the analysis module **53**.

The feedback module **55** provides automated feedback to the individual patient based, in part, on the patient status indicator **54**. As described above, the feedback could be by electronic mail or by automated voice mail or facsimile. Preferably, the feedback is provided in a tiered manner. In the described embodiment, four levels of automated feedback are provided. At a first level, an interpretation of the patient status indicator **54** is provided. At a second level, a notification of

potential medical concern based on the patient status indicator **54** is provided. This feedback level could also be coupled with human contact by specially trained technicians or medical personnel. At a third level, the notification of potential medical concern is forwarded to medical practitioners located in the patient's geographic area. Finally, at a fourth level, a set of reprogramming instructions based on the patient status indicator **54** could be transmitted directly to the implantable medical device to modify the programming instructions contained therein. As is customary in the medical arts, the basic tiered feedback scheme would be modified in the event of bona fide medical emergency. The application server **35** (shown in FIG. **2**) performs the functionality of the feedback module **55**.

FIG. **4** is a block diagram showing the analysis module **53** of the server system **16** of FIG. **3**. The analysis module **53** contains two functional submodules: comparison module **62** and derivation module **63**. The purpose of the comparison module **62** is to compare two or more individual measures, either collected or derived. The purpose of the derivation module **63** is to determine a derived measure based on one or more collected measures which is then used by the comparison module **62**. For instance, a new and improved indicator of impending heart failure could be derived based on the exemplary cardiac collected measures set described with reference to FIG. **5**. The analysis module **53** can operate either in a batch mode of operation wherein patient status indicators are generated for a set of individual patients or in a dynamic mode wherein a patient status indicator is generated on the fly for an individual patient.

The comparison module **62** receives as inputs from the database **17** two input sets functionally defined as peer collected measures sets **60** and sibling collected measures sets **61**, although in practice, the collected measures sets are stored on a per sampling basis. Peer collected measures sets **60** contain individual collected measures sets that all relate to the same type of patient information, for instance, atrial electrical activity, but which have been periodically collected over time. Sibling collected measures sets **61** contain individual collected measures sets that relate to different types of patient information, but which may have been collected at the same time or different times. In practice, the collected measures sets are not separately stored as "peer" and "sibling" measures. Rather, each individual patient care record stores multiple sets of sibling collected measures. The distinction between peer collected measures sets **60** and sibling collected measures sets **61** is further described below with reference to FIG. **6**.

The derivation module **63** determines derived measures sets **64** on an as-needed basis in response to requests from the comparison module **62**. The derived measures **64** are determined by performing linear and non-linear mathematical operations on selected peer measures **60** and sibling measures **61**, as is known in the art.

FIG. **5** is a database schema showing, by way of example, the organization of a cardiac patient care record stored **70** in the database **17** of the system **10** of FIG. **1**. Only the information pertaining to collected measures sets are shown. Each patient care record would also contain normal identifying and treatment profile information, as well as medical history and other pertinent data (not shown). Each patient care record stores a multitude of collected measures sets for an individual patient. Each individual set represents a recorded snapshot of telemetered signals data which was recorded, for instance, per heartbeat or binned average basis by the implantable medical device **12**. For example, for a cardiac patient, the following information would be recorded as a collected mea-

asures set: atrial electrical activity **71**, ventricular electrical activity **72**, time of day **73**, activity level **74**, cardiac output **75**, oxygen level **76**, cardiovascular pressure measures **77**, pulmonary measures **78**, interventions made by the implantable medical device **78**, and the relative success of any interventions made **80**. In addition, the implantable medical device **12** would also communicate device specific information, including battery status **81** and program settings **82**. Other types of collected measures are possible. In addition, a well-documented set of derived measures can be determined based on the collected measures, as is known in the art.

FIG. **6** is a record view showing, by way of example, a set of partial cardiac patient care records stored in the database **17** of the system **10** of FIG. **1**. Three patient care records are shown for Patient 1, Patient 2, and Patient 3. For each patient, three sets of measures are shown, X, Y, and Z. The measures are organized into sets with Set 0 representing sibling measures made at a reference time $t=0$. Similarly, Set $n-2$, Set $n-1$ and Set n each represent sibling measures made at later reference times $t=n-2$, $t=n-1$ and $t=n$, respectively.

For a given patient, for instance, Patient 1, all measures representing the same type of patient information, such as measure X, are peer measures. These are measures, which are monitored over time in a disease-matched peer group. All measures representing different types of patient information, such as measures X, Y, and Z, are sibling measures. These are measures which are also measured over time, but which might have medically significant meaning when compared to each other within a single set. Each of the measures, X, Y, and Z, could be either collected or derived measures.

The analysis module **53** (shown in FIG. **4**) performs two basic forms of comparison. First, individual measures for a given patient can be compared to other individual measures for that same patient. These comparisons might be peer-to-peer measures projected over time, for instance, $X_n, X_{n-1}, X_{n-2}, \dots, X_0$, or sibling-to-sibling measures for a single snapshot, for instance, X_n, Y_n , and Z_n , or projected over time, for instance, $X_n, Y_n, Z_n, X_{n-1}, Y_{n-1}, Z_{n-1}, X_{n-2}, Y_{n-2}, Z_{n-2}, \dots, X_0, Y_0, Z_0$. Second, individual measures for a given patient can be compared to other individual measures for a group of other patients sharing the same disease-specific characteristics or to the patient population in general. Again, these comparisons might be peer-to-peer measures projected over time, for instance, $X_n, X_n^s, X_n^s, X_{n-1}, X_{n-1}^s, X_{n-1}^s, X_{n-2}, X_{n-2}^s, X_{n-2}^s, \dots, X_0, X_0^s, X_0^s$, or comparing the individual patient's measures to an average from the group. Similarly, these comparisons might be sibling-to-sibling measures for single snapshots, for instance, $X_n, X_n^s, X_n^s, Y_n, Y_n^s, Y_n^s$, and Z_n, Z_n^s, Z_n^s , or projected over time, for instance, $X_n, X_n^s, X_n^s, Y_n, Y_n^s, Y_n^s, Z_n, Z_n^s, Z_n^s, X_{n-1}, X_{n-1}^s, X_{n-1}^s, Y_{n-1}, Y_{n-1}^s, Y_{n-1}^s, Z_{n-1}, Z_{n-1}^s, Z_{n-1}^s, X_{n-2}, X_{n-2}^s, X_{n-2}^s, Y_{n-2}, Y_{n-2}^s, Y_{n-2}^s, Z_{n-2}, Z_{n-2}^s, Z_{n-2}^s, \dots, X_0, X_0^s, X_0^s, Y_0, Y_0^s, Y_0^s$, and Z_0, Z_0^s, Z_0^s . Other forms of comparisons are feasible.

FIG. **7** is a flow diagram showing a method **90** for automated collection and analysis of patient information retrieved from an implantable medical device **12** for remote patient care in accordance with the present invention. The method **90** is implemented as a conventional computer program for execution by the server system **16** (shown in FIG. **1**). As a preparatory step, the patient care records are organized in the database **17** with a unique patient care record assigned to each individual patient (block **91**). Next, the collected measures sets for an individual patient are retrieved from the implantable medical device **12** (block **92**) using a programmer, interrogator, telemetered signals transceiver, and the like. The retrieved collected measures sets are sent, on a substantially regular basis, over the internet **15** or similar communi-

cations link (block **93**) and periodically received by the server system **16** (block **94**). The collected measures sets are stored into the patient care record in the database **17** for that individual patient (block **95**). One or more of the collected measures sets for that patient are analyzed (block **96**), as further described below with reference to FIG. **8**. Finally, feedback based on the analysis is sent to that patient over the internet **15** as an email message, via telephone line as an automated voice mail or facsimile message, or by similar feedback communications link (block **97**), as further described below with reference to FIG. **11**.

FIG. **8** is a flow diagram showing the routine for analyzing collected measures sets **96** for use in the method of FIG. **7**. The purpose of this routine is to make a determination of general patient wellness based on comparisons and heuristic trends analyses of the measures, both collected and derived, in the patient care records in the database **17**. A first collected measures set is selected from a patient care record in the database **17** (block **100**). If the measures comparison is to be made to other measures originating from the patient care record for the same individual patient (block **101**), a second collected measures set is selected from that patient care record (block **102**). Otherwise, a group measures comparison is being made (block **101**) and a second collected measures set is selected from another patient care record in the database **17** (block **103**). Note the second collected measures set could also contain averaged measures for a group of disease specific patients or for the patient population in general.

Next, if a sibling measures comparison is to be made (block **104**), a routine for comparing sibling collected measures sets is performed (block **105**), as further described below with reference to FIG. **9**. Similarly, if a peer measures comparison is to be made (block **106**), a routine for comparing sibling collected measures sets is performed (block **107**), as further described below with reference to FIGS. **10A** and **10B**.

Finally, a patient status indicator is generated (block **108**). By way of example, cardiac output could ordinarily be approximately 5.0 liters per minute with a standard deviation of ± 1.0 . An actionable medical phenomenon could occur when the cardiac output of a patient is ± 3.0 -4.0 standard deviations out of the norm. A comparison of the cardiac output measures **75** (shown in FIG. **5**) for an individual patient against previous cardiac output measures **75** would establish the presence of any type of downward health trend as to the particular patient. A comparison of the cardiac output measures **75** of the particular patient to the cardiac output measures **75** of a group of patients would establish whether the patient is trending out of the norm. From this type of analysis, the analysis module **53** generates a patient status indicator **54** and other metrics of patient wellness, as is known in the art.

FIG. **9** is a flow diagram showing the routine for comparing sibling collected measures sets **105** for use in the routine of FIG. **8**. Sibling measures originate from the patient care records for an individual patient. The purpose of this routine is either to compare sibling derived measures to sibling derived measures (blocks **111-113**) or sibling collected measures to sibling collected measures (blocks **115-117**). Thus, if derived measures are being compared (block **110**), measures are selected from each collected measures set (block **111**). First and second derived measures are derived from the selected measures (block **112**) using the derivation module **63** (shown in FIG. **4**). The first and second derived measures are then compared (block **113**) using the comparison module **62** (also shown in FIG. **4**). The steps of selecting, determining,

and comparing (blocks 111-113) are repeated until no further comparisons are required (block 114), whereupon the routine returns.

If collected measures are being compared (block 110), measures are selected from each collected measures set (block 115). The first and second collected measures are then compared (block 116) using the comparison module 62 (also shown in FIG. 4). The steps of selecting and comparing (blocks 115-116) are repeated until no further comparisons are required (block 117), whereupon the routine returns.

FIGS. 10A and 10B are a flow diagram showing the routine for comparing peer collected measures sets 107 for use in the routine of FIG. 8. Peer measures originate from patient care records for different patients, including groups of disease specific patients or the patient population in general. The purpose of this routine is to compare peer derived measures to peer derived measures (blocks 122-125), peer derived measures to peer collected measures (blocks 126-129), peer collected measures to peer derived measures (block 131-134), or peer collected measures to peer collected measures (blocks 135-137). Thus, if the first measure being compared is a derived measure (block 120) and the second measure being compared is also a derived measure (block 121), measures are selected from each collected measures set (block 122). First and second derived measures are derived from the selected measures (block 123) using the derivation module 63 (shown in FIG. 4). The first and second derived measures are then compared (block 124) using the comparison module 62 (also shown in FIG. 4). The steps of selecting, determining, and comparing (blocks 122-124) are repeated until no further comparisons are required (block 115), whereupon the routine returns.

If the first measure being compared is a derived measure (block 120) but the second measure being compared is a collected measure (block 121), a first measure is selected from the first collected measures set (block 126). A first derived measure is derived from the first selected measure (block 127) using the derivation module 63 (shown in FIG. 4). The first derived and second collected measures are then compared (block 128) using the comparison module 62 (also shown in FIG. 4). The steps of selecting, determining, and comparing (blocks 126-128) are repeated until no further comparisons are required (block 129), whereupon the routine returns.

If the first measure being compared is a collected measure (block 120) but the second measure being compared is a derived measure (block 130), a second measure is selected from the second collected measures set (block 131). A second derived measure is derived from the second selected measure (block 132) using the derivation module 63 (shown in FIG. 4). The first collected and second derived measures are then compared (block 133) using the comparison module 62 (also shown in FIG. 4). The steps of selecting, determining, and comparing (blocks 131-133) are repeated until no further comparisons are required (block 134), whereupon the routine returns.

If the first measure being compared is a collected measure (block 120) and the second measure being compared is also a collected measure (block 130), measures are selected from each collected measures set (block 135). The first and second collected measures are then compared (block 136) using the comparison module 62 (also shown in FIG. 4). The steps of selecting and comparing (blocks 135-136) are repeated until no further comparisons are required (block 137), whereupon the routine returns.

FIG. 11 is a flow diagram showing the routine for providing feedback 97 for use in the method of FIG. 7. The purpose of

this routine is to provide tiered feedback based on the patient status indicator. Four levels of feedback are provided with increasing levels of patient involvement and medical care intervention. At a first level (block 150), an interpretation of the patient status indicator 54, preferably phrased in lay terminology, and related health care information is sent to the individual patient (block 151) using the feedback module 55 (shown in FIG. 3). At a second level (block 152), a notification of potential medical concern, based on the analysis and heuristic trends analysis, is sent to the individual patient (block 153) using the feedback module 55. At a third level (block 154), the notification of potential medical concern is forwarded to the physician responsible for the individual patient or similar health care professionals (block 155) using the feedback module 55. Finally, at a fourth level (block 156), reprogramming instructions are sent to the implantable medical device 12 (block 157) using the feedback module 55.

Therefore, through the use of the collected measures sets, the present invention makes possible immediate access to expert medical care at any time and in any place. For example, after establishing and registering for each patient an appropriate baseline set of measures, the database server could contain a virtually up-to-date patient history, which is available to medical providers for the remote diagnosis and prevention of serious illness regardless of the relative location of the patient or time of day.

Moreover, the gathering and storage of multiple sets of critical patient information obtained on a routine basis makes possible treatment methodologies based on an algorithmic analysis of the collected data sets. Each successive introduction of a new collected measures set into the database server would help to continually improve the accuracy and effectiveness of the algorithms used. In addition, the present invention potentially enables the detection, prevention, and cure of previously unknown forms of disorders based on a trends analysis and by a cross-referencing approach to create continuously improving peer-group reference databases.

Finally, the present invention makes possible the provision of tiered patient feedback based on the automated analysis of the collected measures sets. This type of feedback system is suitable for use in, for example, a subscription based health care service. At a basic level, informational feedback can be provided by way of a simple interpretation of the collected data. The feedback could be built up to provide a graded response to the patient, for example, to notify the patient that he or she is trending into a potential trouble zone. Human interaction could be introduced, both by remotely situated and local medical practitioners. Finally, the feedback could include direct interventive measures, such as remotely reprogramming a patient's IPG.

While the invention has been particularly shown and described as referenced to the embodiments thereof, those skilled in the art will understand that the foregoing and other changes in form and detail may be made therein without departing from the spirit and scope of the invention.

What is claimed is:

1. A system for evaluating a patient status for use in heart failure assessment, comprising:

an implantable medical device configured to periodically collect patient data on a long-term, daily basis, wherein the implantable medical device is further configured to store a collected measures set containing a portion of the patient data;

a comparison module configured to receive the collected measures set and compare the collected measures set to a second collected measures set containing comparison data to determine a trend in the patient data;

13

an analysis module configured to generate a patient status indicator based on the trend; and

a feedback module configured to provide a notification of a potential medical concern based on the patient status indicator, wherein the patient data comprises the number of device interventions made, the type of device interventions made, and the relative success of any interventions made on a per heartbeat or binned average basis.

2. The system of claim 1, wherein the comparison data in the second collected measures set comprises averaged measures.

3. The system of claim 1, further comprising a collection client and a network server, wherein the collection client is configured to be communicatively interposed between the implantable medical device and a communication link, retrieve the collected measures set from the implantable medical device, and download the collected measures set into the network server over the communications link.

4. The system of claim 3, wherein the collection client is selected from the group consisting of: a programmer, interrogator, recorder, monitor, telemetered signals transceiver, personal computer, digital data processor, and combinations thereof.

5. The system of claim 1, wherein the implantable medical device is further configured to provide cardiac pacing and defibrillation.

6. The system of claim 1, wherein the feedback module is further configured to provide tiered notifications comprising: at a first level, an interpretation of the patient status; at a second level, a notification of potential medical concern based on the patient status; at a third level, a notification of potential medical concern based on the patient status to medical personnel; and at a fourth level, a set of reprogramming instructions based on the patient status to an implantable medical device.

7. The system of claim 1, further comprising a programmer configured to retrieve and display patient data from the implantable medical device.

8. The system of claim 1, wherein the implantable medical device comprises a battery and is configured to store data comprising battery status, and wherein the feedback module is configured to provide notification of the battery status.

9. The system of claim 1, wherein the feedback module is further configured to provide the notification consistent with a particular level of patient involvement and medical care intervention from a plurality of levels of patient involvement and medical care intervention.

10. A method for evaluating a patient status for use in heart failure assessment, comprising:

periodically collecting, by an implantable medical device, patient data on a long-term, daily basis;

14

storing, by the implantable medical device, a collected measures set containing a portion of the patient data; receiving, by a comparison module, the collected measures set and comparing the collected measures set to a second collected measures set containing comparison data to determine a trend in the patient data;

generating, by an analysis module, a patient status indicator based on the trend; and

providing, by a feedback module, a notification of a potential medical concern based on the patient status indicator, wherein the patient data comprises the number of device interventions made, the type of device interventions made and the relative success of any interventions made on a per heartbeat or binned average basis.

11. The method of claim 10, wherein the comparison data in the second collected measures set comprises averaged measures.

12. The method of claim 10, further comprising retrieving, by a collection client, the collected measures set from the implantable medical device and downloading the collected measures set into a network server over a communications link.

13. The method of claim 12, wherein the collection client is selected from the group consisting of: a programmer, interrogator, recorder, monitor, telemetered signals transceiver, personal computer, digital data processor, and combinations thereof.

14. The method of claim 10, providing cardiac pacing and defibrillation by the implantable medical device.

15. The method of claim 10, wherein providing a notification comprises one or more of tiered notifications comprising: at a first level, providing an interpretation of the patient status;

at a second level, providing a notification of potential medical concern based on the patient status;

at a third level, providing a notification of potential medical concern based on the patient status to medical personnel; and

at a fourth level, providing a set of reprogramming instructions based on the patient status to an implantable medical device.

16. The method of claim 10, further comprising retrieving and displaying patient data from the implantable medical device by a programmer.

17. The method of claim 10, further comprising storing battery status data by the medical device and providing notification of the battery status by the feedback module.

18. The method of claim 10, wherein providing the notification is consistent with a particular level of patient involvement and medical care intervention from a plurality of levels of patient involvement and medical care intervention.

* * * * *

专利名称(译)	用于评估患者状态以用于心力衰竭评估的系统和方法		
公开(公告)号	US9186061	公开(公告)日	2015-11-17
申请号	US14/053375	申请日	2013-10-14
[标]申请(专利权)人(译)	心脏起搏器股份公司		
申请(专利权)人(译)	心脏起搏器, INC.		
当前申请(专利权)人(译)	心脏起搏器, INC.		
[标]发明人	BARDY GUST		
发明人	BARDY, GUST		
IPC分类号	A61B5/00 G06F19/00 G06Q50/24 A61B5/0205 G16H10/60		
CPC分类号	A61B5/0031 A61B5/0205 G06F19/322 G06F19/3418 G06Q50/24 G06F19/3406 Y10S128/92 G16H10/60 G16H40/63		
优先权	11/540251 2012-10-02 US 09/948307 2006-12-05 US 09/324894 2001-11-06 US		
其他公开文献	US20140039327A1		
外部链接	Espacenet USPTO		

摘要(译)

提出了一种用于从采样的健康测量中评估患者状态以用于心力衰竭评估的系统和方法。存储生理措施, 包括通过用于患者的可植入医疗装置基本上连续地定期记录的直接测量和从直接测量得到的测量中的至少一种。对每种生理测量中的至少一种生理测量进行采样, 每种生理测量涉及相同类型的生理测量, 以及生理测量的每一种涉及不同类型的生理测量。通过分析从多个记录点组装的采样生理测量来确定患者的状态。评估采样的生理测量。识别由患者状态指示的可能影响患者心脏性能的趋势。将每种趋势与恶化的心力衰竭指征进行比较, 以生成参数违规的通知。

