

(12) **Patent Application Publication**
Ruppersberg

(43) **Pub. Date:** **May 3, 2018**

CPC *A61B 5/6858* (2013.01); *A61B 5/0422*
(2013.01); *A61B 2562/164* (2013.01); *A61B*
2562/046 (2013.01); *A61B 2562/125*
(2013.01); *A61B 2562/0209* (2013.01)

(22) Filed: **Oct. 25, 2017**


(60) Provisional application No. 62/414,183, filed on Oct. 28, 2016.

(51) **Int. Cl.**

A61B 5/00 (2006.01)
A61B 5/042 (2006.01)

(57) **ABSTRACT**

Disclosed are various examples and embodiments of a cardiac mapping catheter configured for electrophysiological (EP) mapping and suitable for intravascular insertion in a patient's heart, and methods of making same. The cardiac mapping catheter comprises a plurality support arms having electrodes disposed thereon. Various configurations of the cardiac mapping catheter are described and disclosed which provide improved spatial resolution and sensing of EP signals acquired from inside a patient's heart.






FIG. 1
PRIOR ART




FIG. 2

FIG. 3a




FIG. 3b




FIG. 4a




FIG. 4b




FIG. 4c




FIG. 4d




FIG. 5a




FIG. 5b

ELECTROPHYSIOLOGICAL MAPPING CATHETER

RELATED APPLICATIONS

[0001] This application claims priority and other benefits from U.S. Provisional Patent Application Ser. No. 62/414,183 entitled “Improved Electrophysiological Mapping Catheter” to Ruppertsberg filed Oct. 28, 2017 (hereafter “the ’183 patent application”). The entirety of the ’183 patent application is hereby incorporated by reference herein.

FIELD OF THE INVENTION

[0002] Various embodiments described and disclosed herein relate to the field of medicine generally, and more particularly to electrophysiological (EP) mapping catheters employed to diagnose and treat cardiac rhythm disorders in a patient’s heart.

BACKGROUND

[0003] Elongated medical devices suitable for intravascular insertion, such as catheters, especially ablation catheters, and guide wires for guiding catheters through vessels, organs or other body cavities are often employed in the treatment of atrial fibrillation (Afib). Atrial fibrillation is the most frequent arrhythmic disorder of the heart. Blood clotting occurring in the fibrillating atria is one main cause of stroke. Afib is also one of the most important disorders associated with a high risk of fatality. The cause of Afib has been subject to intensive scientific investigations and is largely understood. In most patients, the pulmonary veins draining into the left atrium are the sources of rapid arrhythmic action potentials which trigger circular excitation patterns (rotors) in the left atrium that induce a high frequency fibrillation through their re-entry mechanism. Those rotors have the character of small action potential cyclones of 2 to 3 cm² in size. The likelihood of occurrence of those rotors and the frequency of pathological action potential generation in the pulmonary veins increases with fibrotic structural changes and certain modifications of ion channel expression patterns in atrial cells with age.

[0004] The only potentially curative treatments for Afib are open heart surgery or cardiac ablation employing a catheter for those parts of the atrial wall tissue which originate, transmit or maintain the pathologic excitation circles.

[0005] Open heart surgery and catheter ablation are limited by potentially fatal and/or severe side effects associated with either procedure. When the integrity of the atrial wall is destroyed by excessive ablation, perforations of the atrial wall into the pericardium or fistulas into the esophagus can result in severe to deadly outcomes. The alteration of endocardial cells on the intra-cardiac surfaces can also initiate clotting in the treated atrium, which may lead to deadly strokes. That is why ablation procedures require the use of anticoagulation techniques. Last but not least, if the intensity of the ablation is kept too low to avoid the foregoing side effects, in many cases the therapeutic effect is insufficient and patients are often provided with success rates of only 50-70%.

[0006] To improve the situation, mapping catheters are often used first to identify circular excitation patterns (rotors) in the left atrium. After rotors have been identified, force sensing catheters are used that allow improved control

of cardiac ablation catheter positions and pressures, which permits the intensity of tissue ablation to be better modulated and controlled. Further, water irrigation is often employed to keep endothelial tissue free of lesions during the ablation procedure, and micro-calorimetric sensors may be employed to measure and control the amount of heat delivered to the tissue during the ablation procedure.

[0007] U.S. Pat. No. 8,364,234 discloses a system for sensing multiple local electric voltages from endocardial surface of a heart. The system includes a first elongate tubular member; a basket assembly having a plurality of flexible splines for guiding a plurality of exposed electrodes, the splines having proximal portions, distal portions and medial portions therein between; a proximal anchor for securely affixing the proximal portions of the splines; the proximal anchor being secured at the distal end of the first elongate tubular member; a distal tip consisting essentially of means for only securely affixing the distal portions of the splines wherein at least some of the splines in the radially expanded non-spherical shape contain a distal outward bend disposed at the distal portion of the spline at a location near to the distal tip of the basket assembly to bend the splines back towards the proximal anchor. A disadvantage of this type of mapping system is the low resolution sometimes provided by the mapping electrode array, as the splines upon which the electrodes are mounted or attached tend to bunch or cluster when the endocardial surface of the patient’s heart is contacted, thus reducing the area of the patient’s heart that is sensed, and the spatial resolution provided, by the electrodes.

[0008] Laughner et. al. in JACC, CLINICAL ELECTROPHYSIOLOGY, 2016; 2(1):55-65. doi: 10.1016, conclude that known mapping basket catheters (MBC’s) provide insufficient spatial resolution due to poor contact, demonstrate frequent bunching of basket splines, and possess inadequate electrode density to permit accurate detection of rotors near the equatorial electrodes of MBCs.

[0009] What is needed are improved means and methods of acquiring cardiac mapping data from inside a patient’s heart using a cardiac mapping catheter, where improved spatial resolution of the electrodes when they are in contact with the patient’s endocardium is provided.

SUMMARY

[0010] In one embodiment, there is provided a cardiac mapping catheter configured for electrophysiological mapping and suitable for intravascular insertion in a patient’s heart comprising a flexible elongated body having a distal portion with a distal end and a proximal portion and an electrode assembly located at the distal portion, the electrode assembly comprising a plurality x of at least 4 support arms, each support arm having a proximal end part, a distal end part, and a main part located between the proximal end part and the distal end part, each of the plurality of support arms comprising a plurality of electrodes, the electrodes being configured to acquire electrophysiological signals from the patient’s heart, the plurality of support arms being configured to have a first retracted condition where the plurality of support arms is arranged in a collapsed bundle, and a second expanded condition where the plurality of support arms forms an expanded basket structure, wherein the plurality of support arms further comprises first and second neighboring support arms, the proximal end parts of the first and second neighboring support arms being combined or held together

near or adjoining one another, the distal end part of the first support arm being combined or held together near or adjoining a distal end part of a neighboring support arm that is not the second support arm, the distal end part of the second support arm being combined or held together near or adjoining a distal end part of a neighboring support arm that is not the first support arm, each of the plurality of support arms in the electrode assembly being combined or held together at or near its distal end part with a neighboring support arm that is different from the neighboring support arm with which it is combined or held together at its proximal end part.

[0011] In another embodiment, there is provided a method of making a cardiac mapping catheter configured for electrophysiological mapping and suitable for intravascular insertion in a patient's heart, the method comprising forming a flexible elongated body having a distal portion with a distal end and a proximal portion, and forming an electrode assembly configured to be located at or near the distal portion, the electrode assembly comprising a plurality x of at least 4 support arms, each support arm having a proximal end part, a distal end part, and a main part located between the proximal end part and the distal end part, each of the plurality of support arms comprising a plurality of electrodes, the electrodes being configured to acquire electrophysiological signals from the patient's heart, the plurality of support arms being configured to have a first retracted condition where the plurality of support arms is arranged in a collapsed bundle, and a second expanded condition where the plurality of support arms forms an expanded basket structure, wherein the plurality of support arms further comprises first and second neighboring support arms, the proximal end parts of the first and second neighboring support arms being combined or held together near or adjoining one another, the distal end part of the first support arm being combined or held together near or adjoining a distal end part of a neighboring support arm that is not the second support arm, the distal end part of the second support arm being combined or held together near or adjoining a distal end part of a neighboring support arm that is not the first support arm, each of the plurality of support arms in the electrode assembly being combined or held together at or near its distal end part with a neighboring support arm that is different from the neighboring support arm with which it is combined or held together at its proximal end part.

[0012] In yet another embodiment, there is provided a cardiac mapping catheter configured for electrophysiological mapping and suitable for intravascular insertion in a patient's heart comprising a flexible elongated body having a distal portion with a distal end and a proximal portion and an electrode assembly located at the distal portion, the electrode assembly comprising a plurality x of at least 4 support arms, each support arm having a proximal end part, a distal end part, and a main part located between the proximal end part and the distal end part, each of the plurality of support arms comprising a plurality of electrodes, the electrodes being configured to acquire electrophysiological signals from the patient's heart, the plurality of support arms being configured to have a first retracted condition where the plurality of support arms is arranged in a collapsed bundle, and a second expanded condition where the plurality of support arms forms an expanded basket structure, wherein the plurality of support arms further comprises first and second neighboring support arms, the distal end parts of the first and second neighboring support

arms being combined or held together near or adjoining one another, the proximal end part of the first support arm being combined or held together near or adjoining a proximal end part of a neighboring support arm that is not the second support arm, the proximal end part of the second support arm being combined or held together near or adjoining a proximal end part of a neighboring support arm that is not the first support arm, each of the plurality of support arms in the electrode assembly being combined or held together at or near its proximal end part with a neighboring support arm that is different from the neighboring support arm with which it is combined or held together at its distal end part.

[0013] In still another embodiment, there is provided cardiac mapping catheter configured for electrophysiological mapping and suitable for intravascular insertion in a patient's heart comprising a flexible elongated body having a distal portion with a distal end and a proximal portion and an electrode assembly located at the distal portion, the electrode assembly comprising a plurality x of at least 4 support arms, each support arm having a proximal end part, a distal end part, and a main part located between the proximal end part and the distal end part, each of the plurality of support arms comprising a plurality of electrodes, the electrodes being configured to acquire electrophysiological signals from the patient's heart, the plurality of support arms being configured to have a first retracted condition where the plurality of support arms is arranged in a collapsed bundle, and a second expanded condition where the plurality of support arms forms an expanded basket structure, wherein the basket structure comprises two pole areas P1 and P2 that lie along a basket axis A, in the expanded condition each of the support arms spans a curve of about 180° between the two pole areas P1 and P2, an angle α defines a circumferential distance along a support arm from at least one of the poles P1 and P2 to a boundary between at least one of the proximal and distal end parts of the support arm and the central or main part of the support arm, the angle α ranges between about 5° and about 40° , and no electrodes are disposed along the circumferential distance or distances defined by the angle α .

[0014] In another embodiment, there is provided a cardiac mapping catheter configured for electrophysiological mapping and suitable for intravascular insertion in a patient's heart comprising a flexible elongated body having a distal portion with a distal end and a proximal portion and an electrode assembly located at the distal portion, the electrode assembly comprising a plurality x of at least 4 support arms, each support arm having a proximal end part, a distal end part, and a main part located between the proximal end part and the distal end part, each of the plurality of support arms comprising a plurality of electrodes, the electrodes being configured to acquire electrophysiological signals from the patient's heart, the plurality of support arms being configured to have a first retracted condition where the plurality of support arms is arranged in a collapsed bundle, and a second expanded condition where the plurality of support arms forms an expanded basket structure, wherein the proximal end part of each support arm is combined or held near or together with the proximal end part of a neighboring support arm, and the distal end part of each support member is combined or held near or together with the distal end part of a support arm that is not the neighboring support arm.

[0015] In yet another embodiment, there is provided a cardiac mapping catheter configured for electrophysiological

cal mapping and suitable for intravascular insertion in a patient's heart comprising a flexible elongated body having a distal portion with a distal end and a proximal portion and an electrode assembly located at the distal portion, the electrode assembly comprising a plurality x of at least 4 support arms, each support arm having a proximal end part, a distal end part, and a main part located between the proximal end part and the distal end part, each of the plurality of support arms comprising a plurality of electrodes, the electrodes being configured to acquire electrophysiological signals from the patient's heart, the plurality of support arms being configured to have a first retracted condition where the plurality of support arms is arranged in a collapsed bundle, and a second expanded condition where the plurality of support arms forms an expanded basket structure, wherein the distal end part of each support arm is combined or held near or together with the distal end part of a neighboring support arm, and the proximal end part of each support member is combined or held near or together with the proximal end part of a support arm that is not the neighboring support arm.

[0016] In still another embodiment, there is provided a cardiac mapping catheter configured for electrophysiological mapping and suitable for intravascular insertion in a patient's heart comprising a flexible elongated body having a distal portion with a distal end and a proximal portion, and an electrode assembly located at the distal portion, the electrode assembly comprising a plurality x of at least 4 support arms, each support arm having a proximal end part, a distal end part, and a main part located between the proximal end part and the distal end part, each of the plurality of support arms comprising a plurality of electrodes, the electrodes being configured to acquire electrophysiological signals from the patient's heart, the plurality of support arms being configured to have a first retracted condition where the plurality of support arms is arranged in a collapsed bundle, and a second expanded condition where the plurality of support arms forms an expanded basket structure, at least one of the distal end parts and the proximal end parts being combined or held together with combining means, wherein the support arms and combining means are together configured such that one support arm may be not be deflected or bent towards a neighboring support arm by an angle exceeding β when at least one of the arms is in contact with a surface, the angle β ranging between about 5° and about 30° .

[0017] Further embodiments are disclosed herein or will become apparent to those skilled in the art after having read and understood the claims, specification and drawings hereof.

BRIEF DESCRIPTION OF THE DRAWINGS

[0018] Different aspects of the various embodiments will become apparent from the following specification, drawings and claims in which:

[0019] FIG. 1a is a schematic view of a basket type electrophysiological mapping catheter according to the prior art with an electrode assembly comprising support arms, the electrode assembly being in an expanded condition with a part of the support arms touching a surface;

[0020] FIG. 2 is a schematic view of an electrophysiological mapping system comprising an elongated medical device for exploration or treatment of a vessel or organ or other body cavity, having an electrode assembly for electrophysi-

ological mapping of cardiac or vessel areas, the electrode assembly being in a first, retracted condition, and a data processing and control unit/and a data output unit;

[0021] FIG. 3a is a perspective view on a distal portion of the elongated medical device according to FIG. 2 in a second, expanded condition of the electrode assembly;

[0022] FIG. 3b is a perspective view on the distal portion of an elongated medical device in a further embodiment in the second, expanded condition of the electrode assembly;

[0023] FIG. 4a is an enlarged view of an area of the electrode assembly of the elongated medical device of FIG. 3a according to the marking IVa in FIG. 3a;

[0024] FIG. 4b is an enlarged view of an area of the electrode assembly of the elongated medical device of FIG. 3b according to the marking IVb in FIG. 3b;

[0025] FIG. 4c is an enlarged view of an area of an electrode assembly of a further embodiment of an elongated medical device;

[0026] FIG. 4d is an enlarged view of an area of an electrode assembly of a further embodiment of an elongated medical device;

[0027] FIG. 5a is an enlarged cut section through a pair of neighboring support arms according to the marking Va in FIG. 4a, and

[0028] FIG. 5b is an enlarged cut section through a pair of neighboring support arms analog to FIG. 5a according to a further embodiment of an elongated medical device.

[0029] The drawings are not necessarily to scale. Like numbers refer to like parts or steps throughout the drawings.

DETAILED DESCRIPTIONS OF SOME EMBODIMENTS

[0030] Described herein are various embodiments of a cardiac mapping catheter, and associated components, systems and methods of making and using same.

[0031] Systems and methods configured to detect in a patient's heart a location of a source of at least one cardiac rhythm disorder are disclosed herein. In the following description, for the purposes of explanation, numerous specific details are set forth in order to provide a thorough understanding of example embodiments or aspects. It will be evident, however, to one skilled in the art that an example embodiment may be practiced without necessarily using all of the disclosed specific details.

[0032] In one embodiment, an elongated medical device is provided that is suitable for intravascular insertion, such as a catheter for exploration or treatment of a vessel, organ or other body cavity which includes an electrode assembly for electrophysiological mapping of cardiac or vessel areas or the like medical apparatus. The electrode assembly may be used to map circular excitation patterns (rotors), e.g., of the left atrium of the heart.

[0033] Referring now to FIG. 1, there is illustrated a prior art elongated medical device 110 which is formed as a mapping catheter. The elongated medical device 110 comprises an elongated body 112, only a distal portion 113 of which is shown in FIG. 1. The elongated medical device 110/mapping catheter comprises a basket type electrode assembly 180 that is displayed in FIG. 1 in its expanded condition (EC). The electrode assembly 180 comprises eight support arms 181 that carry electrodes 182. In the example shown, there are eight electrodes 182 arranged on each of the eight support arms 181. A tip 116 is disposed at a distal end 114 of the distal portion 113 of the elongated medical

device **110**. FIG. 1 depicts the situation where the basket type electrode assembly **180** with its support arms **181** touches a surface S, e.g., an organ or body surface such as a patient's endocardium. As can be seen, the support arms **181** in contact with surface S bunch or accumulate on the surface S, and form a cluster **190** such that the 24 electrodes of the affected three support arms **181** effectively act, by way of example, as only 8 electrodes, as in the example of FIG. 1 the 24 electrodes of the three support arms are bunched together to form eight clusters, each cluster having three electrodes associated therewith. Due to such clustering, the spatial resolution of the electrodes is reduced significantly.

[0034] Referring to FIGS. 2, 3a, 4a and 5a, there is shown an elongated medical device **1** formed as mapping catheter. The elongated medical device **1** comprises an elongated body **2**, comprising a distal portion **3** and a proximal portion **5**. At the distal portion **3** of the elongated medical device **1**, a tip **6** is arranged at the distal end **4** of the device as shown in FIG. 3a. The elongated medical device **1** further comprises an electrode assembly **80**/mapping electrode assembly **80** that is located at the distal portion **3** and comprises in the embodiment of FIGS. 2 and 3a a plurality x of eight support arms **81** (or splines), where at least four ($x=4$) of such support arms **81** are provided. Each support arm **81** has a proximal end part **81a**, a distal end part **81b** and a main part **81c** located between the proximal end part **81a** and the distal end part **81b**. The eight support arms **81** are connected to the tip **6** at their respective distal end parts **81b**. Note that even and odd numbers of support arms **81** are contemplated, such as by way of non-limiting example 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15 and 16 support arms **81**.

[0035] The central part **81c** of each support arm **81** carries a plurality of electrodes **82** (also referred to as mapping electrodes), which according to one embodiment may comprise gold or gold plating for enhanced electro-conductivity; other suitable electrically conductive and biocompatible metals and metal alloys for the electrodes are also contemplated, such as platinum, titanium, niobium, tantalum, and/or alloys or mixtures thereof. In one embodiment ten electrodes **82** are disposed on each support arm. In some embodiments, and by way of non-limiting example, the surface area an electrode **82** may range between about 0.01 mm² and about 0.25 mm².

[0036] A basket structure electrode assembly **80** may be formed using conventional wire, braided twisted or stranded electrical conductors and conventional electrodes. Common techniques for operably connecting metal electrodes to their corresponding wire electrical conductors in medical electrical leads include welding, swaging crimping and staking. Likewise, the flexible elongated body **2** of the catheter **1** may comprise a polymeric coating or material such as silicone, polyurethane or any other suitable polymeric material. Indeed, in one embodiment catheter **1** is formed and manufactured using largely conventional manufacturing methods and materials, where lead body **2** is formed using well-known biocompatible polymeric materials that sheath or overlie internally disposed flexible electrical conductors (e.g., braided, stranded, and/or twisted wires) that are electrically connected at their distal ends to the electrodes disposed on the support arms, and the support arms themselves are formed from similar or the same biocompatible polymeric materials, flexible electrical conductors, and metal or metal alloy electrodes.

[0037] At the proximal end of the elongated medical device **1**, a handle **7** or other manipulable control device may be attached to the proximal portion **5**. The handle **7** may be used to manually control expansion or retraction of the electrode assembly **80** using, by way of non-limiting example, an internal pull wire operably connected to a proximal end of the support arms. When the internal pull wire is pushed in a distal direction, the support arms assume an expanded condition to form the basket structure. When the internal pull wire is pulled in a proximal direction, the support arms assume a retracted condition inside the catheter body **2**.

[0038] The electrode assembly **80** in FIG. 2 is shown in its first condition UC (unexpanded condition), where the electrode assembly **80** is stored internally in space **8** within the tubular elongated body **2** of the elongated medical device **1**. In this stored position the plurality of at least $x=4$ support arms **81** forms a dense collapsed bundle. In the first condition UC the elongated medical device **1**/catheter may be introduced into a vessel, organ or other body cavity by, for example, intravascular means.

[0039] In FIG. 3a the electrode assembly **80** is in its second condition EC (expanded condition) in which the support arms **81** project away from the elongated body **2** to form a basket type structure **83**. In this second expanded condition EC the device is deployed to collect electrophysiological data, i.e., for electrophysiological mapping.

[0040] As can be seen in FIG. 3a, the basket structure **83** with the support arms **81** has two pole areas P1, P2, which define a basket axis A. Between the two poles or pole areas P1, P2 each of the support arms **81** spans a curve or bow of about 180°. As shown in FIG. 3a, and in one embodiment, an angle α defines a circumferential distance along two support arms that have been combined or held together between axis A and the combining means **90** associated with the two such support arms. According to the embodiment that is employed, the angle α is not limited to circumferential distances defined by basket axis A and combining means **90**, however, and can extend beyond combining means **90** or terminate prior to reaching combining means **90**. In some embodiments, the circumferential distance defined by angle α delineates or approximately delineates the border or boundary between the respective proximal end parts **81a**/distal end parts **81b** and the central or main parts **81c** disposed along the curve or bow defined by the pertinent support arms **81**. In some embodiments, the angle α ranges between about 5° and about 40°, between about 5° and about 30°, between about 5° and about 25°, between about 5° and about 20°, between about 5° and about 15°, and between about 5° and about 10°. In the embodiment of FIG. 3a, angle α is about 15°.

[0041] It should be mentioned that the number of electrodes on the support arm may be varied such that in a pair of neighboring support arms one support arm carries more electrodes than the other one. For example, one support arm may carry twelve electrodes while a neighboring support arm carries eight electrodes. With such varying numbers of electrodes, the number of electrodes in the equator area or central portion of the basket structure can be enhanced, while the number of electrodes towards the "poles" (which often produce the least useful information) may be reduced.

[0042] For example, when the electrodes **82** are disposed in the central or main part **81c** of each support arm and not in the proximal end part **81a** and/or the distal end part **81b** of

such support arm, and in the case where the angle α delineates or approximately delineates the border or boundary between such proximal end part **81a**, distal end part **81b**, and the central or main part **81c**, electrodes **82** can be configured such that they are disposed along such proximal end part **81a** or distal end part **81b**, and the angle α can be employed to define where electrodes are not to be found on the support arms. In such a case, the greater the angle α , the greater the circumferential distance to poles P1 or P2 from the nearest electrode **82**. Such an electrode configuration can result in enhanced sensing and spatial resolution since electrodes are not being “wasted” due to their undesired proximity to the poles P1 and P2.

[0043] Referring to FIGS. **3a**, **4a** and **5a**, the plurality x of eight support arms **81** is shown to comprise pairs of neighboring support arms **81.1**, **81.2**. In one embodiment, all first and second neighboring support arms **81.1**, **81.2** are combined by combining means **90** at their proximal end parts **81a** to form united end parts **88a**, so that all pairs of neighboring support arms **81.1**, **81.2** are united at their proximal end parts **81a**.

[0044] Further, and in one embodiment, all second and first neighboring support arms **81.2**, **81.1** are combined by combining means **90** at their distal end parts **81b**, to form united end parts **88b**, such that all pairs of neighboring support arms **81.2**, **81.1** are united at their distal end parts **81b**. As shown in FIG. **3a**, each support arm **81** is combined at its distal end part **81b** with a neighboring support arm **81** that is different from the neighboring support arm to which it is combined or attached at its proximal end part **81a**, which forms a mechanically stabilized framework that is configured to prevent or impede the undesired clustering of electrodes in only a few locations along the patient’s endocardial wall or surface. Instead, the stabilized framework of support arms results in electrodes being much more evenly and regularly spaced and positioned along the patient’s endocardial wall or surface during an EP mapping procedure.

[0045] As shown in the Figures, a modification in combining neighboring support arms **81.1**, **81.2** may be employed, which besides forming united end parts **88a**, **88b**, further stabilizes the basket structure **83** of the electrode assembly **80**. As a result, and in one embodiment, the central part **81c** of an individual support arm **81** has a limited maximum angle β under which it may be deflected or bent towards a neighboring support arm when touching a surface. In one embodiment, this result is achieved at least in part by appropriate configuration of combining means **90** with respect to the two support arms **81** to which combining means **90** is attached. That is, combining means **90** located at one or both ends of a given support arm **81** are configured to constrain the lateral movement of one support arm towards or in the direction of an adjoining or neighboring support arm. In one embodiment, the maximum angle β of deflection is approximately $\pm(360^\circ/2x)$, with x being the number of support arms **81**. In another embodiment, this maximum possible angle β of deflection/freedom to be bent is less than $\pm((360^\circ/x)-(360^\circ/10))$, with x being the number of support arms **81**. Many values for angle β are contemplated, such as angle β being about 5° , about 10° , about 15° , about 20° , about 22.5° , about 25° , about 30° , and/or about 35° . Ranges of angle β are also contemplated, such as between about 5° and about 35° , between about 5° and about 30° , between about 10° and about 30° , and between about

10° and about 25° , and between about 10° and about 20° . Other ranges and values of angle β are also contemplated. As a further result, in use of the medical device, the resulting electrode distribution of the basket structure **83** when in contact with surface **S** is more uniform than in the prior art (where support arms tend to bunch or cluster together). In one embodiment, united end portions **88a**, **88b** may be formed in basket-type electrode assemblies **80** having an even number (number divisible by 2) of support arms **81**.

[0046] The combining means **90** are preferably arranged on the border between the respective proximal end parts **81a**/distal end parts **81b** and the central parts **81c**. In case of an adhesive or welded combining means **90**, the combining means **90** may extend between this border and the pole area along a part of the length of the neighboring proximal and/or distal end parts **81a**, **81b** of the support arms **81** or over the entire length of the neighboring proximal and/or distal end parts **81a**, **81b**.

[0047] In the embodiment of FIGS. **3a**, **4a**, **5a** the combining means **90** are formed as clamping elements or clamps **91**. By means of the clamping elements **91** the distal end parts **81b** and the proximal end parts **81a** of neighboring support arms **81.1**, **81.2** are clamped together in tight fit. Such clamps or clamping elements **91** may easily be applied to a basket type catheter even after the electrode assembly **80** has been mounted at the elongated medical device **1**. A retrofitting of basket type catheters with combining means **90** is accordingly possible and such retrofitted catheters are also within the scope of what is described and disclosed herein.

[0048] Some embodiments of alternative combining means **91** are displayed in FIGS. **4d** and **5b**. Many other types of combining structures and/or means are contemplated, however, including one or more polymeric layers, covers, sheaths, overmoldings, tubing, shrink tubing, clamps, ring members, rings, adhesives, lugs, welds, stakes, crimps, other suitable means or structures, or any combination or plurality thereof.

[0049] In the embodiment shown in FIG. **4d**, the distal end parts **81b** of neighboring support arms **81.1**, **81.2** and the proximal end parts **81a** of neighboring support arms **81.1**, **81.2** are combined to form united end parts **88a**, **88b** by means of a joint **93** formed using an adhesive. The adhesive of joint **93** may be applied to portions or over almost the entire length of the united end parts **88a**, **88b**. Alternatively, a welded joint or welded connection may also be used to form joint **93**.

[0050] In the embodiment shown in FIG. **5b**, the distal end parts **81b** of neighboring support arms **81.1**, **81.2** and the proximal end parts **81a** of neighboring support arms **81.1**, **81.2** are combined to united end parts **88a**, **88b** by means of ring members or rings **92** instead of clamping elements. Clamping means of different types may also be used in combination.

[0051] Further, instead of ring member **92**, a tube or shrink tube (not shown in the Figures), e.g., made of a polymeric material, may be used which may encompass or extend over the united proximal and distal end parts **81a**, **81b** over a part of their length or over their entire length and combine them to form the united end parts **88a**, **88b**.

[0052] Combining means **90**, especially in embodiments where clamps or clamping elements **91** or ring members **92** are used, may also function as mapping electrodes. The combining means **90**, formed of an electrically conductive

metal, is electrically connected to electrical conductors or lines disposed in or on the support arms **81**. The number of mapping electrodes may accordingly be augmented or enhanced.

[0053] Referring again to FIG. **4a**, in one embodiment each of support arms **81** comprises a strand **86** formed of a shape memory metal and a PCB (printed circuit board) layer **85**, where the PCB layers **85** carry the electrodes **82** and electrical conductors (not visible in the Figures) for operative connection to electrodes **82**. The PCB layers **85** at least partially surround the strands **86**, which in one embodiment may be formed as Nitinol wires of 0.1-0.3 mm diameter, preferentially 0.2 mm diameter. Other suitable metals or metal alloys may also be employed to form such strands, wires or electrical conductors.

[0054] Referring again to FIGS. **2** and **3a**, the electrode assembly **80** is connected via connection **12** with a data processing and control unit **15**, which energizes and controls the electrodes **82**. Data processing and control unit **15** processes electrode mapping data from the electrode assembly **80** and outputs mapping data on a data output screen **14** of a data output unit **16**. Connection **12** may be a cable, ribbon cable, flat conductor, flat flexible cable or any other suitable electrical connection. At the end of connection or line **12** there are connectors **13** located for connecting the elongated medical device **1** and its electrode assembly **80** and associated electronics to the data processing and control unit **15**.

[0055] In one embodiment, the data processing and control unit **15** may comprise a suitably programmed and configured computing device such as a personal computer. Elongated medical device **1** may form a portion of a catheter system interfaced to a computing device. In respect to the electrophysiological mapping data, in one embodiment the data processing and control unit **15** is configured to process analog and/or digitized electrode measurement data and to output data for visualizing circular excitation pattern (rotors), e.g., in the left atrium of a patient's heart on a data output screen **14** of a data output unit **16**.

[0056] In operation of the medical device **1**, the medical device **1** or catheter is inserted in the patient's vessel, organ or other body cavity until it reaches the target area, which in one example is the left atrium of a patient's heart, or any other portion of the heart. Upon arrival in the target area the operator may expand the electrode assembly **80** by manipulating the handle **7**. In this expanded condition EC of the electrode assembly **80** and its support arms **81** the medical device **1** will be pushed with its distal end **4** against body tissue and electrophysiological mapping may be initiated automatically or by the health care provider. Data analysis of electrophysiological data, such as action potential data, is performed on the data processing and control unit **15** respectively on a suitably programmed computing device.

[0057] FIGS. **3b** and **4b** display a further embodiment of the elongated medical device **11**. For reference numerals and functions not described in the following text, reference is made to the descriptions of FIGS. **2**, **3a**, **4a** and **5a**. Similar parts are indicated with similar reference numerals. The embodiments shown in FIGS. **3b** and **4b** differ from those described with respect to FIGS. **2**, **3a**, **4a** and **5a** in that the combining means **90** are realized in the form of a flexible electrical polymeric substrate or sheet **94** disposed at the united end parts **88a**, **88b** of the neighboring support arms **81.1**, **81.2**. Flexible electrical polymeric substrate or sheet

94 comprises electrical conductors, which in one embodiment are made using thin film electrical conductor deposition techniques. In some embodiments, the thin film electrical conductors and their corresponding electrodes may be formed or deposited on a material chosen from the group of Mylar, Kevlar, polyimide, PEEK, an electrically conductive polyester, or other suitable flexible biocompatible materials. Flexible electrical polymeric substrate or sheet **94** may also, e.g., be formed as a PCB layer or an electro-ceramic layer. Further, and in the embodiments shown in FIGS. **3b** and **4b**, two electrodes **82** are disposed on each united end part **88a**, **88b** of the support arms **81**, while four electrodes **82** are located on each central part **81c** of the support arms **81**.

[0058] The angle α defining the circumferential distance between the respective pole P1 or P2 and the border between the respective proximal end parts **81a**/distal end parts **81b** and the central parts **81c** on this curve or bow is about 40° in this embodiment. Accordingly, a split point **87** (indicated in FIG. **4b**) which lies in the border between the respective proximal end parts **81a**/distal end parts **81b** and the central parts **81c** is in the same circumferential distance as defined by angle α of about 40°.

[0059] FIG. **4c** displays a further embodiment of the elongated medical device similar to the embodiment of FIGS. **3b** and **4b**, but with modified support arms **81**. For reference numerals and functions not described in the following text, reference is made to the descriptions of FIGS. **2**, **3a**, **3b**, **4a**, **4b** and **5a**. Similar parts are indicated with similar reference numerals. The embodiment of FIG. **4c** differs from that of FIGS. **3b** and **4b** in that there is only one shape memory strand **86** in the united end parts **88a**, **88b**, whereas there are two strands **86** in the embodiment of FIGS. **3b** and **4b**.

[0060] At the split point **87**, the single strand **86** splits into two strands **86**, one in each neighboring support arm **81.1**, **81.2**. Single strand **86** may be welded in split point **87** with the two strands **86** of the neighboring support arms **81.1**, **81.2**.

[0061] Note that the various embodiments include those described above in the Summary, where, for example: (a) the attachment of distal and proximal end parts in neighboring support arms is reversed; (b) one end of a support arm need not be attached to a neighboring support arm (but only to a support arm that is not the same as that to which the support arm is attached or combined at another end); (c) where the angle α along a support arm is constrained between certain angular limits and no electrodes are disposed on a support arm within the range of angle α , and (d) where the maximum angle β over which one support arm may be deflected towards a neighboring support arm when at least one of the arms is in contact with a surface such as a patient's endocardium is constrained within certain angular limits.

[0062] The various systems, devices, components and methods described and disclosed herein may also be adapted and configured for use in electrophysiological mapping applications other than those involving the interior of a patient's heart. These alternative applications include EP mapping and diagnosis of a patient's epicardium, a patient's spinal cord or other nerves, or a patient's brain or portions thereof.

[0063] In addition, the cardiac mapping catheter described and disclosed herein may be modified to include a cardiac ablation device at or near distal end **114** or tip **116**. Such ablation devices may include, but are not limited to RF,

cryogenic, and radioactive ablation devices. The cardiac mapping catheter may also include a force sensor, temperature sensor and/or irrigation device disposed near or at its tip 116. Moreover, the various embodiments described and disclosed herein include methods of making and using same, as described, for example, in the Summary above.

[0064] Additional embodiments can include the following elements and features:

Embodiment A

[0065] A cardiac mapping catheter configured for electrophysiological mapping and suitable for intravascular insertion in a patient's heart, comprising a flexible elongated body having a distal portion with a distal end and a proximal portion, and an electrode assembly located at the distal portion, the electrode assembly comprising a plurality x of at least 4 support arms, each support arm having a proximal end part, a distal end part, and a main part located between the proximal end part and the distal end part, each of the plurality of support arms comprising a plurality of electrodes, the electrodes being configured to acquire electrophysiological signals from the patient's heart, the plurality of support arms being configured to have a first retracted condition where the plurality of support arms is arranged in a collapsed bundle, and a second expanded condition where the plurality of support arms forms an expanded basket structure, wherein the plurality of support arms further comprises first and second neighboring support arms, the proximal end parts of the first and second neighboring support arms being combined or held together near or adjoining one another, the distal end part of the first support arm being combined or held together near or adjoining a distal end part of a neighboring support arm that is not the second support arm, the distal end part of the second support arm being combined or held together near or adjoining a distal end part of a neighboring support arm that is not the first support arm, each of the plurality of support arms in the electrode assembly being combined or held together at or near its distal end part with a neighboring support arm that is different from the neighboring support arm with which it is combined or held together at its proximal end part.

[0066] Embodiment A, and other embodiments, may include one or more of the following elements or features: x is evenly divisible by the number 2; at least one of the distal end parts and the proximal end parts are combined or held together with combining means; the support arms and combining means are together configured such that one support arm cannot be deflected or bent towards a neighboring support arm by an angle exceeding β when at least one of the arms is in contact with a surface, the angle β ranging between about 5° and about 30° ; the combining means comprises one or more of a polymeric layer, a cover, a sheath, overmolding, tubing, shrink tubing, a clamp, a ring member, an adhesive joint, a lug, a weld, a stake, a crimp, or any combination of the foregoing; at least some of the combining means comprise an electrically conductive metal or metal alloy forming one or more electrodes, and such electrodes are electrically connected to electrical conductors disposed in one or more of the support arms; at least one of the support arms comprises a flexible electrical polymeric sheet comprising electrodes; the number x of support arms equals 4, 6, 8, 10 or 12; the number of electrodes disposed on each support arm ranges between 4 electrodes and 24 electrodes; the plurality of electrodes disposed on each

support arm is distributed spatially substantially evenly thereon; the basket structure comprises two pole areas P1 and P2 that lie along a basket axis A; in the expanded condition each of the support arms spans a curve of about 180° between the two pole areas P1 and P2; an angle α defines a circumferential distance along a support arm from at least one of the poles P1 and P2 to a boundary between at least one of the proximal and distal end parts of the support arm and the central or main part of the support arm, the angle α ranges between about 5° and about 40° , and no electrodes are disposed along the circumferential distance or distances defined by the angle α ; the angle α ranges between about 5° and about 30° ; the angle α ranges between about 10° and about 25° ; and braided, twisted or stranded electrical conductors operatively connected to the electrodes; at least portions of the flexible elongated body comprise an electrically insulative polymeric material.

Embodiment B

[0067] A method of making a cardiac mapping catheter configured for electrophysiological mapping and suitable for intravascular insertion in a patient's heart, the method comprising forming a flexible elongated body having a distal portion with a distal end and a proximal portion, and forming an electrode assembly configured to be located at or near the distal portion, the electrode assembly comprising a plurality x of at least 4 support arms, each support arm having a proximal end part, a distal end part, and a main part located between the proximal end part and the distal end part, each of the plurality of support arms comprising a plurality of electrodes, the electrodes being configured to acquire electrophysiological signals from the patient's heart, the plurality of support arms being configured to have a first retracted condition where the plurality of support arms is arranged in a collapsed bundle, and a second expanded condition where the plurality of support arms forms an expanded basket structure; wherein the plurality of support arms further comprises first and second neighboring support arms, the proximal end parts of the first and second neighboring support arms being combined or held together near or adjoining one another, the distal end part of the first support arm being combined or held together near or adjoining a distal end part of a neighboring support arm that is not the second support arm, the distal end part of the second support arm being combined or held together near or adjoining a distal end part of a neighboring support arm that is not the first support arm, each of the plurality of support arms in the electrode assembly being combined or held together at or near its distal end part with a neighboring support arm that is different from the neighboring support arm with which it is combined or held together at its proximal end part.

[0068] Embodiment B, and other embodiments, may include one or more of the following elements, features or steps: x is evenly divisible by the number 2; combining or holding together the distal end parts or proximal end parts with combining means; one or more of a polymeric layer, a cover, a sheath, overmolding, tubing, shrink tubing, a clamp, a ring member, an adhesive joint, a lug, a weld, a stake, a crimp, or any combination of the foregoing; the support arms are formed using a flexible electrical polymeric sheet; an angle α defines a circumferential distance along a support arm from at least one of the poles P1 and P2 to a boundary between at least one of the proximal and distal end parts of the support arm and the central or main part of the support

arm, the angle α ranges between about 5° and about 40°, and no electrodes are disposed along the circumferential distance or distances defined by the angle α ; the angle α ranges between about 5° and about 30°; the angle α ranges between about 10° and about 25°; operatively connecting braided, twisted or stranded electrical conductors to the electrodes; and forming at least portions of the flexible elongated body with an electrically insulative polymeric material.

Embodiment C

[0069] A cardiac mapping catheter configured for electrophysiological mapping and suitable for intravascular insertion in a patient's heart, comprising a flexible elongated body having a distal portion with a distal end and a proximal portion, and an electrode assembly located at the distal portion, the electrode assembly comprising a plurality x of at least 4 support arms, each support arm having a proximal end part, a distal end part, and a main part located between the proximal end part and the distal end part, each of the plurality of support arms comprising a plurality of electrodes, the electrodes being configured to acquire electrophysiological signals from the patient's heart, the plurality of support arms being configured to have a first retracted condition where the plurality of support arms is arranged in a collapsed bundle, and a second expanded condition where the plurality of support arms forms an expanded basket structure, wherein the plurality of support arms further comprises first and second neighboring support arms, the distal end parts of the first and second neighboring support arms being combined or held together near or adjoining one another, the proximal end part of the first support arm being combined or held together near or adjoining a proximal end part of a neighboring support arm that is not the second support arm, the proximal end part of the second support arm being combined or held together near or adjoining a proximal end part of a neighboring support arm that is not the first support arm, each of the plurality of support arms in the electrode assembly being combined or held together at or near its proximal end part with a neighboring support arm that is different from the neighboring support arm with which it is combined or held together at its distal end part.

[0070] Embodiment C, and other embodiments, may include one or more of the following elements or features: x is evenly divisible by the number 2.

Embodiment D

[0071] A cardiac mapping catheter configured for electrophysiological mapping and suitable for intravascular insertion in a patient's heart, comprising a flexible elongated body having a distal portion with a distal end and a proximal portion, and an electrode assembly located at the distal portion, the electrode assembly comprising a plurality x of at least 4 support arms, each support arm having a proximal end part, a distal end part, and a main part located between the proximal end part and the distal end part, each of the plurality of support arms comprising a plurality of electrodes, the electrodes being configured to acquire electrophysiological signals from the patient's heart, the plurality of support arms being configured to have a first retracted condition where the plurality of support arms is arranged in a collapsed bundle, and a second expanded condition where the plurality of support arms forms an expanded basket structure; wherein the basket structure comprises two pole

areas P1 and P2 that lie along a basket axis A, in the expanded condition each of the support arms spans a curve of about 180° between the two pole areas P1 and P2, an angle α defines a circumferential distance along a support arm from at least one of the poles P1 and P2 to a boundary between at least one of the proximal and distal end parts of the support arm and the central or main part of the support arm, the angle α ranges between about 5° and about 40°, and no electrodes are disposed along the circumferential distance or distances defined by the angle α .

Embodiment E

[0072] A cardiac mapping catheter configured for electrophysiological mapping and suitable for intravascular insertion in a patient's heart, comprising a flexible elongated body having a distal portion with a distal end and a proximal portion, and an electrode assembly located at the distal portion, the electrode assembly comprising a plurality x of at least 4 support arms, each support arm having a proximal end part, a distal end part, and a main part located between the proximal end part and the distal end part, each of the plurality of support arms comprising a plurality of electrodes, the electrodes being configured to acquire electrophysiological signals from the patient's heart, the plurality of support arms being configured to have a first retracted condition where the plurality of support arms is arranged in a collapsed bundle, and a second expanded condition where the plurality of support arms forms an expanded basket structure; wherein the proximal end part of each support arm is combined or held near or together with the proximal end part of a neighboring support arm, and the distal end part of each support member is combined or held near or together with the distal end part of a support arm that is not the neighboring support arm.

Embodiment F

[0073] A cardiac mapping catheter configured for electrophysiological mapping and suitable for intravascular insertion in a patient's heart, comprising a flexible elongated body having a distal portion with a distal end and a proximal portion, and an electrode assembly located at the distal portion, the electrode assembly comprising a plurality x of at least 4 support arms, each support arm having a proximal end part, a distal end part, and a main part located between the proximal end part and the distal end part, each of the plurality of support arms comprising a plurality of electrodes, the electrodes being configured to acquire electrophysiological signals from the patient's heart, the plurality of support arms being configured to have a first retracted condition where the plurality of support arms is arranged in a collapsed bundle, and a second expanded condition where the plurality of support arms forms an expanded basket structure; wherein the distal end part of each support arm is combined or held near or together with the distal end part of a neighboring support arm, and the proximal end part of each support member is combined or held near or together with the proximal end part of a support arm that is not the neighboring support arm.

Embodiment G

[0074] A cardiac mapping catheter configured for electrophysiological mapping and suitable for intravascular insertion in a patient's heart, comprising a flexible elongated

body having a distal portion with a distal end and a proximal portion, and an electrode assembly located at the distal portion, the electrode assembly comprising a plurality x of at least 4 support arms, each support arm having a proximal end part, a distal end part, and a main part located between the proximal end part and the distal end part, each of the plurality of support arms comprising a plurality of electrodes, the electrodes being configured to acquire electrophysiological signals from the patient's heart, the plurality of support arms being configured to have a first retracted condition where the plurality of support arms is arranged in a collapsed bundle, and a second expanded condition where the plurality of support arms forms an expanded basket structure, at least one of the distal end parts and the proximal end parts being combined or held together with combining means, wherein the support arms and combining means are together configured such that one support arm may be not be deflected or bent towards a neighboring support arm by an angle exceeding β when at least one of the arms is in contact with a surface, the angle β ranging between about 5° and about 30° .

[0075] What have been described above are examples and embodiments of the devices and methods described and disclosed herein. It is, of course, not possible to describe every conceivable combination of components or methodologies for purposes of describing the invention, but one of ordinary skill in the art will recognize that many further combinations and permutations of the devices and methods described and disclosed herein are contemplated and possible. Accordingly, the devices and methods described and disclosed herein are intended to embrace all such alterations, modifications and variations that fall within the scope of the appended claims. In the claims, unless otherwise indicated, the article "a" is to refer to "one or more than one."

[0076] The foregoing outlines features of several embodiments so that those skilled in the art may better understand the detailed description set forth herein. Those skilled in the art will now understand that many different permutations, combinations and variations of hearing aid 10 fall within the scope of the various embodiments. Those skilled in the art should appreciate that they may readily use the present disclosure as a basis for designing or modifying other processes and structures for carrying out the same purposes and/or achieving the same advantages of the embodiments introduced herein. Those skilled in the art should also realize that such equivalent constructions do not depart from the spirit and scope of the present disclosure, and that they may make various changes, substitutions and alterations herein without departing from the spirit and scope of the present disclosure.

[0077] After having read and understood the present specification, those skilled in the art will now understand and appreciate that the various embodiments described herein provide solutions to long-standing problems, both in the use of electrophysiological mapping systems and in the use of cardiac ablation systems.

I claim:

1. A cardiac mapping catheter configured for electrophysiological mapping and suitable for intravascular insertion in a patient's heart, comprising:

- a flexible elongated body having a distal portion with a distal end and a proximal portion, and
- an electrode assembly located at the distal portion, the electrode assembly comprising a plurality x of at least

4 support arms, each support arm having a proximal end part, a distal end part, and a main part located between the proximal end part and the distal end part, each of the plurality of support arms comprising a plurality of electrodes, the electrodes being configured to acquire electrophysiological signals from the patient's heart, the plurality of support arms being configured to have a first retracted condition where the plurality of support arms is arranged in a collapsed bundle, and a second expanded condition where the plurality of support arms forms an expanded basket structure;

wherein the plurality of support arms further comprises first and second neighboring support arms, the proximal end parts of the first and second neighboring support arms being combined or held together near or adjoining one another, the distal end part of the first support arm being combined or held together near or adjoining a distal end part of a neighboring support arm that is not the second support arm, the distal end part of the second support arm being combined or held together near or adjoining a distal end part of a neighboring support arm that is not the first support arm, each of the plurality of support arms in the electrode assembly being combined or held together at or near its distal end part with a neighboring support arm that is different from the neighboring support arm with which it is combined or held together at its proximal end part.

2. The cardiac mapping electrode of claim 1, wherein x is evenly divisible by the number 2.

3. The cardiac mapping catheter of claim 1, wherein at least one of the distal end parts and the proximal end parts are combined or held together with combining means.

4. The cardiac mapping catheter of claim 3, wherein the support arms and combining means are together configured such that one support arm cannot be deflected or bent towards a neighboring support arm by an angle exceeding β when at least one of the arms is in contact with a surface, the angle β ranging between about 5° and about 30° .

5. The cardiac mapping catheter of claim 3, wherein the combining means comprises one or more of a polymeric layer, a cover, a sheath, overmolding, tubing, shrink tubing, a clamp, a ring member, an adhesive joint, a lug, a weld, a stake, a crimp, or any combination of the foregoing.

6. The cardiac mapping catheter of claim 3, wherein at least some of the combining means comprise an electrically conductive metal or metal alloy forming one or more electrodes, and such electrodes are electrically connected to electrical conductors disposed in one or more of the support arms.

7. The cardiac mapping catheter of claim 1, wherein at least one of the support arms comprises a flexible electrical polymeric sheet comprising electrodes.

8. The cardiac mapping catheter of claim 1, wherein the number x of support arms equals 4, 6, 8, 10 or 12.

9. The cardiac mapping catheter of claim 1, wherein the number of electrodes disposed on each support arm ranges between 4 electrodes and 24 electrodes.

10. The cardiac mapping catheter of claim 1, wherein the plurality of electrodes disposed on each support arm is distributed spatially substantially evenly thereon.

11. The cardiac mapping catheter of claim 1, wherein the basket structure comprises two pole areas P1 and P2 that lie along a basket axis A.

12. The cardiac mapping catheter of claim 11, wherein in the expanded condition each of the support arms spans a curve of about 180° between the two pole areas P1 and P2.

13. The cardiac mapping catheter of claim 11, wherein an angle α defines a circumferential distance along a support arm from at least one of the poles P1 and P2 to a boundary between at least one of the proximal and distal end parts of the support arm and the central or main part of the support arm, the angle α ranges between about 5° and about 40°, and no electrodes are disposed along the circumferential distance or distances defined by the angle α .

14. The cardiac mapping catheter of claim 13, wherein the angle α ranges between about 5° and about 30°.

15. The cardiac mapping catheter of claim 13, wherein the angle α ranges between about 10° and about 25°.

16. The cardiac mapping catheter of claim 1, further comprising braided, twisted or stranded electrical conductors operatively connected to the electrodes.

17. The cardiac mapping catheter of claim 1, wherein at least portions of the flexible elongated body comprise an electrically insulative polymeric material.

18. A method of making a cardiac mapping catheter configured for electrophysiological mapping and suitable for intravascular insertion in a patient's heart, the method comprising:

- forming a flexible elongated body having a distal portion with a distal end and a proximal portion, and
- forming an electrode assembly configured to be located at or near the distal portion, the electrode assembly comprising a plurality x of at least 4 support arms, each support arm having a proximal end part, a distal end part, and a main part located between the proximal end

part and the distal end part, each of the plurality of support arms comprising a plurality of electrodes, the electrodes being configured to acquire electrophysiological signals from the patient's heart, the plurality of support arms being configured to have a first retracted condition where the plurality of support arms is arranged in a collapsed bundle, and a second expanded condition where the plurality of support arms forms an expanded basket structure;

wherein the plurality of support arms further comprises first and second neighboring support arms, the proximal end parts of the first and second neighboring support arms being combined or held together near or adjoining one another, the distal end part of the first support arm being combined or held together near or adjoining a distal end part of a neighboring support arm that is not the second support arm, the distal end part of the second support arm being combined or held together near or adjoining a distal end part of a neighboring support arm that is not the first support arm, each of the plurality of support arms in the electrode assembly being combined or held together at or near its distal end part with a neighboring support arm that is different from the neighboring support arm with which it is combined or held together at its proximal end part.

19. The method of claim 18, wherein x is evenly divisible by the number 2.

20. The method of claim 18, further comprising combining or holding together the distal end parts or proximal end parts with combining means.

* * * * *

专利名称(译)	电生理测绘导管		
公开(公告)号	US20180116595A1	公开(公告)日	2018-05-03
申请号	US15/793594	申请日	2017-10-25
[标]申请(专利权)人(译)	ablaacon公司		
申请(专利权)人(译)	ablaacon Inc.		
当前申请(专利权)人(译)	ablaacon公司		
[标]发明人	RUPPERSBERG PETER		
发明人	RUPPERSBERG, PETER		
IPC分类号	A61B5/00 A61B5/042		
CPC分类号	A61B5/6858 A61B5/0422 A61B2562/0209 A61B2562/046 A61B2562/125 A61B2562/164		
优先权	62/414183 2016-10-28 US		
外部链接	Espacenet USPTO		

摘要(译)

公开了配置用于电生理 (EP) 作图并适用于血管内插入患者心脏的心脏标测导管的各种示例和实施例及其制造方法。心脏标测导管包括多个支撑臂，其上设置有电极。描述和公开了心脏标测导管的各种配置，其提供了从患者心脏内获得的EP信号的改善的空间分辨率和感测。

