



US010219746B2

(12) **United States Patent**
McHale et al.

(10) **Patent No.:** **US 10,219,746 B2**
(45) **Date of Patent:** ***Mar. 5, 2019**

(54) **OXIMETER PROBE OFF INDICATOR
DEFINING PROBE OFF SPACE**

(71) Applicant: **MASIMO CORPORATION**, Irvine,
CA (US)

(72) Inventors: **Ryan Timothy McHale**, Tustin, CA
(US); **Walter M. Weber**, Laguna Hills,
CA (US)

(73) Assignee: **Masimo Corporation**, Irvine, CA (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 282 days.

This patent is subject to a terminal dis-
claimer.

(21) Appl. No.: **15/187,719**

(22) Filed: **Jun. 20, 2016**

(65) **Prior Publication Data**

US 2016/0296169 A1 Oct. 13, 2016

Related U.S. Application Data

(63) Continuation of application No. 13/610,610, filed on
Sep. 11, 2012, now Pat. No. 9,370,326, which is a
(Continued)

(51) **Int. Cl.**
A61B 5/1455 (2006.01)
A61B 5/00 (2006.01)

(52) **U.S. Cl.**
CPC **A61B 5/684** (2013.01); **A61B 5/0022**
(2013.01); **A61B 5/14551** (2013.01);
(Continued)

(58) **Field of Classification Search**

CPC ... A61B 5/0059; A61B 5/0205; A61B 5/1455;
A61B 5/14551; A61B 5/14552;

(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,295,475 A 10/1981 Tozala
4,331,161 A 5/1982 Patel

(Continued)

FOREIGN PATENT DOCUMENTS

JP 09-108203 4/1997

OTHER PUBLICATIONS

US 8,845,543, 09/2014, Diab et al. (withdrawn)
(Continued)

Primary Examiner — Eric Winakur


Assistant Examiner — Chu Chuan (J J) Liu

(74) *Attorney, Agent, or Firm* — Knobbe Martens Olson
& Bear LLP

(57) **ABSTRACT**

An embodiment of the present disclosure seeks to select characteristics of incoming intensity data that cause comparisons of selected characteristics to produce defined probe off space having reduced crossover with defined probe on space. Once defined, the present disclosure compares characteristics of incoming intensity data with the now defined probe off space, and in some embodiments, defined probe on space, to determine whether a probe off condition exists. When a processor determines a probe off condition exists, the processor may output or trigger an output signal that audibly and/or visually indicates to a user that the optical sensor should be adjusted for a proper application to a measurement site.

2 Claims, 9 Drawing Sheets



Related U.S. Application Data

continuation of application No. 11/871,690, filed on Oct. 12, 2007, now Pat. No. 8,265,723.

(60) Provisional application No. 60/851,448, filed on Oct. 12, 2006.

(52) U.S. Cl.

CPC *A61B 5/14552* (2013.01); *A61B 5/6826* (2013.01); *A61B 5/6832* (2013.01); *A61B 5/6838* (2013.01); *A61B 5/7221* (2013.01); *A61B 5/7246* (2013.01); *A61B 5/742* (2013.01); *A61B 5/7405* (2013.01); *A61B 5/746* (2013.01); *A61B 5/7445* (2013.01); *A61B 2560/0214* (2013.01); *A61B 2560/0456* (2013.01); *A61B 2560/0475* (2013.01)

(58) Field of Classification Search

CPC *A61B 5/14532*; *A61B 5/72*; *A61B 5/0022*; *A61B 5/684*; *A61B 5/7221*; *A61B 5/742*; *A61B 5/7246*; *A61B 5/7405*; *A61B 5/7445*; *A61B 5/746*; *A61B 5/6826*; *A61B 5/6838*; *A61B 5/6832*

See application file for complete search history.

(56)**References Cited**

U.S. PATENT DOCUMENTS

4,399,824 A	8/1983	Davidson	5,760,910 A	6/1998	Lepper, Jr. et al.
4,561,440 A	12/1985	Kubo et al.	5,769,785 A	6/1998	Diab et al.
4,603,700 A	8/1986	Nichols et al.	5,782,757 A	7/1998	Diab et al.
4,960,128 A	10/1990	Gordon et al.	5,785,659 A	7/1998	Caro et al.
4,964,408 A	10/1990	Hink et al.	5,791,347 A	8/1998	Flaherty et al.
5,003,979 A	4/1991	Merickel et al.	5,810,734 A	9/1998	Caro et al.
5,041,187 A	8/1991	Hink et al.	5,823,950 A	10/1998	Diab et al.
5,069,213 A	12/1991	Polczynski	5,830,131 A	11/1998	Caro et al.
5,163,438 A	11/1992	Gordon et al.	5,833,618 A	11/1998	Caro et al.
5,226,417 A	7/1993	Swedlow et al.	5,846,190 A	12/1998	Woehrle
5,319,355 A	6/1994	Russek	5,860,919 A	1/1999	Kiani-Azarbayjany et al.
5,337,744 A	8/1994	Branigan	5,890,929 A	4/1999	Mills et al.
5,341,805 A	8/1994	Stavridi et al.	5,904,654 A	5/1999	Wohlmann et al.
5,368,041 A	11/1994	Shambroom	5,919,134 A	7/1999	Diab
D353,195 S	12/1994	Savage et al.	5,934,925 A	8/1999	Tobler et al.
D353,196 S	12/1994	Savage et al.	5,940,182 A	8/1999	Lepper, Jr. et al.
5,370,114 A	12/1994	Wong et al.	5,976,466 A	11/1999	Ratner et al.
5,377,676 A	1/1995	Vari et al.	5,995,855 A	11/1999	Kiani et al.
D359,546 S	6/1995	Savage et al.	5,997,343 A	12/1999	Mills et al.
5,431,170 A	7/1995	Mathews	6,002,952 A	12/1999	Diab et al.
D361,840 S	8/1995	Savage et al.	6,011,986 A	1/2000	Diab et al.
D362,063 S	9/1995	Savage et al.	6,027,452 A	2/2000	Flaherty et al.
5,452,717 A	9/1995	Branigan et al.	6,035,223 A	3/2000	Baker, Jr.
D363,120 S	10/1995	Savage et al.	6,036,642 A	3/2000	Diab et al.
5,456,252 A	10/1995	Vari et al.	6,045,509 A	4/2000	Caro et al.
5,469,845 A	11/1995	DeLonzor et al.	6,067,462 A	5/2000	Diab et al.
5,479,934 A	1/1996	Imran	6,081,735 A	6/2000	Diab et al.
5,482,036 A	1/1996	Diab et al.	6,088,607 A	7/2000	Diab et al.
5,490,505 A	2/1996	Diab et al.	6,110,522 A	8/2000	Lepper, Jr. et al.
5,494,043 A	2/1996	O'Sullivan et al.	6,124,597 A	9/2000	Shehada
5,503,148 A	4/1996	Pologe et al.	6,128,521 A	10/2000	Marro et al.
5,533,511 A	7/1996	Kaspari et al.	6,129,675 A	10/2000	Jay
5,534,851 A	7/1996	Russek	6,144,868 A	11/2000	Parker
5,553,615 A	9/1996	Carim et al.	6,151,516 A	11/2000	Kiani-Azarbayjany et al.
5,561,275 A	10/1996	Savage et al.	6,152,754 A	11/2000	Gerhardt et al.
5,562,002 A	10/1996	Lalin	6,157,850 A	12/2000	Diab et al.
5,590,649 A	1/1997	Caro et al.	6,165,005 A	12/2000	Mills et al.
5,602,924 A	2/1997	Durand et al.	6,184,521 B1	2/2001	Coffin, IV et al.
5,632,272 A	5/1997	Diab et al.	6,206,830 B1	3/2001	Diab et al.
5,638,816 A	6/1997	Kiani-Azarbayjany et al.	6,229,856 B1	5/2001	Diab et al.
5,638,818 A	6/1997	Diab et al.	6,232,609 B1	5/2001	Snyder et al.
5,645,440 A	7/1997	Tobler et al.	6,236,872 B1	5/2001	Diab et al.
5,685,299 A	11/1997	Diab et al.	6,241,683 B1	6/2001	Macklem et al.
D393,830 S	4/1998	Tobler et al.	6,253,097 B1	6/2001	Aronow et al.
5,743,262 A	4/1998	Lepper, Jr. et al.	6,256,523 B1	7/2001	Diab et al.
5,758,644 A	6/1998	Diab et al.	6,263,222 B1	7/2001	Diab et al.
			6,278,522 B1	8/2001	Lepper, Jr. et al.
			6,280,213 B1	8/2001	Tobler et al.
			6,285,896 B1	9/2001	Tobler et al.
			6,301,493 B1	10/2001	Marro et al.
			6,317,627 B1	11/2001	Ennen et al.
			6,321,100 B1	11/2001	Parker
			6,325,761 B1	12/2001	Jay
			6,334,065 B1	12/2001	Al-Ali et al.
			6,343,224 B1	1/2002	Parker
			6,349,228 B1	2/2002	Kiani et al.
			6,360,114 B1	3/2002	Diab et al.
			6,368,283 B1	4/2002	Xu et al.
			6,371,921 B1	4/2002	Caro et al.
			6,377,829 B1	4/2002	Al-Ali
			6,388,240 B2	5/2002	Schulz et al.
			6,397,091 B2	5/2002	Diab et al.
			6,430,437 B1	8/2002	Marro
			6,430,525 B1	8/2002	Weber et al.
			6,463,311 B1	10/2002	Diab
			6,470,199 B1	10/2002	Kopotic et al.
			6,501,975 B2	12/2002	Diab et al.
			6,505,059 B1	1/2003	Kollias et al.
			6,510,329 B2	1/2003	Heckel
			6,515,273 B2	2/2003	Al-Ali
			6,519,487 B1	2/2003	Parker
			6,525,386 B1	2/2003	Mills et al.
			6,526,300 B1	2/2003	Kiani et al.
			6,541,756 B2	4/2003	Schulz et al.
			6,542,764 B1	4/2003	Al-Ali et al.
			6,580,086 B1	6/2003	Schulz et al.
			6,584,336 B1	6/2003	Ali et al.
			6,591,123 B2	7/2003	Fein et al.
			6,595,316 B2	7/2003	Cybulski et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,597,932 B2	7/2003	Tian et al.	7,221,971 B2	5/2007	Diab
6,597,933 B2	7/2003	Kiani et al.	7,225,006 B2	5/2007	Al-Ali et al.
6,606,511 B1	8/2003	Ali et al.	7,225,007 B2	5/2007	Al-Ali
6,632,181 B2	10/2003	Flaherty et al.	RE39,672 E	6/2007	Shehada et al.
6,639,668 B1	10/2003	Trepagnier	7,239,905 B2	7/2007	Kiani-Azarbayjany et al.
6,640,116 B2	10/2003	Diab	7,245,953 B1	7/2007	Parker
6,643,530 B2	11/2003	Diab et al.	7,254,429 B2	8/2007	Schurman et al.
6,650,917 B2	11/2003	Diab et al.	7,254,431 B2	8/2007	Al-Ali
6,654,624 B2	11/2003	Diab et al.	7,254,433 B2	8/2007	Diab et al.
6,658,276 B2	12/2003	Kiani et al.	7,254,434 B2	8/2007	Schulz et al.
6,661,161 B1	12/2003	Lanzo et al.	7,272,425 B2	9/2007	Al-Ali
6,671,531 B2	12/2003	Al-Ali et al.	7,274,955 B2	9/2007	Kiani et al.
6,678,543 B2	1/2004	Diab et al.	D554,263 S	10/2007	Al-Ali
6,684,090 B2	1/2004	Ali et al.	7,280,858 B2	10/2007	Al-Ali et al.
6,684,091 B2	1/2004	Parker	7,289,835 B2	10/2007	Mansfield et al.
6,697,656 B1	2/2004	Al-Ali	7,292,883 B2	11/2007	De Felice et al.
6,697,657 B1	2/2004	Shehada et al.	7,295,866 B2	11/2007	Al-Ali
6,697,658 B2	2/2004	Al-Ali	7,328,053 B1	2/2008	Diab et al.
RE38,476 E	3/2004	Diab et al.	7,332,784 B2	2/2008	Mills et al.
6,699,194 B1	3/2004	Diab et al.	7,340,287 B2	3/2008	Mason et al.
6,714,804 B2	3/2004	Al-Ali et al.	7,341,559 B2	3/2008	Schulz et al.
RE38,492 E	4/2004	Diab et al.	7,343,186 B2	3/2008	Lamego et al.
6,721,582 B2	4/2004	Trepagnier et al.	D566,282 S	4/2008	Al-Ali et al.
6,721,585 B1	4/2004	Parker	7,355,512 B1	4/2008	Al-Ali
6,725,075 B2	4/2004	Al-Ali	7,356,365 B2	4/2008	Schurman
6,728,560 B2	4/2004	Kollias et al.	7,371,981 B2	5/2008	Abdul-Hafiz
6,735,459 B2	5/2004	Parker	7,373,193 B2	5/2008	Al-Ali et al.
6,745,060 B2	6/2004	Diab et al.	7,373,194 B2	5/2008	Weber et al.
6,760,607 B2	7/2004	Al-Ali	7,376,453 B1	5/2008	Diab et al.
6,770,028 B1	8/2004	Ali et al.	7,377,794 B2	5/2008	Al Ali et al.
6,771,994 B2	8/2004	Kiani et al.	7,377,899 B2	5/2008	Weber et al.
6,792,300 B1	9/2004	Diab et al.	7,383,070 B2	6/2008	Diab et al.
6,813,511 B2	11/2004	Diab et al.	7,415,297 B2	8/2008	Al-Ali et al.
6,816,741 B2	11/2004	Diab	7,428,432 B2	9/2008	Ali et al.
6,822,564 B2	11/2004	Al-Ali	7,438,683 B2	10/2008	Al-Ali et al.
6,826,419 B2	11/2004	Diab et al.	7,440,787 B2	10/2008	Diab
6,830,711 B2	12/2004	Mills et al.	7,454,240 B2	11/2008	Diab et al.
6,850,787 B2	2/2005	Weber et al.	7,457,652 B2	11/2008	Porges et al.
6,850,788 B2	2/2005	Al-Ali	7,467,002 B2	12/2008	Weber et al.
6,852,083 B2	2/2005	Caro et al.	7,469,157 B2	12/2008	Diab et al.
6,861,639 B2	3/2005	Al-Ali	7,471,969 B2	12/2008	Diab et al.
6,882,874 B2	4/2005	Huiku	7,471,971 B2	12/2008	Diab et al.
6,898,452 B2	5/2005	Al-Ali et al.	7,483,729 B2	1/2009	Al-Ali et al.
6,920,345 B2	7/2005	Al-Ali et al.	7,483,730 B2	1/2009	Diab et al.
6,931,268 B1	8/2005	Kiani-Azarbayjany et al.	7,489,958 B2	2/2009	Diab et al.
6,934,570 B2	8/2005	Kiani et al.	7,496,391 B2	2/2009	Diab et al.
6,939,305 B2	9/2005	Flaherty et al.	7,496,393 B2	2/2009	Diab et al.
6,943,348 B1	9/2005	Coffin, IV	D587,657 S	3/2009	Al-Ali et al.
6,950,687 B2	9/2005	Al-Ali	7,499,741 B2	3/2009	Diab et al.
6,961,598 B2	11/2005	Diab	7,499,835 B2	3/2009	Weber et al.
6,970,792 B1	11/2005	Diab	7,500,950 B2	3/2009	Al-Ali et al.
6,979,812 B2	12/2005	Al-Ali	7,509,154 B2	3/2009	Diab et al.
6,985,764 B2	1/2006	Mason et al.	7,509,494 B2	3/2009	Al-Ali
6,993,371 B2	1/2006	Kiani et al.	7,510,849 B2	3/2009	Schurman et al.
6,996,427 B2	2/2006	Ali et al.	7,526,328 B2	4/2009	Diab et al.
6,999,904 B2	2/2006	Weber et al.	7,530,942 B1	5/2009	Diab
7,003,338 B2	2/2006	Weber et al.	7,530,949 B2	5/2009	Al Ali et al.
7,003,339 B2	2/2006	Diab et al.	7,530,955 B2	5/2009	Diab et al.
7,015,451 B2	3/2006	Dalke et al.	7,563,110 B2	7/2009	Al-Ali et al.
7,024,233 B2	4/2006	Ali et al.	7,596,398 B2	9/2009	Al-Ali et al.
7,027,849 B2	4/2006	Al-Ali	7,618,375 B2	11/2009	Flaherty
7,030,749 B2	4/2006	Al-Ali	D606,659 S	12/2009	Kiani et al.
7,039,449 B2	5/2006	Al-Ali	7,647,083 B2	1/2010	Al-Ali et al.
7,041,060 B2	5/2006	Flaherty et al.	D609,193 S	2/2010	Al-Ali et al.
7,044,918 B2	5/2006	Diab	7,679,519 B2	3/2010	Lindner et al.
7,067,893 B2	6/2006	Mills et al.	D614,305 S	4/2010	Al-Ali et al.
7,096,052 B2	8/2006	Mason et al.	RE41,317 E	5/2010	Parker
7,096,054 B2	8/2006	Abdul-Hafiz et al.	7,729,733 B2	6/2010	Al-Ali et al.
7,132,641 B2	11/2006	Schulz et al.	7,734,320 B2	6/2010	Al-Ali
7,142,901 B2	11/2006	Kiani et al.	7,761,127 B2	7/2010	Al-Ali et al.
7,149,561 B2	12/2006	Diab	7,761,128 B2	7/2010	Al-Ali et al.
7,186,966 B2	3/2007	Al-Ali	7,764,982 B2	7/2010	Dalke et al.
7,190,261 B2	3/2007	Al-Ali	D621,516 S	8/2010	Kiani et al.
7,215,984 B2	5/2007	Diab	7,791,155 B2	9/2010	Diab
7,215,986 B2	5/2007	Diab	7,801,581 B2	9/2010	Diab
			7,822,452 B2	10/2010	Schurman et al.
			RE41,912 E	11/2010	Parker
			7,844,313 B2	11/2010	Kiani et al.
			7,844,314 B2	11/2010	Al-Ali

(56)

References Cited

U.S. PATENT DOCUMENTS

7,844,315	B2	11/2010	Al-Ali	8,359,080	B2	1/2013	Diab et al.
7,865,222	B2	1/2011	Weber et al.	8,364,223	B2	1/2013	Al-Ali et al.
7,873,497	B2	1/2011	Weber et al.	8,364,226	B2	1/2013	Diab et al.
7,880,606	B2	2/2011	Al-Ali	8,374,665	B2	2/2013	Lamego
7,880,626	B2	2/2011	Al-Ali et al.	8,385,995	B2	2/2013	Al-Ali et al.
7,891,355	B2	2/2011	Al-Ali et al.	8,385,996	B2	2/2013	Smith et al.
7,894,868	B2	2/2011	Al-Ali et al.	8,388,353	B2	3/2013	Kiani et al.
7,899,507	B2	3/2011	Al-Ali et al.	8,399,822	B2	3/2013	Al-Ali
7,899,518	B2	3/2011	Trepagnier et al.	8,401,602	B2	3/2013	Kiani
7,904,132	B2	3/2011	Weber et al.	8,405,608	B2	3/2013	Al-Ali et al.
7,909,772	B2	3/2011	Popov et al.	8,414,499	B2	4/2013	Al-Ali et al.
7,910,875	B2	3/2011	Al-Ali	8,418,524	B2	4/2013	Al-Ali
7,919,713	B2	4/2011	Al-Ali et al.	8,423,106	B2	4/2013	Lamego et al.
7,937,128	B2	5/2011	Al-Ali	8,428,967	B2	4/2013	Olsen et al.
7,937,129	B2	5/2011	Mason et al.	8,430,817	B1	4/2013	Al-Ali et al.
7,937,130	B2	5/2011	Diab et al.	8,437,825	B2	5/2013	Dalvi et al.
7,941,199	B2	5/2011	Kiani	8,455,290	B2	6/2013	Siskavich
7,951,086	B2	5/2011	Flaherty et al.	8,457,703	B2	6/2013	Al-Ali
7,957,780	B2	6/2011	Lamego et al.	8,457,707	B2	6/2013	Kiani
7,962,188	B2	6/2011	Kiani et al.	8,463,349	B2	6/2013	Diab et al.
7,962,190	B1	6/2011	Diab et al.	8,466,286	B2	6/2013	Bellot et al.
7,976,472	B2	7/2011	Kiani	8,471,713	B2	6/2013	Poeze et al.
7,988,637	B2	8/2011	Diab	8,473,020	B2	6/2013	Kiani et al.
7,990,382	B2	8/2011	Kiani	8,483,787	B2	7/2013	Al-Ali et al.
7,991,446	B2	8/2011	Ali et al.	8,489,364	B2	7/2013	Weber et al.
8,000,761	B2	8/2011	Al-Ali	8,498,684	B2	7/2013	Weber et al.
8,008,088	B2	8/2011	Bellott et al.	8,504,128	B2	8/2013	Blank et al.
RE42,753	E	9/2011	Kiani-Azarbayjany et al.	8,509,867	B2	8/2013	Workman et al.
8,019,400	B2	9/2011	Diab et al.	8,515,509	B2	8/2013	Bruinsma et al.
8,028,701	B2	10/2011	Al-Ali et al.	8,523,781	B2	9/2013	Al-Ali
8,029,765	B2	10/2011	Bellott et al.	8,529,301	B2	9/2013	Al-Ali et al.
8,036,727	B2	10/2011	Schurman et al.	8,532,727	B2	9/2013	Ali et al.
8,036,728	B2	10/2011	Diab et al.	8,532,728	B2	9/2013	Diab et al.
8,046,040	B2	10/2011	Ali et al.	D692,145	S	10/2013	Al-Ali et al.
8,046,041	B2	10/2011	Diab et al.	8,547,209	B2	10/2013	Kiani et al.
8,046,042	B2	10/2011	Diab et al.	8,548,548	B2	10/2013	Al-Ali
8,048,040	B2	11/2011	Kiani	8,548,549	B2	10/2013	Schurman et al.
8,050,728	B2	11/2011	Al-Ali et al.	8,548,550	B2	10/2013	Al-Ali et al.
RE43,169	E	2/2012	Parker	8,560,032	B2	10/2013	Al-Ali et al.
8,118,620	B2	2/2012	Al-Ali et al.	8,560,034	B1	10/2013	Diab et al.
8,126,528	B2	2/2012	Diab et al.	8,570,167	B2	10/2013	Al-Ali
8,128,572	B2	3/2012	Diab et al.	8,570,503	B2	10/2013	Vo et al.
8,130,105	B2	3/2012	Al-Ali et al.	8,571,617	B2	10/2013	Reichgott et al.
8,145,287	B2	3/2012	Diab et al.	8,571,618	B1	10/2013	Lamego et al.
8,150,487	B2	4/2012	Diab et al.	8,571,619	B2	10/2013	Al-Ali et al.
8,175,672	B2	5/2012	Parker	8,577,431	B2	11/2013	Lamego et al.
8,180,420	B2	5/2012	Diab et al.	8,581,732	B2	11/2013	Al-Ali et al.
8,182,443	B1	5/2012	Kiani	8,584,345	B2	11/2013	Al-Ali et al.
8,185,180	B2	5/2012	Diab et al.	8,588,880	B2	11/2013	Abdul-Hafiz et al.
8,190,223	B2	5/2012	Al-Ali et al.	8,600,467	B2	12/2013	Al-Ali et al.
8,190,227	B2	5/2012	Diab et al.	8,606,342	B2	12/2013	Diab
8,203,438	B2	6/2012	Kiani et al.	8,626,255	B2	1/2014	Al-Ali et al.
8,203,704	B2	6/2012	Merritt et al.	8,630,691	B2	1/2014	Lamego et al.
8,204,566	B2	6/2012	Schurman et al.	8,634,889	B2	1/2014	Al-Ali et al.
8,219,172	B2	7/2012	Schurman et al.	8,641,631	B2	2/2014	Sierra et al.
8,224,411	B2	7/2012	Al-Ali et al.	8,652,060	B2	2/2014	Al-Ali
8,228,181	B2	7/2012	Al-Ali	8,663,107	B2	3/2014	Kiani
8,229,533	B2	7/2012	Diab et al.	8,666,468	B1	3/2014	Al-Ali
8,233,955	B2	7/2012	Al-Ali et al.	8,667,967	B2	3/2014	Al-Ali et al.
8,244,325	B2	8/2012	Al-Ali et al.	8,670,811	B2	3/2014	O'Reilly
8,255,026	B1	8/2012	Al-Ali	8,670,814	B2	3/2014	Diab et al.
8,255,027	B2	8/2012	Al-Ali et al.	8,676,286	B2	3/2014	Weber et al.
8,255,028	B2	8/2012	Al-Ali et al.	8,682,407	B2	3/2014	Al-Ali
8,260,577	B2	9/2012	Weber et al.	RE44,823	E	4/2014	Parker
8,265,723	B1	9/2012	McHale et al.	RE44,875	E	4/2014	Kiani et al.
8,274,360	B2	9/2012	Sampath et al.	8,690,799	B2	4/2014	Telfort et al.
8,301,217	B2	10/2012	Al-Ali et al.	8,700,112	B2	4/2014	Kiani
8,306,596	B2	11/2012	Schurman et al.	8,702,627	B2	4/2014	Telfort et al.
8,310,336	B2	11/2012	Muhsin et al.	8,706,179	B2	4/2014	Parker
8,315,683	B2	11/2012	Al-Ali et al.	8,712,494	B1	4/2014	MacNeish, III et al.
RE43,860	E	12/2012	Parker	8,715,206	B2	5/2014	Telfort et al.
8,337,403	B2	12/2012	Al-Ali et al.	8,718,735	B2	5/2014	Lamego et al.
8,346,330	B2	1/2013	Lamego	8,718,737	B2	5/2014	Diab et al.
8,353,842	B2	1/2013	Al-Ali et al.	8,718,738	B2	5/2014	Blank et al.
8,355,766	B2	1/2013	MacNeish, III et al.	8,720,249	B2	5/2014	Al-Ali
				8,721,541	B2	5/2014	Al-Ali et al.
				8,721,542	B2	5/2014	Al-Ali et al.
				8,723,677	B1	5/2014	Kiani
				8,740,792	B1	6/2014	Kiani et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

8,754,776	B2	6/2014	Poeze et al.	9,176,141	B2	11/2015	Al-Ali et al.
8,755,535	B2	6/2014	Telfort et al.	9,186,102	B2	11/2015	Bruinsma et al.
8,755,856	B2	6/2014	Diab et al.	9,192,312	B2	11/2015	Al-Ali
8,755,872	B1	6/2014	Marinow	9,192,329	B2	11/2015	Al-Ali
8,761,850	B2	6/2014	Lamego	9,192,351	B1	11/2015	Telfort et al.
8,764,671	B2	7/2014	Kiani	9,195,385	B2	11/2015	Al-Ali et al.
8,768,423	B2	7/2014	Shakespeare et al.	9,211,072	B2	12/2015	Kiani
8,771,204	B2	7/2014	Telfort et al.	9,211,095	B1	12/2015	Al-Ali
8,777,634	B2	7/2014	Kiani et al.	9,218,454	B2	12/2015	Kiani et al.
8,781,543	B2	7/2014	Diab et al.	9,226,696	B2	1/2016	Kiani
8,781,544	B2	7/2014	Al-Ali et al.	9,241,662	B2	1/2016	Al-Ali et al.
8,781,549	B2	7/2014	Al-Ali et al.	9,245,668	B1	1/2016	Vo et al.
8,788,003	B2	7/2014	Schurman et al.	9,259,185	B2	2/2016	Abdul-Hafiz et al.
8,790,268	B2	7/2014	Al-Ali	9,267,572	B2	2/2016	Barker et al.
8,801,613	B2	8/2014	Al-Ali et al.	9,277,880	B2	3/2016	Poeze et al.
8,821,397	B2	9/2014	Al-Ali et al.	9,289,167	B2	3/2016	Diab et al.
8,821,415	B2	9/2014	Al-Ali et al.	9,295,421	B2	3/2016	Kiani et al.
8,830,449	B1	9/2014	Lamego et al.	9,307,928	B1	4/2016	Al-Ali et al.
8,831,700	B2	9/2014	Schurman et al.	9,323,894	B2	4/2016	Kiani
8,840,549	B2	9/2014	Al-Ali et al.	D755,392	S	5/2016	Hwang et al.
8,847,740	B2	9/2014	Kiani et al.	9,326,712	B1	5/2016	Kiani
8,849,365	B2	9/2014	Smith et al.	9,333,316	B2	5/2016	Kiani
8,852,094	B2	10/2014	Al-Ali et al.	9,339,220	B2	5/2016	Lamego et al.
8,852,994	B2	10/2014	Wojtczuk et al.	9,341,565	B2	5/2016	Lamego et al.
8,868,147	B2	10/2014	Stippick et al.	9,351,673	B2	5/2016	Diab et al.
8,868,150	B2	10/2014	Al-Ali et al.	9,351,675	B2	5/2016	Al-Ali et al.
8,870,792	B2	10/2014	Al-Ali et al.	9,364,181	B2	6/2016	Kiani et al.
8,886,271	B2	11/2014	Kiani et al.	9,368,671	B2	6/2016	Wojtczuk et al.
8,888,539	B2	11/2014	Al-Ali et al.	9,370,325	B2	6/2016	Al-Ali et al.
8,888,708	B2	11/2014	Diab et al.	9,370,326	B2	6/2016	McHale et al.
8,892,180	B2	11/2014	Weber et al.	9,370,335	B2	6/2016	Al-Ali et al.
8,897,847	B2	11/2014	Al-Ali	9,375,185	B2	6/2016	Ali et al.
8,909,310	B2	12/2014	Lamego et al.	9,386,953	B2	7/2016	Al-Ali
8,911,377	B2	12/2014	Al-Ali	9,386,961	B2	7/2016	Al-Ali et al.
8,912,909	B2	12/2014	Al-Ali et al.	9,392,945	B2	7/2016	Al-Ali et al.
8,920,317	B2	12/2014	Al-Ali et al.	9,397,448	B2	7/2016	Al-Ali et al.
8,921,699	B2	12/2014	Al-Ali et al.	9,408,542	B1	8/2016	Kinast et al.
8,922,382	B2	12/2014	Al-Ali et al.	9,436,645	B2	9/2016	Al-Ali et al.
8,929,964	B2	1/2015	Al-Ali et al.	9,445,759	B1	9/2016	Lamego et al.
8,942,777	B2	1/2015	Diab et al.	9,466,919	B2	10/2016	Kiani et al.
8,948,834	B2	2/2015	Diab et al.	9,474,474	B2	10/2016	Lamego et al.
8,948,835	B2	2/2015	Diab	9,480,422	B2	11/2016	Al-Ali
8,965,471	B2	2/2015	Lamego	9,480,435	B2	11/2016	Olsen
8,983,564	B2	3/2015	Al-Ali	9,492,110	B2	11/2016	Al-Ali et al.
8,989,831	B2	3/2015	Al-Ali et al.	9,510,779	B2	12/2016	Poeze et al.
8,996,085	B2	3/2015	Kiani et al.	9,517,024	B2	12/2016	Kiani et al.
8,998,809	B2	4/2015	Kiani	9,532,722	B2	1/2017	Lamego et al.
9,028,429	B2	5/2015	Telfort et al.	9,538,949	B2	1/2017	Al-Ali et al.
9,037,207	B2	5/2015	Al-Ali et al.	9,538,980	B2	1/2017	Telfort et al.
9,060,721	B2	6/2015	Reichgott et al.	9,549,696	B2	1/2017	Lamego et al.
9,066,666	B2	6/2015	Kiani	9,554,737	B2	1/2017	Schurman et al.
9,066,680	B1	6/2015	Al-Ali et al.	9,560,996	B2	2/2017	Kiani
9,072,474	B2	7/2015	Al-Ali et al.	9,560,998	B2	2/2017	Al-Ali et al.
9,078,560	B2	7/2015	Schurman et al.	9,566,019	B2	2/2017	Al-Ali et al.
9,084,569	B2	7/2015	Weber et al.	9,579,039	B2	2/2017	Jansen et al.
9,095,316	B2	8/2015	Welch et al.	9,591,975	B2	3/2017	Dalvi et al.
9,106,038	B2	8/2015	Telfort et al.	9,622,692	B2	4/2017	Lamego et al.
9,107,625	B2	8/2015	Telfort et al.	9,622,693	B2	4/2017	Diab
9,107,626	B2	8/2015	Al-Ali et al.	D788,312	S	5/2017	Al-Ali et al.
9,113,831	B2	8/2015	Al-Ali	9,636,055	B2	5/2017	Al-Ali et al.
9,113,832	B2	8/2015	Al-Ali	9,636,056	B2	5/2017	Al-Ali
9,119,595	B2	9/2015	Lamego	9,649,054	B2	5/2017	Lamego et al.
9,131,881	B2	9/2015	Diab et al.	9,662,052	B2	5/2017	Al-Ali et al.
9,131,882	B2	9/2015	Al-Ali et al.	9,668,679	B2	6/2017	Schurman et al.
9,131,883	B2	9/2015	Al-Ali	9,668,680	B2	6/2017	Bruinsma et al.
9,131,917	B2	9/2015	Telfort et al.	9,668,703	B2	6/2017	Al-Ali
9,138,180	B1	9/2015	Coverston et al.	9,675,286	B2	6/2017	Diab
9,138,182	B2	9/2015	Al-Ali et al.	9,687,160	B2	6/2017	Kiani
9,138,192	B2	9/2015	Weber et al.	9,693,719	B2	7/2017	Al-Ali et al.
9,142,117	B2	9/2015	Muhsin et al.	9,693,737	B2	7/2017	Al-Ali
9,153,112	B1	10/2015	Kiani et al.	9,697,928	B2	7/2017	Al-Ali et al.
9,153,121	B2	10/2015	Kiani et al.	9,717,425	B2	8/2017	Kiani et al.
9,161,696	B2	10/2015	Al-Ali et al.	9,717,458	B2	8/2017	Lamego et al.
9,161,713	B2	10/2015	Al-Ali et al.	9,724,016	B1	8/2017	Al-Ali et al.
9,167,995	B2	10/2015	Lamego et al.	9,724,024	B2	8/2017	Al-Ali
				9,724,025	B1	8/2017	Kiani et al.
				9,730,640	B2	8/2017	Diab et al.
				9,743,887	B2	8/2017	Al-Ali et al.
				9,749,232	B2	8/2017	Sampath et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

9,750,442 B2	9/2017	Olsen	2011/0125060 A1	5/2011	Telfort et al.
9,750,443 B2	9/2017	Smith et al.	2011/0208015 A1	8/2011	Welch et al.
9,750,461 B1	9/2017	Telfort	2011/0213212 A1	9/2011	Al-Ali
9,775,545 B2	10/2017	Al-Ali et al.	2011/0230733 A1	9/2011	Al-Ali
9,775,546 B2	10/2017	Diab et al.	2011/0237969 A1	9/2011	Eckerbom et al.
9,775,570 B2	10/2017	Al-Ali	2011/0288383 A1	11/2011	Diab
9,778,079 B1	10/2017	Al-Ali et al.	2011/0301444 A1	12/2011	Al-Ali
9,782,077 B2	10/2017	Lamego et al.	2012/0041316 A1	2/2012	Al-Ali et al.
9,782,110 B2	10/2017	Kiani	2012/0046557 A1	2/2012	Kiani
9,787,568 B2	10/2017	Lamego et al.	2012/0059267 A1	3/2012	Lamego et al.
9,788,735 B2	10/2017	Al-Ali	2012/0088984 A1	4/2012	Al-Ali et al.
9,788,768 B2	10/2017	Al-Ali et al.	2012/0165629 A1	6/2012	Merritt et al.
9,795,300 B2	10/2017	Al-Ali	2012/0179006 A1	7/2012	Jansen et al.
9,795,310 B2	10/2017	Al-Ali	2012/0209082 A1	8/2012	Al-Ali
9,795,358 B2	10/2017	Telfort et al.	2012/0209084 A1	8/2012	Olsen et al.
9,795,739 B2	10/2017	Al-Ali et al.	2012/0283524 A1	11/2012	Kiani et al.
9,801,556 B2	10/2017	Kiani	2012/0296178 A1	11/2012	Lamego et al.
9,801,588 B2	10/2017	Weber et al.	2012/0319816 A1	12/2012	Al-Ali
9,808,188 B1	11/2017	Perea et al.	2012/0330112 A1	12/2012	Lamego et al.
9,814,418 B2	11/2017	Weber et al.	2013/0006076 A1	1/2013	McHale
9,820,691 B2	11/2017	Kiani	2013/0023775 A1	1/2013	Lamego et al.
9,833,152 B2	12/2017	Kiani et al.	2013/0041591 A1	2/2013	Lamego
9,833,180 B2	12/2017	Shakespeare et al.	2013/0046204 A1	2/2013	Lamego et al.
9,839,379 B2	12/2017	Al-Ali et al.	2013/0060147 A1	3/2013	Welch et al.
9,839,381 B1	12/2017	Weber et al.	2013/0096405 A1	4/2013	Garfio
9,847,002 B2	12/2017	Kiani et al.	2013/0096936 A1	4/2013	Sampath et al.
9,847,749 B2	12/2017	Kiani et al.	2013/0190581 A1	7/2013	Al-Ali et al.
9,848,800 B1	12/2017	Lee et al.	2013/0211214 A1	8/2013	Olsen
9,848,806 B2	12/2017	Al-Ali et al.	2013/0243021 A1	9/2013	Siskavich
9,848,807 B2	12/2017	Lamego	2013/0253334 A1	9/2013	Al-Ali et al.
9,861,298 B2	1/2018	Eckerbom et al.	2013/0262730 A1	10/2013	Al-Ali et al.
9,861,304 B2	1/2018	Al-Ali et al.	2013/0267804 A1	10/2013	Al-Ali
9,861,305 B1	1/2018	Weber et al.	2013/0274572 A1	10/2013	Al-Ali et al.
9,867,578 B2	1/2018	Al-Ali et al.	2013/0296672 A1	11/2013	O'Neil et al.
9,872,623 B2	1/2018	Al-Ali	2013/0296713 A1	11/2013	Al-Ali et al.
9,876,320 B2	1/2018	Coverston et al.	2013/0317370 A1	11/2013	Dalvi et al.
9,877,650 B2	1/2018	Muhsin et al.	2013/0324808 A1	12/2013	Al-Ali et al.
9,877,686 B2	1/2018	Al-Ali et al.	2013/0331660 A1	12/2013	Al-Ali et al.
9,891,079 B2	2/2018	Dalvi	2013/0331670 A1	12/2013	Kiani
9,895,107 B2	2/2018	Al-Ali et al.	2014/0012100 A1	1/2014	Al-Ali et al.
9,913,617 B2	3/2018	Al-Ali et al.	2014/0034353 A1	2/2014	Al-Ali et al.
9,924,893 B2	3/2018	Schurman et al.	2014/0051953 A1	2/2014	Lamego et al.
9,924,897 B1	3/2018	Abdul-Hafiz	2014/0066783 A1	3/2014	Kiani et al.
9,936,917 B2	4/2018	Poeze et al.	2014/0077956 A1	3/2014	Sampath et al.
9,943,269 B2	4/2018	Muhsin et al.	2014/0081100 A1	3/2014	Muhsin et al.
9,949,676 B2	4/2018	Al-Ali	2014/0081175 A1	3/2014	Telfort
9,955,937 B2	5/2018	Telfort	2014/0094667 A1	4/2014	Schurman et al.
9,965,946 B2	5/2018	Al-Ali	2014/0100434 A1	4/2014	Diab et al.
9,980,667 B2	5/2018	Kiani et al.	2014/0114199 A1	4/2014	Lamego et al.
D820,865 S	6/2018	Muhsin et al.	2014/0120564 A1	5/2014	Workman et al.
9,986,919 B2	6/2018	Lamego et al.	2014/0121482 A1	5/2014	Merritt et al.
9,986,952 B2	6/2018	Dalvi et al.	2014/0121483 A1	5/2014	Kiani
9,989,560 B2	6/2018	Poeze et al.	2014/0127137 A1	5/2014	Bellott et al.
9,993,207 B2	6/2018	Al-Ali et al.	2014/0129702 A1	5/2014	Lamego et al.
10,007,758 B2	6/2018	Al-Ali et al.	2014/0135588 A1	5/2014	Al-Ali et al.
D822,215 S	7/2018	Al-Ali et al.	2014/0142401 A1	5/2014	Al-Ali et al.
D822,216 S	7/2018	Barker et al.	2014/0163344 A1	6/2014	Al-Ali
10,010,276 B2	7/2018	Al-Ali et al.	2014/0163402 A1	6/2014	Lamego et al.
10,039,482 B2	8/2018	Al-Ali et al.	2014/0166076 A1	6/2014	Kiani et al.
10,052,037 B2	8/2018	Kinast et al.	2014/0171763 A1	6/2014	Diab
10,058,275 B2	8/2018	Al-Ali et al.	2014/0180038 A1	6/2014	Kiani
2004/0097797 A1 *	5/2004	Porges	2014/0180154 A1	6/2014	Sierra et al.
			2014/0180160 A1	6/2014	Brown et al.
2005/0277819 A1	12/2005	Kiani et al.	2014/0187973 A1	7/2014	Brown et al.
2006/0211925 A1 *	9/2006	Lamego	2014/0194766 A1	7/2014	Al-Ali et al.
			2014/0206963 A1	7/2014	Al-Ali
			2014/0213864 A1	7/2014	Abdul-Hafiz et al.
			2014/0266790 A1	9/2014	Al-Ali et al.
			2014/0275808 A1	9/2014	Poeze et al.
			2014/0275835 A1	9/2014	Lamego et al.
			2014/0275871 A1	9/2014	Lamego et al.
2007/0282478 A1	12/2007	Al-Ali et al.	2014/0275872 A1	9/2014	Merritt et al.
2008/0030468 A1	2/2008	Al-Ali et al.	2014/0275881 A1	9/2014	Lamego et al.
2009/0247984 A1	10/2009	Lamego et al.	2014/0276115 A1	9/2014	Dalvi et al.
2009/0275813 A1	11/2009	Davis	2014/0288400 A1	9/2014	Diab et al.
2009/0275844 A1	11/2009	Al-Ali	2014/0303520 A1	10/2014	Telfort et al.
2010/0004518 A1	1/2010	Vo et al.	2014/0316217 A1	10/2014	Purdon et al.
2010/0030040 A1	2/2010	Poeze et al.	2014/0316218 A1	10/2014	Purdon et al.
2011/0082711 A1	4/2011	Poeze et al.	2014/0316228 A1	10/2014	Blank et al.
2011/0105854 A1	5/2011	Kiani et al.			

(56)

References Cited

U.S. PATENT DOCUMENTS

2014/0323825	A1	10/2014	Al-Ali et al.	2016/0166182	A1	6/2016	Al-Ali et al.
2014/0323897	A1	10/2014	Brown et al.	2016/0166183	A1	6/2016	Poeze et al.
2014/0323898	A1	10/2014	Purdon et al.	2016/0196388	A1	7/2016	Lamego
2014/0330092	A1	11/2014	Al-Ali et al.	2016/0197436	A1	7/2016	Barker et al.
2014/0330098	A1	11/2014	Merritt et al.	2016/0213281	A1	7/2016	Eckerbom et al.
2014/0330099	A1	11/2014	Al-Ali et al.	2016/0228043	A1	8/2016	O'Neil et al.
2014/0336481	A1	11/2014	Shakespeare et al.	2016/0233632	A1	8/2016	Scruggs et al.
2014/0357966	A1	12/2014	Al-Ali et al.	2016/0234944	A1	8/2016	Schmidt et al.
2014/0371548	A1	12/2014	Al-Ali et al.	2016/0270735	A1	9/2016	Diab et al.
2014/0371632	A1	12/2014	Al-Ali et al.	2016/0283665	A1	9/2016	Sampath et al.
2014/0378784	A1	12/2014	Kiani et al.	2016/0287090	A1	10/2016	Al-Ali et al.
2015/0005600	A1	1/2015	Blank et al.	2016/0287786	A1	10/2016	Kiani
2015/0011907	A1	1/2015	Purdon et al.	2016/0296169	A1	10/2016	McHale et al.
2015/0012231	A1	1/2015	Poeze et al.	2016/0310052	A1	10/2016	Al-Ali et al.
2015/0018650	A1	1/2015	Al-Ali et al.	2016/0314260	A1	10/2016	Kiani
2015/0025406	A1	1/2015	Al-Ali	2016/0324488	A1	11/2016	Olsen
2015/0032029	A1	1/2015	Al-Ali et al.	2016/0327984	A1	11/2016	Al-Ali et al.
2015/0038859	A1	2/2015	Dalvi et al.	2016/0331332	A1	11/2016	Al-Ali
2015/0045637	A1	2/2015	Dalvi	2016/0367173	A1	12/2016	Dalvi et al.
2015/0045685	A1	2/2015	Al-Ali et al.	2017/0000394	A1	1/2017	Al-Ali et al.
2015/0051462	A1	2/2015	Olsen	2017/0007134	A1	1/2017	Al-Ali et al.
2015/0080754	A1	3/2015	Purdon et al.	2017/0007198	A1	1/2017	Al-Ali et al.
2015/0087936	A1	3/2015	Al-Ali et al.	2017/0014083	A1	1/2017	Diab et al.
2015/0094546	A1	4/2015	Al-Ali	2017/0014084	A1	1/2017	Al-Ali et al.
2015/0097701	A1	4/2015	Al-Ali et al.	2017/0027456	A1	2/2017	Kinast et al.
2015/0099324	A1	4/2015	Wojtczuk et al.	2017/0042488	A1	2/2017	Muhsin
2015/0099950	A1	4/2015	Al-Ali et al.	2017/0055851	A1	3/2017	Al-Ali
2015/0099951	A1	4/2015	Al-Ali et al.	2017/0055882	A1	3/2017	Al-Ali et al.
2015/0099955	A1	4/2015	Al-Ali et al.	2017/0055887	A1	3/2017	Al-Ali
2015/0101844	A1	4/2015	Al-Ali et al.	2017/0055896	A1	3/2017	Al-Ali et al.
2015/0106121	A1	4/2015	Muhsin et al.	2017/0079594	A1	3/2017	Telfort et al.
2015/0112151	A1	4/2015	Muhsin et al.	2017/0086723	A1	3/2017	Al-Ali et al.
2015/0116076	A1	4/2015	Al-Ali et al.	2017/0143281	A1	5/2017	Olsen
2015/0126830	A1	5/2015	Schurman et al.	2017/0147774	A1	5/2017	Kiani
2015/0133755	A1	5/2015	Smith et al.	2017/0156620	A1	6/2017	Al-Ali et al.
2015/0140863	A1	5/2015	Al-Ali et al.	2017/0173632	A1	6/2017	Al-Ali
2015/0141781	A1	5/2015	Weber et al.	2017/0187146	A1	6/2017	Kiani et al.
2015/0165312	A1	6/2015	Kiani	2017/0188919	A1	7/2017	Al-Ali et al.
2015/0196237	A1	7/2015	Lamego	2017/0196464	A1	7/2017	Jansen et al.
2015/0201874	A1	7/2015	Diab	2017/0196470	A1	7/2017	Lamego et al.
2015/0208966	A1	7/2015	Al-Ali	2017/0224262	A1	8/2017	Al-Ali
2015/0216459	A1	8/2015	Al-Ali et al.	2017/0228516	A1	8/2017	Sampath et al.
2015/0230755	A1	8/2015	Al-Ali et al.	2017/0245790	A1	8/2017	Al-Ali et al.
2015/0238722	A1	8/2015	Al-Ali	2017/0251974	A1	9/2017	Shreim et al.
2015/0245773	A1	9/2015	Lamego et al.	2017/0251975	A1	9/2017	Shreim et al.
2015/0245793	A1	9/2015	Al-Ali et al.	2017/0258403	A1	9/2017	Abdul-Hafiz et al.
2015/0245794	A1	9/2015	Al-Ali	2017/0311851	A1	11/2017	Schurman et al.
2015/0257689	A1	9/2015	Al-Ali et al.	2017/0311891	A1	11/2017	Kiani et al.
2015/0272514	A1	10/2015	Kiani et al.	2017/0325728	A1	11/2017	Al-Ali et al.
2015/0351697	A1	12/2015	Weber et al.	2017/0332976	A1	11/2017	Al-Ali et al.
2015/0351704	A1	12/2015	Kiani et al.	2017/0340293	A1	11/2017	Al-Ali et al.
2015/0359429	A1	12/2015	Al-Ali et al.	2017/0360310	A1	12/2017	Kiani et al.
2015/0366472	A1	12/2015	Kiani	2017/0367632	A1	12/2017	Al-Ali et al.
2015/0366507	A1	12/2015	Blank	2018/0008146	A1	1/2018	Al-Ali et al.
2015/0374298	A1	12/2015	Al-Ali et al.	2018/0014752	A1	1/2018	Al-Ali et al.
2015/0380875	A1	12/2015	Coverston et al.	2018/0028124	A1	2/2018	Al-Ali et al.
2016/0000362	A1	1/2016	Diab et al.	2018/0055385	A1	3/2018	Al-Ali
2016/0007930	A1	1/2016	Weber et al.	2018/0055390	A1	3/2018	Kiani et al.
2016/0029932	A1	2/2016	Al-Ali	2018/0055430	A1	3/2018	Diab et al.
2016/0029933	A1	2/2016	Al-Ali et al.	2018/0064381	A1	3/2018	Shakespeare et al.
2016/0045118	A1	2/2016	Kiani	2018/0069776	A1	3/2018	Lamego et al.
2016/0051205	A1	2/2016	Al-Ali et al.	2018/0082767	A1	3/2018	Al-Ali et al.
2016/0058338	A1	3/2016	Schurman et al.	2018/0085068	A1	3/2018	Telfort
2016/0058347	A1	3/2016	Reichgott et al.	2018/0087937	A1	3/2018	Al-Ali et al.
2016/0066823	A1	3/2016	Kind et al.	2018/0103874	A1	4/2018	Lee et al.
2016/0066824	A1	3/2016	Al-Ali et al.	2018/0103905	A1	4/2018	Kiani
2016/0066879	A1	3/2016	Telfort et al.	2018/0110478	A1	4/2018	Al-Ali
2016/0072429	A1	3/2016	Kiani et al.	2018/0116575	A1	5/2018	Perea et al.
2016/0073967	A1	3/2016	Lamego et al.	2018/0125368	A1	5/2018	Lamego et al.
2016/0081552	A1	3/2016	Wojtczuk et al.	2018/0125430	A1	5/2018	Al-Ali et al.
2016/0095543	A1	4/2016	Telfort et al.	2018/0125445	A1	5/2018	Telfort et al.
2016/0095548	A1	4/2016	Al-Ali et al.	2018/0130325	A1	5/2018	Kiani et al.
2016/0103598	A1	4/2016	Al-Ali et al.	2018/0132769	A1	5/2018	Weber et al.
2016/0113527	A1	4/2016	Al-Ali et al.	2018/0132770	A1	5/2018	Lamego
2016/0143548	A1	5/2016	Al-Ali	2018/0146901	A1	5/2018	Al-Ali et al.
				2018/0146902	A1	5/2018	Kiani et al.
				2018/0153442	A1	6/2018	Eckerbom et al.
				2018/0153447	A1	6/2018	Al-Ali et al.
				2018/0153448	A1	6/2018	Weber et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2018/0161499	A1	6/2018	Al-Ali et al.
2018/0168491	A1	6/2018	Al-Ali et al.
2018/0174679	A1	6/2018	Sampath et al.
2018/0174680	A1	6/2018	Sampath et al.
2018/0182484	A1	6/2018	Sampath et al.
2018/0184917	A1	7/2018	Kiani
2018/0192953	A1	7/2018	Shreim et al.
2018/0199871	A1	7/2018	Pauley et al.
2018/0214090	A1	8/2018	Al-Ali et al.
2018/0218792	A1	8/2018	Muhsin et al.

OTHER PUBLICATIONS

Notice of Reasons for Rejection (Office Action) from International Application No. 2000-606119, dated Dec. 3, 2009 in 5 pages.
Extended European Search Report, App. No. EP 10 18 1436, Date of Actual Completion of Search: Nov. 26, 2010, 2 pages.

* cited by examiner




FIG. 1




FIG. 2

Probe On Ratio Range 302

Wavelength	510	520	530	540	550	560	570	580	590	600
Max. Ratio	4.0622	4.0185	3.5852	1.7902	1.0000	1.0000	1.1529	2.0712	2.5688	
Min. Ratio	1.4435	1.2403	1.3010	0.9876	1.0000	1.0000	0.8922	0.9316	0.9893	

Probe Off Ratio Range 304

Wavelength	510	520	530	540	550	560	570	580	590	600
Max. Ratio	1.0491	1.7501	1.2234	1.0785	1.0000	1.0000	1.3123	1.4723	1.1305	
Min. Ratio	0.6942	0.4748	0.6163	0.8003	1.0000	1.0000	0.6699	0.6623	0.8293	

308 310 306

FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7





FIG. 8



OXIMETER PROBE OFF INDICATOR DEFINING PROBE OFF SPACE

INCORPORATION BY REFERENCE TO ANY PRIORITY APPLICATIONS

The present application claims priority benefit under 35 U.S.C. § 120 to, and is a continuation of U.S. patent application Ser. No. 13/610,610, filed Sep. 11, 2012 entitled ““Oximeter Probe Off Indicator Defining Probe Off Space””, which is a continuation of U.S. patent application Ser. No. 11/871,690, filed Oct. 12, 2007 entitled “Oximeter Probe Off Indicator Defining Probe Off Space”, now U.S. Pat. No. 8,265,723, which claims priority benefit under 35 U.S.C. § 119(e) from U.S. Provisional Application No. 60/851,448, filed Oct. 12, 2006, entitled “Oximeter Probe Off Indicator Defining Probe Off Space”, the disclosure of which is hereby incorporated by reference in its entirety.

Any and all applications for which a foreign or domestic priority claim is identified in the Application Data Sheet as filed with the present application are hereby incorporated by reference under 37 CFR 1.57.

CROSS-REFERENCE TO RELATED APPLICATIONS

The present disclosure is related to U.S. Pat. No. 6,526,300, U.S. Pat. No. 6,654,624, and the continuation, continuation-in-part, and divisional applications thereof. The foregoing disclosures are incorporated herein by reference and included in the present provisional filing.

BACKGROUND OF THE DISCLOSURE

Field of the Disclosure

The present disclosure relates in general to patient monitoring and in particular to oximeter patient monitors capable of indicating probe off conditions.

Description of the Related Art

Oximeter systems providing measurements of a monitored patient have become the standard of care in many patient care settings, including surgical, post surgical, neonatal, general ward, home care, physical training, and the like. In general, oximeter systems accept one or more noninvasive signals from an optical sensor or probe capable of emitting light into a tissue site and capable of detecting light attenuated by the tissue site. Accurate determination of the measurements and audio/visual indications is often dependent upon proper application of the optical sensor to the tissue site. In the present disclosure, “probe on” conditions include their ordinary broad meaning known to one of skill in the art, including designating proper application of an optical probe to a measurement site. “Probe off” conditions include their ordinary broad meaning known to one of skill in the art, including designating improper application of an optical probe to a measurement site.

Many oximeters may fail to accurately detect probe off conditions. As stated, this condition occurs when the optical sensor becomes partially or completely dislodged from the patient (measurement site), but continues to detect signals. Probe off errors can be serious because the oximeter may output normal measurements, and audio/visual indications of the monitored parameters when, in fact, the probe is not properly attached to the patient, probe off errors may potentially lead to missed physiological events.

Several solutions to more accurately monitor and detect probe off conditions are disclosed in U.S. Pat. No. 6,654,

624, assigned to Masimo Corporation (“Masimo”) of Irvine, Calif., and incorporated by reference herein. For example, the ’624 patent discloses monitor-based detection of probe off conditions. In particular, an intelligent, rule-based processor uses signal quality measurements to limit the operating region of the oximeter without significant negative impact on low perfusion performance. These signal-quality operating limits are superimposed on a graph of signal strength versus emitter gain to improve probe off detection. In this manner, the oximeter can reject intensity signals that have sufficient signal strength to fall within an operating region, but that are unlikely to be a plethysmograph signal. One signal quality measurement that is used is pulse rate density, which is the percentage of time detected pulses satisfy a physiologically acceptable model. Another signal quality measurement is harmonic energy ratio, which is the percentage of signal energy that occurs at the pulse rate and its harmonics. The operating region of the oximeter is then defined in terms of signal strength versus gain, signal strength versus PR density and energy ratio versus pre-defined energy ratio limits. Thus, the ’624 disclosure seeks to limit the scope of acceptable probe on space, as defined by signal strength versus gain, PR density, and energy ratios, and seeks to designate all non-probe on space as probe off space.

SUMMARY OF THE DISCLOSURE

An embodiment of the present disclosure seeks to select characteristics of incoming intensity data that cause comparisons of the selected characteristics to produce defined probe off space having reduced crossover with defined probe on space. Once defined, the present disclosure compares characteristics of incoming intensity data with the now defined probe off space, and in some embodiments, probe on space, to determine whether a probe off condition exists. When a processor determines a probe off condition exists, the processor may output or trigger an output signal that audibly and/or visually indicates to a user that the optical sensor should be adjusted for a proper application to a measurement site.

In an embodiment, the characteristics include ratio data, such as, for example, data of signals responsive to the intensity signals normalized through division by one of the intensity signals. Such division generates ratio data channels, each indicative of one intensity signal other than the normalizing signal. The ratio data channels can be monitored during clinical or other trials where probe off conditions are known to exist. Moreover, oximeter manufacturers typically monitor ratio data channels during, for example, the clinical trials to relate acquired data to the accurate determination of physiological parameter measurements and/or the audio and visual indications of the same. Thus, probe off trial data can be usable to determine probe off space defined in the context of the acquired ratio data on two or more data channels. Moreover, the clinical trial data can also be usable to determine probe on space defined in the context of the acquired ratio data on one or more of the ratio data channels during valid patient monitoring.

Once the probe off space, and in some embodiments, the probe on space, is defined, ratio data acquired before, periodically during, randomly or pseudo-randomly during patient measurements, combinations of the same, or the like, can be compared against stored probe off and probe on spaces to determine whether a probe off condition exists.

For purposes of summarizing the disclosure, certain aspects, advantages and novel features of the disclosure have

been described herein. Of course, it is to be understood that not necessarily all such aspects, advantages or features will be embodied in any particular embodiment of the disclosure.

BRIEF DESCRIPTION OF THE DRAWINGS

A general architecture that implements the various features of the disclosure will now be described with reference to the drawings. The drawings and the associated descriptions are provided to illustrate embodiments of the disclosure and not to limit its scope.

FIG. 1 illustrates an exemplary oximeter patient monitoring system, according to an embodiment of the disclosure.

FIG. 2 illustrates an exemplary block diagram of the oximeter patient monitoring system of FIG. 1.

FIG. 3 illustrates exemplary tables of ratio channel data for probe on and probe off conditions, according to an embodiment of the disclosure.

FIGS. 4-7 illustrate exemplary comparative graphs of the ratio channel data of FIG. 3.

FIG. 8 illustrates a simplified exemplary block diagram of a probe off detector, according to an embodiment of the disclosure.

FIG. 9 illustrates an exemplary probe off determination method, according to an embodiment of the disclosure.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

To facilitate a further understanding of the disclosure, the remainder of the description describes the disclosure with reference to specific drawings. Moreover, in this application, reference is made to blood parameters. Some references have common shorthand designations. For example, as used herein, HbCO designates carboxyhemoglobin, HbMet designates methemoglobin, HbT designates total hemoglobin, SpO₂ designates functional arterial saturation, and SpaO₂ designates fractional arterial saturation. Other shorthand designations such as COHb, MetHb, and tHb are also common in the art for these same constituents. These constituents are generally reported in terms of a percentage, often referred to as saturation, relative concentration, concentration, or fractional saturation. Total hemoglobin is generally reported as a concentration in g/dL. The use of the particular shorthand designators presented in this application does not restrict the term to any particular manner in which the designated constituent is reported.

FIG. 1 illustrates a perspective view of a patient monitor system 100, according to an embodiment of the present disclosure. The system 100 includes a portable patient monitor 102 capable of noninvasively determining one or more physiological parameters. In an embodiment, the portable patient monitor 102 may mechanically and electrically mate with a docking station 104 to recharge batteries, upload and download information, upgrade software or firmware, communicate with other monitors or the like. The monitor 102 also comprises one or more displays 106 capable displaying a wide variety of measured values in a manner that provides for quick and efficient conveyance of information to a caregiver. For example, the display 106 displays values for HbCO 108, HbMet 109, MbT 110, SpO₂ 112, SpaO₂ 114, beats-per-minute 116, scaled plethysmograph data 118, PTTTM 120 and other information including information audibly and/or visually alerting a caregiver to any probe off conditions. The other information may include historical or trending data, combined parameter data, confidence or perfusion indicators, or the like.

FIG. 1 further illustrates the monitor 102 communicating with a reusable optical sensor 154 through a patient cable 156. In general, the monitor 102 drives the sensor 154 to emit light of differing wavelengths into the body tissue 158. The sensor 154 detects the light after attenuation by the body tissue 158 and outputs a signal indicative of the amount of light received by the sensor 154 through the cable 156. In addition, in some embodiments, the monitor 102 communicates with a temperature sensor and/or a memory device associated with one or more of the sensor 154 and the cable 156.

In an embodiment, the monitor 102 receives sensor output and determines continuous and non-invasive measurements of a wide variety of blood parameters. Although disclosed with reference to the portable monitors 102, an artisan will recognize from the disclosure herein that aspects of the present disclosure can be adopted into tabletop monitors, wireless sensors, or other patient-wearable personal monitors, or multi-parameter patient monitors.

The sensor 154 may advantageously comprise a reusable sensor in the form a clip including a spring biased pivot point capable of removably attaching the reusable sensor to a patient's finger 158. Although disclosed with reference to a reusable sensor having a spring, an artisan will recognize from the disclosure herein that the sensor 154 can advantageously comprise a disposable adhesive type sensor, a combination sensor including reusable and disposable components, components incorporated into other medical devices such as catheters, or the like, or other reusable sensor designs. Moreover, the artisan will recognize from the disclosure herein that the sensor 154 can comprise mechanical structures, adhesive or other tape structures, Velcro wraps or combination structures specialized for the type of patient, type of monitoring, type of monitor, or the like. In an embodiment, the sensor 154 provides data to the monitor 102, and vice versa through the cable 156, although such communication can advantageously be wireless, over public or private networks or computing systems or devices, through intermediate medical or other devices, combinations of the same, or the like. In an embodiment, the monitor 102 may include one or more audio, visual or messaging (pagers, emails, instant and phone messages, vocally presented numbers, messages and alarms, voice-over-IP ("VOIP") interfaces and functionality, or the like) alarms, user input keypad 160, or the like.

Although described in terms of certain embodiments, other embodiments or combination of embodiments will be apparent to those of ordinary skill in the art from the disclosure herein. For example, the monitor 102 may combine other information with intensity-derived information to influence diagnoses or device operation. For example, patterns or changes in the continuous noninvasive monitoring of intensity-derived information may cause the activation of other vital sign measurement devices, such as, for example, blood pressure cuffs. Moreover, the monitor 102 may comprise a personal or wearable noninvasive multi-parameter patient monitor that wirelessly communicates with a monitoring station to provide the monitoring station with measurements for some or all of the physiological parameters measurable by the monitor. For example, the monitor may travel with a patient as the patient, for example, moves through a care site such as a hospital. Wireless networks incorporating such personal pulse technologies are commercially available from Masimo marketed under the brand RadNetTM and RadLinkTM. Other monitors 102 may include a wireless patient monitor where a traditional sensor communicates with a wireless transmission device wearable, for

example, on the wrist. In other embodiments, the wireless transmission device may advantageously be incorporated into a sensor housing adapted for wireless communication. In an embodiment, a wireless receiver communicates with a sensor port in the same manner as a wired sensor. Thus, a traditional sensor and a traditional sensor port may be unaware that a patient cable has been replaced with wireless transmissions.

FIG. 2 illustrates an exemplary block diagram of an embodiment of a patient monitoring system 200. As shown in FIG. 2, the system 200 includes a patient monitor 202 comprising a processing board 204 and a host instrument 208. The processing board 204 communicates with a sensor 206 to receive one or more intensity signal(s) indicative of one or more parameters of tissue of a patient. The processing board 204 also communicates with a host instrument 208 to display determined parameter values calculated using the one or more intensity signals. According to an embodiment, the board 204 comprises processing circuitry arranged on one or more printed circuit boards capable of installation into the monitor 202, or capable of being distributed as some or all of one or more OEM components for a wide variety of host instruments monitoring a wide variety of patient information. In an embodiment, the processing board 204 comprises a sensor interface 210, a digital signal processor and signal extractor ("DSP" or "processor") 212, and an instrument manager 214. In general, the sensor interface 210 converts digital control signals into analog drive signals capable of driving sensor emitters, and converts composite analog intensity signal(s) from light sensitive detectors into digital data.

In an embodiment, the sensor interface 210 manages communication with external computing devices. For example, in an embodiment, a multipurpose sensor port (or input/output port) is capable of connecting to the sensor 206 or alternatively connecting to a computing device, such as a personal computer, a PDA, additional monitoring equipment or networks, or the like. When connected to the computing device, the processing board 204 may upload various stored data for, for example, off-line analysis and diagnosis. The stored data may comprise trend data for any one or more of the measured parameter data, plethysmograph waveform data acoustic sound waveform, or the like. Moreover, the processing board 204 may advantageously download from the computing device various upgrades or executable programs, may perform diagnosis on the hardware or software of the monitor 202. In addition, the processing board 204 may advantageously be used to view and examine patient data, including raw data, at or away from a monitoring site, through data uploads/downloads, or network connections, combinations, or the like, such as for customer support purposes including software maintenance, customer technical support, and the like.

According to an embodiment, the DSP 212 comprises a processing device based on the Super Harvard ARChitecture ("SHARC"), such as those commercially available from Analog Devices. However, a skilled artisan will recognize from the disclosure herein that the DSP 212 can comprise a wide variety of data and/or signal processors capable of executing programs for determining physiological parameters from input data. In particular, the DSP 212 includes program instructions capable of receiving multiple channels of data related to one or more intensity signals representative of the absorption (from transmissive or reflective sensor systems) of a plurality of wavelengths of emitted light by body tissue. In an embodiment, the DSP 212 accepts data related to the absorption of two (2) to eight (8) wavelengths

of light, although an artisan will recognize from the disclosure herein that the data can be related to the absorption of two (2) to sixteen (16) or more wavelengths.

The processing board 204 also includes the instrument manager 214. According to an embodiment, the instrument manager 214 may comprise one or more microcontrollers controlling system management, including, for example, communications of calculated parameter data and the like to the host instrument 208. The instrument manager 214 may also act as a watchdog circuit by, for example, monitoring the activity of the DSP 212 and resetting it when appropriate.

The sensor 206 may comprise a reusable clip-type sensor, a disposable adhesive-type sensor, a combination sensor having reusable and disposable components, or the like. Moreover, an artisan will recognize from the disclosure herein that the sensor 206 can also comprise mechanical structures, adhesive or other tape structures, Velcro wraps or combination structures specialized for the type of patient, type of monitoring, type of monitor, or the like. In an embodiment, the sensor 206 provides data to the board 204 and vice versa through, for example, a patient cable. An artisan will also recognize from the disclosure herein that such communication can be wireless, over public or private networks or computing systems or devices, or the like.

The sensor 206 includes a plurality of emitters 216 irradiating the body tissue 218 with differing wavelengths of light, and one or more detectors 220 capable of detecting the light after attenuation by the tissue 218. The sensor 206 may also include other electrical components such as, for example, a memory device 222 comprising an EPROM, EEPROM, ROM, RAM, microcontroller, combinations of the same, or the like. In an embodiment, other sensor components may include a temperature determination device 223.

The memory 222 may advantageously store some or all of a wide variety data and information, including, for example, information on the type or operation of the sensor 206; type or identification of sensor buyer or distributor or groups of buyer or distributors, sensor manufacturer information, sensor characteristics including the number of emitting devices, the number of emission wavelengths, data relating to emission centroids, data relating to a change in emission characteristics based on varying temperature, history of the sensor temperature, current, or voltage, emitter specifications, emitter drive requirements, demodulation data, calculation mode data, the parameters for which the sensor is capable of supplying sufficient measurement data (e.g., HbCO, HbMet, HbT, or the like), calibration or parameter coefficient data, software such as scripts, executable code, or the like, sensor electronic elements, whether the sensor is a disposable, reusable, multi-site, partially reusable, partially disposable sensor, whether it is an adhesive or non-adhesive sensor, whether the sensor is a reflectance, transmittance, or transreflectance sensor, whether the sensor is a finger, hand, foot, forehead, or ear sensor, whether the sensor is a stereo sensor or a two-headed sensor, sensor life data indicating whether some or all sensor components have expired and should be replaced, encryption information, keys, indexes to keys or hash functions, or the like, monitor or algorithm upgrade instructions or data, some or all of parameter equations, information about the patient, age, sex, medications, and other information that may be useful for the accuracy or alarm settings and sensitivities, trend history, alarm history, or the like. In an embodiment, the monitor may advantageously store data on the memory device, including, for example, measured trending data for any

number of parameters for any number of patients, or the like, sensor use or expiration calculations, sensor history, or the like.

The patient monitor **202** also includes the host instrument **208**. In an embodiment, the host instrument **208** communicates with the board **204** to receive signals indicative of the physiological parameter information calculated by the DSP **212**. The host instrument **208** preferably includes one or more display devices **224** capable of displaying indicia representative of the calculated physiological parameters of the tissue **218** at the measurement site. In an embodiment, the host instrument **208** may advantageously comprise a handheld housing capable of displaying parameter data, including but not limited to pulse rate, plethysmograph data, perfusion quality such as a perfusion quality index ("PQI") signal or measurement quality ("SIQ"), values of blood constituents in body tissue, including for example, SpO₂, HbCO, HbMet, Hbt, or the like. In other embodiments, the host instrument **208** is capable of displaying values for one or more of Hbt, Hb, blood glucose, bilirubin, or the like. The host instrument **208** may be capable of storing or displaying historical or trending data related to one or more of the measured values, combinations of the measured values, plethysmograph data, or the like. The host instrument **208** also includes an audio indicator **226** and user input device **228**, such as, for example, a keypad, touch screen, pointing device, voice recognition device, or the like.

In still additional embodiments, the host instrument **208** includes audio or visual alarms that alert caregivers that one or more physiological parameters are falling below predetermined safe thresholds. The host instrument **208** may include indications of the confidence a caregiver should have in the displayed data. In a further embodiment, the host instrument **208** may advantageously include circuitry capable of determining the expiration or overuse of components of the sensor **206**, including, for example, reusable elements, disposable elements, or combinations of the same.

Although described in terms of certain embodiments, other embodiments or combination of embodiments will be apparent to those of ordinary skill in the art from the disclosure herein. For example, the monitor **202** may comprise one or more monitoring systems monitoring parameters, such as, for example, vital signs, blood pressure, ECG or EKG, respiration, glucose, bilirubin, or the like. Such systems may combine other information with intensity-derived information to influence diagnosis or device operation. Moreover, the monitor **202** may advantageously include an audio system, preferably comprising a high quality audio processor and high quality speakers to provide for voiced alarms, messaging, or the like. In an embodiment, the monitor **202** may advantageously include an audio out jack, conventional audio jacks, headphone jacks, or the like, such that any of the display information disclosed herein may be audibilized for a listener. For example, the monitor **202** may include an audible transducer input (such as a microphone, piezoelectric sensor, or the like) for collecting one or more of heart sounds, lung sounds, trachea sounds, or other body sounds and such sounds may be reproduced through the audio system and output from the monitor **202**. Also, wired or wireless communications (such as Bluetooth or WiFi, including IEEE 801.11a, b, or g), mobile communications, combinations of the same, or the like, may be used to transmit the audio output to other audio transducers separate from the monitor **202**. In addition, patterns or changes in the continuous noninvasive monitoring of inten-

sity-derived information may cause the activation of other vital sign measurement devices, such as, for example, blood pressure cuffs.

FIG. **2** also illustrates the DSP **112** including memory capable of storing data indicative of a defined probe off space **260** and a defined probe on space **262**. In a further embodiment, the spaces **260**, **262** include ratio data **264**, **266**. For example, the probe off space **260** or probe on space **262** may include data acquired through clinical or other trials where data was gathered during known probe off conditions. Examples of such trials may include a myriad of possible common occurrences in hospital or caregiver settings, such as, for example, attaching a reusable clip to a standard hospital bed sheet, instrument pole, clothing, or leaving the clip hanging in the air in one or a variety of lighting conditions. In addition, in an embodiment, the probe off data **260** may include clinical experiments where a sensor hangs approximately eighteen (18) inches off the edge of a desk with a fan set on low placed about three (3) feet from the sensor. Data was collected in five-minute intervals in various lighting conditions, including, for example: (1) ambient light, such as when lights are on in a room; (2) dim or dark light, such as when many of the lights are off in the room; (3) shadow light, such as when lights are off and a separate light is positioned to create shadows from the desk edge that the sensor will swing in to and out of during data collection; (4) reflective light, such as when a box is placed approximately six (6) inches from the sensor with the sensor light emitters facing the box, and (i) all lights are on in the room, and (ii) all other lights are off in the room.

While disclosed with reference to some or all of the foregoing clinical data collections, an artisan will recognize from the disclosure herein that many common probe off environmental conditions could be simulated to create large data sets of ratio channel data during such probe off conditions, including, for example, collection of data when emitters and detector are separated only by air, or the like.

The probe on space **262** may include data acquired through clinical or other trials where data was gathered to, for example, determine correlations between monitor acquired measurement data and clinically or model acquired measurement data. Such experiments carefully monitor the condition of probe placement, and therefore, generally define probe on space. Such probe on space may be further limited using techniques disclosed, for example, in the '624 patent referenced in the foregoing or other techniques recognizable to an artisan from the disclosure herein.

FIG. **3** illustrates exemplary tables **302**, **304** of ratio data for probe on **304** and probe off **302** conditions, according to an embodiment of the disclosure. As shown in FIG. **3**, the probe off table **302** comprises ratio data ranges for data channels associated with particular wavelengths in at least an eight (8) wavelength oximeter system, the ratio data ranges acquired, for example, during one or more of the foregoing probe off clinical trials. For example, in an embodiment, the monitor drives eight (8) light-emitting diodes (LEDs) with nominal centroids at about 610, about 620, about 630, about 660, about 700, about 730, about 800 and about 905 nm. Although disclosed in reference to certain preferred wavelengths, an embodiment of the eight (8) emission centroids may range from about 605 nm to about 614 nm, from about 615 nm to about 624 nm, from about 625 nm to about 635 nm, from about 655 nm to about 665 nm, from about 690 nm to about 710 nm, from about 720 nm to about 740 nm, from about 785 nm to about 825 nm, and from 875 nm to about 935 nm. An artisan will recognize from the disclosure herein that other wavelengths may be of

particular value based on, for example, the absorption spectra of desired physiological parameters, their responsiveness to probe off conditions, or the like. For example, experimental data may determine that wavelengths different from those particularly useful in determining measurement and other displayed data may advantageously be used to determine probe off and/or probe on conditions, as discussed herein. A particular patient monitor may use a certain number of wavelengths for measurement channels and some subgroup or an entirely different additional group of wavelengths for the probe off determinations. For example a monitor may use two (2) to eight (8) or more wavelengths selected for their responsiveness to physiological parameters, and may use one (1) to eight (8) or more overlapping, entirely different, or the like, of wavelengths for probe off and/or probe on determinations. In such embodiments, the wavelengths may be determined based on their ability to clearly distinguish probe off space from probe on space.

The data channel 306 corresponds to detection of light at approximately 700 nm and is used to normalize the other data channels, although other channels could also be used. From the tables 302, 304, selection of the data channels 308, 310 correspond to light detected from emission of the 610 nm and 630 nm LED's, respectively, increase the likelihood that probe off space can accurately be determined. For example, in the data channels corresponding to the 610 nm and 630 nm LED's the probe off space 302 and the probe on space 304 do not overlap with or otherwise conflict with one another. This distinction can be graphically represented as shown in FIGS. 4-7. For example, FIG. 4 illustrates the distance between valid probe on data or probe on space 402 versus valid probe off data or probe off space 404 for data channels corresponding to the detection of light at 610 and 620 nm. FIG. 5 similarly illustrates the space separation for data channels corresponding to the detection of light at 610 and 630 nm, and FIG. 6 illustrates the space separation for data channels corresponding to the detection of light at 620 and 630 nm. Reviewing FIGS. 4-6 collectively, FIG. 5 shows the clearest or largest distinction between potentially valid probe on space 502 and probe off space 504. Thus, were an oximeter system to make a two (2) dimensional comparison using the foregoing data channels, it would be best served to use the data channels corresponding to the detection of light at 610 and 630 nm.

FIG. 7 illustrates a three (3) dimensional graph that combines the data channels corresponding to the detection of light at 610, 620 and 630 nm. Although FIGS. 4 and 6 indicate that the data channel corresponding to 620 nm is not ideal for the separation of spaces, the three (3) dimensional plot of FIG. 7 illustrates that higher dimensions of space increase the separation between defined probe off 704 and probe on 702 regions. Thus, in an oximeter having eight (8) wavelengths of emitted light, a probe off and probe on space may be defined using as many as seven (7) dimensions (the eighth being used for normalization). Such increased dimensional analysis may advantageously provide ever increasing separation between defined probe off and probe on regions.

FIG. 8 illustrates a simplified exemplary block diagram of a probe off detector 802, according to an embodiment of the disclosure. As shown in FIG. 8, the probe off detector 802 includes inputs of data channels 804 corresponding to two (2) or more wavelengths of emitted light, probe off data 806, and in some embodiments, probe on data 806. Comparison of characteristics of the data channels, such as, for example, ratio data, can be compared to multidimensional probe off and/or probe on space to determine and output 808 of a probe off indication.

FIG. 9 illustrates an exemplary probe off determination process 900, according to an embodiment of the disclosure. The process 900 includes block 902 where probe off data is collected from, for example, clinical trials, mathematical models, extrapolated data, non-probe on data, or the like. In block 904, the collected probe off (and, in some embodiments, probe on data) may be reviewed to determine characteristics that reduce crossover between probe off and probe on space. For example, characteristics may be chosen that decouple the probe off determinations from measurement determinations. For example, when the characteristics comprise ratio data, or normalized data channels responsive to intensity data channels from the sensor, the ratio data corresponding to particular wavelengths may indicate a greater separation between valid parameter data (probe on conditions) and probe off conditions. In some embodiments, increasing the dimensions may advantageously cause further separation between valid and invalid conditions.

In block 906, the probe off data (and in some embodiments, probe on data) is stored in memory on a patient monitor. In an embodiment, such probe on or off data may be updated through upgrading tools, network connectivity such as the internet, smartcards, or other memory devices or network computing. In block 908, the patient monitor acquires data from a measurement site. The acquisition may be at or near a start of data acquisition, periodically throughout acquisition, randomly, in response to particular conditions or changes in conditions, combinations of the same or the like. In block 910, the DSP compares characteristics of the acquired data to the characteristics stored as probe on and off data. Block 912 determines whether a probe off exists by determining whether the characteristics fall within one of the probe off or probe on spaces. When the acquired data falls within the probe off space, a probe off condition is determined to exist and in block 914, the DSP triggers a probe off indicator. The probe off indicator may be an audible sound, such as a constant or varying tone or beep, a visual indicator, such as a flashing and/or colored display or display element(s), combinations of the same or the like. The probe off indicator may comprise help screens or training indicia to guide a caregiver on how to properly attach the probe. The probe off indicator may continue to activate until the probe is properly positioned. In the case of a probe off condition, the process 900 returns to block 908 and acquires data from the measurement site. When a probe off condition does not exist at block 912, block 914 determines parameter measurements according to probe on operation of the patient monitor.

While the probe off indicator has been described in certain embodiments herein, other embodiments of the present disclosure will be known to those of skill in the art from the descriptions herein. Moreover, the described embodiments have been presented by way of example only, and are not intended to limit the scope of the disclosure. Moreover, those of skill in the art understand that information and signals can be represented using a variety of different technologies and techniques. For example, data, instructions, commands, information, signals, bits, symbols, and chips that can be referenced throughout the above description may be represented by voltages, currents, electromagnetic waves, magnetic fields or particles, optical fields or particles, or any combination thereof.

Those of skill in the art further appreciate that the various illustrative logical blocks, modules, circuits, and algorithm steps described in connection with the embodiments disclosed herein can be implemented as electronic hardware, computer software, or combinations of both. To illustrate

11

this interchangeability of hardware and software, various illustrative components, blocks, modules, circuits, and steps have been described above generally in terms of their functionality. Whether such functionality is implemented as hardware or software depends upon the particular application and design constraints imposed on the overall system. Skilled artisans can implement the described functionality in varying ways for each particular application, but such implementation decisions should not be interpreted as causing a departure from the scope of the present disclosure.

The various illustrative logical blocks, modules, and circuits described in connection with the embodiments disclosed herein can be implemented or performed with a general purpose processor, a digital signal processor (DSP), an application specific integrated circuit (ASIC), a field programmable gate array (FPGA) or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. A general purpose processor can be a microprocessor, but in the alternative, the processor can be any conventional processor, controller, microcontroller, or state machine. A processor can also be implemented as a combination of computing devices, e.g., a combination of a DSP and a microprocessor, a plurality of microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration.

The steps of a method or algorithm described in connection with the embodiments disclosed herein can be embodied directly in hardware, in a software module executed by a processor, or in a combination of the two. A software module can reside in RAM memory, flash memory, ROM memory, EPROM memory, EEPROM memory, registers, hard disk, a removable disk, a CD-ROM, or other form of storage medium known in the art. A storage medium is coupled to the processor, such that the processor can read information from, and write information to, the storage medium. In the alternative, the storage medium can be integral to the processor. The processor and the storage medium can reside in an ASIC. The ASIC can reside in a user terminal, physiological monitor and/or sensor. The processor and the storage medium can reside as discrete components in a user terminal, physiological monitor and/or sensor.

Although the foregoing disclosure has been described in terms of certain preferred embodiments, other embodiments will be apparent to those of ordinary skill in the art from the disclosure herein. Additionally, other combinations, omissions, substitutions and modifications will be apparent to the skilled artisan in view of the disclosure herein. Moreover, it

12

is contemplated that various aspects and features of the disclosure described can be practiced separately, combined together, or substituted for one another, and that a variety of combination and subcombinations of the features and aspects can be made and still fall within the scope of the disclosure. Furthermore, the systems described above need not include all of the modules and functions described in the preferred embodiments. Accordingly, the present disclosure is not intended to be limited by the recitation of the preferred embodiments, but is to be defined by reference to the appended claims.

Additionally, all publications, patents, and patent applications mentioned in this specification are herein incorporated by reference to the same extent as if each individual publication, patent, or patent application was specifically and individually indicated to be incorporated by reference.

What is claimed is:

1. A method of improving a determination an optical probe is not properly positioned with respect to a measurement site on a patient by creating greater separation between valid parameter data specifically associated with probe on conditions and invalid parameter data specifically associated with probe off conditions, and by storing representations of multi-dimensional shapes of said valid and invalid parameter data to be accessible to a processing system to validate or invalidate parameter measurements using said shapes, the method comprising:

activating a noninvasive oximeter sensor, said activating consistent with activations when said sensor is properly applied to said measurement site of said patient for monitoring one or more physiological conditions, however, said noninvasive oximeter sensor being placed in predetermined probe off conditions;

receiving probe off data responsive to signals detected by said noninvasive oximeter sensor;

defining a probe off space from analysis of said probe off data, said probe off space being multi-dimensional;

defining a probe on space representing valid parameter data, said probe on space being multi-dimensional;

when said probe off space is not operably separate from said probe on space, increasing said multi-dimensions to increase separation between said probe off space and said probe on space; and

storing said probe off and said probe on space in memory, said memory operably accessible by a patient monitor.

2. The method of claim 1, wherein said data received comprises probe off data received during clinical trials.

* * * * *

专利名称(译)	血氧计探头关闭指示器定义探头关闭空间		
公开(公告)号	US10219746	公开(公告)日	2019-03-05
申请号	US15/187719	申请日	2016-06-20
[标]申请(专利权)人(译)	梅西莫股份有限公司		
申请(专利权)人(译)	Masimo公司		
当前申请(专利权)人(译)	Masimo公司		
[标]发明人	MCHALE RYAN TIMOTHY WEBER WALTER M		
发明人	MCHALE, RYAN TIMOTHY WEBER, WALTER M.		
IPC分类号	A61B5/1455 A61B5/00		
CPC分类号	A61B5/684 A61B5/14551 A61B5/14552 A61B5/6826 A61B5/6832 A61B5/6838 A61B5/7221 A61B5/7246 A61B5/742 A61B5/7405 A61B5/746 A61B5/7445 A61B5/0022 A61B2560/0475 A61B2560/0214 A61B2560/0456		
优先权	11/871690 2011-09-12 US 60/851448 2006-10-12 US		
其他公开文献	US20160296169A1		
外部链接	Espacenet		

摘要(译)

本公开的一个实施例试图选择输入强度数据的特征，该特征导致所选特征的比较以产生具有与空间上的限定探针的交叉减少的限定探测器空间。一旦定义，本公开将输入强度数据的特征与现在定义的探测空间进行比较，并且在一些实施例中，定义空间上的探测，以确定是否存在探测关闭条件。当处理器确定存在探测器关闭条件时，处理器可以输出或触发输出信号，该输出信号可听地和/或可视地向用户指示应该调整光学传感器以适当地应用于测量站点。

